

CATERPILLAR MACHINE PRICE LIST

140LVR

140LVR MOTOR GRADER PIRACICABA, BRAZIL	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

Standard Equipment:

POWERTRAIN

- Air cleaner, dual stage dry type radial seal with service indicator and automatic dust ejector
- Air-to-air after cooler (ATAAC)
- Belt, serpentine, automatic tensioner
- Brakes, oil disc, four-wheel, hydraulic
- Demand fan, hydraulic
- Electronic over-speed protection
- Engine, C9 with ACERT technology, diesel with automatic engine derate and idle control. EPA/ARB tier 4 final & EU stage IV certified engine & aftertreatment
- Parking brake, multi-disc, sealed and oil cooled
- Sediment drain, fuel tank
- Tandem drive
- Transmission, 8 speed forward and 6 speed reverse, power shift, direct drive
- VHP Plus (Variable Horse Power Plus)

ELECTRICAL

- Alarm, back-up
- Alternator, 150 ampere, sealed
- Batteries, maintenance free, heavy duty, 1125 CCA
- Breaker panel
- Electrical system, 24 volt
- Lights, reversing
- Starter, electric

OPERATOR ENVIRONMENT

- Steering wheel
- Air Conditioning with heater
- Articulation
- Centershift pin indicator
- Display, digital speed and gear
- Load sensing hydraulic controls:
 - Right/left blade lift
 - Circle drive
 - Center shift
 - Side shift
 - Blade tip
 - Front wheel lean
- Doors, left and right side
- Gauge, machine level
- Gauges (analog) inside the cab (includes fuel, articulation, engine coolant temp, engine RPM and hydraulic oil temp, DEF/AdBlue)
- Lights, night time cab
- Messenger Display
- Meter

- Hour digital
- Mirror
- Inside rearview, wide angle
- Power port, 12V
- Radio ready, entertainment
- ROPS cab, 77dB(A) ISO 6394
- Storage area for cooler/lunchbox
- Throttle control, electronic
- Windows: laminated glass
- Fixed front with intermittent wiper windows: tempered
- Left and right side wipers
- Cab Storage

SAFETY AND SECURITY

- Clutch, circle drive slip
- Doors, 2 engine compartment, (two left hand, two right hand) locking
- Doors, 2 service, left and right locking
- Ground level engine shutdown
- Hammer (emergency exit)
- Horn, electric
- Seat belt, retractable 3"
- Secondary steering
- Tandem walkway/guards

FLUIDS

- Antifreeze
- Extended life coolant -35C/-30F

OTHER STANDARD EQUIPMENT

- Accumulators -brake -dual certified
- Drawbar, 6 shoe w/replaceable wear strips
- Fluid check, ground level
- Fuel tank, 100 gallon (378 L)
- Ground level fueling
- DEF/AdBlue Tank, 3.3 gallon (12.5 L)
- Hydraulic lines for base functions
- Pump, hydraulic, high capacity (100cc / 6 cu in)
- Radiator, cleanout access (both sides with swing doors)
- SOS ports - engine -hydraulic -transmission -coolant -fuel
- Tool box
- Debris guard

CATERPILLAR MACHINE PRICE LIST

140LVR

140LVR MOTOR GRADER PIRACICABA, BRAZIL	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

**Lane 2 is reserved for the Base Order Management Program.
 Please use Lane 2 when placing orders that are part of the Base Order
 Management Program.**

515-2449	140 13A MOTOR GRADER 0 LANE 2 - AVAILABLE FROM PIRACICABA FACTORY LANE 3 - AVAILABLE FROM PIRACICABA FACTORY	\$354,360
515-8361	140 13A AWD MOTOR GRADER 0 LANE 2 - AVAILABLE FROM PIRACICABA FACTORY LANE 3 - AVAILABLE FROM PIRACICABA FACTORY	\$406,570
0P-4773	140 13A MISC MATL 0 AVAILABLE FROM PIRACICABA FACTORY	NC

Only reference numbers that have the text
 "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER	0	NC

PERFORMANCE PACKAGES

MOLDBOARDS

L	320-9924	MOLDBOARD, 12' BASIC FOR USE IN LANE 3 ONLY INCLUDES: - Moldboard 12' x 24" x 7/8" (3658mm x 610mm x 22mm) - Curved Cutting Edge, 6" X 5/8" (152mm x 16mm) - End Bits, Standard, Without Overlay	0	NC
L	526-7045	MOLDBOARD, 14' BASIC INCLUDES: - Moldboard 14' x 24" x 7/8" (4267mm x 610mm x 22mm) - Curved Cutting Edge, 8" x 3/4" (203mm x 19mm) - End Bits, Standard, Without Overlay	0	\$595
L	439-9110	MOLDBOARD, 14' PLUS INCLUDES: - Moldboard 14' x 27" x 1" (4267mm x 686mm x 25mm) - Curved Cutting Edge, 8" x 3/4" (203mm x 19mm) - End Bits, Standard, With Overlay	0	\$1,410

REAR WORK TOOLS

P	523-8156	NO HITCH Provides a plate that bolts to the bumper that allows for attachment points for ripper or auxiliary hoses.	0	NC
P	507-7694	HITCH, TOWING Retrieval hitch. Does not include pin.	0	\$560
P	515-4649	RIPPER-SCARIFIER, REAR Hydraulic, rear mounted ripper with three straight ripper shanks. Can accommodate two additional ripper shanks and nine scarifier teeth which must be ordered separately. RECOMMENDED FOR USE WITH: 336-1559 PUSH PLATE, COUNTERWEIGHT	0	\$21,000
L	558-2400	RIPPER, SNOW WING READY FOR USE IN LANE 3 ONLY Hydraulic, rear mounted ripper with three straight ripper shanks. Includes the mount for the Caterpillar Mastless Snow Wing on the right side of the ripper backplate. Can accommodate two additional ripper shanks, nine scarifier teeth, and the Caterpillar Mastless Snow wing which must be ordered separately.	0	\$22,410

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

PERFORMANCE PACKAGES (CONT.)

WEATHER PACKAGES

L	522-6386	WEATHER, STANDARD, TANDEM 0 Recommended for year around use when typical ambient temperature range is 0 degrees C (32 degrees F) to 43 degrees C (110 degrees F) and operating at altitude below 1220 m (4000 feet). INCLUDES: - Batteries, Heavy Duty - 1125 CCA - Oil, Hydraulic, 10W ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		NC
L	522-6393	COLD WEATHER, TANDEM 0 Recommended for year around use when typical ambient temperature range is -18 degrees C (0 degrees F) to 43 degrees C (110 degrees F) and operating at altitude below 1220 m (4000 feet). INCLUDES: - Starting Aid, Ether - Batteries, Extreme Duty -1400 CCA - Oil, Hydraulic, 10W ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$780
L	522-6394	COLD WEATHER PLUS, TANDEM 0 Recommended for year around use when typical ambient temperature range is -40 degrees C (-40 degrees F) to 40 degrees C (104 degrees) or operating at altitude above 1220 m (4000 feet). INCLUDES: - Block heater - Starting Aid, Ether - Cold Start; Transmission oil and fan brake bypass - Batteries, Extreme Duty -1400 CCA - Oil Hydraulic, 0-20W - 249-5516 HEATER, ENGINE COOLANT, 120V REQUIRES: 515-2232 STARTER EXTREME DUTY ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$3,050
L	522-6397	WEATHER, STANDARD, AWD 0 Recommended for year around use when typical ambient temperature range is 0 degrees C (32 degrees F) to 43 degrees C (110 degrees F) and operating at altitude below 1220 m (4000 feet). INCLUDES: - Batteries, Heavy Duty - 1125 CCA - Oil, Hydraulic, 10W ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		NC
P	522-6395	COLD WEATHER, AWD 0 Recommended for year around use when typical ambient temperature range is -18 degrees C (0 degrees F) to 43 degrees C (110 degrees F) and operating at altitude below 1220 m (4000 feet). INCLUDES: - Starting Aid, Ether - Batteries, Extreme Duty -1400 CCA - Oil, Hydraulic, 10W - 249-5516 HEATER, ENGINE COOLANT, 120V ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$780

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

PERFORMANCE PACKAGES (CONT.)

WEATHER PACKAGES (Cont.)

P	522-6396	COLD WEATHER PLUS PKG, AWD 0 Recommended for year around use when typical ambient temperature range is -40 degrees C (-40 degrees F) to 40 degrees C (104 degrees) or operating at altitude above 1220 m (4000 feet). INCLUDES: - Block heater - Starting Aid, Ether - Cold Start; Transmission oil and fan brake bypass - Batteries, Extreme Duty -1400 CCA - Oil, Hydraulic, Cold, 0W-20 - 249-5516 HEATER, ENGINE COOLANT, 120V REQUIRES: 515-2232 STARTER EXTREME DUTY ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$3,875
---	----------	---	--	---------

PRECLEANER

L	380-6774	PRECLEANER, NON SY-KLONE 0 Includes dust ejector for medium to heavy dust environments.		NC
L	380-6775	PRECLEANER, SY-KLONE 5 For use in snow applications, especially when fine snow dust is common, NOT recommended for medium to heavy dust environments.		\$770

LINK BAR SYSTEM

L	559-2201	LINK BAR, HYDRAULIC 0 Link Bar with Hydraulic Locking Pin, Adjustment Controlled from Cab.		NC
L	559-2202	LINK BAR, MANUAL 0 Link Bar with Manual Locking Pin, Adjustment Requires Hand Tools.		\$-885

DRAWBAR ARRANGEMENT

P	522-6751	DRAWBAR, STANDARD 0 Standard (H-Type) DCM. Standard shimmed circle wear strips. Standard shimmed moldboard wear strips. Intended for customers who perform rough grading or road maintenance and do not frequently maintain their drawbar, circle and moldboard		\$-2,815
P	522-6756	DRAWBAR, TOP ADJUST 0 Top Adjust (M-Type) DCM. Top-adjust circle wear strips. Setscrew moldboard wear strip adjustment. Adjustment allows for DCM assembly to keep tighter grades. Ideal for customers who perform finish grading work and frequently maintain their drawbar, circle and moldboard for factory tightness.		NC

BLADE TECHNOLOGY

P	566-5529	NO GRADE CONTROL TECHNOLOGY 0 CANNOT BE USED WITH: 524-8990 BASE+1 (RIP) ARO 524-8993 BASE+3 (RIP,MMS,FL) ARO 524-8995 BASE+4 (RIP,FL,WM,WT) ARO		NC
---	----------	--	--	----

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

PERFORMANCE PACKAGES (CONT.)

BLADE TECHNOLOGY (Cont.)

P	563-5453	DIGITAL BLADE SLOPE METER 0 FOR USE IN LANE 3 ONLY Provides an entry level real-time digital readout of the cross slope of the blade as a job aid to help an operator maintain an accurate and consistent cross slope. Can be used to measure/maintain true cross slope in a road when machine is NOT articulated and blade is perpendicular to machine. Does NOT automatically control elevation of one side of blade and is NOT upgradeable to Cat GRADE Cross Slope, Cross Slope Indicate, 2D (Cross Slope, Sonic, or Laser), or 3D (GPS or UTS) aftermarket options. CANNOT BE USED WITH: 524-8990 BASE+1 (RIP) ARO 524-8993 BASE+3 (RIP,MMS,FL) ARO 524-8995 BASE+4 (RIP,FL,WM,WT) ARO		\$3,050
P	522-6757	CAT GRADE ARO 0 Allows the Motor Grader to be equipped with either a Cross Slope, Sonic, Laser, GPS, or ATS electronics kit. Provides software, harnesses for sensors, mounting for sensors and blade mast bracket. No sensors included. Cat motor graders have an open architecture that allow aftermarket brands to install their grade control systems. To support integration of machine guidance systems other than Cat Grade or Trimble refer to AEXQ2281-00. REQUIRES: 522-6756 DRAWBAR, TOP ADJUST and 524-8990 BASE+1 (RIP) ARO or 524-8993 BASE+ 3 (RIP,MMS,FL) ARO or 524-8995 BASE+4 (RIP,FL,WM,WT) ARO		\$6,860
P	563-5226	CROSS SLOPE INDICATE 0 Provides real-time digital readout of the cross slope as a job aid to help an operator maintain an accurate and consistent cross slope. Cannot be used to automatically control one side of the blade like full Cross Slope. ARO is also included. CAN be upgraded to full Cross Slope or Cat GRADE. REQUIRES: 522-6756 DRAWBAR, TOP ADJUST CANNOT BE USED WITH: 524-8990 BASE+1 (RIP) ARO 524-8993 BASE+3 (RIP,MMS,FL) ARO 524-8995 BASE+4 (RIP,FL,WM,WT) ARO		\$11,100
P	522-6760	CROSS SLOPE AUTO 0 Allows the operator to manually control one end of the blade to match the curb or crown while automatically maintaining the desired slope of the blade. This system is used to maintain the crown of a gravel road or the shoulder of a road. Provides cab switches, software, harnesses for sensors, mounting for sensors and blade mast bracket. Cat GRADE ARO is included in this option. REQUIRES: 522-6756 DRAWBAR, TOP ADJUST and 524-8990 BASE+1 (RIP) ARO or 524-8993 BASE+ 3 (RIP,MMS,FL) ARO or 524-8995 BASE+4 (RIP,FL,WM,WT) ARO		\$13,280

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

PERFORMANCE PACKAGES (CONT.)

HYDRAULIC LOCK OUT

L	437-0690	NO LOCK OUT, CAB 0		NC
		Includes plate and screw-truss head for Cab, it is required for Cab without mechanical lock.		
L	453-2908	LOCK OUT, MANUAL 5		\$1,375
		Mechanically locks all moldboard, machine and attachment control levers during machine roading.		

HYDRAULICS

Note: Hydraulic Definitons

Base = 8 functions: right and left blade lift, circle turn, drawbar center shift, blade side shift, blade tip, front wheel lean, frame articulation. Float function standard for all hydraulic packages (Blade Lift & Front Lift).

- RIP = Ripper**
- MMS = Mid Mount Scarifier**
- FL = Front Blade Lift**
- WM = Snow Wing Mast**
- WT = Snow Wing Tilt**
- DA1 = Dozer Angle 1 (angles front blade left OR right)**
- ARO = Attachment Ready Option for Cat GRADE**

P	524-8998	HYDRAULIC BASE 0		NC
		Base hydraulic system includes right and left blade lift, circle turn, drawbar center shift, blade side shift, blade tip, front wheel articulation		
P	524-8989	BASE + 1 (RIP) 0		\$1,850
		Ripper function. Includes the Ripper Lines.		
P	524-8990	BASE + 1 (RIP) ARO 0		\$8,680
		Ripper function. Includes the Ripper Lines.Cat GRADE Attachment Ready Option (ARO) or Cross		
P	524-8991	BASE + 2 (RIP,FL) 0		\$2,885
		Ripper and Front Lift functions. Includes the Front Lift Lines and Ripper Lines.		
P	524-8992	BASE + 3 (RIP, MMS, FL) 0		\$4,340
		FOR USE IN LANE 3 ONLY Ripper, Mid-Mount Scarifier, and Front Blade Lift functions. Includes the Ripper Lines, Mid-Mount Scarifier Lines and Front Lift Lines.		
		REQUIRES: 339-7734 Bracket (if you need to use Mid-Mount Scarifier)		
P	524-8993	BASE + 3 (RIP,MMS,FL) ARO 0		\$9,750
		FOR USE IN LANE 3 ONLY Ripper, Mid-Mount Scarifier, and Front Blade Lift functions. Includes the Ripper Lines, Mid-Mount Scarifier Lines and Front Lift Lines. For use with Cat GRADE Attachment Ready Option (ARO) or Cross Slope. REQUIRES: 339-7734 Bracket (if you need to use Mid-Mount Scarifier)		

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

HYDRAULICS (CONT.)

P	563-2341	BASE + 4 (RIP,FL,WM,WT) 0 FOR USE IN LANE 3 ONLY Ripper, Front Lift, Snow Wing Lift and Snow Wing Tilt functions. Includes the Front Blade Lift Lines and Ripper Lines. Snow Wing levers are mounted right of the steering wheel. ONLY FOR USE WITH: SNOW WING (from WT-MG Price Pages)		\$7,670
P	524-8994	BASE + 4 (RIP,FL,WM,WT) 0 Ripper, Front Lift, Snow Wing Lift and Snow Wing Tilt functions. Includes the Front Blade Lift Lines and Ripper Lines. Snow Wing levers are mounted left of the steering wheel. ONLY FOR USE WITH: SNOW WING (from WT-MG Price Pages)		\$7,670
P	524-8995	BASE + 4 (RIP,FL,WM,WT) ARO 0 Ripper, Front Blade Lift, Snow Wing Lift and Snow Wing Tilt functions. Includes the Front Blade Lift Lines and Ripper Lines. For use with Cat GRADE Attachment Option (ARO) or Cross Slope. Snow Wing levers are mounted left of the steering wheel. ONLY FOR USE WITH: SNOW WING (from WT-MG Price Pages)		\$14,490
P	524-8997	BASE + 5 (RIP,FL,WM,WT,DA1) 0 FOR USE IN LANE 3 ONLY Ripper, Front Blade Lift, Snow Wing Lift, Snow Wing Tilt, and Front Angle functions. Includes the Front Blade Lift Lines, Front Blade Angle Lines, and Ripper Lines. Snow Wing levers are mounted left of the steering wheel ONLY FOR USE WITH: SNOW WING (from WT-MG Price Pages) and ANGLE BLADES (from WT-MG Price Pages)		\$9,660

LINE GROUPS

ACCUMULATORS

P	515-2586	NO ACCUMULATORS, NO ARO 0 Provides hydraulic lines for base functions		NC
P	515-2585	NO ACCUMULATORS, WITH ARO 0 -Includes Lines GP Cynlinder, Adaptor and Hose, Pump -Non-Accumulator REQUIRES: 524-8990 BASE+1 (RIP) ARO or 524-8993 BASE+ 3 (RIP,MMS,FL) ARO or 524-8995 BASE+ 4 (RIP,FL,WM,WT) ARO		NC
P	526-9853	ACCUMULATORS, NO ARO 0 Provides hydraulic lines for base functions and accumulators for the blade lift. Allows approximately 1-3" of vertical blade travel to reduce impact loads. Nitrogen/oil accumulators activated by electric switch.		\$4,805
P	524-1763	ACCUMULATORS, WITH ARO 0 FOR USE IN LANE 3 ONLY Provides hydraulic lines for base functions and accumulators for the blade lift. Allows approximately 1-3" of vertical blade travel to reduce impact loads. Nitrogen/oil accumulators activated by electric switch. REQUIRES: 524-8990 BASE+1 (RIP) + ACCUGRADE or 524-8993 BASE+3 (RIP, MMS, FL)+ ACCUGRADE or 524-8995 BASE+4(RIP,FL,WM,WT)ACCUGRADE		\$4,805

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

STARTERS, BATTERIES, & ALTERNATORS

STARTER ARRANGEMENT

P	515-2231	STARTER, HEAVY DUTY 0		NC
		Provides a 710 Amp. starter Recommended for year around use when typical ambient temperature range is -18 degrees C (0 degrees F) to 43 degrees C (110 degrees F) and operating at altitude below 1220 m (4000 ft).		
P	515-2232	STARTER, EXTREME DUTY 0		\$420
		Provides a 825 Amp. starter Recommended for year around use when typical ambient temperature range is -40 degrees C (-40 degrees F) to 40 degrees C (104 degrees F) and operating at altitude above 1220 m (4000 ft).		

ELECTRICAL

BRAKE LIGHTS

P	522-1597	LIGHTS, BRAKE AND BACKUP 0		NC
		Provides stationary rear brake lights along with the back-up lights. Does not include front headlights or turn signals Cannot use this lighting package with headlights because there are no turn signals. CANNOT BE USED WITH: 519-3700 LOW BAR, HALOGEN, TANDEM 558-5819 LOW BAR, LED, TANDEM 519-3702 HIGH BAR, HALOGEN, TANDEM 558-5820 HIGH BAR, LED, TANDEM 519-3705 LOW BAR, HALOGEN, AWD 558-5822 LOW BAR, LED, AWD 519-3706 HIGH BAR, HALOGEN, AWD 558-5823 HIGH BAR, LED, AWD		
P	562-3742	ROADING LIGHTS W/FOLD DOWN ARM 0		\$1, 935
		Provides stationary rear brake lights along with the back-up lights, dimmer switch for road lighting, drop-down stop, tail, and rear turn signals and back-up lights. Must select front light bar. REQUIRES: 519-3700 LOW BAR, HALOGEN, TANDEM or 558-5819 LOW BAR, LED, TANDEM or 519-3702 HIGH BAR, HALOGEN, TANDEM or 558-5820 HIGH BAR, LED, TANDEM or 519-3705 LOW BAR, HALOGEN, AWD or 558-5822 LOW BAR, LED, AWD or 519-3706 HIGH BAR, HALOGEN, AWD or 558-5823 HIGH BAR, LED, AWD		

OPERATOR ENVIRONMENT

CAB

P	522-6687	CAB, BASIC 0		NC
		INCLUDES: - Enclosed ROPS - Heater + A/C - 150 amp alternator - Wiper/washer, front - Standard Glass - Hammer (emergency exit)		

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

CAB (Cont.)

P	522-6688	CAB, PLUS 0		\$1,895
		INCLUDES:		
		- Cab, BASIC Features		
		- Rear Wiper		
		- CB Radio Mounting		
		- Rear Window Screen		
		- Defrost Fans (x2)		

SEAT

P	437-0684	SEAT, MECHANICAL SUSPENSION 25		\$1,555
		PVC / vinyl seat, mechanical suspension		
P	518-3382	SEAT, CLOTH AIR SUSPENSION 0		\$2,635
		Cloth seat, air suspension		
P	591-6989	SEAT, CLOTH, HIGH BACK 0		\$3,195
		Includes:		
		Air suspension, heat, adjustable damper		
		cloth cushion, adjustable angle and depth		

MIRROR

P	565-2320	MIRRORS, EXTERNAL. 0		NC
		Outside Mounted Mirrors		
P	524-3111	MIRRORS, HEATED EXTERNAL. 0		\$182
		Provides mirrors with a 24V heating element to keep mirrors ice free in cold weather operations.		

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet.

Availability varies by country, please contact your Cat marketing representative with questions or click on the link below:

[HTTPS://DEALER.CAT.COM/en/bt/otd/machine-price-list.html](https://dealer.cat.com/en/bt/otd/machine-price-list.html)

From there click on the "PRODUCT LINK Hardware Certification" link

P	519-3712	PRODUCT LINK, CELLULAR PLE641 0		NC
		Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and condition information for viewing in Product Link-s remote monitoring web interface. technology provides capabilities for frequent transmission and larger volumes of data.		
P	519-3710	PROD LINK, DUAL PLE641 + PL631. 0		\$1,251
		The Product Link Elite series dual solution uses a combination of GSM and CDMA 3G cellular and satellite networks to transmit location, utilization and condition information for viewing in Product Link-s remote monitoring web interface. For applications that require travel between areas of both cellular and satellite coverage.		

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

COOLING

COOLING FAN

P	558-3846	FAN, STANDARD TANDEM 0 Provides a hydraulically driven demand fan ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		NC
P	550-9200	FAN, REVERSING TANDEM 0 Provides a hydraulically driven demand fan that can reverse direction to prevent debris build up on the cooling package and engine enclosure. Includes automatic and manual controls for airflow reversal. Recommended for applications with a high content of airborne debris. ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$3,195
P	558-3845	FAN, STANDARD AWD 0 Provides a hydraulically driven demand fan ONLY FOR USE WITH: 515-8361 140-13A AWD MOTOR GRADER		NC
P	550-9201	FAN, REVERSING AWD 0 Provides a hydraulically driven demand fan that can reverse direction to prevent debris build up on the cooling package and engine enclosure. Includes automatic and manual controls for airflow reversal. Recommended for applications with a high content of airborne debris. ONLY FOR USE WITH: 515-8361 140-13A AWD MOTOR GRADER		\$3,195

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS

Tires listed below include a set of six tires.
****To calculate tire loads with machine attachments, please reference the MG Tire Selection Pocket Guide (media #AEXQ0182), available on the Electronic Sales Library.**
All tire selections should be made with consideration for planned machine attachments (OEM and aftermarket) and their additional weight. Each tire has a maximum load rating that is not to be exceeded. The tire selection should be based on the maximum of all tire position loads on the machine. Assistance for calculating the highest tire load can be found in the Tire Load Worksheet in the back of the Caterpillar Motor Graders Tire Selection Pocket Guide. Failure to abide by the load ratings of the tires without first consulting the local tire supplier representative could result in nullification of the tire warranty.

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice, but we reserve the right to change to alternate tires. If the tire brand cannot be supplied, the dealer will be contacted to propose alternative tire options. The dealer will need to respond with an alternative tire selection within 72 hours. If no response is provided by the supplier, the order will default to a comparable tire. As a consequence of a tire change the total machine price will be decreased or increased relative to the price of the new tire selection.

The information provided can be used to make a tire selection based on the particular conditions at the site. When available, the tire manufacturer should be consulted regarding proper tire selection.

APPLICATION SPECIFIC

L	515-5399	TIRES,14.0R24 SOIL TRACTION MP 0 Tire group received will be one of the tire groups listed below: - Bridgestone VKT 1* on 10" x 24" multi-piece rims. - Michelin XGLA2 1* on 10" x 24" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER	\$5,840
L	515-5400	TIRES,17.5R25 SOIL TRACTION MP 0 Tire group received will be one of the tire groups listed below: - Bridgestone VKT 1* on 14" x 25" multi-piece rims. - Michelin XTLA 1* on 14" x 25" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER	\$9,970

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS (CONT.)

APPLICATION SPECIFIC (Cont.)

L	515-5404	TIRES, 14.0R24 SOIL TRACTION MP 0 Tire group received will be one of the tire groups listed below: - Bridgestone VKT 1* on 10" x 24" multi-piece rims. - Michelin XGLA2 1* on 10" x 24" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$5,840
L	515-5405	TIRES, 17.5R25 SOIL TRACTION MP 0 Tire group received will be one of the tire groups listed below: - Bridgestone VKT 1* on 14" x 25" multi-piece rims. - Michelin XTLA 1* on 14" x 25" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$9,970

SHIPPING TIRES

L	448-5577	TIRES, 14.0 SHIPPING, MP 90 FOR USE IN LANE 3 ONLY Due to the height of the shipping tires, unloading will most likely require a crane to avoid damaging the bottom of the machine. Shipping tire for use during shipment of machine only. Solid rubber band mounted on 10" x 24" multi-piece rims. Must be replaced with pneumatic tire before delivering to customer. ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$2,060
L	440-3433	TIRES, 17.5 SHIPPING, MP 274 FOR USE WITH LANE 3 ONLY Due to the height of the shipping tires, unloading will most likely require a crane to avoid damaging the bottom of the machine. Shipping tire for use during shipment of machine only. Solid rubber band mounted on 14" x 25" multi-piece rims. Must be replaced with pneumatic tire before delivering to customer ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$2,320
L	448-5584	TIRES, 14.0 SHIPPING, AWD, MP 69 FOR USE WITH LANE 3 ONLY Due to the height of the shipping tires, unloading will most likely require a crane to avoid damaging the bottom of the machine. Shipping tire for use during shipment of machine only. Solid rubber band mounted on 10" x 24" multi-piece rims. Must be replaced with pneumatic tire before delivering to customer. ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$2,060
L	440-3434	TIRES, 17.5 SHIPPING, AWD, MP 83 FOR USE WITH LANE 3 ONLY Due to the height of the shipping tires, unloading will most likely require a crane to avoid damaging the bottom of the machine. Shipping tire for use during shipment of machine only. Solid rubber band mounted on 14" x 25" multi-piece rims. Must be replaced with pneumatic tire before delivering to customer ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$2,320

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS (CONT.)

MAXAM

L	578-9458	TIRES 17.5R25 MA MS202 ** MP 0 FOR USE IN LANE 3 ONLY Maxam MS202 2* on 14- x 25- multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8600 lbs) 3900kg.* ONLY FOR USE WITH: 515-2449 140 13A MOTOR GRADER	0	\$8,850
L	578-9460	TIRES 14.00R24 MA MS202 * MP 0 FOR USE IN LANE 3 ONLY Maxam MS202 2* on 14- x 25- multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8600 lbs) 3900kg.* ONLY FOR USE WITH: 515-2449 140 13A MOTOR GRADER	0	\$7,290
L	578-9462	TIRES 17.5R25 MA MS202 ** MP 0 FOR USE IN LANE 3 ONLY Maxam MS202 2* on 14- x 25- multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8600 lbs) 3900kg.** ONLY FOR USE WITH: 515-8361 140 13A AWD MOTOR GRADER	0	\$8,850
L	578-9463	TIRES 14.00R24 MA MS202 * MP 0 FOR USE IN LANE 3 ONLY Maxam MS202 2* on 14- x 25- multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8600 lbs) 3900kg.** ONLY FOR USE WITH: 515-8361 140 13A AWD MOTOR GRADER	0	\$7,290

MICHELIN

L	252-0701	TIRES,14.0R24 MX XSNO + * G2 MP 1,282 FOR USE IN LANE 3 ONLY Michelin XSNO 1* on 10" x 24" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (7824 lbs) 3550 kg.** ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER	1,282	\$13,830
L	252-0771	TIRES, 17.5R25 MX XTLA * L2 MP 1,371 Michelin XTLA 1* on 14" x 25" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER	1,371	\$15,250
L	249-7845	TIRES,14.0R24 MX XSNO + * G2 MP 1,261 Michelin XSNO 1* on 10" x 24" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (7824 lbs) 3550 kg.** ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER	1,261	\$13,830
L	252-0679	TIRES,14.0R24 MX XGLA2 * G2 MP 1,069 Michelin XGLA2 1* on 10" x 24" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (7824 lbs) 3550 kg.** ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER	1,069	\$9,970
L	252-0777	TIRES,17.5R25 MX XSNO + * G2 MP 1,093 Michelin XSNO+ 1* on 14" x 25" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER	1,093	\$19,190

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS (CONT.)

MICHELIN (Cont.)

L	252-0681	TIRES,14.0R24 MX XGLA2 * G2 MP 1,048 Michelin XGLA2 1* on 10" x 24" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (7824 lbs) 3550 kg.** ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$9,970
L	252-0773	TIRES, 17.5R25 MX XTLA * L2 MP 268 Michelin XTLA 1* on 14" x 25" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$15,250
L	252-0779	TIRES,17.5R25 MX XSNO+ * G2 MP. 903 Michelin XSNO+ 1* on 14" x 25" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$19,190

BRIDGESTONE

L	252-0714	TIRES, 14.0 R24 BS VKT * G2 MP 1,540 Bridgestone VKT 1* on 10- x 24- multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING 3650 kg (8,045 lbs).** ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$6,840
L	252-0775	TIRES, 17.5R25 BS VKT * D2A MP 1,810 Bridgestone VKT 1* on 14" x 25" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$10,970
L	586-5268	TIRES,14.00R24 BS VKT ***E-2MP. 0 FOR USE IN LANE 3 ONLY Bridgestone VKT 3* on 10- x 24- multi-piece rims. THE TIRE MANUFACTURE DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING 3650 kg (8,045 lbs).** ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$6,840
L	586-5273	TIRES,14.00R24 BS VKT ***E-2MP. 0 FOR USE IN LANE 3 ONLY 6 X Bridgestone VKT 3* on 10- X 24- Multipiece Rims THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING 3650 kg (8045 LBS). ONLY FOR USE WITH: 515-8361 140-13A AWD MOTOR GRADER		\$6,840
L	249-7841	TIRES, 17.5R25 BS VKT * D2A MP 1,620 Bridgestone VKT 1* on 14" x 25" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-8361 140-13A AWD MOTOR GRADER		\$10,970
L	252-0716	TIRES, 14.0R24 BS VKT * G2 MP 1,519 Bridgestone VKT 1* on 10" x 24" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$6,840

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS (CONT.)

BRIDGESTONE (Cont.)

L	600-4199	TIRES, 550/65R25 BS VTS *L3 MP 0 Offers optimum traction and low ground pressure for fine grading applications. Bridgestone VTS 1* on 14" x 25" multi-piece rims. THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-8361 140-13A MOTOR GRADER		\$21,160
---	----------	---	--	----------

GOODYEAR

L	310-7326	TIRE, 17.5R25 GY RL2+ 6S 1*MP 1,200 Goodyear RL2+ 6S on 14" x 25" multi-piece rims THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$18,290
L	310-7327	TIRES, GY17.5R25* COMBO MP 1,200 Goodyear RL2+ 6S on 14" x 25" multi-piece rims THE TIRE MANUFACTURER DOES NOT RECOMMEND THIS TIRE FOR INDIVIDUAL TIRE LOADS EXCEEDING (8045 lbs) 3650 kg.** ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$18,290

FLUIDS

COOLANT ANTIFREEZE

P	522-6654	COOLANT (-40C) 0 Standard engine coolant		NC
P	522-6655	COOLANT (-50C) 0 Engine coolant recommended for extreme low temperatures		\$283 NET

CAB ANTIFREEZE

	0P-1939	ANTIFREEZE WINDSHIELD WASHER 0		NC
--	---------	--	--	----

FUEL ANTIFREEZE

	0P-3978	FUEL ANTIFREEZE, -25C (-13F) 0 Provides fuel (diesel) antifreeze protection down to -25C (-13F)		NC
--	---------	--	--	----

DOCUMENTATION

LANGUAGE SELECTION

NOTE: This part number will provide the language for Messenger and Statement of Conformity.

L	386-1254	LANGUAGE, ENGLISH 0		NC
L	386-5928	LANGUAGE, SPANISH 0		NC

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

DOCUMENTATION (CONT.)

DECAL PACKAGES

NOTE:This part number will provide the films in ANSI or ISO Pictograms
The word "WARNING" is on picto decals for ANSI.
Symbols only are on picto decals for ISO.

P	516-2552	DECALS, ENGLISH (US)	0	NC
		Provides decals as required by ANSI.		

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

FEATURE PACKAGES

HEADLIGHT PACKAGES

Cannot mix halogen and LED light packages.

L	519-3700	LOW BAR, HALOGEN, TANDEM 0 Provides halogen low bar headlights with front turn signals, dimmer Switch for road lighting REQUIRES: 562-3742 ROADING LIGHTS W/FOLD DOWN ARM ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$660
P	558-5819	LOW BAR, LED, TANDEM 0 Provides LED low bar headlights with front turn signals, dimmer Switch for road lighting REQUIRES: 562-3742 ROADING LIGHTS W/FOLD DOWN ARM ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$1,405
P	519-3702	HIGH BAR, HALOGEN, TANDEM 0 Provides halogen high bar headlights with front turn signals, dimmer switch for road lighting REQUIRES: 562-3742 ROADING LIGHTS W/FOLD DOWN ARM ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$660
P	558-5820	HIGH BAR, LED, TANDEM 0 Provides LED high bar headlights with front turn signals, dimmer switch for road lighting REQUIRES: 562-3742 ROADING LIGHTS W/FOLD DOWN ARM ONLY FOR USE WITH: 515-2449 140-13A MOTOR GRADER		\$1,405
P	519-3705	LOW BAR, HALOGEN, AWD 0 Provides halogen low bar headlights with front turn signals, dimmer switch for road lighting REQUIRES: 562-3742 ROADING LIGHTS W/FOLD DOWN ARM ONLY FOR USE WITH: 515-8361 140-13A AWD MOTOR GRADER		\$660
P	558-5822	LOW BAR, LED, AWD 0 Provides LED low bar headlights with front turn signals, dimmer switch for road lighting REQUIRES: 562-3742 ROADING LIGHTS W/FOLD DOWN ARM ONLY FOR USE WITH: 515-8361 140-13A AWD MOTOR GRADER		\$1,405
P	519-3706	HIGH BAR, HALOGEN, AWD 0 Provides halogen high bar headlights with front turn signals, dimmer switch for road lighting REQUIRES: 562-3742 ROADING LIGHTS W/FOLD DOWN ARM ONLY FOR USE WITH: 515-8361 140-13A AWD MOTOR GRADER		\$660
P	558-5823	HIGH BAR, LED, AWD 0 Provides LED high bar headlights with front turn signals, dimmer switch for road lighting REQUIRES: 562-3742 ROADING LIGHTS W/FOLD DOWN ARM ONLY FOR USE WITH: 515-8361 140-13A AWD MOTOR GRADER		\$1,405

WORK LIGHT PACKAGES

Cannot mix halogen and LED light packages.

P	522-6533	LIGHTS, WORK BASIC, HALOGEN 0 INCLUDES: - Lights, Halogen, Heel - Lights, Halogen, Midframe Toe - Switch, Work Lighting		\$790
---	----------	--	--	-------

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

FEATURE PACKAGES (CONT.)

WORK LIGHT PACKAGES (Cont.)

P	522-6557	LIGHTS, WORK PLUS, HALOGEN 0 INCLUDES: - Lights, Ripper - Lights, Work, Heel - Lights, Work, Midframe Toe - Switch, Work Lighting		\$1,065
P	563-2272	LIGHTS, WORK PLUS, LED 0 INCLUDES: - Lights, LED, Ripper, - Lights, LED, Heel - Lights, LED, Midframe Toe - Switch, Work Lighting		\$2,670
P	501-4740	LIGHTS, SNOW, HALOGEN 0 INCLUDES: - Light, Halogen, Right Hand, Top of Cab		\$316
P	553-2591	LIGHTS, SNOW, LED 0 INCLUDES: - Light, LED, Right Hand, Top of Cab		\$740

CAB LIGHT PACKAGES

Cannot mix halogen and LED light packages.

P	501-4739	LIGHTS, CAB ROOF, HALOGEN 0 INCLUDES: - 4 Front Facing Lights - 2 Rear Facing Lights		NC
P	558-6474	LIGHTS, CAB ROOF, LED 0 INCLUDES: - 4 Front Facing Lights - 2 Rear Facing Lights		\$1,285

OTHER OPTIONAL ATTACHMENTS

Bluetooth radio technology enables the use of a hands free function such as listening to music and making phone calls. Authorization varies by country, please contact your Cat marketing representative with questions or click on the link below: <https://dealer.cat.com/en/products/technology.html>

P	518-3017	WARNING STROBE 0 Amber high-speed strobe beacon.		\$585
P	524-1765	TRANSMISSION, AUTOSHIFT 0 Improves ease of operation and maximizes productivity by automatically shifting the transmission at optimal shift points.		\$3,305
P	521-3250	CIRCLE SAVER 0 Circle Drive Injector Grease that helps the pinion to maintain its lubrication caused by lack of grease in this component.		\$246
P	524-1768	CAMERA, REAR VISION 0 Provides a 115 degree color camera mounted on the rear of the hood that is connected to a 7 inch (178mm) LCD color display mounted in the cab which shows the view behind the machine.		NC
P	518-3026	RADIO, AM/FM, USB/BLUETOOTH 0 Radio with AM/FM, Bluetooth, and USB		\$600

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

FEATURE PACKAGES (CONT.)

OTHER OPTIONAL ATTACHMENTS (Cont.)

P	524-3110	MIRROR, EXTERNAL, ISO 0 FOR USE IN LANE 3 ONLY Includes extra mirror with small curvature to broader views and reflect wider range, to meet ISO 5006.		\$505
---	----------	--	--	-------

TECHNOLOGY PRODUCTS

P	524-1769	STABLE BLADE 0 Provides sensor and software to automatically reduce engine speed in various applications to reduce machine bounce and scalloping of surface.		\$2,545
P	548-9540	CAT GRADE, BASE KIT 0 Required to mount 2D and 3D display and radio on an ARO machine. INCLUDES: - Radio Cable - Converter - Bracket - Display Mount		\$3,100

GUARDS

P	522-2419	GUARD, TRANSMISSION 0 Provides a steel guard to protect the transmission from ground debris.		\$3,500
P	527-5569	GUARD, AXLE HOSE, AWD 0 Provides additional protection to the front axle cylinders, lines, and fittings. NOT recommended for use with tire chains ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$1,105
P	506-4000	FENDERS, REAR 0 Provides non-metallic rear fenders to aid in reducing the build-up of mud, snow, or debris. Rear fenders are compatible with all MG tire sizes offered by the factory. NOT recommended for use with tire chains.		\$5,190
P	449-7700	FENDERS, FRONT, AWD 0 Non-metallic front fenders aid in reducing the build-up of mud, snow, or debris. Front fenders are NOT compatible w/ all Non-AWD tire sizes offered by the factory. NOT recommended for use with tire chains CANNOT BE USED WITH: MID MOUNT SCARIFIER PACKAGE CANNOT BE USED WITH: GUARD, AXLE HOSE ONLY FOR USE WITH: 515-8361 140-13AAWD MOTOR GRADER		\$3,910
P	522-2402	COVERS, UNDER CAB 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Under cab protection for Electronic Control Module	0	\$735 \$735 NI

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS

STARTING AIDS

L	249-5516	HEATER, ENGINE COOLANT, 120V 3 Engine coolant heater for 120 volt external power source. CANNOT BE USED WITH: 522-6394 COLD WEATHER PLUS, TANDEM 522-6396 COLD WEATHER PLUS PKG, AWD		\$253
---	----------	--	--	--------------

WORK TOOLS

P	336-1559	PUSH PLATE, COUNTERWEIGHT 2,000 Front mounted. Recommended when machine is equipped with rear ripper/scarifier and other rear mounted attachments. NOTE: This cannot be used in conjunction with counterweight, any front lift work tools, or the 'installed' hydraulic front lift. It can be used with a not installed hydraulic front lift CANNOT BE USED WITH: 367-6880 COUNTERWEIGHT 312-2204 LIFT GROUP, MANUAL FRONT		\$4,130
---	----------	---	--	----------------

L	367-6880	COUNTERWEIGHT. 885 Front mounted. Recommended when machine is not equipped with front or rear mounted work tool attachments to provide additional blade performance capability. NOTE: This cannot be used in conjunction with push plate, mid mount scarifier, front lift work tools, or the 'installed' hydraulic front lift. It can be used with a not installed hydraulic front lift NOT RECOMMENDED FOR USE WITH: RIPPER-SCARIFIER, REAR CANNOT BE USED WITH: 336-1559 PUSH PLATE, COUNTERWEIGHT 533-0077 LIFT GROUP, MANUAL FRONT		\$3,300
---	----------	--	--	----------------

P	533-0077	LIFT GROUP, MANUAL 1.5" 1,512 Front hydraulic lift without any work tool attached. NOTE: This Front Lift Group has manual locking pins. (The Installed Manual Lift Group can be attached to the machine at the sametime as the mounting for the mid-mount scarifier, but not the actual scarifier itself).		\$12,040
---	----------	--	--	-----------------

NOTE: A Not-Installed Manual Lift Group can be ordered with an INSTALLED Push Plate or Counterweight. The not-installed lift group will be skidded, banded and shipped with the unit.
 REQUIRES: 359-3925 MOUNTING, FRONT LIFT and
 524-8991 BASE+2 (RIP,FL) or
 524-8992 BASE+ 3 (RIP, MMS, FL) or
 524-8993 BASE+ 3 (RIP,MMS,FL) ARO or
 563-2341 BASE+4 (RIP,FL,WM,WT) or
 524-8995 BASE+4 (RIP,FL,WM,WT) ARO or
 524-8997 BASE+5 (RIP,FL,WM,WT,DA1)
 CANNOT BE USED WITH: 336-1559 PUSH PLATE, COUNTERWEIGHT
 367-6880 COUNTERWEIGHT
 339-7733 MID MOUNT SCARIFIER, BRACKET

L	359-3925	LIFT GROUP, FRONT MOUNTING 10 Two mounting plates welded to both sides of the front frame for factory or future installation of Front Lift. REQUIRED BY: 533-0077 LIFT GROUP, MANUAL, FRONT		\$456
---	----------	--	--	--------------

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

WORK TOOLS (CONT.)

P	516-3994	LINES, RIPPER, ADDITIONAL 0 For use with rear mounted auxiliary functions. Provides two hydraulic hoses with one end bundled at the rear of the machine and the other end bundled at the rear valve bank in front of the cab. CANNOT BE USED WITH: 524-8998 HYDRAULICS BASE		\$438
P	180-1679	MOUNT, SNOW WING, FRAME READY 200 INCLUDES: - Snow Wing Mounting Plate - Attachment Point for Lower Mast Brace - Attachment Point for Upper Mast Brace		\$2,035
P	339-7733	MID MOUNT SCARIFIER, BRACKET 70 FOR USE IN LANE 3 ONLY Brackets welded to front frame for future installation of midmount scarifier. NOTE: This is the mounting only and does not include the scarifier.		\$565
P	523-4579	MID MOUNT SCARIFIER PACKAGE 0 FOR USE IN LANE 3 ONLY INCLUDES: - Mid-mount Scarifier, V-Type with 11 Teeth - MOUNT, MID-MOUNT SCARIFIER ONLY FOR USE WITH: 524-8992 BASE + 3 (RIP, MMS, FBL) or 524-8993 BASE+3(RIP,MMS,FL)ACCUGRD+FLT CANNOT BE USED WITH: ANY FRONT LIFT GROUP		\$16,780

GROUND ENGAGING TOOLS

P	8J-1434	TOOTH, STRAIGHT 67 NOT INSTALLED option is only for use with Miscellaneous orders Ripper tooth group for rear ripper. Includes one straight shank with ripper tooth. Recommended order quantity of 2 ONLY FOR USE WITH: 515-4649 RIPPER/SCARIFIER		\$825
P	4K-3330	SHANKS/TEETH, RIPPER/SCARIFIER 152 Nine shanks for ripper and scarifier combination. Utilizes the scarifier shank positions on a ripper and scarifier combination. Will work with a midmount scarifier ONLY FOR USE WITH: 515-4649 RIPPER/SCARIFIER		\$1,446

FIELD INSTALLED ATTACHMENTS

Available Through Parts Distribution

Reference numbers below are kits used to upgrade existing motor graders with new features or technology

466-5233	KIT, EXTENSIONS, MIRROR HEATED 9" extension from Current Mirror, adds 2 additional mirrors 1 for front visibility and 1 rear visibility. Heated to keep free of ice and snow in cold weather Estimated install Hours: 2
----------	--

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

FIELD INSTALLED ATTACHMENTS (CONT.)

466-5255	KIT, EXTENSIONS, MIRROR STD 9" extension from Current Mirror, adds 2 additional mirrors, 1 for front visibility and 1 rear visibility Estimated install Hours: 2
250-0615	EXTENSION, BLADE, 24" LH 24" x 24" x 7/8" - Left Hand Blade Extension Kit for use with 12 ft. and 14 ft. Basic Moldboards. Estimated install Hours: 1.5
110-5327	EXTENSION, BLADE, 24" LH 24" x 27" x 1" - Left Hand Blade Extension Kit for use with 14 ft. Plus Moldboard. Estimated install Hours: 1.5
524-8605	EXTENSION, BLADE, 24" RH 24" x 24" x 7/8" - Right Hand Blade Extension Kit for use with 12 ft. and 14 ft. Basic Moldboards. Estimated install Hours: 1.5
524-8606	EXTENSION, BLADE, 24" RH 24" x 27" x 1" - Right Hand Blade Extension Kit for use with 14 ft. Plus Moldboard. Estimated install Hours: 1.5
524-8607	KIT, SPARE RIM 14" x 25" MP Spare Rim Estimated install Hours: 0.5
524-8609	KIT, SPARE RIM 10" x 24" MP Spare Rim Estimated install Hours: 0.5
488-2192	KIT, CIRCLE SAVER Circle Saver Estimated install Hours: 0.5 Special Instructions: REHS4230
434-1086	KIT, FENDERS, FRONT AWD Front Fender Kit
515-2225	KIT DRAIN, ENG OIL, HIGH SPEED
533-1551	KIT, FINISH GRADE RDY, STD DCM Provides all critical drawbar, circle, and moldboard wear parts to restore -factory tightness- to aid in maintaining a quality finish with less passes.
543-0052	KIT, GRADE RDY, TOP ADJUST DCM Provides all critical drawbar, circle, and moldboard wear parts required to restore -factory tightness- to aid in maintaining a quality surface finish with less passes.

ALTERNATE SOURCED ATTACHMENTS

Pricing and compatibility available through the Caterpillar Work Tools Price List (WT-MG) for Motor Grader Work Tools.

Please also reference Snow Products for Cat Motor Graders and Cat Medium Wheel Loaders (GEJQ0361).

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

ALTERNATE SOURCED ATTACHMENTS (CONT.)**ANGLE SNOW BLADES**

W	567-2725	BLADE, ANGLE SNOW, HYDRAULIC 40" x 132" 1.5" Pin
W	524-6855	BLADE, ANGLE SNOW, MANUAL 40" x 132" 1.5" Pin
W	567-2727	BLADE, ANGLE SNOW, TRIP EDGE 1.5" Pin

STRAIGHT BLADES

W	524-6868	BLD 112 STRAIGHT 1.5HPL 40" x 112" 1.5" Pin
---	----------	---

LIFT GROUPS

W	568-6277	LIFT GROUP, HYDRAULIC 1.5" Hydraulic locking pins (includes diverter valve to actuate hydraulic locking pins) 1.5" Pin
---	----------	--

FRONT SCARIFIERS

W	212-6232	SCARIFIER, FRONT V-TYPE 1.5HPL INCLUDES: 5 teeth
W	212-6231	SCARIFIER, FRONT V-TYPE 1.5HPL INCLUDES: 11 teeth

ONE-WAY PLOWS

W	230-7097	PLOW, 144 ONE-WAY SNOW HEIGHT: 67"(1702mm) 1.5" Pin
---	----------	---

V PLOWS

W	524-6838	BLD 104 V-PLOW HEIGHT: 69" (1748MM) 1.5" Pin
W	230-7098	BLD 117 V-PLOW 1.5HPL HEIGHT: 82"(2083mm) 1.5" Pin
W	524-6740	BLD 2.7M V-PLOW HEIGHT: 71" (1803MM) 1.5" Pin

U/V ANGLE BLADES

W	567-2728	BLD 120- U/V ANGLE HEIGHT: 40" (1016mm) 1.5" Pin
---	----------	--

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

ALTERNATE SOURCED ATTACHMENTS (CONT.)

U/V ANGLE BLADES (Cont.)

W	567-2729	BLD 144- U/V ANGLE HEIGHT: 40" (1016mm) 1.5" Pin		
W	567-6830	BLD 156- U/V ANGLE HEIGHT: 40" (1016mm) 1.5" Pin		

MASTED SNOW WINGS

W	567-2737	REAR BRACE, HYDRAULIC,ADJ WING 144" Moldboard		
W	567-2738	REAR BRACE, HYDRAULIC,ADJ WING 168" Moldboard		
W	567-2739	REAR BRACE, MANUAL, ADJ WING 144" Moldboard		
W	567-2740	REAR BRACE, MANUAL, ADJ WING 168" Moldboard		
W	258-7961	RIPPER HEIGHT ADJUSTMENT WING 144" Moldboard		
W	258-7962	RIPPER HEIGHT ADJUSTMENT WING 168" Moldboard		

MASTLESS SNOW WINGS

W	567-2733	MASTLESS,MANUAL PUSH POLE WING Ripper Mounted		
W	567-2735	WING, MAN PUSH POLE, BM Bumper Mounted		
W	567-2731	WING, HYD PUSH POLE, RM Ripper Mounted		
W	567-2732	WING, HYD PUSH POLE, BM Bumper Mounted		

PACKING

EXPORT PACKING

OP-2265	ROLL ON-ROLL OFF	0	\$314 NET
	Machine is driveable with nothing removed.		
OP-2962	SHIPPING TIRE FREIGHT OPTION	0	NC
	This OP is required when the machine is ordered with the Shipping Tire		
	This insures the correct trailer is used for shipment preventing		
	This is informational only and there is no additional charge.		
	REQUIRED BY: TIRES, 17.5 SHIPPING, MP		
	TIRES, 14.0 SHIPPING, MP		

ATTACHMENT PACKING

OP-6706	BUNDLE EXPORT PACKING	0	NC
	This OP should be ordered for miscellaneous orders		

CATERPILLAR MACHINE PRICE LIST

140LVR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	---------------------	--------------------	-------------------------

PACKING (CONT.)

PACKING STAIRS

0P-6588	REMOVE PACK LEFT SIDE STAIRS 0 REQUIRED BY: 449-7700 FENDERS FRONT AWD and 526-7045 MOLDBOARD, 14' BASIC or 439-9110 MOLDBOARD, 14' PLUS	NC
---------	--	-----------