



## Index – T5 Series Tractor

<u>EQUIPMENT DESCRIPTION</u>	<u>LATEST REVISION</u>	<u>PAGE NUMBER</u>
T5 Dual Command - Deluxe Cab Fast Pick	10/04/2021	2
T5 Dual Command - Deluxe Cab HiVis Fast Pick	10/04/2021	7
T5 Dual Command - Cab Less Loader Fast Pick	10/04/2021	14
T5 Dual Command - Deluxe ROPS Fast Pick	10/04/2021	18
T5 Dual Command - West Coast Less Loader Fast Pick	10/04/2021	24
T5 Dual Command - Less Fast Pick	10/04/2021	28
T5 Electro Command - Standard Fast Pick	10/04/2021	36
T5 Electro Command - Deluxe Fast Pick	10/04/2021	40
T5 Electro Command - Less Fast Pick	10/04/2021	44
T5 Dynamic Command - Standard Fast Pick	10/04/2021	51
T5 Dynamic Command - Premium Fast Pick	10/04/2021	57
T5 Dynamic Command - Less Fast Pick	10/04/2021	63
T5 Auto Command - Deluxe Fast Pick	10/04/2021	71
T5 Auto Command - Premium Fast Pick	10/04/2021	78
T5 Auto Command – Blue Power	10/04/2021	86
T5 Auto Command - Less Fast Pick	10/04/2021	93



**T5 DUAL COMMAND - DELUXE CAB FAST PICK  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- CommandArc™ ergonomically places most frequently used controls to operator's right
- High visibility panel provides a better view of loader when at full height
- Ten repositionable vents for heating and air conditioning
- Full-size instructor seat
- Electro Hydraulic shuttle lever
- 24x24 Dual Command™ transmission
- Power clutch to allow for gear changes without the use of the foot clutch
- 3.6L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B/Stage V emissions compliant compact HI-eSCR2:  
Integrated Diesel Oxidation Catalyst (DOC), maintenance free Diesel Particulate Filter (DPF), and Selective Catalyst Reduction (SCR) into single compact layout
- Factory Installed Loader available

**T5.90 DC**

90 Gross Engine hp  
73 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.100 DC**

100 Gross Engine hp  
85 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.110 DC**

110 Gross Engine hp  
93 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.120 DC**

117 Gross Engine hp  
100 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**ALL MODELS:**

Tier 4B/Stage V Emissions Compliant  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Constant Engine RPM  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Dual Element Air Filter  
Vertical Exhaust  
30.3 gal Fuel Tank with Guard  
2.8 gal AdBLUE DEF Tank  
Front Axle Support with access for  
Front Pump  
Parking brake

**TRANSMISSION:**

LH side steering column mounted  
Power Shuttle  
24 Forward X 24 Reverse Speeds  
(4) Synchronized Gears with a  
HiLo in each Gear  
Power clutch button on Gear lever  
to allow for gear changes without  
the use of the foot clutch  
(3) Non-synchronized Ranges  
Forward Reverse Synchronized Shuttle  
25 mph (40 kph)  
Speed varies with tire selection

**STEERING/BRAKES:**

Hydrostatic Power Steering  
Brakes-  
Wet disk brakes  
Hydraulically assisted

**AXLES:**

FRONT  
Heavy Duty 4WD  
Electrohydraulic FWD Engagement  
Adjustable Tread Width



**T5 DUAL COMMAND - DELUXE CAB FAST PICK  
US PRICE LIST**

## Standard Equipment

### REAR

Heavy Duty Flange Type  
Adjustable Tread Width

### HYDRAULIC SYSTEM:

Open Center System  
Dual Gear Pumps with Cooler  
Implement Pump: 16.9 gpm (63.8 L)  
Steering Pump: 9.7 gpm (37.0 L)  
Total Flow: 26.6 gpm (100.8 L)  
(2) Open Center Remote Valves with  
detent

REAR DIFFERENTIAL LOCK:  
Electronically Engaged

### PTO:

Fully Independent  
Hydraulic Engagement  
Flip-up PTO Shaft Guard  
540/1000 rpm  
Wet Clutch

### 3-POINT LIFT SYSTEM:

Right hand console mounted control  
Cab - Electronic Draft Control with  
Fender mounted controls  
5,620 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

### ELECTRICAL:

(1) 800 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
3-pin Power Outlet (30 amp)  
Single Pin (8 amp) Accessory Power  
outlet  
CAB - 2 - 12V power sockets  
ROPS - 1 - 12V power socket

### LIGHTING:

#### CAB

Front: (2) Halogen Headlights and  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

### INSTRUMENTATION:

Analog Instrumentation with warning  
lights for air cleaner service,  
alternator, oil pressure, fuel  
sediment/water sensor, PTO  
engagement, head light high beam,  
low fuel and parking brake,  
advanced instrument cluster,  
digital speed readout, gauges  
for fuel level, engine temperature,  
tachometer and hour meter

### OPERATOR PROTECTIVE STRUCTURE:

#### CAB MODELS

ROPS protected, flat deck platform  
with heat and air conditioning, tinted  
windshield, retractable sun screen,  
front and rear wiper / washer,  
instructor seat, two doors with locks,  
one internal & two external mirrors,  
openable side windows, hinged rear  
window (opens completely)  
Steering Wheel - tilt & telescope  
Seat - Cloth covered air suspension  
seat with 10 degrees swivel,  
operator's presence sensor,  
retractable seat belt and arm rests  
Suspended pedals  
Radio, speakers, and antenna

### MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem



**T5 DUAL COMMAND - DELUXE CAB FAST PICK  
US PRICE LIST**

### Standard Equipment

Toolbox

Skid Steer or Euro style Loader  
bucket attach

**WARRANTY:**

New Holland Standard Warranty Applies

**725LU SELF-LEVELING**

Maximum Lift Height @ pivot pin: 135"

Dump Clearance: 102.2"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,428 LBS

59" high @ 800mm: 5,549 LBS

Breakout Force @ 800mm: 5,661 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 93

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

**LOADER:**

**720LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 134"

Dump Clearance: 101.4"

Digging Depth: 7"

Lift Capacity

Max Height @ 800mm: 2,632 LBS

59" high @ 800mm: 3,638 LBS

Breakout Force @ 800mm: 4,455 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees

Bucket Dump Angle: 60 degrees

**T5 DUAL COMMAND - DELUXE CAB FAST PICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
T5.90 STG5 DC	Cab	19,401 LB	9071370P53	\$92,689.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
STD+30+HRN+ACS+MON (334994)	\$85.00			
Mech 3 Pt Hitch Ground Con (332035)	\$285.00			
T5.100 STG5 DC	Cab		9073439P52	\$95,376.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
STD+30+HRN+ACS+MON (334994)	\$85.00			
Mech 3 Pt Hitch Ground Con (332035)	\$285.00			
T5.110 STG5 DC	Cab		9075710P25	\$98,325.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
STD+30+HRN+ACS+MON (334994)	\$85.00			
Mech 3 Pt Hitch Ground Con (332035)	\$285.00			
T5.120 STG5 DC	Cab	19,401 LB	9077756P91	\$100,983.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
STD+30+HRN+ACS+MON (334994)	\$85.00			
Mech 3 Pt Hitch Ground Con (332035)	\$285.00			

**T5 DUAL COMMAND - DELUXE CAB FAST PICK  
 US PRICE LIST**

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0591XX	Deluxe Cab Fast Pick <b>Deluxe Cab Fast Pick Includes:</b> 744588: Deluxe Cab 759176: Hand Brake 336750: 84" Bucket 390832: EDC HPL 390832 334994: STD+30+HRN+ACS+MON 330470: 4 x 110 lb Rear Wheel Weights  Requires one selection for each of the following: Mid mount valve and joystick: 2 Function mid mount valve and joystick OR 2 Function mid mount valve and joystick + 3rd function diverter Loader: 720LU NSL or 725LU MSL loader (select one)		(903235P54)	(\$4,202.00)
---------	--	--	-------------	--------------

**HYDRAULICS**

MID-MOUNT

SD\_T8280 MID-MOUNT VALVES

762168	2 MMV Includes +/- transmissions buttons plus button to operate 3rd function. 4th and 5th buttons not in use in NA  Cab only		9001248P94	\$1,622.00
762169	2 MMV w/ 3 function diverter Includes +/- transmissions buttons plus button to operate 3rd function. 4th and 5th buttons not in use in NA  Cab only		9001874P18	\$2,434.00

**T5 DUAL COMMAND - DELUXE CAB FAST PICK  
 US PRICE LIST**

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

	336740	HD Non Self Leveling Ldr +SSQA <b>720LU Non Self Leveling with Skid Steer Style Attachment</b>		9005911P29	\$7,677.00
	336742	HD Non Self Leveling Ldr +Euro <b>720LU Non Self Leveling with Euro Style Attachment</b>		9005911P29	\$7,677.00
	336744	HD Self Leveling Ldr +SSQA <b>725LU Mechanical Self Leveling with Skid Steer Style Attachment</b>		9006846P84	\$8,892.00
	336746	HD Self Leveling Ldr +Euro <b>725LU Mechanical Self Leveling with Euro Style Attachment</b>		9006846P84	\$8,892.00

**MISCELLANEOUS**

FENDERS REAR

SD\_T8740 FRONT FENDERS

	744674	Dynamic Fenders		9000602P14	\$782.00
--	--------	-----------------	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9840 COUNTRY CONFIGURATION

	334256	Canada (FR) Config ROPS <b>French operator manual</b>			No Charge
	334257	USA Spanish Configuration <b>Spanish operator manual</b>			No Charge



**T5 DUAL COMMAND - DELUXE CAB HIVIS FP  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- CommandArc™ ergonomically places most frequently used controls to operator's right
- High visibility panel provides a better view of loader when at full height
- Ten repositionable vents for heating and air conditioning
- Full-size instructor seat
- Electro Hydraulic shuttle lever
- 24x24 Dual Command™ transmission
- Power clutch to allow for gear changes without the use of the foot clutch
- 3.6L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B/Stage V emissions compliant compact HI-eSCR2:
  - Integrated Diesel Oxidation Catalyst (DOC), maintenance free Diesel Particulate Filter (DPF), and Selective Catalyst Reduction (SCR) into single compact layout
- Factory Installed Loader available

**T5.90 DC**

90 Gross Engine hp  
73 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.100 DC**

100 Gross Engine hp  
85 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.110 DC**

110 Gross Engine hp  
93 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.120 DC**

117 Gross Engine hp  
100 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**ALL MODELS:**

Tier 4B/Stage V Emissions Compliant  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Constant Engine RPM  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Dual Element Air Filter  
Vertical Exhaust  
30.3 gal Fuel Tank with Guard  
2.8 gal AdBLUE DEF Tank  
Front Axle Support with access for  
Front Pump  
Parking brake

**TRANSMISSION:**

LH side steering column mounted  
Power Shuttle  
24 Forward X 24 Reverse Speeds  
(4) Synchronized Gears with a  
HiLo in each Gear  
Power clutch button on Gear lever  
to allow for gear changes without  
the use of the foot clutch  
(3) Non-synchronized Ranges  
Forward Reverse Synchronized Shuttle  
25 mph (40 kph)  
Speed varies with tire selection

**STEERING/BRAKES:**

Hydrostatic Power Steering  
Brakes-  
Wet disk brakes  
Hydraulically assisted

**AXLES:**

FRONT  
Heavy Duty 4WD  
Electrohydraulic FWD Engagement  
Adjustable Tread Width





**T5 DUAL COMMAND - DELUXE CAB HIVIS FP  
US PRICE LIST**

## Standard Equipment

### REAR

Heavy Duty Flange Type  
Adjustable Tread Width

### HYDRAULIC SYSTEM:

Open Center System  
Dual Gear Pumps with Cooler  
Implement Pump: 16.9 gpm (63.8 L)  
Steering Pump: 9.7 gpm (37.0 L)  
Total Flow: 26.6 gpm (100.8 L)  
(2) Open Center Remote Valves with detent

REAR DIFFERENTIAL LOCK:  
Electronically Engaged

### PTO:

Fully Independent  
Hydraulic Engagement  
Flip-up PTO Shaft Guard  
540/1000 rpm  
Wet Clutch

### 3-POINT LIFT SYSTEM:

Right hand console mounted control  
Cab - Electronic Draft Control with Fender mounted controls  
5,620 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

### ELECTRICAL:

(1) 800 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting and signals  
3-pin Power Outlet (30 amp)  
Single Pin (8 amp) Accessory Power outlet  
CAB - 2 - 12V power sockets  
ROPS - 1 - 12V power socket

### LIGHTING:

#### CAB

Front: (2) Halogen Headlights and  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

### INSTRUMENTATION:

Analog Instrumentation with warning lights for air cleaner service, alternator, oil pressure, fuel sediment/water sensor, PTO engagement, head light high beam, low fuel and parking brake, advanced instrument cluster, digital speed readout, gauges for fuel level, engine temperature, tachometer and hour meter

### OPERATOR PROTECTIVE STRUCTURE:

#### CAB MODELS

ROPS protected, flat deck platform with heat and air conditioning, tinted windshield, retractable sun screen, front and rear wiper / washer, instructor seat, two doors with locks, one internal & two external mirrors, openable side windows, hinged rear window (opens completely)  
Steering Wheel - tilt & telescope  
Seat - Cloth covered air suspension seat with 10 degrees swivel, operator's presence sensor, retractable seat belt and arm rests  
Suspended pedals  
Radio, speakers, and antenna

### MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem



**T5 DUAL COMMAND - DELUXE CAB HIVIS FP  
US PRICE LIST**

### Standard Equipment

Toolbox

Skid Steer or Euro style Loader  
bucket attach

**WARRANTY:**

New Holland Standard Warranty Applies

**725LU SELF-LEVELING**

Maximum Lift Height @ pivot pin: 135"

Dump Clearance: 102.2"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,428 LBS

59" high @ 800mm: 5,549 LBS

Breakout Force @ 800mm: 5,661 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 93

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

**LOADER:**

**720LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 134"

Dump Clearance: 101.4"

Digging Depth: 7"

Lift Capacity

Max Height @ 800mm: 2,632 LBS

59" high @ 800mm: 3,638 LBS

Breakout Force @ 800mm: 4,455 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees

Bucket Dump Angle: 60 degrees

**T5 DUAL COMMAND - DELUXE CAB HIVIS FP  
 US PRICE LIST**

### Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
T5.90 STG5 DC	Cab	19,401 LB	9071370P53	\$92,689.00
Includes the following Equipment				
14.9R24 R1W (8239404)		\$2,362.00		
18.4R34 R1W (8365404)		\$4,188.00		
STD+30+HRN+ACS+MON (334994)		\$85.00		
Mech 3 Pt Hitch Ground Con (332035)		\$285.00		
T5.100 STG5 DC	Cab		9073439P52	\$95,376.00
Includes the following Equipment				
14.9R24 R1W (8239404)		\$2,362.00		
18.4R34 R1W (8365404)		\$4,188.00		
STD+30+HRN+ACS+MON (334994)		\$85.00		
Mech 3 Pt Hitch Ground Con (332035)		\$285.00		
T5.110 STG5 DC	Cab		9075710P25	\$98,325.00
Includes the following Equipment				
14.9R24 R1W (8239404)		\$2,362.00		
18.4R34 R1W (8365404)		\$4,188.00		
STD+30+HRN+ACS+MON (334994)		\$85.00		
Mech 3 Pt Hitch Ground Con (332035)		\$285.00		
T5.120 STG5 DC	Cab	19,401 LB	9077756P91	\$100,983.00
Includes the following Equipment				
14.9R24 R1W (8239404)		\$2,362.00		
18.4R34 R1W (8365404)		\$4,188.00		
STD+30+HRN+ACS+MON (334994)		\$85.00		
Mech 3 Pt Hitch Ground Con (332035)		\$285.00		

**T5 DUAL COMMAND - DELUXE CAB HiVIS FP  
 US PRICE LIST**

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0593XX	Deluxe Cab HiVis Fast Pick <b>Deluxe Cab HiVis Fast Pick Includes:</b> 334183: Deluxe Cab w/HiVis Panel 759176: Hand Brake 336750: 84" Bucket 390832: EDC HPL 390832 334994: STD+30+HRN+ACS+MON 330470: 4 x 110 lb Rear Wheel Weights  Requires one selection for each of the following: Mid mount valve and joystick: 2 Function mid mount valve and joystick OR 2 Function mid mount valve and joystick + 3rd function diverter Loader: 720LU NSL or 725LU MSL Loader (select one)		(903235P54)	(\$4,202.00)
---------	--	--	-------------	--------------

**HYDRAULICS**

MID-MOUNT

SD\_T8280 MID-MOUNT VALVES

762168	2 MMV Includes +/- transmissions buttons plus button to operate 3rd function. 4th and 5th buttons not in use in NA  Cab only		9001248P94	\$1,622.00
762169	2 MMV w/ 3 function diverter Includes +/- transmissions buttons plus button to operate 3rd function. 4th and 5th buttons not in use in NA  Cab only		9001874P18	\$2,434.00

**T5 DUAL COMMAND - DELUXE CAB HIVIS FP  
 US PRICE LIST**

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

	336740	HD Non Self Leveling Ldr +SSQA <b>720LU Non Self Leveling with Skid Steer Style Attachment</b>		9005911P29	\$7,677.00
	336742	HD Non Self Leveling Ldr +Euro <b>720LU Non Self Leveling with Euro Style Attachment</b>		9005911P29	\$7,677.00
	336744	HD Self Leveling Ldr +SSQA <b>725LU Mechanical Self Leveling with Skid Steer Style Attachment</b>		9006846P84	\$8,892.00
	336746	HD Self Leveling Ldr +Euro <b>725LU Mechanical Self Leveling with Euro Style Attachment</b>		9006846P84	\$8,892.00

**MISCELLANEOUS**

FENDERS REAR

SD\_T8740 FRONT FENDERS

	744674	Dynamic Fenders		9000602P14	\$782.00
--	--------	-----------------	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9840 COUNTRY CONFIGURATION

	334256	Canada (FR) Config ROPS <b>French operator manual</b>			No Charge
	334257	USA Spanish Configuration <b>Spanish operator manual</b>			No Charge



**T5 DUAL COMMAND - CAB LESS LOADER FP  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- CommandArc™ ergonomically places most frequently used controls to operator's right
- High visibility panel provides a better view of loader when at full height
- Ten repositionable vents for heating and air conditioning
- Full-size instructor seat
- Electro Hydraulic shuttle lever
- 24x24 Dual Command™ transmission
- Power clutch to allow for gear changes without the use of the foot clutch
- 3.6L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B/Stage V emissions compliant compact HI-eSCR2:  
Integrated Diesel Oxidation Catalyst (DOC), maintenance free Diesel Particulate Filter (DPF), and Selective Catalyst Reduction (SCR) into single compact layout
- Factory Installed Loader available

**T5.90 DC**

90 Gross Engine hp  
73 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.100 DC**

100 Gross Engine hp  
85 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.110 DC**

110 Gross Engine hp  
93 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.120 DC**

117 Gross Engine hp  
100 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**ALL MODELS:**

Tier 4B/Stage V Emissions Compliant  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Constant Engine RPM  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Dual Element Air Filter  
Vertical Exhaust  
30.3 gal Fuel Tank with Guard  
2.8 gal AdBLUE DEF Tank  
Front Axle Support with access for  
Front Pump  
Parking brake

**TRANSMISSION:**

LH side steering column mounted  
Power Shuttle  
24 Forward X 24 Reverse Speeds  
(4) Synchronized Gears with a  
HiLo in each Gear  
Power clutch button on Gear lever  
to allow for gear changes without  
the use of the foot clutch  
(3) Non-synchronized Ranges  
Forward Reverse Synchronized Shuttle  
25 mph (40 kph)  
Speed varies with tire selection

**STEERING/BRAKES:**

Hydrostatic Power Steering  
Brakes-  
Wet disk brakes  
Hydraulically assisted

**AXLES:**

FRONT  
Heavy Duty 4WD  
Electrohydraulic FWD Engagement  
Adjustable Tread Width



**T5 DUAL COMMAND - CAB LESS LOADER FP  
US PRICE LIST**

## Standard Equipment

### REAR

Heavy Duty Flange Type  
Adjustable Tread Width

### HYDRAULIC SYSTEM:

Open Center System  
Dual Gear Pumps with Cooler  
Implement Pump: 16.9 gpm (63.8 L)  
Steering Pump: 9.7 gpm (37.0 L)  
Total Flow: 26.6 gpm (100.8 L)  
(2) Open Center Remote Valves with detent

### REAR DIFFERENTIAL LOCK:

Electronically Engaged

### PTO:

Fully Independent  
Hydraulic Engagement  
Flip-up PTO Shaft Guard  
540/1000 rpm  
Wet Clutch

### 3-POINT LIFT SYSTEM:

Right hand console mounted control  
Cab - Electronic Draft Control with Fender mounted controls  
5,620 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

### ELECTRICAL:

(1) 800 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting and signals  
3-pin Power Outlet (30 amp)  
Single Pin (8 amp) Accessory Power outlet  
CAB - 2 - 12V power sockets  
ROPS - 1 - 12V power socket

### LIGHTING:

#### CAB

Front: (2) Halogen Headlights and  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

### INSTRUMENTATION:

Analog Instrumentation with warning lights for air cleaner service, alternator, oil pressure, fuel sediment/water sensor, PTO engagement, head light high beam, low fuel and parking brake, advanced instrument cluster, digital speed readout, gauges for fuel level, engine temperature, tachometer and hour meter

### OPERATOR PROTECTIVE STRUCTURE:

#### CAB MODELS

ROPS protected, flat deck platform with heat and air conditioning, tinted windshield, retractable sun screen, front and rear wiper / washer, instructor seat, two doors with locks, one internal & two external mirrors, openable side windows, hinged rear window (opens completely)  
Steering Wheel - tilt & telescope  
Seat - Cloth covered air suspension seat with 10 degrees swivel, operator's presence sensor, retractable seat belt and arm rests  
Suspended pedals  
Radio, speakers, and antenna

### MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem  
Toolbox

### WARRANTY:

New Holland Standard Warranty Applies

**T5 DUAL COMMAND - CAB LESS LOADER FP  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
T5.90 STG5 DC	Cab	19,401 LB	9071370P53	\$92,689.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
STD+30+HRN+ACS+MON (334994)	\$85.00			
Mech 3 Pt Hitch Ground Con (332035)	\$285.00			
T5.100 STG5 DC	Cab		9073439P52	\$95,376.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
STD+30+HRN+ACS+MON (334994)	\$85.00			
Mech 3 Pt Hitch Ground Con (332035)	\$285.00			
T5.110 STG5 DC	Cab		9075710P25	\$98,325.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
STD+30+HRN+ACS+MON (334994)	\$85.00			
Mech 3 Pt Hitch Ground Con (332035)	\$285.00			
T5.120 STG5 DC	Cab	19,401 LB	9077756P91	\$100,983.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
STD+30+HRN+ACS+MON (334994)	\$85.00			
Mech 3 Pt Hitch Ground Con (332035)	\$285.00			



**T5 DUAL COMMAND - CAB LESS LOADER FP  
 US PRICE LIST**

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0594XX	Cab Less Loader <b>Cab Less Loader Fast Pick Includes:</b> 744588: Deluxe Cab 759176: Hand Brake 390124: Less Mid-Mount 743593: Less Front Loader 335215: 8 WEIGHTS 40 KG - CA		(903235P54)	(\$4,202.00)
---------	--	--	-------------	--------------

**MISCELLANEOUS**

FENDERS REAR

SD\_T8740 FRONT FENDERS

744674	Dynamic Fenders		9000602P14	\$782.00
--------	-----------------	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9840 COUNTRY CONFIGURATION

334256	Canada (FR) Config ROPS <b>French operator manual</b>			No Charge
334257	USA Spanish Configuration <b>Spanish operator manual</b>			No Charge



**T5 DUAL COMMAND - DELUXE ROPS FAST PICK  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- CommandArc™ ergonomically places most frequently used controls to operator's right
- High visibility panel provides a better view of loader when at full height
- Ten repositionable vents for heating and air conditioning
- Full-size instructor seat
- Electro Hydraulic shuttle lever
- 24x24 Dual Command™ transmission
- Power clutch to allow for gear changes without the use of the foot clutch
- 3.6L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B/Stage V emissions compliant compact HI-eSCR2:  
Integrated Diesel Oxidation Catalyst (DOC), maintenance free Diesel Particulate Filter (DPF), and Selective Catalyst Reduction (SCR) into single compact layout
- Factory Installed Loader available

**T5.90 DC**

90 Gross Engine hp  
73 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.100 DC**

100 Gross Engine hp  
85 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.110 DC**

110 Gross Engine hp  
93 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.120 DC**

117 Gross Engine hp  
100 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**ALL MODELS:**

Tier 4B/Stage V Emissions Compliant  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Constant Engine RPM  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Dual Element Air Filter  
Vertical Exhaust  
30.3 gal Fuel Tank with Guard  
2.8 gal AdBLUE DEF Tank  
Front Axle Support with access for  
Front Pump  
Parking brake

**TRANSMISSION:**

LH side steering column mounted  
Power Shuttle  
24 Forward X 24 Reverse Speeds  
(4) Synchronized Gears with a  
HiLo in each Gear  
Power clutch button on Gear lever  
to allow for gear changes without  
the use of the foot clutch  
(3) Non-synchronized Ranges  
Forward Reverse Synchronized Shuttle  
25 mph (40 kph)  
Speed varies with tire selection

**STEERING/BRAKES:**

Hydrostatic Power Steering  
Brakes-  
Wet disk brakes  
Hydraulically assisted

**AXLES:**

FRONT  
Heavy Duty 4WD  
Electrohydraulic FWD Engagement  
Adjustable Tread Width



**T5 DUAL COMMAND - DELUXE ROPS FAST PICK  
US PRICE LIST**

## Standard Equipment

### REAR

Heavy Duty Flange Type  
Adjustable Tread Width

### HYDRAULIC SYSTEM:

Open Center System  
Dual Gear Pumps with Cooler  
Implement Pump: 16.9 gpm (63.8 L)  
Steering Pump: 9.7 gpm (37.0 L)  
Total Flow: 26.6 gpm (100.8 L)  
(2) Open Center Remote Valves with  
detent

### REAR DIFFERENTIAL LOCK:

Electronically Engaged

### PTO:

Fully Independent  
Hydraulic Engagement  
Flip-up PTO Shaft Guard  
540/1000 rpm  
Wet Clutch

### 3-POINT LIFT SYSTEM:

Right hand console mounted control  
ROPS - Mechanical Draft Control with  
Lift-O-Matic Plus  
5,620 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

### ELECTRICAL:

(1) 800 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
3-pin Power Outlet (30 amp)  
Single Pin (8 amp) Accessory Power  
outlet  
ROPS - 1 - 12V power socket

### LIGHTING:

#### ROPS

Front: (2) Halogen Headlights  
Rear: (1) Worklight  
Turn Signals/Flashers/Rear Lights

### INSTRUMENTATION:

Analog Instrumentation with warning  
lights for air cleaner service,  
alternator, oil pressure, fuel  
sediment/water sensor, PTO  
engagement, head light high beam,  
low fuel and parking brake,  
advanced instrument cluster,  
digital speed readout, gauges  
for fuel level, engine temperature,  
tachometer and hour meter

### OPERATOR PROTECTIVE STRUCTURE:

#### ROPS MODELS

2-Post Foldable ROPS with ISO-  
mounted flat deck platform  
Steering Wheel - adjustable tilt  
Seat - Vinyl covered with mechanical  
suspension, operator's presence  
sensor, retractable seat belts and  
arm rests  
Suspended pedals  
Locking brake pedals

### MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem  
Toolbox

### WARRANTY:

New Holland Standard Warranty Applies

### LOADER:

#### 720LU NON SELF-LEVELING

Maximum Lift Height @ pivot pin: 134"  
Dump Clearance: 101.4"  
Digging Depth: 7"  
Lift Capacity

**T5 DUAL COMMAND - DELUXE ROPS FAST PICK  
 US PRICE LIST**

### Standard Equipment

Max Height @ 800mm: 2,632 LBS  
 59" high @ 800mm: 3,638 LBS  
 Breakout Force @ 800mm: 4,455 LBS  
 Reach @ Max Lift Height: 43"  
 Reach @ Ground Level: 91"  
 Bucket Rollback Angle: 44 degrees  
 Bucket Dump Angle: 60 degrees  
 Skid Steer or Euro style Loader  
 bucket attach

725LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 135"  
 Dump Clearance: 102.2"  
 Digging Depth: 6.4"  
 Lift Capacity  
 Max Height @ 800mm: 3,428 LBS  
 59" high @ 800mm: 5,549 LBS  
 Breakout Force @ 800mm: 5,661 LBS  
 Reach @ Max Lift Height: 43"  
 Reach @ Ground Level: 93

Bucket Rollback Angle: 40 degrees  
 Bucket Dump Angle: 60 degrees  
 Skid Steer or Euro style Loader  
 bucket attach

725LU SELF-LEVELING

Maximum Lift Height @ pivot pin: 135"  
 Dump Clearance: 102.2"  
 Digging Depth: 6.4"  
 Lift Capacity  
 Max Height @ 800mm: 3,428 LBS  
 59" high @ 800mm: 5,549 LBS  
 Breakout Force @ 800mm: 5,661 LBS  
 Reach @ Max Lift Height: 43"  
 Reach @ Ground Level: 93  
 Bucket Rollback Angle: 40 degrees  
 Bucket Dump Angle: 60 degrees  
 Skid Steer or Euro style Loader  
 bucket attach



**T5 DUAL COMMAND - DELUXE ROPS FAST PICK  
US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
T5.90 STG5 DC	Rops	19,401 LB	9060370P31	\$78,403.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
T5.100 STG5 DC	Rops		9062439P30	\$81,090.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
T5.110 STG5 DC	Rops		9064710P03	\$84,039.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
T5.120 STG5 DC	Rops		9066756P69	\$86,697.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			

**T5 DUAL COMMAND - DELUXE ROPS FAST PICK  
 US PRICE LIST**

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0589XX	Deluxe ROPS Fast Pick <b>Deluxe ROPS Fast Pick Includes:</b> <b>334190: Deluxe Platform w/FOPS</b> <b>759176: Hand Brake</b> <b>336750: 84" Bucket</b> <b>743595: Lift-O-Matic Plus</b> <b>330470: 4 x 110 lb Rear Wheel Weights</b>  <b>Requires one selection for each of the following:</b> <b>Mid mount valve and joystick:</b> 2 Function mid mount valve and joystick OR 2 Function mid mount valve and joystick + 3rd function diverter <b>Loader:</b> 720LU NSL or 725LU MSL loader (select one)		(903235P54)	(\$4,202.00)
---------	---	--	-------------	--------------

**HYDRAULICS**

MID-MOUNT

SD\_T8280 MID-MOUNT VALVES

762166	2MMV w/ Joystick New <b>3rd live not available on T5 DC models</b>  <b>ROPS only</b>		9001248P94	\$1,622.00
762167	2MMV+DIV w/ Joystick New <b>With Diverter valve</b> <b>ROPS only</b>		9001874P18	\$2,434.00

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

336740	HD Non Self Leveling Ldr +SSQA <b>720LU Non Self Leveling with Skid Steer Style Attachment</b>		9005911P29	\$7,677.00
336742	HD Non Self Leveling Ldr +Euro <b>720LU Non Self Leveling with Euro Style Attachment</b>		9005911P29	\$7,677.00

**T5 DUAL COMMAND - DELUXE ROPS FAST PICK  
 US PRICE LIST**

	336744	HD Self Leveling Ldr +SSQA <b>725LU Mechanical Self Leveling with Skid Steer Style Attachment</b>		9006846P84	\$8,892.00
	336746	HD Self Leveling Ldr +Euro <b>725LU Mechanical Self Leveling with Euro Style Attachment</b>		9006846P84	\$8,892.00

**HITCH**

REAR 3 POINT HITCH

SD\_T8130 3 POINT HITCH CONTROL

	332035	Mech 3 Pt Hitch Ground Control		9000219P45	\$285.00
--	--------	--------------------------------	--	------------	----------

**MISCELLANEOUS**

FENDERS FRONT

SD\_T8700 FENDERS

	744599	Rear Fenders w/Extensions		9000139P37	\$181.00
--	--------	---------------------------	--	------------	----------

FENDERS REAR

SD\_T8740 FRONT FENDERS

	744674	Dynamic Fenders		9000602P14	\$782.00
--	--------	-----------------	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9840 COUNTRY CONFIGURATION

	334256	Canada (FR) Config ROPS <b>French operator manual</b>			No Charge
	334257	USA Spanish Configuration <b>Spanish operator manual</b>			No Charge



**T5 DUAL COMMAND - WEST COAST LESS LOADER  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- CommandArc™ ergonomically places most frequently used controls to operator's right
- High visibility panel provides a better view of loader when at full height
- Ten repositionable vents for heating and air conditioning
- Full-size instructor seat
- Electro Hydraulic shuttle lever
- 24x24 Dual Command™ transmission
- Power clutch to allow for gear changes without the use of the foot clutch
- 3.6L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B/Stage V emissions compliant compact HI-eSCR2:
  - Integrated Diesel Oxidation Catalyst (DOC), maintenance free Diesel Particulate Filter (DPF), and Selective Catalyst Reduction (SCR) into single compact layout
- Factory Installed Loader available

**T5.90 DC**

90 Gross Engine hp  
73 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.100 DC**

100 Gross Engine hp  
85 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.110 DC**

110 Gross Engine hp  
93 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.120 DC**

117 Gross Engine hp  
100 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**ALL MODELS:**

Tier 4B/Stage V Emissions Compliant  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Constant Engine RPM  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Dual Element Air Filter  
Vertical Exhaust  
30.3 gal Fuel Tank with Guard  
2.8 gal AdBLUE DEF Tank  
Front Axle Support with access for  
Front Pump  
Parking brake

**TRANSMISSION:**

LH side steering column mounted  
Power Shuttle  
24 Forward X 24 Reverse Speeds  
(4) Synchronized Gears with a  
HiLo in each Gear  
Power clutch button on Gear lever  
to allow for gear changes without  
the use of the foot clutch  
(3) Non-synchronized Ranges  
Forward Reverse Synchronized Shuttle  
25 mph (40 kph)  
Speed varies with tire selection

**STEERING/BRAKES:**

Hydrostatic Power Steering  
Brakes-  
Wet disk brakes  
Hydraulically assisted

**AXLES:**

FRONT  
Heavy Duty 4WD  
Electrohydraulic FWD Engagement  
Adjustable Tread Width





**T5 DUAL COMMAND - WEST COAST LESS LOADER  
US PRICE LIST**

## Standard Equipment

### REAR

Heavy Duty Flange Type  
Adjustable Tread Width

### HYDRAULIC SYSTEM:

Open Center System  
Dual Gear Pumps with Cooler  
Implement Pump: 16.9 gpm (63.8 L)  
Steering Pump: 9.7 gpm (37.0 L)  
Total Flow: 26.6 gpm (100.8 L)  
(2) Open Center Remote Valves with detent

REAR DIFFERENTIAL LOCK:  
Electronically Engaged

### PTO:

Fully Independent  
Hydraulic Engagement  
Flip-up PTO Shaft Guard  
540/1000 rpm  
Wet Clutch

### 3-POINT LIFT SYSTEM:

Right hand console mounted control  
ROPS - Mechanical Draft Control with Lift-O-Matic Plus  
5,620 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

### ELECTRICAL:

(1) 800 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting and signals  
3-pin Power Outlet (30 amp)  
Single Pin (8 amp) Accessory Power

outlet

ROPS - 1 - 12V power socket

### LIGHTING:

ROPS  
Front: (2) Halogen Headlights  
Rear: (1) Worklight  
Turn Signals/Flashers/Rear Lights

### INSTRUMENTATION:

Analog Instrumentation with warning lights for air cleaner service, alternator, oil pressure, fuel sediment/water sensor, PTO engagement, head light high beam, low fuel and parking brake, advanced instrument cluster, digital speed readout, gauges for fuel level, engine temperature, tachometer and hour meter

### OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS  
2-Post Foldable ROPS with ISO-mounted flat deck platform  
Steering Wheel - adjustable tilt  
Seat - Vinyl covered with mechanical suspension, operator's presence sensor, retractable seat belts and arm rests  
Suspended pedals  
Locking brake pedals

### MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem  
Toolbox

### WARRANTY:

New Holland Standard Warranty Applies



**T5 DUAL COMMAND - WEST COAST LESS LOADER  
US PRICE LIST**

### Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
T5.90 STG5 DC	Rops	19,401 LB	9060370P31	\$78,403.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
T5.100 STG5 DC	Rops		9062439P30	\$81,090.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
T5.110 STG5 DC	Rops		9064710P03	\$84,039.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
T5.120 STG5 DC	Rops		9066756P69	\$86,697.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			

**T5 DUAL COMMAND - WEST COAST LESS LOADER  
 US PRICE LIST**

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

	X0596XX	West Coast Less Loader <b>West Coast Less Loader Fast Pick Includes:</b> <b>392315: Platform w/Foldable ROPS</b> <b>759176: Hand Brake</b> <b>390124: Less Mid-Mount</b> <b>743593: Less Front Loader</b> <b>XT8140X: Less Bucket</b> <b>332035: Mech 3 Pt Hitch Ground Control</b> <b>335215: 8 WEIGHTS 40 KG - CA</b>		(903235P54)	(\$4,202.00)
--	---------	---	--	-------------	--------------

**HITCH**

REAR 3 POINT HITCH

SD\_T8200 HITCH

	758931	MDC HPL+LOM+2AUX <b>2 auxiliary lift rams for ROPS</b> <b>8,000 lbs lift capacity</b>		9000900P90	\$1,170.00
--	--------	---	--	------------	------------

**OPERATOR'S MANUALS**

SD\_T9840 COUNTRY CONFIGURATION

	334256	Canada (FR) Config ROPS <b>French operator manual</b>			No Charge
	334257	USA Spanish Configuration <b>Spanish operator manual</b>			No Charge



**T5 DUAL COMMAND - LESS FAST PICK  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- CommandArc™ ergonomically places most frequently used controls to operator's right
- High visibility panel provides a better view of loader when at full height
- Ten repositionable vents for heating and air conditioning
- Full-size instructor seat
- Electro Hydraulic shuttle lever
- 24x24 Dual Command™ transmission
- Power clutch to allow for gear changes without the use of the foot clutch
- 3.6L, 4-cylinder, 16 valve F5G engines with common rail fuel injection system
- Tier 4B/Stage V emissions compliant compact HI-eSCR2:
  - Integrated Diesel Oxidation Catalyst (DOC), maintenance free Diesel Particulate Filter (DPF), and Selective Catalyst Reduction (SCR) into single compact layout
- Factory Installed Loader available

**T5.90 DC**

90 Gross Engine hp  
73 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.100 DC**

100 Gross Engine hp  
85 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.110 DC**

110 Gross Engine hp  
93 PTO hp @ 2300 rpm  
4 Cyl Turbocharged Engine  
207 cu in (3.6 L) Displacement

**T5.120 DC**

117 Gross Engine hp  
100 PTO hp @ 2300 rpm

4 Cyl Turbocharged Engine  
207 cu in (3.4 L) Displacement

**ALL MODELS:**

Tier 4B Emissions Compliant:  
(SCR + CEGR)  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Constant Engine RPM  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Dual Element Air Filter  
Vertical Exhaust  
30.3 gal Fuel Tank with Guard  
2.8 gal AdBLUE DEF Tank  
Front Axle Support with access for  
Front Pump  
Parking brake

**TRANSMISSION:**

LH side steering column mounted  
Power Shuttle  
24 Forward X 24 Reverse Speeds  
(4) Synchronized Gears with a  
HiLo in each Gear  
Power clutch button on Gear lever  
to allow for gear changes without  
the use of the foot clutch  
(3) Non-synchronized Ranges  
Forward Reverse Synchronized Shuttle  
25 mph (40 kph)  
Speed varies with tire selection

**STEERING/BRAKES:**

Hydrostatic Power Steering  
Brakes-  
Wet disk brakes  
Hydraulically assisted

**AXLES:**

FRONT  
Heavy Duty 4WD  
Electrohydraulic FWD Engagement  
Adjustable Tread Width



**T5 DUAL COMMAND - LESS FAST PICK  
US PRICE LIST**

## Standard Equipment

### REAR

Heavy Duty Flange Type  
Adjustable Tread Width

### HYDRAULIC SYSTEM:

Open Center System  
Dual Gear Pumps with Cooler  
Implement Pump: 16.9 gpm (63.8 L)  
Steering Pump: 9.7 gpm (37.0 L)  
Total Flow: 26.6 gpm (100.8 L)  
(2) Open Center Remote Valves with  
detent

### REAR DIFFERENTIAL LOCK:

Electronically Engaged

### PTO:

Fully Independent  
Hydraulic Engagement  
Flip-up PTO Shaft Guard  
540/1000 rpm  
Wet Clutch

### 3-POINT LIFT SYSTEM:

Right hand console mounted control  
Cab - Electronic Draft Control with  
Fender mounted controls  
ROPS - Mechanical Draft Control with  
Lift-O-Matic Plus  
5,620 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

### ELECTRICAL:

(1) 800 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
3-pin Power Outlet (30 amp)  
Single Pin (8 amp) Accessory Power

outlet

CAB - 2 - 12V power sockets

ROPS - 1 - 12V power socket

### LIGHTING:

CAB

Front: (2) Halogen Headlights and  
(2) cab mounted worklights

Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

ROPS

Front: (2) Halogen Headlights

Rear: (1) Worklight

Turn Signals/Flashers/Rear Lights

### INSTRUMENTATION:

Analog Instrumentation with warning  
lights for air cleaner service,  
alternator, oil pressure, fuel  
sediment/water sensor, PTO  
engagement, head light high beam,  
low fuel and parking brake,  
advanced instrument cluster,  
digital speed readout, gauges  
for fuel level, engine temperature,  
tachometer and hour meter

### OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, flat deck platform  
with heat and air conditioning, tinted  
windshield, retractable sun screen,  
front and rear wiper / washer,  
instructor seat, two doors with locks,  
one internal & two external mirrors,  
openable side windows, hinged rear  
window (opens completely)

Steering Wheel - tilt & telescope

Seat - Cloth covered air suspension

seat with 10 degrees swivel,

operator's presence sensor,

retractable seat belt and arm rests

Suspended pedals

Radio, speakers, and antenna



**T5 DUAL COMMAND - LESS FAST PICK  
US PRICE LIST**

**Standard Equipment**

**ROPS MODELS**

2-Post Foldable ROPS with ISO-  
mounted flat deck platform  
Steering Wheel - adjustable tilt  
Seat - Vinyl covered with mechanical  
suspension, operator's presence  
sensor, retractable seat belts and  
arm rests  
Suspended pedals  
Locking brake pedals

**MISCELLANEOUS:**

Pivoting Engine Hood  
SMV Emblem  
Toolbox

**WARRANTY:**

New Holland Standard Warranty Applies

**LOADER:**

**720LU NON SELF-LEVELING**

Maximum Lift Height @ pivot pin: 134"  
Dump Clearance: 101.4"

Digging Depth: 7"

Lift Capacity

Max Height @ 800mm: 2,632 LBS

59" high @ 800mm: 3,638 LBS

Breakout Force @ 800mm: 4,455 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 91"

Bucket Rollback Angle: 44 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

**725LU SELF-LEVELING**

Maximum Lift Height @ pivot pin: 135"

Dump Clearance: 102.2"

Digging Depth: 6.4"

Lift Capacity

Max Height @ 800mm: 3,428 LBS

59" high @ 800mm: 5,549 LBS

Breakout Force @ 800mm: 5,661 LBS

Reach @ Max Lift Height: 43"

Reach @ Ground Level: 93"

Bucket Rollback Angle: 40 degrees

Bucket Dump Angle: 60 degrees

Skid Steer or Euro style Loader

bucket attach

**T5 DUAL COMMAND - LESS FAST PICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
T5.90 STG5 DC	Cab	19,401 LB	9071370P53	\$92,689.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
STD+30+HRN+ACS+MON (334994)	\$85.00			
Mech 3 Pt Hitch Ground Con (332035)	\$285.00			
T5.90 STG5 DC	Rops	19,401 LB	9060370P31	\$78,403.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
T5.100 STG5 DC	Cab		9073439P52	\$95,376.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
STD+30+HRN+ACS+MON (334994)	\$85.00			
Mech 3 Pt Hitch Ground Con (332035)	\$285.00			
T5.100 STG5 DC	Rops		9062439P30	\$81,090.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
T5.110 STG5 DC	Cab		9075710P25	\$98,325.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
STD+30+HRN+ACS+MON (334994)	\$85.00			
Mech 3 Pt Hitch Ground Con (332035)	\$285.00			
T5.110 STG5 DC	Rops		9064710P03	\$84,039.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
T5.120 STG5 DC	Cab	19,401 LB	9077756P91	\$100,983.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			
STD+30+HRN+ACS+MON (334994)	\$85.00			
Mech 3 Pt Hitch Ground Con (332035)	\$285.00			
T5.120 STG5 DC	Rops		9066756P69	\$86,697.00
Includes the following Equipment				
14.9R24 R1W (8239404)	\$2,362.00			
18.4R34 R1W (8365404)	\$4,188.00			

**T5 DUAL COMMAND - LESS FAST PICK  
 US PRICE LIST**

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

	X99801X Custom Configuration			No Charge
--	------------------------------	--	--	-----------

**OPERATOR PLATFORM**

SD\_T9200 OPERATOR STRUCTURE #1

ROPS				
	392315 Platform w/Foldable ROPS <b>Includes tilt column</b>			No Charge
	334190 Deluxe Platform w/FOPS <b>Includes tilt column, FOPS canopy, noise reduction kit and 12V power outlet</b>		9001397P55	\$1,815.00
Cab				
	744588 Deluxe Cab <b>Includes instructor seat, rear wiper and washer, radio &amp; internal mirror</b>			No Charge
	334183 Deluxe Cab w/HiVis Panel <b>Includes high visibility panel, instructor seat, rear wiper and washer, radio &amp; internal mirror</b>		9000468P93	\$609.00

**POWER TRAIN**

TRANSMISSION

SD\_T2820 PARK LOCK

	743551 Parking Lock		9000044P66	\$58.00
	759176 Hand Brake <b>Hand operated parking brake lever Standard Equipment</b>			No Charge

**TIRES**

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

Ag Front Tires				
	8232404 11.2R24 R1W		9001011P78	\$1,314.00



**T5 DUAL COMMAND - LESS FAST PICK  
 US PRICE LIST**

	8235404	12.4R24 R1W		9001208P90	\$1,570.00
	8236404	13.6R24 R1W		9001478P40	\$1,920.00
	8239404	14.9R24 R1W		9001818P74	\$2,362.00
<b>Specialty Front Tires</b>					
	8290904	12.5/80-18 10PR R4		9001444P52	\$1,876.00
	8873402	360/80R20 TRI 2 HD <b>Municipal Tread</b>		9001645P49	\$2,137.00
	8247404	11.2R28 R1W		9001248P94	\$1,622.00

**REAR**

**SD\_T4950 REAR WHEELS AND TIRES**

<b>Ag Rear Tires</b>					
	8357404	18.4R30 R1W <b>4WD Front Tire - 12.4R24 (8235404)</b>		9002928P31	\$3,803.00
	8302804	16.9R34 R1W <b>Front Tire - 13.6R24 (8236404)</b>		9002107P49	\$2,737.00
	8365404	18.4R34 R1W <b>4WD Front Tire - 14.9R24 (8239404)</b>		9003224P76	\$4,188.00
<b>Specialty Rear Tires</b>					
	8391904	19.5L-24 10 PR R4 <b>4WD Front Tire - 12.5/80-18 (8290904)</b>		9002236P08	\$2,904.00
	8906401	440/80 R30 TRI 2 <b>Municipal tread 4WD Front Tire - 360/80R20 (8873402)</b>		9003066P14	\$3,982.00
	8372404	13.6R38 R1W 8372404 <b>4WD Front Tire - 11.2R28 (8247404)</b>		9001966P58	\$2,554.00

**HYDRAULICS**

**MID-MOUNT**

**SD\_T8280 MID-MOUNT VALVES**

	762166	2MMV w/ Joystick New <b>3rd live not available on T5 DC models</b>  <b>ROPS only</b>		9001248P94	\$1,622.00
	762167	2MMV+DIV w/ Joystick New <b>With Diverter valve ROPS only</b>		9001874P18	\$2,434.00
	762168	2 MMV <b>Includes +/- transmissions buttons plus button to operate 3rd function. 4th and 5th buttons not in use in NA</b>  <b>Cab only</b>		9001248P94	\$1,622.00

**T5 DUAL COMMAND - LESS FAST PICK  
 US PRICE LIST**

	762169	2 MMV w/ 3 function diverter <b>Includes +/- transmissions buttons plus button to operate 3rd function. 4th and 5th buttons not in use in NA</b>  <b>Cab only</b>		9001874P18	\$2,434.00
--	--------	--	--	------------	------------

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

	336740	HD Non Self Leveling Ldr +SSQA <b>720LU Non Self Leveling with Skid Steer Style Attachment</b>		9005911P29	\$7,677.00
	336742	HD Non Self Leveling Ldr +Euro <b>720LU Non Self Leveling with Euro Style Attachment</b>		9005911P29	\$7,677.00
	336744	HD Self Leveling Ldr +SSQA <b>725LU Mechanical Self Leveling with Skid Steer Style Attachment</b>		9006846P84	\$8,892.00
	336746	HD Self Leveling Ldr +Euro <b>725LU Mechanical Self Leveling with Euro Style Attachment</b>		9006846P84	\$8,892.00

SD\_T8140 BUCKET

	336750	84" Bucket		9000792P33	\$1,029.00
--	--------	------------	--	------------	------------

**HITCH**

REAR 3 POINT HITCH

SD\_T8200 HITCH

	390832	EDC HPL 390832			No Charge
	758931	MDC HPL+LOM+2AUX <b>2 auxiliary lift rams for ROPS 8,000 lbs lift capacity</b>		9000900P90	\$1,170.00
	758932	EDC HPL + 2 AUX <b>2 auxiliary lift rams for Cab 8,000 lbs lift capacity</b>		9000900P90	\$1,170.00

**CAB OR ROPS PLATFORM**

OTHER

SD\_T6730 PIN CONNECTOR

	334994	STD+30+HRN+ACS+MON <b>Monitor mounting bracket, 30Ah socket &amp; 2-12V power outlets Cab ONLY</b>		9000065P45	\$85.00
--	--------	---	--	------------	---------

**T5 DUAL COMMAND - LESS FAST PICK  
 US PRICE LIST**

**WEIGHTS**

FRONT

SD\_T2150 FRONT BALLAST

	333215	Front Carrier +6 88 lb Weights <b>Total weight - 661 lbs (300 kg)</b>		9000688P38	\$894.00
	335215	8 WEIGHTS 40 KG - CA <b>Total weight - 837 lbs (380 kg)</b>		9000871P64	\$1,132.00

REAR

SD\_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights <b>Total weight - 440 lbs (200 kg)</b> <b>NOT compatible with 24" rear tires option</b>		9000537P46	\$698.00
--	--------	---	--	------------	----------

**MISCELLANEOUS**

FENDERS FRONT

SD\_T8700 FENDERS

	744599	Rear Fenders w/Extensions		9000139P37	\$181.00
--	--------	---------------------------	--	------------	----------

FENDERS REAR

SD\_T8740 FRONT FENDERS

	744674	Dynamic Fenders		9000602P14	\$782.00
--	--------	-----------------	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9840 COUNTRY CONFIGURATION

	334256	Canada (FR) Config ROPS <b>French operator manual</b>			No Charge
	334257	USA Spanish Configuration <b>Spanish operator manual</b>			No Charge



**T5 ELECTRO COMMAND - STANDARD FASTPICK  
US PRICE LIST**

## Standard Equipment

KEY SELLING POINTS (some features are optional equipment):

- 16 x 16 Electro Command semi-powershift transmission
- Auto PTO manages PTO engagement in relation to the rear hitch position
- Engine Speed Management (constant engine RPM) - 2 settings
- Terralock™ automatic traction system
- CommandArc™ ergonomics
- 200 degree windshield wiper
- Standard high visibility panel (opening)
- (10) repositionable AC/heater vents
- Full-size instructor seat
- Hydraulic shuttle lever -finger control
- 3.4L, 4-cylinder, F5G engines with 4 valves per cylinder common rail fuel injection systems
- 8,084 lb. 3-point lift capacity
- Tier 4B/final emissions compliant ECOBlue Compact HI-eSCR (Selective Catalytic Reduction) after-treatment with low rate Cooled Exhaust Gas Recirculation (CEGR); no diesel particulate filter, no regeneration req.

MODELS:

T5.110

- 107 gross engine HP
- 93 PTO HP @ 2300 rpm
- 4-cyl. turbocharged and intercooled
- 207 cu. in. (3.4 L) displacement
- 4 valves per cylinder

T5.120

- 117 gross engine HP
- 100 PTO HP @ 2300 rpm
- 4-cyl. turbocharged and intercooled
- 207 cu. in. (3.4 L) displacement
- 4 Valves per cylinder

ENGINE:

- Tier 4B emissions: Compact HI-eSCR SCR with low rate CEGR
- Electronic injection Bosch high-pressure common rail system
- Engine Speed Management
- Electric engine shutoff
- Grid heater starting Aid
- Engine block heater
- Dual element air filter
- Vertical exhaust
- 43.6 gallon (165 L) fuel tank with guard
- 3.2 gallon (12 L) DEF (diesel exhaust fluid) tank

TRANSMISSION:

- 16 x 16 semi-powershift
- 8 push button powershift speeds
- Control buttons on gear shift lever and on CommandArc™
- Electrohydraulic shuttle
- 25-mph (40-kph) road speed
- 16th gear (32nd w/creeper) is an economy gear that operates the engine at a lower RPM to save fuel
- Multi-disk cerametallic clutch
- Transmission heater

STEERING/BRAKES:

- Hydrostatic power steering
- Hydraulic wet brakes (equalizing and self-adjusting)
- Park brake

FRONT AXLE:

- Class 1.5 w/Auto 4WD management
- Electrohydraulic FWD engagement

-REAR AXLE:

- Heavy-duty flange
- Dog clutch differential lock
- Auto differential lock management
- Electrohydraulic rear differential lock



**T5 ELECTRO COMMAND - STANDARD FASTPICK  
US PRICE LIST**

## Standard Equipment

### HYDRAULIC SYSTEM:

- Fixed displacement pumps
- Tandem gear pumps
- Maximum flow at rated engine speed:
  - Implement pump: 21.1 gpm (80 l/m)
  - Steering pump: 11.4 gpm (43 l/m)
- (2) closed center rear remote valves configurable detent w/ quick release couplers
- 2 function mechanical mid mount valve and joystick
- Complete loader ready

### PTO:

- Fully independent
- Flip-up PTO shaft guard
- 540/1000 rpm interchangeable shaft
- Electrohydraulic engagement
- Multi-plate clutch
- Fender-mounted EDC / PTO switches

### 3-POINT LIFT SYSTEM:

- Right hand console-mounted mouse
- Electronic Draft Control (EDC)
- Fast raise/lower control
- 8,084 lb. lift cap (OECD, 90% psi at 24" rear of lower link balls)
- Category II flexible lower link ends
- Telescopic stabilizers

### INSTRUMENTATION:

- Analog/digital instrument panel with:
  - Integrated warning lights
  - Analog fuel, temp., and temp. gauges
  - Digital hour meter, direction display, ground speed, and PTO speed

### ELECTRICAL:

- (1) 12-volt, 800 CCA battery
- 120-amp alternator
- 7-pin outlet for implement lighting
- 3-pin connector (TYCO CPC)
- Single pin (8-amp) power outlet
- Detusch diagnostic port

### LIGHTING:

- (2) Halogen front hood headlights
- (2) Front and (2) rear cab work lights
- Turn signals, flashers, and brake lights

### OPERATOR'S STATION:

- Flat deck platform and integral ROPS
- Heater and air conditioner
- "A" pillar exhaust
- (2) tinted doors with locks
- Partially opening tinted side windows
- Hinged tinted rear window
- Rear cab access plug for imp. wires
- Front and rear wipers and washers
- Tilt and telescoping steering wheel
- Fixed external mirrors
- Radio and speakers
- Deluxe air suspension seat with operator's presence and seat belt
- Instructor's seat with seat belt
- HiVis panel (overhead window-opens)

### MISCELLANEOUS:

- One-piece hood with gas strut
- Swinging drawbar
- SMV emblem
- Toolbox
- 6 rear wheel weights

### WARRANTY:

New Holland standard warranty applies

**T5 ELECTRO COMMAND - STANDARD FASTPICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	Weight	Factory Data	List Price
T5.110 ELEC COM T4B	8,157 LB	9087250P02	\$111,859.00
Includes the following Equipment			
14.9R24 A8 HD Rim (8242301)	\$2,361.00		
460/85(18.4)R34 A8 FI,MI,C (8365401)	\$4,189.00		
T5.120 ELEC COM T4B	8,157 LB	9088996P44	\$114,098.00
Includes the following Equipment			
14.9R24 A8 HD Rim (8242301)	\$2,361.00		
460/85(18.4)R34 A8 FI,MI,C (8365401)	\$4,189.00		

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0474XX	NAR NH PCK C STD <b>Standard Fastpick Package includes:</b> 330849 2 Mechanical Rear Remotes 392428 2 Fixed Wide Angle Mirrors 390430 16 x 16 SPS 40 KPH 758820 2 Slice Mech CC MMV 332850 Deluxe Fabric Seat w/Air Suspension 330308 HD MFD Axle w/ Hydraulic Diff Lock 758980 Complete Loader Ready 744982 Engine Block and Transmission Heaters 330471 6 Rear Wheel Weights		(904091P10)	(\$5,245.00)
---------	--	--	-------------	--------------

**PTO**

REAR PTO

SD\_T8010 PTO

331729	540/540E/1000 RPM		9000680P16	\$872.00
--------	-------------------	--	------------	----------



**T5 ELECTRO COMMAND - STANDARD FASTPICK  
US PRICE LIST**

**CAB OR ROPS PLATFORM**

MONITOR MOUNTING

SD\_T7612 BRACKET MONITOR

	338761	Monitor Mounting Bracket		9000118P56	\$152.00
--	--------	--------------------------	--	------------	----------

**ELECTRICAL/CONNECTORS**

BATTERY

SD\_T7420 BATTERY

	334774	Batt. 140 AH W/B.IS. <b>Battery Isolator</b>		9000330P72	\$424.00
--	--------	---	--	------------	----------

**LIGHTS**

ROTARY BEACON

SD\_T9146 ROTARY BEACON

	759160	ROTARY BEACON 759160		9000095P16	\$122.00
	335916	2 Beacons RH and LH Side <b>Left and right side safety beacons</b>		9000187P20	\$240.00

**MANUALS**

OPERATORS

SD\_T9840 COUNTRY CONFIGURATION

	335148	USA Spanish Config <b>Spanish Operator Manual</b>			No Charge
	335151	Canada (FR) Config <b>French Operator Manual</b>			No Charge

**MISCELLANEOUS**

FENDERS FRONT

SD\_T8740 FRONT FENDERS

	758330	Dynamic Front Fenders 480mm <b>18.9 inch (480 mm) dynamic front fenders</b>		9000633P36	\$812.00
--	--------	--	--	------------	----------



**T5 ELECTRO COMMAND - DELUXE FASTPICK  
US PRICE LIST**

## Standard Equipment

KEY SELLING POINTS (some features are optional equipment):

- 16 x 16 Electro Command semi-powershift transmission with Auto Shift feature
- Auto PTO manages PTO engagement in relation to the rear hitch position
- Engine Speed Management (constant engine RPM) - 2 settings
- Terralock™ automatic traction system
- CommandArc™ ergonomics
- 200 degree windshield wiper
- Standard high visibility panel (opening)
- (10) repositionable AC/heater vents
- Full-size instructor seat
- Hydraulic shuttle lever -finger control
- 3.4L, 4-cylinder, F5G engines with 4 valves per cylinder common rail fuel injection systems
- 8,084 lb. 3-point lift capacity
- Tier 4B/final emissions compliant ECOBlue Compact HI-eSCR (Selective Catalytic Reduction) after-treatment with low rate Cooled Exhaust Gas Recirculation (CEGR); no diesel particulate filter, no regeneration req.

**MODELS:**

T5.110

- 107 gross engine HP
- 93 PTO HP @ 2300 rpm
- 4-cyl. turbocharged and intercooled
- 207 cu. in. (3.4 L) displacement
- 4 valves per cylinder

T5.120

- 117 gross engine HP
- 100 PTO HP @ 2300 rpm
- 4-cyl. turbocharged and intercooled
- 207 cu. in. (3.4 L) displacement
- 4 Valves per cylinder

**ENGINE:**

- Tier 4B emissions: Compact HI-eSCR SCR with low rate CEGR
- Electronic injection Bosch high-pressure common rail system
- Engine Speed Management
- Electric engine shutoff
- Grid heater starting Aid
- Engine block heater
- Dual element air filter
- Vertical exhaust
- 43.6 gallon (165 L) fuel tank with guard
- 3.2 gallon (12 L) DEF (diesel exhaust fluid) tank

**TRANSMISSION:**

- 16 x 16 semi-powershift with Auto Shift
- 8 push button powershift speeds
- Control buttons on gear shift lever and on CommandArc™
- Electrohydraulic shuttle
- 25-mph (40-kph) road speed
- 16th gear (32nd w/creeper) is an economy gear that operates the engine at a lower RPM to save fuel
- Multi-disk cerametallic clutch
- Transmission heater

**STEERING/BRAKES:**

- Hydrostatic power steering
- Hydraulic wet brakes (equalizing and self-adjusting)
- Park brake

**FRONT AXLE:**

- Class 1.5 w/Auto 4WD management
- Electrohydraulic FWD and differential lock engagement

**-REAR AXLE:**

- Heavy-duty flange
- Dog clutch differential lock
- Auto differential lock management
- Electrohydraulic rear differential lock





**T5 ELECTRO COMMAND - DELUXE FASTPICK  
US PRICE LIST**

## Standard Equipment

### HYDRAULIC SYSTEM:

- Fixed displacement pumps
- Tandem gear pumps
- Maximum flow at rated engine speed:
  - Implement pump: 21.1 gpm (80 l/m)
  - Steering pump: 11.4 gpm (43 l/m)
- (3) closed center rear remote valves configurable detent w/ quick release couplers
- 2 function mid mount valve with electronic arm-rest mounted joystick
- Complete loader ready

### PTO:

- Fully independent
- Flip-up PTO shaft guard
- 540/1000 rpm interchangeable shaft
- Electrohydraulic engagement
- Multi-plate clutch
- Fender-mounted EDC / PTO switches

### 3-POINT LIFT SYSTEM:

- Right hand console-mounted mouse
- Electronic Draft Control (EDC)
- Fast raise/lower control
- 8,084 lb. lift cap (OECD, 90% psi at 24" rear of lower link balls)
- Category II flexible lower link ends
- Telescopic stabilizers

### INSTRUMENTATION:

- Analog/digital instrument panel with:
  - Integrated warning lights
  - Analog fuel, temp., and temp. gauges
  - Digital hour meter, direction display, ground speed, and PTO speed

### ELECTRICAL:

- (1) 12-volt, 800 CCA battery
- 120-amp alternator
- 7-pin outlet for implement lighting
- 3-pin connector (TYCO CPC)
- Single pin (8-amp) power outlet
- Detusch diagnostic port

### LIGHTING:

- (2) Halogen front hood headlights
- (2) Front and (2) rear cab work lights
- Turn signals, flashers, and brake lights

### OPERATOR'S STATION:

- Flat deck platform and integral ROPS
- Cab suspension
- Heater and air conditioner
- "A" pillar exhaust
- (2) tinted doors with locks
- Partially opening tinted side windows
- Hinged tinted rear window
- Rear cab access plug for imp. wires
- Front and rear wipers and washers
- Tilt and telescoping steering wheel
- Telescopic external mirrors
- Monitor mounting bracket
- Radio and speakers
- Premium air suspension seat with operator's presence and seat belt
- Instructor's seat with seat belt
- HiVis panel (overhead window-opens)

### MISCELLANEOUS:

- One-piece hood with gas strut
- Swinging drawbar
- SMV emblem
- Toolbox
- 6 rear wheel weights

### WARRANTY:

New Holland standard warranty applies

**T5 ELECTRO COMMAND - DELUXE FASTPICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	Weight	Factory Data	List Price
T5.110 ELEC COM T4B	8,157 LB	9087250P02	\$111,859.00
Includes the following Equipment			
14.9R24 A8 HD Rim (8242301)	\$2,361.00		
460/85(18.4)R34 A8 FI,MI,C (8365401)	\$4,189.00		
T5.120 ELEC COM T4B	8,157 LB	9088996P44	\$114,098.00
Includes the following Equipment			
14.9R24 A8 HD Rim (8242301)	\$2,361.00		
460/85(18.4)R34 A8 FI,MI,C (8365401)	\$4,189.00		

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0473XX	NAR NH PCK B DELUXE <b>Deluxe Fastpick Package Includes:</b> 331844 3 Mechanical Rear Remotes 341852 2 External Telescopic Wide Angle Mirrors 330471 6 Rear Wheel Weights 744982 Engine Block and Transmission Heaters 334775 40 KPH W/Autofunction 330308 HD MFD Axle w/ Hydraulic Diff Lock 338761 Monitor Mounting Bracket 758980 Complete Loader Ready 758821 2 MMV CC w/EH Joystick 758312 Premium Air Seat		(904091P10)	(\$5,245.00)
---------	---	--	-------------	--------------

**PTO**

REAR PTO

SD\_T8010 PTO

331729	540/540E/1000 RPM		9000680P16	\$872.00
--------	-------------------	--	------------	----------

**T5 ELECTRO COMMAND - DELUXE FASTPICK  
 US PRICE LIST**

**ELECTRICAL/CONNECTORS**

BATTERY

SD\_T7420 BATTERY

	334774	Batt. 140 AH W/B.IS. <b>Battery Isolator</b>		9000330P72	\$424.00
--	--------	---	--	------------	----------

**LIGHTS**

ROTARY BEACON

SD\_T9146 ROTARY BEACON

	759160	ROTARY BEACON 759160		9000095P16	\$122.00
	335916	2 Beacons RH and LH Side <b>Left and right side safety beacons</b>		9000187P20	\$240.00

**MANUALS**

OPERATORS

SD\_T9840 COUNTRY CONFIGURATION

	335148	USA Spanish Config <b>Spanish Operator Manual</b>			No Charge
	335151	Canada (FR) Config <b>French Operator Manual</b>			No Charge

**MISCELLANEOUS**

FENDERS FRONT

SD\_T8740 FRONT FENDERS

	758330	Dynamic Front Fenders 480mm <b>18.9 inch (480 mm) dynamic front fenders</b>		9000633P36	\$812.00
--	--------	--	--	------------	----------



**T5 ELECTRO COMMAND - LESS FASTPICK  
US PRICE LIST**

## Standard Equipment

KEY SELLING POINTS (some features are optional equipment):

- 16 x 16 Electro Command semi-powershift transmission now with optional Auto Shift feature
- Comfort Ride™ cab suspension for a smoother ride - Optional
- Auto PTO manages PTO engagement in relation to the rear hitch position
- Engine Speed Management (constant engine RPM) - 2 settings
- Terralock™ automatic traction system
- Terraglide™ opt. front axle suspension
- Opt TerraGlide™ class 1.5 HD front axle
- CommandArc™ ergonomics
- Optional LED work lights
- 200 degree windshield wiper
- Standard high visibility panel (opening)
- (10) repositionable AC/heater vents
- Full-size instructor seat
- Electrohydraulic armrest-mntd joystick
- Hydraulic shuttle lever -finger control
- 8,084 lb. 3-point lift capacity
- Tier 4B/final emissions compliant ECOBlue Compact HI-eSCR (Selective Catalytic Reduction) after-treatment with low rate Cooled Exhaust Gas Recirculation (CEGR); no diesel particulate filter, no regeneration req.

**MODELS:**

T5.110

- 107 gross engine HP
- 93 PTO HP @ 2300 rpm
- 4-cyl. turbocharged and intercooled
- 207 cu. in. (3.4 L) displacement
- 4 valves per cylinder

T5.120

- 117 gross engine HP
- 100 PTO HP @ 2300 rpm
- 4-cyl. turbocharged and intercooled
- 207 cu. in. (3.4 L) displacement
- 4 Valves per cylinder

KEY COMMON FEATURES & OPTIONS:

- 16X16 Electro Command transmission with optional Auto Shift feature
- Optional Suspended cab w/HiVis panel
- Heavy-duty class 1.5 front axle with optional hydraulic differential lock
- Opt. premium air suspension seat with armrests, backrest, and heated cushion
- Full-size, deluxe radio with Bluetooth™
- Telescopic rearview mirror option
- (3) closed center rear remotes option
- Electrohydraulic mid-mount valve and armrest-mounted elec. joystick option
- Auto PTO option
- Engine block heater option

**ENGINE:**

- Tier 4B emissions: Compact HI-eSCR SCR with low rate CEGR
- Electronic injection Bosch high-pressure common rail system
- Engine Speed Management
- Electric engine shutoff
- Grid heater starting Aid
- Dual element air filter
- Vertical exhaust
- 43.6 gallon (165 L) fuel tank with guard
- 3.2 gallon (12 L) DEF (diesel exhaust fluid) tank

**TRANSMISSION:**

- 16 x 16 semi-powershift
- 8 push button powershift speeds
- Control buttons on gear shift lever and on CommandArc™
- Electrohydraulic shuttle
- 25-mph (40-kph) road speed
- 16th gear (32nd w/creeper) is an economy gear that operates the engine at a lower RPM to save fuel
- Multi-disk cerametallic clutch



**T5 ELECTRO COMMAND - LESS FASTPICK  
US PRICE LIST**

## Standard Equipment

### STEERING/BRAKES:

- Hydrostatic power steering
- Hydraulic wet brakes (equalizing and self-adjusting)
- Park brake

### FRONT AXLE:

- Class 1.5 w/Auto 4WD management
- Limited slip differential
- Opt. electrohydraulic FWD engagement
- Opt. suspended front axle

### -REAR AXLE:

- Heavy-duty flange
- Dog clutch differential lock
- Auto differential lock management
- Electrohydraulic rear differential lock

### HYDRAULIC SYSTEM:

- Fixed displacement pumps
- Tandem gear pumps
- Maximum flow at rated engine speed:
  - Implement pump: 21.1 gpm (80 l/m)
  - Steering pump: 11.4 gpm (43 l/m)
- (2) closed center rear remote valves configurable detent w/ quick release couplers

### PTO:

- Fully independent
- Flip-up PTO shaft guard
- 540/1000 rpm interchangeable shaft
- Electrohydraulic engagement
- Multi-plate clutch
- Fender-mounted EDC / PTO switches

### 3-POINT LIFT SYSTEM:

- Right hand console-mounted mouse
- Electronic Draft Control (EDC)
- Fast raise/lower control
- 8,084 lb. lift cap (OECD, 90% psi at 24" rear of lower link balls)
- Category II flexible lower link ends
- Telescopic stabilizers

### INSTRUMENTATION:

- Analog/digital instrument panel with:
  - Integrated warning lights
  - Analog fuel, temp., and temp. gauges
  - Digital hour meter, direction display, ground speed, and PTO speed

### ELECTRICAL:

- (1) 12-volt, 800 CCA battery
- 120-amp alternator
- 7-pin outlet for implement lighting
- 3-pin connector (TYCO CPC)
- Single pin (8-amp) power outlet
- Detusch diagnostic port

### LIGHTING:

- (2) Halogen front hood headlights
- (2) Front and (2) rear cab work lights
- Turn signals, flashers, and brake lights

### OPERATOR'S STATION:

- Flat deck platform and integral ROPS
- Heater and air conditioner
- "A" pillar exhaust
- (2) tinted doors with locks
- Partially opening tinted side windows
- Hinged tinted rear window
- Rear cab access plug for imp. wires
- Front and rear wipers and washers
- Tilt and telescoping steering wheel
- Fixed external mirrors
- Radio and speakers
- Deluxe air suspension seat with operator's presence and seat belt
- Instructor's seat with seat belt
- HiVis panel (overhead window-opens)

### MISCELLANEOUS:

- One-piece hood with gas strut
- Swinging drawbar
- SMV emblem
- Toolbox

### WARRANTY:

New Holland standard warranty applies

**T5 ELECTRO COMMAND - LESS FASTPICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	Weight	Factory Data	List Price
T5.110 ELEC COM T4B	8,157 LB	9087250P02	\$111,859.00
Includes the following Equipment			
14.9R24 A8 HD Rim (8242301)	\$2,361.00		
460/85(18.4)R34 A8 FI,MI,C (8365401)	\$4,189.00		
T5.120 ELEC COM T4B	8,157 LB	9088996P44	\$114,098.00
Includes the following Equipment			
14.9R24 A8 HD Rim (8242301)	\$2,361.00		
460/85(18.4)R34 A8 FI,MI,C (8365401)	\$4,189.00		

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0475XX	LESS PACKAGING			No Charge
---------	----------------	--	--	-----------

**OPERATOR PLATFORM**

SD\_T9200 OPERATOR STRUCTURE #1

336730	Susp HiVis A/C <b>Cab Suspension</b>		9001227P72	\$1,574.00
--------	---	--	------------	------------

**POWER TRAIN**

**TRANSMISSION**

SD\_T2810 TRANSMISSION

390430	16x16 SPS 40KPH			No Charge
334775	40KPH W/Autofunction <b>Auto Shift</b>		9000619P32	\$794.00
334114	16x16 40KPH W/Creep <b>Creeper</b>		9000674P70	\$865.00
334779	40KPH W/AutoF+Creep <b>Auto Shift + Creeper</b>		9001293P24	\$1,658.00

**T5 ELECTRO COMMAND - LESS FASTPICK  
US PRICE LIST**

AXLES

SD\_T4010 FRONT AXLE

	337707	Suspended Front Axle Less Brks		9003560P70	\$4,565.00
--	--------	--------------------------------	--	------------	------------

TIRES

BRAND CHOICE

SD\_T4900 TIRE CATEGORY CHOICE

	330438	No tire brand preference			No Charge
	330447	Alliance		9000378P30	\$485.00
	330439	Mitas		9000378P30	\$485.00
	330418	Trelleborg		9000378P30	\$485.00
	330442	Michelin		9000943P80	\$1,210.00

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

Ag Front Tires					
	8235401	12.4R24 A8 <b>R1W, Adjustable Rim, Match w/ 8357401 rear tire/wheel</b>		9001223P82	\$1,569.00
	8242301	14.9R24 A8 HD Rim <b>R1W, adjustable rim Match with 8365401 rear tire/wheel</b>		9001841P58	\$2,361.00
	8201801	9.5R28 <b>R1W, Adjustable Rim, Match w/ 8369501 rear tire/wheel</b>		9001506P96	\$1,932.00

REAR

SD\_T4950 REAR WHEELS AND TIRES

Ag Rear Tires					
	8357401	18.4R30 R1W <b>Matching front tire/whl is 8235401, 12.4R24 (320/85R24) R1W, adjustable rim Not compatible with narrow rear fenders option code: 331870</b>		9002966P34	\$3,803.00
	8365401	460/85(18.4)R34 A8 FI,MI,CO,TR <b>Matching front tire/whl is 8242301, 14.9R24 (380/85R24) R1W, adjustable rim Not compatible with narrow rear fenders option code: 331870</b>		9003267P42	\$4,189.00



**T5 ELECTRO COMMAND - LESS FASTPICK  
 US PRICE LIST**

Specialty Rear Tires						
		8369501	12.4R38 ) W11 x 38 <b>Matching front tire/wheel is 9.5R28</b> <b>Not compatible with front fender options</b> <b>758329 and 758330</b> <b>Row Crop with adjustable rim</b> <b>Required when selecting narrow rear fender</b> <b>option 331870</b>		9001746P42	\$2,239.00

**HYDRAULICS**

REAR REMOTES

SD_T8270 REAR REMOTES						
		330849	2 MRRV (2C) Fixed Pump,EDC <b>2 closed center mechanical hydraulic remote valves both with configurable detent</b>			No Charge
		331844	3 MRRV (1NC+2C)Fixed Pump,EDC <b>3 mechanical rear hydraulic remote valves,</b> <b>2 with configurable detents and 1 with non-configurable detent</b>		9001275P30	\$1,635.00

MID-MOUNT

SD_T8280 MID-MOUNT VALVES						
		758820	2 Slice Mech CC MMV <b>2 function mid mount valve with mechanical joystick</b>		9001227P72	\$1,574.00
		758821	2 MMV CC w/EH Joystk <b>2 function mid mount valve with armrest mounted electronic joystick</b>		9001698P84	\$2,178.00

**LOADER**

LOADER BRACKETS

SD_T8110 LOADER BRACKETS						
		758980	Loader Ready. <b>Complete loader ready</b> <b>Includes:</b> <b>- Complete TPS mounting brackets</b> <b>- Hose kit from mid mount valve to vertical brackets</b> <b>- Multi-coupler base</b>  <b>Requires a mid mount valve selection</b>		9003908P58	\$5,011.00



**T5 ELECTRO COMMAND - LESS FASTPICK  
US PRICE LIST**

**ENGINE**

AIR INTAKE

SD\_T1910 AIR CLEANER

	330200	Air Filter w/Dust Ejector <b>Engine air cleaner with dust ejector</b>		9000102P96	\$132.00
--	--------	--	--	------------	----------

SD\_T1931 COLD WEATHER STARTI

	744982	Block Heater_120V		9000137P28	\$176.00
--	--------	-------------------	--	------------	----------

**PTO**

REAR PTO

SD\_T8010 PTO

	331729	540/540E/1000 RPM		9000680P16	\$872.00
--	--------	-------------------	--	------------	----------

**CAB OR ROPS PLATFORM**

MONITOR MOUNTING

SD\_T7612 BRACKET MONITOR

	338761	Monitor Mounting Bracket		9000118P56	\$152.00
--	--------	--------------------------	--	------------	----------

OTHER

SD\_T9360 RR MIRRORS

	341852	2 External Wide Angle Mirrors <b>2 Telescopic Rear Wide Angle Mirrors With Mechanical Adjustment</b>		9000341P64	\$438.00
--	--------	---	--	------------	----------

**ELECTRICAL/CONNECTORS**

BATTERY

SD\_T7420 BATTERY

	334774	Batt. 140 AH W/B.IS. <b>Battery Isolator</b>		9000330P72	\$424.00
--	--------	---	--	------------	----------

**LIGHTS**

ROTARY BEACON

SD\_T9146 ROTARY BEACON

	759160	ROTARY BEACON 759160		9000095P16	\$122.00
--	--------	----------------------	--	------------	----------

**T5 ELECTRO COMMAND - LESS FASTPICK  
 US PRICE LIST**

	335916	2 Beacons RH and LH Side <b>Left and right side safety beacons</b>		9000187P20	\$240.00
--	--------	---	--	------------	----------

**WEIGHTS**

FRONT

SD\_T2150 FRONT BALLAST

	331759	10 Weights <b>Qty. 10, 88 lb. (40 Kg) weights totaling 882 lb. (400 Kg) Requires a front axle support with weight carrier (335156 or 758385)</b>		9000991P38	\$1,271.00
--	--------	---	--	------------	------------

SD\_T8100 FRONT THREE POINT HITCH

	335156	L/FHPL L/FPTO-STD <b>Standard front axle support with weight carrier. Not compatible with suspended front axle.</b>		9000305P76	\$392.00
	758385	L/FHPL L/FPTO-MULTI <b>Suspended axle front axle support with weight carrier Not compatible with non suspended front axle.</b>			No Charge

REAR

SD\_T4961 REAR BALLAST

	330471	6 Rear Wheel Weights <b>6, 110 lb. (50 kg.) rear disc weights totaling 661 lb. (300Kg)</b>		9000831P48	\$1,066.00
--	--------	---	--	------------	------------

**MISCELLANEOUS**

FENDERS FRONT

SD\_T8740 FRONT FENDERS

	758330	Dynamic Front Fenders 480mm <b>18.9 inch (480 mm) dynamic front fenders</b>		9000633P36	\$812.00
--	--------	--	--	------------	----------

REVERSE ALARM

SD\_T9249 REVERSE ALARM

	332692	Reverse Alarm w/Work Light		9000209P04	\$268.00
--	--------	----------------------------	--	------------	----------



**T5 DYNAMIC COMMAND - STANDARD FAST PICK  
US PRICE LIST**

**Standard Equipment**

KEY SELLING POINTS:

- Fuel efficient high torque 4.5L, 4-cylinder
- FPT engines with 4 valves per cylinder and common rail fuel injection systems
- Tier 4B EPA emissions compliant with SCR only ECOBlue™ HI-eSCR Tier4B emissions system
- Underhood compact aftertreatment
- 24X24 Dynamic Command™ 8-Step Semi-Powershift transmission
- Best in class cab in terms of space and comfort (same cab as the T6 and T7 Series)
- Standard LED work lighting
- High level of Automating features (E-Hydr 4WD, PTO, e-controlled remotes)
- Closed Center Load Sensing "high efficiency" pumps, up to 108 l/m
- Easy attach remote outlets
- New bold styling (hood, cab roof, lighting)
- Long Stable 98" wheel base for all Models
- Gross Vehicle Weight up to 18,700 lbs.

MODELS

-----  
T5.130 Dynamic Command  
Rated PTO HP - 102  
Rated Engine HP - 120  
Maximum Engine HP - 130  
Rated Speed - 2200 RPM  
274 cu. in. (4.5L) - 4 Cylinder  
Fuel Tank: 47 Gallon (180L)  
DEF Tank: 5 Gallon (19L)

T5.140 Dynamic Command  
Rated PTO HP - 111  
ENGINE Rated Engine HP - 130  
Maximum Engine HP - 140  
Rated Speed - 2200 RPM  
274 cu. in. (4.5L) - 4 Cylinder  
Fuel Tank: 47 Gallon (180L)  
DEF Tank: 5 Gallon (19L)

ENGINE

- Tier 4B Emissions Compliant  
ECOBlue™ HI-eSCR Tier4B system  
Engine with Turbocharger and  
Air-to-Air Intercooler  
4 Valves Per Cylinder  
Bosch Common Rail Fuel Injection  
Pump (electronic)  
Grid Heater Starting Aid  
Cold weather pack block and  
transmission heater  
Dual Element Air Filter with Pre-Cleaner  
(spin tube intakes)  
A-Pillar Exhaust with Integral Muffler  
Viscous Fan (5 blade)  
Hand Throttle

TRANSMISSION

- 24x24 Dynamic Command Semi Powershift Transmission
- Clutchless Range Change between Ranges A/B, B/C.
- 25-MPH (40-KPH) (varies by tire size)

CAB

- -High Roof w/ Opening Visibility Panel and Sunshade  
-Cab suspension  
- Flat Deck Platform with Integrated ROPS  
- Standard Air Conditioner and Heater with 4-Speed Pressurizer and dual zone air conditioning  
- Two doors with Locks  
- Two-speed Intermittent Front  
- Wiper/Washer  
- Rear Intermittent Wiper/Washer  
- Hinged Rear Window  
- Tinted Glass with Sunshade  
- Tilt and Telescoping Steering Wheel  
- IntelliView™ IV disp. mtd. on arm rest  
- Deluxe Air Suspension Seat with Automatic Adjustment, Operator



**T5 DYNAMIC COMMAND - STANDARD FAST PICK  
 US PRICE LIST**

## Standard Equipment

Presence Switch and Lap Belt

- Instructor Seat
- Deluxe radio
- Digital clock
- Integral ROPS
- Interior dome light
- (2) External courtesy lights
- (2) External telescopic remote
- Adjustable mirrors
- Horn
- Std steering wheel & floor mat
- ISOBUS II connector

STEERING & BRAKES

- 
- Hydrostatic power steering
  - Hydraulic wet disc brakes (self-equalizing/self-adjusting)
  - Parking brake (automotive style)

FRONT AXLE

- 
- Front FWD (TerraLock™ )
  - Class 1.75 heavy-duty FWD axle
  - 55-degree turning angle
  - Dual steering cylinders
  - 11-degree axle oscillation
  - Electrohydraulic FWD engagement
  - TerraLock™ Auto FWD/Diff-Lock
  - Driveshaft shield

REAR AXLE

- 
- Heavy-duty flange axle
  - Wet plate differential lock
  - Electrohydraulic-engaged dif. lock

ELECTRICAL

- 
- (1) 12-volt 1300 CCA battery
  - 120-amp alternator
  - Geared starter motor (4.2 kW)
  - 7-pin outlet for implement lighting
  - 3-pin 40-amp implement socket
  - ISO/JD (30 amp) socket

- 15 amp screw-type +/- terminals
- Single pin (8 amp) accessory outlet
- Cigarette lighter
- (2) single-pin outlets for beacon on roof
- Battery boost terminals
- ISOBUS Class 2

LIGHTS

- 
- (4) Halogen front hood headlights
  - (2) LED front hood signature lights
  - (8) LED cab mounted work lights
    - (4) LED high front & rear
    - (4) LED mid-mount front & rear
  - (2) taillights
  - Front & Rear Flashing Cab Safety Lights
  - Time Delayed, Self-Cancelling Turn Indicators with Audiable Warning Rotary beacon

PTO

- 
- Independent 540/540E/1000 RPM PTO with reversible shaft and flip-up shield
  - Multi-plate wet clutch design
  - Electrohydraulic-engagement with soft start/auto feathering
  - Hydraulic piston PTO brake w/override

HYDRAULIC SYSTEM

- 
- Closed-center load-sensing pump
  - Flow at 1,900 RPM: 28.5 gpm (108 l/m)
  - (2) electro-hydraulic rear remote valves controlled in SideWinder II™ console (fully programmable)
  - Oil collection bottles
  - Hydraulic tapping port (Power Beyond)
  - Independent pump for CVT and operating circuits
  - 3 function electronic mid mount valve and joystick



**T5 DYNAMIC COMMAND - STANDARD FAST PICK  
US PRICE LIST**

### Standard Equipment

3-POINT LIFT SYSTEM

- 
- Electronic Draft Control (EDC)
- Lower link sensing
- Fast raise/lower control
- Dynamic Ride Control™
- Category II flex link ends
- Telescopic stabilizers
- 10228 lb. Lift Capacity with Dual 80mm
- External Rams

MISCELLANEOUS

- 
- Complete loader ready: vertical and horizontal brackets and hoses from valve to vertical bracket
- Rear wheel weights
- Flip-up engine hood
- Swinging drawbar
- SMV emblem
- Toolbox

WARRANTY

-----  
New Holland standard warranty applies

**T5 DYNAMIC COMMAND - STANDARD FAST PICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	Weight	Factory Data	List Price
T5.130 DCT	19,401 LB	9098531P94	\$126,323.00
T5.140 DCT	19,401 LB	9101514P66	\$130,147.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0474XX	NAR NH PCK C STD <b>Standard Fast Pick Package Includes:</b> 759768: BASE COLOUR HI ROOF 758479: Suspended_Cab 758402: Grid_Heater + 110V Pack 759137: 2X150KG + 2X250KG Wheel Weight 759166: BASIC AUTO FEATURE 759155: BASIC ARMST MTD DOG 759777: ROTARY BEACON 759777 758357: 8 LED High Power Hi-Roof  Requires selection of the following: Loader Ready + 2 MMV + 2 function Joystick or Loader Ready + 3 MMV + 3 function Joystick		(900482P04)	(\$618.00)
---------	---	--	-------------	------------

**TIRES**

**BRAND CHOICE**

SD\_T4900 TIRE CATEGORY CHOICE

330418	Trelleborg		9000477P36	\$612.00
330438	No tire brand preference			No Charge
330447	Alliance		9000477P36	\$612.00
330439	Mitas		9000477P36	\$612.00
330446	Firestone		9000477P36	\$612.00
330442	Michelin		9000477P36	\$612.00
330444	Nokian		9000477P36	\$612.00

**T5 DYNAMIC COMMAND - STANDARD FAST PICK  
 US PRICE LIST**

**FRONT WHEELS & TIRES**

**SD\_T4940 FRONT WHEELS AND TIRES**

Ag Front Tires					
	8235401	12.4R24 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match w/ 8357401 rear tire/wheel</b>		9001223P82	\$1,569.00
	8242301	14.9R24 A8 HD Rim <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match with 8365401 rear tire/wheel</b>			No Charge
	8299801	Non-Return Ship Wheels - 4WD		9000081P12	\$104.00
	8880401	360/80R24 GRSLND, Adj. Rim		9001666P08	\$2,136.00
	8247401	11.2R28 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Matches with 8372401 Rear tires 13.6R38 (340/85R38) MAVT</b>		9001265P94	\$1,623.00

**REAR WHEELS & TIRES**

**SD\_T4950 REAR WHEELS AND TIRES**

	8357401	18.4R30 R1W		9002966P34	\$3,803.00
	8365401	460/85(18.4)R34 A8 FI,MI,CO,TR			No Charge
	8372401	13.6R38 A8		9001992P90	\$2,555.00
	8399801	Non-Returnable Shipping Wheel		9000494P52	\$634.00
	8916401	440/80R34 GRSLND, Adj. Rim		9002774P46	\$3,557.00

**HYDRAULICS**

**COMPLETE LOADER READY**

**SD\_T8110 LOADER BRACKETS**

	759470	NA LDR RDY+2MMV+ADV <b>Complete Loader Ready - 2 Function Enhanced</b> <b>TPS Mount Bracket Set (with Grill Guard),</b> <b>2 Function MMV, and Enhanced Joystick</b> <b>(Includes valve, joystick, hose kit, &amp; MC 4)</b>		9003830P58	\$4,911.00
	759471	NA LDR RDY+3MMV+ADV <b>Complete Loader Ready - 3 Function Enhanced</b> <b>TPS Mount Bracket Set (with Grill Guard),</b> <b>3 Function MMV, and Enhanced Joystick</b> <b>(Includes valve, joystick, hose kit, &amp; MC 4+2)</b>		9004045P08	\$5,186.00

**T5 DYNAMIC COMMAND - STANDARD FAST PICK  
 US PRICE LIST**

**CAB OPTION**

SD\_T9360 RR MIRRORS

	759154	2 Tele/Heat/Rem Adj Mirror		9000055P38	\$71.00
--	--------	----------------------------	--	------------	---------

**SEATS**

SD\_T8500 SEAT

	758670	Deluxe Air and Belt		9000639P60	\$820.00
	758486	MAXIMO EVO <b>Semi Active Suspension, Heated, Vented, Belt,                  Alacantara/Leather, Up/Down Headrest                  (Maximo Evo)</b>		9003265P86	\$4,187.00

**MONITOR BRACKETS**

SD\_T9223 RH WINDOW BAR MOUNT

	758153	Monitor Mounting Bracket.		9000127P92	\$164.00
	758154	RH Window Bar Display Ready.		9000209P04	\$268.00
	758621	10" Color Touch Screen Display		9004964P70	\$6,365.00

**ISO BUS CONNECTOR**

SD\_T7642 ISO BUS

	758632	ISO CL2+9PIN IN CAB <b>ISOBUS CL 3 BASIC + IN CAB 9 PIN PLUG + SPEED CONTROL</b>			No Charge
--	--------	---	--	--	-----------

**MISCELLANEOUS**

**FENDERS FRONT**

SD\_T8740 FRONT FENDERS

	758330	Dynamic Front Fenders 480mm		9000631P02	\$809.00
--	--------	-----------------------------	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	758535	Spanish NAR			No Charge
	759101	French NAR			No Charge





**T5 DYNAMIC COMMAND - PREMIUM FAST PICK  
US PRICE LIST**

**Standard Equipment**

KEY SELLING POINTS:

- Fuel efficient high torque 4.5L, 4-cylinder
- FPT engines with 4 valves per cylinder and common rail fuel injection systems
- Tier 4B EPA emissions compliant with SCR only ECOBlue™ HI-eSCR Tier4B emissions system
- Underhood compact aftertreatment
- 24X24 Dynamic Command™ 8-Step Semi-Powershift transmission
- Best in class cab in terms of space and comfort (same cab as the T6 and T7 Series)
- Standard LED work lighting
- High level of Automating features (E-Hydr 4WD, PTO, e-controlled remotes)
- Closed Center Load Sensing "high efficiency" pumps, up to 108 l/m
- Easy attach remote outlets
- New bold styling (hood, cab roof, lighting)
- Long Stable 98" wheel base for all Models
- Gross Vehicle Weight up to 18,700 lbs.

MODELS

-----  
T5.130 Dynamic Command  
Rated PTO HP - 102  
Rated Engine HP - 120  
Maximum Engine HP - 130  
Rated Speed - 2200 RPM  
274 cu. in. (4.5L) - 4 Cylinder  
Fuel Tank: 47 Gallon (180L)  
DEF Tank: 5 Gallon (19L)

T5.140 Dynamic Command  
Rated PTO HP - 111  
ENGINE Rated Engine HP - 130  
Maximum Engine HP - 140  
Rated Speed - 2200 RPM  
274 cu. in. (4.5L) - 4 Cylinder  
Fuel Tank: 47 Gallon (180L)  
DEF Tank: 5 Gallon (19L)

ENGINE

- Tier 4B Emissions Compliant  
ECOBlue™ HI-eSCR Tier4B system  
Engine with Turbocharger and  
Air-to-Air Intercooler  
4 Valves Per Cylinder  
Bosch Common Rail Fuel Injection  
Pump (electronic)  
Grid Heater Starting Aid  
Cold weather pack block and  
transmission heater  
Dual Element Air Filter with Pre-Cleaner  
(spin tube intakes)  
A-Pillar Exhaust with Integral Muffler  
Viscous Fan (5 blade)  
Hand Throttle

TRANSMISSION

- 24x24 Dynamic Command Semi Powershift Transmission
- Clutchless Range Change between Ranges A/B, B/C.
- 25-MPH (40-KPH) (varies by tire size)

CAB

- -Low Roof w/ Opening Visibility Panel and Sunshade  
-Cab suspension  
- Flat Deck Platform with Integrated ROPS  
- Standard Air Conditioner and Heater with 4-Speed Pressurizer and dual zone air conditioning  
- Two doors with Locks  
- Two-speed Intermittent Front  
- Wiper/Washer  
- Rear Intermittent Wiper/Washer  
- Hinged Rear Window  
- Tinted Glass with Sunshade  
- Tilt and Telescoping Steering Wheel  
- IntelliView™ IV disp. mtd. on arm rest  
- Deluxe Air Suspension Seat with Automatic Adjustment, Operator



**T5 DYNAMIC COMMAND - PREMIUM FAST PICK  
 US PRICE LIST**

## Standard Equipment

Presence Switch and Lap Belt

- Instructor Seat
- Deluxe radio
- Digital clock
- Integral ROPS
- Interior dome light
- (2) External courtesy lights
- (2) External telescopic remote
- Adjustable mirrors
- Horn
- Std steering wheel & floor mat
- ISOBUS II connector

STEERING & BRAKES

- 
- Hydrostatic power steering
  - Hydraulic wet disc brakes (self-equalizing/self-adjusting)
  - Parking brake (automotive style)

FRONT AXLE

- 
- Front FWD (TerraLock™ )
  - Class 1.75 heavy-duty FWD axle
  - 55-degree turning angle
  - Dual steering cylinders
  - 11-degree axle oscillation
  - Electrohydraulic FWD engagement
  - TerraLock™ Auto FWD/Diff-Lock
  - Driveshaft shield

REAR AXLE

- 
- Heavy-duty flange axle
  - Wet plate differential lock
  - Electrohydraulic-engaged dif. lock

ELECTRICAL

- 
- (1) 12-volt 1300 CCA battery
  - 120-amp alternator
  - Geared starter motor (4.2 kW)
  - 7-pin outlet for implement lighting
  - 3-pin 40-amp implement socket
  - ISO/JD (30 amp) socket

- 15 amp screw-type +/- terminals
- Single pin (8 amp) accessory outlet
- Cigarette lighter
- (2) single-pin outlets for beacon on roof
- Battery boost terminals
- ISOBUS Class 2

LIGHTS

- 
- (4) Halogen front hood headlights
  - (2) LED front hood signature lights
  - (8) LED cab mounted work lights
    - (4) LED high front & rear
    - (4) LED mid-mount front & rear
  - (2) taillights
  - Front & Rear Flashing Cab Safety Lights
  - Time Delayed, Self-Cancelling Turn Indicators with Audiable Warning Rotary beacon

PTO

- 
- Independent 540/540E/1000 RPM PTO with reversible shaft and flip-up shield
  - Multi-plate wet clutch design
  - Electrohydraulic-engagement with soft start/auto feathering
  - Hydraulic piston PTO brake w/override

HYDRAULIC SYSTEM

- 
- Closed-center load-sensing pump
  - Flow at 1,900 RPM: 28.5 gpm (108 l/m)
  - (2) electro-hydraulic rear remote valves controlled in SideWinder II™ console (fully programmable)
  - Oil collection bottles
  - Hydraulic tapping port (Power Beyond)
  - Independent pump for CVT and operating circuits
  - 3 function electronic mid mount valve and joystick



**T5 DYNAMIC COMMAND - PREMIUM FAST PICK  
US PRICE LIST**

**Standard Equipment**

3-POINT LIFT SYSTEM

-----

Electronic Draft Control (EDC)

Lower link sensing

Fast raise/lower control

Dynamic Ride Control™

Category II flex link ends

Telescopic stabilizers

10228 lb. Lift Capacity with Dual 80mm

External Rams

Complete loader ready: vertical and  
horizontal brackets and hoses from  
valve to vertical bracket

Rear wheel weights

Flip-up engine hood

Swinging drawbar

SMV emblem

Toolbox

WARRANTY

-----

New Holland standard warranty applies

MISCELLANEOUS

-----

**T5 DYNAMIC COMMAND - PREMIUM FAST PICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	Weight	Factory Data	List Price
T5.130 DCT	19,401 LB	9098531P94	\$126,323.00
T5.140 DCT	19,401 LB	9101514P66	\$130,147.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0472XX	NAR NH PCK A PREMIUM <b>Premium Fast Pick Package Includes:</b> 762040: LOW ROOF HIVIS PAN 758479: Suspended_Cab 758402: Grid_Heater + 110V Pack 759666: 1.75 W/EH DIFF LOCK 759137: 2X150KG + 2X250KG Wheel Weight 758631: ADV TRANS AUTO FEAT 759756: LARGE T.S. DISPLAY 759777: ROTARY BEACON 759777 758482: Air Conditioning W/ATC  Requires selection of the following: Loader Ready + 2 MMV + 2 function Joystick or Loader Ready + 3 MMV + 3 function Joystick		(900482P04)	(\$618.00)
---------	--	--	-------------	------------

**TIRES**

**BRAND CHOICE**

SD\_T4900 TIRE CATEGORY CHOICE

330418	Trelleborg		9000477P36	\$612.00
330438	No tire brand preference			No Charge
330447	Alliance		9000477P36	\$612.00
330439	Mitas		9000477P36	\$612.00
330446	Firestone		9000477P36	\$612.00

**T5 DYNAMIC COMMAND - PREMIUM FAST PICK  
 US PRICE LIST**

	330442	Michelin		9000477P36	\$612.00
	330444	Nokian		9000477P36	\$612.00

**FRONT WHEELS & TIRES**

SD\_T4940 FRONT WHEELS AND TIRES

	8235401	12.4R24 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match w/ 8357401 rear tire/wheel</b>		9001223P82	\$1,569.00
	8242301	14.9R24 A8 HD Rim <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match with 8365401 rear tire/wheel</b>			No Charge
	8299801	Non-Return Ship Wheels - 4WD		9000081P12	\$104.00
	8880401	360/80R24 GRSLND, Adj. Rim		9001666P08	\$2,136.00
	8247401	11.2R28 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b>  <b>Matches with 8372401 Rear tires 13.6R38 (340/85R38) MAVT</b>		9001265P94	\$1,623.00

**REAR WHEELS & TIRES**

SD\_T4950 REAR WHEELS AND TIRES

	8365401	460/85(18.4)R34 A8 FI,MI,CO,TR			No Charge
	8372401	13.6R38 A8		9001992P90	\$2,555.00
	8399801	Non-Returnable Shipping Wheel		9000494P52	\$634.00
	8916401	440/80R34 GRSLND, Adj. Rim		9002774P46	\$3,557.00

**HYDRAULICS**

**COMPLETE LOADER READY**

SD\_T8110 LOADER BRACKETS

	759470	NA LDR RDY+2MMV+ADV <b>Complete Loader Ready - 2 Function Enhanced</b> <b>TPS Mount Bracket Set (with Grill Guard),</b> <b>2 Function MMV, and Enhanced Joystick</b> <b>(Includes valve, joystick, hose kit, &amp; MC 4)</b>		9003830P58	\$4,911.00
	759471	NA LDR RDY+3MMV+ADV <b>Complete Loader Ready - 3 Function Enhanced</b> <b>TPS Mount Bracket Set (with Grill Guard),</b> <b>3 Function MMV, and Enhanced Joystick</b> <b>(Includes valve, joystick, hose kit, &amp; MC 4+2)</b>		9004045P08	\$5,186.00



**T5 DYNAMIC COMMAND - PREMIUM FAST PICK  
US PRICE LIST**

**CAB OPTION**

SD\_T9360 RR MIRRORS

	759154	2 Tele/Heat/Rem Adj Mirror		9000055P38	\$71.00
--	--------	----------------------------	--	------------	---------

LIGHTS

SD\_T9130 WORK LAMPS

	762051	12 LED W/LGTS HI PWR		9001333P80	\$1,710.00
--	--------	----------------------	--	------------	------------

MONITOR BRACKETS

SD\_T9223 RH WINDOW BAR MOUNT

	758153	Monitor Mounting Bracket.		9000127P92	\$164.00
	758154	RH Window Bar Display Ready.		9000209P04	\$268.00
	758621	10" Color Touch Screen Display		9004964P70	\$6,365.00

ISO BUS CONNECTOR

SD\_T7642 ISO BUS

	758632	ISO CL2+9PIN IN CAB <b>ISOBUS CL 3 BASIC + IN CAB 9 PIN PLUG + SPEED CONTROL</b>			No Charge
--	--------	---	--	--	-----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	758535	Spanish NAR			No Charge
	759101	French NAR			No Charge



**T5 DYNAMIC COMMAND - LESS FAST PICK  
US PRICE LIST**

**Standard Equipment**

KEY SELLING POINTS:

- Fuel efficient high torque 4.5L, 4-cylinder
- FPT engines with 4 valves per cylinder and common rail fuel injection systems
- Tier 4B EPA emissions compliant with SCR only ECOBlue™ HI-eSCR Tier4B emissions system
- Underhood compact aftertreatment
- 24x24 Dynamic Command™ 8-Step Semi-Powershift transmission
- Best in class cab in terms of space and comfort (same cab as the T6 and T7 Series)
- Standard LED work lighting
- High level of Automating features (E-Hydr 4WD, PTO, e-controlled remotes)
- Closed Center Load Sensing "high efficiency" pumps, up to 108 l/m
- Easy attach remote outlets
- New bold styling (hood, cab roof, lighting)
- Long Stable 98" wheel base for all Models
- Gross Vehicle Weight up to 18,700 lbs.

MODELS

-----  
 T5.130 Dynamic Command  
 Rated PTO HP - 102  
 Rated Engine HP - 120  
 Maximum Engine HP - 130  
 Rated Speed - 2200 RPM  
 274 cu. in. (4.5L) - 4 Cylinder  
 Fuel Tank: 47 Gallon (180L)  
 DEF Tank: 5 Gallon (19L)

T5.140 Dynamic Command  
 Rated PTO HP - 111  
 ENGINE Rated Engine HP - 130  
 Maximum Engine HP - 140  
 Rated Speed - 2200 RPM  
 274 cu. in. (4.5L) - 4 Cylinder  
 Fuel Tank: 47 Gallon (180L)  
 DEF Tank: 5 Gallon (19L)

ENGINE

- Tier 4B Emissions Compliant  
 ECOBlue™ HI-eSCR Tier4B system  
 Engine with Turbocharger and  
 Air-to-Air Intercooler  
 4 Valves Per Cylinder  
 Bosch Common Rail Fuel Injection  
 Pump (electronic)  
 Grid Heater Starting Aid  
 Dual Element Air Filter with Pre-Cleaner  
 (spin tube intakes)  
 A-Pillar Exhaust with Integral Muffler  
 Viscous Fan (5 blade)  
 Hand Throttle

TRANSMISSION

- 24x24 Dynamic Command Semi Powershift Transmission
- Clutchless Range Change between Ranges A/B, B/C.
- 25-MPH (40-KPH) (varies by tire size)

CAB

- -High Roof w/ Opening Visibility Panel and Sunshade
- Flat Deck Platform with Integrated ROPS
  - Standard Air Conditioner and Heater with 4-Speed Pressurizer and dual zone air conditioning
  - Two doors with Locks
  - Two-speed Intermittent Front
  - Wiper/Washer
  - Rear Intermittent Wiper/Washer
  - Hinged Rear Window
  - Tinted Glass with Sunshade
  - Tilt and Telescoping Steering Wheel
  - IntelliView™ IV disp. mtd. on arm rest
  - Deluxe Air Suspension Seat with Automatic Adjustment, Operator Presence Switch and Lap Belt
  - Instructor Seat
  - Deluxe radio



**T5 DYNAMIC COMMAND - LESS FAST PICK  
US PRICE LIST**

**Standard Equipment**

- Digital clock
- Integral ROPS
- Interior dome light
- (2) External courtesy lights
- (2) External telescopic remote
- Adjustable mirrors
- Horn
- Std steering wheel & floor mat
- ISOBUS II connector

STEERING & BRAKES

- Hydrostatic power steering
- Hydraulic wet disc brakes (self-equalizing/self-adjusting)
- Parking brake (automotive style)

FRONT AXLE

- Front FWD (TerraLock™ )
- Class 1.75 heavy-duty FWD axle
- 55-degree turning angle
- Dual steering cylinders
- 11-degree axle oscillation
- Electrohydraulic FWD engagement
- TerraLock™ Auto FWD/Diff-Lock
- Driveshaft shield

REAR AXLE

- Heavy-duty flange axle
- Wet plate differential lock
- Electrohydraulic-engaged dif. lock

ELECTRICAL

- (1) 12-volt 1300 CCA battery
- 120-amp alternator
- Geared starter motor (4.2 kW)
- 7-pin outlet for implement lighting
- 3-pin 40-amp implement socket
- ISO/JD (30 amp) socket
- 15 amp screw-type +/- terminals
- Single pin (8 amp) accessory outlet
- Cigarette lighter

- (2) single-pin outlets for beacon on roof
- Battery boost terminals
- ISOBUS Class 2

LIGHTS

- (4) Halogen front hood headlights
- (2) LED front hood signature lights
- (8) LED cab mounted work lights
- (4) LED high front & rear
- (4) LED mid-mount front & rear
- (2) taillights
- Front & Rear Flashing Cab Safety Lights
- Time Delayed, Self-Cancelling Turn Indicators with Audiable Warning

PTO

- Independent 540/540E/1000 RPM PTO with reversible shaft and flip-up shield
- Multi-plate wet clutch design
- Electrohydraulic-engagement with soft start/auto feathering
- Hydraulic piston PTO brake w/override

HYDRAULIC SYSTEM

- Closed-center load-sensing pump
- Flow at 1,900 RPM: 28.5 gpm (108 l/m)
- (2) electro-hydraulic rear remote valves controlled in SideWinder II™ console (fully programmable)
- Oil collection bottles
- Hydraulic tapping port (Power Beyond)
- Independent pump for CVT and operating circuits

3-POINT LIFT SYSTEM

- Electronic Draft Control (EDC)
- Lower link sensing
- Fast raise/lower control
- Dynamic Ride Control™





**T5 DYNAMIC COMMAND - LESS FAST PICK  
US PRICE LIST**

## Standard Equipment

Category II flex link ends  
 Telescopic stabilizers  
 10228 lb. Lift Capacity with Dual 80mm  
 External Rams

MISCELLANEOUS

-----  
 Flip-up engine hood  
 Swinging drawbar  
 SMV emblem  
 Toolbox

WARRANTY

-----  
 New Holland standard warranty applies

**T5 DYNAMIC COMMAND - LESS FAST PICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	Weight	Factory Data	List Price
T5.130 DCT	19,401 LB	9098531P94	\$126,323.00
T5.140 DCT	19,401 LB	9101514P66	\$130,147.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0475XX	LESS PACKAGING			No Charge
---------	----------------	--	--	-----------

**CAB CONFIGURATION**

CAB ROOF/COLOR

SD\_T9850 SPECIAL COLORS/PANELS

762040	LOW ROOF HIVIS PAN. Low roof with a new visibility panel		9000639P60	\$820.00
--------	---	--	------------	----------

**FIXED OR SUSPENDED**

SD\_T9200 OPERATOR STRUCTURE #1

758479	Suspended_Cab Two shocks mounted in rear of cab increase operator comfort Reduces shock loads transmitted to the tractor by up to 25% When coupled with a suspended axle, the ultimate in ride comfort is achieved. Includes tinted rear window		9001503P84	\$1,928.00
--------	--	--	------------	------------

**ENGINE**

**COLD WEATHER AIDS**

SD\_T1938 WEATHER PACK

758402	Grid_Heater + 110V Pack Grid heater and cold weather pack Includes engine block heater and transmission heater		9000345P54	\$443.00
--------	--	--	------------	----------

**T5 DYNAMIC COMMAND - LESS FAST PICK  
 US PRICE LIST**

**TRANSMISSION**

SD\_T2800 SPEED

	759112	40K ECO - DCT+CREEPE <b>24 Speed Dynamic Command Transmission up to 8 Power Shifts per range over 3 ranges Pushbutton shift, no need for mechanical range lever, no need to clutch between ranges Creep - 722 Feet per hour (220 meters per hour)</b>		9002130P96	\$2,732.00
--	--------	--	--	------------	------------

SD\_T2816 AUTO FEATURES

	758631	ADV TRANS AUTO FEAT		9001414P92	\$1,814.00
--	--------	---------------------	--	------------	------------

**FRONT AXLE**

SD\_T4010 FRONT AXLE

	759670	Class 1.75 Suspd Front Axle <b>Axle less brakes with Steering Sensors Suspension: Cushions and dampens the movement of the front axle, Smoother ride for increased operator comfort and decreased fatigue, Improved traction, Suspenso can be locked solid by the operator using an in-cab switch, located on the RH console</b>		9003230P76	\$4,142.00
--	--------	---	--	------------	------------

**TIRES**

BRAND CHOICE

SD\_T4900 TIRE CATEGORY CHOICE

	330418	Trelleborg		9000477P36	\$612.00
	330438	No tire brand preference			No Charge
	330447	Alliance		9000477P36	\$612.00
	330439	Mitas		9000477P36	\$612.00
	330446	Firestone		9000477P36	\$612.00
	330442	Michelin		9000477P36	\$612.00
	330444	Nokian		9000477P36	\$612.00

**T5 DYNAMIC COMMAND - LESS FAST PICK  
 US PRICE LIST**

**FRONT WHEELS & TIRES**

SD\_T4940 FRONT WHEELS AND TIRES

8235401	12.4R24 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match w/ 8357401 rear tire/wheel</b>	9001223P82	\$1,569.00
8242301	14.9R24 A8 HD Rim <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match with 8365401 rear tire/wheel</b>		No Charge
8299801	Non-Return Ship Wheels - 4WD	9000081P12	\$104.00
8880401	360/80R24 GRSLND, Adj. Rim	9001666P08	\$2,136.00
8247401	11.2R28 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Matches with 8372401 Rear tires 13.6R38 (340/85R38) MAVT</b>	9001265P94	\$1,623.00

**REAR WHEELS & TIRES**

SD\_T4950 REAR WHEELS AND TIRES

8357401	18.4R30 R1W	9002966P34	\$3,803.00
8365401	460/85(18.4)R34 A8 FI,MI,CO,TR		No Charge
8372401	13.6R38 A8	9001992P90	\$2,555.00
8399801	Non-Returnable Shipping Wheel	9000494P52	\$634.00
8916401	440/80R34 GRSLND, Adj. Rim	9002774P46	\$3,557.00

**HYDRAULICS**

**COMPLETE LOADER READY**

SD\_T8110 LOADER BRACKETS

759470	NA LDR RDY+2MMV+ADV <b>Complete Loader Ready - 2 Function Enhanced</b> <b>TPS Mount Bracket Set (with Grill Guard),</b> <b>2 Function MMV, and Enhanced Joystick</b> <b>(Includes valve, joystick, hose kit, &amp; MC 4)</b>	9003830P58	\$4,911.00
759471	NA LDR RDY+3MMV+ADV <b>Complete Loader Ready - 3 Function Enhanced</b> <b>TPS Mount Bracket Set (with Grill Guard),</b> <b>3 Function MMV, and Enhanced Joystick</b> <b>(Includes valve, joystick, hose kit, &amp; MC 4+2)</b>	9004045P08	\$5,186.00

**MID MOUNT VALVES**

SD\_T7780 JOYSTICK

759396	EHSTICK ADV +/- PROP	9002130P96	\$2,732.00
--------	----------------------	------------	------------

**T5 DYNAMIC COMMAND - LESS FAST PICK  
 US PRICE LIST**

SD\_T7790 MID-MOUNT VALVES

	743689	2 Electronic MMV		9002130P96	\$2,732.00
	743690	3 Electronic MMV		9003264P30	\$4,185.00

**WEIGHTS**

FRONT

SD\_T2150 FRONT BALLAST

	759769	10 FRONT WEIGHTS <b>Qty. 10, 88 lb. (40 Kg) weights                  totaling 882 lb. (400 Kg)</b>		9000988P26	\$1,267.00
--	--------	---	--	------------	------------

REAR WHEEL WEIGHTS

SD\_T4960 WHEEL WEIGHTS

	759137	2X150KG + 2X250KG Wheel Weight		9001332P24	\$1,708.00
--	--------	--------------------------------	--	------------	------------

**CAB OPTION**

SD\_T9360 RR MIRRORS

	759154	2 Tele/Heat/Rem Adj Mirror		9000055P38	\$71.00
--	--------	----------------------------	--	------------	---------

SEATS

SD\_T8500 SEAT

	758670	Deluxe Air and Belt		9000639P60	\$820.00
	758485	Deluxe Seat Air Susp Heated <b>Super Deluxe Seat with Low Frequency                  Suspension (+DDS) Belt and Swivel                  Headrest Heated Leather/Alcantara</b>		9001666P08	\$2,136.00
	758486	MAXIMO EVO <b>Semi Active Suspension, Heated, Vented, Belt,                  Alcantara/Leather, Up/Down Headrest                  (Maximo Evo)</b>		9003265P86	\$4,187.00

LIGHTS

SD\_T9130 WORK LAMPS

	762051	12 LED W/LGTS HI PWR		9001333P80	\$1,710.00
--	--------	----------------------	--	------------	------------

SD\_T9146 ROTARY BEACON

	758491	Twin Beacon		9000712P14	\$913.00
	759777	ROTARY BEACON 759777		9000353P34	\$453.00

**T5 DYNAMIC COMMAND - LESS FAST PICK  
 US PRICE LIST**

**MONITOR BRACKETS**

SD\_T9223 RH WINDOW BAR MOUNT

	758153	Monitor Mounting Bracket.		9000127P92	\$164.00
	758154	RH Window Bar Display Ready.		9000209P04	\$268.00
	758621	10" Color Touch Screen Display		9004964P70	\$6,365.00

SD\_T9230 CLIMATE CONTROL

	758482	Air Conditioning W/ATC		9000618P54	\$793.00
--	--------	------------------------	--	------------	----------

**ISO BUS CONNECTOR**

SD\_T7642 ISO BUS

	758632	ISO CL2+9PIN IN CAB <b>ISOBUS CL 3 BASIC + IN CAB 9 PIN PLUG + SPEED CONTROL</b>			No Charge
--	--------	---	--	--	-----------

**AUTO GUIDANCE**

**AUTO GUIDANCE READY**

SD\_T6300 STEERING OR AUTOGUIDANCE READY

	759185	Autoguidance Ready <b>Autoguidance Ready prewired for guidance does not include Nav III Controller and NH 372 receiver</b>		9004532P58	\$5,811.00
--	--------	---	--	------------	------------

SD\_T7616 AUTOGUIDANCE NAV/CO

	762158	AUTOGUID. - Lv.1 <b>Includes Auto Guidance Ready offering with Nav III Controller and NH 372 receiver activated to WAAS level accuracy (Level 1)</b>		9012575P16	\$16,122.00
	762159	AUTOGUID. - Lv.2 <b>Includes Auto Guidance Ready offering with Nav III Controller and NH 372 receiver activated to OmniSTAR HP/G2/XP &amp; CenterPoint RTX level accuracy (Level 2)</b>		9014914P38	\$19,121.00

**MISCELLANEOUS**

**FENDERS FRONT**

SD\_T8740 FRONT FENDERS

	758330	Dynamic Front Fenders 480mm		9000631P02	\$809.00
--	--------	-----------------------------	--	------------	----------

**RADAR**

SD\_T7580 RADAR

	758501	Radar NAR		9000696P54	\$893.00
--	--------	-----------	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	758535	Spanish NAR			No Charge
	759101	French NAR			No Charge



**T5 AUTO COMMAND - DELUXE FASTPICK  
US PRICE LIST**

**Standard Equipment**

KEY SELLING POINTS:

- Fuel efficient high torque 4.5L, 4-cylinder
- FPT engines with 4 valves per cylinder and common rail fuel injection systems
- Tier 4B EPA emissions compliant with SCR only ECOBlue™ HI-eSCR Tier4B emissions system
- Underhood compact aftertreatment
- Auto Command™ CVT high efficiency Transmission
- Best in class cab in terms of space and comfort (same cab as the T6 and T7 Series)
- Standard LED work lighting
- High level of Automating features (E-Hydr 4WD, PTO, e-controlled remotes)
- Closed Center Load Sensing "high efficiency" pumps, up to 108 l/m
- Easy attach remote outlets
- New bold styling (hood, cab roof, lighting)
- Long Stable 98" wheel base for all Models
- Gross Vehicle Weight up to 18,700 lbs.

MODELS

T5.130 Auto Command  
 Rated PTO HP - 102  
 Rated Engine HP - 120  
 Maximum Engine HP - 130  
 Rated Speed - 2200 RPM  
 274 cu. in. (4.5L) - 4 Cylinder  
 Fuel Tank: 47 Gallon (180L)  
 DEF Tank: 5 Gallon (19L)

T5.140 Auto Command  
 Rated PTO HP - 111  
 ENGINE Rated Engine HP - 130  
 Maximum Engine HP - 140  
 Rated Speed - 2200 RPM  
 274 cu. in. (4.5L) - 4 Cylinder  
 Fuel Tank: 47 Gallon (180L)  
 DEF Tank: 5 Gallon (19L)

ENGINE

- 
- Tier 4B Emissions Compliant
- ECOBlue™ HI-eSCR Tier4B system
- Engine with Turbocharger and
- Air-to-Air Intercooler
- 4 Valves Per Cylinder
- Bosch Common Rail Fuel Injection
- Pump (electronic)
- Grid Heater Starting Aid
- Dual Element Air Filter with Pre-Cleaner (spin tube intakes)
- A-Pillar Exhaust with Integral Muffler
- Viscous Fan (5 blade)
- Hand Throttle

TRANSMISSION

- 
- Auto Command™ CVT with
- column-mounted power shuttle
- Command Grip™ multi-function controller
- Infinite speed from 0 to 25 MPH
- 3 target speed selections
- Infinite target speed thumb wheel
- Right foot "go pedal"
- 25-MPH (40-KPH) (varies by tire size)

CAB

- 
- Low Roof w/ Opening Visibility
- Panel and Sunshade
- Flat Deck Platform with
- Integrated ROPS
- Standard Air Conditioner and
- Heater with 4-Speed Pressurizer and
- dual zone air conditioning
- Two doors with Locks
- Two-speed Intermittent Front
- Wiper/Washer
- Rear Intermittent Wiper/Washer
- Hinged Rear Window
- Tinted Glass with Sunshade
- Tilt and Telescoping Steering Wheel
- IntelliView™ IV disp. mtd. on arm rest



**T5 AUTO COMMAND - DELUXE FASTPICK  
 US PRICE LIST**

## Standard Equipment

- Deluxe Air Suspension Seat with Automatic Adjustment, Operator Presence Switch and Lap Belt
- Instructor Seat
- Deluxe radio
- Digital clock
- Integral ROPS
- Interior dome light
- (2) External courtesy lights
- (2) External telescopic remote
- Adjustable mirrors
- Horn
- Std steering wheel & floor mat
- ISOBUS II connector

**STEERING & BRAKES**

- 
- Hydrostatic power steering
  - Hydraulic wet disc brakes (self-equalizing/self-adjusting)
  - Parking brake (automotive style)

**FRONT AXLE**

- 
- Front FWD (TerraLock™ )
  - Class 1.75 heavy-duty FWD axle
  - 55-degree turning angle
  - Dual steering cylinders
  - 11-degree axle oscillation
  - Electrohydraulic FWD engagement
  - TerraLock™ Auto FWD/Diff-Lock
  - Driveshaft shield

**REAR AXLE**

- 
- Heavy-duty flange axle
  - Wet plate differential lock
  - Electrohydraulic-engaged dif. lock

**ELECTRICAL**

- 
- (1) 12-volt 1300 CCA battery
  - 120-amp alternator
  - Geared starter motor (4.2 kW)
  - 7-pin outlet for implement lighting
  - 3-pin 40-amp implement socket
  - ISO/JD (30 amp) socket
  - 15 amp screw-type +/- terminals
  - Single pin (8 amp) accessory outlet
  - Cigarette lighter
  - (2) single-pin outlets for beacon on roof
  - Battery boost terminals
  - ISOBUS Class 2

**LIGHTS**

- 
- (4) Halogen front hood headlights
  - (2) LED front hood signature lights
  - (12) LED cab mounted work lights
    - (8) LED high front & rear
    - (4) LED mid-mount front & rear
  - (2) taillights
  - Front & Rear Flashing Cab Safety Lights
  - Time Delayed, Self-Cancelling Turn Indicators with Audiable Warning

**PTO**

- 
- Independent 540/540E/1000 RPM PTO with reversible shaft and flip-up shield
  - Multi-plate wet clutch design
  - Electrohydraulic-engagement with soft start/auto feathering
  - Hydraulic piston PTO brake w/override

**HYDRAULIC SYSTEM**

- 
- Closed-center load-sensing pump
  - Flow at 1,900 RPM: 28.5 gpm (108 l/m)
  - (2) electro-hydraulic rear remote valves controlled in SideWinder II™ console (fully programmable)





**T5 AUTO COMMAND - DELUXE FASTPICK  
US PRICE LIST**

**Standard Equipment**

Oil collection bottles  
Hydraulic tapping port (Power Beyond)  
Independent pump for CVT and  
operating circuits

3-POINT LIFT SYSTEM

-----  
Electronic Draft Control (EDC)  
Lower link sensing  
Fast raise/lower control  
Dynamic Ride Control™  
Category II flex link ends  
Telescopic stabilizers  
10228 lb. Lift Capacity with Dual 80mm  
External Rams

MISCELLANEOUS

-----  
Flip-up engine hood  
Swinging drawbar  
SMV emblem  
Toolbox

WARRANTY

-----  
New Holland standard warranty applies

**T5 AUTO COMMAND - DELUXE FASTPICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	Weight	Factory Data	List Price
T5.130 AUTOCOMMAND	13,228 LB	9121325P10	\$155,545.00
Includes the following Equipment ISO CL3+9PIN+SPEED (758710)		\$412.00	
T5.140 AUTOCOMMAND	19,400 LB	9124307P82	\$159,369.00
Includes the following Equipment ISO CL3+9PIN+SPEED (758710)		\$412.00	

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0473XX	NAR NH PCK B DELUXE <b>Deluxe Fastpick Package Includes:</b> 759154: 2 Tele/Heat/Rem Adj Mirror 758485: Deluxe Seat Air Susp Heated 758594: 12 LED High Power Hi-Roof 758491: Twin Beacon 758153: Moniot Mounting Bracket.		(903406P26)	(\$4,367.00)
---------	--	--	-------------	--------------

**ENGINE**

COLD WEATHER AIDS

SD\_T1938 WEATHER PACK

758402	Grid_Heater + 110V Pack <b>Grid heater and cold weather pack</b> Includes engine block heater and transmission heater		9000345P54	\$443.00
--------	---	--	------------	----------

**TIRES**

BRAND CHOICE

SD\_T4900 TIRE CATEGORY CHOICE

330438	No tire brand preference			No Charge
--------	--------------------------	--	--	-----------

**T5 AUTO COMMAND - DELUXE FASTPICK  
 US PRICE LIST**

	330442	Michelin		9000477P36	\$612.00
	330444	Nokian		9000477P36	\$612.00

**FRONT WHEELS & TIRES**

**SD\_T4940 FRONT WHEELS AND TIRES**

<b>Ag Front Tires</b>					
	8235401	12.4R24 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match w/ 8357401 rear tire/wheel</b>		9001223P82	\$1,569.00
	8242301	14.9R24 A8 HD Rim <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match with 8365401 rear tire/wheel</b>			No Charge
	8247401	11.2R28 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Matches with 8372401 Rear tires 13.6R38 (340/85R38) MAVT</b>		9001265P94	\$1,623.00
<b>MUNICIPALTY - ADJUSTABLE RIMS</b>					
	8880401	360/80R24 GRSLND, Adj. Rim <b>Match with 8916401 rear tire/wheel</b> <b>Municipal tire with adjustable rim</b>		9001666P08	\$2,136.00
<b>Shipping wheels</b>					
	8299801	Non-Return Ship Wheels - 4WD		9000081P12	\$104.00

**REAR WHEELS & TIRES**

**SD\_T4950 REAR WHEELS AND TIRES**

<b>Ag Rear Tires</b>					
	8372401	13.6R38 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Matches with 8247401 Fronts 11.2R28 (280/85R28) MAVT</b>		9001992P90	\$2,555.00
	8357401	18.4R30 R1W <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match w/ 8235401 front tire/wheel</b>  <b>Not compatible with narrow rear fenders</b> <b>option code: 331870</b>		9002966P34	\$3,803.00
	8365401	460/85(18.4)R34 A8 FI,MI,CO,TR <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Matches with 8242301 14.9R24 (380/85R24) MAVT</b>			No Charge
<b>MUNICIPALTY - ADJUSTABLE RIMS</b>					
	8916401	440/80R34 GRSLND, Adj. Rim <b>Matches with 888041, 360/80R24 TRI 2 MAVT</b> <b>Front Tires</b>		9002774P46	\$3,557.00



**T5 AUTO COMMAND - DELUXE FASTPICK  
 US PRICE LIST**

Shipping wheels					
	8399801	Non-Returnable Shipping Wheel		9000494P52	\$634.00

**HYDRAULICS**

REAR REMOTES

SD_T8270 REAR REMOTES					
	759365	3 MECH RR (3NC) <b>3 MECH REAR REMOTES (3NC)</b>		9000763P62	\$979.00
	743685	4 Mech Rear Remotes (2NC+2C) <b>4 mechanical rear remote valves, two with configurable detents</b>		9001705P08	\$2,186.00

COMPLETE LOADER READY

SD_T8110 LOADER BRACKETS					
	744711	L/Loader Ready w/MMV		(903907P80)	(\$5,010.00)
	758353	Loader Ready + 2 EH MMV + Joy <b>Complete Loader Ready - 2 Function TPS Mount Bracket Set (with Grill Guard), 2 Function MMV, and Joystick with Proportional Rocker (Includes valve, joystick, hose kit, &amp; MC 4)</b>			No Charge
	758354	Loader Ready + 3 EH MMV + Joy <b>Complete Loader Ready - 3 Function TPS Mount Bracket Set (with Grill Guard), 3 Function MMV, and Joystick with Proportional Rocker (Includes valve, joystick, hose kit, &amp; MC 4+2)</b>			No Charge

JOYSTICK CONTROL

SD_T7780 JOYSTICK					
	758069	Joystick with Rocker Switch			No Charge

MID MOUNT VALVES

SD_T7790 MID-MOUNT VALVES					
	743689	2 Electronic MMV			No Charge
	743690	3 Electronic MMV		9001133P34	\$1,453.00



**T5 AUTO COMMAND - DELUXE FASTPICK  
US PRICE LIST**

**WEIGHTS**

REAR WHEEL WEIGHTS

SD\_T4960 WHEEL WEIGHTS

		759137	2X150KG + 2X250KG Wheel Weight		9001332P24	\$1,708.00
--	--	--------	--------------------------------	--	------------	------------

**AUTO GUIDANCE**

AUTO GUIDANCE READY

SD\_T6300 STEERING OR AUTOGUIDANCE READY

		759185	Autoguidance Ready <b>Autoguidance Ready prewired for guidance does not include Nav III Controller and NH 372 receiver</b>		9004532P58	\$5,811.00
--	--	--------	---	--	------------	------------

SD\_T7616 AUTOGUIDANCE NAV/CO

		762158	AUTOGUID. - Lv.1 <b>Includes Auto Guidance Ready offering with Nav III Controller and NH 372 receiver activated to WAAS level accuracy (Level 1)</b>		9012575P16	\$16,122.00
		762159	AUTOGUID. - Lv.2 <b>Includes Auto Guidance Ready offering with Nav III Controller and NH 372 receiver activated to OmniSTAR HP/G2/XP &amp; CenterPoint RTX level accuracy (Level 2)</b>		9014914P38	\$19,121.00

**MISCELLANEOUS**

FENDERS REAR

SD\_T8700 FENDERS

		743777	Standard fenders with extensn			No Charge
		759767	NARROW FNDRS L/EXT.			No Charge

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

		758535	Spanish NAR			No Charge
		759101	French NAR			No Charge



**T5 AUTO COMMAND - PREMIUM FASTPICK  
US PRICE LIST**

**Standard Equipment**

KEY SELLING POINTS:

- Fuel efficient high torque 4.5L, 4-cylinder
- FPT engines with 4 valves per cylinder and common rail fuel injection systems
- Tier 4B EPA emissions compliant with SCR only ECOBlue™ HI-eSCR Tier4B emissions system
- Underhood compact aftertreatment
- Auto Command™ CVT high efficiency Transmission
- Best in class cab in terms of space and comfort (same cab as the T6 and T7 Series)
- Standard LED work lighting
- High level of Automating features (E-Hydr 4WD, PTO, e-controlled remotes)
- Closed Center Load Sensing "high efficiency" pumps, up to 108 l/m
- Easy attach remote outlets
- New bold styling (hood, cab roof, lighting)
- Long Stable 98" wheel base for all Models
- Gross Vehicle Weight up to 18,700 lbs.

MODELS

-----  
T5.130 Auto Command  
Rated PTO HP - 102  
Rated Engine HP - 120  
Maximum Engine HP - 130  
Rated Speed - 2200 RPM  
274 cu. in. (4.5L) - 4 Cylinder  
Fuel Tank: 47 Gallon (180L)  
DEF Tank: 5 Gallon (19L)

T5.140 Auto Command  
Rated PTO HP - 111  
ENGINE Rated Engine HP - 130  
Maximum Engine HP - 140  
Rated Speed - 2200 RPM  
274 cu. in. (4.5L) - 4 Cylinder  
Fuel Tank: 47 Gallon (180L)  
DEF Tank: 5 Gallon (19L)

ENGINE

- Tier 4B Emissions Compliant  
ECOBlue™ HI-eSCR Tier4B system  
Engine with Turbocharger and  
Air-to-Air Intercooler  
4 Valves Per Cylinder  
Bosch Common Rail Fuel Injection  
Pump (electronic)  
Grid Heater Starting Aid  
Dual Element Air Filter with Pre-Cleaner  
(spin tube intakes)  
A-Pillar Exhaust with Integral Muffler  
Viscous Fan (5 blade)  
Hand Throttle

TRANSMISSION

- Auto Command™ CVT with  
column-mounted power shuttle  
Command Grip™ multi-function controller  
Infinite speed from 0 to 25 MPH  
3 target speed selections  
Infinite target speed thumb wheel  
Right foot "go pedal"  
25-MPH (40-KPH) (varies by tire size)

CAB

- - Low Roof w/ Opening Visibility  
Panel and Sunshade  
- Flat Deck Platform with  
Integrated ROPS  
- Standard Air Conditioner and  
Heater with 4-Speed Pressurizer and  
dual zone air conditioning  
- Two doors with Locks  
- Two-speed Intermittent Front  
- Wiper/Washer  
- Rear Intermittent Wiper/Washer  
- Hinged Rear Window  
- Tinted Glass with Sunshade  
- Tilt and Telescoping Steering Wheel  
- IntelliView™ IV disp. mtd. on arm rest



**T5 AUTO COMMAND - PREMIUM FASTPICK  
US PRICE LIST**

**Standard Equipment**

- Deluxe Air Suspension Seat with Automatic Adjustment, Operator Presence Switch and Lap Belt
- Instructor Seat
- Deluxe radio
- Digital clock
- Integral ROPS
- Interior dome light
- (2) External courtesy lights
- (2) External telescopic remote
- Adjustable mirrors
- Horn
- Std steering wheel & floor mat
- ISOBUS II connector

**STEERING & BRAKES**

- Hydrostatic power steering
- Hydraulic wet disc brakes (self-equalizing/self-adjusting)
- Parking brake (automotive style)

**FRONT AXLE**

- Front FWD (TerraLock™ )
- Class 1.75 heavy-duty FWD axle
- 55-degree turning angle
- Dual steering cylinders
- 11-degree axle oscillation
- Electrohydraulic FWD engagement
- TerraLock™ Auto FWD/Diff-Lock
- Driveshaft shield

**REAR AXLE**

- Heavy-duty flange axle
- Wet plate differential lock
- Electrohydraulic-engaged dif. lock

**ELECTRICAL**

- (1) 12-volt 1300 CCA battery
- 120-amp alternator
- Geared starter motor (4.2 kW)
- 7-pin outlet for implement lighting
- 3-pin 40-amp implement socket
- ISO/JD (30 amp) socket
- 15 amp screw-type +/- terminals
- Single pin (8 amp) accessory outlet
- Cigarette lighter
- (2) single-pin outlets for beacon on roof
- Battery boost terminals
- ISOBUS Class 2

**LIGHTS**

- (4) Halogen front hood headlights
- (2) LED front hood signature lights
- (12) LED cab mounted work lights
  - (8) LED high front & rear
  - (4) LED mid-mount front & rear
- (2) taillights
- Front & Rear Flashing Cab Safety Lights
- Time Delayed, Self-Cancelling Turn Indicators with Audiable Warning

**PTO**

- Independent 540/540E/1000 RPM PTO with reversible shaft and flip-up shield
- Multi-plate wet clutch design
- Electrohydraulic-engagement with soft start/auto feathering
- Hydraulic piston PTO brake w/override

**HYDRAULIC SYSTEM**

- Closed-center load-sensing pump
- Flow at 1,900 RPM: 28.5 gpm (108 l/m)
- (2) electro-hydraulic rear remote valves controlled in SideWinder II™ console (fully programmable)



**T5 AUTO COMMAND - PREMIUM FASTPICK  
US PRICE LIST**

**Standard Equipment**

Oil collection bottles  
Hydraulic tapping port (Power Beyond)  
Independent pump for CVT and  
operating circuits

3-POINT LIFT SYSTEM

-----  
Electronic Draft Control (EDC)  
Lower link sensing  
Fast raise/lower control  
Dynamic Ride Control™  
Category II flex link ends  
Telescopic stabilizers  
10228 lb. Lift Capacity with Dual 80mm  
External Rams

MISCELLANEOUS

-----  
Flip-up engine hood  
Swinging drawbar  
SMV emblem  
Toolbox

WARRANTY

-----  
New Holland standard warranty applies



**T5 AUTO COMMAND - PREMIUM FASTPICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	Weight	Factory Data	List Price
T5.130 AUTOCOMMAND	13,228 LB	9121325P10	\$155,545.00
Includes the following Equipment ISO CL3+9PIN+SPEED (758710)		\$412.00	
T5.140 AUTOCOMMAND	19,400 LB	9124307P82	\$159,369.00
Includes the following Equipment ISO CL3+9PIN+SPEED (758710)		\$412.00	

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0472XX	NAR NH PCK A PREMIUM <b>Premium Fastpick Package Includes:</b> 743680: Fender EDC/PTO/Rem Valv Control 758671: Deluxe Air and Heated Cushion 758596: 16 LED High Power Hi-Roof 759675: WET DIFF & 4WD CLTCH		(900482P04)	(\$618.00)
---------	--	--	-------------	------------

**ENGINE**

**COLD WEATHER AIDS**

SD\_T1938 WEATHER PACK

758402	Grid_Heater + 110V Pack <b>Grid heater and cold weather pack</b> Includes engine block heater and transmission heater		9000345P54	\$443.00
--------	---	--	------------	----------

**FRONT AXLE**

SD\_T4010 FRONT AXLE

759669	SUSP. AXLE L/BRKS		9003230P76	\$4,142.00
--------	-------------------	--	------------	------------

**T5 AUTO COMMAND - PREMIUM FASTPICK  
 US PRICE LIST**

**TIRES**

BRAND CHOICE

SD\_T4900 TIRE CATEGORY CHOICE

	330438	No tire brand preference			No Charge
	330442	Michelin		9000477P36	\$612.00
	330444	Nokian		9000477P36	\$612.00

FRONT WHEELS & TIRES

SD\_T4940 FRONT WHEELS AND TIRES

Ag Front Tires					
	8235401	12.4R24 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match w/ 8357401 rear tire/wheel</b>		9001223P82	\$1,569.00
	8242301	14.9R24 A8 HD Rim <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match with 8365401 rear tire/wheel</b>			No Charge
	8247401	11.2R28 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Matches with 8372401 Rear tires 13.6R38 (340/85R38) MAVT</b>		9001265P94	\$1,623.00
MUNICIPALTY - ADJUSTABLE RIMS					
	8880401	360/80R24 GRSLND, Adj. Rim <b>Match with 8916401 rear tire/wheel</b> <b>Municipal tire with adjustable rim</b>		9001666P08	\$2,136.00
Shipping wheels					
	8299801	Non-Return Ship Wheels - 4WD		9000081P12	\$104.00

REAR WHEELS & TIRES

SD\_T4950 REAR WHEELS AND TIRES

Ag Rear Tires					
	8372401	13.6R38 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Matches with 8247401 Fronts 11.2R28 (280/85R28) MAVT</b>		9001992P90	\$2,555.00
	8357401	18.4R30 R1W <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match w/ 8235401 front tire/wheel</b>  <b>Not compatible with narrow rear fenders</b> <b>option code: 331870</b>		9002966P34	\$3,803.00



**T5 AUTO COMMAND - PREMIUM FASTPICK  
 US PRICE LIST**

	8365401	460/85(18.4)R34 A8 FI,MI,CO,TR <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Matches with 8242301 14.9R24 (380/85R24) MAVT</b>			No Charge
MUNICIPALTY - ADJUSTABLE RIMS					
	8916401	440/80R34 GRSLND, Adj. Rim <b>Matches with 888041, 360/80R24 TRI 2 MAVT</b> <b>Front Tires</b>		9002774P46	\$3,557.00
Shipping wheels					
	8399801	Non-Returnable Shipping Wheel		9000494P52	\$634.00

**HYDRAULICS**

REAR REMOTES

SD\_T8270 REAR REMOTES

	759690	2 RR MV + 1 EH.RR.V. <b>2 RR MV (CONFIG. DETENT) + 1 ELECTRO HYD. REAR REMOTE VALVES</b>		9001448P46	\$1,857.00
	759691	2 RR MV + 2 EH.RR.V. <b>2 RR MV (CONFIG. DETENT) + 2 ELECTRO HYD. REAR REMOTE VALVES</b>		9002219P88	\$2,846.00

COMPLETE LOADER READY

SD\_T8110 LOADER BRACKETS

	744711	L/Loader Ready w/MMV		(903907P80)	(\$5,010.00)
	758353	Loader Ready + 2 EH MMV + Joy <b>Complete Loader Ready - 2 Function</b> <b>TPS Mount Bracket Set (with Grill Guard),</b> <b>2 Function MMV, and Joystick with Proportional Rocker</b> <b>(Includes valve, joystick, hose kit, &amp; MC 4)</b>			No Charge
	758354	Loader Ready + 3 EH MMV + Joy <b>Complete Loader Ready - 3 Function</b> <b>TPS Mount Bracket Set (with Grill Guard),</b> <b>3 Function MMV, and Joystick with Proportional Rocker</b> <b>(Includes valve, joystick, hose kit, &amp; MC 4+2)</b>			No Charge

JOYSTICK CONTROL

SD\_T7780 JOYSTICK

	758069	Joystick with Rocker Switch			No Charge
--	--------	-----------------------------	--	--	-----------

**T5 AUTO COMMAND - PREMIUM FASTPICK  
 US PRICE LIST**

**MID MOUNT VALVES**

SD\_T7790 MID-MOUNT VALVES

	743689	2 Electronic MMV			No Charge
	743690	3 Electronic MMV		9001133P34	\$1,453.00

**WEIGHTS**

**REAR WHEEL WEIGHTS**

SD\_T4960 WHEEL WEIGHTS

	759137	2X150KG + 2X250KG Wheel Weight		9001332P24	\$1,708.00
--	--------	--------------------------------	--	------------	------------

**CAB OPTION**

SD\_T4820 HEADLAND SYSTEM

	758592	Adv. Headland Ctrl Confg EHR <b>Allows End of Row functions to be precisely programmed.</b> <b>More user-friendly than basic End of Row controls</b> <b>Allows operator to choose within the display which remote is operated on the MultiFunction handle</b> <b>Requires display</b>		9000826P80	\$1,060.00
--	--------	---	--	------------	------------

**AUTO GUIDANCE**

**AUTO GUIDANCE READY**

SD\_T6300 STEERING OR AUTOGUIDANCE READY

	759185	Autoguidance Ready <b>Autoguidance Ready prewired for guidance does not include Nav III Controller and NH 372 receiver</b>		9004532P58	\$5,811.00
--	--------	---	--	------------	------------

SD\_T7616 AUTOGUIDANCE NAV/CO

	762158	AUTOGUID. - Lv.1 <b>Includes Auto Guidance Ready offering with Nav III Controller and NH 372 receiver activated to WAAS level accuracy (Level 1)</b>		9012575P16	\$16,122.00
	762159	AUTOGUID. - Lv.2 <b>Includes Auto Guidance Ready offering with Nav III Controller and NH 372 receiver activated to OmniSTAR HP/G2/XP &amp; CenterPoint RTX level accuracy (Level 2)</b>		9014914P38	\$19,121.00



**T5 AUTO COMMAND - PREMIUM FASTPICK  
 US PRICE LIST**

**MISCELLANEOUS**

FENDERS REAR

SD\_T8700 FENDERS

	743777	Standard fenders with extensn			No Charge
--	--------	-------------------------------	--	--	-----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	758535	Spanish NAR			No Charge
	759101	French NAR			No Charge



**T5 AUTO COMMAND - BLUE POWER  
US PRICE LIST**

**Standard Equipment**

KEY SELLING POINTS:

- Fuel efficient high torque 4.5L, 4-cylinder
- FPT engines with 4 valves per cylinder and common rail fuel injection systems
- Tier 4B EPA emissions compliant with SCR only ECOBlue™ HI-eSCR Tier4B emissions system
- Underhood compact aftertreatment
- Auto Command™ CVT high efficiency Transmission
- Best in class cab in terms of space and comfort (same cab as the T6 and T7 Series)
- Standard LED work lighting
- High level of Automating features (E-Hydr 4WD, PTO, e-controlled remotes)
- Closed Center Load Sensing "high efficiency" pumps, up to 108 l/m
- Easy attach remote outlets
- New bold styling (hood, cab roof, lighting)
- Long Stable 98" wheel base for all Models
- Gross Vehicle Weight up to 18,700 lbs.

MODELS

T5.130 Auto Command  
 Rated PTO HP - 102  
 Rated Engine HP - 120  
 Maximum Engine HP - 130  
 Rated Speed - 2200 RPM  
 274 cu. in. (4.5L) - 4 Cylinder  
 Fuel Tank: 47 Gallon (180L)  
 DEF Tank: 5 Gallon (19L)

T5.140 Auto Command  
 Rated PTO HP - 111  
 ENGINE Rated Engine HP - 130  
 Maximum Engine HP - 140  
 Rated Speed - 2200 RPM  
 274 cu. in. (4.5L) - 4 Cylinder  
 Fuel Tank: 47 Gallon (180L)  
 DEF Tank: 5 Gallon (19L)

ENGINE

- 
- Tier 4B Emissions Compliant
- ECOBlue™ HI-eSCR Tier4B system
- Engine with Turbocharger and
- Air-to-Air Intercooler
- 4 Valves Per Cylinder
- Bosch Common Rail Fuel Injection
- Pump (electronic)
- Grid Heater Starting Aid
- Dual Element Air Filter with Pre-Cleaner (spin tube intakes)
- A-Pillar Exhaust with Integral Muffler
- Viscous Fan (5 blade)
- Hand Throttle

TRANSMISSION

- 
- Auto Command™ CVT with
- column-mounted power shuttle
- Command Grip™ multi-function controller
- Infinite speed from 0 to 25 MPH
- 3 target speed selections
- Infinite target speed thumb wheel
- Right foot "go pedal"
- 25-MPH (40-KPH) (varies by tire size)

CAB

- 
- Low Roof w/ Opening Visibility Panel and Sunshade
- Flat Deck Platform with Integrated ROPS
- Standard Air Conditioner and Heater with 4-Speed Pressurizer and dual zone air conditioning
- Two doors with Locks
- Two-speed Intermittent Front
- Wiper/Washer
- Rear Intermittent Wiper/Washer
- Hinged Rear Window
- Tinted Glass with Sunshade
- Tilt and Telescoping Steering Wheel
- IntelliView™ IV disp. mtd. on arm rest



**T5 AUTO COMMAND - BLUE POWER  
US PRICE LIST**

**Standard Equipment**

- Deluxe Air Suspension Seat with Automatic Adjustment, Operator Presence Switch and Lap Belt
- Instructor Seat
- Deluxe radio
- Digital clock
- Integral ROPS
- Interior dome light
- (2) External courtesy lights
- (2) External telescopic remote
- Adjustable mirrors
- Horn
- Std steering wheel & floor mat
- ISOBUS II connector

**STEERING & BRAKES**

- Hydrostatic power steering
- Hydraulic wet disc brakes (self-equalizing/self-adjusting)
- Parking brake (automotive style)

**FRONT AXLE**

- Front FWD (TerraLock™ )
- Class 1.75 heavy-duty FWD axle
- 55-degree turning angle
- Dual steering cylinders
- 11-degree axle oscillation
- Electrohydraulic FWD engagement
- TerraLock™ Auto FWD/Diff-Lock
- Driveshaft shield

**REAR AXLE**

- Heavy-duty flange axle
- Wet plate differential lock
- Electrohydraulic-engaged dif. lock

**ELECTRICAL**

- (1) 12-volt 1300 CCA battery
- 120-amp alternator
- Geared starter motor (4.2 kW)
- 7-pin outlet for implement lighting
- 3-pin 40-amp implement socket
- ISO/JD (30 amp) socket
- 15 amp screw-type +/- terminals
- Single pin (8 amp) accessory outlet
- Cigarette lighter
- (2) single-pin outlets for beacon on roof
- Battery boost terminals
- ISOBUS Class 2

**LIGHTS**

- (4) Halogen front hood headlights
- (2) LED front hood signature lights
- (12) LED cab mounted work lights
  - (8) LED high front & rear
  - (4) LED mid-mount front & rear
- (2) taillights
- Front & Rear Flashing Cab Safety Lights
- Time Delayed, Self-Cancelling Turn Indicators with Audiable Warning

**PTO**

- Independent 540/540E/1000 RPM PTO with reversible shaft and flip-up shield
- Multi-plate wet clutch design
- Electrohydraulic-engagement with soft start/auto feathering
- Hydraulic piston PTO brake w/override

**HYDRAULIC SYSTEM**

- Closed-center load-sensing pump
- Flow at 1,900 RPM: 28.5 gpm (108 l/m)
- (2) electro-hydraulic rear remote valves controlled in SideWinder II™ console (fully programmable)



**T5 AUTO COMMAND - BLUE POWER  
US PRICE LIST**

**Standard Equipment**

Oil collection bottles  
Hydraulic tapping port (Power Beyond)  
Independent pump for CVT and  
operating circuits

3-POINT LIFT SYSTEM

-----  
Electronic Draft Control (EDC)  
Lower link sensing  
Fast raise/lower control  
Dynamic Ride Control™  
Category II flex link ends  
Telescopic stabilizers  
10228 lb. Lift Capacity with Dual 80mm  
External Rams

MISCELLANEOUS

-----  
Flip-up engine hood  
Swinging drawbar  
SMV emblem  
Toolbox

WARRANTY

-----  
New Holland standard warranty applies



**T5 AUTO COMMAND - BLUE POWER  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	Weight	Factory Data	List Price
T5.140 AUTOCOMMAND	19,400 LB	9124307P82	\$159,369.00
Includes the following Equipment ISO CL3+9PIN+SPEED (758710)		\$412.00	

**CAB CONFIGURATION**

CAB ROOF/COLOR

SD\_T9850 SPECIAL COLORS/PANELS

758320	BLUE POW. SPEC. ED. <b>Blue Power Option includes:</b> -#Distinct metallic midnight blue paint -#Chrome colored grill -#Silver wheel rims -#Eye Catching 3D leaf and New Holland Logo -#Blue Power Seat -#Silver light surround on cab work lights -#An extensive list of standard equipment including:  758483: Leather Steering Wheel +Carpet LEATHER STEERING WHEEL+CARPET  759384: SDLX HTD ALCANT Blue Power SDLX SEAT LOW FREQ SUSP/SWIVEL HEADREST/HEATED/LEATHER-ALCANTARA BLUE POWER  758596: 16 LED High Power Hi-Roof 16 LED HIGH POWER HIGH ROOF  758491: Twin Beacon  759154: 2 Tele/Heat/Rem Adj Mirror 2 TELE/HEATED/REM ADJUST MIRRORS (SHATTER PROOF - LARGE HEAD - SPOTTER  759663: 200 AMP ALTERNATOR 759663  758504: Self-Cancel + Audible Turn SELF CANCEL.+AUDI. WARN. TURN INDICATORS		9008096P40	\$10,380.00
--------	--	--	------------	-------------

**ENGINE**

COLD WEATHER AIDS

SD\_T1938 WEATHER PACK

758402	Grid_Heater + 110V Pack <b>Grid heater and cold weather pack</b> <b>Includes engine block heater and transmission heater</b>		9000345P54	\$443.00
--------	--	--	------------	----------

**T5 AUTO COMMAND - BLUE POWER  
 US PRICE LIST**

**FRONT AXLE**

SD\_T4010 FRONT AXLE

	759669	SUSP. AXLE L/BRKS		9003230P76	\$4,142.00
--	--------	-------------------	--	------------	------------

**TIRES**

BRAND CHOICE

SD\_T4900 TIRE CATEGORY CHOICE

	330442	Michelin		9000477P36	\$612.00
--	--------	----------	--	------------	----------

**HYDRAULICS**

REAR REMOTES

SD\_T8270 REAR REMOTES

	759365	3 MECH RR (3NC) <b>3 MECH REAR REMOTES (3NC)</b>		9000763P62	\$979.00
	743685	4 Mech Rear Remotes (2NC+2C) <b>4 mechanical rear remote valves, two with configurable detents</b>		9001705P08	\$2,186.00
	759690	2 RR MV + 1 EH.RR.V. <b>2 RR MV (CONFIG. DETENT) + 1 ELECTRO HYD. REAR REMOTE VALVES</b>		9001448P46	\$1,857.00
	759691	2 RR MV + 2 EH.RR.V. <b>2 RR MV (CONFIG. DETENT) + 2 ELECTRO HYD. REAR REMOTE VALVES</b>		9002219P88	\$2,846.00

COMPLETE LOADER READY

SD\_T8110 LOADER BRACKETS

	744711	L/Loader Ready w/MMV		(903907P80)	(\$5,010.00)
	758353	Loader Ready + 2 EH MMV + Joy <b>Complete Loader Ready - 2 Function TPS Mount Bracket Set (with Grill Guard), 2 Function MMV, and Joystick with Proportional Rocker (Includes valve, joystick, hose kit, &amp; MC 4)</b>			No Charge

**T5 AUTO COMMAND - BLUE POWER  
 US PRICE LIST**

	758354	Loader Ready + 3 EH MMV + Joy <b>Complete Loader Ready - 3 Function                  TPS Mount Bracket Set (with Grill Guard),                  3 Function MMV, and Joystick with Proportional Rocker                  (Includes valve, joystick, hose kit, &amp; MC 4+2)</b>			No Charge
--	--------	--	--	--	-----------

**JOYSTICK CONTROL**

SD\_T7780 JOYSTICK

	759694	L/JOYSTICK W/EDC POD 759694		(901742P52)	(\$2,234.00)
--	--------	-----------------------------	--	-------------	--------------

**MID MOUNT VALVES**

SD\_T7790 MID-MOUNT VALVES

	759695	L/MID-MOUNT VALVES 759695		(902130P96)	(\$2,732.00)
	743689	2 Electronic MMV			No Charge
	743690	3 Electronic MMV		9001133P34	\$1,453.00

**PTO**

**REAR PTO**

SD\_T8710 FENDERS PTO CONTROL

	743680	Fender EDC/PTO/Rem Valv Contrl		9000247P26	\$317.00
--	--------	--------------------------------	--	------------	----------

**WEIGHTS**

**FRONT**

SD\_T2150 FRONT BALLAST

	759769	10 FRONT WEIGHTS <b>Qty. 10, 88 lb. (40 Kg) weights                  totaling 882 lb. (400 Kg)</b>		9000988P26	\$1,267.00
--	--------	---	--	------------	------------

**REAR WHEEL WEIGHTS**

SD\_T4960 WHEEL WEIGHTS

	759137	2X150KG + 2X250KG Wheel Weight		9001332P24	\$1,708.00
--	--------	--------------------------------	--	------------	------------

**T5 AUTO COMMAND - BLUE POWER  
 US PRICE LIST**

**CAB OPTION**

SD\_T4820 HEADLAND SYSTEM

	758592	Adv. Headland Ctrl Config EHR <b>Allows End of Row functions to be precisely programmed.                  More user-friendly than basic End of Row controls                  Allows operator to choose within the display which remote is operated on the MultiFunction handle                  Requires display</b>		9000826P80	\$1,060.00
--	--------	---	--	------------	------------

**MONITOR BRACKETS**

SD\_T9223 RH WINDOW BAR MOUNT

	758153	Monitor Mounting Bracket.		9000127P92	\$164.00
--	--------	---------------------------	--	------------	----------

**AUTO GUIDANCE**

**AUTO GUIDANCE READY**

SD\_T7616 AUTOGUIDANCE NAV/CO

	762158	AUTOGUID. - Lv.1 <b>Includes Auto Guidance Ready offering with Nav III Controller and NH 372 receiver activated to WAAS level accuracy (Level 1)</b>		9012575P16	\$16,122.00
	762159	AUTOGUID. - Lv.2 <b>Includes Auto Guidance Ready offering with Nav III Controller and NH 372 receiver activated to OmniSTAR HP/G2/XP &amp; CenterPoint RTX level accuracy (Level 2)</b>		9014914P38	\$19,121.00

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	758535	Spanish NAR			No Charge
	759101	French NAR			No Charge



**T5 AUTO COMMAND - LESS FASTPICK  
US PRICE LIST**

**Standard Equipment**

KEY SELLING POINTS:

- Fuel efficient high torque 4.5L, 4-cylinder
- FPT engines with 4 valves per cylinder and common rail fuel injection systems
- Tier 4B EPA emissions compliant with SCR only ECOBlue™ HI-eSCR Tier4B emissions system
- Underhood compact aftertreatment
- Auto Command™ CVT high efficiency Transmission
- Best in class cab in terms of space and comfort (same cab as the T6 and T7 Series)
- Standard LED work lighting
- High level of Automating features (E-Hydr 4WD, PTO, e-controlled remotes)
- Closed Center Load Sensing "high efficiency" pumps, up to 108 l/m
- Easy attach remote outlets
- New bold styling (hood, cab roof, lighting)
- Long Stable 98" wheel base for all Models
- Gross Vehicle Weight up to 18,700 lbs.

MODELS

-----  
T5.130 Auto Command  
Rated PTO HP - 102  
Rated Engine HP - 120  
Maximum Engine HP - 130  
Rated Speed - 2200 RPM  
274 cu. in. (4.5L) - 4 Cylinder  
Fuel Tank: 47 Gallon (180L)  
DEF Tank: 5 Gallon (19L)

T5.140 Auto Command  
Rated PTO HP - 111  
ENGINE Rated Engine HP - 130  
Maximum Engine HP - 140  
Rated Speed - 2200 RPM  
274 cu. in. (4.5L) - 4 Cylinder  
Fuel Tank: 47 Gallon (180L)  
DEF Tank: 5 Gallon (19L)

ENGINE

- Tier 4B Emissions Compliant  
ECOBlue™ HI-eSCR Tier4B system  
Engine with Turbocharger and  
Air-to-Air Intercooler  
4 Valves Per Cylinder  
Bosch Common Rail Fuel Injection  
Pump (electronic)  
Grid Heater Starting Aid  
Dual Element Air Filter with Pre-Cleaner  
(spin tube intakes)  
A-Pillar Exhaust with Integral Muffler  
Viscous Fan (5 blade)  
Hand Throttle

TRANSMISSION

- Auto Command™ CVT with  
column-mounted power shuttle  
Command Grip™ multi-function controller  
Infinite speed from 0 to 25 MPH  
3 target speed selections  
Infinite target speed thumb wheel  
Right foot "go pedal"  
25-MPH (40-KPH) (varies by tire size)

CAB

- - Low Roof w/ Opening Visibility  
Panel and Sunshade  
- Flat Deck Platform with  
Integrated ROPS  
- Standard Air Conditioner and  
Heater with 4-Speed Pressurizer and  
dual zone air conditioning  
- Two doors with Locks  
- Two-speed Intermittent Front  
- Wiper/Washer  
- Rear Intermittent Wiper/Washer  
- Hinged Rear Window  
- Tinted Glass with Sunshade  
- Tilt and Telescoping Steering Wheel  
- IntelliView™ IV disp. mtd. on arm rest



**T5 AUTO COMMAND - LESS FASTPICK  
 US PRICE LIST**

## Standard Equipment

- Deluxe Air Suspension Seat with Automatic Adjustment, Operator Presence Switch and Lap Belt
- Instructor Seat
- Deluxe radio
- Digital clock
- Integral ROPS
- Interior dome light
- (2) External courtesy lights
- (2) External telescopic remote
- Adjustable mirrors
- Horn
- Std steering wheel & floor mat
- ISOBUS II connector

**STEERING & BRAKES**

-----

- Hydrostatic power steering
- Hydraulic wet disc brakes (self-equalizing/self-adjusting)
- Parking brake (automotive style)

**FRONT AXLE**

-----

- Front FWD (TerraLock™ )
- Class 1.75 heavy-duty FWD axle
- 55-degree turning angle
- Dual steering cylinders
- 11-degree axle oscillation
- Electrohydraulic FWD engagement
- TerraLock™ Auto FWD/Diff-Lock
- Driveshaft shield

**REAR AXLE**

-----

- Heavy-duty flange axle
- Wet plate differential lock
- Electrohydraulic-engaged dif. lock

**ELECTRICAL**

-----

- (1) 12-volt 1300 CCA battery
- 120-amp alternator
- Geared starter motor (4.2 kW)
- 7-pin outlet for implement lighting
- 3-pin 40-amp implement socket
- ISO/JD (30 amp) socket
- 15 amp screw-type +/- terminals
- Single pin (8 amp) accessory outlet
- Cigarette lighter
- (2) single-pin outlets for beacon on roof
- Battery boost terminals
- ISOBUS Class 2

**LIGHTS**

-----

- (4) Halogen front hood headlights
- (2) LED front hood signature lights
- (12) LED cab mounted work lights
  - (8) LED high front & rear
  - (4) LED mid-mount front & rear
- (2) taillights
- Front & Rear Flashing Cab Safety Lights
- Time Delayed, Self-Cancelling Turn Indicators with Audiable Warning

**PTO**

-----

- Independent 540/540E/1000 RPM PTO with reversible shaft and flip-up shield
- Multi-plate wet clutch design
- Electrohydraulic-engagement with soft start/auto feathering
- Hydraulic piston PTO brake w/override

**HYDRAULIC SYSTEM**

-----

- Closed-center load-sensing pump
- Flow at 1,900 RPM: 28.5 gpm (108 l/m)
- (2) electro-hydraulic rear remote valves controlled in SideWinder II™ console (fully programmable)



**T5 AUTO COMMAND - LESS FASTPICK  
US PRICE LIST**

**Standard Equipment**

Oil collection bottles  
Hydraulic tapping port (Power Beyond)  
Independent pump for CVT and  
operating circuits

3-POINT LIFT SYSTEM

-----  
Electronic Draft Control (EDC)  
Lower link sensing  
Fast raise/lower control  
Dynamic Ride Control™  
Category II flex link ends  
Telescopic stabilizers  
10228 lb. Lift Capacity with Dual 80mm  
External Rams

MISCELLANEOUS

-----  
Flip-up engine hood  
Swinging drawbar  
SMV emblem  
Toolbox

WARRANTY

-----  
New Holland standard warranty applies

**T5 AUTO COMMAND - LESS FASTPICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	Weight	Factory Data	List Price
T5.130 AUTOCOMMAND	13,228 LB	9121325P10	\$155,545.00
Includes the following Equipment ISO CL3+9PIN+SPEED (758710)		\$412.00	
T5.140 AUTOCOMMAND	19,400 LB	9124307P82	\$159,369.00
Includes the following Equipment ISO CL3+9PIN+SPEED (758710)		\$412.00	

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD_T9980 PACKAGING				
X0475XX	LESS PACKAGING			No Charge

**ENGINE**

**COLD WEATHER AIDS**

SD_T1938 WEATHER PACK				
758402	Grid_Heater + 110V Pack <b>Grid heater and cold weather pack</b> Includes engine block heater and transmission heater		9000345P54	\$443.00

**FRONT AXLE**

SD_T4010 FRONT AXLE				
759669	SUSP. AXLE L/BRKS		9003230P76	\$4,142.00

**TIRES**

**BRAND CHOICE**

SD_T4900 TIRE CATEGORY CHOICE				
330438	No tire brand preference			No Charge



**T5 AUTO COMMAND - LESS FASTPICK  
 US PRICE LIST**

	330442	Michelin		9000477P36	\$612.00
	330444	Nokian		9000477P36	\$612.00

**FRONT WHEELS & TIRES**

**SD\_T4940 FRONT WHEELS AND TIRES**

<b>Ag Front Tires</b>					
	8235401	12.4R24 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match w/ 8357401 rear tire/wheel</b>		9001223P82	\$1,569.00
	8242301	14.9R24 A8 HD Rim <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match with 8365401 rear tire/wheel</b>			No Charge
	8247401	11.2R28 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Matches with 8372401 Rear tires 13.6R38 (340/85R38) MAVT</b>		9001265P94	\$1,623.00
<b>MUNICIPALTY - ADJUSTABLE RIMS</b>					
	8880401	360/80R24 GRSLND, Adj. Rim <b>Match with 8916401 rear tire/wheel</b> <b>Municipal tire with adjustable rim</b>		9001666P08	\$2,136.00
<b>Shipping wheels</b>					
	8299801	Non-Return Ship Wheels - 4WD		9000081P12	\$104.00

**REAR WHEELS & TIRES**

**SD\_T4950 REAR WHEELS AND TIRES**

<b>Ag Rear Tires</b>					
	8372401	13.6R38 A8 <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Matches with 8247401 Fronts 11.2R28 (280/85R28) MAVT</b>		9001992P90	\$2,555.00
	8357401	18.4R30 R1W <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Match w/ 8235401 front tire/wheel</b>  <b>Not compatible with narrow rear fenders</b> <b>option code: 331870</b>		9002966P34	\$3,803.00
	8365401	460/85(18.4)R34 A8 FI,MI,CO,TR <b>R1W RADIAL ISO 4WD ADJUSTABLE RIM</b> <b>Matches with 8242301 14.9R24 (380/85R24) MAVT</b>			No Charge
<b>MUNICIPALTY - ADJUSTABLE RIMS</b>					
	8916401	440/80R34 GRSLND, Adj. Rim <b>Matches with 888041, 360/80R24 TRI 2 MAVT</b> <b>Front Tires</b>		9002774P46	\$3,557.00

**T5 AUTO COMMAND - LESS FASTPICK  
 US PRICE LIST**

Shipping wheels					
	8399801	Non-Returnable Shipping Wheel		9000494P52	\$634.00

**HYDRAULICS**

REAR REMOTES

SD_T8270 REAR REMOTES					
	759365	3 MECH RR (3NC) <b>3 MECH REAR REMOTES (3NC)</b>		9000763P62	\$979.00
	743685	4 Mech Rear Remotes (2NC+2C) <b>4 mechanical rear remote valves, two with configurable detents</b>		9001705P08	\$2,186.00
	759690	2 RR MV + 1 EH.RR.V. <b>2 RR MV (CONFIG. DETENT) + 1 ELECTRO HYD. REAR REMOTE VALVES</b>		9001448P46	\$1,857.00
	759691	2 RR MV + 2 EH.RR.V. <b>2 RR MV (CONFIG. DETENT) + 2 ELECTRO HYD. REAR REMOTE VALVES</b>		9002219P88	\$2,846.00

COMPLETE LOADER READY

SD_T8110 LOADER BRACKETS					
	744711	L/Loader Ready w/MMV		(903907P80)	(\$5,010.00)
	758353	Loader Ready + 2 EH MMV + Joy <b>Complete Loader Ready - 2 Function TPS Mount Bracket Set (with Grill Guard), 2 Function MMV, and Joystick with Proportional Rocker (Includes valve, joystick, hose kit, &amp; MC 4)</b>			No Charge
	758354	Loader Ready + 3 EH MMV + Joy <b>Complete Loader Ready - 3 Function TPS Mount Bracket Set (with Grill Guard), 3 Function MMV, and Joystick with Proportional Rocker (Includes valve, joystick, hose kit, &amp; MC 4+2)</b>			No Charge

JOYSTICK CONTROL

SD_T7780 JOYSTICK					
	758069	Joystick with Rocker Switch			No Charge
	759694	L/JOYSTICK W/EDC POD 759694		(901742P52)	(\$2,234.00)

**T5 AUTO COMMAND - LESS FASTPICK  
 US PRICE LIST**

**MID MOUNT VALVES**

SD\_T7790 MID-MOUNT VALVES

	759695	L/MID-MOUNT VALVES 759695		(902130P96)	(\$2,732.00)
	743689	2 Electronic MMV			No Charge
	743690	3 Electronic MMV		9001133P34	\$1,453.00

**PTO**

**REAR PTO**

SD\_T8710 FENDERS PTO CONTROL

	743680	Fender EDC/PTO/Rem Valv Contrl		9000247P26	\$317.00
--	--------	--------------------------------	--	------------	----------

**WEIGHTS**

**FRONT**

SD\_T2150 FRONT BALLAST

	759769	10 FRONT WEIGHTS <b>Qty. 10, 88 lb. (40 Kg) weights                  totaling 882 lb. (400 Kg)</b>		9000988P26	\$1,267.00
--	--------	---	--	------------	------------

**REAR WHEEL WEIGHTS**

SD\_T4960 WHEEL WEIGHTS

	759137	2X150KG + 2X250KG Wheel Weight		9001332P24	\$1,708.00
--	--------	--------------------------------	--	------------	------------

**CAB OPTION**

SD\_T4820 HEADLAND SYSTEM

	758592	Adv. Headland Ctrl Config EHR <b>Allows End of Row functions to be precisely programmed.                  More user-friendly than basic End of Row controls                  Allows operator to choose within the display which remote is                  operated on the MultiFunction handle                  Requires display</b>		9000826P80	\$1,060.00
--	--------	--	--	------------	------------

SD\_T9360 RR MIRRORS

	759153	2 Telescopic Mirrors 759153			No Charge
	759154	2 Tele/Heat/Rem Adj Mirror		9000055P38	\$71.00

**T5 AUTO COMMAND - LESS FASTPICK  
 US PRICE LIST**

**SEATS**

**SD\_T8500 SEAT**

	758485	Deluxe Seat Air Susp Heated		9001666P08	\$2,136.00
	758671	Deluxe Air and Heated Cushion		9000362P70	\$465.00
	759735	DLX AIR SUSP. + BELT			No Charge

**LIGHTS**

**SD\_T9130 WORK LAMPS**

	758594	12 LED High Power Hi-Roof <b>High Power LED lights produce 1950 Lumens</b> <b>4 front roof-mounted LED work lights</b> <b>4 rear roof-mounted LED work lights</b> <b>2 front grab rail-mounted LED work lights</b> <b>2 rear post-mounted LED work lights</b> <b>2 halogen road hood lights</b> <b>2 halogen work hood lights</b>		9001333P80	\$1,710.00
	758596	16 LED High Power Hi-Roof		9002668P38	\$3,421.00

**SD\_T9146 ROTARY BEACON**

	758491	Twin Beacon		9000712P14	\$913.00
--	--------	-------------	--	------------	----------

**MONITOR BRACKETS**

**SD\_T9223 RH WINDOW BAR MOUNT**

	758153	Monitor Mounting Bracket.		9000127P92	\$164.00
--	--------	---------------------------	--	------------	----------

**SD\_T9230 CLIMATE CONTROL**

	759728	AIR CONDITIONING 759728		(900618P54)	(\$793.00)
--	--------	-------------------------	--	-------------	------------

**AUTO GUIDANCE**

**AUTO GUIDANCE READY**

**SD\_T6300 STEERING OR AUTOGUIDANCE READY**

	759185	Autoguidance Ready <b>Autoguidance Ready prewired for guidance does not include Nav III Controller and NH 372 receiver</b>		9004532P58	\$5,811.00
--	--------	---	--	------------	------------

**T5 AUTO COMMAND - LESS FASTPICK  
 US PRICE LIST**

SD\_T7616 AUTOGUIDANCE NAV/CO

	762158	AUTOGUID. - Lv.1 Includes Auto Guidance Ready offering with Nav III Controller and NH 372 receiver activated to WAAS level accuracy (Level 1)		9012575P16	\$16,122.00
	762159	AUTOGUID. - Lv.2 Includes Auto Guidance Ready offering with Nav III Controller and NH 372 receiver activated to OmniSTAR HP/G2/XP & CenterPoint RTX level accuracy (Level 2)		9014914P38	\$19,121.00

**MISCELLANEOUS**

FENDERS REAR

SD\_T8700 FENDERS

	743777	Standard fenders with extensn			No Charge
	759767	NARROW FNDRS L/EXT.			No Charge

RADAR

SD\_T7580 RADAR

	758501	Radar NAR		9000696P54	\$893.00
--	--------	-----------	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	758535	Spanish NAR			No Charge
	759101	French NAR			No Charge