



## WORKMASTER™ Series Tractor Index

<u>EQUIPMENT DESCRIPTION</u>	<u>LATEST REVISION</u>	<u>PAGE NUMBER</u>
<u>Index</u>	10/04/21	1
<u>Models</u>		
WORKMASTER 55, 65, 75 STANDARD CAB FAST PICK	10/04/21	2
WORKMASTER 55, 65, 75 STANDARD CAB HIVIS FAST PICK	10/04/21	6
WORKMASTER 55, 65, 75 DELUXE CAB FAST PICK	10/04/21	10
WORKMASTER 55, 65, 75 DELUXE CAB HIVIS FAST PICK	10/04/21	15
WORKMASTER 75 STANDARD ROPS FAST PICK	10/04/21	20
WORKMASTER 75 DELUXE ROPS FAST PICK	10/04/21	24
WORKMASTER 55, 65, 75 WEST COAST FAST PICK	10/04/21	28
WORKMASTER 55, 65, 75 CAB A LA CARTE	10/04/21	32
WORKMASTER 75 ROPS A LA CARTE	10/04/21	38
WORKMASTER 55, 65, 75 Special Order	10/04/21	43
PARTS DIVISION SUPPLIED ACCESSORIES	10/04/21	45



**WORKMASTER 55-75 STANDARD CAB FAST PICK  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

**DIESEL ENGINE**

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

**ALL MODELS:**

Tier B Emissions Compliant:  
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

**TRANSMISSION:**

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

**STEERING/BRAKES:**

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

**4WD FRONT AXLE:**

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

**REAR AXLE**

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

**HYDRAULIC SYSTEM:**

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55-75 STANDARD CAB FAST PICK  
US PRICE LIST**

## Standard Equipment

### 3-POINT LIFT SYSTEM:

Right hand console mounted  
lever control  
Mechanical Draft Control  
3,500 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

### ELECTRICAL:

(1) 840 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
25 amp socket  
12V power socket (cigarette lighter)

### INSTRUMENTATION:

Analog Instrumentation with warning  
lights for turn signals, high beam,  
work lights, side lights, rear PTO,  
4WD, differential lock, low fuel,  
alternator, oil pressure, brake fluid,  
grid heater & hand brake  
Gauges for fuel level, engine  
temperature and tachometer  
Digital Readout for PTO speed,  
ground speed, battery & hours

### CAB LIGHTING:

Front: (2) Halogen Headlights  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

### TIRES:

11.2x24 R1 Front  
16.9X30 R1 Rear

### OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS  
ROPS protected, 4 post, flat deck  
platform with heat and air  
conditioning, tinted windshield,  
retractable sun screen, front wiper  
and washer, rear wiper and washer,  
two doors with locks, two external  
mirrors, hinged rear window (opens  
completely)  
Steering Wheel - adjustable tilt  
Seat - Cloth covered air suspension,  
operator's presence sensor,  
retractable seat belt and arm rests  
Instructor Seat  
Suspended pedals  
Radio, speakers, and antenna

### MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem  
Toolbox

### WARRANTY:

New Holland Standard Warranty Applies

### LOADER:

#### 550LU NON SELF-LEVELING

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 2,425 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 23.7"  
Reach @ Ground Level: 85.8"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 58 degrees  
Skid Steer style bucket attach  
72" Bucket

**WORKMASTER 55-75 STANDARD CAB FAST PICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB	9045169P80	\$57,910.00
WORKMASTER 65 T4A	Cab	6,239 LB	9047382P66	\$60,747.00
WORKMASTER 75 T4A	Cab	6,239 LB	9049594P74	\$63,583.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0590XX	Standard Cab Fast Pick <b>Standard Cab Fast Pick pricing includes:</b> Cab with openable Black-Out panel 2 rear remotes 550LU NSL loader with SSL quick attach and 72" bucket  <b>Allows for choice of the following:</b> Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Rear weights: 4 rear wheel weights OR NO rear wheel weights		(902237P82)	(\$2,869.00)
---------	---	--	-------------	--------------

**TIRES**

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge
8290904	12.5/80-18 10PR R4 <b>Matching rear tires = 19.5L-24 10 PR R4 (8391904)</b>		9000577P20	\$740.00

**WORKMASTER 55-75 STANDARD CAB FAST PICK  
 US PRICE LIST**

REAR

SD\_T4950 REAR WHEELS AND TIRES

	8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge
	8391904	19.5L-24 10 PR R4 <b>Matching front tires = 12.5/80-18 10PR R4 (8290904)</b>		9000265P98	\$341.00

**WEIGHTS**

REAR

SD\_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights <b>Two weights per side (110 lbs each) = 440 lbs total</b>		9000525P72	\$674.00
--	--------	---	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD\_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 55-75 STD CAB H1VIS FAST PIC  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- Best-in-Class value cab - HiVis panel
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

**DIESEL ENGINE**

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

**ALL MODELS:**

Tier B Emissions Compliant:  
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

**TRANSMISSION:**

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

**STEERING/BRAKES:**

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

**4WD FRONT AXLE:**

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

**REAR AXLE**

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

**HYDRAULIC SYSTEM:**

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55-75 STD CAB HIVIS FAST PIC  
US PRICE LIST**

## Standard Equipment

### 3-POINT LIFT SYSTEM:

Right hand console mounted  
lever control  
Mechanical Draft Control  
3,500 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

### ELECTRICAL:

(1) 840 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
25 amp socket  
12V power socket (cigarette lighter)

### INSTRUMENTATION:

Analog Instrumentation with warning  
lights for turn signals, high beam,  
work lights, side lights, rear PTO,  
4WD, differential lock, low fuel,  
alternator, oil pressure, brake fluid,  
grid heater & hand brake  
Gauges for fuel level, engine  
temperature and tachometer  
Digital Readout for PTO speed,  
ground speed, battery & hours

### CAB LIGHTING:

Front: (2) Halogen Headlights  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

### TIRES:

11.2x24 R1 Front  
16.9X30 R1 Rear

### OPERATOR PROTECTIVE STRUCTURE:

#### CAB MODELS

ROPS protected, 4 post, flat deck  
platform with heat and air  
conditioning, tinted windshield,  
retractable sun screen, high visibility  
panel, front wiper and washer, rear  
wiper and washer, two doors with  
locks, two external mirrors, hinged rear  
window (opens completely)  
Steering Wheel - adjustable tilt  
Seat - Cloth covered air suspension,  
operator's presence sensor,  
retractable seat belt and arm rests  
Instructor Seat  
Suspended pedals  
Radio, speakers, and antenna

### MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem  
Toolbox

### WARRANTY:

New Holland Standard Warranty Applies

### LOADER:

#### 550LU NON SELF-LEVELING

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 2,425 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 23.7"  
Reach @ Ground Level: 85.8"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 58 degrees  
Skid Steer style bucket attach  
72" Bucket

**WORKMASTER 55-75 STD CAB H1VIS FAST PIC  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB	9045169P80	\$57,910.00
WORKMASTER 65 T4A	Cab	6,239 LB	9047382P66	\$60,747.00
WORKMASTER 75 T4A	Cab	6,239 LB	9049594P74	\$63,583.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0592XX	Standard Cab HiVis Fast Pick <b>Standard Cab HiVis Fast Pick pricing includes:</b> Cab with openable Clear HiVis panel 2 rear remotes 550LU NSL loader with SSL quick attach and 72" bucket  <b>Allows for choice of the following:</b> Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Rear weights: 4 rear wheel weights OR NO rear wheel weights		(901915P68)	(\$2,456.00)
---------	---	--	-------------	--------------

**TIRES**

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge
8290904	12.5/80-18 10PR R4 <b>Matching rear tires = 19.5L-24 10 PR R4 (8391904)</b>		9000577P20	\$740.00



**WORKMASTER 55-75 STD CAB HIVIS FAST PIC  
 US PRICE LIST**

REAR

SD\_T4950 REAR WHEELS AND TIRES

	8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge
	8391904	19.5L-24 10 PR R4 <b>Matching front tires = 12.5/80-18 10PR R4 (8290904)</b>		9000265P98	\$341.00

**WEIGHTS**

REAR

SD\_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights <b>Two weights per side (110 lbs each) = 440 lbs total</b>		9000525P72	\$674.00
--	--------	---	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD\_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 55-75 DELUXE CAB FAST PICK  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

**DIESEL ENGINE**

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

**ALL MODELS:**

Tier B Emissions Compliant:  
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

**TRANSMISSION:**

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

**STEERING/BRAKES:**

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

**4WD FRONT AXLE:**

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

**REAR AXLE**

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

**HYDRAULIC SYSTEM:**

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(3) Open Center Remote Valves with

Detent & Kickout on #2 & #3

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55-75 DELUXE CAB FAST PICK  
US PRICE LIST**

## Standard Equipment

**3-POINT LIFT SYSTEM:**

Right hand console mounted  
lever control  
Mechanical Draft Control  
3,500 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

**ELECTRICAL:**

(1) 840 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
25 amp socket  
12V power socket (cigarette lighter)

**INSTRUMENTATION:**

Analog Instrumentation with warning  
lights for turn signals, high beam,  
work lights, side lights, rear PTO,  
4WD, differential lock, low fuel,  
alternator, oil pressure, brake fluid,  
grid heater & hand brake  
Gauges for fuel level, engine  
temperature and tachometer  
Digital Readout for PTO speed,  
ground speed, battery & hours

**CAB LIGHTING:**

Front: (2) Halogen Headlights  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

**TIRES:**

11.2x24 R1 Front  
16.9X30 R1 Rear

**MISCELLANEOUS:**

Pivoting Engine Hood  
SMV Emblem  
4 x 110 lb Rear Wheel Weights  
Toolbox

**OPERATOR PROTECTIVE STRUCTURE:**

CAB MODELS  
ROPS protected, 4 post, flat deck  
platform with heat and air  
conditioning, tinted windshield,  
retractable sun screen, front wiper  
and washer, rear wiper and washer,  
two doors with locks, two external  
mirrors, hinged rear window (opens  
completely)  
Steering Wheel - adjustable tilt  
Seat - Cloth covered air suspension,  
operator's presence sensor,  
retractable seat belt and arm rests  
Instructor Seat  
Suspended pedals  
Radio, speakers, and antenna

**WARRANTY:**

New Holland Standard Warranty Applies



**WORKMASTER 55-75 DELUXE CAB FAST PICK  
US PRICE LIST**

**Standard Equipment**

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 2,425 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 23.7"  
Reach @ Ground Level: 85.8"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 58 degrees  
Skid Steer or Euro style bucket attach  
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 3,086 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 20.8"  
Reach @ Ground Level: 79.9"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style bucket attach  
72" Bucket

**WORKMASTER 55-75 DELUXE CAB FAST PICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB	9045169P80	\$57,910.00
WORKMASTER 65 T4A	Cab	6,239 LB	9047382P66	\$60,747.00
WORKMASTER 75 T4A	Cab	6,239 LB	9049594P74	\$63,583.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0591XX	Deluxe Cab Fast Pick <b>Deluxe Cab Fast Pick pricing includes:</b> Cab with openable Black-Out panel 3 rear remotes 4 rear wheel weights  <b>Allows for choice of the following:</b> <b>Tires:</b> 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front <b>Loader:</b> 550LU NSL loader with SSL quick attach and 72" bucket OR 555LU MSL loader with EURO quick attach and 72" bucket		(901021P02)	(\$1,309.00)
---------	--	--	-------------	--------------

**TIRES**

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge
8290904	12.5/80-18 10PR R4 <b>Matching rear tires = 19.5L-24 10 PR R4 (8391904)</b>		9000577P20	\$740.00



**WORKMASTER 55-75 DELUXE CAB FAST PICK  
 US PRICE LIST**

**REAR**

SD\_T4950 REAR WHEELS AND TIRES

	8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge
	8391904	19.5L-24 10 PR R4 <b>Matching front tires = 12.5/80-18 10PR R4 (8290904)</b>		9000265P98	\$341.00

**LOADER**

**LOADER**

SD\_T8110 LOADER BRACKETS

	344739	LOADER-NSL.2F.SSLWGG <b>550LU</b> Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344742	LOADER-MSL-2F-EU-WGG <b>555LU</b> Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000944P58	\$1,211.00

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD\_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- Best-in-Class value cab - HiVis panel
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

**DIESEL ENGINE**

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

**ALL MODELS:**

Tier B Emissions Compliant:  
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

**TRANSMISSION:**

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

**STEERING/BRAKES:**

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

**4WD FRONT AXLE:**

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

**REAR AXLE**

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

**HYDRAULIC SYSTEM:**

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(3) Open Center Remote Valves with

Detent & Kickout on #2 & #3

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK  
US PRICE LIST**

**Standard Equipment**

**3-POINT LIFT SYSTEM:**

- Right hand console mounted lever control
- Mechanical Draft Control
- 3,500 Pounds Lift Capacity
- Category II Ends
- Telescopic Stabilizers
- Flexible Lower Link Ends

**ELECTRICAL:**

- (1) 840 cca Heavy-Duty Battery
- 120 amp Alternator
- 7-pin Outlet for trailer/implement lighting and signals
- 25 amp socket
- 12V power socket (cigarette lighter)

**INSTRUMENTATION:**

- Analog Instrumentation with warning lights for turn signals, high beam, work lights, side lights, rear PTO, 4WD, differential lock, low fuel, alternator, oil pressure, brake fluid, grid heater & hand brake
- Gauges for fuel level, engine temperature and tachometer
- Digital Readout for PTO speed, ground speed, battery & hours

**CAB LIGHTING:**

- Front: (2) Halogen Headlights  
(2) cab mounted worklights
- Rear: (2) cab mounted worklights
- Turn Signals/Flashers/Rear Lights

**TIRES:**

- 11.2x24 R1 Front
- 16.9X30 R1 Rear

**MISCELLANEOUS:**

- Pivoting Engine Hood
- SMV Emblem
- 4 x 110 lb Rear Wheel Weights
- Toolbox

**OPERATOR PROTECTIVE STRUCTURE:**

**CAB MODELS**

- ROPS protected, 4 post, flat deck platform with heat and air conditioning, tinted windshield, retractable sun screen, high visibility panel, front wiper and washer, rear wiper and washer, two doors with locks, two external mirrors, hinged rear window (opens completely)
- Steering Wheel - adjustable tilt
- Seat - Cloth covered air suspension, operator's presence sensor, retractable seat belt and arm rests
- Instructor Seat
- Suspended pedals
- Radio, speakers, and antenna

**WARRANTY:**

New Holland Standard Warranty Applies





**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK  
US PRICE LIST**

### Standard Equipment

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 2,425 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 23.7"  
Reach @ Ground Level: 85.8"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 58 degrees  
Skid Steer or Euro style bucket attach  
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 3,086 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 20.8"  
Reach @ Ground Level: 79.9"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style bucket attach  
72" Bucket

**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB	9045169P80	\$57,910.00
WORKMASTER 65 T4A	Cab	6,239 LB	9047382P66	\$60,747.00
WORKMASTER 75 T4A	Cab	6,239 LB	9049594P74	\$63,583.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0593XX	Deluxe Cab HiVis Fast Pick <b>Deluxe Cab HiVis Fast Pick pricing includes:</b> Cab with openable Clear HiVis panel 3 rear remotes 4 rear wheel weights  <b>Allows for choice of the following:</b> <b>Tires:</b> 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front <b>Loader:</b> 550LU NSL loader with SSL quick attach and 72" bucket OR 555LU MSL loader with EURO quick attach and 72" bucket		(900697P32)	(\$894.00)
---------	--	--	-------------	------------

**TIRES**

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge
8290904	12.5/80-18 10PR R4 <b>Matching rear tires = 19.5L-24 10 PR R4 (8391904)</b>		9000577P20	\$740.00



**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK  
 US PRICE LIST**

**REAR**

SD\_T4950 REAR WHEELS AND TIRES

	8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge
	8391904	19.5L-24 10 PR R4 <b>Matching front tires = 12.5/80-18 10PR R4 (8290904)</b>		9000265P98	\$341.00

**LOADER**

**LOADER**

SD\_T8110 LOADER BRACKETS

	344739	LOADER-NSL.2F.SSLWGG <b>550LU</b> Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344742	LOADER-MSL-2F-EU-WGG <b>555LU</b> Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000944P58	\$1,211.00

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD\_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 75 STANDARD ROPS FAST PICK  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- Best-in-Class value ROPS platform
- Mechanical suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

**DIESEL ENGINE**

Workmaster 75  
74 Gross Engine hp  
60 PTO hp @ 2300 rpm  
3 Cyl Turbocharged Engine  
179 cu in (2.9 L) Displacement

**ALL MODELS:**

Tier B Emissions Compliant:  
(CEGR + DOC)  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Powercore Dry Air Cleaner  
Under Hood Muffler  
Vertical Exhaust  
21.6 gal Fuel Tank  
2 function mid mount valve & joystick  
16.9X30 rear and 11.2X24 front tires

**TRANSMISSION:**

LH side steering column mounted  
Power Shuttle  
12 Forward and 12 Reverse Speeds  
(4) Synchronized Gears  
(3) Non-synchronized Ranges  
(2) clutches, 5 wet disc plates  
FWD - 25 mph (40 KPH)  
Speed varies with tire selection  
Hand Operated Park Brake

**STEERING/BRAKES:**

Hydrostatic Power Steering  
Brakes- Hydraulically assisted wet disc

**4WD FRONT AXLE:**

Limited Slip  
Electro-Hydraulic engagement standard  
Adjustable Tread Width from 51.5 in.  
to 79.4 in.

**REAR AXLE**

Flange Type  
Adjustable Tread Width 60.1 in.  
to 76.0 in.

**HYDRAULIC SYSTEM:**

Open Center System  
Dual Gear Pumps  
Implement Pump: 12.5 gpm (47.7 L)  
Steering Pump: 7.6 gpm (28.7 L)  
Total Flow: 20.1 gpm (76.4 L)  
(2) Open Center Remote Valves with  
Detent & Kickout on #2

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

Fully Independent  
Flip-up PTO Shaft Guard

**4WD power shuttle:**

-540 RPM hydraulic wet clutch  
-Hydraulic engagement  
-Wet clutch  
1-3/8 in. 6 splines

**3-POINT LIFT SYSTEM:**

Right hand console mounted  
lever control  
Mechanical Draft Control  
3,500 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends



**WORKMASTER 75 STANDARD ROPS FAST PICK  
US PRICE LIST**

## Standard Equipment

**ELECTRICAL:**

(1) 840 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
25 amp socket  
12V power socket (cigarette lighter)

**INSTRUMENTATION:**

Analog Instrumentation with warning  
lights for turn signals, high beam,  
work lights, side lights, rear PTO,  
4WD, differential lock, low fuel,  
alternator, oil pressure, brake fluid,  
grid heater & hand brake  
Gauges for fuel level, engine  
temperature and tachometer  
Digital Readout for PTO speed,  
ground speed, battery & hours

**ROPS LIGHTING:**

Front: (2) Halogen Headlights  
Rear: (1) Right hand fender  
mounted worklights  
Turn Signals/Flashers/Rear Lights

**OPERATOR PROTECTIVE STRUCTURE:****ROPS MODELS**

2-Post Foldable ROPS with ISO-  
mounted flat deck platform  
Steering Wheel - adjustable tilt  
Seat - Vinyl mechanical suspension,  
operator's presence sensor,  
retractable seat belts and arm rests  
Suspended pedals  
Locking brake pedals

**TIRES:**

11.2x24 R1 Front  
16.9X30 R1 Rear

**MISCELLANEOUS:**

Pivoting Engine Hood  
SMV Emblem  
Toolbox

**WARRANTY:**

New Holland Standard Warranty Applies

**LOADER:****550LU NON SELF-LEVELING**

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 2,425 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 23.7"  
Reach @ Ground Level: 85.8"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 58 degrees  
Skid Steer style bucket attach  
72" Bucket

**WORKMASTER 75 STANDARD ROPS FAST PICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 75 T4A	Rops	6,239 LB	9042727P62	\$54,779.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0588XX	STANDARD FAST PICK <b>Standard ROPS Fast Pick pricing includes:</b> 2 rear remotes 550LU NSL loader with SSL quick attach and 72" bucket  <b>Allows for choice of the following:</b> <b>Tires:</b> 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front <b>Rear weights:</b> 4 rear wheel weights OR NO rear wheel weights		(902237P82)	(\$2,869.00)
---------	---	--	-------------	--------------

**TIRES**

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge
8290904	12.5/80-18 10PR R4 <b>Matching rear tires = 19.5L-24 10 PR R4 (8391904)</b>		9000577P20	\$740.00

REAR

SD\_T4950 REAR WHEELS AND TIRES

8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge
---------	---	--	--	-----------



**WORKMASTER 75 STANDARD ROPS FAST PICK  
US PRICE LIST**

	8391904	19.5L-24 10 PR R4 <b>Matching front tires = 12.5/80-18 10PR R4 (8290904)</b>		9000265P98	\$341.00
--	---------	---	--	------------	----------

**WEIGHTS**

REAR

SD\_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights <b>Two weights per side (110 lbs each) = 440 lbs total</b>		9000525P72	\$674.00
--	--------	---	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD\_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 75 DELUXE ROPS FAST PICK  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- Best-in-Class value ROPS platform
- Mechanical suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

**DIESEL ENGINE**

Workmaster 75  
74 Gross Engine hp  
60 PTO hp @ 2300 rpm  
3 Cyl Turbocharged Engine  
179 cu in (2.9 L) Displacement

**ALL MODELS:**

Tier B Emissions Compliant:  
(CEGR + DOC)  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Powercore Dry Air Cleaner  
Under Hood Muffler  
Vertical Exhaust  
21.6 gal Fuel Tank  
2 function mid mount valve & joystick  
16.9X30 rear and 11.2X24 front tires

**TRANSMISSION:**

LH side steering column mounted  
Power Shuttle  
12 Forward and 12 Reverse Speeds  
(4) Synchronized Gears  
(3) Non-synchronized Ranges  
(2) clutches, 5 wet disc plates  
FWD - 25 mph (40 KPH)  
Speed varies with tire selection  
Hand Operated Park Brake

**STEERING/BRAKES:**

Hydrostatic Power Steering  
Brakes- Hydraulically assisted wet disc

**4WD FRONT AXLE:**

Limited Slip  
Electro-Hydraulic engagement standard  
Adjustable Tread Width from 51.5 in.  
to 79.4 in.

**REAR AXLE**

Flange Type  
Adjustable Tread Width 60.1 in.  
to 76.0 in.

**HYDRAULIC SYSTEM:**

Open Center System  
Dual Gear Pumps  
Implement Pump: 12.5 gpm (47.7 L)  
Steering Pump: 7.6 gpm (28.7 L)  
Total Flow: 20.1 gpm (76.4 L)  
(3) Open Center Remote Valves with  
Detent & Kickout on #2 & #3

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

Fully Independent  
Flip-up PTO Shaft Guard

**4WD power shuttle:**

-540 RPM hydraulic wet clutch  
-Hydraulic engagement  
-Wet clutch  
1-3/8 in. 6 splines

**3-POINT LIFT SYSTEM:**

Right hand console mounted  
lever control  
Mechanical Draft Control  
3,500 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends





**WORKMASTER 75 DELUXE ROPS FAST PICK  
US PRICE LIST**

## Standard Equipment

### ELECTRICAL:

(1) 840 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
25 amp socket  
12V power socket (cigarette lighter)

### INSTRUMENTATION:

Analog Instrumentation with warning  
lights for turn signals, high beam,  
work lights, side lights, rear PTO,  
4WD, differential lock, low fuel,  
alternator, oil pressure, brake fluid,  
grid heater & hand brake  
Gauges for fuel level, engine  
temperature and tachometer  
Digital Readout for PTO speed,  
ground speed, battery & hours

### ROPS LIGHTING:

Front: (2) Halogen Headlights  
Rear: (1) Right hand fender  
mounted worklights  
Turn Signals/Flashers/Rear Lights

### OPERATOR PROTECTIVE STRUCTURE:

#### ROPS MODELS

2-Post Foldable ROPS with ISO-  
mounted flat deck platform  
Steering Wheel - adjustable tilt  
Seat - Vinyl mechanical suspension,  
operator's presence sensor,  
retractable seat belts and arm rests  
Suspended pedals  
Locking brake pedals

### TIRES:

11.2x24 R1 Front  
16.9X30 R1 Rear

### MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem  
4 x 110 lb Rear Wheel Weights  
Toolbox

### WARRANTY:

New Holland Standard Warranty Applies

### LOADER:

#### 550LU NON SELF-LEVELING

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 2,425 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 23.7"  
Reach @ Ground Level: 85.8"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 58 degrees  
Skid Steer or Euro style bucket attach  
72" Bucket

#### 555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 3,086 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 20.8"  
Reach @ Ground Level: 79.9"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style bucket attach  
72" Bucket

**WORKMASTER 75 DELUXE ROPS FAST PICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 75 T4A	Rops	6,239 LB	9042727P62	\$54,779.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0589XX	Deluxe ROPS Fast Pick <b>Deluxe ROPS Fast Pick pricing includes:</b> 3 rear remotes 4 rear wheel weights  <b>Allows for choice of the following:</b> <b>Tires:</b> 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front <b>Loader:</b> 550LU NSL loader with SSL quick attach and 72" bucket OR 555LU MSL loader with EURO quick attach and 72" bucket		(901021P02)	(\$1,309.00)
---------	---	--	-------------	--------------

**TIRES**

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge
8290904	12.5/80-18 10PR R4 <b>Matching rear tires = 19.5L-24 10 PR R4 (8391904)</b>		9000577P20	\$740.00

REAR

SD\_T4950 REAR WHEELS AND TIRES

8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge
---------	---	--	--	-----------



**WORKMASTER 75 DELUXE ROPS FAST PICK  
 US PRICE LIST**

	8391904	19.5L-24 10 PR R4 <b>Matching front tires = 12.5/80-18 10PR R4 (8290904)</b>		9000265P98	\$341.00
--	---------	---	--	------------	----------

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

	344739	LOADER-NSL.2F.SSLWGG <b>550LU</b> Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344742	LOADER-MSL-2F-EU-WGG <b>555LU</b> Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000944P58	\$1,211.00

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD\_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 55-75 WEST COAST FAST PICK  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- Best-in-Class value cab & ROPS platform
- 12x12 power shuttle transmission
- Lift-O-Matic
- 1 Auxiliary lift ram (4,000 lbs)
- 8 Front weights
- 3 Rear remotes

**DIESEL ENGINE**

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

**ALL MODELS:**

Tier B Emissions Compliant:

(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

**TRANSMISSION:**

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

**STEERING/BRAKES:**

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

**4WD FRONT AXLE:**

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

**REAR AXLE**

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

**HYDRAULIC SYSTEM:**

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55-75 WEST COAST FAST PICK  
US PRICE LIST**

## Standard Equipment

### 3-POINT LIFT SYSTEM:

Right hand console mounted  
lever control  
Mechanical Draft Control  
4,000 Pounds Lift Capacity with  
1 Auxiliary Lift Ram  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

### ELECTRICAL:

(1) 840 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
25 amp socket  
12V power socket (cigarette lighter)

### INSTRUMENTATION:

Analog Instrumentation with warning  
lights for turn signals, high beam,  
work lights, side lights, rear PTO,  
4WD, differential lock, low fuel,  
alternator, oil pressure, brake fluid,  
grid heater & hand brake  
Gauges for fuel level, engine  
temperature and tachometer  
Digital Readout for PTO speed,  
ground speed, battery & hours

### CAB LIGHTING:

Front: (2) Halogen Headlights  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

### ROPS LIGHTING:

Front: (2) Halogen Headlights  
Rear: (1) Right hand fender  
mounted worklights  
Turn Signals/Flashers/Rear Lights

### OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS  
ROPS protected, 4 post, flat deck  
platform with heat and air  
conditioning, tinted windshield,  
retractable sun screen, front wiper  
and washer, rear wiper and washer,  
two doors with locks, two external  
mirrors, hinged rear window (opens  
completely)  
Steering Wheel - adjustable tilt  
Seat - Cloth covered air suspension,  
operator's presence sensor,  
retractable seat belt and arm rests  
Instructor Seat  
Suspended pedals  
Radio, speakers, and antenna

### ROPS MODELS

2-Post Foldable ROPS with ISO-  
mounted flat deck platform  
Steering Wheel - adjustable tilt  
Seat - Vinyl mechanical suspension,  
operator's presence sensor,  
retractable seat belts and arm rests  
Suspended pedals  
Locking brake pedals

### TIRES:

11.2x24 R1 Front  
16.9X30 R1 Rear

### MISCELLANEOUS:

Pivoting Engine Hood  
SMV Emblem  
Toolbox

### WARRANTY:

New Holland Standard Warranty Applies

**WORKMASTER 55-75 WEST COAST FAST PICK  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB	9045169P80	\$57,910.00
WORKMASTER 65 T4A	Cab	6,239 LB	9047382P66	\$60,747.00
WORKMASTER 75 T4A	Cab	6,239 LB	9049594P74	\$63,583.00
WORKMASTER 75 T4A	Rops	6,239 LB	9042727P62	\$54,779.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**FAST PICK CONFIGURATION**

SD\_T9980 PACKAGING

X0596XX	West Coast Less Loader <b>West Coast Less Loader Fast Pick pricing includes:</b> 3 rear remotes Less loader and mid mount valve 8 front weights Auxiliary lift ram  <b>Cab Models:</b> Cab with openable Black-Out panel  <b>Allows for choice of the following:</b> <b>Tires:</b> 16.9x30 R1 rear with 11.2x24 R1 front OR Front and rear shipping wheels <b>Rear weights:</b> 4 rear wheel weights OR NO rear wheel weights		(906851P52)	(\$8,784.00)
---------	---	--	-------------	--------------

**TIRES**

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

8299801	Non-Return Ship Wheels - 4WD		(900656P76)	(\$842.00)
8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge



**WORKMASTER 55-75 WEST COAST FAST PICK  
US PRICE LIST**

REAR

SD\_T4950 REAR WHEELS AND TIRES

	8399801	Non-Returnable Shipping Wheel		(901270P62)	(\$1,629.00)
	8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge

**WEIGHTS**

REAR

SD\_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights <b>Two weights per side (110 lbs each) = 440 lbs total</b>		9000525P72	\$674.00
--	--------	---	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD\_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 55, 65, 75 CAB A LA CARTE  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

**DIESEL ENGINE**

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

**ALL MODELS:**

Tier B Emissions Compliant:  
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

**TRANSMISSION:**

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

**STEERING/BRAKES:**

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

**4WD FRONT AXLE:**

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

**REAR AXLE**

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

**HYDRAULIC SYSTEM:**

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines





**WORKMASTER 55, 65, 75 CAB A LA CARTE  
US PRICE LIST**

**Standard Equipment**

**3-POINT LIFT SYSTEM:**

Right hand console mounted  
lever control  
Mechanical Draft Control  
3,500 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends

**ELECTRICAL:**

(1) 840 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
25 amp socket  
12V power socket (cigarette lighter)

**INSTRUMENTATION:**

Analog Instrumentation with warning  
lights for turn signals, high beam,  
work lights, side lights, rear PTO,  
4WD, differential lock, low fuel,  
alternator, oil pressure, brake fluid,  
grid heater & hand brake  
Gauges for fuel level, engine  
temperature and tachometer  
Digital Readout for PTO speed,  
ground speed, battery & hours

**CAB LIGHTING:**

Front: (2) Halogen Headlights  
(2) cab mounted worklights  
Rear: (2) cab mounted worklights  
Turn Signals/Flashers/Rear Lights

**TIRES:**

11.2x24 R1 Front  
16.9X30 R1 Rear

**MISCELLANEOUS:**

Pivoting Engine Hood  
SMV Emblem  
Toolbox

**OPERATOR PROTECTIVE STRUCTURE:**

CAB MODELS  
ROPS protected, 4 post, flat deck  
platform with heat and air  
conditioning, tinted windshield,  
retractable sun screen, front wiper  
and washer, rear wiper and washer,  
two doors with locks, two external  
mirrors, hinged rear window (opens  
completely)  
Steering Wheel - adjustable tilt  
Seat - Cloth covered air suspension,  
operator's presence sensor,  
retractable seat belt and arm rests  
Instructor Seat  
Suspended pedals  
Radio, speakers, and antenna

**WARRANTY:**

New Holland Standard Warranty Applies



**WORKMASTER 55, 65, 75 CAB A LA CARTE  
US PRICE LIST**

**Standard Equipment**

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 2,425 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 23.7"  
Reach @ Ground Level: 85.8"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 58 degrees  
Skid Steer or Euro style bucket attach  
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 3,086 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 20.8"  
Reach @ Ground Level: 79.9"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style bucket attach  
72" Bucket

**WORKMASTER 55, 65, 75 CAB A LA CARTE  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB	9045169P80	\$57,910.00
WORKMASTER 65 T4A	Cab	6,239 LB	9047382P66	\$60,747.00
WORKMASTER 75 T4A	Cab	6,239 LB	9049594P74	\$63,583.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**OPERATOR PLATFORM**

SD\_T9200 OPERATOR STRUCTURE #1

	333606	CAB FIX SCREEN OPEN <b>Cab with openable high visibility panel</b>		9000322P14	\$413.00
--	--------	---	--	------------	----------

**TIRES**

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

	8299801	Non-Return Ship Wheels - 4WD		(900656P76)	(\$842.00)
	8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge
	8290904	12.5/80-18 10PR R4 <b>Matching rear tires = 19.5L-24 10 PR R4 (8391904)</b>		9000577P20	\$740.00

REAR

SD\_T4950 REAR WHEELS AND TIRES

	8399801	Non-Returnable Shipping Wheel		(901270P62)	(\$1,629.00)
	8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge
	8391904	19.5L-24 10 PR R4 <b>Matching front tires = 12.5/80-18 10PR R4 (8290904)</b>		9000265P98	\$341.00

**WORKMASTER 55, 65, 75 CAB A LA CARTE  
 US PRICE LIST**

**HYDRAULICS**

REAR REMOTES

SD\_T8270 REAR REMOTES

	335413	2 Rem. Valve (1 S/D) <b>2 rear remote valves</b>  <b>Float, Detent and kickout on 2nd remote</b>			No Charge
	335640	3 REMOTE VALVE <b>3 rear remote valves</b>  <b>Float, Detent and kickout on 2nd and 3rd remotes</b>		9000691P08	\$886.00

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

	344739	LOADER-NSL.2F.SSLWGG <b>550LU</b> <b>Non self leveling with skid steer style attachment</b> <b>Includes:</b> -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344743	LOADER-NSL-2F-EU-WGG <b>550LU</b> <b>Non self leveling with euro style attachment</b> <b>Includes:</b> -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344738	LOADER-MSL.2F.SSLWGG <b>555LU</b> <b>Mechanical self leveling with skid steer style attachment</b> <b>Includes:</b> -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000944P58	\$1,211.00

**WORKMASTER 55, 65, 75 CAB A LA CARTE  
 US PRICE LIST**

	344742	LOADER-MSL-2F-EU-WGG <b>555LU</b> <b>Mechanical self leveling with euro style attachment</b> <b>Includes:</b> -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000944P58	\$1,211.00
--	--------	---	--	------------	------------

**3-POINT HITCH**

REAR 3 POINT HITCH

SD\_T8200 HITCH

	332785	MDC Hitch aux lift ram <b>1 Auxiliary lift ram = 4,000 lbs total lift capacity</b>		9000392P34	\$503.00
--	--------	---	--	------------	----------

**WEIGHTS**

REAR

SD\_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights <b>Two weights per side (110 lbs each) = 440 lbs total</b>		9000525P72	\$674.00
--	--------	---	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD\_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 75 ROPS A LA CARTE  
US PRICE LIST**

## Standard Equipment

**KEY SELLING POINTS:**

- Best-in-Class value ROPS platform
- Mechanical suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

**DIESEL ENGINE**

Workmaster 75  
74 Gross Engine hp  
60 PTO hp @ 2300 rpm  
3 Cyl Turbocharged Engine  
179 cu in (2.9 L) Displacement

**ALL MODELS:**

Tier B Emissions Compliant:  
(CEGR + DOC)  
Electronic Injection Bosch  
High-pressure Common Rail System  
Electric Engine Shutoff  
Hand and Foot Throttle Controls  
Grid Heater Starting Aid  
Powercore Dry Air Cleaner  
Under Hood Muffler  
Vertical Exhaust  
21.6 gal Fuel Tank  
2 function mid mount valve & joystick  
16.9X30 rear and 11.2X24 front tires

**TRANSMISSION:**

LH side steering column mounted  
Power Shuttle  
12 Forward and 12 Reverse Speeds  
(4) Synchronized Gears  
(3) Non-synchronized Ranges  
(2) clutches, 5 wet disc plates  
FWD - 25 mph (40 KPH)  
Speed varies with tire selection  
Hand Operated Park Brake

**STEERING/BRAKES:**

Hydrostatic Power Steering  
Brakes- Hydraulically assisted wet disc

**4WD FRONT AXLE:**

Limited Slip  
Electro-Hydraulic engagement standard  
Adjustable Tread Width from 51.5 in.  
to 79.4 in.

**REAR AXLE**

Flange Type  
Adjustable Tread Width 60.1 in.  
to 76.0 in.

**HYDRAULIC SYSTEM:**

Open Center System  
Dual Gear Pumps  
Implement Pump: 12.5 gpm (47.7 L)  
Steering Pump: 7.6 gpm (28.7 L)  
Total Flow: 20.1 gpm (76.4 L)  
(2) Open Center Remote Valves with  
Detent & Kickout on #2

**REAR DIFFERENTIAL LOCK:**

Mechanically Engaged

**PTO:**

Fully Independent  
Flip-up PTO Shaft Guard

**4WD power shuttle:**

-540 RPM hydraulic wet clutch  
-Hydraulic engagement  
-Wet clutch  
1-3/8 in. 6 splines

**3-POINT LIFT SYSTEM:**

Right hand console mounted  
lever control  
Mechanical Draft Control  
3,500 Pounds Lift Capacity  
Category II Ends  
Telescopic Stabilizers  
Flexible Lower Link Ends



**WORKMASTER 75 ROPS A LA CARTE  
US PRICE LIST**

## Standard Equipment

**ELECTRICAL:**

(1) 840 cca Heavy-Duty Battery  
120 amp Alternator  
7-pin Outlet for trailer/implement lighting  
and signals  
25 amp socket  
12V power socket (cigarette lighter)

**INSTRUMENTATION:**

Analog Instrumentation with warning  
lights for turn signals, high beam,  
work lights, side lights, rear PTO,  
4WD, differential lock, low fuel,  
alternator, oil pressure, brake fluid,  
grid heater & hand brake  
Gauges for fuel level, engine  
temperature and tachometer  
Digital Readout for PTO speed,  
ground speed, battery & hours

**ROPS LIGHTING:**

Front: (2) Halogen Headlights  
Rear: (1) Right hand fender  
mounted worklights  
Turn Signals/Flashers/Rear Lights

**OPERATOR PROTECTIVE STRUCTURE:****ROPS MODELS**

2-Post Foldable ROPS with ISO-  
mounted flat deck platform  
Steering Wheel - adjustable tilt  
Seat - Vinyl mechanical suspension,  
operator's presence sensor,  
retractable seat belts and arm rests  
Suspended pedals  
Locking brake pedals

**TIRES:**

11.2x24 R1 Front  
16.9X30 R1 Rear

**MISCELLANEOUS:**

Pivoting Engine Hood  
SMV Emblem  
Toolbox

**WARRANTY:**

New Holland Standard Warranty Applies

**LOADER:****550LU NON SELF-LEVELING**

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 2,425 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 23.7"  
Reach @ Ground Level: 85.8"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 58 degrees  
Skid Steer or Euro style bucket attach  
72" Bucket

**555LU MECHANICAL SELF-LEVELING**

Maximum Lift Height @  
pivot pin: 131.8"  
Dump Clearance @ 45 deg: 98.8"  
Digging Depth: 5.9"  
Lift Capacity @ 800mm: 3,086 LBS  
Breakout Force @ 800mm: TBC LBS  
Reach @ Max Lift Height @ 45  
deg: 20.8"  
Reach @ Ground Level: 79.9"  
Bucket Rollback Angle: 42 degrees  
Bucket Dump Angle: 60 degrees  
Skid Steer or Euro style bucket attach  
72" Bucket

**WORKMASTER 75 ROPS A LA CARTE  
 US PRICE LIST**

**Models**

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 75 T4A	Rops	6,239 LB	9042727P62	\$54,779.00

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**TIRES**

FRONT

SD\_T4940 FRONT WHEELS AND TIRES

8299801	Non-Return Ship Wheels - 4WD		(900656P76)	(\$842.00)
8232304	11.2 x 24 6PR R1 <b>Matching rear tires = 16.9-30 (8355304)</b>			No Charge
8290904	12.5/80-18 10PR R4 <b>Matching rear tires = 19.5L-24 10 PR R4 (8391904)</b>		9000577P20	\$740.00

REAR

SD\_T4950 REAR WHEELS AND TIRES

8399801	Non-Returnable Shipping Wheel		(901270P62)	(\$1,629.00)
8355304	16.9-30 6PR R1 <b>Matching front tires = 11.2-24 (8232304)</b>			No Charge
8391904	19.5L-24 10 PR R4 <b>Matching front tires = 12.5/80-18 10PR R4 (8290904)</b>		9000265P98	\$341.00

**HYDRAULICS**

REAR REMOTES

SD\_T8270 REAR REMOTES

335413	2 Rem. Valve (1 S/D) <b>2 rear remote valves</b> <b>Float, Detent and kickout on 2nd remote</b>			No Charge
335640	3 REMOTE VALVE <b>3 rear remote valves</b> <b>Float, Detent and kickout on 2nd and 3rd remotes</b>		9000691P08	\$886.00



**WORKMASTER 75 ROPS A LA CARTE  
 US PRICE LIST**

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

	344739	LOADER-NSL.2F.SSLWGG <b>550LU</b> Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344743	LOADER-NSL-2F-EU-WGG <b>550LU</b> Non self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344738	LOADER-MSL.2F.SSLWGG <b>555LU</b> Mechanical self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000944P58	\$1,211.00
	344742	LOADER-MSL-2F-EU-WGG <b>555LU</b> Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000944P58	\$1,211.00

**3-POINT HITCH**

REAR 3 POINT HITCH

SD\_T8200 HITCH

	332785	MDC Hitch aux lift ram <b>1 Auxiliary lift ram = 4,000 lbs total lift capacity</b>		9000392P34	\$503.00
--	--------	---	--	------------	----------



**WORKMASTER 75 ROPS A LA CARTE  
US PRICE LIST**

**WEIGHTS**

REAR

SD\_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights <b>Two weights per side (110 lbs each) = 440 lbs total</b>		9000525P72	\$674.00
--	--------	---	--	------------	----------

**OPERATOR'S MANUALS**

SD\_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD\_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 55, 65, 75 SPECIAL ORDER  
US PRICE LIST**

**Standard Equipment**

Special Custom Order Options

Requires YSR, YRT or YGR order codes.

Please place an order in the system with the configuration as close as possible to your desired configuration and then contact Dealer Sales Support with the following information to get the order configuration changed:

1. Vehicle Number(s)
2. Order Code(s) desired for each vehicle number

The orders will then be sent to have the order configurations changed to include your desired order code(s).

**Factory Supplied Options**

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

**OPERATOR PLATFORM**

SD\_T8520 INSTRUCTIONAL SEAT

	390865	Less Instructional Seat <b>Removes instructor seat option from Cab Models</b>		(900460P98)	(\$591.00)
--	--------	--	--	-------------	------------



**WORKMASTER 55, 65, 75 SPECIAL ORDER  
US PRICE LIST**

**LOADER**

LOADER

SD\_T8110 LOADER BRACKETS

		391489	Less Loader Bracket <b>No Loader</b>  Removes mid mount valve, loader & bucket		(906599P58)	(\$8,461.00)
--	--	--------	---	--	-------------	--------------

**WEIGHTS**

FRONT

SD\_T2150 FRONT BALLAST

		330183	FRONT WEIGHT 8X30KG <b>Front weight carrier (42 lbs) + 8 front weights (66 lbs) = 572 lbs</b>  <b>NOT COMPATIBLE with front loader</b>		9000904P02	\$1,159.00
--	--	--------	---	--	------------	------------

PARTS DIVISION SUPPLIED ACCESSORIES FOR WORKMASTER 55, 65 & 75 Tractors				
Part Number	Description	WORKMASTER 75	WORKMASTER 55, 65, 75	Notes
	<b>HYDRAULICS</b>	<b>ROPS</b>	<b>CAB</b>	
731345550	3 Rear Remotes	X	X	
	<b>ELECTRICAL</b>			
731231551	Rotary Beacon Kit	X		Connects to 12V power socket
731231552	Rotary Beacon Kit		X	Connects to 12V power socket
719216551	Engine Block Heater Kit	X	X	
	<b>PLATFORM</b>			
718130551	Monitor Mounting Bracket		X	Requires Cab
710857552	Canopy	X		
	<b>LOADER</b>			
731200551	3rd Function Diverter Valve	X	X	
731197551	Loader Suspension	X	X	
731198551	3rd Function Diverter Valve + Loader Suspension	X	X	