



WORKMASTER™ Series Tractor Index

<u>EQUIPMENT DESCRIPTION</u>	<u>LATEST REVISION</u>	<u>PAGE NUMBER</u>
<u>Index</u>	10/04/21	1
<u>Models</u>		
WORKMASTER 95, 105, 120 STANDARD CAB FAST PICK	10/04/21	2
WORKMASTER 95, 105, 120 CAB MOWING FAST PICK	10/04/21	8
WORKMASTER 95, 105, 120 A LA CARTE CAB	10/04/21	14
WORKMASTER 95, 105, 120 STANDARD ROPS FAST PICK	10/04/21	20
WORKMASTER 95, 105, 120 CALIFORNIA SPECIAL ROPS FAST PICK	10/04/21	27
WORKMASTER 95, 105, 120 LOW PROFILE ALL PURPOSE FAST PICK	10/04/21	32
WORKMASTER 95, 105, 120 POULTRY NSL/NO LOADER FAST PICKS	10/04/21	33
WORKMASTER 95, 105, 120 ROPS MOWING FAST PICK	10/04/21	39
WORKMASTER 95, 105, 120 A LA CARTE ROPS	10/04/21	46
TIRE CHART	10/04/21	58



**WORKMASTER 95-120 CAB FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Vertical Exhaust
29 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
12 Forward and 12 Reverse Speeds
Creeper ready
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH)
Speed varies with tire selection
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 66.5 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.8 in. to 79.5 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2 &
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 CAB FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 900 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

12.4x24 R1 Front
18.4X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS
ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer style bucket attach
84" bucket



**WORKMASTER 95-120 CAB FAST PICK
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Cab	MFD	6,768 LB	9063488P10	\$81,395.00
WORKMASTER 105 TIER4	Cab	MFD	7,936 LB	9065959P14	\$84,563.00
WORKMASTER 120 TIER4	Cab	MFD	7,253 LB	9069027P66	\$88,497.00



**WORKMASTER 95-120 CAB FAST PICK
 US PRICE LIST**

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

FAST PICK CONFIGURATION

SD_T9980 PACKAGING

XF9911X	Standard Cab Fast Pick Standard Cab Fast Pick pricing includes: Cab with openable Black-Out panel 632TL NSL loader with SSL quick attach and 84" bucket Allows for choice of the following: Hydraulic Pumps - 16.9 gpm (64 L) = (342056) - 21.6 gpm (82 L) = (347541) Rear Remotes - 2 Rear Remotes = (762204) - 3 Rear Remotes = (762205) 3-PT Hitch Capacity - 3200 lb (1451 kg) = (342053) - 6200 lb (2812 kg) = (342054) PTO - 540 RPM = (759271) - 540/1000 RPM = (759273) Tires: - 18.4-30 R1 rear (8930605)with 12.4-24 R1 front (8230506) OR - 16.4-34 R1 rear (8930601) with 13.6-24 R1 front (8230505) Rear weights: - No rear wheel weights - 4 rear wheel weights = (762028)		(903153P54)	(\$4,043.00)
---------	---	--	-------------	--------------

OPERATOR PLATFORM

SD_T9200 OPERATOR STRUCTURE #1

Cab				
762204	HVAC CAB 2 REMOTE PS Cab with TWO rear remotes			No Charge
762205	HVAC CAB 3 REMOTE PS Cab with THREE rear remotes		9000681P72	\$874.00



**WORKMASTER 95-120 CAB FAST PICK
 US PRICE LIST**

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag					
	8230506	FRONT 12.4 - 24 R1 Requires 18.4-30 rear tires			No Charge
	8230505	13.6 -24 R1 Requires 16.9-34 rear tires		9000187P20	\$240.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag					
	8930605	REAR 18.4 - 30 R1 Requires 12.4-24 4WD front			No Charge
	8930601	REAR 16.9 - 34 R1 Requires 13.6-24 4WD front		(900119P34)	(\$153.00)

HYDRAULICS

PUMP

SD_T8230 HYD PUMP

	347541	HYD PUMP 21 gpm 21.6 GPM (82 LPM) Implement Pump		9000468P00	\$600.00
	342056	HYD PUMP 70,0 LPM 16.9 GPM (64 LPM) Implement Pump			No Charge

PTO

REAR PTO

SD_T8010 PTO

	759271	540 RPM W CAP			No Charge
	759273	540-1000 RPM W CAP		9000452P40	\$580.00

3-POINT HITCH

SD_T8200 HITCH

	342053	2000KG/4409LBS-Telesc/COMBI 3-PT lift capacity of 3,200 lbs.			No Charge
	342054	3500KG/7716LBS-Telesc/COMBI 2 auxiliary lift rams to increase rear hitch capacity to 6,200 lbs.		9000852P54	\$1,093.00



**WORKMASTER 95-120 CAB FAST PICK
 US PRICE LIST**

WEIGHTS

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

	762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires		9000537P42	\$689.00
--	--------	--	--	------------	----------

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

	342076	French (Canada)			No Charge
	342077	Spanish			No Charge



**WORKMASTER 95-120 CAB MOWING FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Vertical Exhaust
29 gal Fuel Tank
2.9 gal DEF Tank

TRANSMISSION:

LH side steering column mounted
Power Shuttle
12 Forward and 12 Reverse Speeds
Creeper ready
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH)
Speed varies with tire selection
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 66.5 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.8 in. to 79.5 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(3) Open Center Remote Valves with
Detent & Kickout on #2 &
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 CAB MOWING FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 900 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

12.4x24 R1 Front
18.4X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies



**WORKMASTER 95-120 CAB MOWING FAST PICK
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Cab	MFD	6,768 LB	9063488P10	\$81,395.00
WORKMASTER 105 TIER4	Cab	MFD	7,936 LB	9065959P14	\$84,563.00
WORKMASTER 120 TIER4	Cab	MFD	7,253 LB	9069027P66	\$88,497.00



**WORKMASTER 95-120 CAB MOWING FAST PICK
 US PRICE LIST**

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

FAST PICK CONFIGURATION

SD_T9980 PACKAGING

	<p>XF9922X Cab Mowing Fast Pick</p> <p>Cab Mowing Fast Pick pricing includes:</p> <ul style="list-style-type: none"> 3 Rear Remotes Less loader and mid-mount valve <p>Allows for choice of the following:</p> <p>Hydraulic Pumps</p> <ul style="list-style-type: none"> - 16.9 gpm (64 L) = (342056) - 21.6 gpm (82 L) = (347541) <p>3-PT Hitch Capacity</p> <ul style="list-style-type: none"> - 3200 lb (1451 kg) = (342053) - 6200 lb (2812 kg) = (342054) <p>PTO</p> <ul style="list-style-type: none"> - 540 RPM = (759271) - 540/540E RPM = (759272) - 540/1000 RPM = (759273) <p>Mid Mount Valve/Loader</p> <ul style="list-style-type: none"> - No Mid-Mount Valve or Loader - Mid-Mount Valve and Joystick only = (762699) - Loader Ready = (762698) <p>Tires:</p> <ul style="list-style-type: none"> - 18.4-30 R1 rear (8930605)with 12.4-24 R1 front (8230506) OR -16.9-34 R1 rear (8930601) with 13.6-24 R1 front (8230505) <p>Rear weights:</p> <ul style="list-style-type: none"> - No rear wheel weights - 4 rear wheel weights = (762028) - 8 rear wheel weights = (759650) <p>Front weights:</p> <ul style="list-style-type: none"> - No front weights - 8 front weights = (342069) - 10 front weights = (342070) 		(909272P64)	(\$11,888.00)
--	---	--	-------------	---------------



**WORKMASTER 95-120 CAB MOWING FAST PICK
 US PRICE LIST**

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag					
	8230506	FRONT 12.4 - 24 R1 Requires 18.4-30 rear tires			No Charge
	8230505	13.6 -24 R1 Requires 16.9-34 rear tires		9000187P20	\$240.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag					
	8930605	REAR 18.4 - 30 R1 Requires 12.4-24 4WD front			No Charge
	8930601	REAR 16.9 - 34 R1 Requires 13.6-24 4WD front		(900119P34)	(\$153.00)

HYDRAULICS

PUMP

SD_T8230 HYD PUMP

	347541	HYD PUMP 21 gpm 21.6 GPM (82 LPM) Implement Pump		9000468P00	\$600.00
	342056	HYD PUMP 70,0 LPM 16.9 GPM (64 LPM) Implement Pump			No Charge

LOADER

LOADER

SD_T8110 LOADER BRACKETS

	343421	LESS LOADER/LESS LOADER READY Less loader			No Charge
	762699	LESS LOADER W/ MMV Mid Mount Valve and Joystick ONLY.		9001261P26	\$1,617.00
	762698	LOADER READY 762698 Complete loader ready includes: - Horizontal and Vertical TPS loader brackets - 2 function mid mount valve and joystick - Hoses from mid mount valve to vertical bracket - Grill guard		9005539P56	\$7,102.00



**WORKMASTER 95-120 CAB MOWING FAST PICK
 US PRICE LIST**

PTO

REAR PTO

SD_T8010 PTO

	759271	540 RPM W CAP			No Charge
	759272	540-540E RPM W CAP		9000387P66	\$497.00
	759273	540-1000 RPM W CAP		9000452P40	\$580.00

3-POINT HITCH

SD_T8200 HITCH

	342053	2000KG/4409LBS-Telesc/COMBI 3-PT lift capacity of 3,200 lbs.			No Charge
	342054	3500KG/7716LBS-Telesc/COMBI 2 auxiliary lift rams to increase rear hitch capacity to 6,200 lbs.		9000852P54	\$1,093.00

WEIGHTS

FRONT WEIGHTS

SD_T2151 WEIGHT PACK

	342070	110KgFCW/10X40-510kg Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs		9001065P48	\$1,366.00
	342069	110KgFC W/8X40-430kg Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs		9000852P54	\$1,093.00

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

	759650	4X55or32Kg EACH SIDE 4 (110 lb) rear weights per side = 440 lbs total for all rear tires sizes except 500/60-22.5 4 (70 lb) rear weights per side = 280 lbs total for 500/60-22.5 rear tires		9001073P28	\$1,376.00
--	--------	--	--	------------	------------

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

	342075	English (USA)			No Charge
	342076	French (Canada)			No Charge
	342077	Spanish			No Charge



**WORKMASTER 95-120 A LA CARTE CAB
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Vertical Exhaust
29 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
12 Forward and 12 Reverse Speeds
Creeper ready
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH)
Speed varies with tire selection
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 63.8 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.9 in. to 79.7 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2 &
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 A LA CARTE CAB
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 900 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

12.4x24 R1 Front
18.4X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS
ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer style bucket attach
84" bucket



**WORKMASTER 95-120 A LA CARTE CAB
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Cab	MFD	6,768 LB	9063488P10	\$81,395.00
WORKMASTER 105 TIER4	Cab	MFD	7,936 LB	9065959P14	\$84,563.00
WORKMASTER 120 TIER4	Cab	MFD	7,253 LB	9069027P66	\$88,497.00



**WORKMASTER 95-120 A LA CARTE CAB
 US PRICE LIST**

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

OPERATOR PLATFORM

SD_T9200 OPERATOR STRUCTURE #1

Cab				
	762204	HVAC CAB 2 REMOTE PS Cab with TWO rear remotes		No Charge
	762205	HVAC CAB 3 REMOTE PS Cab with THREE rear remotes	9000681P72	\$874.00

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag				
	8220701	11.2 - 24 R1 Requires 16.9-30 rear tires	(900050P70)	(\$65.00)
	8230506	FRONT 12.4 - 24 R1 Requires 18.4-30 rear tires		No Charge
	8230505	13.6 -24 R1 Requires 16.9-34 rear tires	9000187P20	\$240.00
4WD Front Tires - Ind				
	8230503	FRONT 12.5 - 18 R4 Requires 19.5L-24 rear tires	9000596P70	\$765.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag				
	8930602	REAR 16.9 - 30 R1 Requires 11.2-24 4WD front	9000255P84	\$328.00
	8930605	REAR 18.4 - 30 R1 Requires 12.4-24 4WD front		No Charge
	8930601	REAR 16.9 - 34 R1 Requires 13.6-24 4WD front	(900119P34)	(\$153.00)
Rear tires - Ind				
	8930603	REAR 19.5 - 24 R4 Requires 12.5/80-18 4WD front tires	9000533P52	\$684.00



**WORKMASTER 95-120 A LA CARTE CAB
US PRICE LIST**

HYDRAULICS

PUMP

SD_T8230 HYD PUMP

	347541	HYD PUMP 21 gpm 21.6 GPM (82 LPM) Implement Pump		9000468P00	\$600.00
	342056	HYD PUMP 70,0 LPM 16.9 GPM (64 LPM) Implement Pump			No Charge

LOADER

LOADER

SD_T8110 LOADER BRACKETS

	343421	LESS LOADER/LESS LOADER READY Less loader		(906801P60)	(\$8,720.00)
	762699	LESS LOADER W/ MMV Mid Mount Valve and Joystick ONLY.		(905539P56)	(\$7,102.00)
	762698	LOADER READY 762698 Complete loader ready includes: - Horizontal and Vertical TPS loader brackets - 2 function mid mount valve and joystick - Hoses from mid mount valve to vertical bracket - Grill guard		(901261P26)	(\$1,617.00)
	763052	632TL AND 84 BKT SSL 763052 632TL Non self leveling loader with 84" SSL Bucket			No Charge

PTO

REAR PTO

SD_T8010 PTO

	759271	540 RPM W CAP			No Charge
	759272	540-540E RPM W CAP		9000387P66	\$497.00
	759273	540-1000 RPM W CAP		9000452P40	\$580.00

3-POINT HITCH

SD_T8200 HITCH

	342053	2000KG/4409LBS-Telesc/COMBI 3-PT lift capacity of 3,200 lbs.			No Charge
	342054	3500KG/7716LBS-Telesc/COMBI 2 auxiliary lift rams to increase rear hitch capacity to 6,200 lbs.		9000852P54	\$1,093.00



**WORKMASTER 95-120 A LA CARTE CAB
 US PRICE LIST**

WEIGHTS

FRONT WEIGHTS

SD_T2151 WEIGHT PACK

	342070	110KgFCW/10X40-510kg Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs		9001065P48	\$1,366.00
	342069	110KgFC W/8X40-430kg Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs		9000852P54	\$1,093.00

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

	762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires		9000537P42	\$689.00
	759650	4X55or32Kg EACH SIDE 4 (110 lb) rear weights per side = 440 lbs total for all rear tires sizes except 500/60-22.5 4 (70 lb) rear weights per side = 280 lbs total for 500/60-22.5 rear tires		9001073P28	\$1,376.00

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

	342076	French (Canada)			No Charge
	342077	Spanish			No Charge



**WORKMASTER 95-120 ROPS FASTPICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Semi straddle ROPS
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
Creep ready
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH) speed may vary
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 66.5 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.8 in. to 79.5 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 ROPS FASTPICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

12.4x24 R1 Front
18.4X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS
2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING
Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer bucket attach
84" bucket



**WORKMASTER 95-120 ROPS FASTPICK
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	8,367 LB	9051019P02	\$65,409.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB	9053490P06	\$68,577.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB	9056558P58	\$72,511.00



**WORKMASTER 95-120 ROPS FASTPICK
 US PRICE LIST**

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

FAST PICK CONFIGURATION

SD_T9980 PACKAGING

	XF9913X	Standard ROPS Fast Pick ROPS Standard Fast Pick pricing includes: 632TL NSL loader with SSL quick attach and 84" bucket Allows for choice of the following: Hydraulic Pumps - 16.9 gpm (64 L) = (342056) - 21.6 gpm (82 L) = (347541) Rear Remotes - 2 Rear Remotes = (762052) - 3 Rear Remotes = (762053) 3-PT Hitch Capacity - 3200 lb (1451 kg) = (342053) - 6200 lb (2812 kg) = (342054) PTO - 540 RPM = (759271) - 540/1000 RPM = (759273) Tires: - 18.4-30 R1 rear (8930605)with 12.4-24 R1 front (8230506) OR - 16.4-34 R1 rear (8930601) with 13.6-24 R1 front (8230505) Rear weights: - No rear wheel weights - 4 rear wheel weights = (762028)		(903153P54)	(\$4,043.00)
--	---------	--	--	-------------	--------------



**WORKMASTER 95-120 ROPS FASTPICK
 US PRICE LIST**

		XF9917X	Low Profile All Purpose Fast P Low Profile All Purpose Fast Pick ROPS includes: Allows for choice of the following: Hydraulic Pumps - 16.9 gpm (64 L) = (342056) - 21.6 gpm (82 L) = (347541) Rear Remotes - 2 Rear Remotes = (762052) - 3 Rear Remotes = (762053) 3-PT Hitch Capacity - 3200 lb (1451 kg) = (342053) - 6200 lb (2812 kg) = (342054) PTO - 540 RPM = (759271) - 540/1000 RPM = (759273) Mid Mount Valve/Loader - No Mid-Mount Valve or Loader - Loader Ready = (762698) - Full Loader 632LA NSL with SSL QA 84" Bucket = (762057) Tires: - 16.9-30 R1 rear (8930602) with 11.2-24 R1 front (8220701) OR - 500/60-22.5 rear (8310501) with 11.5/80-15.3 front (8811501) OR - 19.5-24 R4 rear (8930603) with 12.5-18 front (8230503) Rear weights: - No rear wheel weights - 4 rear wheel weights = (762028) Front weights: - No front weights - 8 front weights = (342069) - 10 front weights = (342070)		(903153P54)	(\$4,043.00)
--	--	---------	--	--	-------------	--------------

OTHER EQUIPMENT

SD_T1010 ENGINE OPTIONS

		343472	VISCOUS FAN			No Charge
		343473	REVERSE FAN		9001790P10	\$2,295.00



**WORKMASTER 95-120 ROPS FASTPICK
 US PRICE LIST**

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag					
	8230506	FRONT 12.4 - 24 R1 Requires 18.4-30 rear tires			No Charge
	8230505	13.6 -24 R1 Requires 16.9-34 rear tires		9000187P20	\$240.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag					
	8930605	REAR 18.4 - 30 R1 Requires 12.4-24 4WD front			No Charge
	8930601	REAR 16.9 - 34 R1 Requires 13.6-24 4WD front		(900119P34)	(\$153.00)

HYDRAULICS

REAR REMOTES

SD_T8270 REAR REMOTES

	762052	2 REMOTE 762052 2 rear remotes for Open Platform with foldable ROPS Float on remote 1 Extend and retract detent and kick-out on remote 2			No Charge
	762053	3 REMOTE 762053 3 rear remotes for Open Platform with foldable ROPS Float on remote 1 & 3 Extend and retract detent and kick-out on remote 2		9000681P72	\$874.00

PUMP

SD_T8230 HYD PUMP

	347541	HYD PUMP 21 gpm 21.6 GPM (82 LPM) Implement Pump		9000468P00	\$600.00
	342056	HYD PUMP 70,0 LPM 16.9 GPM (64 LPM) Implement Pump			No Charge



**WORKMASTER 95-120 ROPS FASTPICK
 US PRICE LIST**

PTO

REAR PTO

SD_T8010 PTO

	759271	540 RPM W CAP			No Charge
	759273	540-1000 RPM W CAP		9000452P40	\$580.00

3-POINT HITCH

SD_T8200 HITCH

	342053	2000KG/4409LBS-Telesc/COMBI 3-PT lift capacity of 3,200 lbs.			No Charge
	342054	3500KG/7716LBS-Telesc/COMBI 2 auxiliary lift rams to increase rear hitch capacity to 6,200 lbs.		9000852P54	\$1,093.00

WEIGHTS

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

	762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires		9000537P42	\$689.00
--	--------	--	--	------------	----------

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

	342076	French (Canada)			No Charge
	342077	Spanish			No Charge



**WORKMASTER 95-120 CALIFORNIA SPECIAL ROP
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Low profile semi straddle ROPS
- Low profile air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- 21.6 gpm hydraulic pump
- 3 rear remote valves
- 6200 lb. 3-pt lift capacity
- 540/1000 rpm PTO

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank

TRANSMISSION:

LH side steering column mounted
Power Shuttle
Creeper ready
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH) speed may vary
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 63.8 in. to 71.6 in.

REAR AXLE

Flange Type
Tread Width: 63.9 in. to 79.7 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 21.6 gpm (82 L)
Steering Pump: 9.7 gpm (36 L)
Total Flow: 31.3 gpm (118 L)
(3) Open Center Remote Valves with
Detent & Kickout on #2
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540/1000 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 CALIFORNIA SPECIAL ROP
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
6,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

TIRES:

11.5/80-15.3 R1 Front
500/60-22.5 R1 Rear
OR
12.5/80-18 R4 Front
19.5L24 R4 Rear
OR
11.2-24 R1 Front
16.9-30 R1 Rear

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

Weights:

10 Front weight + carrier (1,034 lb.)
4 Rear wheel weight (2 per wheel)

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

WARRANTY:

New Holland Standard Warranty Applies

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS



**WORKMASTER 95-120 CALIFORNIA SPECIAL ROP
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	8,367 LB	9051019P02	\$65,409.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB	9053490P06	\$68,577.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB	9056558P58	\$72,511.00



**WORKMASTER 95-120 CALIFORNIA SPECIAL ROP
 US PRICE LIST**

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

FAST PICK CONFIGURATION

SD_T9980 PACKAGING

	XF9919X	California Special ROPS Fast P California Special ROPS Fast Pick includes: Hydraulic Pump - 21.6 gpm (82 L) = (347541) Rear Remotes - 3 Rear Remotes = (762053) 3-PT Hitch Capacity - 6200 lb (2812 kg) = (342054) PTO - 540/1000 RPM = (759273) Mid Mount Valve/Loader - No Mid-Mount Valve or Loader Tires: - 19.5-24 R4 rear (8930603) with 12.5-18 front (8230503) Rear weights: - 2x55 EACH side (762028) Front weights: - 10 Front weights = (342070) Allows for choice of the following: Engine Fan - Reversing Fan (343473) Tires: - 500/60-22.5 rear (8310501) with 11.5/80-15.3 front (8811501) OR - 16.9-30 R1 rear (8930602) with 11.2-24 R1 front (8220701) Manuals: - French (372076) - Spanish (342077)		(909955P14)	(\$12,763.00)
--	---------	--	--	-------------	---------------



**WORKMASTER 95-120 CALIFORNIA SPECIAL ROP
 US PRICE LIST**

OTHER EQUIPMENT

SD_T1010 ENGINE OPTIONS

	343472	VISCOUS FAN			No Charge
	343473	REVERSE FAN		9001790P10	\$2,295.00

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag					
	8220701	11.2 - 24 R1 Requires 16.9-30 rear tires		(900050P70)	(\$65.00)
	8811501	11.5/80-15.3 R1 Requires 500/60-22.5 rear tires (ROPS ONLY)		9000596P70	\$765.00
4WD Front Tires - Ind					
	8230503	FRONT 12.5 - 18 R4 Requires 19.5L-24 rear tires		9000596P70	\$765.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag					
	8930602	REAR 16.9 - 30 R1 Requires 11.2-24 4WD front		9000255P84	\$328.00
	8310501	500/60-22.5 R1 Requires 11.5/80-15.3 4WD front tires (ROPS ONLY)		9000533P52	\$684.00
Rear tires - Ind					
	8930603	REAR 19.5 - 24 R4 Requires 12.5/80-18 4WD front tires		9000533P52	\$684.00

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

	342076	French (Canada)			No Charge
	342077	Spanish			No Charge



**WORKMASTER 95-120 AP LOW PRO FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Low profile semi straddle ROPS
- Low profile air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
Creeper ready
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH) speed may vary
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 63.8 in. to 71.6 in.

REAR AXLE

Flange Type
Tread Width: 63.9 in. to 79.7 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 AP LOW PRO FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS
2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

TIRES:

11.5/80-15.3 R1 Front
500/60-22.5 R1 Rear
OR
12.5/80-18 R4 Front
19.5L24 R4 Rear
OR
11.2-24 Front
16.9x30 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies



**WORKMASTER 95-120 AP LOW PRO FAST PICK
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	8,367 LB	9051019P02	\$65,409.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB	9053490P06	\$68,577.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB	9056558P58	\$72,511.00



**WORKMASTER 95-120 AP LOW PRO FAST PICK
 US PRICE LIST**

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

FAST PICK CONFIGURATION

SD_T9980 PACKAGING

	XF9917X	<p>Low Profile All Purpose Fast P Low Profile All Purpose Fast Pick ROPS includes:</p> <p>Allows for choice of the following: Hydraulic Pumps - 16.9 gpm (64 L) = (342056) - 21.6 gpm (82 L) = (347541) Rear Remotes - 2 Rear Remotes = (762052) - 3 Rear Remotes = (762053) 3-PT Hitch Capacity - 3200 lb (1451 kg) = (342053) - 6200 lb (2812 kg) = (342054) PTO - 540 RPM = (759271) - 540/1000 RPM = (759273) Mid Mount Valve/Loader - No Mid-Mount Valve or Loader - Loader Ready = (762698) - Full Loader 632LA NSL with SSL QA 84" Bucket = (762057) Tires: - 16.9-30 R1 rear (8930602) with 11.2-24 R1 front (8220701) OR - 500/60-22.5 rear (8310501) with 11.5/80-15.3 front (8811501) OR - 19.5-24 R4 rear (8930603) with 12.5-18 front (8230503) Rear weights: - No rear wheel weights - 4 rear wheel weights = (762028) Front weights: - No front weights - 8 front weights = (342069) - 10 front weights = (342070)</p>		(903153P54)	(\$4,043.00)
--	---------	---	--	-------------	--------------



**WORKMASTER 95-120 AP LOW PRO FAST PICK
 US PRICE LIST**

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag					
	8811501	11.5/80-15.3 R1 Requires 500/60-22.5 rear tires (ROPS ONLY)		9000596P70	\$765.00
4WD Front Tires - Ind					
	8230503	FRONT 12.5 - 18 R4 Requires 19.5L-24 rear tires		9000596P70	\$765.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag					
	8930602	REAR 16.9 - 30 R1 Requires 11.2-24 4WD front		9000255P84	\$328.00
	8310501	500/60-22.5 R1 Requires 11.5/80-15.3 4WD front tires (ROPS ONLY)		9000533P52	\$684.00
Rear tires - Ind					
	8930603	REAR 19.5 - 24 R4 Requires 12.5/80-18 4WD front tires		9000533P52	\$684.00

HYDRAULICS

REAR REMOTES

SD_T8270 REAR REMOTES

	762052	2 REMOTE 762052 2 rear remotes for Open Platform with foldable ROPS Float on remote 1 Extend and retract detent and kick-out on remote 2			No Charge
	762053	3 REMOTE 762053 3 rear remotes for Open Platform with foldable ROPS Float on remote 1 & 3 Extend and retract detent and kick-out on remote 2		9000681P72	\$874.00

PUMP

SD_T8230 HYD PUMP

	347541	HYD PUMP 21 gpm 21.6 GPM (82 LPM) Implement Pump		9000468P00	\$600.00
--	--------	--	--	------------	----------



**WORKMASTER 95-120 AP LOW PRO FAST PICK
 US PRICE LIST**

	342056	HYD PUMP 70,0 LPM 16.9 GPM (64 LPM) Implement Pump			No Charge
--	--------	--	--	--	-----------

LOADER

LOADER

SD_T8110 LOADER BRACKETS

	762698	LOADER READY 762698 Complete loader ready includes: - Horizontal and Vertical TPS loader brackets - 2 function mid mount valve and joystick - Hoses from mid mount valve to vertical bracket - Grill guard		(901261P26)	(\$1,617.00)
	763052	632TL AND 84 BKT SSL 763052 632TL Non self leveling loader with 84" SSL Bucket			No Charge

PTO

REAR PTO

SD_T8010 PTO

	759271	540 RPM W CAP			No Charge
	759273	540-1000 RPM W CAP		9000452P40	\$580.00

3-POINT HITCH

SD_T8200 HITCH

	342053	2000KG/4409LBS-Telesc/COMBI 3-PT lift capacity of 3,200 lbs.			No Charge
	342054	3500KG/7716LBS-Telesc/COMBI 2 auxiliary lift rams to increase rear hitch capacity to 6,200 lbs.		9000852P54	\$1,093.00

WEIGHTS

FRONT WEIGHTS

SD_T2151 WEIGHT PACK

	342070	110KgFCW/10X40-510kg Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs		9001065P48	\$1,366.00
	342069	110KgFC W/8X40-430kg Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs		9000852P54	\$1,093.00



**WORKMASTER 95-120 AP LOW PRO FAST PICK
 US PRICE LIST**

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

	762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires		9000537P42	\$689.00
--	--------	--	--	------------	----------

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

	342076	French (Canada)			No Charge
	342077	Spanish			No Charge



**WORKMASTER 95-120 POULTRY FAST PICKS
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Low profile semi straddle ROPS
- Low profile air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Engine Reversing Fan
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
Creeper ready
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH) speed may vary
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 63.8 in. to 68.5 in.

REAR AXLE

Flange Type
Tread Width: 64.8 in. to 72.7 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 POULTRY FAST PICKS
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

TIRES:

11.5/80-15.3 R1 Front
500/60-22.5 R1 Rear
OR
12.5/80-18 R4 Front
19.5L24 R4 Rear

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer bucket attach
84" bucket



**WORKMASTER 95-120 POULTRY FAST PICKS
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	8,367 LB	9051019P02	\$65,409.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB	9053490P06	\$68,577.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB	9056558P58	\$72,511.00



**WORKMASTER 95-120 POULTRY FAST PICKS
 US PRICE LIST**

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

FAST PICK CONFIGURATION

SD_T9980 PACKAGING

	XF9915X	<p>Poultry NSL Loader Fast Pick</p> <p>Poultry NSL Loader Fast Pick pricing includes:</p> <p>Reversing engine fan 632LA NSL loader with SSL quick attach and 84" bucket</p> <p>Allows for choice of the following:</p> <p>Hydraulic Pumps</p> <ul style="list-style-type: none"> - 16.9 gpm (64 L) = (342056) - 21.6 gpm (82 L) = (347541) <p>Rear Remotes</p> <ul style="list-style-type: none"> - 2 Rear Remotes = (762052) - 3 Rear Remotes = (762053) <p>3-PT Hitch Capacity</p> <ul style="list-style-type: none"> - 3200 lb (1451 kg) = (342053) - 6200 lb (2812 kg) = (342054) <p>PTO</p> <ul style="list-style-type: none"> - 540 RPM = (759271) - 540/1000 RPM = (759273) <p>Tires:</p> <ul style="list-style-type: none"> - 500/60-22.5 rear (8310501) with 11.5/80-15.3 front (8811501) <p align="center">OR</p> <ul style="list-style-type: none"> - 19.5-24 R4 rear (8930603) with 12.5-18 front (8230503) <p>Rear weights:</p> <ul style="list-style-type: none"> - No rear wheel weights - 4 rear wheel weights = (762028) 		(900468P00)	(\$600.00)
--	---------	--	--	-------------	------------



**WORKMASTER 95-120 POULTRY FAST PICKS
 US PRICE LIST**

		XF9916X	Poultry NO Loader Fast Pick Poultry NSL Loader Fast Pick pricing includes: Reversing engine fan Less loader and mid-mount valve Allows for choice of the following: Hydraulic Pumps - 16.9 gpm (64 L) = (342056) - 21.6 gpm (82 L) = (347541) Rear Remotes - 2 Rear Remotes = (762052) - 3 Rear Remotes = (762053) 3-PT Hitch Capacity - 3200 lb (1451 kg) = (342053) - 6200 lb (2812 kg) = (342054) PTO - 540 RPM = (759271) - 540/1000 RPM = (759273) Tires: - 500/60-22.5 rear (8310501) with 11.5/80-15.3 front (8811501) OR - 19.5-24 R4 rear (8930603) with 12.5-18 front (8230503) Rear weights: - No rear wheel weights - 4 rear wheel weights = (762028)		(907269P60)	(\$9,320.00)
--	--	---------	--	--	-------------	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag						
		8811501	11.5/80-15.3 R1 Requires 500/60-22.5 rear tires (ROPS ONLY)		9000596P70	\$765.00
4WD Front Tires - Ind						
		8230503	FRONT 12.5 - 18 R4 Requires 19.5L-24 rear tires		9000596P70	\$765.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag						
		8310501	500/60-22.5 R1 Requires 11.5/80-15.3 4WD front tires (ROPS ONLY)		9000533P52	\$684.00



**WORKMASTER 95-120 POULTRY FAST PICKS
 US PRICE LIST**

Rear tires - Ind					
	8930603	REAR 19.5 - 24 R4 Requires 12.5/80-18 4WD front tires		9000533P52	\$684.00

HYDRAULICS

REAR REMOTES

SD_T8270 REAR REMOTES					
	762052	2 REMOTE 762052 2 rear remotes for Open Platform with foldable ROPS Float on remote 1 Extend and retract detent and kick-out on remote 2			No Charge
	762053	3 REMOTE 762053 3 rear remotes for Open Platform with foldable ROPS Float on remote 1 & 3 Extend and retract detent and kick-out on remote 2		9000681P72	\$874.00

PUMP

SD_T8230 HYD PUMP					
	347541	HYD PUMP 21 gpm 21.6 GPM (82 LPM) Implement Pump		9000468P00	\$600.00
	342056	HYD PUMP 70,0 LPM 16.9 GPM (64 LPM) Implement Pump			No Charge

PTO

REAR PTO

SD_T8010 PTO					
	759271	540 RPM W CAP			No Charge
	759273	540-1000 RPM W CAP		9000452P40	\$580.00

3-POINT HITCH

SD_T8200 HITCH					
	342053	2000KG/4409LBS-Telesc/COMBI 3-PT lift capacity of 3,200 lbs.			No Charge
	342054	3500KG/7716LBS-Telesc/COMBI 2 auxiliary lift rams to increase rear hitch capacity to 6,200 lbs.		9000852P54	\$1,093.00



**WORKMASTER 95-120 POULTRY FAST PICKS
 US PRICE LIST**

WEIGHTS

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

	762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires		9000537P42	\$689.00
--	--------	--	--	------------	----------

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

	342076	French (Canada)			No Charge
	342077	Spanish			No Charge



**WORKMASTER 95-120 ROPS MOWING FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Semi straddle ROPS
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
Creeper ready
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH) speed may vary
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 66.5 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.8 in. to 79.5 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(3) Open Center Remote Valves with
Detent & Kickout on #2
Float on #1 & #3

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 ROPS MOWING FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

TIRES:

12.4x24 R1 Front
18.4X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies



**WORKMASTER 95-120 ROPS MOWING FAST PICK
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	8,367 LB	9051019P02	\$65,409.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB	9053490P06	\$68,577.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB	9056558P58	\$72,511.00



**WORKMASTER 95-120 ROPS MOWING FAST PICK
 US PRICE LIST**

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

FAST PICK CONFIGURATION

SD_T9980 PACKAGING

	XF9918X	ROPS Mowing Fast Pick ROPS Mowing Fast Pick pricing includes: 3 Rear Remotes Less loader and mid-mount valve Allows for choice of the following: Hydraulic Pumps - 16.9 gpm (64 L) = (342056) - 21.6 gpm (82 L) = (347541) 3-PT Hitch Capacity - 3200 lb (1451 kg) = (342053) - 6200 lb (2812 kg) = (342054) PTO - 540 RPM = (759271) - 540/1000 RPM = (759273) Mid Mount Valve/Loader - No Mid-Mount Valve or Loader - Mid-Mount Valve and Joystick only = (762699) - Loader Ready = (762698) Tires: - 18.4-30 R1 rear (8930605)with 12.4-24 R1 front (8230506) OR -16.9-34 R1 rear (8930601) with 13.6-24 R1 front (8230505) Rear weights: - No rear wheel weights - 4 rear wheel weights = (762028) - 8 rear wheel weights = (759650) Front weights: - No front weights - 8 front weights = (342069) - 10 front weights = (342070)		(909272P64)	(\$11,888.00)
--	---------	---	--	-------------	---------------



**WORKMASTER 95-120 ROPS MOWING FAST PICK
 US PRICE LIST**

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag					
	8230506	FRONT 12.4 - 24 R1 Requires 18.4-30 rear tires			No Charge
	8230505	13.6 -24 R1 Requires 16.9-34 rear tires		9000187P20	\$240.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag					
	8930605	REAR 18.4 - 30 R1 Requires 12.4-24 4WD front			No Charge
	8930601	REAR 16.9 - 34 R1 Requires 13.6-24 4WD front		(900119P34)	(\$153.00)

LOADER

LOADER

SD_T8110 LOADER BRACKETS

	762699	LESS LOADER W/ MMV Mid Mount Valve and Joystick ONLY.		9001261P26	\$1,617.00
	762698	LOADER READY 762698 Complete loader ready includes: - Horizontal and Vertical TPS loader brackets - 2 function mid mount valve and joystick - Hoses from mid mount valve to vertical bracket - Grill guard		9005539P56	\$7,102.00

PTO

REAR PTO

SD_T8010 PTO

	759271	540 RPM W CAP			No Charge
	759272	540-540E RPM W CAP		9000387P66	\$497.00
	759273	540-1000 RPM W CAP		9000452P40	\$580.00



**WORKMASTER 95-120 ROPS MOWING FAST PICK
 US PRICE LIST**

WEIGHTS

FRONT WEIGHTS

SD_T2151 WEIGHT PACK

	342070	110KgFCW/10X40-510kg Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs		9001065P48	\$1,366.00
	342069	110KgFC W/8X40-430kg Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs		9000852P54	\$1,093.00

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

	762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires		9000537P42	\$689.00
	759650	4X55or32Kg EACH SIDE 4 (110 lb) rear weights per side = 440 lbs total for all rear tires sizes except 500/60-22.5 4 (70 lb) rear weights per side = 280 lbs total for 500/60-22.5 rear tires		9001073P28	\$1,376.00

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

	342076	French (Canada)			No Charge
	342077	Spanish			No Charge



**WORKMASTER 95-120 A LA CARTE ROPS
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Semi straddle ROPS
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

Workmaster 95

97 Gross Engine hp
78 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 105

112 Gross Engine hp
92 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

Workmaster 120

120 Gross Engine hp
100 PTO hp @ 2300 rpm
4 Cyl Turbocharged Engine
207cu in (3.4 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + SCR + CUC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Horizontal Rearward Exhaust
24 gal Fuel Tank
2.9 gal DEF Tank
2 function mid mount valve & joystick

TRANSMISSION:

LH side steering column mounted
Power Shuttle
Creeper ready
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 19 mph (30 KPH) speed may vary
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Tread Width: 63.8 in. to 72.9 in.

REAR AXLE

Flange Type
Tread Width: 63.9 in. to 79.7 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 16.9 gpm (64 L)
Steering Pump: 9.7 gpm (37 L)
Total Flow: 26.6 gpm (101 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2
Float on #1

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
540 RPM hydraulic wet clutch
Electronic engagement
1-3/8 in. 6 splines



**WORKMASTER 95-120 A LA CARTE ROPS
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,200 Pounds Lift Capacity
Category I/II Combi Ball Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 800 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
30 amp power plug
12V power socket (cigarette lighter)

INSTRUMENTATION:

Digital /Analog Instrumentation with
warning lights for turn signals, high
beam, work lights, side lights,
rear PTO, 4WD, differential lock,
low fuel, alternator, oil pressure,
brake fluid, grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery, hours &
DEF level percentage

TIRES:

12.4x24 R1 Front
18.4X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Low profile air suspension seat,
operator's presence sensor, and
retractable seat belts
Suspended pedals
Locking brake pedals

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

632TL NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 134.5"
Dump Clearance @ 45 deg: 98.4"
Digging Depth: 5.1"
Lift Capacity @ 800mm: 2,028 LBS
Breakout Force @ 800mm: 3,102 LBS
Reach @ Max Lift Height @ 45
deg: 37.8"
Reach @ Ground Level: 87.4"
Bucket Rollback Angle: 40 degrees
Bucket Dump Angle: 53 degrees
Skid Steer bucket attach
84" bucket



**WORKMASTER 95-120 A LA CARTE ROPS
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	TRACTION	Weight	Factory Data	List Price
WORKMASTER 95 TIER4	Rops	MFD	8,367 LB	9051019P02	\$65,409.00
WORKMASTER 105 TIER4	Rops	MFD	7,451 LB	9053490P06	\$68,577.00
WORKMASTER 120 TIER4	Rops	MFD	7,936 LB	9056558P58	\$72,511.00



**WORKMASTER 95-120 A LA CARTE ROPS
 US PRICE LIST**

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

4WD Front Tires - Ag				
	8220701	11.2 - 24 R1 Requires 16.9-30 rear tires	(900050P70)	(\$65.00)
	8230506	FRONT 12.4 - 24 R1 Requires 18.4-30 rear tires		No Charge
	8230505	13.6 -24 R1 Requires 16.9-34 rear tires	9000187P20	\$240.00
	8811501	11.5/80-15.3 R1 Requires 500/60-22.5 rear tires (ROPS ONLY)	9000596P70	\$765.00
4WD Front Tires - Ind				
	8230503	FRONT 12.5 - 18 R4 Requires 19.5L-24 rear tires	9000596P70	\$765.00

REAR

SD_T4950 REAR WHEELS AND TIRES

Rear tires - Ag				
	8930602	REAR 16.9 - 30 R1 Requires 11.2-24 4WD front	9000255P84	\$328.00
	8930605	REAR 18.4 - 30 R1 Requires 12.4-24 4WD front		No Charge
	8930601	REAR 16.9 - 34 R1 Requires 13.6-24 4WD front	(900119P34)	(\$153.00)
	8310501	500/60-22.5 R1 Requires 11.5/80-15.3 4WD front tires (ROPS ONLY)	9000533P52	\$684.00
Rear tires - Ind				
	8930603	REAR 19.5 - 24 R4 Requires 12.5/80-18 4WD front tires	9000533P52	\$684.00



**WORKMASTER 95-120 A LA CARTE ROPS
 US PRICE LIST**

HYDRAULICS

REAR REMOTES

SD_T8270 REAR REMOTES

	762052	2 REMOTE 762052 2 rear remotes for Open Platform with foldable ROPS Float on remote 1 Extend and retract detent and kick-out on remote 2			No Charge
	762053	3 REMOTE 762053 3 rear remotes for Open Platform with foldable ROPS Float on remote 1 & 3 Extend and retract detent and kick-out on remote 2		9000681P72	\$874.00

PUMP

SD_T8230 HYD PUMP

	347541	HYD PUMP 21 gpm 21.6 GPM (82 LPM) Implement Pump		9000468P00	\$600.00
	342056	HYD PUMP 70,0 LPM 16.9 GPM (64 LPM) Implement Pump			No Charge

LOADER

LOADER

SD_T8110 LOADER BRACKETS

	762699	LESS LOADER W/ MMV Mid Mount Valve and Joystick ONLY.		(905539P56)	(\$7,102.00)
	762698	LOADER READY 762698 Complete loader ready includes: - Horizontal and Vertical TPS loader brackets - 2 function mid mount valve and joystick - Hoses from mid mount valve to vertical bracket - Grill guard		(901261P26)	(\$1,617.00)
	763052	632TL AND 84 BKT SSL 763052 632TL Non self leveling loader with 84" SSL Bucket			No Charge

PTO

REAR PTO

SD_T8010 PTO

	759271	540 RPM W CAP			No Charge
	759272	540-540E RPM W CAP		9000387P66	\$497.00
	759273	540-1000 RPM W CAP		9000452P40	\$580.00



**WORKMASTER 95-120 A LA CARTE ROPS
 US PRICE LIST**

3-POINT HITCH

SD_T8200 HITCH

	342053	2000KG/4409LBS-Telesc/COMBI 3-PT lift capacity of 3,200 lbs.			No Charge
	342054	3500KG/7716LBS-Telesc/COMBI 2 auxiliary lift rams to increase rear hitch capacity to 6,200 lbs.		9000852P54	\$1,093.00

WEIGHTS

FRONT WEIGHTS

SD_T2151 WEIGHT PACK

	342070	110KgFCW/10X40-510kg Front carrier (154 lbs) + 10 weights (88lbs each) = 1,034 lbs		9001065P48	\$1,366.00
	342069	110KgFC W/8X40-430kg Front carrier (154 lbs) + 8 weights (88lbs each) = 858 lbs		9000852P54	\$1,093.00

REAR WHEEL WEIGHTS

SD_T4960 WHEEL WEIGHTS

	762028	2X55or32Kg EACH SIDE 2 (110 lb) rear weights per side = 220 lbs total for all rear tires sizes except 500/60-22.5 2 (70 lb) rear weights per side = 140 lbs total for 500/60-22.5 rear tires		9000537P42	\$689.00
	759650	4X55or32Kg EACH SIDE 4 (110 lb) rear weights per side = 440 lbs total for all rear tires sizes except 500/60-22.5 4 (70 lb) rear weights per side = 280 lbs total for 500/60-22.5 rear tires		9001073P28	\$1,376.00

OPERATOR'S MANUALS

SD_T9805 OPERATOR MANUAL (SE

	342076	French (Canada)			No Charge
	342077	Spanish			No Charge

WORKMASTER 95, 105 & 120 Tire Chart					
Tire Type	Application	Rear Tires		Matching 4WD Front Tires	
		Tire	Order Code	Tire	Order Code
Bias	Agricultural - R1	16.9-30	8930602	11.2-24	8220701
		18.4-30	8930605	12.4-24	8230506
		16.9-34	8930601	13.6-24	8230505
Specialty	Agricultural - R1	500/60-22.5	8310501	11.5/80-15.3	8811501
	Industrial - R4	19.5L24	8930603	12.5/80-18	8290904