

CATERPILLAR MACHINE PRICE LIST

770G

770G TRUCK
 DECATUR, IL, USA

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

- Cat C15 ACERT diesel engine
- Air cleaner with precleaner (2)
- Air-To-Air aftercooler (ATAAC)
- Electric start
- Engine idle shutdown
- Global off-highway aluminum radiator
- Automatic Retarder Control (ARC)
- Manual retarder (utilizes rear oil cooled, multiple disc brakes)
- Brake release motor, towing
- Dry disc brakes, front
- Front brake disconnect switch, front
- Oil-cooled multiple disc brakes, rear
- Brake wear indicator, rear
- Parking brake
- Secondary brake
- Service brake
- Transmission:
 - 7 speed automatic powershift w/ (ECPC) electronic clutch pressure control
 - Advanced productivity electronic control strategy (APECS)
 - Automatic neutral idle
 - Autostall
 - Second gear start

- Fuel level monitoring
- Display languages, market based
- Air conditioning / heat
- Automatic temperature control
- Ashtray and cigarette lighter
- Coat hook
- Cup holders (4)
- Diagnostic connection port, 24V
- Entertainment radio ready: 5 amp converter, speakers and wiring harness
- Foot rest
- Brake oil temperature gauge
- Coolant temperature gauge
- Engine overspeed indicator
- Fuel level indicator
- Hour meter
- Speedometer w/odometer
- Tachometer
- Transmission gear indicator
- Hoist lever
- Horn
- Light, courtesy and dome
- Mirrors, heated
- Rollover protection (ROPS) and falling object protection (FOPS)
- Cat COSS 2 deluxe seat
- full air suspension
- heated/ventilated
- retractable 4 point seat belt with shoulder harness
- Seat, training, with lap belt
- Steering wheel, padded/tilt/telescopic
- Storage compartment
- Sun visor
- Throttle lock
- Window, sliding, right side (emergency exit)
- Window, powered, left side windshield wiper intermittent and washer

SUSPENSION SYSTEMS

Suspension, front and rear

ELECTRICAL

- Alarm backup
- Alternator, 120 amp
- Batteries, maintenance-free, 12V (2), 1400 CCA combined
- Electrical system, 25 AMP, 24V to 12V converter
- Backup light, halogen
- Directional signals/hazard warning, front & rear, LED
- Engine compartment light
- Headlights with dimmer
- Operator access courtesy lights
- Lights, side profile
- Lights, stop/tail, LED
- Service center
 - Battery jump start
 - Breakers, electrical
 - Lock out switch
 - Ports, ET and VIMS

TECHNOLOGY PRODUCTS

- Economy modes, standard and adaptive
- Product link ready
- Payload System (TPMS)
- Vital Info Management System (VIMS)
- Tire monitoring system (TKPH/TMPH)

GUARDS

- Driveline
- Engine crankcase
- Fan

OPERATOR ENVIRONMENT

- Advisor display
- Air cleaner service indicator
- Fluid level monitoring

FLUIDS

- Extended life coolant, -34C (-30F)
- Grouped ground-level filters

CATERPILLAR MACHINE PRICE LIST

770G

770G TRUCK
DECATUR, IL, USA

Ship Weight
lbs

LIST PRICE
AT DEALER

OTHER STANDARD EQUIPMENT

- Body down indicator
- Body safety pin (secures body in up position)
- Center mounted rims
- Fuel tank, 530L (140 gallons)
- Ground level battery disconnect
- Ground level engine shutdown
- Ground level grease fittings
- Operation Maintenance Manual (OMM)
- Rims 13 x 33
- Rock ejectors
- Secondary steering, electric
- Tie down eyes
- Tow hooks, front/tow pin, rear
- Vandalism protection locks

CATERPILLAR MACHINE PRICE LIST

770G

770G TRUCK	Ship Weight	LIST PRICE
DECATUR, IL, USA	lbs	AT DEALER

300-0001	770G OFF-HIGHWAY TRUCK 67,398 LANE 2 - AVAILABLE FROM DECATUR FACTORY LANE 3 - AVAILABLE FROM DECATUR FACTORY		\$662,310
-----------------	--	--	------------------

AVAILABLE FOR: AM-NORTH, EU, TURKEY, JAPAN AND SOUTH KOREA

0P-2937	770G MISC MATL DECATUR 0 AVAILABLE FROM DECATUR FACTORY		NC
----------------	---	--	-----------

Only reference numbers that have the text
 "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a misc order.

0P-3759	770 BODY & BODY ATT MISC MTL 0 AVAILABLE FROM DECATUR FACTORY		NC
----------------	---	--	-----------

Use this as the top level reference number when ordering a body or
 body attachments without ordering a machine.

CATERPILLAR MACHINE PRICE LIST

770G

USE	REF NO.	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	--------------------	-------------------------

NOTE

TPMS REQUIRES: Download cable 305-5528 available from Cat Parts system. VIMS pc annual software subscription available through Cat Literature Distribution System. Caterpillar Dealer annual subscription: form number JERD-2138, Mail Code 969. Customer annual subscription: form number JERD-2175, mail code 47.

CATERPILLAR MACHINE PRICE LIST

770G

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

	OP-9002	LANE 2 ORDER	0	NC
	OP-9003	LANE 3 ORDER	0	NC

REGIONAL PACKAGES

L	444-8412	REGIONAL PKG, NORTH AMERICA Accumulators with ANSI films.	509	NC
---	----------	--	-----	----

PERFORMANCE PACKAGES

L	561-8761	STANDARD PERFORMANCE. FOR USE IN LANE 3 ONLY Tier 4 Engine without compression brake and extended life brakes.	0	\$4,210
L	444-8420	ADVANCED BRAKING PERFORMANCE. Tier 4 Engine with compression brake and extended life brakes.	25,166	\$8,150

FEATURE PACKAGES

LIGHTING PACKAGE

L	541-1712	LIGHTING, HALOGEN Contains halogen flood lights.	0	NC
L	541-1713	LIGHTING, HID Contains high intensity discharge (HID) high beam flood lights.	0	\$685
L	468-8678	LIGHTING, LED Contains LED lights. -Front low beam headlights (4 LED/all facing forward) -Front high beam headlights (4 LED/all facing forward) -Rear lights (2 LED/all facing rear) -4 side work lights (4 LED/2 facing side and 2 facing rear tires) -1 engine bay light (1 LED/facing the RH side of engine)	0	\$5,350

WEATHER PACKAGES

L	444-8436	WEATHER PACKAGE, BASIC For use in ambient temperature above -18C (0F). Contains 2 batteries and standard mirrors.	619	NC
L	444-8437	WEATHER PACKAGE, HEATED MIRRORS For use in ambient temperature above -18C (0F). Contains 2 batteries, heated mirrors and ether aid.	624	\$1,175
L	444-8438	WEATHER PACKAGE, PREMIUM For use in ambient temperature below -18C (0F). 120 Volt. Contains 2 batteries, fuel heater, fuel line heater, heated mirrors, ether aid, engine block heater and tarp for radiator inlet grill.	813	\$3,375

SERVICE PACKAGES

L	309-1646	GREASE FITTINGS, CLUSTERED Includes clustered ground level grease fittings.	40	\$7,790
---	----------	--	----	---------

CATERPILLAR MACHINE PRICE LIST

770G

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FEATURE PACKAGES (CONT.)

SERVICE PACKAGES (Cont.)

L	444-8435	GREASE FITTINGS, CLSTRD W/FF 58 Includes clustered ground level grease fittings and fast fill.		\$9,220
L	361-9374	AUTO LUBE 133 Autolube in place of clustered grease fittings.		\$18,100
L	444-8434	AUTO LUBE WITH FAST FILL 151 Autolube in place of clustered grease fittings and fast fill.		\$19,400

POWERTRAIN

EXHAUST PACKAGES

L	343-4106	EXHAUST 106 Exhaust has full-time routing of exhaust through muffler which has lower sound levels.		NC
L	343-4105	EXHAUST, BODY HEAT 302 Allows both full time body heat or muffler via muffler diverter box. CANNOT BE USED WITH: RUBBER LINER		\$6,370

SUSPENSION SYSTEMS

L	444-8428	SUSPENSION, EU 3,256 Suspension and Cylinders. complies with pressure vessel regulations.		NC
---	----------	---	--	----

ELECTRICAL

ADVISOR LANGUAGE

L	341-6731	LANGUAGE, ADVISOR 0 Languages for Advisor are English/Spanish/French/German/Italian/Portuguese/Dutch/Norwegian/Swedish.		NC
---	----------	---	--	----

OPERATOR ENVIRONMENT

CAB FILTRATION

L	299-7274	FILTER, AIR 18 For use when not ordering the pre cleaner.		NC
L	341-3855	PRECLEANER GP. 35 For use in excessively dusty applications.		\$2,500

CATERPILLAR MACHINE PRICE LIST

770G

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet.

Authorization varies by country, please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.

Satellite Product Link uses a satellite network for remote transmission of asset information including location, utilization, and condition. For use in areas with poor or no cellular coverage.

The traction control feature is ideal for customers with everyday changing underfoot conditions such as muddy or soft ground due to water trucks or inclement weather. This feature is beneficial for operator efficiency and safety by allowing the operator to maintain control and higher travel speeds for the truck. Other benefits include lower tire cost by minimizing tire slippage and damage. This traction control electronically monitors and controls rear wheel slippage for greater traction and enhanced truck performance in poor underfoot conditions. If slippage exceeds a set limit based on turning angle and machine speed, the oil cooled disc brakes engage slow the spinning wheel. Torque is then automatically transferred to the wheel with better traction.

L	509-3016	PL, CELL PL641 0		NC
		Includes Cellular Product Link, PL641 and standard steering control.		
L	509-3017	PL, CELL PL641 / TRACTION CTRL 0		\$6,940
		Includes Cellular Product Link, PL641 and Traction Control System.		
L	444-8450	PL, SAT PL321 264		\$316 NET
		Includes Satellite Product Link, PL321 and standard steering control.		
L	444-8451	PL, SAT PL321 / TRACTION CTRL 335		\$7,390
		Includes Satellite Product Link, PL321 and Traction Control System.		

CATERPILLAR MACHINE PRICE LIST

770G

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS

TIRES

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice. However, if the tire type cannot be supplied we will contact the dealer to propose alternatives. The dealer needs to choose between an alternative tire or a "rims only" option (where available) within 72 hours. If no response is provided by the deadline, the order will default to the alternative tire and will be changed at that point. As a consequence of a possible tire change, the total machine price will be decreased or increased depending on the price of the new tire.

The information provided can be used to make a tire selection based on the particular conditions at the site. When available, the tire manufacturer should be consulted regarding proper tire selection.

Tread void ratio can be used to evaluate the damage resistance or traction capability of a particular tire. Tires with a numerically low tread void ratio tend to perform better in soft underfoot conditions; tires with a numerically high void ratio tend to perform better in harsh conditions where damage and puncture are a concern.

TKPH (ton kilometer per hour) and distance per hour are measures of the capability of the tire to withstand heat. Tires with a high TKPH or distance per hour ratings will be better suited for long, fast hauls but will be more susceptible to cuts and damage. Tires with a low TKPH or distance per hour rating are better suited for slow speed short hauls and provide improved cut and damage resistance.

Tires will have varying degrees of durability and wear rates.

L	325-1402	TIRES, 18.00 R33 BS VMTP ** E2A 2,718 Bridgestone Radial; Manufacture PN 423866 TKPH=185 (TMPH=126); Max Distance Per Hour=26 km (16 mi) Tread Void Ratio=57%; Tread Depth=55 mm Provides maximum traction on soft ground with a high cut resistance compound.		\$1,240
L	175-0489	TIRES, 18.0R33BS VMTP E2ALS**E4 5,740 FOR USE IN LANE 3 ONLY Bridgestone Radial; Manufacture PN TKPH=148 (TMPH=92) Tread Compound: E2A LS A cut resistant tire with exceptional tread wear and traction.		\$1,240

CATERPILLAR MACHINE PRICE LIST

770G

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS (CONT.)

TIRES (Cont.)

L	524-1346	TIRES, 18.00R33 CONTI ** E4. 0 Continental Radial RDTMaster iTire; Manufacturer PN 1270474 TKPH=192 (TMPH=131); Max Distance Per Hour=22 km (14 mi) Tread Void Ratio=64%; Tread Depth=54 mm Provides a maximum traction pattern with a medium cut and heat resistant compound. Included CPC sensor for pressure and temperature. NOTE: All Continental tires are included with Continental CPC sensor. Tire sensor does not communicate directly with machine. Additional hardware required through Continental for full functionality. Please contact your local Continental tire dealer for more information.		\$-7,970
L	579-3856	TIRES, 18.00R33 MX B XLG *** E4. 0 Michelin Radial; Manufacturer PN 553513 TKPH=301 (TMPH=206); Max Distance Per Hour=34 km (21.1 mi) Tread Void Ratio=63%; Tread Depth=60 mm Provides excellent grip in loose ground conditions.		\$18,390
	143-4010	TIRES, ALLOWANCE FOR OMISSION 0 Less: 1 set of six 18.00R33 (E4).		\$-24,090

BODY

BODY PACKAGES

Caterpillar offers a base body, a base body plus liner, sideboards, and a rubber liner option.

Caterpillar's updated body strategy provides our Customers with a wide range of body applications, with no need for Customer or Dealer modifications upon receipt from the factory. It is Caterpillar's recommendation to always use the Body Selection Guide (AEXC0673) and to know the customer applications prior to ordering any body and placing it into service. If the application is unknown, a single steel liner is recommended. When a body is placed into service, Caterpillar has provided clear and complete inspection guidelines (REHS5062) that should be followed to ensure maximum body life. Caterpillar will not make any recommendations that deviate from these published guidelines. Any deviations from the Body Selection Guide, including liner, are at the Dealer and Customer's discretion and responsibility. You may also contact the Caterpillar Global Construction & Infrastructure (GCI) or Caterpillar Global Mining (CGM) Regional Application Specialist with use of the body system selection guide or for selecting your body.

L	362-8600	BODY, FLAT FLOOR 17,244 FOR USE IN LANE 3 ONLY Recommended for low abrasive materials with low impact. Good for feeding hoppers and crushers. All steel wear surfaces are 400 BHN. Exhaust heat ready. Includes one piece floor of 16mm (.63"); sidewall of 10mm (.39"); frontwall of 14mm (.55"). Capacity: 25.2 m3 (32.9 yd3) SAE 2:1		\$49,820
---	----------	---	--	----------

CATERPILLAR MACHINE PRICE LIST

770G

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

BODY (CONT.)

BODY PACKAGES (Cont.)

L	444-8460	BODY, FLAT FLOOR, STEEL LINER 23,487 Recommended for hard rock, abrasive materials, and other applications with higher impact requirements. Good for feeding hopper and crushers. Exhaust heat ready. All steel wear surfaces are 400 BHN. Includes base floor with additional floor liner of 16mm (.63"); sidewall liner of 8mm (.31"); frontwall liner of 8mm (.31"). Capacity: 24.9 m3 (32.5 yd3) SAE 2:1		\$59,720
L	444-8461	BODY, FLAT FLOOR, RUBBER LINER 25,082 FOR USE IN LANE 3 ONLY Recommended for hard rock and abrasive applications. Highest level of impact and abrasion resistance. Not recommended for cohesive applications. Good for feeding hoppers and crushers. Includes base floor with additional rubber floor liner of 102mm (4"); steel sidewall liner of 8mm (.31"); steel frontwall liner 8mm (.31"). Capacity: 23.6 m3 (30.8 yd3) SAE 2:1 ONLY FOR USE WITH: 343-4106 EXHAUST		\$70,150
L	362-8650	BODY, QUARRY 22,141 Recommended for low abrasive materials with low impact. Good for load centering, stability, material retention on slopes. All steel wear surfaces are 400 BHN. Exhaust heat ready. Includes floor of 25mm (1"). Does not include liner package. Sidewall of 14mm (.55"); frontwall of 16mm (.63"). Capacity: 25.1 m3 (32.9 yd3) SAE 2:1		\$57,230
L	362-8610	BODY, DUAL SLOPE 16,812 FOR USE IN LANE 3 ONLY Recommended for low abrasive materials with low impact. Good for load centering, stability, material retention on slopes. All steel wear surfaces are 400 BHN. Exhaust heat ready. Includes one piece floor 16mm (.63"); sidewall of 10mm (.39"); frontwall of 14mm (.55"). Capacity: 25.2 m3 (32.9 yd3) SAE 2:1		\$49,110
L	444-8462	BODY, DUAL SLOPE, STEEL LINER 22,996 Recommended for hard rock, abrasive materials, and applications with higher impact requirements. Good for load centering, stability, material retention on slopes. All steel wear surfaces are 400 BHN. Exhaust heat ready. Includes base floor with additional liner of 16mm (.63"); sidewall liner of 8mm (.31"); frontwall liner of 8mm (.31"). Capacity: 24.8 m3 (32.5 yd3) SAE 2:1		\$63,220

PACKING

STORAGE PROTECTION

NOTE: For Chassis orders only, not Body orders.

OP-2671	NO STORAGE PROTECTION 0 Please select this if you do not want Rust Preventative applied. ONLY FOR USE WITH: US dealers	NC
---------	---	----

NOTE: If No Storage Protection is selected, then corrosion damage will not be covered under standard machine warranty.

CATERPILLAR MACHINE PRICE LIST

770G

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-----------------------------	--------------------	-------------------------

PACKING (CONT.)

STORAGE PROTECTION (Cont.)

0P-4616	STORAGE PROTECTION 0 Please select this if you want Rust Preventative applied.	NC
---------	--	-----------

CATERPILLAR MACHINE PRICE LIST

770G

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

FEATURE PACKAGES

VISIBILITY PACKAGE

L	549-6787	VISIBILITY, CAMERA 0 Contains Work Area Vision System (WAVS) with single rearview camera.		\$3,265
L	341-3750	VISIBILITY,CAMERA & EU MIRRORS. 26 Contains ISO 5006 mirrors and Work Area Vision System (WAVS) with single rearview camera. The WAVS system with rear vision camera is available to monitor movement behind the truck for improved visibility and enhanced operator efficiency. REQUIRED BY: EU & Japan dealers		\$3,905

TIRES, RIMS, AND WHEELS

WHEEL CHOCKS

L	365-8571	WHEEL CHOCKS (ANSI) 93 Wheel chocks with ANSI labels.		\$1,290
---	----------	---	--	---------

BODY

BODY ATTACHMENTS

L	362-8620	SIDEBARDS AS 806 Adds 155mm (6in) extension to the body side walls and provides 2.5 m3 (3.4 yd3) of additional volume. ONLY FOR USE WITH: ALL DUAL SLOPE, FLAT FLOOR AND QUARRY BODY AND LINER SYSTEMS		\$3,840
L	363-6370	GUARD, OVERHEAD 210 Provides vertical sheet metal around perimeter to limit spillage from canopy.		\$1,315

FLUIDS

ANTIFREEZE

Standard factory antifreeze protects to -30F (-34C).

0P-2406	ANTIFREEZE, -50C (-58F) 0	\$275 NET
0P-2402	COOLANT, -40C (-40F) 0	\$275 NET

FIELD INSTALLED ATTACHMENTS

For Dealer Installed Options, please refer to Salesgram TEKQ1423 published in September 2017.

CATERPILLAR MACHINE PRICE LIST

770G

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------------	--------------------	-------------------------

PACKING

MUST SELECT ONE

0P-0269	DOMESTIC TRUCK 0 The rear dual tires, parts boxes and handrail skid shipped on a separate truck.	NC
0P-0210	PACK, DOMESTIC TRUCK 0 Use this as the packing reference number on a MISC MSO.	NC