

CATERPILLAR MACHINE PRICE LIST

950M-BR

950M WHEEL LOADER
 PIRACICABA, BRAZIL

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

- Engine, Cat C7.1 ACERT
- Torque converter, with lock-up clutch free wheel stator
- Tranmission countershaft, automatic, powershift (5F/3R)
- Pump transmission, split flow
- Productive Economy Mode (fuel consumption optimization)
- Brakes, full hydraulic enclosed wet-disc with Integrated Braking System (IBS)
- Brake wear indicators
- Fan drive hydraulic, electronically controlled, temperature sensing, on demand
- Fuel priming pump (electric)
- Fuel/Water separator
- Engine air intake with strata-tubes
- Parking Brake, disk & caliper

- compartment for cell phone/MP3 player
- Coat hooks (2)
- Sliding window
- Ergonomic Cab Access
- Sun visor, front
- Computerized monitoring system
- Front dash information display with:
 - Speedometer/Tachometer
 - Digital gear indicator
 - Temperatures: engine coolant, hydraulic oil, transmission oil
 - Fuel level
- Warning Indicators:
 - Temperatures: axle oil, engine intake manifold
 - Pressures: engine oil, fuel pressure
- Hi/Low, primary steering oil, service brake oil
- Battery voltage Hi/Low
- Engine air filter restriction
- Hydraulic oil filter restriction
- Hydraulic oil level low
- Parking brake
- Transmission filter bypass
- Multi-function monitor:
 - 180mm(7") color LCD touch-screen display
 - Rear-view camera image display (reverse travel activated)
- Machine utilization information:
 - Total fuel consumption
 - Average fuel burn rate
 - Engine fuel consumption
 - Total idle time
 - Total operating hours
 - Travel distance (odometer)
 - Total idle fuel
 - Total operating hours, neutral
 - Total operating hours with hydraulic filter in bypass

HYDRAULICS

- Load sensing system with variable displacement piston pump.
- Hoses, Caterpillar XT
- Couplings, Caterpillar O-ring face seal
- Hydraulic oil cooler (swing out)
- Oil sampling valves
- Remote diagnostic pressure taps
- Hydraulic Service Center

ELECTRICAL

- Batteries (2), maintenance free 1400CCA
- Starting and charging system (24V)
- Alarm, back-up
- Ignition key; start/stop switch
- Main disconnect switch
- Receptacle remote start (cables not included)
- Starter, electric, heavy duty
- Emergency shut-off switch
- Rear camera
- Electrical Service Center

OTHER STANDARD EQUIPMENT

- Engine idle management system and auto idle shutdown
- Filters: fuel, engine air, engine oil, hydraulic oil, transmission
- Hitch, drawbar
- Kickout, lift & tilt, automatic (adjustable)
- Sight gauges: engine coolant, hydraulic oil, and transmission oil level
- Lift and tie down points
- Articulation locking bar
- Parallel Z-bar lifting

OPERATOR ENVIRONMENT

- A-Post mounted membrane 16 switch keypad
- Climate control
- Bucket/Work tool function lockout
- EH Parking Brake
- Intermittent front wiper control
- Horn, electric
- Lights, cab dome (2)
- Radio ready (entertainment) includes antenna, speaker & converters (12V 10A)
- 3 receptacles, 12V
- Beverage holders (2) with storage

CATERPILLAR MACHINE PRICE LIST

950M-BR

950M WHEEL LOADER PIRACICABA, BRAZIL	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

**Lane 2 is reserved for the Base Order Management Program.
 Please use Lane 2 when placing orders that are part of the Base Order
 Management Program.**

592-1073	950M WHEEL LOADER AM-N FTO1 0 LANE 1 - AVAILABLE FROM SAVANNAH DISTRIBUTION CENTER INCLUDES: 464-2600 950M WHEEL LOADER 543-3587 REGIONAL PKG, AM-N 513-5389 STANDARD PKG WITH AD/CPM RDY 538-2776 LINKAGE, STANDARD LIFT 393-0072 COUNTERWEIGHT, 1460KG 366-9903 AXLES, MANUAL/OPEN, ED 506-3506 HYDRAULICS, 2V RC (3V READY) 366-9912 HYDRAULIC OIL, STANDARD 373-3911 STARTING, COLD (120V) 384-7006 MANUAL DIFF, STEERING WHEEL 493-9615 WINDOWS, STANDARD 538-2771 CAB TRIM, DELUXE (HMU) 505-1519 FILTRATION, STANDARD 551-3397 SEAT BELT, 3" 372-1600 RADIO, AM/FM/USB/MP3 BLUETOOTH 372-1603 RADIO, CB (READY) 550-9881 LIGHTS, STANDARD 434-0690 NETWORK MANAGER ONLY 538-2796 STEERING SYST, STD, WHL 521-9358 COOLING CORES, 9 FPI 513-5394 FAN, STANDARD 371-7064 ANTIFREEZE, -34C (-29F) 367-9027 GUARD, POWERTRAIN 538-2788 LUBRICATION, MANUAL, STD 373-3900 QUICK COUPLER READY, STD 365-0112 AIR INLET STANDARD, RAIN CAP 336-0000 HOOD, NON-METALLIC 464-6672 FENDERS, BASIC + 465-6576 SOUND SUPPRESSION, STANDARD	\$331,460
----------	---	-----------

NOTE: Please refer to the Lane 1 section to complete your order.

CATERPILLAR MACHINE PRICE LIST

950M-BR

950M WHEEL LOADER PIRACICABA, BRAZIL	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

592-1074	950M WHEEL LOADER AM-N FTO2 0 LANE 1 - AVAILABLE FROM SAVANNAH DISTRIBUTION CENTER	\$337,400
-----------------	--	------------------

- INCLUDES:
- 464-2600 950M WHEEL LOADER
 - 336-0000 HOOD, NON-METALLIC
 - 365-0112 AIR INLET STANDARD, RAIN CAP
 - 366-9908 AXLES, AUTO/AUTO, ED
 - 366-9912 HYDRAULIC OIL, STANDARD
 - 367-9027 GUARD, POWERTRAIN
 - 371-7064 ANTIFREEZE, -34C (-29F)
 - 372-1600 RADIO, AM/FM/USB/MP3 BLUETOOTH
 - 372-1603 RADIO, CB (READY)
 - 373-3900 QUICK COUPLER READY, STD
 - 373-3911 STARTING, COLD (120V)
 - 384-7005 AUTO DIFF, STEERING WHEEL
 - 393-0072 COUNTERWEIGHT, 1460KG
 - 434-0690 NETWORK MANAGER ONLY
 - 464-6672 FENDERS, BASIC +
 - 465-6576 SOUND SUPPRESSION, STANDARD
 - 493-9615 WINDOWS, STANDARD
 - 505-1519 FILTRATION, STANDARD
 - 506-3506 HYDRAULICS, 2V RC (3V READY)
 - 513-5389 STANDARD PKG WITH AD/CPM RDY
 - 513-5394 FAN, STANDARD
 - 521-9358 COOLING CORES, 9 FPI
 - 538-2771 CAB TRIM, DELUXE (HMU)
 - 538-2776 LINKAGE, STANDARD LIFT
 - 538-2788 LUBRICATION, MANUAL, STD
 - 538-2796 STEERING SYST, STD, WHL
 - 543-3587 REGIONAL PKG, AM-N
 - 550-9881 LIGHTS, STANDARD
 - 551-3397 SEAT BELT, 3"

NOTE: Please refer to the Lane 1 section to complete your order.

CATERPILLAR MACHINE PRICE LIST

950M-BR

950M WHEEL LOADER PIRACICABA, BRAZIL	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

592-1075	950M WHEEL LOADER AM-N FT03 0	\$337, 550
	LANE 1 - AVAILABLE FROM SAVANNAH DISTRIBUTION CENTER	

- INCLUDES:
- 464-2600 950M WHEEL LOADER
 - 336-0000 HOOD, NON-METALLIC
 - 365-0112 AIR INLET STANDARD, RAIN CAP
 - 366-9908 AXLES, AUTO/AUTO, ED
 - 366-9912 HYDRAULIC OIL, STANDARD
 - 367-9027 GUARD, POWERTRAIN
 - 371-7064 ANTIFREEZE, -34C (-29F)
 - 372-1600 RADIO, AM/FM/USB/MP3 BLUETOOTH
 - 372-1603 RADIO, CB (READY)
 - 373-3900 QUICK COUPLER READY, STD
 - 373-3911 STARTING, COLD (120V)
 - 393-0072 COUNTERWEIGHT, 1460KG
 - 384-7005 AUTO DIFF, STEERING WHEEL
 - 434-0690 NETWORK MANAGER ONLY
 - 464-6674 FENDERS, BASIC +, LOW PROFILE
 - 465-6576 SOUND SUPPRESSION, STANDARD
 - 493-9615 WINDOWS, STANDARD
 - 505-1519 FILTRATION, STANDARD
 - 506-3506 HYDRAULICS, 2V RC (3V READY)
 - 513-5389 STANDARD PKG WITH AD/CPM RDY
 - 513-5394 FAN, STANDARD
 - 521-9358 COOLING CORES, 9 FPI
 - 538-2771 CAB TRIM, DELUXE (HMU)
 - 538-2776 LINKAGE, STANDARD LIFT
 - 538-2788 LUBRICATION, MANUAL, STD
 - 538-2796 STEERING SYST, STD, WHL
 - 550-9881 LIGHTS, STANDARD
 - 543-3587 REGIONAL PKG, AM-N
 - 551-3397 SEAT BELT, 3"

NOTE: Please refer to the Lane 1 section to complete your order.

464-2600	950M WHEEL LOADER 0	\$313, 740
	LANE 2 - AVAILABLE FROM PIRACICABA FACTORY	
	LANE 3 - AVAILABLE FROM PIRACICABA FACTORY	

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 1 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS

LANE SELECTION

OP-9001	LANE 1 ORDER	0	NC
---------	--------------	---	----

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet.

Authorization varies by country, please contact your Cat marketing representative with questions or click on the link below:
<HTTPS://DEALER.CAT.COM/en/bt/otd/machine-price-list.html>
 From there click on the "PRODUCT LINK Hardware Certification" link.

L	578-6376	PRODUCT LINK, CELLULAR PL641 0 Product Link Elite series PLE641 (consisting of PL641 radio and PLE601 network manager) uses cellular networks to transmit location, utilization, health and productivity information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.	NC
L	566-2099	PRODUCT LINK, SATELLITE PL631 0 Product Link Elite series PLE631 (consisting of PL631 radio and PLE601 network manager) uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.	\$446

OPERATOR ENVIRONMENT

L	571-3995	LEVERS 2V, STEERING WHEEL 0 INCLUDES: -2 single action levers for implement lift & tilt controls -FNR switch on implement pod	NC
L	571-3996	LEVERS 3V, STEERING WHEEL 0 INCLUDES: -3 single action levers for implement lift, tilt & 3rd function controls -FNR switch on implement pod REQUIRES: 562-0146 HYDRAULICS, 3V RC STD	NC
L	562-0139	JOYSTICK 2V, STEERING WHEEL 0 INCLUDES: -Implement joystick for lift & tilt controls -Horn, FNR and kickdown trigger switches integrated in implement joystick	\$1,110
L	562-0140	JOYSTICK 3V, STEERING WHEEL 0 INCLUDES: -Implement joystick for lift & tilt controls -Horn, FNR & kickdown trigger switches integrated in implement joystick -1 roller switch controlling the 3rd function integrated in the joystick REQUIRES: 562-0146 HYDRAULICS, 3V RC STD	\$1,560

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 1 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

LIGHTS

L	522-4166	LIGHTS, HALOGEN 0 Includes: -2 halogen forward roading lights (low/high beam) with halogen turn signals -2 halogen rear facing working lights in the hood -2 LED position/stop/turn lights -4 halogen working lights on the cab		NC
L	522-4167	LIGHTS, HALOGEN, PREMIUM 0 INCLUDES: -2 halogen forward roading lights (low/high beam) with halogen turn signals -2 halogen rear facing working lights in the hood -2 LED position/stop/turn lights -8 halogen working lights on the cab		\$890
L	562-0137	LIGHTS, LED 0 INCLUDES: -2 LED forward roading lights (low/high beam) with LED turn signals -2 LED rear facing working lights in the hood. -2 LED position/stop/turn lights -4 LED working lights on the cab		\$2,575
L	562-0138	LIGHTS, LED, PREMIUM 0 Provides LED Rooding lights: -2 Forward roading lights LED(low/high beam) with LED turn signal -2 Rear LED position stop turn lights Provides LED Work lights: -2 Forward facing standard lights on the top of the cab -2 Forward facing high intensity lights on the top of the cab -4 Rear facing standard lights on the top of the cab -2 Rear facing standard lights on the Hood.		\$3,425

TIRES

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice. However, if the tire type cannot be supplied we will contact the dealer to propose alternatives. The dealer needs to choose between an alternative tire or a "rims only" option (where available) within 72 hours. If no response is provided by the deadline, the order will default to the alternative tire and will be changed at that point. As a consequence of a possible tire change, the total machine price will be decreased or increased depending on the price of the new tire.

TIRES AVAILABLE FROM MAXAM

P	547-8401	TIRES,23.5R25 MA MS302 **E3/L3 0 MAXAM RADIAL; TREAD DEPTH=36.5mm; Rim=19.5"x25" 3 piece Provides reduced vibration, damage resistance, and traction in soft to rocky underfoot conditions. CANNOT BE USED WITH: 592-1075 950M WHEEL LOADER AM-N FTO3		\$-9,000
P	509-1481	TIRES, 750/65R25 BS VTS * L3 0 ONLY FOR USE WITH: 592-1075 950M WHEEL LOADER AM-N FTO3		\$11,000

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 1 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

OPERATION AND MAINTENANCE MANUAL

NOTE: Operation and maintenance Manual will be included in language requested below.

OP-3380	INSTRUCTIONS, ENGLISH	0	NC
OP-3389	INSTRUCTIONS, FRENCH	0	NC

WORKTOOLS

BUCKETS

P	516-1452	BKTA GP ST 115" 4.50YD3 PO PERFORMANCE SERIES BUCKET INCLUDES: BOLT-ON CUTTING EDGE (BOCE)	4,242	\$16,428
P	516-1417	BKTA GP ST 115" 4.50YD3 FUS PERFORMANCE SERIES BUCKET INCLUDES: BOLT-ON CUTTING EDGE (BOCE)	3,948	\$16,001
P	361-1437	OMISSION, WORKTOOL Required in orders configured without a work tool or QC in order to prevent from damages on the linkage.	0	NC

QUICK COUPLERS

L	349-5246	QUICK COUPLER, FUSION Fusion style coupler.	1,248	\$6,778
---	----------	--	-------	---------

LINES CONNECTING

P	378-8421	LINES GP-IMPLEMENT 3V (QC) ALSO AVAILABLE ON A MISCELLANEOUS ORDER REQUIRES: 562-0146 HYDRAULICS, 3V RC STD 349-5246 QUICK COUPLER, FUSION	22	\$560
---	----------	---	----	-------

CYLINDER PROTECTION

OP-3940	PROTECTION, CYLINDER ROD	0	NC
---------	------------------------------------	---	----

FLUIDS

FUEL ANTIFREEZE

OP-3978	FUEL ANTIFREEZE, -25C (-13F) Provides fuel (diesel) antifreeze protection down to -25C (-13F).	0	NC
---------	---	---	----

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 1 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-------------------------	--------------------	-------------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

STORAGE PROTECTION

0P-2918	<p>STORAGE PROTECTION..... 0</p> <p>This product is added for corrosion protection while shipping and for extended storage periods. This product will need to be power washed with soapy water prior the shipment to the customer. REQUIRED BY : ALL LANE CONFIGURATION</p>	NC
----------------	--	-----------

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 1 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

LANE 1 AM-NORTH OPTIONAL ATTACHMENTS

TECHNOLOGY PRODUCTS.

P	453-3250	AUTODIG SOFTWARE 0 Includes software for Aggregate Autodig. NOT RECOMMENDED for hardbank or large rock loading.		\$1,450
P	517-7123	CPM PAYLOAD SOFTWARE 0 Includes hardware and permanent software for CPM. Software is factory enabled, but the system must be calibrated prior to customer use. See note above for calibration instructions. (Not available for all countries. Contact PL Admin for details).		\$5,040

BEACON

P	566-2044	LIGHT, WARNING BEACON 0 Provides hard mounted strobe beacon on hinged (breakaway) bracket mounted to the rear of the cab structure.		\$493
---	----------	---	--	-------

HYDRAULICS

L	562-0146	HYDRAULICS, 3V RC STD 0 REQUIRED BY: 571-3996 LEVERS 3V, STEERING WHEEL 562-0140 JOYSTICK 3V, STEERING WHEEL		\$5,560
---	----------	---	--	---------

COOLANT

P	0P-3506	ANTIFREEZE, -50C (-58F) 0 Premix Antifreeze, -50C or -58F.		\$283 NET
---	---------	--	--	-----------

INSTRUCTIONS

FILMS

P	386-7389	FILM, CPM 0 REQUIRED BY : CANADIAN DEALER ORDER WITH CPM		NC
P	0P-3507	FILMS, ISO 0 REQUIRED BY: Quebec		NC

PACKING

	0P-6619	ROLL ON-ROLL OFF 0 Machine is in mobile condition and all attachments are installed unless specified.		\$267 NET
--	---------	---	--	-----------

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER	0	NC

REGIONAL PACKAGES

L	543-3587	REGIONAL PKG, AM-N	0	NC
		INCLUDES: -ANSI films -EPA Tier 4 Final Compliant Engine		

SPECIAL ARRANGEMENTS

L	513-5391	INDUSTRIAL PACKAGE	0	\$10,480
		FOR USE WITH LANE 3 ONLY Provides machine features required in waste transfer stations, recycling stations, green waste and scrap applications. INCLUDES: -Reinforced platform -Carbon cab air filter -Guards: hitch, bottom cab (skirt), front frame, crankcase -Lift cylinder baffles -Heavy duty ladder RECOMMENDED: 540-4373 TIRES, 23.5X25 BR TRACTION or 540-4374 TIRES, 23.5X25 BR SMOOTH 505-1521 FILTRATION AR, STEEL or 505-1522 FILTRATION AR, STEEL CLNR AUX and 493-9616 WINDOWS, FLAT, RUBBER MOUNTED or 493-9617 WINDOWS, FLAT, RUBBER MOUNTED GRD and 485-4387 GUARDS, LIGHT REQUIRES: 366-9906 AXLES, LOCK/OPEN, ED, SG or 366-9910 AXLES, AUTO DIFF F/R, ED, SG and 478-8371 FENDERS, NARROW and 488-1138 SOUND SUPPRESSION, INDUSTRIAL (NACD) or 465-6590 SOUND SUPPRESSION, LOW (EUR) 399-4332 GUARD, HINGED, POWERTRAIN and 360-8835 GUARD, TILT CYLINDER		

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

SPECIAL ARRANGEMENTS (CONT.)

L	543-3606	CORROSION PROTECTION PACKAGE 0		\$6,600
		FOR USE WITH LANE 3 ONLY Minimizes the harmful effect in highly corrosive environments applications such as fertilizer handling, salt and its derivatives.		

INCLUDES:

- Platform;
- Electrical & Hydraulic installation;
- Cab air filter;
- Heavy duty alternator;
- Heavy duty switch disconnect;
- Silicon protection is applied on all the electric terminals, exposed connectors are treated with tube heat shrinkable;
- Anticorrosion vapor capsules in closed compartments;

REQUIRES:

- 365-0120 PRECLEANER, TURBINE
- 477-1660 WINDOW AR, CAB - CORROSION, OR
- 477-1659 WINDOW AR, RM - CORROSION

RECOMMENDED:

- 524-1394 COOLING GP (6FPI) - CORROSION, OR
- 524-1393 COOLING GP (9FPI) - CORROSION
- Cores protected
- Grease points on the radiator hinges
- 477-1667 HOOD AR - CORROSION
- 521-9198 PAINTING GROUP, CORROSION (NACD), OR
- 522-5231 PAINTING GROUP, CORROSION (EU)
- Differentiated Painting Process
- Extra Varnish protection is applied on the engine compartment, chassis internal
- 506-0545 PROTECTION PACKAGE, LINES
- Hose couplings treated with tube heat shrinkable and sealant silicone.
- 513-5392 FAN, VPF, ISO, OR
- 513-5393 FAN, VPF, ANSI
- 495-7494 AUTOLUBE - for 950M, OR
- 495-7496 AUTOLUBE - for 962M
- 505-1520 FILTRATION, STD, PRECLEANER

L	513-5390	LOGGER PACKAGE 0		NC
		FOR USE WITH LANE 3 ONLY Provides machine features required in forestry applications.		

INCLUDES:

- Platform
- Cab air filter

REQUIRES: 505-1554 LINKAGE, LOGGER
393-0072 COUNTERWEIGHT, 1460KG

L	513-5389	STANDARD PKG WITH AD/CPM RDY 0		\$236
		Provides machine features required in standard applications.		

INCLUDES:

- Platform
- Cab air filter
- CPM Payload Ready & Autodig Ready
- Includes hardware and 250 hour CPM demo mode only. Demo mode is dealer activated. System must be calibrated prior to use.
- Requires purchase of software for permanent feature activation.
- See the Optional Technology section for software options.

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

BOOMS, STICKS, AND LINKAGES

LINKAGES

L	538-2776	LINKAGE, STANDARD LIFT 0 ONLY FOR USE WITH: 513-5391 INDUSTRIAL PACKAGE or 513-5389 STANDARD PKG W/AUTODIG + CPM		NC
L	538-2777	LINKAGE, HIGH LIFT 0 FOR USE WITH LANE 3 ONLY Provides increased dump clearance of 20" (506mm) over standard lift arms. ONLY FOR USE WITH: 513-5391 INDUSTRIAL PACKAGE or 513-5389 STANDARD PKG W/AUTODIG + CPM		\$6,910
L	538-2778	LINKAGE, LOGGER 0 FOR USE WITH LANE 3 ONLY Provide oversize tilt and lift cylinders. REQUIRES: 393-0072 COUNTERWEIGHT, 1460KG 500-2566 HYDRAULICS, 3V RC LOGGER 468-0173 FILM, FOREST ONLY FOR USE WITH: 513-5390 LOGGER PACKAGE (AM-N)		\$5,890

COUNTERWEIGHT

L	393-0069	COUNTERWEIGHT, 960KG 0 ONLY FOR USE WITH: 505-1552 LINKAGE, STANDARD LIFT		NC
L	393-0072	COUNTERWEIGHT, 1460KG 0		\$2,185
L	423-1214	COUNTERWEIGHT, REAR GUARD 0 FOR USE WITH LANE 3 ONLY Hinged guard protecting radiator grill and cores for machine working in confined application. Provide same stability as the standard counterweight. ONLY FOR USE WITH: 538-2776 LINKAGE, STANDARD LIFT		\$11,300

POWERTRAIN

ENGINE PRECLEANER

L	365-0121	AIR INLET PRECLEANER, TRASH 0 FOR USE WITH LANE 3 ONLY Turbine engine air inlet precleaner, to be used in extremely high dust and airborne debris environments with a grill protecting precleaner from large debris.		\$980
L	365-0112	AIR INLET STANDARD, RAIN CAP 0 Includes standard strata tubes precleaner ejecting up to 96% of debris.		NC
L	365-0120	AIR INLET PRECLEANER, TURBINE 0 Turbine engine air inlet precleaner, to be used in extremely high dust and airborne debris environments.		\$745

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

POWERTRAIN (CONT.)

AXLE PACKAGES

Axle packages include a combination of traction aids, Ecology Drain (ED), Seal Guards (SG), and Axle Oil Cooler (AOC).

L	366-9903	AXLES, MANUAL/OPEN, ED 0 INCLUDES: -Manual front diff lock -Open rear differential -Ecology Drain CANNOT BE USED WITH: 513-5391 INDUSTRIAL PACKAGE		\$600
L	366-9906	AXLES, MANUAL/OPEN, ED, SG 0 FOR USE WITH LANE 3 ONLY Includes: -Manual front diff lock -Open rear differential -Ecology Drain -Seal Guards		\$2,180
L	366-9910	AXLES, AUTO/AUTO, ED, SG 0 FOR USE WITH LANE 3 ONLY INCLUDES: -Automatic front and rear diff lock -Ecology Drain -Seal Guards		\$8,120
L	366-9907	AXLES, MANUAL/OPEN, ED, AOC 0 INCLUDES: -Manual front diff lock -Open rear differential -Ecology Drain -Axle Oil Coolers Provides installed oil cooler system for front & rear axles Recommended for machines operating in high energy applications, such as extended load & carry CANNOT BE USED WITH: 513-5391 INDUSTRIAL PACKAGE		\$7,350
L	366-9908	AXLES, AUTO/AUTO, ED 0 INCLUDES: -Automatic front and rear diff lock -Ecology Drain CANNOT BE USED WITH: 513-5391 INDUSTRIAL PACKAGE		\$6,540
L	366-9911	AXLES, AUTO/AUTO, ED, AOC 0 FOR USE IN LANE 3 ONLY INCLUDES: -Automatic front and rear diff lock -Ecology Drain -Axle Oil Coolers Provides installed oil cooler system for front & rear axles Recommended for machines operating in high energy applications, such as extended load & carry. CANNOT BE USED WITH: 513-5391 INDUSTRIAL PACKAGE		\$13,290
L	366-9909	AXLES, AUTO/AUTO, ED, ETS 0 FOR USE IN LANE 3 ONLY INCLUDES: -Automatic front and rear diff lock -Ecology Drain -Extreme Temp Seals CANNOT BE USED WITH: 513-5391 INDUSTRIAL PACKAGE		\$7,500

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

POWERTRAIN (CONT.)

AXLE PACKAGES (Cont.)

L	366-9905	AXLES, MANUAL/OPEN, ED, ETS 0 FOR USE IN LANE 3 ONLY INCLUDES: -Manual front diff lock -Open rear differential -Ecology Drain -Extreme Temp Seals CANNOT BE USED WITH: 513-5391 INDUSTRIAL PACKAGE		\$1,565
---	----------	---	--	---------

HYDRAULICS

L	500-2567	HYDRAULICS, 4V RC STD/LOG 0 FOR USE WITH LANE 3 ONLY Provides 4 valve hydraulics and ride control. ONLY FOR USE WITH: 538-2778 LINKAGE, STANDARD LIFT 538-2776 LINKAGE, LOGGER		\$14,000
L	500-2571	HYDRAULICS, 4V RC HL 0 FOR USE WITH LANE 3 ONLY Provides 4 valve hydraulics and ride control. ONLY FOR USE WITH: 538-2777 LINKAGE, HIGH LIFT		\$14,000
L	500-2570	HYDRAULICS, 3V RC HL 0 FOR USE WITH LANE 3 ONLY. Provides 3 valve hydraulics and ride control. ONLY FOR USE WITH: 538-2777 LINKAGE, HIGH LIFT		\$10,580
L	506-3506	HYDRAULICS, 2V RC (3V READY) 0 Provides 2 valve hydraulics (3V ready) and ride control.		\$5,020
L	500-2566	HYDRAULICS, 3V RC STD/LOG 0 Provides 3 valve hydraulics and ride control. ONLY FOR USE WITH: 505-1552 LINKAGE, STANDARD LIFT 505-1554 LINKAGE, LOGGER 950		\$10,580
L	501-0400	HYDRAULICS, 2V RC 0 Provides 2 valve hydraulics and ride control.		\$4,720

HYDRAULIC OIL

L	366-9912	HYDRAULIC OIL, STANDARD 0 Cat HYDO Advanced 10 allows to extend oil change intervals up to 6000 hours with S-O-S services.		NC
---	----------	---	--	----

STARTERS, BATTERIES, & ALTERNATORS

ENGINE STARTING PACKAGE

L	373-3911	STARTING, COLD (120V) 0 Provides 145-amp brushed alternator, 120V block heater, ether aid ready, transmission & fan bypass.		\$1,625
L	373-3910	STARTING, STANDARD 0 Provides 145-amp brushed alternator.		NC

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

ELECTRICAL

LIGHTS

L	569-2124	LIGHTS, LED, PREMIUM 0 Provides LED Rooding lights: -2 Forward roading lights LED(low/high beam) with LED turn signal -2 Rear LED position stop turn lights Provides LED Work lights: -2 Forward facing standard lights on the top of the cab -2 Forward facing high intensity lights on the top of the cab -4 Rear facing standard lights on the top of the cab -2 Rear facing standard lights on the Hood		\$3,425
L	486-2308	LIGHTS, HALOGEN, PREMIUM 0 Includes: -2 halogen forward roading lights (low/high beam) with halogen turn signals -2 halogen rear facing working lights in the hood -2 LED position/stop/turn lights -8 halogen working lights on the cab		\$900
L	486-2311	LIGHTS, HALOGEN 0 Provides Rooding lights : - 2 forward roading lights halogen(low/high beam) with Halogen turn signal. - 2 rear LED position stop turn lights Provides Halogen Work lights : - 2 forward facing standard lights on the top of the cab - 2 rear facing standard lights on the top of the cab - 2 rear facing standard lights on the Hood		NC
L	522-3605	LIGHTS, LED 0 FOR USE IN LANE 3 ONLY INCLUDES: -2 LED forward roading lights (low/high beam) with LED turn signals -2 LED rear facing working lights in the hood -2 LED position/stop/turn lights -4 LED working lights on the cab		\$2,575

OPERATOR ENVIRONMENT

Bluetooth radio technology enables the use of a hands free function such as listening to music and making phone calls. Authorization varies by country, please contact your Cat marketing representative with questions or click on the link below:
<https://dealer.cat.com/en/products/technology.html>

WINDOWS

L	477-1660	WINDOWS (CORROSION) 0 FOR USE WITH LANE 3 ONLY Provides a paint thickness which is more than two times the thickness of the standard paint, giving the cab extra resistance against corrosion. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		NC
---	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

WINDOWS (Cont.)

L	477-1659	WINDOWS RM (CORROSION) 0 FOR USE WITH LANE 3 ONLY Provides front windows mounted in rubber seals for faster replacement, with a paint thickness which is more than two times the thickness of the standard paint, giving the cab extra resistance against corrosion. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		\$5,680
L	493-9616	WINDOWS, RUBBER MOUNTED 0 FOR USE WITH LANE 3 ONLY Provides front windows mounted in rubber seals.		\$5,290
L	493-9617	WINDOWS, RUBBER MTD, FRONT GRD 0 FOR USE IN LANE 3 ONLY Provides front windows mounted in rubber seals and a front window guard.		\$8,970
L	493-9619	WINDOWS, STANDARD, FRONT GUARD 0 FOR USE IN LANE 3 ONLY Provides a front window guard.		\$3,685
L	493-9618	WINDOWS, STANDARD, FULL GUARD 0 FOR USE IN LANE 3 ONLY Provides a full window guard.		\$12,670
L	493-9615	WINDOWS, STANDARD 0		NC

STEERING

L	538-2794	STEERING SYST, STD, JOY 0 Provides an EH steering system.		\$10,110
L	538-2796	STEERING SYST, STD, WHL 0 Provides an HMU steering system.		NC
L	538-2795	STEERING SYST, SECONDARY, JOY 0 Provides an EH steering system & secondary steering.		\$14,660
L	538-2797	STEERING SYST, SECONDARY, WHL 0 Provides an HMU steering system & secondary steering.		\$4,550

IMPLEMENT SINGLE AXIS LEVERS FOR STEERING

L	539-6028	LEVERS 4V, STEERING WHEEL 0 FOR USE WITH LANE 3 ONLY INCLUDES: -3 single action levers for implement lift, tilt & 3rd function controls -1 roller switch controlling the 4th function & FNR switch on implement pod ONLY FOR USE WITH: 538-2797 STEERING, WHEEL HMU, SECOND or 538-2796 STEERING, WHEEL HMU		NC
L	539-6051	LEVERS 4V, STEERING JOYSTICK 0 FOR USE WITH LANE 3 ONLY INCLUDES: -3 single action levers for implement lift, tilt & 3rd function controls -1 roller switch controlling the 4th function on implement pod ONLY FOR USE WITH: 538-2795 STEERING, LHD JOYSTICK, SECOND or 538-2794 STEERING, LHD JOYSTICK		NC

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

IMPLEMENT SINGLE AXIS LEVERS FOR STEERING (Cont.)

L	539-6031	LEVERS 2V, STEERING JOYSTICK 0 INCLUDES: -2 single action levers for implement lift & tilt controls ONLY FOR USE WITH: 501-0400 HYDRAULICS, 2V RC, STD/LOG/HL 434-0710 STEERING, LHD, JOYSTICK 434-0711 STEERING, LHD JOYSTICK, SECOND 538-2795 STEERING, LHD JOYSTICK, SECOND 538-2794 STEERING, LHD JOYSTICK		NC
L	539-6041	LEVERS 3V, STEERING JOYSTICK 0 INCLUDES: -3 single action levers for implement lift, tilt & 3rd function ONLY FOR USE WITH: 500-2566 HYDRAULICS, 3V RC, STD/LOGGER 538-2795 STEERING, LHD JOYSTICK, SECOND 538-2794 STEERING, LHD JOYSTICK		NC
L	539-6020	LEVERS 2V, STEERING WHEEL 0 INCLUDES: -2 single action levers for implement lift & tilt controls -FNR switch on implement pod ONLY FOR USE WITH: 501-0400 HYDRAULICS, 2V RC, STD/LOG/HL 538-2797 STEERING, WHEEL HMU, SECOND 538-2796 STEERING, WHEEL HMU		NC
L	539-6024	LEVERS 3V, STEERING WHEEL 0 INCLUDES: -3 single action levers for implement lift, tilt & 3rd function controls -FNR switch on implement pod ONLY FOR USE WITH: 500-2566 HYDRAULICS, 3V RC, STD/LOGGER 538-2797 STEERING, WHEEL HMU, SECOND 538-2796 STEERING, WHEEL HMU		NC

IMPLEMENT JOYSTICK FOR STEERING

L	539-6054	JOYSTICK 4V, STEERING JOYSTICK 0 FOR USE WITH LANE 3 ONLY INCLUDES: -Implement joystick for lift & tilt controls -Horn & kickdown trigger switches integrated in implement joystick -2 rollers switch controlling the 3rd & 4th functions integrated in the joystick ONLY FOR USE WITH: 538-2795 STEERING, LHD JOYSTICK, SECOND 538-2794 STEERING, LHD JOYSTICK		\$1,590
L	539-6036	JOYSTICK 2V, STEERING JOYSTICK 0 INCLUDES: -Implement joystick for lift & tilt controls -Horn & kickdown trigger switches integrated in implement joystick ONLY FOR USE WITH: 501-0400 HYDRAULICS, 2V RC, STD/LOG/HL 538-2795 STEERING, LHD JOYSTICK, SECOND 538-2794 STEERING, LHD JOYSTICK		\$1,100

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

IMPLEMENT JOYSTICK FOR STEERING (Cont.)

L	539-6046	JOYSTICK 3V, STEERING JOYSTICK 0 INCLUDES: -Implement joystick for lift & tilt controls -Horn & kickdown trigger switches integrated in implement joystick -1 roller switch controlling the 3rd function integrated in the joystick ONLY FOR USE WITH: 500-2566 HYDRAULICS, 3V RC, STD/LOGGER or 538-2795 STEERING, LHD JOYSTICK, SECOND 538-2794 STEERING, LHD JOYSTICK		\$1,545
L	539-6022	JOYSTICK 2V, STEERING WHEEL 0 INCLUDES: -Implement joystick for lift & tilt controls -Horn, FNR and kickdown trigger switches integrated in implement joystick ONLY FOR USE WITH: 501-0400 HYDRAULICS, 2V RC, STD/LOG/HL 538-2797 STEERING, WHEEL HMU, SECOND 538-2796 STEERING, WHEEL HMU		\$1,100
L	539-6026	JOYSTICK 3V, STEERING WHEEL 0 INCLUDES: -Implement joystick for lift & tilt controls -Horn, FNR & kickdown trigger switches integrated in implement joystick -1 roller switch controlling the 3rd function integrated in the joystick ONLY FOR USE WITH: 500-2566 HYDRAULICS, 3V RC, STD/LOGGER 538-2797 STEERING, WHEEL HMU, SECOND 538-2796 STEERING, WHEEL HMU		\$1,545
L	539-6029	JOYSTICK 4V, STEERING WHEEL 0 FOR USE WITH LANE 3 ONLY INCLUDES: -Implement joystick for lift & tilt controls -Horn, FNR & kickdown trigger switches integrated in implement joystick -2 rollers switch controlling the 3rd & 4th functions integrated in the joystick ONLY FOR USE WITH: 538-2797 STEERING, WHEEL HMU, SECOND 538-2796 STEERING, WHEEL HMU		\$1,720

SEAT BELT

L	551-3397	SEAT BELT, 3" 0		\$106
---	----------	---------------------------	--	-------

DIFFERENTIAL

L	384-7005	AUTO DIFF, STEERING WHEEL 0 ONLY FOR USE WITH: 366-9908 AXLES, AUTO DIFF F/R, ED or 366-9910 AXLES, AUTO DIFF F/R, ED, SG or 366-9911 AXLES, AUTO DIFF F/R, ED, AOC and 538-2797 STEERING, WHEEL HMU, SECOND 538-2796 STEERING, WHEEL HMU		NC
---	----------	--	--	----

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

DIFFERENTIAL (Cont.)

L	384-7006	MANUAL DIFF, STEERING WHEEL 0 ONLY FOR USE WITH: 366-9903 AXLES, LOCK/OPEN, ED or 366-9905 AXLES, LOCK/OPEN, ED, ETS or 366-9906 AXLES, LOCK/OPEN, ED, SG or 366-9907 AXLES, LOCK/OPEN, ED, AOC and 538-2797 STEERING, WHEEL HMU, SECOND 538-2796 STEERING, WHEEL HMU		NC
L	384-7003	AUTO DIFF, STEERING JOYSTICK 0 ONLY FOR USE WITH: 366-9908 AXLES, AUTO DIFF F/R, ED or 366-9910 AXLES, AUTO DIFF F/R, ED, SG or 366-9911 AXLES, AUTO DIFF F/R, ED, AOC and 538-2795 STEERING, LHD JOYSTICK, SECOND or 538-2794 STEERING, LHD JOYSTICK		NC
L	384-7004	MANUAL DIFF, STEERING JOYSTICK 0 ONLY FOR USE WITH: 366-9903 AXLES, LOCK/OPEN, ED or 366-9905 AXLES, LOCK/OPEN, ED, ETS or 366-9906 AXLES, LOCK/OPEN, ED, SG or 366-9907 AXLES, LOCK/OPEN, ED, AOC and 538-2795 STEERING, LHD JOYSTICK, SECOND or 538-2794 STEERING, LHD JOYSTICK		NC

CAB FILTERS

L	505-1521	FILTRATION, STEEL 0 FOR USE WITH LANE 3 ONLY INCLUDES: -CAB ROOF, STEEL -COVER, HVAC, STEEL. CANNOT BE USED WITH: 543-3606 CORROSION RESISTANT PACKAGE REQUIRED BY: STEEL MILL PACKAGE		\$2,165
L	505-1519	FILTRATION, STANDARD 0 INCLUDES: -CAB ROOF, NON-METALLIC -COVER, HVAC, NON-METALLIC		NC
L	505-1520	FILTRATION, STD, PRECLEANER 0 FOR USE WITH LANE 3 ONLY INCLUDES: -CAB ROOF, NON-METALLIC -COVER, HVAC, NON-METALLIC -PRECLEANER, HVAC Provides a precleaner for dusty environments for cab air intake.		\$695
L	505-1522	FILTRATION, STEEL, ACF PRECLNR 0 FOR USE WITH LANE 3 ONLY INCLUDES: -CAB ROOF, STEEL -COVER, HVAC, STEEL FOR ACF -ACF PRECLEANER, HVAC CANNOT BE USED WITH: 543-3606 CORROSION RESISTANT PACKAGE		\$3,535

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

CAB FILTERS (Cont.)

L	505-1523	FILTRATION, STD, ACF PRECLNR 0 FOR USE WITH LANE 3 ONLY INCLUDES: -CAB ROOF, NON-METALLIC -COVER, HVAC, STEEL FOR ACF -ACF PRECLEANER, HVAC CANNOT BE USED WITH: 543-3606 CORROSION RESISTANT PACKAGE		\$1,880
---	----------	--	--	---------

TRIM ARRANGEMENT

L	538-2770	CAB TRIM, COMFORT (HMU) 0 INCLUDES: -SEAT, COMFORT, HMU Provides steering wheel and comfort seat with manual lumbar adjustment -MIRRORS, EXTERNAL -SUN VISOR, REAR Provides pull down sun screen in rear window. ONLY FOR USE WITH: 538-2797 STEERING, WHEEL HMU, SECOND or 538-2796 STEERING, WHEEL HMU		\$69
---	----------	---	--	------

L	538-2771	CAB TRIM, DELUXE (HMU) 0 INCLUDES: -SEAT, DELUXE, HMU Provides steering wheel and deluxe seat containing resistance heating, manual lumbar and 2-way thigh adjustment, ride stiffness adjustment, and suede accents. -MIRRORS, EXTERNAL, HEATED -DOOR, REMOTE OPENING SYSTEM Provides remote manual switch allowing to open the cab door from ground level. -SUN VISOR, REAR Provides pull down sun screen in rear window. ONLY FOR USE WITH: 538-2797 STEERING, WHEEL HMU, SECOND or 538-2796 STEERING, WHEEL HMU		\$1,035
---	----------	---	--	---------

L	538-2773	CAB TRIM, COMFORT (LHD) 0 FOR USE WITH LANE 3 ONLY INCLUDES: -SEAT, COMFORT, LHD Provides steering joystick on left hand armrest and comfort seat with ride stiffness adjustment and manual lumbar adjustment. -MIRRORS, EXTERNAL -SUN VISOR, REAR Provides pull down sun screen in rear window. ONLY FOR USE WITH: 538-2795 STEERING, LHD JOYSTICK, SECOND or 538-2794 STEERING, LHD JOYSTICK		\$69
---	----------	--	--	------

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

TRIM ARRANGEMENT (Cont.)

L	538-2774	CAB TRIM, DELUXE (LHD) 0 INCLUDES: -SEAT, DELUXE, LHD Provides steering joystick on left hand armrest and deluxe seat containing resistance heating, manual lumbar and 2-way thigh adjustment, ride stiffness adjustment, dynamic end dampening, and suede accents. -MIRRORS, EXTERNAL, HEATED -DOOR, REMOTE OPENING SYSTEM Provides remote manual switch allowing to open the cab door from ground level. -SUN VISOR, REAR Provides pull down sun screen in rear window. ONLY FOR USE WITH: 538-2795 STEERING, LHD JOYSTICK, SECOND or 538-2794 STEERING, LHD JOYSTICK 434-0710 STEERING, LHD JOYSTICK or 434-0711 STEERING, LHD JOYSTICK, SECOND	0	\$1,190
L	538-2772	CAB TRIM, PREMIUM PLUS (HMU) 0 FOR USE WITH LANE 3 ONLY INCLUDES: -SEAT, PREMIUM PLUS, HMU Provides steering wheel and premium plus seat containing forced air heating and cooling, 2-way thigh adjustment, power lumbar and back bolster adjustment, ride stiffness adjustment, dynamic end dampening, and leather finish. -MIRRORS, EXTERNAL, HEATED -DOOR, REMOTE OPENING SYSTEM Provides remote manual switch allowing to open the cab door from ground level. -SUN VISOR, REAR Provides pull down sun screen in rear window ONLY FOR USE WITH: 538-2797 STEERING, WHEEL HMU, SECOND or 538-2796 STEERING, WHEEL HMU	0	\$3,925
L	538-2775	CAB TRIM, PREMIUM PLUS (LHD) 0 FOR USE WITH LANE 3 ONLY INCLUDES: -SEAT, PREMIUM PLUS, LHD Provides steering joystick on left hand armrest and premium plus seat containing forced air heating and cooling, 2-way thigh adjustment, power lumbar and back bolster adjustment, ride stiffness adjustment, dynamic end dampening, and leather finish. -MIRRORS, EXTERNAL, HEATED -DOOR, REMOTE OPENING SYSTEM Provides remote manual switch allowing to open the cab door from ground level. -SUN VISOR, REAR Provides pull down sun screen in rear window. ONLY FOR USE WITH: 384-7008 STEERING, LHD JOYSTICK, SECOND or 384-7007 STEERING, LHD JOYSTICK	0	\$3,925

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet.

Availability varies by country, please contact your Cat marketing representative with questions or click on the link below:
[HTTPS://DEALER.CAT.COM/en/bt/otd/machine-price-list.html](https://dealer.cat.com/en/bt/otd/machine-price-list.html)
 From there click on the "PRODUCT LINK Hardware Certification" link.

L	434-0691	PRODUCT LINK, CELLULAR PLE641 0 Product Link Elite series PLE641 (consisting of PL641 radio and PLE601 network manager) uses cellular networks to transmit location, utilization, health and productivity information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		NC
L	434-0693	PRODUCT LINK, SATELLITE PLE631 0 Product Link Elite series PLE631 (consisting of PL631 radio and PLE601 network manager) uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		\$446

COOLING

COOLING SYSTEM

L	521-9359	COOLING CORES, 6 FPI 0 Provides cooling capability up to 43C (109F) ambient. Radiator with 6 fins per inch.		\$347
L	521-9358	COOLING CORES, 9 FPI 0 Provides cooling capability up to 47C (117F) ambient. Radiator with 9 fins per inch.		NC
L	524-1394	COOLING CORES 6 FPI, CORROSION 0 FOR USE WITH LANE 3 ONLY Provides cooling capability up to 43C (109F) ambient. Radiator with 6 fins per inch. - Cores protected (painted); - Grease points on the radiator hinges. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		\$3,060
L	524-1393	COOLING CORES 9 FPI, CORROSION 0 FOR USE WITH LANE 3 ONLY Provides cooling capability up to 47C (117F) ambient. Radiator with 9 fins per inch. - Cores protected (painted); - Grease points on the radiator hinges. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		\$2,705

COOLING FAN

L	513-5394	FAN, STANDARD 0 Standard load sensing hydraulically driven fan.		NC
---	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

COOLING (CONT.)

COOLING FAN (Cont.)

L	513-5393	FAN, REVERSING, VPF, ANSI 0		\$5,330
		FOR USE WITH LANE 3 ONLY Provides an attachment reversing function to the standard hydraulically driven demand fan. This provides the ability to rotate blades and to reverse the airflow direction to remove debris from the radiator and engine enclosures while the machine is still operating. Includes automatic and manual controls for airflow reversal. Recommended for applications with a high content of airborne debris. ONLY FOR USE WITH: 521-9359 COOLING CORES 6 FPI 524-1394 COOLING CORES 6 FPI, CORROSION		

COOLANT

L	371-7064	ANTIFREEZE, -34C (-29F) 0		NC
		Premix Antifreeze, -34C or -29F		
L	423-2664	ANTIFREEZE, -50C (-58F) 0		\$283 NET
		Premix Antifreeze, -50C or -58F		

TIRES, RIMS, AND WHEELS

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice. However, if the tire type cannot be supplied we will contact the dealer to propose alternatives. The dealer needs to choose between an alternative tire or a "rims only" option (where available) within 72 hours. If no response is provided by the deadline, the order will default to the alternative tire and will be changed at that point. As a consequence of a possible tire change, the total machine price will be decreased or increased depending on the price of the new tire.

NOTE: All tires include rims & come in a set of 4. Tires are tubeless & non-directional unless otherwise stated.

NOTE: Other tires are available upon request.

TIRES AVAILABLE FROM MICHELIN

P	373-4052	TIRES, 23.5R25 MX XHA2 * L3 0		\$-3,310
---	----------	---	--	----------

TIRES AVAILABLE FROM BRIDGESTONE

P	373-4053	TIRES, 23.5R25 BS VJT * L3 0		\$-3,415
		FOR USE IN LANE 3 ONLY		
P	509-1481	TIRES, 750/65R25 BS VTS * L3 0		\$11,000
		FOR USE IN LANE 3 ONLY		

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS (CONT.)

TIRES AVAILABLE FROM MAXAM

P	547-8401	TIRES, 23.5R25 MA MS302 **E3/L3 0 MAXAM RADIAL; TREAD DEPTH=36.5mm; Rim=19.5"x25" 3 piece Provides reduced vibration, damage resistance, and traction in soft to rocky underfoot conditions.		\$-9,000
P	594-6818	TIRES, 23.5R25 MA MS202 ** L2 0 FOR USE IN LANE 3 ONLY		\$-6,960

SOLID TIRES

P	540-4373	TIRES, 23.5X25 BR TRACTION 0 FOR USE IN LANE 3 ONLY Brawler HPS Solidflex Traction Off-the-Road (OTR) tread solid tires pressed on to standard CAT rims. Ideal for harsh/special applications on unimproved surfaces, such as as brick, glass, and scrap yards where debris is not an issue. Machine oscillation is reduced.		\$17,250
P	540-4374	TIRES, 23.5X25 BR SMOOTH 0 FOR USE IN LANE 3 ONLY Brawler HPS Solidflex Smooth tread solid tires pressed on to standard CAT rims. Ideal for harsh/special applications where debris is an is an issue, such as scrap yards, recycling centers and waste transfer stations. Machine oscillation is reduced.		\$20,550

TIRES/RIMS, ALLOWANCE FOR OMISSION

Dealers should contact their Application Specialist if they plan to use a tire not offered on the price list. Some tires may require axle oscillation stops or other machine modifications.

P	373-4064	RIMS ONLY, TIRES OMITTED 0 FOR USE IN LANE 3 ONLY		\$-16,240
P	0P-3647	OMISSION, TIRES AND RIMS 0 FOR USE IN LANE 3 ONLY		\$-19,590

BODY

FENDERS

L	464-6675	FENDERS, ROADING, LOW PROFILE 0 FOR USE IN LANE 3 ONLY Provides front fenders with fender extensions and full wrap fenders for rear wheels. ONLY FOR USE WITH: LOW-PROFILE (65-SERIES) TIRES		\$3,115
L	464-6672	FENDERS, BASIC +. 0		NC
L	464-6673	FENDERS, ROADING 0 Provide non-metallic front fenders with top extension, mud flaps and full wrap non-metallic rear fenders with removable mud flaps. CANNOT BE USED WITH: LOW-PROFILE (65-SERIES) TIRES		\$2,815

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

BODY (CONT.)

FENDERS (Cont.)

L	464-6674	FENDERS, BASIC +, LOW PROFILE 0 FOR USE IN LANE 3 ONLY Provide non-metallic front fenders with mud flaps and short rear fender extensions covering top of wheel. ONLY FOR USE WITH: LOW-PROFILE (65-SERIES) TIRES		\$155
C	478-8371	FENDERS, NARROW 0 FOR USE IN LANE 3 ONLY CONTACT CUSTOM PRODUCTS FOR AVAILABILITY. Provides narrow steel front fenders, steel rear fender extensions and heavy duty hanging steel steps. CANNOT BE USED WITH: LOW-PROFILE (65-SERIES) TIRES REQUIRED BY: INDUSTRIAL PACKAGE		\$3,085

HOOD

L	477-1667	HOOD - CORROSION 0 FOR USE IN LANE 3 ONLY Grease points for the articulated Hood Pins. Provide sufficient greasing and normal hinge functioning in corrosive environment. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		NC
L	336-0000	HOOD, NON-METALLIC 0		NC

SOUND SUPPRESSION

L	465-6576	SOUND SUPPRESSION, STANDARD 0		NC
L	488-1138	SOUND SUPPRESSION, INDUSTRIAL 0 FOR USE WITH LANE 3 ONLY Provides steering cylinder guards for high debris applications.		\$1,100

FLUIDS

LUBRICATION ARRANGEMENTS

L	538-2788	LUBRICATION, MANUAL, STD 0 ONLY FOR USE WITH: 538-2776 LINKAGE, STANDARD LIFT or 538-2778 LINKAGE, LOGGER		NC
L	538-2789	AUTOLUBE, STD/LOG 0 Provides Caterpillar autolube system. ONLY FOR USE WITH: 538-2776 LINKAGE, STANDARD LIFT or 538-2778 LINKAGE, LOGGER		\$6,540
L	538-2792	LUBRICATION, MANUAL, HL 0 FOR USE IN LANE 3 ONLY ONLY FOR USE WITH: 538-2777 LINKAGE, HIGH LIFT		NC
L	538-2793	AUTOLUBE, HL 0 FOR USE IN LANE 3 ONLY Provides Caterpillar Autolube System for high lift. ONLY FOR USE WITH: 538-2777 LINKAGE, HIGH LIFT		\$6,750

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------------	-----------------	----------------------

FLUIDS (CONT.)

FUEL ANTIFREEZE

0P-3978	FUEL ANTIFREEZE, -25C (-13F)	0	NC
	Provides fuel (diesel) antifreeze protection down to -25C (-13F)		

INSTRUCTIONS

OPERATION AND MAINTENANCE MANUAL

NOTE: Operation and maintenance Manual will be included in language requested below.

0P-3380	INSTRUCTIONS, ENGLISH	0	NC
---------	---------------------------------	---	----

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OPERATOR ENVIRONMENT

RADIOS.

Bluetooth radio technology enables the use of a hands free function such as listening to music and making phone calls. Authorization varies by country, please contact your Cat marketing representative with questions or click on the link below: <https://dealer.cat.com/en/products/technology.html>

P	372-1603	RADIO, CB (READY) 0 Provides adjustable mounting brackets for two radios, a 20 amp 24V to 12V converter, a CB antenna, CB cable converter, and two separate four wire connectors that contain a ground, 12V and 24 V circuits. INCLUDED IN: 486-9205 OBJECT DETN & CB RADIO READY		\$970
P	600-3625	RADIO, AM/FM/BLUETOOTH 0 Provides AM/FM/MP3 radio.		\$600

INTEGRATED OBJECT DETECTION SYSTEM

The Cat Integrated Object Detection adds radar and alarms to the standard on-board rear vision camera to notify the operator when something is close to the rear of the machine. This system is configured with zones, and objects in those zones trigger various levels of alarms. A display screen in the cab provides visual confirmation of the objects detected by the radar, so operators can make informed decisions.

L	486-9204	OBJECT DETECTION 0 CANNOT BE USED WITH: 423-1214 COUNTERWEIGHT, REAR GUARD		\$2,800
L	486-9205	OBJECT DETN & CB RADIO READY 0 INCLUDES: 486-9204 OBJECT DETECTION 372-1603 RADIO, CB (READY) CANNOT BE USED WITH: 423-1214 COUNTERWEIGHT, REAR GUARD		\$3,740

VISIBILITY

P	380-5964	SECONDARY CAMERA DISPLAY 0 FOR USE WITH LANE 3 ONLY Provides full-time display dedicated to rear-view camera.		\$1,780
---	----------	--	--	---------

SECURITY SYSTEM

P	372-1604	SECURITY SYSTEM, MACHINE 0 FOR USE WITH LANE 3 ONLY Protects from vandalism and theft by preventing unauthorized personnel from starting a machine. Machines start only after a unique MSS key is inserted into the ignition. MSS keys can be programmed to start machines only certain days or hours.		\$710
---	----------	---	--	-------

LIGHTS

P	513-2458	LIGHTS, REVERSING STROBE 0 Provides 2 reversing white strobes.		\$279
---	----------	--	--	-------

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

LIGHTS (Cont.)

P	460-7450	LIGHT, SEAT BELT WARNING 0 Provides a seat belt warning light mounted to the rear of the cab structure.		\$233
P	491-7467	LIGHT, WARNING BEACON 0 Provides hard mounted strobe beacon on hinged (breakaway) bracket mounted to the rear of the cab structure.		\$493

TECHNOLOGY PRODUCTS

REQUIRED BY: AM-S

SOFTWARE ENABLED ATTACHMENTS (SEA) INSTRUCTIONS

Technology apps are activated by Software Enabled Attachments (SEA). SEAs are available factory installed or can be purchased for dealer installation.

Refer to Information Release Memo (IRM) EES03 -01 (media number PELJ0138) in the Caterpillar Media Information Center for further explanation of SEAs. Select the Product Support tab and search for number PELJ0138. Refer to REHS1238 & REHS8401 for how to obtain a Factory Level Password. Contact FPS: Internet with Corporate Web Security (CWS) ([https:// fps.cat.com/](https://fps.cat.com/)).

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

CAT PRODUCTION MEASUREMENT (CPM) PAYLOAD WEIGHING SYSTEM

- Cat M-series Medium Wheel Loaders are available with the Cat Production Measurement (CPM) that includes an integrated onboard payload weighing scale. This measures and/or records:
- Payload weight, material ID, truck ID, cycle (bucket dumps) count and fuel consumption
 - Allows on-the-go weighing of the bucket payload during the lift cycle
 - Daily payload total (tonnes/tons), productivity (tonnes/hour or tons/hour) and efficiency (tonnes/litre or tons/gal) data is reported wirelessly via Product Link to the Vision Link fleet management web portal (Cat Essentials Product Link subscription required).
 - Detailed payload, productivity and efficiency data can be downloaded to a laptop computer for analysis in the optional VIMS pc software (VIMS pc and VIMS data cable are required, but VIMS is NOT required).
 - Payload tickets can be printed with an optional printer

Refer to the Cat Connect Payload Technologies intranet page (<https://dealer.cat.com/payload>) for complete technical specifications; operation, sales, marketing and technical support publications.

NOTES:

- 1) Permanent software is available from the factory below.
- 2) For field installation, permanent software can be purchased through the Caterpillar Feature Protection System and enabled by a dealer technician with Cat ET and an SEA password. SEA p/n 517-4683. Consult ANTARES parts distribution system for latest SEA price.
- 3) Both demo and permanent software require calibration prior to customer use.

CALIBRATION INSTRUCTIONS

This requires calibration and set-up by either the dealer or customer. Refer to the Systems Operation Test & Adjust manual UENR7119 for system calibration, material and truck ID lists set-up and operation instructions.

P	370-3813	CPM PAYLOAD WEIGHING READY 0		\$233
		FOR USE IN LANE 3 ONLY		
		Includes CPM hardware and demo software for up to 250 hours. Demo software must be dealer enabled. Permanent activation requires software purchase and calibration. See notes 2 & 3 above.		
		CANNOT BE USED WITH: 512-0858 STANDARD PACKAGE		
P	517-7123	CPM PAYLOAD SOFTWARE 0		\$5,040
		Includes hardware and permanent software for CPM. Software is factory enabled, but the system must be calibrated prior to customer use. See note above for calibration instructions.		
		(Not available for all countries. Contact PL Admin for details).		
		REQUIRES: 478-1336 AUTODIG & CPM PAYLOAD, ARO		
		ONLY FOR USE WITH: 370-3813 CPM PAYLOAD WEIGHING READY or 512-0858 STANDARD PACKAGE		
		CANNOT BE USED WITH: 517-7122 AUTODIG + CPM PAYLOAD		

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

AUTODIG

Autodig is a software enabled attachment that controls the implement system during the bucket loading portion of a cycle to automatically load aggregate material.
 NOT RECOMMENDED for hardbank or large rock loading.

P	453-3250	AUTODIG SOFTWARE	0	\$1,450
		Includes software for Aggregate Autodig. NOT RECOMMENDED for hardbank or large rock loading. REQUIRES: 478-1336 AUTODIG & CPM PAYLOAD, ARO		

GUARDS

L	397-1606	GUARD, TILT CYLINDER	0	\$1,435
		FOR USE IN LANE 3 ONLY ONLY FOR USE WITH: LINKAGE, LOGGER		
P	485-4387	GUARDS, LIGHT	0	\$1,615
		FOR USE IN LANE 3 ONLY Provide protection guard for lights installed on the cab and counterweight.		
L	360-8835	GUARD, TILT CYLINDER	0	\$1,435
		FOR USE WITH LANE 3 ONLY CANNOT BE USED WITH: LINKAGE, LOGGER REQUIRED BY: INDUSTRIAL PACKAGE		
L	367-9027	GUARD, POWERTRAIN	0	\$1,545
L	399-4332	GUARD, HINGED, POWERTRAIN	0	\$3,365
		FOR USE WITH LANE 3 ONLY Provides heavy duty guard to protect the bottom of the transmission; hinged for service. ONLY FOR USE WITH: INDUSTRIAL PACKAGE REQUIRED BY: INDUSTRIAL PACKAGE		

OTHER ATTACHMENTS

P	506-4369	WHEEL CHOCKS	0	\$505
		Provides wheel chocks that mount to the frame.		
P	503-4735	OIL CHANGE SYSTEM, HIGH SPEED	0	\$295
		Easy access drain line and Wiggins connector for remote engine oil drain. Provides quick, clean, and easy engine oil change without having to climb under the machine to access a gravity drain.		

CORROSION RESISTANT OPTIONS

L	506-0545	PROTECTION PACKAGE, LINES	0	\$4,865
		FOR USE WITH LANE 3 ONLY Hoses treated with tube heat shrinkable and sealant silicone. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		
L	521-9198	PAINTING GROUP, CORROSION	0	\$5,040
		FOR USE IN LANE 3 ONLY Provides a paint thickness which is more than two times the thickness of the standard paint, giving the machine extra resistance against corrosion. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

QUICK COUPLERS

P	373-3904	QUICK COUPLER READY, HL 0 FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 538-2777 LINKAGE, HIGH LIFT REQUIRED BY: AM-N Dealers		\$3,795
P	373-3900	QUICK COUPLER READY, STD 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed Caterpillar Work Tools & Services (CWTS) fusion style coupler. ONLY FOR USE WITH: 538-2776 LINKAGE, STANDARD LIFT 538-2778 LINKAGE, LOGGER REQUIRED BY: AM-N Dealers		\$3,795
P	378-8421	LINES GP-IMPLEMENT 3V (QC) 22 ALSO AVAILABLE ON A MISCELLANEOUS ORDER REQUIRES: 500-2566 or 500-2570 HYDRAULICS, 3V 349-5246 QUICK COUPLER, FUSION		\$560
L	378-8422	LINES GP-IMPLEMENT 3V&4V (QC) 44 FOR USE WITH LANE 3 ONLY REQUIRES: 373-3894 or 373-3898 HYDRAULICS, 4V 349-5246 QUICK COUPLER, FUSION		\$1,118
L	349-5246	QUICK COUPLER, FUSION 1,248 1,248 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed Caterpillar Work Tools & Services (CWTS) Fusion style coupler. Requires 378-8421 Lines if ordering 3V hydraulics. ONLY FOR USE WITH: 373-3900 QUICK COUPLER READY, STD LIFT OR 373-3904 QUICK COUPLER READY, HIGH LIFT		\$6,778 \$6,778 NI

WORK TOOLS

OMISSION WORK TOOL

P	361-1437	OMISSION, WORKTOOL 0 Required in orders configured without a work tool or QC in order to prevent from damages on the linkage.		NC
---	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------------	--------------------	-------------------------

BUCKETS

REQUIRED BY: AM-S

Buckets must be ordered Installed on a Machine Order.
 For questions on buckets intended for Machine Orders please contact your Marketing Subsidiary Machine Coordinator.

Loose buckets should be ordered on a MISC Order through Caterpillar Work Tools - Wamego using source code OP-0672.

For availability of loose buckets please email worktools@cat.com.
 If you are going to order a loose bucket from CWTS and a machine from Aurora and if you need them shipped at the same time then you need to cross-reference the MSO's with each other.

"GET" is NOT automatically included on bucket orders. "GET" must be entered on the order with your bucket selection, unless text for bucket states otherwise. Please make the "GET" selection from the "GET" listed immediately following the bucket listing.

Recommend use of bolt-on adapter option, adapter and segment option, or bolt-on cutting edge option for general purpose buckets and material handling buckets.

Material density will determine the appropriate capacity bucket. Refer to the Spec log. Exceeding maximum payload may cause loader instability.

ALL BUCKETS ARE ALSO AVAILABLE ON A MISCELLANEOUS ORDER.

110% FILL FACTOR: This capacity is calculated considering GETs installed.

GENERAL PURPOSE PERFORMANCE SERIES BUCKETS (PIN-ON)

P	516-1452	BKTA GP ST 115" 4.50YD3 PO 4, 242 PERFORMANCE SERIES BUCKET INCLUDES: BOLT-ON CUTTING EDGE (BOCE)	\$16, 428
P	516-2814	BKTA GP ST 115" 4.75YD3 PO 4, 323 FOR USE WITH LANE 3 ONLY PERFORMANCE SERIES BUCKET INCLUDES: BOLT-ON CUTTING EDGE (BOCE)	\$16, 853

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

BUCKETS (CONT.)

GENERAL PURPOSE BUCKETS (FUSION)

P	354-4856	BKT GP ST 114" 4.75YD3 FUS	3,503	\$14,932
			3,503	\$14,932 NI

FOR USE IN LANE 3 ONLY
 PERFORMANCE SERIES BUCKET
 CAPACITIES:
 4.5YD3 (3.4M3) w/bolt-on adaptaters, 117" (2972mm) wide
 4.75YD3 (3.6M3) w/bolt-on adaptaters and segment, 117" (2972mm) wide
 4.75YD3 (3.6M3) w/bolt-on cutting edges, 114"(2894mm)wide (Bucket Tag)
 110% FILL FACTOR:
 5.25YD3 (4M3) with GETs
 RECOMMENDED WITH : COUNTERWEIGHT, 1460KG

GROUND ENGAGING TOOLS

CUTTING EDGE

P	139-9229	CUTTING EDGE, BOLT-ON	600	\$1,461
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Width: 2906MM		

INSTRUCTIONS

FILMS

P	468-0170	FILM, SCRAP	0	NC
		ONLY FOR USE WITH: 513-5391 INDUSTRIAL PACKAGE		
P	468-0171	FILM, WASTE	0	NC
		ONLY FOR USE WITH: 513-5391 INDUSTRIAL PACKAGE or 505-1506 INDUSTRIAL PACKAGE		
P	468-0173	FILM, FOREST	0	NC
		ONLY FOR USE WITH: 538-2778 LINKAGE, LOGGER		

PACKING

EXPORT PACKING

	OP-6619	ROLL ON-ROLL OFF	0	\$267 NET
		Machine is in mobile condition and all attachments are installed unless specified.		

ALLOWANCE FOR OMISSION

P	OP-4781	ALLOWANCE FOR OMISSION	0	\$483
		REQUIRED BY: 373-4064 RIMS ONLY, TIRES OMITTED		

CATERPILLAR MACHINE PRICE LIST

950M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

PACKING (CONT.)

STORAGE PROTECTION

0P-2918	STORAGE PROTECTION 0 This product is added for corrosion protection while shipping and for extended storage periods. This product will need to be power washed with soapy water prior the shipment to the customer. REQUIRED BY : ALL LANE CONFIGURATION	NC
---------	--	-----------

SPECIAL INSTRUCTIONS

0P-2949	EXPOSITION INSTRUCTION 0 This special instruction must be selected whenever dealer is placing an order for a unit intended for use at expositions and/or trade fairs	NC
---------	--	-----------

CYLINDER PROTECTION

0P-3940	PROTECTION, CYLINDER ROD 0	NC
---------	---	-----------

AM-NORTH INFORMATION

REGIONAL PACKAGE

Information only DO NOT ORDER

L	505-1505	STANDARD PACKAGE 0 Provides machine features required in standard and forestry applications. PACKAGE INCLUDES: - Platform - Filter cab air - Standard Radiator grill INCLUDED IN: 513-5376 950M WHEEL LOADER AM-N DCA9 513-5377 950M WHEEL LOADER AM-N DCA10 513-5378 950M WHEEL LOADER AM-N DCA11	NC
---	----------	---	-----------

TECHNOLOGY PRODUCTS

L	434-0690	NETWORK MANAGER ONLY 0 Information only DO NOT ORDER INCLUDED IN: 513-5376 950M WHEEL LOADER AM-N DCA9 513-5377 950M WHEEL LOADER AM-N DCA10 513-5378 950M WHEEL LOADER AM-N DCA11	NC
---	----------	---	-----------