

CATERPILLAR MACHINE PRICE LIST

AP655FAP655F ASPHALT PAVER
MINNEAPOLIS, MN, USA (SAP)Ship Weight
lbsLIST PRICE
AT DEALER

Standard Equipment:

POWERTRAIN

CAT turbo-charged diesel engine
Air cleaner, dry-type dual element with
integral precleaner
Air-to-air after cooler (ATAAC)
Belt, automatic tensioner
Demand fans
Fuel filter / water separator
Fuel priming pump, electric
Propel system - direct hydrostatic,
dual path drive, electronic control
Dual braking systems (service & parking)
Dual propel pump and motor system
Propel modes, pave/travel/maneuver
Speed control system

ELECTRICAL

Alarm, back-up
Alternator, 100-amp
Batteries, two maintenance free,
1000 CCA each
CAT ET diagnostic connector
Integrated 70 KW generator
Horn, forward warning
Machine security system wire-ready
Product link ready
Remote jump start receptacle
Starting and charging system, 24-volt
Plug and play aftermarket grade and
slope ready machine wiring

OPERATOR ENVIRONMENT

Electronic monitoring and warning
system with advanced element
diagnostics
Automatic engine speed control
Dual, swing-out operator stations
-Control console, tilting
-Propel console, tilting
-Cup holder
-Ground speed indicator
-Propel lever with speed control dial
-Steering wheel, spring return
12 V aux power port
Hopper wing control, independent
Hour meter
Instrumentation, dual LCD touchscreens
Lockable vandalism guards
Platform handrails / guardrails
Power assist steering
Throttle control, high/low idle,
ECO-mode and variable, electronic

APPLICATION SPECIFIC COMPONENTS

Adjustable height augers, hydraulic
cast ni-hard steel, split segment,
406 mm (16 in) diameter
Electronic auger/feeder control system
-Gateless feeder system
-Manual override
-Reversible
-Variable speed
Heavy-duty feeder flight bars, forged
steel, bushed roller chain
High-hardness, abrasion resistant drag
pans, replaceable
Outboard feeder drives
Remote mounted bearing lube points

FLUIDS

Extended life coolant with protection
to -37C (-35F)

OTHER STANDARD EQUIPMENT

Doors, service access, hinged, locking
Filters, hydraulic, grouped
Fuel tank with sediment drain,
278 L (73 gal)
Grouped lube points
Pressure test ports, hydraulic
quick-connect
Screed counterbalance
Screed lock pins
Sight gauges:
-engine coolant
-pump drive
-material feed planetaries
Slow moving vehicle sign (for AM-N)
S.O.S. sampling ports
Sound-suppression insulation kit
Steering guide (1)
Tow point indicator scales, lower
Vandalism protection caplocks

CATERPILLAR MACHINE PRICE LIST

AP655F

AP655F ASPHALT PAVER
MINNEAPOLIS, MN, USA (SAP)

Ship Weight
lbs

LIST PRICE
AT DEALER

**Lane 2 is reserved for the Base Order Management Program.
Please use Lane 2 when placing orders that are part of the
Base Order Management program.**

424-9114	AP655F MTS ASPHALT PAVER, HRC	31,820	\$362,150
	LANE 2 - AVAILABLE FROM MINNEAPOLIS FACTORY		
	LANE 3 - AVAILABLE FROM MINNEAPOLIS FACTORY		

Mobil-trac System. Fully bogied undercarriage with rubber coated steel mid-wheels. Two-speed planetaries and single speed motors. Automatic track tensioning, hydraulic MUST select rubber belt from Mandatory Attachment section. For use with Tier 4F EPA/STG IV EU, aftertreatment and DEF systems.

OP-3697	AP655F MISC MATERIAL	0	NC
	AVAILABLE FROM MINNEAPOLIS FACTORY		
	Only reference numbers that have the text "ALSO AVAILABLE ON A MISCELLANEOUS" can be used on a MISC order.		

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0		NC
	Only for dealer enrolled in the Base Orders Management (BOM) program.			
OP-9003	LANE 3 ORDER	0		NC

FEATURE PACKAGES

HOPPER APRON CONTROL

L	433-7572	APRON, MANUAL FOLD	150		NC
		Manual raise hopper apron for easy material clean-out. Apron provides a minimum front entry height of 529 mm (20.8"). Can be used with either a standard side profile or low side profile hopper as Hopper provides a volume of 6.99 cu m (246.8 cu ft).			
L	565-4371	APRON, STR HYD FOLD, MTS	0		\$6,820
		Hydraulically actuated hopper apron folds straight across the front and contains material after truck dump and while raising hoppers. Provides a minimum center entry height of 527 mm (20.75") and a side entry height of 587 mm (23.1"). Combines with a low side profile to provide a hopper volume of 6.99 cu m (246.8 cu ft). ONLY FOR USE WITH: 424-9114 AP655F MTS ASPHALT PAVER, HRC or 424-9197 AP655F MTS ASPHALT PAVER, LRC			

HOPPER FLASHING

L	424-9173	FLASHING, MANUAL FOLD	110		NC
		Heavy-duty black Tivar flashing to reduce material spillage from front of hopper. ONLY FOR USE WITH: 433-7572 APRON, MANUAL FOLD			
L	567-5057	FLASHING, STR HYD FOLD	0		NC
		Heavy-duty black Tivar flashing to reduce material spillage from front of hopper. ONLY FOR USE WITH: 565-4371 APRON, STR HYD FOLD, MTS or 565-4372 APRON, STR HYD FOLD			
L	576-6555	FLASHING, STR HYD FOLD, RGD	0		NC
		Heavy-duty black Tivar flashing to reduce material spillage from front of hopper plus the added benefit of additional support to increase flashing stiffness. ONLY FOR USE WITH: 565-4371 APRON, STR HYD FOLD, MTS			

TRUCK INTERFACE

L	488-9800	PUSH ROLLER, OSCILLATING	1,165		\$5,010
			1,165		\$5,010 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Oscillating, solid push roller on a fore-aft adjustable pivot for centering truck and to assist steering during unloading. Includes scrapers to prevent material build-up. CANNOT BE USED WITH: 488-5079 HITCH, HYDRAULIC TRUCK			

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FEATURE PACKAGES (CONT.)

TRUCK INTERFACE (Cont.)

L	433-7570	HITCH, HYD PREP, TRACTOR	250	\$1,470 \$1,470 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes hydraulic lines required to accept truck hitch. Recommended if a future field installed truck hitch is likely. ONLY FOR USE WITH: AP655F MTS ASPHALT PAVER and 488-9800 PUSH ROLLER, OSCILLATING or 448-5079 HITCH, HYDRAULIC TRUCK		
L	448-5079	HITCH, HYDRAULIC TRUCK	1,0500	\$17,760 \$17,760 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Truck hitch (clamp arms with rollers) to hold truck to paver when unloading. Actuated from operator's console. Includes scrapers to minimize material accumulation. Also includes truck hitch valve and hydraulic hoses. REQUIRES: HITCH, HYD PREP, TRACTOR		

MAINFRAME EXTENSIONS

L	433-7577	EXTENSION, MAINFRAME, POWER	2750	\$6,610 \$6,610 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Pair of hydraulically powered mainframe extensions to direct material delivery to endgate and facilitate frequent screed width changes. Extends 0.46 m (18") past mainframe. CANNOT BE USED WITH: CONTROL, FEEDER, PADDLE CANNOT BE USED WITH: NON-COMMERCIAL WIDE WIDTH PAVING PACKAGES CANNOT BE USED WITH: EXTENSION 2'6" MAINFRAME		
L	423-7851	MAINFRAME, NO POWER EXTENSION	15	NC
		Cover plates required when no power extensions are selected.		

AUGER EXTENSIONS

P	416-4109	EXTENSION, 6" AUGER, PAIR	55	\$1,035 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER For paving base tractor width to base tractor width plus 1.2 m (4'). Includes a LH and RH 152 mm (6") auger extension. FOR USE WITH: ALL SCREEDS AND ALSO FOR TRACTORS ORDERED WITHOUT A SCREED TO MEET MINIMUM PAVING REQUIREMENT FOR MOST APPLICATIONS.		
P	438-6252	AUGER 18" EXTENSION PER SIDE	195	\$2,495 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Recommended if paving base tractor width plus 1.2 m (4') to base tractor width plus 1.8 m (6'). Includes a pair (left and right) of 152 mm (6") and a pair (left and right) of 305 mm (1') auger extensions. RECOMMENDED FOR USE WITH: REAR MOUNT SCREEDS w/o Wide Width Paving packages.		

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FEATURE PACKAGES (CONT.)

AUGER EXTENSIONS (Cont.)

P	416-4110	KIT, AUGER AND MAINFRAME EXT 270 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Recommended if paving base tractor width plus 1.8 m (6') to base tractor width plus 2.4 m (8') wide. Includes a pair (left and right) of 152 mm (6") auger extensions, two pairs (left and right) of 305 mm (1') auger extensions and a pair of foldable, hinged 610 mm (2') mainframe extensions to facilitate frequent screed width changes. RECOMMENDED FOR USE WITH: ALL SCREEDS w/o Wide Width Paving packages.		\$5,450 NI
---	----------	---	--	-------------------

SCREED INTERFACE PACKAGES

L	433-6621	ADAPTER, VIBE SCREED 1 Provides hydraulics for vibe-only screeds. No provision for tamper systems. CANNOT BE USED WITH: 522-1493 SCREED, SE50 VT		NC
L	433-6615	ADAPTER, TAMP/VIBE SCREED 120 Provides hydraulics for vibe system plus pump, valve and hoses for tamper system. Works with tamper and vibe screeds.		\$2,120

WASH DOWN SYSTEMS

L	424-9195	TANK, WASHDOWN 75 30 L (8 gal) tank with integral pump mounted below deck on RH side. Intended for use with ecological cleaning fluids. Includes pump.		\$2,590
L	424-9152	PUMP, DIESEL 10 FOR USE WITH LANE 3 ONLY Provides diesel fuel supply for pressurized washdown system, taken directly from paver fuel tank.		\$785
L	327-9167	COVER, NO WASHDOWN 0		NC

POWERTRAIN

ENGINE

L	424-9229	ENGINE, TIER 4F EPA/STG IV EU 0 129KW Engine, TIER 4F EPA/STG IV EU, aftertreatment and DEF system.		NC
---	----------	---	--	-----------

ENGINE ATTACHMENTS

Engine attachments is not required for Engine, C7.1 ACERT

L	477-9916	HEATER, ENGINE COOLANT, 120V 0 120 V - For additional cold weather startability. Typical North American plug with two flat prongs and 1 round ground prong. ONLY FOR USE WITH: 424-9229 ENGINE, TIER 4F EPA/STG IV EU		NC
L	477-9917	HEATER, ENGINE COOLANT, 240V 0 240 V - For additional cold weather startability. Typical European plug with two round prongs, a ground hole, and two ground grooves along the outside of the plug. ONLY FOR USE WITH: 424-9229 ENGINE, TIER 4F EPA/STG IV EU		NC

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

UNDERCARRIAGE

MTS UNDERCARRIAGE

Track selection is not required for AP655F ST ASPHALT PAVER

L	293-9075	TRACK, MTS, TREADBAR 0 FOR USE WITH LANE 3 ONLY Mobil-trac rubber belts with lugs. 62 mm (2.4") thick. REQUIRED BY: AP655F MTS ASPHALT PAVER		\$23,060
L	297-9687	TRACK, MTS, SMOOTH 0 Mobil-trac rubber smooth belts. 58 mm (2.3") thick. REQUIRED BY: AP655F MTS ASPHALT PAVER		\$23,520

ELECTRICAL

LIGHTING

P	424-0927	LIGHTS, WORKING 10 Four 24V halogen floodlamps. Two front and two rear facing.		\$780
P	399-3169	LIGHTS, ROADING 15 Includes 2 front headlamps with turn signals, 2 rear floodlamps, 2 rear turn signals with brake lamps.		\$1,255

FEEDER CONTROL SENSORS

P	416-1465	CONTROL, FEEDER, PADDLE 40 Two, proportional, contacting paddle sensors that automatically actuate the feeders to maintain a preset amount of material ahead of the screed. Located at end of augers. CANNOT BE USED WITH: 433-7577 EXTENSION, MAINFRAME, POWER		\$2,435 NI
P	416-1467	SENSOR, FEEDER, SONIC 20 Two, proportional, non-contacting sonic sensors that automatically actuate the feeders to maintain a preset amount of material ahead of the screed. Located at end of augers.		\$4,010 NI
P	435-0910	SENSOR, AUG SONIC, CONV PADDLE 85 Two, proportional, non-contacting auger sonic sensors and two proportional conveyor paddle sensors that automatically actuate the feeders to maintain a preset amount of material ahead of the screed. Located at end of augers.		\$6,450 NI
P	465-1275	SENSOR, AUG SONIC, CONV SONIC 25 Four, proportional, non-contacting auger and conveyor sonic sensors that automatically actuate the feeders to maintain a preset amount of material ahead of the screed.		\$7,880 NI

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT

STEERING CONTROL

Steering control selection is not required for AP655F ST ASPHALT PAVER

L	416-4118	STEERING, SPRING RETURN 5		NC
		Conventional type, spring return controlled steering wheels. ONLY FOR USE WITH: 424-9114 AP655F MTS ASPHALT PAVER, HRC 424-9197 AP655F MTS ASPHALT PAVER, LRC		
L	416-4119	STEERING, FRICTION 10		\$4,655
		Operator adjustable steering wheel brake holds the steering wheel in the desired position to maintain the selected turning radius. ONLY FOR USE WITH: 424-9114 AP655F MTS ASPHALT PAVER, HRC 424-9197 AP655F MTS ASPHALT PAVER, LRC		

DECEL PEDAL

P	416-1453	PEDALS, DECELERATOR 2		\$1,775
		Two decelerator pedals, one for each operator station, that provide dynamic machine speed control without having to decrease the propel speed setting.		
L	416-1454	COVER, NO DECEL PEDAL 5		NC
		No provision for decel pedals.		

SEAT

L	416-1446	SEAT, VINYL SUSPENSION 140		NC
		Seats, vinyl, suspension, flip up armrests. Retractable 51 mm (2") seat belt.		
L	416-1447	SEAT, VINYL, DELUXE 150		\$1,515
		Pneumatic suspension vinyl seats with extendable flip-up armrests. Heated lumbar support and retractable 51 mm (2") seat belt.		

VENTILATION SYSTEM

Required for U.S. market only

L	433-7574	VENTILATION SYSTEM, NO CANOPY 290		\$8,610
		Asphalt fumes extraction with hydraulically driven fan. CANNOT BE USED WITH: 434-0040 HARD TOP CANOPY		
L	433-7575	VENTILATION SYSTEM, CANOPY 290		\$8,610
		FOR USE WITH LANE 3 ONLY Asphalt fumes extraction with hydraulically driven fan.		

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the cost of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

P	462-0803	PRODUCT LINK, CELLULAR PL641 10 Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		NC
P	462-0804	PRODUCT LINK, SATELLITE PL631 10 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		\$446
P	462-2916	PRODUCT LINK, CELLULAR PLE641 12 ONLY FOR USE WITH LANE 3 Product Link Elite series PLE641 (consisting of PL641 radio and PLE601 network manager) uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		\$378
P	462-2917	PRODUCT LINK, SATELLITE PLE631 12 ONLY FOR USE WITH LANE 3 Product Link Elite series PLE631 (consisting of PL631 radio and PLE601 network manager) uses satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		\$824

CONTROL CYLINDERS

L	433-7564	CYLINDER KIT, STANDARD 0 16" Auger segments, tow arm group, standard auger, tow point and screed lift cylinders. CANNOT BE USED WITH: 453-6578 SCREED, SE60 or SCREED, WEILER, SE10F		NC
L	433-7566	CYLINDER KIT, 3M STANDARD 935 16" Auger segments, tow arm group for pulling a 10 m screed with a 2.5 m tractor, standard auger, tow point and screed lift cylinders. Recommended for use with SE60 V Screeds and Weiler SE10 Screed. CANNOT BE USED WITH: 428-4845 SCREED, SE50 or 522-1493 SCREED, SE50 VT or SCREED, WEILER SE8F		NC

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OTHER ATTACHMENTS

COMMISSIONING SUPPORT

NOTE: It is recommended that startup and commissioning of machines be included as part of the machine sale. The net charge covers a three day commissioning event. Trained personnel cover proper machine setup, basic maintenance, operation and application on a customer's jobsite. To request and schedule a machine commissioning event, dealers will need to contact the Caterpillar Paving Technical Training group by filling out the outline request form.

URL: https://www.catpaving.com/registration/class_request_form

OP-2586	COMMISSIONING, NEEDED 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Commissioning Needed, trained personnel are required to properly commission the machine.	\$6,520 NET
OP-2587	COMMISSIONING, NOT NEEDED 0 Commissioning training not needed - Special Case, only to be used by qualified dealers who meet GCI's standard requirements to self-commission machines with customers. For questions, please consult your local GCI Paving Territory Manager.	NC

INSTRUCTIONS

PICTOGRAPH FILMS

L	424-9116 INSTRUCTIONS, NORTH AMERICAN 0 ANSI picto warning decals using symbols plus the word "WARNING" as required for the USA. ONLY FOR USE WITH: 424-9114 AP655F MTS ASPHALT PAVER	NC
---	--	----

PAINT

L	567-0751 PAINT, STANDARD, ANSI/ISO 0 Provides standard Caterpillar Yellow and Black paint scheme. Select this option for when custom paint is not desired. Films are provided in the pictograph film selection above.	NC
L	566-2438 PAINT, CUSTOM, ANSI 0 This option DOES NOT provide a custom paint scheme. This option DOES provide required safety and regulatory ANSI films installed on the machine; PLUS, it provides necessary loose films for application by the dealership after custom paint is applied. ONLY FOR USE WITH: 424-9116 INSTRUCTIONS, NORTH AMERICAN	\$210

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

ELECTRICAL

POWER DISTRIBUTION

Maximum of one power supply per order.

P	416-2013	PANEL, POWER SUPPLY	90	\$6,820
		Electrical distribution panel with a total output of 6.6 kVA continuous with 8 kVA start-up capability, protected by a circuit breaker at the panel, provides power for ex-factory installed lighting and customer work tools. Includes eight 120 V outlets. Mounted on RH side of safety railing behind operator station.		

LIGHTING

P	198-8284	LIGHT, HAZARD	15	\$760 NI
		LED amber beacon light mounted on a 3' mast with coil cord and connector. CANNOT BE USED WITH: 434-0040 HARD TOP CANOPY		
P	363-7444	LIGHT, HAZARD, CANOPY	0	\$349 NI
		FOR USE WITH LANE 3 ONLY Two LED amber beacon lights mounted to the hard top canopy. ONLY FOR USE WITH: 523-4277 WIRING, LIGHTS/HAZARD READY		
P	418-0539	LIGHTS, HID/LED, CANOPY	15	\$1,710
		FOR USE WITH LANE 3 ONLY Six LED lights, two forward facing and four rear facing mounted to the hard top canopy ONLY FOR USE WITH: 523-4277 WIRING, LIGHTS/HAZARD READY		
P	523-4277	WIRING, LIGHTS/HAZARD READY	0	\$364
		FOR USE WITH LANE 3 ONLY Wiring and mounting plates installed in hard top fiberglass canopy to accept LED lights for night paving and amber beacons. REQUIRES: 434-0040 HARD TOP CANOPY		

OPERATOR ENVIRONMENT

OPERATOR PROTECTION

L	434-0040	CANOPY, HARD TOP	703 0	\$5,970 \$5,970 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Hardtop canopy to provide paver operator sun and rain protection. Raises or lowers by folding manually. ONLY FOR USE WITH: 433-7575 VENTILATION SYSTEM, CANOPY or 433-7576 COVER, NO VENTILATION, CANOPY		
P	434-0046	WINDSHIELD, DUAL WINDOW	194 194	\$4,945 \$4,945 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER ONLY FOR USE WITH: 434-0040 HARD TOP CANOPY		
P	187-6649	UMBRELLA, CAT	20	\$185 NI
		One umbrella to provide paver operator sun and rain protection. Measures 54" x 54" and is collapsible. Includes support shaft and mounting hardware.		

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS

GRADE AND SLOPE CONTROLS

P	416-2003	CONTROL, BASE CAT G&S SYSTEM	0 0	\$8,530 \$8,530 NI
		MUST BE ORDERED WITH A TRACTOR OR SCREED. NI IS FOR SCREED ORDERS ONLY Cat Grade and slope controller, power supply, harness, and mounting provisions for grade sensors. User interface integrated in existing screed displays. Only LANE 2 & 3 machine orders with a screed are calibrated from the factory. FOR GRADE/GRADE OPERATION MUST HAVE TWO GRADE SENSORS FOR GRADE/SLOPE OPERATION MUST HAVE ONE GRADE SENSOR AND SLOPE SENSOR.		
P	362-8687	SENSOR, SLOPE	20	\$2,905 NI
		Includes one slope sensor located on transverse beam at front of screed with mounting hardware. Connects to main CAT G&S wiring harness. FOR GRADE/SLOPE OPERATION MUST HAVE ONE SLOPE SENSOR AND ONE GRADE SENSOR ONLY ONE SLOPE SENSOR PER MACHINE ORDER ALLOWED		
P	416-2006	ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM SENSOR, GRADE, SONIC	50	\$4,740 NI
		Contact-free tracing of ground or stringline with self-averaging to minimize effect of short surface irregularities and objects. Includes one sonic tracer consisting of five maintenance-free ceramic sensors with automatic temperature compensation, coily cable, sensor pole, two support arms and mounting hardware. Unit is 28 cm (11 in) long. FOR GRADE/GRADE OPERATION ORDER QTY 2		
P	459-6770	ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM SENSOR, GRADE, SONIC, EXTEND	50	\$4,740 NI
		Contact-free tracing of ground or stringline with self-averaging to minimize effect of short surface irregularities and objects. Includes one sonic tracer consisting of five maintenance-free ceramic sensors with automatic temperature compensation, coily cable, sensor pole, and a telescoping sensor mount. The square tubing telescoping mount has a range of approximately 26" to 46" and mounts on the endgate. The sonic sensing unit is 28 cm (11") long. FOR GRADE/GRADE OPERATION ORDER QTY 2		
P	416-2007	ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM SENSOR, GRADE, MECHANICAL	70	\$3,315 NI
		Mechanically traces the ground or stringline. Includes one proportional contacting mechanical sensor with one wand and one riding shoe attachment, coily cable, sensor pole, two support arms and mounting hardware. FOR GRADE/GRADE OPERATION ORDER QTY 2 ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM		

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

GRADE AND SLOPE CONTROLS (Cont.)

P	513-0333	SENSOR, GRADE, MECH, EXTEND 0 FOR USE WITH LANE 3 ONLY Mechanically traces the ground or stringline. Includes one proportional contacting mechanical sensor with one wand and one riding shoe attachment, coily cable, sensor pole, and a telescoping sensor mount. The square tubing telescoping mount has a range of approximately 26" to 46" and mounts on the endgate. FOR GRADE/GRADE OPERATION ORDER QTY 2 ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM		\$3,315 NI
---	----------	--	--	------------

LEVELING DEVICES

P	417-1907	BEAM, SONIC AVERAGING, CAT G&S 190 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Non-contacting beam utilizing three sonic tracers for enhanced averaging capability. System smooths out any unevenness of the reference surface by calculating an average value over the entire length of the beam. 9.1 m (30') total beam length of four sections with both ends that fold for adjustability and ease of transport. Includes: two sonic tracers (assumes customer already has one, if not, an additional sonic tracer must be selected), wiring harness, two support arms, two tow arm support brackets, and mounting hardware. REQUIRES: ONE SENSOR, GRADE, SONIC TO MAKE A COMPLETE AVERAGING BEAM ON ONE SIDE OF THE MACHINE		\$17,620 NI
---	----------	---	--	-------------

NOTE: IF YOUR CUSTOMER WOULD LIKE TO USE THE AVERAGING BEAM ON BOTH SIDES OF THE MACHINES WITHOUT USING TOOLS, PLEASE ORDER THE FOLLOWING FROM PARTS:

- 443-3733 (Qty 1) and
- 8T-4223 (Qty 3) and
- 8T-4956 (Qty 3)

P	491-0721	ONLY FOR USE WITH: 416-2003 CONTROL, BASE CAT G&S SYSTEM CASE, SONIC SENSOR 0 Case for storing grade sensors. Provides a storage location for up to four sonic sensors and two mechanical sensors. This case is only needed when running two BEAM, SONIC AVERAGING, CAT G&S on one machine. ONLY FOR USE WITH: 417-1907 BEAM, SONIC AVERAGING, CAT G&S		\$255 NI
---	----------	--	--	----------

MATERIAL SENSOR

P	510-5990	SENSOR, HOPPER MATL LEVEL/TEMP 0 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides one non-contacting sonic sensor, mounted above the hopper, to inform the operator of the amount of material in the hopper. In addition, the option informs the operator of the material temperature by way of a single infrared temperature sensor. Material level and temperature information is available on the machine display at the operator station.		\$4,020 \$4,020 NI
---	----------	---	--	-----------------------

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS

OTHER TRACTOR ATTACHMENTS

L	480-0259	PLOW, TRACK	80 80	\$2,405 \$2,405 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Heavy duty ground scraper in front of tracks that can be secured in raised position. Provides smoother operation and longer track life.		
P	438-6149	EXTENSION, 1' AUGER LH	70	\$800 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER One 305 mm (1") auger extension and mounting hardware.		
P	438-6150	EXTENSION, 1' AUGER RH	70	\$800 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER One 305 mm (1") auger extension and mounting hardware.		
P	416-4130	EXTENSION, 2'6" AUGER LH	150	\$1,695 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER One 755 mm (2' 6") auger extension and mounting hardware.		
P	416-4131	EXTENSION, 2'6" AUGER RH	150	\$1,695 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER One 755 mm (2' 6") auger extension and mounting hardware.		
P	416-1189	KIT, 9'10" AUG, MAINFRAME EXT	0	\$14,170 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Recommended for wide width paving with Weiler screeds equipped with 3' of extensions on each side of the screed. Includes two 755 mm (2'6") left hand augers and two 755 mm (2'6") right hand augers, two augers support bearings and mainframe braces, four 788 mm (2'7") mainframe extensions, and two mainframe extension mounts.		
P	215-7553	EXTENSION, 0-2' MAINFRAME,PAIR	70	\$1,305 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Consists of a pair of hinged mainframe extensions foldable from 0 mm (0 ft) to 610 mm (2') to facilitate frequent screed width changes. Bolts to mainframe. Does not raise and lower the augers. Unless the customer has auger extensions the preferred package is the KIT, AUGER AND MAINFRAME EXT Included in: KIT AUGER AND MAINFRAME EXT		
P	438-6255	EXTENSION, 1' MAINFRAME	25	\$420 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER One 305 mm (1') fixed mainframe extension and mounting hardware. FOR DUAL MAINFRAME EXTENSIONS ORDER QTY 2		
P	416-4129	EXTENSION, 2'6" MAINFRAME	80	\$670 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER One 788 mm (2' 7") fixed mainframe extension and mounting hardware. FOR DUAL MAINFRAME EXTENSIONS ORDER QTY 2 CANNOT BE USED WITH: 433-7577 EXTENSION, MAINFRAME, POWER		
P	493-3538	KIT, ANGLED DEFLECTOR	0	\$300 NI
		Single plate angled deflector kit for the front of the auger drive housing and a standard auger segment for the right side auger. This kit changes material flow from feeding from both sides to a left to right material flow.		

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

OTHER TRACTOR ATTACHMENTS (Cont.)

P	273-9969	GUIDE, STEERING 15 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Second, adjustable position steering guide with indicator chain.		\$695 NI
P	435-1067	INDICATOR, TOW POINT 5 Pair of tow point height gauges mounted on top of paver deck.		\$690
P	458-4087	KIT, UPTIME 5 Consists of critical spare parts to ensure maximum machine uptime. Items come packed in a lockable toolbox and each part is clearly identified. Kit includes: O-rings, relays, sensors, position sensors, and fuses.		\$900 NI
P	416-4128	SPRAY WAND 15 FOR USE WITH LANE 3 ONLY Includes 9 m (30') hose, spray wand and quick-connect coupling. ONLY FOR USE WITH: 424-9195 TANK, WASHDOWN or 424-9152 PUMP, DIESEL CANNOT BE USED WITH: 463-6563 HOSE, REEL WITH WAND		\$481 NI
P	463-6563	HOSE, REEL WITH WAND 60 Includes 9 m (30') hose on self-storing reel with spray wand mounted to left-hand handrail at rear of tractor. ONLY FOR USE WITH: 424-9195 TANK, WASHDOWN or 424-9152 PUMP, DIESEL CANNOT BE USED WITH: 416-4128 SPRAY WAND		\$1,940
P	460-2964	PLATE, HOPPER, MAN APRON 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two hopper floor plate inserts to eliminate the drop in the front of the hopper. Raises the truck entry height by 1.5", but minimizes material build up in the hopper. Uses the flashing supplied with the machine. ONLY WORKS WITH MANUAL APRONS		\$1,755 NI
P	480-7961	MIRRORS, EXTENSION, SCREED 0 FOR USE WITH LANE 3 ONLY Includes 2 convex mirrors mounted outboard of the screed lift cylinders to provide the screed operator with a clear view of material in front of the screed extensions.		\$141
P	490-4132	VISORS, DISPLAY, TRACTOR 0 Includes two folding visors that shade the tractor displays from sunlight. The visors fold back to allow the installation of the vandal covers.		\$825
P	505-0166	DEFLECTOR, CONVEYOR 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Conveyor deflector that is positioned more directly under the head shaft. The plate minimizes material carry forward under the tractor in over feed conditions such as wide width or deep paving. Requires the removal of the production deflector.		\$530 NI
P	460-2967	FLASHING, SIDE 0 Rubber flashing for use with rubber flashing options and manual fold tivar. Includes two folded rubber flashing pieces that mount on the sides of hopper above the standard flashing. Reduces material spillage between the sides of hopper and truck box. ONLY FOR USE WITH: 424-9173 FLASHING, MANUAL FOLD or 424-9175 FLASHING, MANUAL FOLD RUBBER		\$775

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

OTHER TRACTOR ATTACHMENTS (Cont.)

P	567-5095	FLASHING, SIDE, SHORT 0		\$995
		Rubber flashing for use with hydraulic folding, standard entry, Tivar flashing options. Includes two folded rubber flashing pieces that mount on the sides of hopper above the standard flashing. Reduces material spillage between the sides of hopper and truck box. ONLY FOR USE WITH: 567-5057 FLASHING, STR HYD FOLD SE or 576-6555 FLASHING, STR HYD FOLD, RGD		

BALLAST PACKAGES

P	435-1041	BALLAST, 2 PLATE BUMPER 335		\$1,000
		Adds 151 kg (333 lbs) of steel plate mounted to the front bumper for improved tractive effort and stability for wide width paving. Limits bumper oscillation in some bumper positions. CANNOT BE USED WITH: 435-1042 BALLAST, 4 PLATE BUMPER or 435-1043 BALLAST, 6 PLATE BUMPER		
P	435-1042	BALLAST, 4 PLATE BUMPER 668		\$2,005
		Adds 303 kg (668 lbs) of steel plate mounted to the front bumper for improved tractive effort and stability for wide width paving. Limits bumper oscillation in some bumper positions. CANNOT BE USED WITH: 435-1041 BALLAST, 2 PLATE BUMPER or 435-1043 BALLAST, 6 PLATE BUMPER		
P	435-1043	BALLAST, 6 PLATE BUMPER 776		\$2,340
		Adds 352 kg (777 lbs) of steel plate mounted to the front bumper for improved tractive effort and stability for wide width paving. Limits bumper oscillation in some bumper positions. CANNOT BE USED WITH: 435-1041 BALLAST, 2 PLATE BUMPER or 435-1042 BALLAST, 4 PLATE BUMPER		
P	435-1044	BALLAST, 4 PLATE, SIDE 300		\$875
		Adds 133 kg (293 lbs) of steel plate mounted to the outside of the front of the machine frame behind the bumper. ONLY FOR USE WITH: AP655F MTS ASPHALT PAVER		

LEVELING DEVICES

P	109-5623	LEVELER, 30' OUTBOARD 2,190		\$8,270 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER 30' long multi-pad aluminum beam (measured from front to rear-most pivot pin) that runs along the outside of the tractor and the screed. Utilizes a combination of beams and shoes that pivot on pins to provide the optimum reference for grade controls. Two sub-beams with two shoes each attach to both the front and rear of the main beam. A string line runs along the top of the beam from front to rear. The whole unit is to be positioned mid-way along the paver and the grade sensor (not provided) mounts on the tow arm and senses the midpoint of the string. The leveler gets pulled by the paver and increases the sensing length. It averages the high and low points in the reference surface to maximize the self-leveling characteristics of the paver. Includes mounting hardware. Best for smoothness and rideability. Good for joint matching. Primarily for highways and paving jobs with long pulls due to difficulty in maneuvering.		

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

LEVELING DEVICES (Cont.)

P	109-5622	LEVELER, 40' OUTBOARD 2,280 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER SAME AS LEVELER, 30' OUTBOARD above except for 40' long multi-pad aluminum beam. Capable of producing an even flatter and more level surface than the 30' leveler but is not as transportable.		\$8,500 NI
P	109-5625	LEVELER, FORE'N AFT 420 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER 12' long multi-pad aluminum beam (measured from front to rear-most pivot pin) that mounts ahead and inboard of the screed. Two sub-beams with two shoes each that pivot on pins attach to the main beam. This leveler gets pulled by the paver. An additional towed shoe attaches to the screed and rides on the mat. A string line gets stretched between the front inboard and aft leveler. A grade sensor (not provided) mounts on the tow arm and senses the string midpoint. During paving the front leveler will average out the high and low points of the reference surface while the aft leveler responds to height changes in the mat behind the screed. Includes mounting hardware. Best for highways and paving jobs with long pulls. Not as effective as an outboard leveler. Used when outboard referencing is not practical due to width restrictions.		\$8,110 NI

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS

SE50 V and SE50 VT SCREED SELECTIONS

P	428-4845	SCREED, SE50 V	7,239 0	\$84,720 \$84,720 NI
---	----------	--------------------------	------------	-------------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
Double extending vibratory screed. Provides paving widths from 2.55 M to 5.00 m (8' 4.3" to 16' 4.8"). Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color displays for controlling screed temperature, vibrate speeds, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Screed plate thickness is 13 mm (0.5"). Hydraulic extensions have hydraulic power for height and electrical power for slope.

Main screed has electric powered crown.
ONLY FOR USE WITH: 433-7564 CYLINDER KIT, STANDARD

P	522-1493	SCREED, SE50 VT	0 0	\$97,450 \$97,450 NI
---	----------	---------------------------	--------	-------------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
Double extending screed with tamper bar and vibrate. Provides paving widths from 2.55 m to 5.00 m (8' 4.3" to 16' 4.8"). Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color displays for controlling screed temperature, tamper and vibrate speed, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Screed plate thickness is 13 mm (0.5"). Main screed has a split plate design with electric powered crown.

ONLY FOR USE WITH: 433-6615 ADAPTER, TAMP/VIBRE SCREED and 433-7564 CYLINDER KIT, STANDARD

CONTROL CYLINDERS

Selection required with SCREED, SE50 V & SCREED, SE50 VT

L	437-0067	CYLINDER KIT, STANDARD	0	NC
---	----------	----------------------------------	---	----

Standard extend and retract cylinders.
REQUIRED BY: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT

PICTO LABELS

Selection required with SCREED, SE50 V & SCREED, SE50 VT

L	449-8858	FILM GP US	0	NC
---	----------	----------------------	---	----

Picto warning decals using symbols plus the word "WARNING" as required for the USA.
Also includes extension width scales reading inches.
REQUIRED BY: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

EXTENSION CONTROLS

Selection required with SCREED, SE50 V & SCREED, SE50 VT

L	450-6610	EXT, POWER FOR MANUAL ENDGATE 0 Provides hydraulic motor power for raising and lowering extension height relative to the main screed. FOR USE WITH ALL MANUAL ENDGATES REQUIRED BY: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT		\$3,330
L	473-3320	EXT, POWER FOR POWER ENDGATE 0 FOR USE WITH LANE 3 ONLY Provides hydraulic motor power for raising and lowering extension height relative to the main screed. FOR USE WITH ALL POWER ENDGATES REQUIRED BY: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT		\$6,660

SCREED ENDGATES

Selection required with SCREED, SE50 V & SCREED, SE50 VT

All standard and powered endgates have an upward travel of 50 mm (2") above grade and 150 mm (6") below grade.

L	538-9613	ENDGATE, ADJUSTABLE CRANK 0 Standard endgate with replaceable wear skis and two adjustable crank jacks. ONLY FOR USE WITH: 450-6610 EXT, POWER FOR MANUAL ENDGATE or 450-6608 EXT, MANUAL FOR MANUAL ENDGATE REQUIRED BY: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT		NC
L	523-4576	ENDGATE, POWER 0 Left and right powered endgate with replaceable wear skis and two hydraulic cylinders to position the height of the endgate. ONLY FOR USE WITH: 473-3319 EXT. MANUAL FOR POWER ENDGATE or 473-3320 EXT. POWER FOR POWER ENDGATE REQUIRED BY: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT		\$8,520

ENDGATE HEATER OPTIONS

L	490-1681	HEATER, ENDGATE 0 ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes heating elements for the wear skis. ONLY FOR USE WITH: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT	0	\$2,170 \$2,170 NI
---	----------	---	---	-----------------------

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

ENDGATE HEATER OPTIONS (Cont.)

L	438-1030	HEATER, ENDGATE, FOLDING	0 0	\$2,420 \$2,420 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two heater elements to heat the endgate shoes on folding end gates. ONLY FOR USE WITH: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT				

FOLDING HEATER OPTION

L	443-3557	SCREED ENDGATES, FOLDING	0 0	\$5,320 \$5,320 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Foldable endgates to allow narrowest transport width. ONLY FOR USE WITH: 438-1030 HEATER, ENDGATE, FOLDING				

SE50 V AND SE50 VT OPTIONAL ATTACHMENTS

P	467-0083	VISORS, DISPLAY	6	\$333
Includes two folding visors that shade the screed display from sunlight. The visors fold back to allow the installation of the vandal covers.				
P	473-3330	CONTROL, PENDANT	7	\$2,400
ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER Two removable pendant controls with coily cords. Allows adjustment of optional powered endgate, screed width, extension height and slope and manual override and pause of the feeders system. ONLY FOR USE WITH: 522-1493 SCREED, SE50 VT				
P	473-3322	CONTROL, PENDANT	7	\$2,400
ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER Two removable pendant controls with coily cord. Allows adjustment of optional powered endgate, screed width, extension height and slope and manual override and pause of the feeders system. ONLY FOR USE WITH: 428-4845 SCREED, SE50 V				
P	480-7055	MOUNT, SWIVEL CONTROLS	0	\$1,295 NI
ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER Includes a left and right mounting bracket to allow the left and right screed operator controls to swivel up and down and also left and right. ONLY FOR USE WITH: 428-4845 SCREED, SE50 V				
P	467-4275	UMBRELLA, SCREED OPERATOR	35	\$333 NI
ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER One CAT umbrella and mount to provide screed operator sun and rain protection. Measures 54" x 54" and is collapsible. Includes support shaft and mounting hardware. For a complete machine, providing protection to both screed operators, order qty 2. ONLY FOR USE WITH: 428-4845 SCREED, SE50 V				

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE50 V AND SE50 VT OPTIONAL ATTACHMENTS (Cont.)

P	472-0510	SHOE, WIDE 72 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER Consist of two wide endgate shoes that can be used to replace the standard endgate shoe. The wide shoes are 88 mm (3.5") wide. These shoes are wider than the endgate structure. This shoe can be used with the endgate heater.		\$885 NI
P	472-0512	SHOE, EDGE 26 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER Consists of two vertical endgate shoes that can be used to replace the standard endgate shoe. The vertical edge shoes also have the mounting tabs welded to the outside of the vertical structure. The vertical shoe is 5 mm thick and has 16 mm of clearance from the bottom wear surface up to the mounting tabs. At the mounting tabs total width is 50 mm. The vertical endgate shoes do not work with endgate heaters.		\$775 NI
P	467-4575	SHOE, SAFETY EDGE 125 ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER Reversible safety edge shoe for use on either side of the screed. Attaches to the rear of the endgate and modifies the edge of the mat as it leaves the screed. Mounts to the same location as the folding endgate, so it cannot be used while the folding endgate is installed.		\$885 NI
P	490-2550	PACKAGE, CUT OFF SHOE 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER One plate for 1' cut off and one plate for 2' cut off reducing paving widths in 6" increments. ONLY FOR USE WITH: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT		\$2,150 NI
P	486-4622	EXTENSION, 9.8" SCREED 180 ALSO AVAILABLE ON A MISCELLANEOUS ORDER One 9.8" (250 mm) screed extension. Electrically heated. No vibration. 1/4 turn quick connect harnesses. ORDER QTY 2 IF EXTENSION NEEDED ON BOTH SIDES OF SCREED FOR USE WITH SE50 V SCREEDS J9700137 AND ABOVE ONLY FOR USE WITH: 428-4845 SCREED, SE50 V		\$4,410 NI
P	486-4620	EXTENSION, 2' 5.5" SCREED 487 ALSO AVAILABLE ON A MISCELLANEOUS ORDER One 2' 5.5" (750 mm) screed extension. Electrically heated. Includes quick connect shaft, mounting hardware, and 1/4 turn harnesses. ORDERS QTY 2 IF EXTENSION NEEDED ON BOTH SIDES OF SCREED. FOR USE WITH SE50 V SCREEDS J9700137 AND ABOVE. ONLY FOR USE WITH: 428-4845 SCREED, SE50 V		\$5,850 NI

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE50 V AND SE50 VT OPTIONAL ATTACHMENTS (Cont.)

P	453-2460	ENDGATE, DEEP LIFT, MANUAL 685 ALSO AVAILABLE ON MISCELLANEOUS ORDER FOR USE WITH LANE 3 ONLY Includes a complete left and right manual endgate with 380 mm (15") travel for deep lift paving. Travel is 75 mm (3") above grade and 12" (305 mm) below grade. Replaces the endgates that ship with the machine. Can be used with folding endgates, but cannot be used with the heated or powered endgate options. ONLY FOR USE WITH: 522-1493 SCREED, SE50 VT		\$7,740 NI
---	----------	--	--	-------------------

SE50 V EXTENSION PACKAGES

P	473-8992	PACKAGE, COMMERCIAL + 1' 7.7" 380 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes mounting hardware and 1/4 turn harnesses. Includes: KIT, AUGER AND MAINFRAME EXT and two mechanical 9.8 " (250 mm) bolt on heated extensions. NOTE: Must remove EXTENSION, MAINFRAME POWER from paver, if equipped, prior to installing this package. FOR SCREED SERIAL NUMBER J9700137 AND ABOVE. ONLY FOR USE WITH: 428-4845 SCREED, SE50 V		\$13,070 NI
P	477-1128	PACKAGE, COMMERCIAL + 4' 11" 1,378 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes a pair (left and right) of 6" (152 mm) auger extensions, two pairs (left and right) of 1' (305 mm) auger extensions and a pair of foldable, hinged 2' (610 mm) mainframe extensions to facilitate frequent screed width changes. Also includes two 4'1" (1.25m) prestrikeoffs and two 2' 5.5" (750 mm) heated-vibratory screed extensions. Includes quick connect drive shaft, mounting hardware and 1/4 turn harnesses. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 6.2 mph (10 kph) FOR SCREED SERIAL NUMBER J9700137 AND ABOVE. ONLY FOR USE WITH: 428-4845 SCREED, SE50 V		\$17,430 NI
P	475-2632	PACKAGE, BASE WIDTH + 4' 11" 2,855 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two 2'6" (755 mm) left hand augers and two 2'6" (755 mm) right hand augers, two auger support bearings and mainframe braces, four 2'7" (788 mm) mainframe extensions, two mainframe extension mounts, two 2' 5.5" (750 mm) heated-vibratory screed extensions, prestrikeoffs and one tube for front mounting support of reference ski. Includes quick connect drive shaft, mounting hardware and 1/4 turn harnesses. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 6.2 mph (10 kph) FOR SCREED SERIAL NUMBER J9700137 AND ABOVE. ONLY FOR USE WITH: 428-4845 SCREED, SE50 V		\$26,160 NI

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE50 VT EXTENSION PACKAGES

P	470-9479	PACKAGE, COMMERCIAL + 1' 7.7". 400 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes: KIT, AUGER AND MAINFRAME EXT and two mechanical 250 mm (9.8") bolt on heated extensions. NOTE: Must remove EXTENSION, MAINFRAME POWER from paver, if equipped, prior to installing this package. ONLY FOR USE WITH: 522-1493 SCREED, SE50 VT		\$11,660 NI
P	477-1130	PACKAGE, COMMERCIAL + 4' 11". 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes: KIT, AUGER AND MAINFRAME EXT, two 1.25 m (4'1") prestrikeoffs, and two 2' 5.5" (750 mm) heated-vibratory screed extensions. NOTE: Must remove EXTENSION, MAINFRAME POWER from paver, if equipped, prior to installing this package. Installation limits travel speed to 6.2 mph (10 kph). ONLY FOR USE WITH: 522-1493 SCREED, SE50 VT		\$26,520 NI
P	475-2633	PACKAGE, BASE WIDTH + 4' 11". 2,754 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two 0.75 m (2'6") left hand augers and two 0.75 m (2'6") right hand augers, two auger support bearings and mainframe braces, four 0.79 m (2'7") mainframe extensions, two mainframe extension mounts, two 0.75 m (2' 5.5") heated-vibratory/tamper screed extensions, two 1.25 m (4'1") prestrikeoffs, and one tube for front mounting support of reference ski. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 6.2 mph (10 kph). FOR AP655F MTS REQUIRES: BALLAST, 4 PLATE SIDE FOR AP655F ST REQUIRES: BALLAST, 2 PLATE BUMPER or BALLAST, 4 PLATE BUMPER or BALLAST, 6 PLATE BUMPER. ONLY FOR USE WITH: 522-1493 SCREED, SE50 VT		\$35,240 NI
P	476-6892	PACKAGE, BASE WIDTH + 8' 2". 3,939 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes three 0.75 m (2'6") left hand augers and three 0.75 m (2'6") right hand augers, two auger support bearings and mainframe braces, six 0.79 m (2'7") mainframe extensions, two mainframe extension mounts, two 1.25 m (4' 1.2") heated-vibratory/tamper screed extensions, prestrikeoffs, and one tube for front mounting support of reference ski. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 6.2 mph (10 kph) FOR AP655F MTS REQUIRES: BALLAST, 4 PLATE SIDE FOR AP655F ST REQUIRES: BALLAST, 2 PLATE BUMPER or BALLAST, 4 PLATE BUMPER or BALLAST, 6 PLATE BUMPER ONLY FOR USE WITH: 522-1493 SCREED, SE50 VT		\$58,740 NI

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE50 VT EXTENSION PACKAGES (Cont.)

P	473-8991	<p>PACKAGE, BASE WIDTH + 9'10" 4,685</p> <p>FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes three 0.75 m (2'6") left hand augers and three 0.75 m (2'6") right hand augers, two auger support bearings and mainframe braces, six 0.79 m (2'7") mainframe extensions, two mainframe extension mounts, four 0.75 m (2' 5.5") heated-vibratory/tamper extensions, prestrikeoffs, and one tube for front mounting support of reference ski. NOTE: Must remove EXTENSION, MAINFRAME, POWER if equipped. Installation limits travel speed to 6.2 mph (10 kph) FOR AP655F MTS REQUIRES: BALLAST, 4 PLATE SIDE FOR AP655F ST REQUIRES: BALLAST, 2 PLATE BUMPER or BALLAST, 4 PLATE BUMPER or BALLAST, 6 PLATE BUMPER ONLY FOR USE WITH: 522-1493 SCREED, SE50 VT</p>	4,685	\$70,490 NI
---	----------	--	-------	--------------------

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE60 V SCREED SELECTIONS

L	453-6578	SCREED, SE60 V	6,819 0	\$97,850 \$97,850 NI
---	----------	--------------------------	------------	-------------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
 Double extending vibratory screed. Provides paving widths from 9' 10" to 19' 6" (3.0 m to 6.0 m). Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color displays for controlling screed temperature, vibrate speeds, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Screed plate thickness is 13 mm (0.5"). Hydraulic extensions have hydraulic power for height and electric power for slope. Main screed has electric powered crown.
 ONLY FOR USE WITH: 433-7566 CYLINDER KIT, 3M STANDARD

CONTROL CYLINDERS

Selection required with Screed, SE60 V

L	461-7477	CYLINDER KIT, STANDARD	181	NC
---	----------	----------------------------------	-----	----

Standard extend and retract cylinders.
 REQUIRED BY: 453-6578 SCREED, SE60 V

PICTO LABELS

Selection required with Screed, SE60 V

L	449-8858	FILM GP US	0	NC
---	----------	----------------------	---	----

Picto warning decals using symbols plus the word "WARNING" as required for the USA.
 Also includes extensions width scales reading inches.
 REQUIRED BY: 453-6578 SCREED, SE60 V

EXTENSION CONTROLS

Selection required with Screed, SE60 V

L	460-8038	EXT, POWER FOR MANUAL ENDGATE	0	NC
---	----------	---	---	----

Provides hydraulic motor power for raising and lowering extension height relative to the main screed.
 FOR USE WITH: ENDGATE MANUAL
 REQUIRED BY: 453-6578 SCREED, SE60 V

L	473-3321	EXT, POWER FOR POWER ENDGATE	0	\$3,330
---	----------	--	---	---------

FOR USE WITH LANE 3 ONLY
 Provides hydraulic motor power for raising and lowering extension height relative to the main screed.
 Also provides hydraulic power for powered endgates.
 FOR USE WITH SE60V SCREEDS JJ300282 AND ABOVE.
 REQUIRED BY: 453-6578 SCREED, SE60 V

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SCREED ENDGATES

Selection required with Screed, SE60 V

All standard and powered endgates have an upward travel of 50 mm (2") above grade and 150 mm (6") below grade.

L	538-9613	ENDGATE, ADJUSTABLE CRANK 0 Standard endgate with replaceable wear skis and two adjustable crank jacks. ONLY FOR USE WITH: 460-8038 EXT, POWER FOR MANUAL ENDGATE REQUIRED BY: 453-6578 SCREED, SE60 V		NC
L	523-4576	ENDGATE, POWER 0 Left and right powered endgate with replaceable wear skis and two hydraulic cylinders to position the height of the endgate. ONLY FOR USE WITH: 473-3321 EXT. POWER FOR MANUAL ENDGATE REQUIRED BY: 453-6578 SCREED, SE60 V		\$8,520

ENDGATE HEATER OPTION

L	490-1681	HEATER, ENDGATE 0 ALSO AVAILABLE ON MISCELLANEOUS ORDER Includes heating elements for the wear skis. ONLY FOR USE WITH: 453-6578 SCREED, SE60 V	0	\$2,170 \$2,170 NI
---	----------	---	---	-----------------------

SE60 V OPTIONAL ATTACHMENTS

P	467-0083	VISORS, DISPLAY 6 Includes two folding visors that shade the screed display from sunlight. The visors fold back to allow the installation of the vandal covers.		\$333
P	473-3322	CONTROL, PENDANT 7 ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER Two removable pendant controls with coily cord. Allows adjustment of optional powered endgate, screed width, extension height and slope and manual override and pause of the feeders system. ONLY FOR USE WITH: 453-6578 SCREED, SE60 V		\$2,400
P	480-7055	MOUNT, SWIVEL CONTROLS 0 ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER Includes a left and right mounting bracket to allow the left and right screed operator controls to swivel up and down and also left and right. ONLY FOR USE WITH: 453-6578 SCREED, SE60 V		\$1,295 NI
P	467-4275	UMBRELLA, SCREED OPERATOR 35 ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER One CAT umbrella and mount to provide screed operator sun and rain protection. Measures 54" x 54" and is collapsible. Includes support shaft and mounting hardware. For a complete machine, providing protection to both screed operators, order qty 2. ONLY FOR USE WITH: 453-6578 SCREED, SE60 V		\$333 NI

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE60 V OPTIONAL ATTACHMENTS (Cont.)

P	472-0510	SHOE, WIDE 72 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER Consist of two wide endgate shoes that can be used to replace the standard endgate shoe. The wide shoes are 3.5" (88 mm) wide. These shoes are wider than the endgate structure. This shoe can be used with the endgate heater.		\$885 NI
P	472-0512	SHOE, EDGE 26 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER Consists of two vertical endgate shoes that can be used to replace the standard endgate shoe. The vertical edge shoes also have the mounting tabs welded to the outside of the vertical structure. The vertical shoe is 5 mm thick and has 16 mm of clearance from the bottom wear surface up to the mounting tabs. At the mounting tabs total width is 50 mm. The vertical endgate shoes do not work with endgate heaters.		\$775 NI
P	467-4575	SHOE, SAFETY EDGE 125 ALSO AVAILABLE FOR USE WITH SCREED MISC ORDER Reversible safety edge shoe for use on either side of the screed. Attaches to the rear of the endgate and modifies the edge of the mat as it leaves the screed. Mounts to the same location as the folding endgate, so it cannot be used while the folding endgate is installed.		\$885 NI
P	490-2550	PACKAGE, CUT OFF SHOE 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER One plate for 1' cut off and one plate for 2' cut off reducing paving widths in 6" increments. ONLY FOR USE WITH: 453-6578 SCREED, SE60 V		\$2,150 NI
P	486-4622	EXTENSION, 9.8" SCREED 180 ALSO AVAILABLE ON A MISCELLANEOUS ORDER One 250 mm (9.8") screed extension. Electrically heated. No vibration. 1/4 turn quick connect harnesses. ORDER QTY 2 IF EXTENSION NEEDED ON BOTH SIDES OF SCREED FOR USE WITH SERIAL NUMBER JJ300282 AND ABOVE. ONLY FOR USE WITH: 453-6578 SCREED, SE60 V		\$4,410 NI
P	486-4620	EXTENSION, 2' 5.5" SCREED 487 ALSO AVAILABLE ON A MISCELLANEOUS ORDER One 750 mm (2' 5.5") screed extension. Electrically heated. Includes quick connect shaft, mounting hardware, and 1/4 turn harnesses. ORDERS QTY 2 IF EXTENSION NEEDED ON BOTH SIDES OF SCREED. FOR USE WITH SERIAL NUMBER JJ300282 AND ABOVE. ONLY FOR USE WITH: 453-6578 SCREED, SE60 V		\$5,850 NI

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

SE60 V EXTENSION PACKAGES

P	477-1137	PACKAGE, BASE WIDTH + 1' 7.7" 380 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two 0.75 m (2'6") left hand augers and two 0.75 m (2'6") right hand augers, two augers support bearings and mainframe braces, four 0.79 m (2'7") mainframe extensions, two mainframe extension mounts, two 259 mm (9.8") heated tamper screed extensions and one tube for front mounting support of reference ski. Screed extensions do not include vibration. Includes mounting hardware and 1/4 turn harnesses. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. FOR SCREED SERIAL NUMBER JJ300282 AND ABOVE. ONLY FOR USE WITH: 453-6578 SCREED, SE60 V		\$13,070 NI
P	475-2632	PACKAGE, BASE WIDTH + 4' 11" 2,855 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two 2'6" (755 mm) left hand augers and two 2'6" (755 mm) right hand augers, two auger support bearings and mainframe braces, four 2'7" (788 mm) mainframe extensions, two mainframe extension mounts, two 2' 5.5" (750 mm) heated-vibratory screed extensions, prestrikeoffs and one tube for front mounting support of reference ski. Includes quick connect drive shaft, mounting hardware and 1/4 turn harnesses. NOTE: Must remove EXTENSION, MAINFRAME POWER if equipped. Installation limits travel speed to 6.2 mph (10 kph) FOR SCREED SERIAL NUMBER JJ300282 AND ABOVE. FOR AP655F MTS REQUIRES: BALLAST, 4 PLATE SIDE FOR AP655F ST REQUIRES: BALLAST, 2 PLATE BUMPER or BALLAST, 4 PLATE BUMPER or BALLAST, 6 PLATE BUMPER ONLY FOR USE WITH: 453-6578 SCREED, SE60 V		\$26,160 NI

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

FRONT MOUNT SCREED SUPPORT

The following Weiler screed selections are the only available configurations from the factory. For all other configurations please contact Weiler directly through their website: www.weilerproducts.com. Parts and warranty for all Weiler products, including the below selections, are administered through Weiler. All other optional attachments such as extensions, should be ordered through Weiler. Screeds ordered from Weiler must be installed at Weiler or the Caterpillar dealership.

L	495-8979	SCREED, WEILER SE8F, BASIC	0 0	\$136,240 \$136,240 NI
		Double extending front mounted extension vibratory screed. Provides paving widths from 8' to 15'6". Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color displays for controlling screed temperature, vibrate speeds, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Hydraulic extensions have hydraulic power for height and slope. Main screed crown is hydraulic. Includes display visors, pendant controls and heated endgates. REQUIRES: 495-9001 THICKNESS SCREWS, CCW or 495-9002 THICKNESS SCREWS, CW and ONLY FOR USE WITH: 433-7564 CYLINDER KIT, STANDARD CANNOT BE USED WITH: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT BASIC or 453-6578 SCREED, SE60 V or 495-8978 SCREED, WEILER SE8F, 12" BERM or 495-8981 SCREED, WEILER SE10F, BASIC or 495-8980 SCREED, WEILER SE10F, 18" BERM		
L	495-8978	SCREED, WEILER SE8F, 12" BERM	0 0	\$143,710 \$143,710 NI
		Double extending front mounted extension vibratory screed. Provides paving widths from 8' to 15'6". Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color display for controlling screed temperature, vibrate speed, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Hydraulic extensions have hydraulic power for height and slope. Main screed crown is hydraulic. Includes display visors, pendant controls and heated endgates. Includes left and right berm attachments in the extensions. REQUIRES: 495-9001 THICKNESS SCREWS, CCW or 495-9002 THICKNESS SCREWS, CW and ONLY FOR USE WITH: 433-7564 CYLINDER KIT, STANDARD CANNOT BE USED WITH: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT BASIC or 453-6578 SCREED, SE60 V or 495-8979 SCREED, WEILER SE8F, BASIC or 495-8981 SCREED, WEILER SE10F, BASIC or 495-8980 SCREED, WEILER SE10F, 18" BERM		

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

FRONT MOUNT SCREED SUPPORT (Cont.)

L	495-8981	SCREED, WEILER SE10F, BASIC	0	\$138,860
			0	\$138,860 NI

Double extending front mounted extension vibratory screed. Provides paving widths from 10' to 19'6". Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color displays for controlling screed temperature, vibe speeds, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Hydraulic extension have hydraulic power for height and slope. Main screed crown is hydraulic. Includes display visors, pendant controls and heated endgates.
 REQUIRES: 495-9001 THICKNESS SCREWS, CCW or 495-9002 THICKNESS SCREWS, CW and
 ONLY FOR USE WITH: 433-7566 CYLINDER KIT, 3M STANDARD
 CANNOT BE USED WITH: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT BASIC or 453-6578 SCREED, SE60 V or 495-8979 SCREED, WEILER SE8F, BASIC or 495-8978 SCREED, WEILER SE8F, 12" BERM or 495-8980 SCREED, WEILER SE10F, 18" BERM

L	495-8980	SCREED, WEILER SE10F, 18" BERM	0	\$147,060
			0	\$147,060 NI

Double extending front mounted extension vibratory screed. Provides paving widths from 10' to 19'6". Includes electric heating elements with automatic regulators on all screed plates. Also includes dual color displays for controlling screed temperature, vibe speeds, counterbalance pressure and optional Cat Grade and Slope control in both metric and SI units. Hydraulic extensions have hydraulic power for height and slope. Main screed crown is hydraulic. Includes display visors, pendant controls and heated endgates. Includes left and right berm attachments in the extensions.
 REQUIRES: 495-9001 THICKNESS SCREWS, CCW or 495-9002 THICKNESS SCREWS, CW and
 ONLY FOR USE WITH: 433-7566 CYLINDER KIT, 3M STANDARD
 CANNOT BE USED WITH: 428-4845 SCREED, SE50 V or 522-1493 SCREED, SE50 VT BASIC or 453-6578 SCREED, SE60 V or 495-8979 SCREED, WEILER SE8F, BASIC or 495-8978 SCREED, WEILER SE8F, 12" BERM or 495-8981 SCREED, WEILER SE10F, BASIC

THICKNESS SCREWS

MUST SELECT ONE WITH WEILER SCREED

P	495-9001	THICKNESS SCREWS, CCW	0	NC
---	----------	---------------------------------	---	----

Two ACME RH threaded screws (8tpi). Counter-clockwise turn increases paving depth.
 ONLY FOR USE WITH: 495-8979 SCREED, WEILER SE8F, BASIC or 495-8978 SCREED, WEILER SE8F, 12" BERM or 495-8981 SCREED, WEILER SE10F, BASIC or 495-8980 SCREED, WEILER SE10F, 18" BERM

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

APPLICATION SPECIFIC COMPONENTS (CONT.)

THICKNESS SCREWS (Cont.)

P	495-9002	THICKNESS SCREWS, CW 0		NC
		Two ACME LH threaded screws (8tpi). Clockwise turn increases paving depth. ONLY FOR USE WITH: 495-8979 SCREED, WEILER SE8F, BASIC or 495-8978 SCREED, WEILER SE8F, 12" BERM or 495-8981 SCREED, WEILER SE10F, BASIC or 495-8980 SCREED, WEILER SE10F, 18" BERM		

FACTORY SOURCED KITS

P	496-9628	LIGHTS, LED, CANOPY 0		\$1,935 NI
		FOR USE WITH LANE 3 ONLY Field installed four forward facing and four rear facing, LED lights, mounted to the hard top canopy. Dealer installation of front, outermost light brackets is required. ONLY FOR USE WITH: 523-4277 WIRING, LIGHTS/HAZARD READY		
P	496-9649	LIGHTS, LED, SCREED 0		\$2,345 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Field installed includes wiring and eight LED lights, four mounted to the rear of the tractor and four mounted to the screed, to illuminate the screed in low light conditions. Dealer installation required.		

CATERPILLAR MACHINE PRICE LIST

AP655F

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

FACTORY SOURCED KITS (CONT.)

PAVER MOUNTED THERMAL PROFILE (PMTP)

This kit is a high accuracy thermal temperature Global Navigational Satellite System (GNSS) mapping system. The factory system maps using Real Time Kinematic (RTK) enabled positioning and is not complete until additional items are purchased and installed by your SITECH dealer. Consult your SITECH representative to order the necessary items, defined below, for RTK enabled mapping of the surface temperature of the asphalt layer behind the paver. The GNSS mapping data is electronically sent to the Trimble Connected Community (TCC) for storage. The files can be manually downloaded from TCC in the .tds format which is able to directly input into the VETA Management and Analysis Software (free download software found at <http://www.intelligentcompaction.com/veta/current-version/> for US DOT's) or other software capable of utilizing the AASHTO standard format.

P	526-9342	MAPPING, THERMAL CAMERA 0		\$42,550 NI
---	----------	--	--	--------------------

AVAILABLE ONLY AS A MISCELLANEOUS ORDER FOR INSTALLATION ON F SERIES PAVERS ONLY
 Components of the Cat supplied kit include: camera mounting mast, thermal camera, MS955 receiver/antenna, mounting provisions for the CB460 display, electronics housing, and wiring for SITECH supplied items. PMTP mapping must be created at RTK accuracy. Failure of the RTK signal causes un-useable positioning data.

MANDATORY ITEMS to be sourced from SITECH include:
 - SNM941 modem for off-boarding of data (requires 3rd party cellular data plan to send data off machine to TCC)
 - RTK position accuracy from either a local base station or Virtual Reference Station(VRS) correction source
 - SNRXXX radio, GNSS upgrade keys, Trimble Connected Community license
 - Thermal mapping only or 3D and thermal mapping software key for the CB460 display

OPTIONAL ITEMS to be sourced from SITECH include:
 - CB460 display (may or not be needed if 3D paving is already customer owned, the CB460 cannot be used simultaneously for 3D and thermal mapping)
 - Adapter plate for mounting as needed for certain machines

REQUIRES 416-2003 CONTROL, BASE CAT G&S SYSTEM if the paver is not already equipped.
 CANNOT BE USED WITH 434-0040 CANOPY, HARD TOP

PACKING

DOMESTIC PACKING

	OP-0210	PACK, DOMESTIC TRUCK 0		NC
--	---------	---	--	-----------

MISCELLANEOUS PACKING

	OP-3651	PACKING, MISC MATERIAL 0		NC
No charge for packing. Applicable freight charges may apply.				