

JOHN DEERE TURF & UTILITY PRODUCTS**UTILITY VEHICLES AND EQUIPMENT****1.7m (66 in.) Straight Blade**
Equipment for Base Machine

66 in. (1.7m) wide straight blade
Replaceable cutting edge
Five-position manual angling
Two adjusting skid shoes
Trip protection

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

8018M		1.7m (66 in.) Straight Blade <i>John Deere and Douglas Dynamics, parent company of WESTERN plows, enter allied distribution agreement.</i> <i>View the WESTERN website for additional information:</i> <i>Dealer account setup information:</i> https://www.westernplows.com/dealership-opportunities <i>Product information:</i> http://dealers.westernplows.com/WesternPlows/pdffiles/Western_Product_Information.pdf <i>Warranty information:</i> http://dealers.westernplows.com/WesternPlows/pdffiles/Western_Warranty_Information.pdf <i>Customer support contact information:</i> http://dealers.westernplows.com/WesternPlows/pdffiles/Western_Customer_Support_Contact_Information.pdf <i>Sales and marketing information:</i> http://dealers.westernplows.com/WesternPlows/pdffiles/Western_Sales_Marketing_Information.pdf <i>For XUV550, XUV550 S4, XUV560, XUV560 S4, XUV590, XUV590 S4, RSX850i, RSX860 Includes front blade, lift arms, and lift components. A winch is needed for blade lift operations, and 2 in. front receiver hitch is needed for mounting the winch (if not already installed). RSX850/860 also requires the Blade Mount Adapter Kit - If the PreRunner bumper is installed, bumper must be removed, and M170669 Fairlead Mounting bracket is required.</i>	1,237.00
-------	--	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------

DESTINATION

001A		US/Canada	In Base Price
------	--	-----------	---------------

LIFT FRAME KITS

3153		Blade Mount Adapter Kit <i>Required on RSX850i/860, NOT required on XUV550, XUV550 S4, XUV560, XUV560 S4, XUV590, XUV590 S4</i>	274.00
3160		Less Blade Mount Adapter Kit <i>For use on XUV550, XUV550 S4, XUV560, XUV560 S4, XUV590, XUV590 S4</i>	In Base Price

ATTACHMENTS FOR FIELD CONVERSION

BM23363		Front Receiver Hitch 50.8-mm (2-in.) Front Receiver Hitch and Recovery Loops	125.19
---------	--	----------------------------------------------------------------------------------------	--------

JOHN DEERE TURF & UTILITY PRODUCTS

UTILITY VEHICLES AND EQUIPMENT

1.7m (66 in.) Straight Blade

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION Continued...	
		Plow Markers	
	BM23029	Plow Markers <i>For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 850D Utility Vehicles. For use on XUV 625i, 825i, 855D Utility Vehicles. (Excludes S4 versions) For use on XUV 550 Utility Vehicles. (Includes S4 versions) For use on TS, TX, TH, Utility Vehicles. (Includes gas and Diesel versions) For use on M-Gator A2 Utility Vehicles. For use on 4x2, 6x4 Utility Vehicles. (Includes Turf/Trail, Diesel versions) For use on CS, CX Utility Vehicles. For use on RSX 850i Utility Vehicles.</i>	43.87

JOHN DEERE TURF & UTILITY PRODUCTS**UTILITY VEHICLES AND EQUIPMENT****1.82m (72 in.) Winch Operated Straight Blade
Equipment for Base Machine**

1.8m (72 in.) wide winch
operated straight blade
Made from thick heavy gauge
steel with heavy-duty ribbing
for rigidity
Low friction black powdercoat
finish
Five-position manual angling

Two adjustable skid shoes
Trip protection
Replaceable steel cutting edge
with optional poly and rubber
wear bars

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

801BM		1.82m (72 in.) Winch Operated Straight Blade <i>For XUV835, XUV865 only. A winch is needed for blade lift operations if not already installed. Roof/OPS mounted auxiliary lights are recommended if used at night or in conditions where good artificial light does not exist. Includes blade, blade frame, push tubes, large roller fairlead for winch, and shift lever mounted winch controls. Requires blade undercarriage (Option Code 3154) if not already installed on the vehicle. Heavy duty front suspension recommended, heavy duty rear suspension also recommended when installing a full cab, sprayer or spreader on all E and M-spec open station vehicles. M-spec cab and R-spec vehicles come from the factory with heavy duty suspension already standard.</i>	1,667.00
-------	--	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------

DESTINATION

001A		US/Canada	In Base Price
------	--	-----------	---------------

LIFT FRAME KITS

3154		Undercarriage mount <i>For use on XUV835, XUV865 only. Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle.</i>	In Base Price
------	--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------

ATTACHMENTS FOR FIELD CONVERSION

	Miscellaneous		
LP49055	3 cu. ft. Salt Spreader <i>E-spec vehicles require E-spec Attachments Harness, Dash Port Harness. M-spec, R-spec vehicles require Dash Port Harness</i>		924.95
LP53512	5 cu. ft. Drop Spreader <i>E-spec vehicles require E-spec Attachments Harness, Dash Port Harness. M-spec, R-spec vehicles require Dash Port Harness</i>		3,399.95
BM26185	Beacon Light <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness. M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness. M-spec cab vehicles require Rear Cab Harness. R-spec vehicles come pre-wired for Beacon Light</i>		257.87
BM26266	E-spec Attachment Harness		273.91

JOHN DEERE TURF & UTILITY PRODUCTS

UTILITY VEHICLES AND EQUIPMENT

1.82m (72 in.) Winch Operated Straight Blade

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		ATTACHMENTS FOR FIELD CONVERSION Continued...	
BM26268		Front Attachment Harness (dash port)	133.76
BM26740		Front Cab Attachment Harness	72.76
BM26215		LED Driving Lights (2 Lights) <i>To mount lights to front of OPS: E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights</i>	359.51
BM26216		LED Work Lights (2 Lights) <i>To mount lights to front of OPS: E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights To mount lights to rear of OPS: E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness M-spec cab vehicles require Rear Cab Harness R-spec vehicles come pre-wired for OPS mounted lights</i>	359.51
BM26401		POLY WEAR BAR - WINCH BLADE	358.46
BM26756		RUBBER WEAR BAR - WINCH BLADE	358.46
BM26739		Rear Cab Attachment Harness	72.76
BM26267		Roof Attachment Harness	88.81
		Plow Markers	
BM26397		Plow Markers	48.16
		Suspension	
BM26395		Heavy Duty Front Shocks <i>Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station</i>	281.41
BM26308		Heavy Duty Rear Shocks <i>Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station</i>	321.00