

**JOHN DEERE TURF & UTILITY PRODUCTS  
UTILITY VEHICLES AND EQUIPMENT**

**1.7m (66 in.) Straight Blade**  
Equipment for Base Machine

66 in. (1.7m) wide straight blade  
Replaceable cutting edge  
Five-position manual angling  
Two adjusting skid shoes  
Trip protection

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

8018M		1.7m (66 in.) Straight Blade <i>For XUV550, XUV550 S4, XUV560, XUV560 S4, XUV590, XUV590 S4, RSX850i, RSX860 Includes front blade, lift arms, and lift components. A winch is needed for blade lift operations, and 2 in. front receiver hitch is needed for mounting the winch (if not already installed). RSX850/860 also requires the Blade Mount Adapter Kit - If the PreRunner bumper is installed, bumper must be removed, and M170669 Fairlead Mounting bracket is required.</i>	1,225.00
-------	--	--	----------

**DESTINATION**

001A		US/Canada	In Base Price
------	--	-----------	---------------

**LIFT FRAME KITS**

3153		Blade Mount Adapter Kit <i>Required on RSX850i/860, NOT required on XUV550, XUV550 S4, XUV560, XUV560 S4, XUV590, XUV590 S4</i>	274.00
3160		Less Implement Lift Frame Kit <i>For use on XUV550, XUV550 S4, XUV560, XUV560 S4, XUV590, XUV590 S4</i>	In Base Price

**ATTACHMENTS FOR FIELD CONVERSION**

BM23363	<b>Drawbar</b>	50.8-mm (2-in.) Front Receiver Hitch and Recovery Loops	121.99
BM23029	<b>Plow Markers</b>	Plow Markers <i>For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 850D Utility Vehicles. For use on XUV 625i, 825i, 855D Utility Vehicles. (Excludes S4 versions) For use on XUV 550 Utility Vehicles. (Includes S4 versions) For use on TS, TX, TH, Utility Vehicles. (Includes gas and Diesel versions) For use on M-Gator A2 Utility Vehicles. For use on 4x2, 6x4 Utility Vehicles. (Includes Turf/Trail, Diesel versions) For use on CS, CX Utility Vehicles. For use on RSX 850i Utility Vehicles.</i>	42.80
BM24723	<b>Winch</b>	WARN ProVantage 1587.573-kg (3500-lb) Winch <i>Requires winch mounting kit and also requires 5.08 cm (2 In.) Front Receiver Hitch with Recovery Loops for mounting. For Model Year 2013 and older Mid Duty and RSX Utility Vehicles. (Includes S4 versions)</i>	628.09

**JOHN DEERE TURF & UTILITY PRODUCTS  
UTILITY VEHICLES AND EQUIPMENT**

**1.7m (66 in.) Straight Blade**  
Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>ATTACHMENTS FOR FIELD CONVERSION Continued...</b>	
BM26741		WARN ProVantage 3500 lb Winch <i>Requires winch mounting kit and also requires 2 In. Front Receiver Hitch with Recovery Loops for mounting. Compatible with Model Year 2014 and newer Mid Duty XUV's.</i>	628.09
BM25079		<b>Winch Mounting Kit</b> Winch Mounting Kit <i>Kit for the non-winch ready RSX units. Requires WARN ProVantage 3500 lb Winch. Kit includes wire harnesses and all necessary hardware to mount winch to bumper.</i>	194.74
BM26249		Winch Mounting Kit (for non winch ready vehicles) <i>Required to mount WARN 3500 lb winch. Kit includes wire harnesses and all necessary hardware to mount winch to bumper. Used for mid-size 550/560/590 non-power steering XUV models. Not used for S4 models.</i>	211.86
BM26246		Winch Mounting Kit (winch ready vehicles) <i>Required to mount WARN 3,500 lb winch. Kit includes wire harnesses and all necessary hardware to mount winch to bumper. For winch ready mid-size XUV and RSX models.</i>	43.87
BM25587		Winch Mounting Kit - S4 (S4 non winch ready vehicles) <i>Required to mount WARN 3,500 lb S4 winch. Kit includes wire harnesses and all necessary hardware to mount winch to bumper. Kit used for mid-size XUV 550/560/590 S4 non-power steering units.</i>	211.86

## JOHN DEERE TURF & UTILITY PRODUCTS UTILITY VEHICLES AND EQUIPMENT

### 1.82m (72 in.) Straight Blade Equipment for Base Machine

72-Inch (182.88 cm) Wide  
Straight Blade  
Three-Position Manual Angling  
Quick Installation  
Frame and Hydraulic Lift  
Two Adjustable Skid Shoes  
Trip Protection  
Replaceable Cutting Edge

The Above Specifications are  
Indicative of the Base Feature  
Machine only and may Differ if  
Alternative Options/Attachments  
are Ordered.

Pricing and Specifications are  
Recommended only and are Subject  
to Change without Notice.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

#### BASE MACHINE

8019M		1.82m (72 in.) Straight Blade <i>This price does NOT include the Mandatory and Recommended Optional Ordering codes. For T-Series Gator Utility Vehicles (unless noted below), HPX, XUV625, XUV825, XUV855 &amp; M-Gators.</i>  Not compatible with - XUV835, XUV865 - XUV825i S4, XUV855D S4. - TE - Model Year 2016 and newer TH Diesel Models	750.00
-------	--	--	--------

#### DESTINATION

001A		US/Canada	In Base Price
------	--	-----------	---------------

#### LIFT FRAME KITS

3150		Implement Lift Frame Kit <i>Lift frame for MY18+ HPX and All 825/855 Models</i>	560.00
3151		Implement Lift Frame Kit <i>Lift frame for T Series unless noted in base code notes and A-1 Models</i>	480.00
3152		Implement Lift Frame Kit <i>Lift frame for 620i, 850D, and MY17 and older HPX Models</i>	560.00
3160		Less Implement Lift Frame Kit	In Base Price

#### POWER / HYDRAULIC LIFT KITS

3171		Hydraulic Implement Lift Kit <i>Hydraulic Implement Lift -620i, 850D, MY17 and older HPX Models Front Blade Adaptor Required (Included in Option Code)</i>	970.00
3172		Hydraulic Implement Lift Kit <i>Hydraulic Implement Lift - T-SERIES (Unless noted in base code)</i>	770.00
3173		Hydraulic Implement Lift Kit <i>Hydraulic Implement Lift - 625, 855, 825, A2, A3 and MY18+ HPX Models</i>	890.00
3180		Less Hydraulic Implement Lift Kit	In Base Price

**JOHN DEERE TURF & UTILITY PRODUCTS  
UTILITY VEHICLES AND EQUIPMENT**

**1.82m (72 in.) Straight Blade**  
Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
		<b>Plow Markers</b>	
BM23029		Plow Markers <i>For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 850D Utility Vehicles. For use on XUV 625i, 825i, 855D Utility Vehicles. (Excludes S4 versions) For use on XUV 550 Utility Vehicles. (Includes S4 versions) For use on TS, TX, TH, Utility Vehicles. (Includes gas and Diesel versions) For use on M-Gator A2 Utility Vehicles. For use on 4x2, 6x4 Utility Vehicles. (Includes Turf/Trail, Diesel versions) For use on CS, CX Utility Vehicles. For use on RSX 850i Utility Vehicles.</i>	42.80
		<b>Suspension</b>	
VGB10544		Heavy-Duty Front Suspension <i>For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 625i, 850D, and 855D Utility Vehicles. Recommended for Crossover Vehicles equipped with Front Blade or Cab.</i>	272.86
		<b>Tire Chains</b>	
TY15650		Rear Tire Chains, 25x11-12 (pair)	102.52
TY25800		Tire Chains (for HPAP 24x10.5-10 or HPAT 24x12-10)	104.15
TY25802		Tire Chains (for HPAT 24x9.5-10)	143.95
TY25814		Tire Chains (for Turf/Hard Surface 24x12.00-10)	96.38
TY24328		Tire chains (pair) for 24x12-12 tires <i>For Turf and Knobby Tires. Not Intended for use on all Four Rear Tires.</i>	105.51
TY25326		Tire chains (pair) for 26x10.5-12 tires	105.51
TY15958		Tire chains (pair) for 26x12-12 tires	115.26

**JOHN DEERE TURF & UTILITY PRODUCTS  
UTILITY VEHICLES AND EQUIPMENT**

**1.82m (72 in.) V-Blade  
Equipment for Base Machine**

72 inch (1.82m) wide adjustable  
V-blade  
Converts from V-position to an  
inverted scoop to a straight  
blade  
Quick installation  
Frame and Hydraulic lift

Two adjustable skid shoes  
Trip protection  
Replaceable cutting edge

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

801AM		1.82m (72 in.) V-Blade <i>This price does NOT include the Mandatory and Recommended Optional Ordering codes. For T-Series Gator Utility Vehicles (unless noted below), HPX, XUV625, XUV825, XUV855 &amp; M-Gators.</i>  <i>Not compatible with</i> - XUV835, XUV865 - XUV825i S4, XUV855D S4. - TE - Model Year 2016 and newer TH Diesel Models	875.00
-------	--	--	--------

**DESTINATION**

001A		US/Canada	In Base Price
------	--	-----------	---------------

**LIFT FRAME KITS**

3150		Implement Lift Frame Kit <i>Lift frame for MY18+ HPX and All 825/855 Models</i>	560.00
3151		Implement Lift Frame Kit <i>Lift frame for T Series unless noted in base code notes and A-1 Models</i>	480.00
3152		Implement Lift Frame Kit <i>Lift frame for 620i, 850D, and MY17 and older HPX Models</i>	560.00
3160		Less Implement Lift Frame Kit	In Base Price

**POWER / HYDRAULIC LIFT KITS**

3171		Hydraulic Implement Lift Kit <i>Hydraulic Implement Lift -620i, 850D, MY17 and older HPX Models Front Blade Adaptor Required (Included in Option Code)</i>	970.00
3172		Hydraulic Implement Lift Kit <i>Hydraulic Implement Lift - T-SERIES (Unless noted in base code)</i>	770.00
3173		Hydraulic Implement Lift Kit <i>Hydraulic Implement Lift - 625, 855, 825, A2, A3 and MY18+ HPX Models</i>	890.00
3180		Less Hydraulic Implement Lift Kit	In Base Price

**ATTACHMENTS FOR FIELD CONVERSION**

JOHN DEERE TURF & UTILITY PRODUCTS  
UTILITY VEHICLES AND EQUIPMENT

1.82m (72 in.) V-Blade  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>ATTACHMENTS FOR FIELD CONVERSION Continued...</b>	
		<b>Plow Markers</b>	
BM23029		Plow Markers <i>For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 850D Utility Vehicles. For use on XUV 625i, 825i, 855D Utility Vehicles. (Excludes S4 versions) For use on XUV 550 Utility Vehicles. (Includes S4 versions) For use on TS, TX, TH, Utility Vehicles. (Includes gas and Diesel versions) For use on M-Gator A2 Utility Vehicles. For use on 4x2, 6x4 Utility Vehicles. (Includes Turf/Trail, Diesel versions) For use on CS, CX Utility Vehicles. For use on RSX 850i Utility Vehicles.</i>	42.80
		<b>Suspension</b>	
VGB10544		Heavy-Duty Front Suspension <i>For use on HPX Gas/Diesel Utility Vehicles. For use on XUV 620i, 625i, 850D, and 855D Utility Vehicles. Recommended for Crossover Vehicles equipped with Front Blade or Cab.</i>	272.86
		<b>Tire Chains</b>	
TY15650		Rear Tire Chains, 25x11-12 (pair)	102.52
TY25800		Tire Chains (for HPAP 24x10.5-10 or HPAT 24x12-10)	104.15
TY25802		Tire Chains (for HPAT 24x9.5-10)	143.95
TY25814		Tire Chains (for Turf/Hard Surface 24x12.00-10)	96.38
TY24328		Tire chains (pair) for 24x12-12 tires <i>For Turf and Knobby Tires. Not Intended for use on all Four Rear Tires.</i>	105.51
TY25326		Tire chains (pair) for 26x10.5-12 tires	105.51
TY15958		Tire chains (pair) for 26x12-12 tires	115.26

**JOHN DEERE TURF & UTILITY PRODUCTS  
UTILITY VEHICLES AND EQUIPMENT**

**1.82m (72 in.) Winch Operated Straight Blade  
Equipment for Base Machine**

1.8m (72 in.) wide winch  
operated straight blade  
Made from thick heavy gauge  
steel with heavy-duty ribbing  
for rigidity  
Low friction black powdercoat  
finish  
Five-position manual angling

Two adjustable skid shoes  
Trip protection  
Replaceable steel cutting edge  
with optional poly and rubber  
wear bars

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

801BM		1.82m (72 in.) Winch Operated Straight Blade <i>Heavy duty front suspension recommended, heavy duty rear suspension also recommended when installing a full cab, sprayer or spreader on all E and M-spec open station vehicles. M-spec cab and R-spec vehicles come from the factory with heavy duty suspension already standard. For XUV835, XUV865 only. A winch is needed for blade lift operations if not already installed. Roof/OPS mounted auxiliary lights are recommended if used at night or in conditions where good artificial light does not exist. Includes blade, blade frame, push tubes, large roller fairlead for winch, and shift lever mounted winch controls. Requires blade undercarriage (Option Code 3154) if not already installed on the vehicle</i>	1,650.00
-------	--	---	----------

**DESTINATION**

001A		US/Canada	In Base Price
------	--	-----------	---------------

**LIFT FRAME KITS**

3154		Undercarriage mount <i>For use on XUV835, XUV865 only Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle.</i>	In Base Price
------	--	--	---------------

**ATTACHMENTS FOR FIELD CONVERSION**

**Harnesses**

BM26266		E-spec Attachment Harness	266.43
BM26268		Front Attachment Harness (dash port)	129.47
BM26740		Front Cab Attachment Harness	70.61
BM26739		Rear Cab Attachment Harness	70.61
BM26267		Roof Attachment Harness	86.67

**JOHN DEERE TURF & UTILITY PRODUCTS  
UTILITY VEHICLES AND EQUIPMENT**

**1.82m (72 in.) Winch Operated Straight Blade**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION Continued...</b>			
		<b>Lighting</b>	
BM26185		Beacon Light <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec cab vehicles require Rear Cab Harness</i> <i>R-spec vehicles come pre-wired for Beacon Light</i>	257.87
BM26215		LED Driving Lights (2 Lights) <i>To mount lights to front of OPS:</i> <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness</i> <i>M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights</i>	359.51
BM26216		LED Work Lights (2 Lights) <i>To mount lights to rear of OPS:</i> <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec cab vehicles require Rear Cab Harness</i> <i>R-spec vehicles come pre-wired for OPS mounted lights</i> <i>To mount lights to front of OPS:</i> <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness</i> <i>M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights</i>	359.51
		<b>Miscellaneous</b>	
BM26401		POLY WEAR BAR - WINCH BLADE	347.76
BM26756		RUBBER WEAR BAR - WINCH BLADE	347.76
		<b>Plow Markers</b>	
BM26397		Plow Markers	47.09
		<b>Spreaders</b>	
LP49055		3 cu. ft. Salt Spreader <i>E-spec vehicles require E-spec Attachments Harness, Dash Port Harness</i> <i>M-spec, R-spec vehicles require Dash Port Harness</i>	885.00
LP53512		5 cu. ft. Drop Spreader <i>E-spec vehicles require E-spec Attachments Harness, Dash Port Harness</i> <i>M-spec, R-spec vehicles require Dash Port Harness</i>	3,342.00
		<b>Suspension</b>	
BM26395		Heavy Duty Front Shocks <i>Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station</i>	272.86
BM26308		Heavy Duty Rear Shocks <i>Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station</i>	311.37
		<b>Winch</b>	
BM26251		WARN ProVantage 2041 kg (4500 lb) Winch <i>Requires Winch Mounting Kit.</i>	742.59
		<b>Winch Mounting Kit</b>	
BM26252		4500LB Winch Mounting Kit <i>For XUV835, XUV865 only. E-spec vehicles require E-spec Attachments Harness.</i> <i>Required to mount winch to front of chassis.</i>	194.74



JOHN DEERE TURF & UTILITY PRODUCTS  
UTILITY VEHICLES AND EQUIPMENT

---

**1.82m (72 in.) Winch Operated Straight Blade**  
Continued

**JOHN DEERE TURF & UTILITY PRODUCTS  
UTILITY VEHICLES AND EQUIPMENT**

**1.82m (72 in.) Hydraulic Straight Blade  
Equipment for Base Machine**

<p>1.82 m (72 in.) wide hydraulic blade Plow width: 1.6 m (64 in.) full angle Plow height: 0.6 m (23.5 in.) Powder-coated steel flared moldboard with four vertical reinforcement ribs Quick installation/removal with quick hitch pins</p>	<p>Plugs directly into vehicle winch harness (standard on M and R spec vehicles, E spec vehicles require E-spec Attachment Harness) Two adjustable skid shoes Full-trip moldboard with two coil springs Replaceable high carbon steel wear edge</p>	<p>Standard plow markers</p>
---	---	------------------------------

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

801EM		<p>1.82m (72 in.) Hydraulic Straight Blade <i>For XUV835, XUV865 only. Roof/OPS mounted auxiliary lights are recommended if used at night or in conditions where good artificial light does not exist. Heavy duty front suspension recommended, heavy duty rear suspension also recommended when installing a full cab, sprayer, or spreader on all E and M-spec open station vehicles. M-spec cab and R-spec vehicles come from the factory with heavy duty suspension already standard. Not for use with Terrahawk tires. Includes blade, and hydraulic unit. Requires undercarriage mount and joystick controller (Option Code 3154) if not already installed on the vehicle. E-spec vehicles require E-spec Attachment Harness and Dash Port Attachment Harness. M-spec and R-spec vehicles require Dash Port Attachment Harness.</i></p>	3,900.00
-------	--	---	----------

**DESTINATION**

001A		<p>US/Canada <i>Requires option code 0409 English operator's manual</i></p>	In Base Price
------	--	---	---------------

**OPERATOR'S MANUAL**

0409		<p>English operator's manual</p>	In Base Price
------	--	----------------------------------	---------------

**LIFT FRAME KITS**

3154		<p>Undercarriage mount <i>Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle. For use on XUV835, XUV865 only. Includes joystick controller</i></p>	In Base Price
------	--	--	---------------

**ATTACHMENTS FOR FIELD CONVERSION**

<b>Harnesses</b>			
BM26266		E-spec Attachment Harness	266.43
BM26268		Front Attachment Harness (dash port)	129.47
BM26740		Front Cab Attachment Harness	70.61

**JOHN DEERE TURF & UTILITY PRODUCTS  
UTILITY VEHICLES AND EQUIPMENT**

**1.82m (72 in.) Hydraulic Straight Blade**  
Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>ATTACHMENTS FOR FIELD CONVERSION Continued...</b>	
BM26739		Rear Cab Attachment Harness	70.61
BM26267		Roof Attachment Harness	86.67
		<b>Lighting</b>	
BM26185		Beacon Light <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec cab vehicles require Rear Cab Harness</i> <i>R-spec vehicles come pre-wired for Beacon Light</i>	257.87
BM26215		LED Driving Lights (2 Lights) <i>To mount lights to front of OPS:</i> <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness</i> <i>M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights</i>	359.51
BM26216		LED Work Lights (2 Lights) <i>To mount lights to rear of OPS:</i> <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec cab vehicles require Rear Cab Harness</i> <i>R-spec vehicles come pre-wired for OPS mounted lights</i> <i>To mount lights to front of OPS:</i> <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness</i> <i>M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights</i>	359.51
		<b>Miscellaneous</b>	
BUC10473		Deflector Kit (Straight Blade) <i>For use on 801CM and 801EM hydraulic straight blade only</i>	333.84
BUC10476		Poly wear bar (Straight Blade) <i>For use on 801CM and 801EM hydraulic straight blade only</i>	491.13
BUC10477		Rubber wear bar (Straight Blade) <i>For use on 801CM and 801EM hydraulic straight blade only</i>	746.86
		<b>Spreaders</b>	
LP49055		3 cu. ft. Salt Spreader <i>E-spec vehicles require E-spec Attachments Harness, Dash Port Harness</i> <i>M-spec, R-spec vehicles require Dash Port Harness</i>	885.00
LP53512		5 cu. ft. Drop Spreader <i>E-spec vehicles require E-spec Attachments Harness, Dash Port Harness</i> <i>M-spec, R-spec vehicles require Dash Port Harness</i>	3,342.00
		<b>Suspension</b>	
BM26395		Heavy Duty Front Shocks <i>Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station</i>	272.86
BM26308		Heavy Duty Rear Shocks <i>Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station</i>	311.37

## JOHN DEERE TURF & UTILITY PRODUCTS UTILITY VEHICLES AND EQUIPMENT

### 1.82m (72 in.) Hydraulic V-Blade Equipment for Base Machine

1.82 m (72 in.) wide hydraulic operated V-blade Plow width: 1.7 m (66 in.) full angle, 1.5 m (61 in.) scoop, 1.7 m (66 in.) full V Powder-coated steel flared moldboard with six vertical reinforcement ribs 65 cm (25.75 in.) center height to 74 cm (29.25 in.) at the outer edge Quick installation/removal with	quick hitch pins Plugs directly into vehicle winch harness (standard on M and R spec vehicles, E spec vehicles require E-spec Attachment Harness) Two adjustable skid shoes Independent trip-edge protection Replaceable high carbon steel wear edge Standard plow markers Quick, double acting hydraulic	cylinders for back dragging performance
---	---	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

#### BASE MACHINE

801DM	1.82m (72 in.) Hydraulic V-Blade <i>Heavy duty front suspension recommended, heavy duty rear suspension also recommended when installing a full cab, sprayer, or spreader on all E and M-spec open station vehicles. M-spec cab and R-spec vehicles come from the factory with heavy duty suspension already standard.</i> <i>Not for use with Terrahawk tires</i> <i>For XUV835, XUV865 only. Roof/OPS mounted auxiliary lights are recommended if used at night or in conditions where good artificial light does not exist.</i> <i>Includes V-blade, and hydraulic unit. Requires undercarriage mount and joystick controller (Option Code 3154) if not already installed on the vehicle</i> <i>E-spec vehicles require E-spec Attachment Harness and Dash Port Attachment Harness</i> <i>M-spec and R-spec vehicles require Dash Port Attachment Harness</i>	4,600.00
-------	--	----------

#### DESTINATION

001A	US/Canada	In Base Price
------	-----------	---------------

#### LIFT FRAME KITS

3154	Undercarriage mount <i>Includes joystick controller</i> <i>Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle.</i> <i>For use on XUV835, XUV865 only</i>	In Base Price
------	---	---------------

#### ATTACHMENTS FOR FIELD CONVERSION

##### Harnesses

BM26266	E-spec Attachment Harness	266.43
BM26268	Front Attachment Harness (dash port)	129.47
BM26740	Front Cab Attachment Harness	70.61
BM26739	Rear Cab Attachment Harness	70.61
BM26267	Roof Attachment Harness	86.67

**JOHN DEERE TURF & UTILITY PRODUCTS  
UTILITY VEHICLES AND EQUIPMENT**

**1.82m (72 in.) Hydraulic V-Blade**  
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION Continued...</b>			
		<b>Lighting</b>	
BM26185		Beacon Light <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec cab vehicles require Rear Cab Harness</i> <i>R-spec vehicles come pre-wired for Beacon Light</i>	257.87
BM26215		LED Driving Lights (2 Lights) <i>To mount lights to front of OPS:</i> <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness</i> <i>M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights</i>	359.51
BM26216		LED Work Lights (2 Lights) <i>To mount lights to rear of OPS:</i> <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec cab vehicles require Rear Cab Harness</i> <i>R-spec vehicles come pre-wired for OPS mounted lights</i> <i>To mount lights to front of OPS:</i> <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness</i> <i>M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights</i>	359.51
		<b>Miscellaneous</b>	
BUC10478		Deflector Kit (V Blade) <i>For use on 801DM hydraulic V blade only</i>	372.36
BUC10483		Poly wear bar (V Blade) <i>For use on 801DM hydraulic V blade only</i>	528.59
		<b>Spreaders</b>	
LP49055		3 cu. ft. Salt Spreader <i>E-spec vehicles require E-spec Attachments Harness, Dash Port Harness</i> <i>M-spec, R-spec vehicles require Dash Port Harness</i>	885.00
LP53512		5 cu. ft. Drop Spreader <i>E-spec vehicles require E-spec Attachments Harness, Dash Port Harness</i> <i>M-spec, R-spec vehicles require Dash Port Harness</i>	3,342.00
		<b>Suspension</b>	
BM26395		Heavy Duty Front Shocks <i>Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station</i>	272.86
BM26308		Heavy Duty Rear Shocks <i>Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station</i>	311.37