

## CATERPILLAR MACHINE PRICE LIST

**CB15**CB15 VIBRATORY ASPHALT COMPACTOR  
MINNEAPOLIS, MN, USA (SAP)Ship Weight  
lbsLIST PRICE  
AT DEALER

Standard Equipment:

**POWERTRAIN**

CAT C4.4, inline four-cylinder turbo-charged diesel engine (106 kW / 142 HP)  
Cyclonic air cleaner  
Water separator  
Ultra clean fuel filter with integrated electric priming pump  
ECO mode throttle system  
Dual braking systems (service & parking)  
Two-speed hydrostatic transmission

**ELECTRICAL**

12-volt electric starting  
120 ampere alternator  
Maintenance free battery - 1000 CCA  
Halogen working lights - bumper mounted (2 front-facing and 2 rear-facing)  
Backup alarm and forward warning horn  
Cat engine and vehicle ECM's - ET compatible  
Product link ready

**OPERATOR ENVIRONMENT**

Isolated ROPS/FOPS structure  
Platform handrails / guardrails  
Four heavy-duty isolation mounts  
Power steering  
Adjustable, suspension, seat  
50 mm (2") wide retractable seat belt  
Adjustable, steering console and control/display console  
Indicator light package with audible warning alarm for:  
-hydraulic oil pressure  
-hydraulic oil temperature  
-engine oil pressure  
-engine coolant temperature  
-glow plugs  
-service fault indicator  
Fuel level gauge  
Water level gauge  
Service hour meter  
Lockable, vandalism guard for instrument panel  
Sliding, rotating seat  
Automatic speed control  
Auto-vibe with adjustable on/off control  
Vibe tachometer  
Speedometer

**DRUMS**

Smooth solid drum  
2130 mm (84") wide x 1300 mm (51") diameter  
Five amplitudes with one vibe frequencies  
Front and rear self adjusting scraper blades  
Pod-style eccentric weight housing

**FLUIDS**

Premixed 50% concentration of extended life coolant with freeze protection to -37C (-35F)

**OTHER STANDARD EQUIPMENT**

Locking engine enclosure  
Sealed for life hitch bearings  
Sight gauges:  
-hydraulic tank level  
-air restriction indicator  
Cap lock for hydraulic tank  
Articulated frame with safety lock  
Transport tie-down and lift points  
208 L (55 gal) fuel tank capacity  
835 L (220 gal) water tank capacity  
Quick connect hydraulic pressure test ports  
SOS ports:  
-engine oil  
Dual water spray bars  
Dual water pumps

CATERPILLAR MACHINE PRICE LIST

**CB15**

CB15 VIBRATORY ASPHALT COMPACTOR MINNEAPOLIS, MN, USA (SAP)	Ship Weight lbs	LIST PRICE AT DEALER
--	--------------------	-------------------------

**Lane 2 is reserved for the Base Order Management Program.  
 Please use Lane 2 when placing orders that are part of the  
 Base Order Management program.**

<b>559-5256</b>	<b>CB15 01A VIB COMP DCA1</b> . . . . . 0 LANE 1 - AVAILABLE FROM MINNEAPOLIS PDC	<b>\$255,280</b>
-----------------	--	------------------

- INCLUDES:  
 522-4607 CB15 01A VIBRATORY COMPACTOR  
 434-0760 ENGINE, TIER 4F, STAGE 4  
 355-1670 BELT, ENG  
 417-5262 HITCH, STANDARD  
 539-2603 DRUM, SOLID  
 424-1371 SYSTEM, VERSA-VIBE  
 501-6572 LIGHTS, WORKING  
 532-8806 PLATFORM, ROPS/FOPS  
 356-0924 ROTATION, FULL  
 454-3055 CONTROL, PREMIUM  
 489-6273 STEERING WHEEL, FIXED  
 527-8200 LANGUAGES, OPTION 1  
 355-3084 SEAT, HEATED VINYL  
 460-8862 PRODUCT LINK, CELLULAR PL641  
 445-8758 NOZZLES, PREMIUM  
 433-0408 OIL, HYD, FACTORY FILLED  
 434-5133 LIGHT, ROTATING BEACON  
 530-3115 LIGHTS, LED, ROPS  
 419-5625 SENSORS, MAT TEMPERATURE  
 362-2758 MIRRORS, EXTERNAL  
 433-7143 FREEZE PROTECTION, ROPS/FOPS

NOTE: Please refer to the Lane 1 section to complete your order.

<b>522-4607</b>	<b>CB15 01A VIBRATORY COMPACTOR</b> . . . . . 0 LANE 2 - AVAILABLE FROM MINNEAPOLIS FACTORY LANE 3 - AVAILABLE FROM MINNEAPOLIS FACTORY	<b>\$236,910</b>
-----------------	---	------------------

<b>0P-4694</b>	<b>CB15 MISC MATERIAL</b> . . . . . 0 AVAILABLE FROM MINNEAPOLIS FACTORY Only reference numbers that have the text "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.	<b>NC</b>
----------------	--	-----------

CATERPILLAR MACHINE PRICE LIST

**CB15**

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	--------	-----------------	----------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS**

**LANE SELECTION**

YOU MUST SELECT THIS REFERENCE WHEN ORDERING FROM PDC

0P-9001	LANE 1 ORDER . . . . .	0	NC
---------	------------------------	---	----

**INSTRUCTIONS - PICTOGRAPH FILMS**

L	522-4617	INSTRUCTIONS, NORTH AMERICAN . . . . .	0	NC
L	522-4618	INSTRUCTIONS, INTERNATIONAL . . . . .	0	NC

**PACKING**

0P-0210	PACK, DOMESTIC TRUCK . . . . .	0	NC
---------	--------------------------------	---	----

**LANE 1 AM-NORTH OPTIONAL ATTACHMENTS**

**CERTIFICATES**

	0P-1870	CERTIFICATE OF ORIGIN . . . . .	0	NC
P	524-1948	COMPLIANCE FILM,ELECT-MAGNETIC . . . . . Film indicates EMC compliance. Required for Canada	0	NC

CATERPILLAR MACHINE PRICE LIST

**CB15**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**LANE SELECTION**

OP-9002	LANE 2 ORDER . . . . .	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER . . . . .	0	NC

**POWERTRAIN**

**ENGINE**

L	434-0760	ENGINE, TIER 4F, STAGE 4 . . . . .	1,407	NC
---	----------	------------------------------------	-------	----

**BELT**

L	355-1670	BELT, ENG . . . . .	2	NC
		Serpentine belt for standard machine.		
L	355-1671	BELT, ENG, A/C . . . . .	2	NC
		Serpentine belt for machines equipped with air conditioning. REQUIRES: 435-4830 AIR CONDITIONER		

**HITCH**

L	417-5262	HITCH, STANDARD . . . . .	937	NC
		Standard hitch without offset		
L	417-5263	HITCH, OFFSET . . . . .	1,047	\$3,740
		Switch control on propel lever gives +/- 152 mm (6") of drum offset. REQUIRES: 454-3055 CONTROL, PREMIUM		

**DRUM TYPE**

L	539-2603	DRUM, SOLID . . . . .	0	NC
		2130 mm (84") solid drums.		
L	493-7508	DRUM, SOLID W/OSCILLATION STD . . . . .	0	NC
		2130 mm (84") solid drums, front drum with conventional vibration and rear drum with oscillatory vibration. Both drum shells are comprised of standard material.		
L	524-8657	DRUM, SOLID W/OSCILLATION HD . . . . .	0	\$12,940
		2130 mm (84") solid drums, front drum with conventional vibration consists of standard material whereas the rear drum, with oscillatory vibration, is comprised of a hardened material for better wear potential.		

**HYDRAULICS**

**VIBRATORY HYDRAULICS**

L	424-1380	SYSTEM, 5 AMPLITUDE . . . . .	1,109	NC
		Frequency of 42 Hz (2520 vpm). Drum mounted handwheel with 5 manual settings for vibratory amplitude control. Includes auto reversing weights. ONLY FOR USE WITH: 539-2603 DRUM, SOLID		

CATERPILLAR MACHINE PRICE LIST

**CB15**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**HYDRAULICS (CONT.)**

**VIBRATORY HYDRAULICS (Cont.)**

L	424-1371	<b>SYSTEM, VERSA-VIBE</b> . . . . . 1,074 Frequency of 42 Hz (2520 vpm) and 63.3 Hz (3800 vpm). Console switch control for amplitude / frequency setting. Handwheel at drum to control amplitude. ONLY FOR USE WITH: 539-2603 DRUM, SOLID		\$6,500
L	524-8662	<b>SYSTEM, 5 AMPLITUDE W/OSC</b> . . . . . 0 Frequency of 42 Hz (2520 vpm) conventional vibration on the front drum with oscillatory vibration at 40 Hz (2400 vpm) in the rear drum. Handwheel with 5 manual settings for amplitude control on front drum only. Includes auto reversing weights. 5 amplitude front drum with oscillatory rear drum. ONLY FOR USE WITH: 524-8657 DRUM, SOLID W/OSCILLATION HD 493-7508 DRUM, SOLID W/OSCILLATION STD		\$4,065
L	524-7896	<b>SYSTEM, VERSA-VIBE W/OSC</b> . . . . . 0 Frequency of 42 Hz (2520 vpm) and 63.3 Hz (3800 vpm) conventional vibration on the front drum with oscillatory vibration at 40 Hz (2400 vpm) on the rear drum. Console switch control for amplitude / frequency setting and handwheel with manual high and low settings for amplitude control on front drum only. Versa-Vibe front drum with oscillatory rear drum. ONLY FOR USE WITH: 524-8657 DRUM, SOLID W/OSCILLATION HD 493-7508 DRUM, SOLID W/OSCILLATION STD		\$10,710

**ELECTRICAL**

**LIGHTING**

L	501-6572	<b>LIGHTS, WORKING</b> . . . . . 0 Includes 2 front and 2 rear facing clear lights located in the bumpers.		NC
L	501-6573	<b>LIGHTS, ROADING AND WORKING</b> . . . . . 0 Includes 2 front high beams headlights, 2 rear facing flood lights, front and rear turn signals, and front and rear indicator/parking lights. All lights are attached to the bumpers.		\$865

**OPERATOR ENVIRONMENT**

**OPERATOR STATION**

L	532-8806	<b>PLATFORM, ROPS/FOPS</b> . . . . . 0 Includes grab handrails and foundation for the sliding and rotating operator station. Lockable personal storage container and compartments for personal item retention and 12 volt power point.		NC
L	532-8807	<b>CAB, ROPS/FOPS</b> . . . . . 0 Cab operator's environment with heater & defroster, and wet-arm wiper/washers (front and rear). Cab is radio ready, including hardware, wiring and 12-volt power point.		\$13,010

**OPERATOR STATION ACCESS**

L	601-8948	<b>PLATFORM ACCESS, LH SIDE, ROPS</b> . . . . . 0 Provides standard access to the left hand side of the machine. ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS		NC
---	----------	--	--	----

CATERPILLAR MACHINE PRICE LIST

**CB15**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**OPERATOR ENVIRONMENT (CONT.)**

**OPERATOR STATION ACCESS (Cont.)**

L	601-8949	PLATFORM ACCESS, DUAL, ROPS . . . . . 0 Provides dual access to the left & right hand sides of the machine. ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS		\$1,995
---	----------	---	--	---------

**OPERATOR STATION MOVEMENT**

L	343-6115	ROTATION, HALF . . . . . 40 Includes operator station controls, LCD display and station slide and 180 deg rotate levers.		NC
L	356-0924	ROTATION, FULL . . . . . 75 Includes operator station controls, LCD display and station slide and 359 deg rotate levers.		\$2,100

**PROPEL LEVER**

L	454-3054	CONTROL, STD . . . . . 2 Includes vehicle wiring and basic 2 button propel lever for propel control, vibratory on/off selection, and water spray functions.		NC
L	454-3055	CONTROL, PREMIUM . . . . . 2 Includes premier wiring and premium 6 button propel lever needed for most options. In addition to the standard control function, the additional 4 buttons will control the offset hitch and edge cutter functionality (only if the machine is equipped with these options).		\$615

**STEERING WHEEL**

L	489-6273	STEERING WHEEL, FIXED . . . . . 0 LH located steering wheel with a fixed location.		NC
L	489-6274	STEERING WHEEL, PIVOTING . . . . . 0 LH located steering wheel with the ability to rotate 45 degrees inward toward the operator. The inward rotation allows enough movement that operators can comfortably steer with precision while performing delicate steering maneuvers. CANNOT BE USED WITH: 434-5079 MAPPING, GNSS 434-7889 MAPPING, GNSS, CAB		\$695

**OPERATOR LANGUAGES**

L	527-8200	LANGUAGES, OPTION 1 . . . . . 0 Includes standard languages (English, Spanish, French, German, Italian, Polish, Portuguese, Turkish, and Korean) for machine operation and control.		NC
---	----------	--	--	----

**SEAT SELECTION**

L	343-6129	SEAT, STD VINYL . . . . . 157 Vinyl suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back.		NC
L	355-3084	SEAT, HEATED VINYL . . . . . 163 Heated vinyl suspension seat with fold-up arms rests, retractable seat belt, weight adj., and tilt back.		\$324

CATERPILLAR MACHINE PRICE LIST

**CB15**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**OPERATOR ENVIRONMENT (CONT.)**

**SEAT SELECTION (Cont.)**

L	344-0124	<b>SEAT, STD CLOTH</b> . . . . . 157 Cloth suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back. Not recommended for use with PLATFORM, ROPS/FOPS due to potential issues from moisture in open platform environment. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		<b>\$215</b>
L	355-3085	<b>SEAT, HEATED CLOTH</b> . . . . . 163 Heated cloth suspension seat with fold-up arm rests, retractable seat belt, weight adj., and tilt back. Not recommended for use with PLATFORM, ROPS/FOPS due to potential issues from moisture in open platform environment. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		<b>\$377</b>

**TECHNOLOGY PRODUCTS**

**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	460-8861	<b>PRODUCT LINK, SATELLITE PL631</b> . . . . . 9 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage. ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS		<b>\$446</b>
L	461-1464	<b>PRODUCT LINK, SATELLITE PL631</b> . . . . . 9 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		<b>\$446</b>
L	460-8862	<b>PRODUCT LINK, CELLULAR PL641</b> . . . . . 9 Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data. ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS		<b>NC</b>
L	461-1465	<b>PRODUCT LINK, CELLULAR PL641</b> . . . . . 9 Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS		<b>NC</b>

CATERPILLAR MACHINE PRICE LIST

**CB15**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**OTHER ATTACHMENTS**

**WATER SPRAY**

P	445-8757	<b>NOZZLES, STANDARD</b> . . . . . 1 Includes 18 high performance plastic nozzles in 2 spray bars per drum. 9 nozzles per spray bar.		NC
P	445-8758	<b>NOZZLES, PREMIUM</b> . . . . . 2 Includes 18 high performance brass nozzles, in 2 spray bars per drum. 9 nozzles per spray bar.		\$314

**FLUIDS**

**HYDRAULIC OIL**

L	433-0408	<b>OIL, HYD, FACTORY FILLED</b> . . . . . 0		NC
L	433-0411	<b>OIL, HI-AMBIENT FACTORY FILLED</b> . . . . . 0 Hydraulic oil recommended for machines operating in high temperature regions.		\$405
L	433-0410	<b>OIL, HYD, BIO, FACTORY FILLED</b> . . . . . 0 FOR USE WITH LANE 3 ONLY Biodegradable oil recommended for hydraulic system when environmental compliance is required or desired.		\$695

**INSTRUCTIONS**

**DECAL PACKAGES**

L	522-4617	<b>INSTRUCTIONS, NORTH AMERICAN</b> . . . . . 0 ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada).		NC
---	----------	---	--	----



CATERPILLAR MACHINE PRICE LIST

**CB15**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
<b>ELECTRICAL</b>				
P	434-5133	<b>LIGHT, ROTATING BEACON</b> . . . . . 13 This option provides 2 LED amber strobe lights and a strobe ON/OFF rocker switch. The rocker switch comes installed from the factory, but the 2 strobe lights are not installed and come stowed in the engine compartment to help prevent loss or damage during transit.		\$700
P	434-4017	<b>LIGHTS, HALOGEN</b> . . . . . 35 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 10 standard output halogen flood lamps: 2 front facing and 2 rear facing lamps mounted to the ROPS canopy; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports. ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS CANNOT BE USED WITH: 530-3115 LIGHTS, LED, ROPS 432-8358 LIGHTS, HIGH INTENSITY, ROPS	0	\$1,190 \$1,190 NI
P	351-3439	<b>LIGHTS, HALOGEN, CAB</b> . . . . . 31 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 10 standard output halogen flood lamps: 2 front facing and 2 rear facing lamps mounted to the cab roof; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS CANNOT BE USED WITH: 515-1430 LIGHTS, LED, CAB 351-3441 LIGHTS, HIGH INTENSITY, CAB	0	\$1,190 \$1,190 NI
P	530-3115	<b>LIGHTS, LED, ROPS</b> . . . . . 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 10 LED flood lamps: 2 front facing and 2 rear facing lamps mounted to the ROPS canopy; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports. ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS CANNOT BE USED WITH: 434-4017 LIGHTS, HALOGEN, ROPS 432-8358 LIGHTS, HIGH INTENSITY, ROPS	0	\$2,165 \$2,165 NI
P	515-1430	<b>LIGHTS, LED, CAB</b> . . . . . 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 10 LED flood lamps: 2 front facing and 2 rear facing lamps mounted to the cab roof; 1 facing the front drum surface and 1 facing the rear drum surface; and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS CANNOT BE USED WITH: 351-3439 LIGHTS, HALOGEN, CAB 351-3441 LIGHTS, HIGH INTENSITY, CAB	0	\$2,165 \$2,165 NI

CATERPILLAR MACHINE PRICE LIST

**CB15**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**ELECTRICAL (CONT.)**

P	432-8358	LIGHTS, HIGH INTENSITY . . . . .	35 0	\$2,765 \$2,765 NI
---	----------	----------------------------------	---------	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER  
 Includes 4 high intensity halogen flood lamps mounted to the ROPS canopy, 2 front facing and 2 rear facing. Selection also includes 6 standard output halogen flood lamps: 1 facing the front drum surface and 1 facing the rear drum surface, and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports.  
 ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS  
 CANNOT BE USED WITH: 434-4017 LIGHTS, HALOGEN, ROPS  
 530-3115 LIGHTS, LED, ROPS

P	351-3441	LIGHTS, HIGH INTENSITY, CAB . . . . .	35 0	\$2,765 \$2,765 NI
---	----------	---------------------------------------	---------	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER  
 Includes 4 high intensity halogen flood lamps mounted to the cab roof, 2 front facing and 2 rear facing. Selection also includes 6 standard output halogen flood lamps: 1 facing the front drum surface and 1 facing the rear drum surface, and 4 facing the lower drum edge, mounted to each of the machine's folded drum supports.  
 ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS  
 CANNOT BE USED WITH: 351-3439 LIGHTS, HALOGEN, CAB  
 515-1430 LIGHTS, LED, CAB

**TECHNOLOGY PRODUCTS**

**CAT COMPACTION CONTROL**

This is a factory designed and integrated SBAS accuracy level pass count and temperature mapping system which requires no off-board infrastructure. For higher level accuracy consult your Dealer Technology Representative to order the necessary base station, data radio and options keys for RTK corrected position signal. Additionally, the machine connectivity modem identified below, requires cellular data plan sold separately. To view IC Mapping data in the office, a VisionLink subscription with 3D Project Monitoring module (an add-on to VisionLink) is required.

P	419-5625	SENSORS, MAT TEMPERATURE . . . . .	9 0	\$3,820 \$3,820 NI
---	----------	------------------------------------	--------	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER  
 Includes front and rear bumper mounted infrared air purged temperature sensors, displayed on the standard LCD display.

P	532-8810	SENSOR, ACCELEROMETER. . . . .	0 0	\$5,530 \$5,530 NI
---	----------	--------------------------------	--------	-----------------------

ALSO AVAILABLE ON A MISCELLANEOUS ORDER  
 Hardware mounted within the front drum to mount the Caterpillar supplied accelerometer for CMV measurement. Output is a unit-less CMV stiffness indication displayed at the operator station.

L	434-5079	MAPPING, GNSS . . . . .	26	\$14,350
---	----------	-------------------------	----	----------

Factory install of all components needed for mapping of temperature, and machine pass count. Includes front and rear bumper mounted infrared, air purged temperature sensors, harnesses, system electronic controls including CB460 Displayed (17.8 cm/7.0 in) and MS952 antenna/receiver.  
 Includes: Sensor, Mat Temperature  
 ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS

CATERPILLAR MACHINE PRICE LIST

**CB15**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**TECHNOLOGY PRODUCTS (CONT.)**

**CAT COMPACTION CONTROL (Cont.)**

L	434-7889	MAPPING, GNSS, CAB . . . . .	26	\$14,350
Factory install of all components needed for mapping of temperature, and machine pass count. Includes front and rear bumper mounted infrared, air purged temperature sensors, harnesses, system electronic controls including CB460 Display (17.8 cm/7.0 in) and MS952 antenna/receiver. Includes: Sensor, Mat Temperature ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS				

**MACHINE TO MACHINE COMMUNICATION**

Machine to Machine Communication is integrated hardware consisting of an electronic control module, radio and antennas with connecting wiring that enables machines to communicate key compaction data via local wireless and/or cellular data networks.  
 Contact your local SITECH dealer and wireless data carrier for additional support and cellular data packages.

L	567-4609	MACHINE CONNECTIVITY, SNM941 . . . . .	0	\$3,635
SIM card enabled CDMA or GSM network with built in WIFI. ONLY FOR USE WITH: 434-5079 MAPPING, GNSS or 434-7889 MAPPING, GNSS, CAB				

**OTHER ATTACHMENTS**

**OPERATOR ENVIRONMENT**

P	513-6265	SEAT BELT, 3" . . . . .	0	\$146
L	435-4830	AIR CONDITIONER . . . . .	46	\$6,340
ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS 355-1671 BELT, ENG, A/C				
P	351-3438	SUN SCREEN . . . . .	4	\$420
Sun screen/visor inside cab. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS				
P	462-0499	MIRRORS, EXTERNAL, FRONT . . . . .	20	\$595
			20	\$595 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 2 external, adjustable mirrors on the front of the cab. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS				
P	462-0500	MIRRORS, EXTERNAL, REAR . . . . .	20	\$595
			20	\$595 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 2 external, adjustable mirrors on the rear of the cab. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS				
P	362-2758	MIRRORS, EXTERNAL . . . . .	0	\$1,170
			0	\$1,170 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes 4 external adjustable mirrors, 2 mounted to the front frame, and 2 mounted to the rear frame.				

CATERPILLAR MACHINE PRICE LIST

**CB15**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**OTHER ATTACHMENTS (CONT.)**

**EDGE MANAGEMENT**

P	530-3109	EDGE CUTTER/COMPACTOR . . . . .	0 0	\$8,930 \$8,930 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes a straight cutting wheel, capable of cutting up to an 85 mm (3.3 in) lift, and a bevel compaction wheel, capable of edge compacting lifts greater than 96 mm (3.7 in) at a 41 degree bevel. For bevel compacting thinner lifts, between 45-96 mm (1.7-3.7 in), please purchase bevel compaction wheel, 461-2682, from the Caterpillar Parts Network. ONLY FOR USE WITH: 454-3055 CONTROL, PREMIUM				

**WATER SYSTEM - UPGRADES**

P	435-1283	MATS, COCOA . . . . .	26 0	\$1,425 \$1,400 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER CANNOT BE USED WITH: 435-1282 MATS, WATER DISTRIBUTION				
P	435-1282	MATS, WATER DISTRIBUTION . . . . .	24 0	\$1,820 \$1,785 NI
ALSO AVAILABLE ON A MISCELLANEOUS ORDER CANNOT BE USED WITH: 435-1283 MATS, COCOA				
P	433-7143	FREEZE PROTECTION, ROPS/FOPS . . . . .	4	\$660
Includes a reservoir that holds windshield washer or RV antifreeze that protects the water lines, pumps, filters, and nozzles from freezing. ONLY FOR USE WITH: 532-8806 PLATFORM, ROPS/FOPS				
P	433-7142	FREEZE PROTECTION, CAB . . . . .	4	\$660
Includes a reservoir that holds windshield washer or RV antifreeze that protects the water lines, pumps, filters, and nozzles from freezing. ONLY FOR USE WITH: 532-8807 CAB, ROPS/FOPS				

**MISCELLANEOUS ATTACHMENTS**

P	257-9360	COVERS, DRUM . . . . .	105	\$730
Helps keep debris out of drums.				

**FACTORY SOURCED KITS**

P	487-5694	PIVOTING STEER WHEEL . . . . .	5	\$695 NI
FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Field installed kit to adapt the standard fixed steering wheel location to one with the ability to rotate 45 degrees inward toward the operator. The inward rotation allows enough movement that operators can comfortably steer with precision while performing delicate steering maneuvers.				

CATERPILLAR MACHINE PRICE LIST

**CB15**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FACTORY SOURCED KITS (CONT.)**

P	544-5129	<b>DRUM KIT, REAR OSC, HD, FLD</b> ..... 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER 2130 mm (84") rear oscillatory drum kit consisting of a standard shell material for field installation into a CB15 or CB66B.		<b>\$24,880 NI</b>
P	544-5130	<b>DRUM KIT, REAR OSC, FLD</b> ..... 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER 2130 mm (84") rear oscillatory drum kit consisting of a hardened shell material for field installation into a CB15 or CB66B.		<b>\$32,530 NI</b>
P	470-1855	<b>ACCELEROMETER READY.</b> ..... 0 FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Hardware mounted within the front drum to mount the aftermarket SITECH supplied CM310 accelerometer for CMV measurement. Output is unit-less CMV stiffness indication displayed on SITECH supplied mapping system.		<b>\$3,345 NI</b>

**DOCUMENTATION**

**CERTIFICATES**

P	354-8706	<b>YEAR OF MANUFACTURE PLATE</b> ..... 0 Plate attached to PIN plate showing year of Final Plant Shipping date. Available for all regions, but required in Brazil. CANNOT BE USED WITH: 535-9662 CE CERTIFICATION		<b>NC</b>
P	0P-1870	<b>CERTIFICATE OF ORIGIN.</b> ..... 0		<b>NC</b>

**PACKING**

	0P-0210	<b>PACK, DOMESTIC TRUCK</b> ..... 0		<b>NC</b>
	0P-3651	<b>PACKING, MISC MATERIAL</b> ..... 0 No charge for packing. Applicable freight charges may apply.		<b>NC</b>