

CS44B VIBRATORY COMPACTOR
 PIRACICABA, BRAZIL

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

Dual element air cleaner
 Fuel filter/water separator/manual
 priming pump and water indicator
 Three-speed throttle switch including
 ECOMODE
 Dual propel pumps - 1 for drum and
 1 for tires
 Dual braking systems (service &
 parking, for both drum and axle)
 Two-speed hydrostatic transmission
 Limited slip differential

ELECTRICAL

12-volt starting and charging system
 alternator
 Maintenance free battery - 750 CCA
 Halogen working lights - canopy mounted
 (2 front-facing and 2 rear-facing)
 Backup alarm and forward warning horn
 Product link ready
 Beacon ready

OPERATOR ENVIRONMENT

ROPS/FOPS platform
 Four heavy-duty isolation mounts
 Platform handrails/guardrails
 Power steering
 Adjustable tilt-steering column
 Adjustable suspension seat
 Retractable seat belt
 Rear view camera with display
 Adjustable, padded arm rest for
 propel lever operation
 On-board display with audible
 warning alarm and interface for:
 -hydraulic oil temperature gauge
 -engine oil pressure gauge
 -engine coolant temperature gauge
 -alternator charge
 -fuel level gauge
 -service hour meter
 -lockable, vandalism guard for
 on-board display

12-volt power (universal and USB point)

COOLING

Premixed 50% concentration of extended
 life coolant with freeze protection
 to -37C (-35F)

DRUMS

Smooth drum
 1676 mm (66") wide x 1225 mm (48")
 diameter
 Dual amplitude with single frequency
 Pod-style eccentric weight
 housing
 Front adjustable steel scraper

OTHER STANDARD EQUIPMENT

Locking composite engine enclosure
 Sealed-for-life hitch bearings
 Sight gauges:
 -coolant level
 -hydraulic oil level
 Hydraulic tank locking cap
 Articulated frame with safety lock
 Transport tie-down and lift points
 Fuel tank with lockable cap
 Quick connect hydraulic pressure test
 ports
 SOS ports:
 -engine
 -hydraulic
 -coolant
 CS universal bumper
 Seat belt, 76.2 mm (3")

CS44B VIBRATORY COMPACTOR
 PIRACICABA, BRAZIL

Ship Weight
 lbs

LIST PRICE
 AT DEALER

**Lane 2 is reserved for the Base Order Management Program.
 Please use Lane 2 when placing orders that are part of the Base Order
 Management program**

560-6336 CS44B VIBRATORY COMPACTOR DCA1 0 \$155,050
 LANE 1 - AVAILABLE FROM BALTIMORE PDC

- INCLUDES:
 386-5361 CS44B VIBRATORY COMPACTOR
 186-2340 TIRES, 14,9-24 BS 6PR
 386-5323 OIL, HYDR, FACTORY FILLED
 386-5324 FREQUENCY, FIXED
 386-5390 CONTROL, BASIC
 386-5571 ENGINE, TIER/STAGE 4 CERTIFIED
 386-5602 NO BLADE
 386-5603 SCRAPER, STEEL, FRONT
 417-9445 PLATFORM, ROPS/FOPS
 426-2675 SEAT, DELUXE CONTROL
 454-5454 PRODUCT LINK, CELLULAR PL641
 467-7329 INSTALLATION, ROPS/FOPS
 477-9990 LANGUAGES, OPTION 1
 554-1057 FILMS

NOTE: Please refer to the Lane 1 section to complete your order.

386-5361 CS44B VIBRATORY COMPACTOR 14,920 \$148,310
 LANE 2 - AVAILABLE FROM PIRACICABA FACTORY
 LANE 3 - AVAILABLE FROM PIRACICABA FACTORY

AVAILABLE FOR: AM-N, EU and South Korea

OP-4247 CS44B MISC MATL 0 NC
 AVAILABLE FROM PIRACICABA FACTORY

Only reference numbers that have the text
 "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.

USE	REF NO.	LANE 1 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS

LANE SELECTION

	0P-9001	LANE 1 ORDER	0	NC
--	---------	------------------------	---	----

INSTRUCTIONS

L	386-5313	INSTRUCTIONS, NORTH AMERICAN ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada).	0	NC
L	386-5314	INSTRUCTIONS, INTERNATIONAL ISO picto warning decals using symbols only as required for all non-North American countries and Quebec, Canada.	0	NC

ANTIFREEZE

	0P-1940	WINDSHIELD WASHER EMPTY	0	NC
--	---------	-----------------------------------	---	----

FUEL PROTECTION

P	0P-4269	ANTIFREEZE, -25C (-13F) Provides fuel (diesel) antifreeze protection down to -45C (-50F)	0	NC
---	---------	---	---	----

STORAGE PROTECTION

	0P-4782	STORAGE PROTECTION	0	NC
--	---------	------------------------------	---	----

CYLINDER PROTECTION

	0P-3940	PROTECTION, CYLINDER ROD	0	NC
--	---------	------------------------------------	---	----

SERVICE MANUAL

	0P-0996	MANUAL, ENGLISH	0	NC
	0P-3389	INSTRUCTIONS, FRENCH	0	NC

USE	REF NO.	LANE 1 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	--------------------	-------------------------

LANE 1 AM-NORTH OPTIONAL ATTACHMENTS

CERTIFICATES

	0P-1870	CERTIFICATE OF ORIGIN	0	NC
P	524-1948	COMPLIANCE FILM,ELECT-MAGNETIC Film indicates EMC compliance. REQUIRED BY: CANADA	0	NC

PACKING

	0P-0210	PACK, DOMESTIC TRUCK	0	NC
--	---------	--------------------------------	---	----

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0		NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.			
OP-9003	LANE 3 ORDER	0		NC

POWERTRAIN

ENGINE

L	386-5571	ENGINE, TIER/STAGE 4 CERTIFIED	0	NC
		Meets U.S. EPA Tier 4 Final emission standards. ONLY FOR USE WITH: 386-5361 CS44B VIBRATORY COMPACTOR		

OPERATOR ENVIRONMENT

OPERATORS STATION

L	417-9445	PLATFORM, ROPS/FOPS	0	\$5,980
		Open platform with handrails, ROPS/FOPS canopy and working lights. ONLY FOR USE WITH: 386-5361 CS44B VIBRATORY COMPACTOR		
L	391-0157	CAB, ROPS/FOPS W/ HTR & AC	613	\$27,550
		ROPS/FOPS Cab, air conditioning, heater/defroster, radio ready headliner, 12-volt power point and working lights ONLY FOR USE WITH: 386-5361 CS44B VIBRATORY COMPACTOR		

SEATS

L	441-5222	SEAT, BASIC CONTROL	248	NC
		LCD display and vinyl seat with NO rotation ONLY FOR USE WITH: 417-9445 PLATFORM, ROPS/FOPS or 446-4913 PLATFORM, ROPS/FOPS		
L	426-2675	SEAT, DELUXE CONTROL	273	\$505
		LCD display and vinyl seat with 20 deg RH operator station rotation ONLY FOR USE WITH: 417-9445 PLATFORM, ROPS/FOPS or 446-4913 PLATFORM, ROPS/FOPS		
L	426-2676	SEAT, DELUXE CONTROL, CAB	172	\$545
		LCD display and cloth seat with NO rotation ONLY FOR USE WITH: 391-0157 CAB, ROPS/FOPS W/HTR + AC or 441-3374 CAB, ROPS/FOPS W/ HTR & AC		

OPERATOR CONTROLS

L	386-5390	CONTROL, BASIC	0	NC
		Basic controls with the following standard machine parameters; engine faults, machine faults, display of coolant temperature, engine oil pressure, fuel tank level, DEF tank level, battery voltage, hyd oil temp, engine rpm, engine load, fuel consumption rate and ambient air temperature		
L	386-5389	CONTROL, DELUXE	5	\$650
		Deluxe controls includes all the basic control features with the addition of machine speed and vibratory speeds (VPM gauge, if equipped with FREQUENCY, VARIABLE system). In addition, the deluxe controls allows for other technology upgrades		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

LANGUAGE OPTIONS

L	477-9990	LANGUAGES, OPTION 1	0	NC
		Includes standard languages (English, Spanish, French, German, Italian, Polish, Portuguese, Turkish, and Korean) for machine operation and control.		

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country, please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Cat marketing representative with questions.

L	454-5453	PRODUCT LINK, SATELLITE PL631	9	\$446
		Product Link Pro series PL631 uses a satellite network to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. For use in areas with poor or no cellular coverage		
L	454-5454	PRODUCT LINK, CELLULAR PL641	9	NC
		Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and condition information for viewing in Product Link-s remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data		

PRODUCT LINK INSTALLATION

L	467-7328	INSTALLATION, CAB	8	NC
		Factory installation of PL on machines with cab ONLY FOR USE WITH: 441-3374 CAB, ROPS/FOPS W/ HTR & AC or 391-0157 CAB, ROPS/FOPS W/ HTR & AC		
L	467-7329	INSTALLATION, ROPS/FOPS	8	NC
		ONLY FOR USE WITH: 446-4913 PLATFORM, ROPS/FOPS or 417-9445 PLATFORM, ROPS/FOPS		

TIRES, RIMS, AND WHEELS

L	186-2340	TIRES, 14,9-24 BS 6PR	0	\$256
		6-ply flotation (diamond tread) tires and rims with liquid ballast		
L	186-2335	TIRES, 14,9-24 8PR R-1	0	\$540
		6-ply traction (lug tread) tires and rims with liquid ballast		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

DRUMS

VIBRATORY SYSTEMS

L	386-5324	FREQUENCY, FIXED 61		NC
		Single 31.9 Hz (1914 vpm) frequency with high and low amplitude		
L	386-5334	FREQUENCY, VARIABLE 67		\$2,655
		Frequency dial that electronically controls the displacement of the vibratory pump. Frequency range from 23.3-31.9 Hz (1400-1914 vpm) ONLY FOR USE WITH: 386-5389 CONTROL, DELUXE		

SCRAPER SYSTEMS

L	386-5603	SCRAPER, STEEL, FRONT 0		NC
		Standard smooth drum with one steel scraper at the front of drum		
L	386-5604	SCRAPER, STEEL, FRONT & REAR 176		\$1,820
		Standard smooth drum with flat steel scrapers at the front and rear of drum		
L	472-2054	SCRAPER, SHELL KIT READY 448		\$6,820
		Factory installed smooth drum with smooth drum and padfoot scrapers. Scrapers at the front and rear for use with smooth drum on machine or with pre-existing dealer/customer padfoot shell kit		
L	386-5606	DRUM, SHELL KIT 2,331		\$15,350
		Factory installed oval padfoot shell halves with padfoot scrapers at the front and rear of drum		
L	386-5607	SHELL KIT, SQR, PADFOOT 2,351		\$15,350
		Factory installed square padfoot shell halves with padfoot scrapers at front and rear of drum		

BLADES

LEVELING BLADE

L	386-5602	NO BLADE 0		NC
L	386-5601	BLADE, LEVELING 1,160		\$12,690
		Factory installed leveling blade and controls		

FLUIDS

HYDRAULIC OIL

L	386-5323	OIL, HYDR, FACTORY FILLED 0		NC
		Cat standard hydraulic oil		
L	386-5333	OIL, BIO HYDR, FACTORY FILLED 0		\$4,735
		This Hydraulic Environmental Ester Synthetic oil is recommended for hydraulic system when environmental compliance is required or desired. Factory filled.		

ANTIFREEZE

	0P-1940	WINDSHIELD WASHER EMPTY 0		NC
		ONLY FOR USE WITH: 391-0157 CAB, ROPS/FOPS W/ HTR & AC or 441-3374 CAB, ROPS/FOPS W/ HTR & AC		
		REQUIRED BY: European Dealers		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FLUIDS (CONT.)

CYLINDER PROTECTION

OP-3940	PROTECTION, CYLINDER ROD	0	NC
---------	------------------------------------	---	----

STORAGE PROTECTION

OP-4782	STORAGE PROTECTION	0	NC
---------	------------------------------	---	----

INSTRUCTIONS

DECAL PACKAGES

L	386-5313	INSTRUCTIONS, NORTH AMERICAN ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada). ONLY FOR USE WITH: 386-5361 CS44B VIBRATORY COMPACTOR and 417-9445 PLATFORM, ROPS/FOPS	0	NC
L	386-5314	INSTRUCTIONS, INTERNATIONAL ISO picto warning decals using symbols only as required for all non-North American countries and Quebec, Canada. ONLY FOR USE WITH: 386-5361 CS44B VIBRATORY COMPACTOR and 417-9445 PLATFORM, ROPS/FOPS	0	NC
L	386-5315	INSTRUCTIONS, NORTH AMERICAN ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada). ONLY FOR USE WITH: 386-5361 CS44B VIBRATORY COMPACTOR and 391-0157 CAB, ROPS/FOPS W/ HTR & AC	0	NC
L	386-5316	INSTRUCTIONS, INTERNATIONAL ISO picto warning decals using symbols only as required for all non-North American countries and Quebec, Canada. ONLY FOR USE WITH: 386-5361 CS44B VIBRATORY COMPACTOR and 391-0157 CAB, ROPS/FOPS W/HTR + AC	0	NC

SERVICE INSTRUCTIONS

OP-0996	MANUAL, ENGLISH	0	NC
---------	---------------------------	---	----

FILM GP

L	554-1057	FILM GP "MADE IN BRAZIL"	0	NC
---	-----------------	---	---	----

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

ELECTRICAL

BEACON, ROTATING

P	449-6298	BEACON, ROTATING	3	\$433
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		

LIGHTS, UPGRADED

P	452-6686	LIGHTS, UPGRADED	5	\$230
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER	5	\$230 NI
		4 additional lights for increased nighttime visibility		

MODULE

P	386-5611	MODULE, RECORDING, FIX FREQ	7	\$6,500
			7	\$6,500 NI

FOR USE IN LANE 3 ONLY
 ALSO AVAILABLE ON A MISCELLANEOUS ORDER
 Factory installed fixed frequency recording module required for French market
 ONLY FOR USE WITH: 386-5361 CS44B VIBRATORY COMPACTOR and 386-5324 FREQUENCY, FIXED and 391-0157 CAB, ROPS/FOPS W/ HTR & AC

P	386-5670	MODULE, RECORDING, VARIABLE	7	\$6,500
			7	\$6,500 NI

FOR USE IN LANE 3 ONLY
 ALSO AVAILABLE ON A MISCELLANEOUS ORDER
 Factory installed variable frequency recording module required for French market
 ONLY FOR USE WITH: 386-5361 CS44B VIBRATORY COMPACTOR and 386-5334 FREQUENCY, VARIABLE and 391-0157 CAB, ROPS/FOPS W/ HTR & AC

TECHNOLOGY PRODUCTS

CAT COMPACTION CONTROL - MEASURE

Base/Entry level compaction measurement systems that detect changes in soil stiffness and provide the operator with real time compaction information on the standard machine display.

L	453-6642	SENSOR, ACCELEROMETER.	13	\$6,440
			13	\$6,440 NI

ALSO AVAILABLE ON A MISCELLANEOUS ORDER
 Traditional soil stiffness measurement providing CMV values resulting from vibration energy imparted to the soil
 ONLY FOR USE WITH: 386-5389 CONTROL, DELUXE and 391-0157 CAB, ROPS/FOPS W/ HTR & AC or 441-3374 CAB, ROPS/FOPS W/ HTR & AC
 CANNOT BE USED WITH: 386-5606 DRUM, SHELL KIT and 386-5607 SHELL KIT, SQR, PADFOOT

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

CAT COMPACTION CONTROL - MEASURE (Cont.)

L	386-5600	SENSOR, ACCELEROMETER.	13 13	\$6,440 \$6,440 NI
		FOR USE IN LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Traditional soil stiffness measurement providing CMV values resulting from vibration energy imparted to the soil. ONLY FOR USE WITH: 386-5389 CONTROL, DELUXE and 446-4913 PLATFORM, ROPS/FOPS or 417-9445 PLATFORM, ROPS/FOPS CANNOT BE USED WITH: 386-5606 DRUM, SHELL KIT or 386-5607 SHELL KIT, SQR, PADFOOT		

GUARDS

P	386-5456	GUARD, TRANSMISSION	44 44	\$1,130 \$1,130 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Protection for the rear axle, hydraulic drive motor and hose fittings REQUIRED BY: EU DEALERS		

FACTORY SOURCED KITS

P	465-1010	SHELL KIT, OVAL, PADFOOT, FLD	1,225	\$16,980 NI
		FOR USE IN LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Field installed oval padfoot shell halves with padfoot scrapers at front and rear of drum		
P	465-1001	SHELL KIT, SQR, PADFOOT, FLD	1,225	\$16,980 NI
		FOR USE IN LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Field installed square padfoot shell halves with padfoot scrapers at front and rear of drum		
P	465-0998	BLADE, LEVELING, FLD	1,160	\$11,080 NI
		FOR USE IN LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER INCLUDES: Field installed components for leveling blade		

DOCUMENTATION

CERTIFICATES

P	0P-1870	CERTIFICATE OF ORIGIN.	0	NC
---	---------	--------------------------------	---	----

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------------	--------------------	-------------------------

PACKING

OP-4505	ROLL ON-ROLL OFF	0		\$915 NET
OP-6706	BUNDLE EXPORT PACKING	0		NC
	This OP should be ordered for all miscellaneous orders			