

CS54B VIBRATORY COMPACTOR  
MINNEAPOLIS, MN, USA (SAP)

Ship Weight  
lbs

LIST PRICE  
AT DEALER

Standard Equipment:

### POWERTRAIN

CAT C4.4 inline four cylinder, turbo-charged diesel engine with glow-plug heater  
Dual element air cleaner  
Fuel filter/water separator/electronic priming pump and water indicator  
Three-speed throttle switch including ECOMODE  
Dual propel pumps - 1 for drum and 1 for tires  
Dual braking systems (service & parking, drum only)  
Two-speed hydrostatic transmission  
Limited slip differential

### ELECTRICAL

24-volt starting and charging system alternator  
(2) Maintenance free batteries - 750 CCA  
Halogen working lights - canopy mounted (2 front-facing and 2 rear-facing)  
Backup alarm and forward warning horn  
Product link ready  
Beacon ready

### OPERATOR ENVIRONMENT

ROPS/FOPS platform  
Four heavy-duty isolation mounts  
Platform handrails/guardrails  
Power steering  
Adjustable tilt-steering column  
Adjustable, rotating suspension seat  
Retractable seat belt  
Rear view camera with display  
Adjustable, padded arm rest for propel lever operation  
On-board display with audible warning alarm and interface for:  
-hydraulic oil temperature gauge  
-engine oil pressure gauge  
-engine coolant temperature gauge  
-alternator charge  
-fuel level gauge  
-service hour meter  
-engine RPM  
-ground speed, vibe speed  
-fuel rate gauge  
-engine load gauge  
-basic compaction measurement  
Lockable, vandalism guard for on-board display  
12-volt power point

### COOLING

Premixed 50% concentration of extended life coolant with freeze protection to -37C (-35F)

### DRUMS

Smooth drum  
2134 mm (84") wide x 1534 mm (60.4") diameter  
Dual amplitude with single frequency  
Dual, pod-style eccentric weight housings  
Front adjustable steel scraper

### OTHER STANDARD EQUIPMENT

Locking composite engine enclosure  
Sealed-for-life hitch bearings  
Sight gauges:  
-coolant level  
-hydraulic oil level  
Hydraulic tank locking cap  
Articulated frame with safety lock  
Transport tie-down and lift points  
Fuel tank with lockable cap  
Quick connect hydraulic pressure test ports  
SOS ports:  
-engine  
-hydraulic  
-coolant  
Universal bumper

CS54B VIBRATORY COMPACTOR  
MINNEAPOLIS, MN, USA (SAP)

Ship Weight  
lbs

LIST PRICE  
AT DEALER

**Lane 2 is reserved for the Base Order Management Program.  
Please use Lane 2 when placing orders that are part of the  
Base Order Management program.**

**497-5491 CS54B VIBRATORY COMPACTOR DCA1 . . . . . 0 \$195,620**  
LANE 1 - AVAILABLE FROM MINNEAPOLIS PDC

- INCLUDES:
- 433-1610 CS54B VIBRATORY COMPACTOR
  - 420-9150 ENGINE, TIER 4F/STAGE 4
  - 479-9014 SCREEN, STANDARD
  - 435-8036 CAB, ROPS/FOPS WITH A/C
  - 356-1227 SEAT, CLOTH
  - 387-1801 BELT SEAT, 3"
  - 477-9990 LANGUAGES, OPTION 1
  - 454-5454 PRODUCT LINK, CELLULAR PL641
  - 454-0249 INSTALLATION, CAB
  - 441-6674 SENSOR, DRIVE POWER
  - 203-4717 TIRES, 23, 1-26 8PR
  - 355-3542 FREQUENCY, FIXED
  - 360-0493 SCRAPER, STEEL, FRONT
  - 362-4940 OIL, HYD, FACTORY FILLED
  - 355-3056 LIGHTS, UPGRADED
  - 107-4641 SUN VISOR, FRONT
  - 107-4643 MIRRORS, REARVIEW, INTERNAL

NOTE: Please refer to the Lane 1 section to complete your order.

**497-5489 CS54B VIBRATORY COMPACTOR DCA2 . . . . . 0 \$172,520**  
LANE 1 - AVAILABLE FROM MINNEAPOLIS PDC

- INCLUDES:
- 433-1610 CS54B VIBRATORY COMPACTOR
  - 420-9150 ENGINE, TIER 4F/STAGE 4
  - 479-9014 SCREEN, STANDARD
  - 435-8035 PLATFORM, ROPS/FOPS
  - 356-1226 SEAT, VINYL
  - 387-1801 BELT SEAT, 3"
  - 477-9990 LANGUAGES, OPTION 1
  - 454-5454 PRODUCT LINK, CELLULAR PL641
  - 454-0250 INSTALLATION, ROPS/FOPS
  - 441-6674 SENSOR, DRIVE POWER
  - 203-4717 TIRES, 23, 1-26 8PR
  - 355-3542 FREQUENCY, FIXED
  - 360-0493 SCRAPER, STEEL, FRONT
  - 362-4940 OIL, HYD, FACTORY FILLED
  - 355-3056 LIGHTS, UPGRADED
  - 354-5413 MIRRORS, REARVIEW, EXTERNAL

NOTE: Please refer to the Lane 1 section to complete your order.

CS54B VIBRATORY COMPACTOR MINNEAPOLIS, MN, USA (SAP)	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

<b>433-1610</b>	<b>CS54B VIBRATORY COMPACTOR</b> ..... 17,668 LANE 2 - AVAILABLE FROM MINNEAPOLIS FACTORY LANE 3 - AVAILABLE FROM MINNEAPOLIS FACTORY	<b>\$165,820</b>
-----------------	---	------------------

<b>OP-2532</b>	<b>CS54B MISC MATL</b> ..... 0 AVAILABLE FROM MINNEAPOLIS FACTORY Only reference numbers that have the text "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.	<b>NC</b>
----------------	---	-----------

USE	REF NO.	<b>LANE 1</b>	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------	--------------------	-------------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS**

***LANE SELECTION***

	0P-9001	LANE 1 ORDER . . . . .	0	NC
--	---------	------------------------	---	----

***INSTRUCTIONS - PICTOGRAPH FILMS***

L	437-9888	INSTRUCTIONS, NA PLATFORM . . . . .	0	NC
---	----------	-------------------------------------	---	----

L	437-9887	INSTRUCTIONS, INT'L PLATFORM . . . . .	0	NC
---	----------	--	---	----

L	437-9886	INSTRUCTIONS, NA CAB . . . . .	0	NC
---	----------	--------------------------------	---	----

L	437-9885	INSTRUCTIONS, INT'L CAB . . . . .	0	NC
---	----------	-----------------------------------	---	----

***PACKING***

	0P-0210	PACK, DOMESTIC TRUCK . . . . .	0	NC
--	---------	--------------------------------	---	----

USE	REF NO.	<b>LANE 1</b>	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------	--------------------	-------------------------

**LANE 1 AM-NORTH OPTIONAL ATTACHMENTS**

***CERTIFICATES***

	0P-1870	CERTIFICATE OF ORIGIN . . . . .	0	<b>NC</b>
P	524-1948	COMPLIANCE FILM,ELECT-MAGNETIC . . . . . Film indicates EMC compliance. Required for Canada	0	<b>NC</b>

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**LANE SELECTION**

OP-9002	<b>LANE 2 ORDER</b> . . . . .	0	<b>NC</b>
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	<b>LANE 3 ORDER</b> . . . . .	0	<b>NC</b>

**POWERTRAIN**

**ENGINE**

L	420-9150	<b>ENGINE, TIER 4F/STAGE 4</b> . . . . .	0	<b>NC</b>
		US EPA Tier 4 Final/EU Stage IV equivalent engine.		

**ENCLOSURES**

L	479-9014	<b>SCREEN, STANDARD</b> . . . . .	7	<b>NC</b>
		Fixed (not openable) screen at rear, right side of the engine compartment.		
L	479-9015	<b>FUEL SYSTEM, DOOR</b> . . . . .	23	<b>\$365</b>
		Hinged and CAT key lockable door to access fuel fill without opening enclosure.		

**OPERATOR ENVIRONMENT**

**OPERATOR STATIONS**

L	435-8035	<b>PLATFORM, ROPS/FOPS</b> . . . . .	1,262	<b>NC</b>
		Open platform with handrails, ROPS/FOPS canopy and working lights.		
L	435-8038	<b>CAB, ROPS/FOPS WITH HEATER</b> . . . . .	1,620	<b>\$17,080</b>
		FOR USE WITH LANE 3 ONLY Two front-facing and two rear-facing working lights, external rear-view mirrors, heater & defroster, and wet-arm wipers/washers (front and rear). Cab is Radio Ready, including hardware, wiring, voltage converter and 12-volt power point. Wiring only - Radio and Speakers not included.		
L	435-8036	<b>CAB, ROPS/FOPS WITH A/C</b> . . . . .	1,700	<b>\$22,810</b>
		Two front-facing and two rear-facing working lights, external rear-view mirrors, air conditioner, heater & defroster, and wet-arm wipers/washers (front and rear). Cab is Radio Ready, including hardware, wiring, voltage converter and 12-volt power point. Wiring only - Radio and Speakers not included.		

**SEATS**

L	356-1226	<b>SEAT, VINYL</b> . . . . .	150	<b>NC</b>
		Standard rotating vinyl covered suspension seat.		
L	356-1227	<b>SEAT, CLOTH</b> . . . . .	150	<b>\$314</b>
		Standard rotating cloth covered suspension seat. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		
L	356-1229	<b>SEAT, CLOTH, DELUXE</b> . . . . .	158	<b>\$545</b>
		Deluxe rotating cloth seat with head rest, air suspension and additional adjustments. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**OPERATOR ENVIRONMENT (CONT.)**

**SEAT BELTS**

L	382-9003	SEAT BELT, 2" .....	2	NC
L	387-1801	SEAT BELT, 3" .....	2	\$146

**OPERATOR LANGUAGES**

L	477-9990	LANGUAGES, OPTION 1 .....	0	NC
Includes standard languages (English, Spanish, French, German, Italian, Polish, Portuguese, Turkish, and Korean) for machine operation and control.				

**TECHNOLOGY PRODUCTS**

**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	454-5453	PRODUCT LINK, SATELLITE PL631 .....	9	\$446
Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.				
L	454-5454	PRODUCT LINK, CELLULAR PL641 .....	9	NC
Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.				

**PRODUCT LINK INSTALLATION**

L	454-0250	INSTALLATION, ROPS/FOPS .....	8	NC
Factory installation of PL on machine with ROPS/FOPS canopy. ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS				
L	454-0249	INSTALLATION, CAB .....	8	NC
Factory installation of PL on machines with cab. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C				

**CAT COMPACTION CONTROL - MEASURE**

Base/Entry level compaction measurement systems that detect changes in soil stiffness and provide the operator with real time compaction information on the standard machine display.

L	444-5931	NO COMPACTION SENSOR .....	0	NC
No Sensors.				

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**TECHNOLOGY PRODUCTS (CONT.)**

**CAT COMPACTION CONTROL - MEASURE (Cont.)**

L	441-6674	<b>SENSOR, DRIVE POWER</b> . . . . . 5 Proprietary Caterpillar technology that directly measures soil stiffness via material deflection (rolling resistance). Includes Sensor, Angle, High-Accuracy.		\$3,960
L	441-6676	<b>SENSOR, ACCELEROMETER.</b> . . . . . 15 Traditional soil stiffness measurement providing CMV values resulting from vibration energy imparted to the soil. Sensor, Accel. will not work with Padfoot Shell Kit operation / Will only work with smooth drum operation.		\$6,440
L	435-8012	<b>SENSOR, DRIVE POWER AND ACCEL</b> . . . . . 20 Provides MDP and CMV systems. Proprietary technology (MDP) that directly measures soil stiffness via material deflection (rolling resistance); plus, CMV traditional soil stiffness measurement providing values resulting from vibration energy imparted to the soil. Includes Sensor, Angle, High-Accuracy		\$8,150

**TIRES, RIMS, AND WHEELS**

L	203-4717	<b>TIRES, 23,1-26 TI 8PR</b> . . . . . 935 8-ply flotation (diamond tread) tires and rims with liquid ballast.		\$2,050
L	203-4718	<b>TIRE, TRACTION</b> . . . . . 935 23.1 x 26 8 ply traction (lug tread) tires and rims with liquid ballast. Typically for use with padfoot style drum.		\$3,420

**DRUMS**

**VIBRATORY SYSTEMS**

L	355-3542	<b>FREQUENCY, FIXED</b> . . . . . 0 Single 31.9 Hz (1914 vpm) frequency with high and low amplitude.		NC
L	355-3541	<b>FREQUENCY, VARIABLE</b> . . . . . 0 Frequency dial that electronically controls the displacement of the vibratory pump. Frequency range from 23.3-31.9 Hz (1400-1914 vpm).		\$2,465

**SCRAPER SYSTEM**

L	360-0493	<b>SCRAPER, STEEL, FRONT</b> . . . . . 132 Standard smooth drum with one steel scraper at the front of the smooth drum.		NC
L	360-0494	<b>SCRAPER, STEEL, FRONT &amp; REAR.</b> . . . . . 487 Standard smooth drum with flat steel scrapers at the front and rear of the smooth drum.		\$1,945
L	360-0495	<b>SCRAPER, POLYURETHANE.</b> . . . . . 492 Two flexible, contacting scrapers blades iso-mounted at the front and rear of the smooth drum.		\$2,590
L	360-0496	<b>DRUM, SHELL KIT</b> . . . . . 3,235 Factory installed oval padfoot shell halves with padfoot scrapers located at the front and rear of the drum.		\$18,020
L	377-2938	<b>SHELL KIT, SQUARE, PADFOOT</b> . . . . . 3,585 Factory installed square padfoot shell halves with padfoot scrapers located at front and rear of the drum.		\$17,670



USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**DRUMS (CONT.)**

**SCRAPER SYSTEM (Cont.)**

L	472-2055	SCRAPER, SHELL KIT READY . . . . .	970	\$6,820
		Factory installed smooth drum with shell kit smooth and padfoot scrapers. Scrapers at the front and rear for use with smooth drum on machine or with dealer supplied padded shell kit.		

**FLUIDS**

**HYDRAULIC OIL**

L	362-4940	OIL, HYDR, FACTORY FILLED . . . . .	0	NC
		Cat standard hydraulic oil.		
L	362-4941	OIL, HYD, BIO, FACTORY FILLED . . . . .	0	\$3,320
		FOR USE WITH LANE 3 ONLY This Hydraulic Environmental Ester Synthetic oil is recommended for hydraulic system when environmental compliance is required or desired. Factory filled.		

**INSTRUCTIONS**

L	437-9888	INSTRUCTIONS, NA PLATFORM . . . . .	0	NC
		ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada). ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS		
L	437-9886	INSTRUCTIONS, NA CAB . . . . .	0	NC
		ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada). ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
<b>ELECTRICAL</b>				
P	355-3059	<b>LIGHTING, WARNING</b> . . . . .	5 0	<b>\$433</b> <b>\$433 NI</b>
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
P	355-3056	<b>LIGHTS, UPGRADED</b> . . . . .	3 0	<b>\$230</b> <b>\$230 NI</b>
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER 4 additional lights for increased nighttime visibility.		
P	355-3062	<b>MODULE, RECORDING, STD FREQ</b> . . . . .	0 26	<b>\$6,500</b> <b>\$6,500 NI</b>
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory or field installed fixed frequency recording module required in France. ONLY FOR USE WITH: 355-3542 FREQUENCY, FIXED and 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		
P	355-3064	<b>MODULE, RECORDING, VARIABLE</b> . . . . .	0 31	<b>\$6,500</b> <b>\$6,500 NI</b>
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory or field installed variable frequency recording module required in France. ONLY FOR USE WITH: 355-3541 FREQUENCY, VARIABLE and 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		
<b>OPERATOR ENVIRONMENT</b>				
P	354-5413	<b>MIRRORS, REARVIEW, EXTERNAL</b> . . . . .	10 0	<b>\$316</b> <b>\$316 NI</b>
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two externally mounted rear-view mirrors. ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS		
P	107-4643	<b>MIRRORS, REARVIEW, INTERNAL</b> . . . . .	10 0	<b>\$214</b> <b>\$214 NI</b>
		Includes two rear-view mirrors mounted inside the cab. ALSO AVAILABLE ON A MISCELLANEOUS ORDER ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		
P	204-4390	<b>SUN SCREEN</b> . . . . .	2 2	<b>\$337</b> <b>\$337 NI</b>
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides pull-down sunscreen for rear window, reduces heat and glare. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		
P	107-4641	<b>SUN VISOR, FRONT</b> . . . . .	2 0	<b>\$79</b> <b>\$79 NI</b>
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Tip-down tinted sun visor for front window, reduces heat and glare. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**TECHNOLOGY PRODUCTS**

**CAT COMPACTION CONTROL - MAP**

This factory designed and integrated mapping system upgrades your CAT COMPACTION CONTROL - MEASURE technology by tying a GPS location to your measurement. Mapping allows for full documentation of the compaction process including compaction measurement, pass count and more. This SBAS accuracy level system requires no off-board infrastructure as long as you have access to regionally available satellite systems. For a higher accuracy solution, order the slope sensor below (for accelerometer sensor system) and consult your Dealer Technology Representative to order the necessary base station, data radio and higher accuracy option key for a RTK solution.

L	375-1612	MAPPING, GNSS . . . . .	45	\$10,430
		CB460 Display (17.8 cm/7.0 in), MS952 antenna/receiver. ONLY FOR USE WITH: 435-8035 PLATFORM ROPS/FOPS and 441-6674 SENSOR, DRIVE POWER or 441-6676 SENSOR, ACCELEROMETER or 435-8012 SENSOR, DRIVE POWER AND ACCEL		
L	375-1607	MAPPING, GNSS . . . . .	45	\$10,430
		CB460 Display (17.8 cm/7.0 in), MS952 antenna/receiver. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C and 441-6674 SENSOR, DRIVE POWER or 441-6676 SENSOR, ACCELEROMETER or 435-8012 SENSOR, DRIVE POWER AND ACCEL		
P	441-6683	SENSOR, ANGLE, HIGH-ACCURACY . . . . .	12 0	\$475 \$475 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Continental slope sensor ONLY FOR USE WITH: MAPPING, GNSS and 441-6676 SENSOR, ACCELEROMETER		

**CAT COMPACTION CONTROL - CONNECT**

CONNECT technology upgrades your mapping system to enable communication of key compaction data via local wireless and/or cellular data networks. This adds 3 important capabilities to your Compaction Control System. First, it allows the data to be sent via the cloud for off-site access without the need to physically offboard the data via USB. Second, it allows multiple machines working in the same location to wirelessly transfer and share live compaction data - otherwise known as Machine to Machine communication. Lastly, it gives the ability to obtain correction signals for higher accuracy mapping (RTK) from Virtual Reference Stations if available in your area. Contact your local SITECH dealer and wireless data carrier for additional support and cellular data packages.

L	569-8583	MACHINE CONNECTIVITY, SNM941 . . . . .	0	\$3,615
		SIM card enabled CDMA or GSM network with built in WIFI. ONLY FOR USE WITH: 375-1612 MAPPING, GNSS 375-1607 MAPPING, GNSS		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**OTHER ATTACHMENTS**

**GUARDS**

P	355-2660	GUARD, TRANSMISSION . . . . .	44 0	\$1,130 \$1,035 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides protection for the rear axle, hydraulic drive motor and hose fittings.		

**FACTORY SOURCED KITS**

P	526-2112	MULTI-MODEL SHELL KIT,OVAL,FLD . . . . .	0	\$18,020 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Kit for dealer installed oval padfoot shell halves with padfoot scrapers at the front and rear of the drum. Can be used on the CS54B, CS56B, CS64B, CS66B, CS68B, CS74B, and CS76B machines.		
P	416-1351	SHELL KIT, SQR, PADFOOT, FLD . . . . .	3,235	\$18,020 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Kit for dealer installed square padfoot shell halves with padfoot scrapers at front and rear of the drum.		
P	491-6770	SCRAPER, POLYURETHANE FLD . . . . .	492	\$2,590 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Non-installed two flexible, contacting scrapers blades with ISO-mounts for the front and rear of the smooth drum.		
P	483-5926	PRINTER PORT WIRING KIT, CAB . . . . .	0	\$406 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes wiring kit only for printer (dealer installed) using on a machine with a mapping system. To be used with Cab, ROPS/FOPS machine.		
P	483-6357	PRINTER PORT WIRING KIT, PLFM . . . . .	0	\$406 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes wiring kit only for printer (dealer installed) used on a machine with a mapping system. To be used with Platform, ROPS/FOPS machine.		

**DOCUMENTATION**

**CERTIFICATES**

P	0P-1870	CERTIFICATE OF ORIGIN . . . . .	0	NC
---	---------	---------------------------------	---	----

**PACKING**

	0P-0210	PACK, DOMESTIC TRUCK . . . . .	0	NC
--	---------	--------------------------------	---	----

---

USE	REF NO.	<b>LANE 2 / 3 OPTIONAL</b>	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------------	--------------------	-------------------------

---

**PACKING (CONT.)**

0P-3651	PACKING, MISC MATERIAL . . . . .	0		<b>NC</b>
	No charge for packing. Applicable freight charges may apply.			