

CS64B VIBRATORY COMPACTOR
MINNEAPOLIS, MN, USA (SAP)

Ship Weight
lbs

LIST PRICE
AT DEALER

Standard Equipment:

POWERTRAIN

CAT C4.4 inline four cylinder, turbo-charged diesel engine with glow-plug heater
Dual element air cleaner
Fuel filter/water separator/electronic priming pump and water indicator
Three-speed throttle switch including ECOMODE
Dual propel pumps - 1 for drum and 1 for tires
Dual braking systems (service & parking, drum only)
Two-speed hydrostatic transmission
Limited slip differential

ELECTRICAL

24-volt starting and charging system alternator
(2) Maintenance free batteries - 750 CCA
Halogen working lights - canopy mounted (2 front-facing and 2 rear-facing)
Backup alarm and forward warning horn
Product link ready
Beacon ready

OPERATOR ENVIRONMENT

ROPS/FOPS platform
Four heavy-duty isolation mounts
Platform handrails/guardrails
Power steering
Adjustable tilt-steering column
Adjustable, rotating suspension seat
Retractable seat belt
Rear view camera with display
Adjustable, padded arm rest for propel lever operation
On-board display with audible warning alarm and interface for:
-hydraulic oil temperature gauge,
-engine oil pressure gauge,
-engine coolant temperature gauge
-alternator charge,
-fuel level gauge,
-service hour meter,
-engine RPM
-ground speed, vibe speed
-fuel rate gauge
-engine load gauge
-basic compaction measurement
Lockable, vandalism guard for on-board display
12-volt power point

COOLING

Premixed 50% concentration of extended life coolant with freeze protection to -37C (-35F)

DRUMS

Smooth drum
2134 mm (84") wide x 1534 mm (60.4") diameter
Dual amplitude with single frequency
Dual, pod-style eccentric weight housings
Front adjustable steel scraper

OTHER STANDARD EQUIPMENT

Locking composite engine enclosure
Sealed-for-life hitch bearings
Sight gauges:
-coolant level
-hydraulic oil level
Hydraulic tank locking cap
Articulated frame with safety lock
Transport tie-down and lift points
Fuel tank with lockable cap
Quick connect hydraulic pressure test ports
SOS ports:
-engine
-hydraulic
-coolant
Universal bumper

CS64B VIBRATORY COMPACTOR
MINNEAPOLIS, MN, USA (SAP)

Ship Weight
lbs

LIST PRICE
AT DEALER

**Lane 2 is reserved for the Base Order Management Program.
Please use Lane 2 when placing orders that are part of the
Base Order Management Program.**

433-1612	CS64B VIBRATORY COMPACTOR 0 LANE 2 - AVAILABLE FROM MINNEAPOLIS FACTORY LANE 3 - AVAILABLE FROM MINNEAPOLIS FACTORY	\$174,900
0P-2715	CS64B MISC MATL 0 AVAILABLE FROM MINNEAPOLIS FACTORY Only reference numbers that have the text "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order.	NC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER	0	NC

POWERTRAIN

ENGINE

L	420-9150	ENGINE, TIER 4F/STAGE 4	0	NC
		U.S. EPA Tier 4 Final/EU Stage IV equivalent engine.		

ENCLOSURES

L	479-9014	SCREEN, STANDARD	7	NC
		Fixed (not openable) screen at rear, right side of the engine compartment.		
L	479-9015	FUEL SYSTEM, DOOR	23	\$365
		Hinged and CAT key lockable door to access fuel fill without opening enclosure.		

OPERATOR ENVIRONMENT

OPERATOR STATIONS

L	435-8035	PLATFORM, ROPS/FOPS	1,262	NC
		Open platform with handrails, ROPS/FOPS canopy and working lights.		
L	435-8038	CAB, ROPS/FOPS WITH HEATER	1,620	\$17,080
		FOR USE WITH LANE 3 ONLY Two front-facing and two rear-facing working lights, external rear-view mirrors, heater & defroster, and wet-arm wipers/washers (front and rear). Cab is Radio Ready, including hardware, wiring, voltage converter and 12-volt power point. Wiring only - Radio and Speakers not included.		
L	435-8036	CAB, ROPS/FOPS WITH A/C	1,700	\$22,810
		Two front-facing and two rear-facing working lights, external rear-view mirrors, air conditioner, heater & defroster, and wet-arm wipers/washers (front and rear). Cab is Radio Ready, including hardware, wiring, voltage converter and 12-volt power point. Wiring only - Radio and Speakers not included.		

SEATS

L	356-1226	SEAT, VINYL	150	NC
		Standard rotating vinyl covered suspension seat.		
L	356-1227	SEAT, CLOTH	150	\$314
		Standard rotating cloth covered suspension seat. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		
L	356-1229	SEAT, CLOTH, DELUXE	158	\$545
		Deluxe rotating cloth seat with head rest, air suspension and additional adjustment. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

SEAT BELTS

L	382-9003	SEAT BELT, 2"	2	NC
L	387-1801	SEAT BELT, 3"	2	\$146

OPERATOR LANGUAGES

L	477-9990	LANGUAGES, OPTION 1	0	NC
Includes standard languages (English, Spanish, French, German, Italian, Polish, Portuguese, Turkish, and Korean) for machine operation and control.				

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact you Caterpillar marketing representative with questions.

L	454-5453	PRODUCT LINK, SATELLITE PL631	9	\$446
Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.				
L	454-5454	PRODUCT LINK, CELLULAR PL641	9	NC
Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.				

PRODUCT LINK INSTALLATION

L	454-0250	INSTALLATION, ROPS/FOPS	8	NC
Factory installation of PL on machine with ROPS/FOPS canopy. ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS				
L	454-0249	INSTALLATION, CAB	8	NC
Factory installation of PL on machines with cab. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C				

CAT COMPACTION CONTROL - MEASURE

Base/Entry level compaction measurement systems that detect changes in soil stiffness and provide the operator with real time compaction information on the standard machine display.

L	444-5931	NO COMPACTION SENSOR	0	NC
No Sensors.				

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

CAT COMPACTION CONTROL - MEASURE (Cont.)

L	441-6674	SENSOR, DRIVE POWER 5 Proprietary Caterpillar technology that directly measures soil stiffness via material deflection (rolling resistance). Includes Sensor, Angle, High-Accuracy.		\$3,960
L	441-6676	SENSOR, ACCELEROMETER. 15 Traditional soil stiffness measurement providing CMV values resulting from vibration energy imparted to the soil. Sensor, Accel. will not work with Padfoot Shell Kit operation / Will only work with smooth drum operation.		\$6,440
L	435-8012	SENSOR, DRIVE POWER AND ACCEL 20 Traditional soil stiffness measurement providing MDP and CMV values resulting from vibration energy imparted to the soil. Includes Sensor, Angle, High-Accuracy.		\$8,150

TIRES, RIMS, AND WHEELS

L	203-4717	TIRES, 23,1-26 TI 8PR 935 8-ply flotation (diamond tread) tires and rims with liquid ballast.		\$2,050
L	203-4718	TIRE, TRACTION 935 23.1 x 26 8 ply traction (lug tread) tires and rims with liquid ballast. Typically for use with padfoot style drum.		\$3,420

DRUMS

VIBRATORY SYSTEMS

L	355-3542	FREQUENCY, FIXED 0 Single 31.9 Hz (1914 vpm) frequency with high and low amplitude.		NC
L	355-3541	FREQUENCY, VARIABLE 0 Frequency dial that electronically controls the displacement of the vibratory pump. Frequency range from 23.3-31.9 Hz (1400-1914 vpm).		\$2,465

SCRAPER SYSTEM

L	360-0493	SCRAPER, STEEL, FRONT 132 Standard smooth drum with one steel scraper at the front of the smooth drum.		NC
L	365-9332	SCRAPER, STEEL, FRONT + REAR. 1,074 Standard smooth drum with flat steel scrapers at the front and rear of the smooth drum.		\$1,945
L	365-9333	SCRAPER, POLYURETHANE 1,085 Two flexible, contacting scrapers blades iso-mounted at the front and rear of the smooth drum.		\$2,590
L	365-9334	DRUM, SHELL KIT 7,132 Factory installed oval padfoot shell halves with padfoot scrapers at the front and rear of the drum.		\$18,020
L	439-0778	SHELL KIT, SQR, PADFOOT 4,297 Factory installed square padfoot shell halves with padfoot scrapers at front and rear of the drum.		\$18,020

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

DRUMS (CONT.)

SCRAPER SYSTEM (Cont.)

L	472-2056	SCRAPER, SHELL KIT READY	970	\$6,820
		Factory installed smooth drum with shell kit smooth and padfoot scrapers. Scrapers at the front and rear for use with smooth drum on machine or with dealer supplied padded shell kit.		

FLUIDS

HYDRAULIC OIL

L	362-4940	OIL, HYDR, FACTORY FILLED	0	NC
		Cat standard hydraulic oil.		
L	362-4941	OIL, HYD, BIO, FACTORY FILLED	0	\$3,320
		FOR USE WITH LANE 3 ONLY This Hydraulic Environmental Ester Synthetic oil is recommended for hydraulic system when environmental compliance is required or desired. Factory filled.		

INSTRUCTIONS

L	437-9886	INSTRUCTIONS, NA CAB	0	NC
		ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada). ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		
L	437-9888	INSTRUCTIONS, NA PLATFORM	0	NC
		ANSI picto warning decals using symbols plus the word "WARNING" as required for North America (except Quebec, Canada). ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
ELECTRICAL				
P	355-3059	LIGHTING, WARNING	5 0	\$433 \$433 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
P	355-3056	LIGHTS, UPGRADED	3 0	\$230 \$230 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER 4 additional lights for increased nighttime visibility.		
P	355-3062	MODULE, RECORDING, STD FREQ	0 26	\$6,500 \$6,500 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory or Field installed fixed frequency recording module required in France. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C and 355-3542 FREQUENCY, FIXED		
P	355-3064	MODULE, RECORDING, VARIABLE	0 31	\$6,500 \$6,500 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory or field installed variable frequency recording module required in France. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C and 355-3541 FREQUENCY, VARIABLE		
OPERATOR ENVIRONMENT				
P	354-5413	MIRRORS, REARVIEW, EXTERNAL	10 0	\$316 \$316 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two externally mounted rear-view mirrors. ONLY FOR USE WITH: 435-8035 PLATFORM, ROPS/FOPS		
P	107-4643	MIRRORS, REARVIEW, INTERNAL	10 0	\$214 \$214 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two rear-view mirrors mounted inside the cab. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		
P	204-4390	SUN SCREEN	2 2	\$337 \$337 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides pull-down sunscreen for rear window, reduces heat and glare. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		
P	107-4641	SUN VISOR, FRONT	2 0	\$79 \$79 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Tip-down tinted sun visor for front window, reduces heat and glare. ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------------	--------------------	-------------------------

TECHNOLOGY PRODUCTS

CAT COMPACTION CONTROL - MAP

This factory designed and integrated mapping system upgrades your CAT COMPACTION CONTROL - MEASURE technology by tying a GPS location to your measurement. Mapping allows for full documentation of the compaction process including compaction measurement, pass count and more. This SBAS accuracy level system requires no off-board infrastructure as long as you have access to regionally available satellite systems. For a higher accuracy solution, order the slope sensor below (for accelerometer sensor system) and consult your Dealer Technology Representative to order the necessary base station, data radio and higher accuracy option key for a RTK solution.

L	375-1612	MAPPING, GNSS	45	\$10,430
		CB460 Display (17.8 cm/7.0 in), MS952 antenna/receiver.		
		ONLY FOR USE WITH: 435-8035 PLATFORM ROPS/FOPS and 441-6674 SENSOR, DRIVE POWER or 441-6676 SENSOR, ACCELEROMETER or 435-8012 SENSOR, DRIVE POWER AND ACCEL		
L	375-1607	MAPPING, GNSS	45	\$10,430
		CB460 Display (17.8 cm/7.0 in), MS952 antenna/receiver.		
		ONLY FOR USE WITH: 435-8038 CAB, ROPS/FOPS WITH HEATER or 435-8036 CAB, ROPS/FOPS WITH A/C and 441-6674 SENSOR, DRIVE POWER or 441-6676 SENSOR, ACCELEROMETER or 435-8012 SENSOR, DRIVE POWER AND ACCEL		
P	441-6683	SENSOR, ANGLE, HIGH-ACCURACY	12 0	\$475 \$475 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER		
		Continental slope sensor is selected.		
		ONLY FOR USE WITH: MAPPING, GNSS 441-6676 SENSOR, ACCELEROMETER		

CAT COMPACTION CONTROL - CONNECT

CONNECT technology upgrades your mapping system to enable communication of key compaction data via local wireless and/or cellular data networks. This adds 3 important capabilities to your Compaction Control System. First, it allows the data to be sent via the cloud for off-site access without the need to physically offboard the data via USB. Second, it allows multiple machines working in the same location to wirelessly transfer and share live compaction data - otherwise known as Machine to Machine communication. Lastly, it gives the ability to obtain correction signals for higher accuracy mapping (RTK) from Virtual Reference Stations if available in your area. Contact your local SITECH dealer and wireless data carrier for additional support and cellular data packages.

L	569-8583	MACHINE CONNECTIVITY, SNM941	0	\$3,615
		SIM card enabled CDMA or GSM network with built in WIFI.		
		ONLY FOR USE WITH: 375-1612 MAPPING, GNSS 375-1607 MAPPING, GNSS		

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS

GUARDS

P	355-2660	GUARD, TRANSMISSION	44 0	\$1,130 \$1,035 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides protection for the rear axle, hydraulic drive motor and hose fittings.		

FACTORY SOURCED KITS

P	526-2112	MULTI-MODEL SHELL KIT,OVAL,FLD	0	\$18,020 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Kit for dealer installed oval padfoot shell halves with padfoot scrapers at the front and rear of the drum. Can be used on the CS54B, CS56B, CS64B, CS66B, CS68B, CS74B, and CS76B machines.		
P	416-1355	SHELL KIT, SQR, PADFOOT, FLD	4,303	\$18,020 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Field installed square padfoot shell halves with padfoot scrapers at front and rear.		
P	491-6771	SCRAPER, POLYURETHANE FLD	492	\$2,590 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Non-installed two flexible, contacting scrapers blades with ISO-mounts for the front and rear of the smooth drum.		
P	483-5926	PRINTER PORT WIRING KIT, CAB	0	\$406 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes wiring kit only for printer (dealer installed) using on a machine with a mapping system. To be used with Cab, ROPS/FOPS machine.		
P	483-6357	PRINTER PORT WIRING KIT, PLFM	0	\$406 NI
		FOR USE WITH LANE 3 ONLY ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes wiring kit only for printer (dealer installed) used on a machine with a mapping system. To be used with Platform, ROPS/FOPS machine.		

DOCUMENTATION

CERTIFICATES

P	0P-1870	CERTIFICATE OF ORIGIN	0	NC
---	---------	---------------------------------	---	----

PACKING

	0P-0210	PACK, DOMESTIC TRUCK	0	NC
--	---------	--------------------------------	---	----

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	----------------------------	--------------------	-------------------------

PACKING (CONT.)

0P-3651	PACKING, MISC MATERIAL 0 No charge for packing. Applicable freight charges may apply.	NC
---------	--	-----------