



2020

**JCB Teleskid
3TS-8T
Compact Track Loader**



**JCB, Inc. North American
Machine Price List
In U.S. Dollars
Effective: January 2, 2020**

Changes to specifications and/or prices may occur.
Please refer to the product manager for updates.



U.S. Dollar Price Page

3TS-8T Teleskid

Effective: January 2, 2020



F.O.B. Savannah, GA

STANDARD EQUIPMENT

ENGINE	4.4L (268CID) 74 SAE Gross hp, JCB Ecomax engine, centrifugal dry type dual stage air cleaner. Fuel filter with water separator, 1000 CCA battery; variable speed hydraulically driven fan.
TRANSMISSION	EH (Electo-Hydraulic) Controls with hydrostatic transmission. Standard two (2) speed transmission is provides a low range of 0 - 6.8 mph and a high range of 0 - 7.8 mph in both forward and reverse. Standard Creep speed provides operation from 0 to 1/2 of full speed for special applications.
RUBBER TRACKS	Fitted with 17.7" wide tracks provide a machine width of 78" and a ground bearing pressure of 5.0 psi.
BRAKES	Machine braking provided through the hydrostatic transmission. Parking brake consists of multiple disc, oil immersed, spring applied hydraulic release that provides a fail safe with the engine off. Electrically activated through a switch on the instrument panel or by raising seat bar.
ELECTRICAL	Meets IP69 (external) IP67 (internal) water ingress standard. Worklights, 2 Front and 1 Rear, Reverse Alarm, Horn, and 12V Accessory Socket.
INSTRUMENTS	Audible and visual warning systems, right and left side mounted instrument panels. Standard electronic throttle control with optional foot throttle.
CAB OR CANOPY	SAE certified ROPS/FOPS, left side entry. Units are equipped with a heated air suspension seat with adjustable arm pods, an operator restraint interlock for drive and loader functions, enclosed Heated Cab with Air Conditioning and sliding window in left door. Right Hand glass standard on all units. LiveLink llite standard on all units.
HYDRAULICS	24gpm @ 3335psi standard flow and 33gpm @ 3335psi on standard equipment.
LOADER	Rated Operating Capacity of 3600 lbs, Radial Lift Loader Design provides a radial lift path, and with a two stage telescopic boom, a hinge pin height of 159" (13'-3") and 96" (8') of forward reach. Auxiliary hydraulic circuit and high flow are standard for operation of hydraulic powered attachments. All machines are equipped with: Automatic Attachment Leveling System, Smooth Ride System (SRS), a Sealed Electric Power Quick Hitch and Hydraulic Float.



U.S. Dollar Price Page

3TS-8T Teleskid

Effective: January 2, 2020



F.O.B. Savannah, GA

STANDARD EQUIPMENT CONT.

SERVICEABILITY

Cab tilts forward to provide further access to the hydraulic components. The bucket tilt (crowd) cylinder has been repositioned inside the boom, thereby allowing the cab to be tilted for service access without raising the boom. Rear door provides access to engine bay and daily maintenance and check points.



3TS-8T Teleskid



U.S. Dollar Price Page

Effective: January 2, 2020

F.O.B. Savannah, GA

SECTION I - YELLOW SERIES

If a Package Build machine from Section I will not meet your requirements, please order a machine by selecting one code from each category below. Select Attachments from Section 4 as needed.

JCB cannot normally modify existing factory inventory. Dealers should order and install items from the Dealer Fit Section to change existing machines.

SALES CODE	ITEM	LIST PRICE
8722	JCB 3TS-8T Tier 4 Tracked, Teleskid Telescopic Compact Track Loader	\$74,704
881A325	17.7" (450 mm) Wide Camso Rubber Tracks - provides a machine width of 77.1" for Teleskid 3TS-8T	\$936
881B411	Enclosed Cab Package - Includes A/C, Heater, Heated Air Suspension Seat, Reverse Alarm & Hydraulic Loader Arm Float - For 3TS-8T Tracked Teleskid Compact Track Loader	\$5,313
881C313	JCB EH Controls - 7 way Multi-Function Joysticks with Auxiliary Hydraulics & Attachment Harness. Required with High Flow Hydraulics for 3TS-8T & W Teleskid Telescopic SSL & CTL	\$1,848
881D300	No Factory Fit Attachment Option. See List of available buckets and pallet forks to complete machine build.	\$0
881E702	3TS-8T Tracked Teleskid Value Package - Includes Foot Throttle, Smooth Ride System (SRS), Attachment Leveling System, Power Quick Hitch, 2 Speed. Dual Pattern Controls, Reversing Fan, ISO/H Pattern, Fender Kit, Radio /Speakers, Block Heater and American Language Pack	\$7,233
881F317	Dual Standard Auxiliary & High Flow Hydraulic System for 3TS-8T & W Teleskid SSL & CTL	\$1,437
LIST PRICE		\$91,470

*NOTE: Canopy option 881B412 \$ 1,042



3TS-8T Teleskid



U.S. Dollar Price Page

Effective: January 2, 2020

F.O.B. Savannah, GA

SECTION 4 - ATTACHMENTS - NEW FACTORY BUILT ORDERS

Select Attachments as desired, within limitations if indicated.

SALES CODE	CARRIAGES	LIST PRICE
No Bucket		
881D300	No Factory Fit Attachment Option. See List of available buckets and pallet forks to complete machine build.	\$0
GP Buckets		
881D303	GP Bucket - 78" - 16.7 cu-ft	\$1,307
881D304	GP Bucket - 84" - 18.1 cu-ft	\$1,375
Landscape Buckets		
881D307	Landscape Bucket - 78" - 20.9 cu-ft	\$1,871
881D308	Landscape Bucket - 84" - 22.7 cu-ft	\$1,970