

BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NPR-XD Crew Cab Chassis, NZ4 176", 16,000 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Selected Model and Options

| Code | Description | Weight | MSRP |
|---------|--|----------|-------------|
| Model | | | |
| NZ4 | NPR-XD Crew Cab Chassis 176 | | \$62,088.00 |
| 54 | White, In rail fuel tank with power windows, power door locks and air conditioning | | \$0.00 |
| Options | | | |
| 099 | 4.777 | 0.0 lbs. | Inc. |
| 54 | White, In rail fuel tank with power windows, power door locks and air conditioning | 0.0 lbs. | Inc. |
| 8RP | AM/FM/CD radio with Aux input/USB port and Bluetooth RPO | 0.0 lbs. | Inc. |
| AQB | Driver seat is reclining high back. Two single occupant fold down seats with tray backs. | 0.0 lbs. | Inc. |
| C60 | Air conditioner | 0.0 lbs. | Inc. |
| I1B | 4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ftlb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level. | 0.0 lbs. | Inc. |
| I1W | Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343, | 0.0 lbs. | Inc. |
| I2C | 140 AMP. with integral regulator. | 0.0 lbs. | Inc. |
| 136 | R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings. | 0.0 lbs. | Inc. |
| I5H | LRR (low rolling resistance) | 0.0 lbs. | Inc. |
| 19K | 14,308 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers. | 0.0 lbs. | Inc. |
| IB9 | 19.5" x 6", 6-hole disc, painted white | 0.0 lbs. | Inc. |
| IC1 | 19.5" x 6", 6-hole disc, painted white | 0.0 lbs. | Inc. |
| ID2 | "I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1. | 0.0 lbs. | Inc. |
| ID8 | 8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar | 0.0 lbs. | Inc. |
| IF9 | 30 gal. rectangular fuel tank. Mounted between frame rail through the rail fuel fill. Fuel water separator with dash mounted warning light. | 0.0 lbs. | Inc. |
| IH7 | 176 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in3 RBM 523,160 lb./ft./in. per rail. | 0.0 lbs. | Inc. |

Current report content is based on data as of 2019-02-12 10:52:51. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NPR-XD Crew Cab Chassis, NZ4 176", 16,000 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Selected Model and Options

| Code | Description | Weight | MSRP | |
|---------|--|----------|-------------|--|
| ILO | Yes | 0.0 lbs. | Inc. | |
| IQ6 | Standard Floor Mats | 0.0 lbs. | Inc. | |
| IR8 | Dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self- adjust outboard mounted drum rear. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard. 4 channel anti- lock brake system. | 0.0 lbs. | Inc. | |
| IX1 | Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts | 0.0 lbs. | Inc. | |
| IX2 | Rear body dome lamp switch | 0.1 lbs. | Inc. | |
| IX7 | Single horizontal with DPF/SCR exhaust system | 0.0 lbs. | Inc. | |
| K40 | Butterfly valve type exhaust brake | 0.0 lbs. | Inc. | |
| KNX | Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID). | 0.0 lbs. | Inc. | |
| XTN/R3M | 225/70R19.5F (12 ply) tubeless Radial, all season | 0.0 lbs. | Inc. | |
| YTN/S3M | 225/70R19.5F (12 ply) tubeless Radial, all season tread. | 0.0 lbs. | Inc. | |
| Totals | | | | |
| | Base Price | | \$62,088.00 | |
| | Destination Charge | | \$1,125.00 | |
| | DEF Fill Charge | | \$10.00 | |
| | Total Options Price | | \$ | |
| | Tire Weight Tax | | \$7.94 | |
| | Total | | \$63,230.94 | |

Current report content is based on data as of 2019-02-12 10:52:51. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NPR-XD Crew Cab Chassis, NZ4 176", 16,000 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Optional Equipment

| Code | Description | Weight | MSRP |
|--------------------|--|------------|------------|
| Additional Options | | - | |
| IF6 | Fire Extinguisher and Triangle Kit mounted in rear organizer on standard cab and under rear seat on crew cab | 19.0 lbs. | \$88.00 |
| IY4 | Delete radio | -3.0 lbs. | (\$136.00) |
| I9H | Heated dual remote control mirrors (15" head) | 3.0 lbs. | \$496.00 |
| IS0 | Heated Mirrors | 1.0 lbs. | \$104.00 |
| IU2 | Mirror Bracket for 102" wide body | 1.0 lbs. | \$136.00 |
| UZF | Back up alarm | 1.0 lbs. | \$112.00 |
| V22 | Chrome Grille | 1.0 lbs. | \$400.00 |
| IG3 | Engine oil pan heater (120v 300w) | 2.0 lbs. | \$172.00 |
| I4H | CAN interface converter | 1.1 lbs. | \$332.00 |
| IH2 | Engine emergency shutdown system HWT, LWL, LOP | 0.0 lbs. | \$100.00 |
| IY9 | Engine idle shutdown (timer set at 3 minutes for engine shutdown) | 0.0 lbs. | \$100.00 |
| 19A | Engine idle shutdown (timer set at 5 minutes for engine shutdown) | 0.0 lbs. | \$100.0 |
| IL9 | PTO enable switch and engine idle up switch recommended for PTO and idle applications only | 0.1 lbs. | \$48.0 |
| I4K | Keyless entry system including two keypads as standard | 1.0 lbs. | \$316.0 |
| 16K | Lockable DEF fill cap | 0.3 lbs. | \$80.0 |
| I1L | Speed limited to 58 MPH | 0.0 lbs. | \$100.0 |
| 12L | Speed limited to 65 MPH | 0.0 lbs. | \$100.0 |
| 14L | Speed limited to 70 MPH | 0.0 lbs. | \$100.0 |
| I3L | Speed limited to 68 MPH | 0.0 lbs. | \$100.0 |
| I5L | Locking DEF cap (all keyed alike on multiple chassis ordered together) | 0.3 lbs. | \$80.0 |
| 17L | High visibility seat belt (red color, driver seat only) | 0.0 lbs. | \$92.0 |
| 18L | High visibility seat belt (red color, driver and RH passenger seat) | 0.0 lbs. | \$184.0 |
| IOM | Cold weather package (block heater and heated fuel filter) | 1.0 lbs. | \$236.0 |
| IV9 | Seat Covers crew cab | 11.0 lbs. | \$520.0 |
| IK9 | 33 Gallon Additional Diesel Fuel Tank (Available on 176" WB std. or crew cab in rail tank only) | 360.0 lbs. | \$1,940.0 |
| Extended Warranty | | | |
| WFF | 60 months / 150,000 Miles | 0.0 lbs. | \$1,550.0 |
| WFG | 60 months / 200,000 Miles | 0.0 lbs. | \$1,875.0 |
| WFI | 60 months / 250,000 Miles | 0.0 lbs. | \$2,600.0 |
| WAG | 60 months / 200,000 Miles PLUS | 0.0 lbs. | \$2,850.0 |

Current report content is based on data as of 2019-02-12 10:52:51. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.