



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NQR Cab Chassis, NR3 150", 17,950 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Selected Model and Options

Code	Description	Weight	MSRP
Model			
NR3	NQR Cab Chassis 150		\$60,028.00
54	White, In rail fuel tank with power windows, power door locks and air conditioning		\$0.00
Options			
098	5.125:1	0.0 lbs.	Inc.
54	White, In rail fuel tank with power windows, power door locks and air conditioning	0.0 lbs.	Inc.
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	0.0 lbs.	Inc.
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	0.0 lbs.	Inc.
C60	Air conditioner	0.0 lbs.	Inc.
I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.	0.0 lbs.	Inc.
I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,	0.0 lbs.	Inc.
I2C	140 AMP. with integral regulator.	0.0 lbs.	Inc.
I5H	LRR (low rolling resistance)	0.0 lbs.	Inc.
IB1	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20in ³ RBM 316,800 lb./ft./in. per rail.	0.0 lbs.	Inc.
IB9	19.5" x 6", 6-hole disc, painted white	0.0 lbs.	Inc.
IC1	19.5" x 6", 6-hole disc, painted white	0.0 lbs.	Inc.
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	0.0 lbs.	Inc.
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	0.0 lbs.	Inc.
ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar	0.0 lbs.	Inc.
ID9	14,550 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers.	0.0 lbs.	Inc.
IF9	30 gal. rectangular fuel tank. Mounted between frame rail through the rail fuel fill. Fuel water separator with dash mounted warning light.	0.0 lbs.	Inc.

Current report content is based on data as of 2019-02-12 10:29:42. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NQR Cab Chassis, NR3 150", 17,950 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Selected Model and Options

Code	Description	Weight	MSRP
IL0	Yes	0.0 lbs.	Inc.
IQ6	Standard Floor Mats	0.0 lbs.	Inc.
IT4	Dual circuit, Hydro-Boost hydraulic brake system with EBD (Electronic Brake Distribution). Mechanical transmission mounted parking brake. Non-asbestos semi metallic linings are standard. Anti-lock brake system	0.0 lbs.	Inc.
IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts	0.0 lbs.	Inc.
IX2	Rear body dome lamp switch	0.1 lbs.	Inc.
IX7	Single horizontal with DPF/SCR exhaust system	0.0 lbs.	Inc.
K40	Butterfly valve type exhaust brake	0.0 lbs.	Inc.
KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).	0.0 lbs.	Inc.
XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season	0.0 lbs.	Inc.
YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.	0.0 lbs.	Inc.
Totals			
	Base Price		\$60,028.00
	Destination Charge		\$1,125.00
	DEF Fill Charge		\$10.00
	Total Options Price		\$
	Tire Weight Tax		\$7.94
	Total		\$61,170.94

Current report content is based on data as of 2019-02-12 10:29:42. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NQR Cab Chassis, NR3 150", 17,950 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Optional Equipment

Code	Description	Weight	MSRP
Road-Ready Body Program			
S11	SUPREME (Van Body) Hardwood Floor / Plywood Sides / Tie Ring, 16' X 96" X 85"	2,724.0 lbs.	\$9,908.00
S42	SUPREME (Van Body) Pine Floor / Plywood Sides / Tie Ring, 16' X 96" X 85"	2,568.0 lbs.	\$9,492.00
SS6	SUPREME (Van Body) Hardwood Floor / Slat Lining, 16' X 96" X 85"	2,741.0 lbs.	\$9,908.00
M11	MORGAN (Van Body) Hardwood Floor / Plywood Lining, 16' X 96" X 85"	2,415.0 lbs.	\$9,196.00
MS6	MORGAN (Van Body) Hardwood Floor / Slat Lining, 16' X 96" X 85"	2,385.0 lbs.	\$9,364.00
M17	MORGAN (Van Body) Hardwood Floor / Plywood Lining, 18' X 96" X 91" (Gate N/A)	2,780.0 lbs.	\$10,784.00
MS8	MORGAN (Van Body) Hardwood Floor / Slat Lining, 18' X 96" X 91" (Gate N/A)	2,790.0 lbs.	\$10,972.00
S17	SUPREME (Van Body) Hardwood Floor / Plywood Sides / Tie Ring, 18' X 96" X 91" (Gate N/A)	2,974.0 lbs.	\$11,428.00
SS8	SUPREME (Van Body) Hardwood Floor / Slat Lining, 18' X 96" X 91" (Gate N/A)	3,167.0 lbs.	\$11,428.00
M21	MORGAN (Van Body) Hardwood Floor / Slat Lining, 16' X 96" X 91"	2,444.0 lbs.	\$9,576.00
M20	MORGAN (Van Body) Hardwood Floor / Plywood Lining, 16' X 96" X 91"	2,511.0 lbs.	\$9,428.00
S20	SUPREME (Van Body) Hardwood Floor / Plywood Sides / Tie Ring, 16' X 96" X 91"	2,793.0 lbs.	\$10,268.00
S19	SUPREME (Van Body) Pine Floor / Plywood Sides / Tie Ring, 16' X 96" X 91"	2,637.0 lbs.	\$9,852.00
S21	SUPREME (Van Body) Hardwood Floor / Slat Lining, 16' X 96" X 91"	2,810.0 lbs.	\$10,268.00
Road-Ready Body Program Options			
IQ9	16' Translucent Roof (Requires S11, S19, S20, S21, S42, or SS6 Supreme body program)	0.0 lbs.	\$192.00
IR3	12' Walk Ramp (Requires S11, S19, S20, S21, S42, or SS6 Supreme body program; N/A with lift gate)	210.0 lbs.	\$1,056.00
I6E	12" X-member Spacing (Requires S11, S19, S20, S21, S42, or SS6 Supreme body program)	56.0 lbs.	\$92.00
I7D	16' Translucent Roof (Requires M11, M20, M21 or MS6 Morgan body program)	-6.0 lbs.	\$108.00
I1E	12' Walk Ramp (Requires M11, M20, M21 or MS6 Morgan body program, N/A with lift gate)	170.0 lbs.	\$1,084.00
I8E	12" X-member Spacing (Requires M11, M20, M21, or MS6 Morgan body program)	72.0 lbs.	\$152.00
I8D	18' Translucent Roof	-6.0 lbs.	\$120.00
I2E	14' Walk Ramp (Requires M17, M18, MS8, or MS9 Morgan body program; N/A with lift gate)	198.0 lbs.	\$1,100.00

Current report content is based on data as of 2019-02-12 10:29:42. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NQR Cab Chassis, NR3 150", 17,950 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Optional Equipment

Code	Description	Weight	MSRP
IR0	18' Translucent Roof	0.0 lbs.	\$220.00
IR4	14' Walk Ramp (Requires S17, S18, SS8, or SS9 Supreme body program, N/A with lift gate)	265.0 lbs.	\$1,152.00
I0P	1 row E-track recess mt. on sides and surface mt. on front (C/L @ 30" above floor) ply 16	60.0 lbs.	\$396.00
I1P	2 rows E-track recess mt. on sides and surface mt. on front (C/L @ 24" & 48" above floor) ply 16	120.0 lbs.	\$784.00
I2P	1 row E-track recess mt. on sides and surface mt. on front (C/L @ 30" above floor)	68.0 lbs.	\$436.00
I3P	2 rows E-track recess mt. on sides and surface mt. on front (C/L @ 24" & 48" above floor)	132.0 lbs.	\$860.00
I7M	1 row E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" above floor) ply 16	54.0 lbs.	\$368.00
I8M	2 rows E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" & 60" above floor) ply 16	108.0 lbs.	\$724.00
I9M	1 row E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" above floor)	60.0 lbs.	\$404.00
I0O	2 rows E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" & 60" above floor)	120.0 lbs.	\$596.00
I7N	1 row E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" above floor) slat 16	54.0 lbs.	\$276.00
I8N	2 rows E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" & 60" above floor) slat 16	108.0 lbs.	\$544.00
I9N	1 row E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" above floor)	60.0 lbs.	\$304.00
I0N	2 rows E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" & 60" above floor)	120.0 lbs.	\$800.00
I6O	City PAK Spec 18, 42" single swing Curbside door with barlock with (1) grab and 1- step stirrup, Location: 58.75" back from the outside front wall to leading edge of door hinged forward, Smooth Steel Scuff sides and front 14 ga. x 12", LED STT lights mounted on rear corner posts in lieu of using STD Incandescent light that come with chassis, (2) rows E-Track recess mounted on sides and surfaced mounted on front wall located 30" & 60" up from the floor to C/L in addition to rope ties	266.0 lbs.	\$2,484.00
I4U	14 ga. x 12" Smooth Steel Scuff sides and front	105.0 lbs.	\$504.00
I5U	14 ga. x 12" Smooth Steel Scuff sides and front	119.0 lbs.	\$532.00
I0U	42" single swing Curbside door with anti-rack bar lock with (1) grab and 1-step stirrup	0.0 lbs.	\$964.00

Current report content is based on data as of 2019-02-12 10:29:42. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NQR Cab Chassis, NR3 150", 17,950 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Optional Equipment

Code	Description	Weight	MSRP
I1U	LED STT & BU lights mounted on rear corner posts in lieu STD Incandescent lights that come with chassis	0.0 lbs.	\$376.00
I1Q	Maxon TE-20L Tuck-A-Way bolt-on liftgate with galvanized finish, Capacity: 2,000 lbs., Gate weight: 570 lbs., Platform size: 36 inches x 80 inches galvanized steel wedge platform, Steel Step Bumpers: one (1) each side with 13.5-inch solid rubber pads (In lieu of STD program body Full Width One Way Step bumper), Two (2) Grab Handles at rear in lieu of one (1) standard grab handle on curb side, Cut off switch in cab, LED STT & BU lights installed on the rear corner posts in lieu of standard Isuzu tail lights (Requires M10, M11, M17, M18, M20, M21, MS4, MS6, MS8, or MS9 Morgan body program; N/A with walk ramp)	585.0 lbs.	\$3,632.00
I0Q	MAXON TE-20L Tuck-A-Way bolt-on liftgate galvanized finish, Capacity: 2000 lbs. (Gate weight: 570 lbs.), Platform size: 36 inches x 80 inches galvanized steel wedge platform, Steel Step Bumpers: one (1) each side with 13.5-inch solid rubber pads (In lieu of STD program body Full Width One Way Step bumper), Two (2) Grab Handles at rear in lieu of one (1) standard grab handle on curb side, Cut off switch in cab, LED SST & BU lights are installed on the rear corner posts in lieu of the standard Isuzu tail lights (Requires S37, S10, S11, S17, S18, S19, S20, S21, S40, S41, S42, SS2, SS4, SS6, SS8, or SS9 Supreme body program; N/A with walk ramp)	585.0 lbs.	\$3,832.00
I2W	LED SST and BU lights in lieu of incandescent chassis tail lights	0.0 lbs.	\$400.00

Additional Options

IF6	Fire Extinguisher and Triangle Kit mounted in rear organizer on standard cab and under rear seat on crew cab	19.0 lbs.	\$88.00
IY4	Delete radio	-3.0 lbs.	(\$136.00)
I9H	Heated dual remote control mirrors (15" head)	3.0 lbs.	\$496.00
IS0	Heated Mirrors	1.0 lbs.	\$104.00
IU2	Mirror Bracket for 102" wide body	1.0 lbs.	\$136.00
UZF	Back up alarm	1.0 lbs.	\$112.00
V22	Chrome Grille	1.0 lbs.	\$400.00
IG3	Engine oil pan heater (120v 300w)	2.0 lbs.	\$172.00
I4H	CAN interface converter	1.1 lbs.	\$332.00
IH2	Engine emergency shutdown system HWT, LWL, LOP	0.0 lbs.	\$100.00

Current report content is based on data as of 2019-02-12 10:29:42. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NQR Cab Chassis, NR3 150", 17,950 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Optional Equipment

Code	Description	Weight	MSRP
IY9	Engine idle shutdown (timer set at 3 minutes for engine shutdown)	0.0 lbs.	\$100.00
I9A	Engine idle shutdown (timer set at 5 minutes for engine shutdown)	0.0 lbs.	\$100.00
IL9	PTO enable switch and engine idle up switch recommended for PTO and idle applications only	0.1 lbs.	\$48.00
I4K	Keyless entry system including two keypads as standard	1.0 lbs.	\$316.00
I5K	Suspension Drivers Seat (not available on crew cab chassis)	18.0 lbs.	\$668.00
I6K	Lockable DEF fill cap	0.3 lbs.	\$80.00
I1L	Speed limited to 58 MPH	0.0 lbs.	\$100.00
I2L	Speed limited to 65 MPH	0.0 lbs.	\$100.00
I4L	Speed limited to 70 MPH	0.0 lbs.	\$100.00
I3L	Speed limited to 68 MPH	0.0 lbs.	\$100.00
I5L	Locking DEF cap (all keyed alike on multiple chassis ordered together)	0.3 lbs.	\$80.00
I7L	High visibility seat belt (red color, driver seat only)	0.0 lbs.	\$92.00
I8L	High visibility seat belt (red color, driver and RH passenger seat)	0.0 lbs.	\$184.00
I0M	Cold weather package (block heater and heated fuel filter)	1.0 lbs.	\$236.00
IF4	Air Deflector roof mounted (not available in Crew Cab)	64.0 lbs.	\$996.00
IV8	Seat Covers standard cab	6.0 lbs.	\$280.00
I0A	Cross rail horizontal DPF/SCR with vertical exhaust (Available only with in rail fuel tank and single cab)	200.0 lbs.	\$3,920.00
I1M	Seat covers standard cab with suspension seat	6.0 lbs.	\$300.00
IK9	33 Gallon Additional Diesel Fuel Tank (Available on 150" WB std. cab in rail tank only)	360.0 lbs.	\$1,940.00
Extended Warranty			
WFF	60 months / 150,000 Miles	0.0 lbs.	\$1,550.00
WFG	60 months / 200,000 Miles	0.0 lbs.	\$1,875.00
WFI	60 months / 250,000 Miles	0.0 lbs.	\$2,600.00
WAG	60 months / 200,000 Miles PLUS	0.0 lbs.	\$2,850.00

Current report content is based on data as of 2019-02-12 10:29:42. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.