



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NPR-HD Cab Chassis, NF3 150", 14,500 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Selected Model and Options

| Code | Description | Weight | MSRP |
|----------------|--|----------|-------------|
| Model | | | |
| NF3 | NPR-HD Cab Chassis 150 | | \$55,228.00 |
| 54 | White, In rail fuel tank with power windows, power door locks and air conditioning | | \$0.00 |
| Options | | | |
| 005 | 4.56:1 | 0.0 lbs. | Inc. |
| 54 | White, In rail fuel tank with power windows, power door locks and air conditioning | 0.0 lbs. | Inc. |
| 8RP | AM/FM/CD radio with Aux input/USB port and Bluetooth RPO | 0.0 lbs. | Inc. |
| AQB | Driver seat is reclining high back. Two single occupant fold down seats with tray backs. | 0.0 lbs. | Inc. |
| C60 | Air conditioner | 0.0 lbs. | Inc. |
| I1B | 4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level. | 0.0 lbs. | Inc. |
| I1W | Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343, | 0.0 lbs. | Inc. |
| I27 | 9,880 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers | 0.0 lbs. | Inc. |
| I2C | 140 AMP. with integral regulator. | 0.0 lbs. | Inc. |
| I36 | R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings. | 0.0 lbs. | Inc. |
| I53I34 | 215/85R16E (10 ply) tubeless Radial, all season tread. | 0.0 lbs. | Inc. |
| I53I69 | 215/85R16E (10 ply) tubeless Radial, all season tread. | 0.0 lbs. | Inc. |
| I5H | LRR (low rolling resistance) | 0.0 lbs. | Inc. |
| IB1 | 150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20in ³ RBM 316,800 lb./ft./in. per rail. | 0.0 lbs. | Inc. |
| ID2 | "I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1. | 0.0 lbs. | Inc. |
| ID4 | 6,830 lb. capacity. Semi-elliptical tapered leaf springs. Includes shock absorbers and stabilizer bar. | 0.0 lbs. | Inc. |
| IF9 | 30 gal. rectangular fuel tank. Mounted between frame rail through the rail fuel fill. Fuel water separator with dash mounted warning light. | 0.0 lbs. | Inc. |

Current report content is based on data as of 2019-02-12 09:15:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NPR-HD Cab Chassis, NF3 150", 14,500 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Selected Model and Options

| Code | Description | Weight | MSRP |
|---------------|---|----------|-------------|
| IL0 | Yes | 0.0 lbs. | Inc. |
| IQ6 | Standard Floor Mats | 0.0 lbs. | Inc. |
| IR8 | Dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard. 4 channel anti-lock brake system. | 0.0 lbs. | Inc. |
| IX1 | Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts | 0.0 lbs. | Inc. |
| IX2 | Rear body dome lamp switch | 0.1 lbs. | Inc. |
| IX7 | Single horizontal with DPF/SCR exhaust system | 0.0 lbs. | Inc. |
| K40 | Butterfly valve type exhaust brake | 0.0 lbs. | Inc. |
| KNX | Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID). | 0.0 lbs. | Inc. |
| RBV | 16" X 6", 6-hole disc, painted white. | 0.0 lbs. | Inc. |
| RBZ | 16" X 6", 6-hole disc, painted white. | 0.0 lbs. | Inc. |
| Totals | | | |
| | Base Price | | \$55,228.00 |
| | Destination Charge | | \$1,125.00 |
| | DEF Fill Charge | | \$10.00 |
| | Total Options Price | | \$ |
| | Tire Weight Tax | | \$0.00 |
| | Total | | \$56,363.00 |

Current report content is based on data as of 2019-02-12 09:15:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NPR-HD Cab Chassis, NF3 150", 14,500 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Optional Equipment

| Code | Description | Weight | MSRP |
|--|---|--------------|-------------|
| Road-Ready Body Program | | | |
| S11 | SUPREME (Van Body) Hardwood Floor / Plywood Sides / Tie Ring, 16' X 96" X 85" | 2,724.0 lbs. | \$9,908.00 |
| S17 | SUPREME (Van Body) Hardwood Floor / Plywood Sides / Tie Ring, 18' X 96" X 91" | 2,974.0 lbs. | \$11,428.00 |
| S42 | SUPREME (Van Body) Pine Floor / Plywood Sides / Tie Ring, 16' X 96" X 85" | 2,568.0 lbs. | \$9,492.00 |
| SS6 | SUPREME (Van Body) Hardwood Floor / Slat Lining, 16' X 96" X 85" | 2,741.0 lbs. | \$9,908.00 |
| SS8 | SUPREME (Van Body) Hardwood Floor / Slat Lining, 18' X 96" X 91" | 3,167.0 lbs. | \$11,428.00 |
| M11 | MORGAN (Van Body) Hardwood Floor / Plywood Lining, 16' X 96" X 85" | 2,415.0 lbs. | \$9,196.00 |
| M17 | MORGAN (Van Body) Hardwood Floor / Plywood Lining, 18' X 96" X 91" | 2,873.0 lbs. | \$10,784.00 |
| MS6 | MORGAN (Van Body) Hardwood Floor / Slat Lining, 16' X 96" X 85" | 2,385.0 lbs. | \$9,364.00 |
| MS8 | MORGAN (Van Body) Hardwood Floor / Slat Lining, 18' X 96" X 91" | 2,799.0 lbs. | \$10,972.00 |
| M21 | MORGAN (Van Body) Hardwood Floor / Slat Lining, 16' X 96" X 91" | 2,444.0 lbs. | \$9,576.00 |
| M20 | MORGAN (Van Body) Hardwood Floor / Plywood Lining, 16' X 96" X 91" | 2,511.0 lbs. | \$9,428.00 |
| S20 | SUPREME (Van Body) Hardwood Floor / Plywood Sides / Tie Ring, 16' X 96" X 91" | 2,793.0 lbs. | \$10,268.00 |
| S19 | SUPREME (Van Body) Pine Floor / Plywood Sides / Tie Ring, 16' X 96" X 91" | 2,637.0 lbs. | \$9,852.00 |
| S21 | SUPREME (Van Body) Hardwood Floor / Slat Lining, 16' X 96" X 91" | 2,810.0 lbs. | \$10,268.00 |
| Road-Ready Body Program Options | | | |
| IQ9 | 16' Translucent Roof (Requires S11, S19, S20, S21, S42, or SS6 Supreme body program) | 0.0 lbs. | \$192.00 |
| IR3 | 12' Walk Ramp (Requires S11, S19, S20, S21, S42, or SS6 Supreme body program; N/A with lift gate) | 210.0 lbs. | \$1,056.00 |
| I6E | 12" X-member Spacing (Requires S11, S19, S20, S21, S42, or SS6 Supreme body program) | 56.0 lbs. | \$92.00 |
| IR0 | 18' Translucent Roof | 0.0 lbs. | \$220.00 |
| IR4 | 14' Walk Ramp (Requires S17, S18, SS8, or SS9 Supreme body program, N/A with lift gate) | 265.0 lbs. | \$1,152.00 |
| I7D | 16' Translucent Roof (Requires M11, M20, M21 or MS6 Morgan body program) | -6.0 lbs. | \$108.00 |
| I1E | 12' Walk Ramp (Requires M11, M20, M21 or MS6 Morgan body program, N/A with lift gate) | 170.0 lbs. | \$1,084.00 |
| I8E | 12" X-member Spacing (Requires M11, M20, M21, or MS6 Morgan body program) | 72.0 lbs. | \$152.00 |

Current report content is based on data as of 2019-02-12 09:15:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NPR-HD Cab Chassis, NF3 150", 14,500 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Optional Equipment

| Code | Description | Weight | MSRP |
|------|---|------------|------------|
| I8D | 18' Translucent Roof | -6.0 lbs. | \$120.00 |
| I2E | 14' Walk Ramp (Requires M17, M18, MS8, or MS9 Morgan body program; N/A with lift gate) | 198.0 lbs. | \$1,100.00 |
| I0P | 1 row E-track recess mt. on sides and surface mt. on front (C/L @ 30" above floor) ply 16 | 60.0 lbs. | \$396.00 |
| I1P | 2 rows E-track recess mt. on sides and surface mt. on front (C/L @ 24" & 48" above floor) ply 16 | 120.0 lbs. | \$784.00 |
| I2P | 1 row E-track recess mt. on sides and surface mt. on front (C/L @ 30" above floor) | 68.0 lbs. | \$436.00 |
| I3P | 2 rows E-track recess mt. on sides and surface mt. on front (C/L @ 24" & 48" above floor) | 132.0 lbs. | \$860.00 |
| I7M | 1 row E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" above floor) ply 16 | 54.0 lbs. | \$368.00 |
| I8M | 2 rows E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" & 60" above floor) ply 16 | 108.0 lbs. | \$724.00 |
| I9M | 1 row E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" above floor) | 60.0 lbs. | \$404.00 |
| I0O | 2 rows E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" & 60" above floor) | 120.0 lbs. | \$596.00 |
| I7N | 1 row E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" above floor) slat 16 | 54.0 lbs. | \$276.00 |
| I8N | 2 rows E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" & 60" above floor) slat 16 | 108.0 lbs. | \$544.00 |
| I9N | 1 row E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" above floor) | 60.0 lbs. | \$304.00 |
| I0N | 2 rows E-track recess mt. on sides and surface mt. on front in addition to tie rings (C/L @ 30" & 60" above floor) | 120.0 lbs. | \$800.00 |
| I6O | City PAK Spec 18, 42" single swing Curbside door with barlock with (1) grab and 1- step stirrup, Location: 58.75" back from the outside front wall to leading edge of door hinged forward, Smooth Steel Scuff sides and front 14 ga. x 12", LED STT lights mounted on rear corner posts in lieu of using STD Incandescent light that come with chassis, (2) rows E-Track recess mounted on sides and surfaced mounted on front wall located 30" & 60" up from the floor to C/L in addition to rope ties | 266.0 lbs. | \$2,484.00 |
| I4U | 14 ga. x 12" Smooth Steel Scuff sides and front | 105.0 lbs. | \$504.00 |
| I5U | 14 ga. x 12" Smooth Steel Scuff sides and front | 119.0 lbs. | \$532.00 |
| I0U | 42" single swing Curbside door with anti-rack bar lock with (1) grab and 1-step stirrup | 0.0 lbs. | \$964.00 |

Current report content is based on data as of 2019-02-12 09:15:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NPR-HD Cab Chassis, NF3 150", 14,500 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Optional Equipment

| Code | Description | Weight | MSRP |
|------|--|------------|------------|
| I1U | LED STT & BU lights mounted on rear corner posts in lieu STD Incandescent lights that come with chassis | 0.0 lbs. | \$376.00 |
| I1Q | Maxon TE-20L Tuck-A-Way bolt-on liftgate with galvanized finish, Capacity: 2,000 lbs., Gate weight: 570 lbs., Platform size: 36 inches x 80 inches galvanized steel wedge platform, Steel Step Bumpers: one (1) each side with 13.5-inch solid rubber pads (In lieu of STD program body Full Width One Way Step bumper), Two (2) Grab Handles at rear in lieu of one (1) standard grab handle on curb side, Cut off switch in cab, LED STT & BU lights installed on the rear corner posts in lieu of standard Isuzu tail lights (Requires M10, M11, M17, M18, M20, M21, MS4, MS6, MS8, or MS9 Morgan body program; N/A with walk ramp) | 585.0 lbs. | \$3,632.00 |
| I0Q | MAXON TE-20L Tuck-A-Way bolt-on liftgate galvanized finish, Capacity: 2000 lbs. (Gate weight: 570 lbs.), Platform size: 36 inches x 80 inches galvanized steel wedge platform, Steel Step Bumpers: one (1) each side with 13.5-inch solid rubber pads (In lieu of STD program body Full Width One Way Step bumper), Two (2) Grab Handles at rear in lieu of one (1) standard grab handle on curb side, Cut off switch in cab, LED SST & BU lights are installed on the rear corner posts in lieu of the standard Isuzu tail lights (Requires S37, S10, S11, S17, S18, S19, S20, S21, S40, S41, S42, SS2, SS4, SS6, SS8, or SS9 Supreme body program; N/A with walk ramp) | 585.0 lbs. | \$3,832.00 |
| I2W | LED SST and BU lights in lieu of incandescent chassis tail lights | 0.0 lbs. | \$400.00 |

Additional Options

| | | | |
|-----|--|-----------|------------|
| IF6 | Fire Extinguisher and Triangle Kit mounted in rear organizer on standard cab and under rear seat on crew cab | 19.0 lbs. | \$88.00 |
| IY4 | Delete radio | -3.0 lbs. | (\$136.00) |
| I9H | Heated dual remote control mirrors (15" head) | 3.0 lbs. | \$496.00 |
| IS0 | Heated Mirrors | 1.0 lbs. | \$104.00 |
| IU2 | Mirror Bracket for 102" wide body | 1.0 lbs. | \$136.00 |
| UZF | Back up alarm | 1.0 lbs. | \$112.00 |
| V22 | Chrome Grille | 1.0 lbs. | \$400.00 |
| IG3 | Engine oil pan heater (120v 300w) | 2.0 lbs. | \$172.00 |
| I4H | CAN interface converter | 1.1 lbs. | \$332.00 |
| IH2 | Engine emergency shutdown system HWT, LWL, LOP | 0.0 lbs. | \$100.00 |

Current report content is based on data as of 2019-02-12 09:15:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



BEYER BROS. ISUZU TRUCK

Guy Montaina

New vehicle (2020 NPR-HD Cab Chassis, NF3 150", 14,500 GVWR. White, In rail fuel tank with power windows, power door locks and air conditioning)

Optional Equipment

| Code | Description | Weight | MSRP |
|--------------------------|--|------------|------------|
| IY9 | Engine idle shutdown (timer set at 3 minutes for engine shutdown) | 0.0 lbs. | \$100.00 |
| I9A | Engine idle shutdown (timer set at 5 minutes for engine shutdown) | 0.0 lbs. | \$100.00 |
| IL9 | PTO enable switch and engine idle up switch recommended for PTO and idle applications only | 0.1 lbs. | \$48.00 |
| I4K | Keyless entry system including two keypads as standard | 1.0 lbs. | \$316.00 |
| I5K | Suspension Drivers Seat (not available on crew cab chassis) | 18.0 lbs. | \$668.00 |
| I6K | Lockable DEF fill cap | 0.3 lbs. | \$80.00 |
| I1L | Speed limited to 58 MPH | 0.0 lbs. | \$100.00 |
| I2L | Speed limited to 65 MPH | 0.0 lbs. | \$100.00 |
| I4L | Speed limited to 70 MPH | 0.0 lbs. | \$100.00 |
| I3L | Speed limited to 68 MPH | 0.0 lbs. | \$100.00 |
| I5L | Locking DEF cap (all keyed alike on multiple chassis ordered together) | 0.3 lbs. | \$80.00 |
| I7L | High visibility seat belt (red color, driver seat only) | 0.0 lbs. | \$92.00 |
| I8L | High visibility seat belt (red color, driver and RH passenger seat) | 0.0 lbs. | \$184.00 |
| I0M | Cold weather package (block heater and heated fuel filter) | 1.0 lbs. | \$236.00 |
| IF4 | Air Deflector roof mounted (not available in Crew Cab) | 64.0 lbs. | \$996.00 |
| IV8 | Seat Covers standard cab | 6.0 lbs. | \$280.00 |
| I0A | Cross rail horizontal DPF/SCR with vertical exhaust (Available only with in rail fuel tank and single cab) | 200.0 lbs. | \$3,920.00 |
| I1M | Seat covers standard cab with suspension seat | 6.0 lbs. | \$300.00 |
| IK9 | 33 Gallon Additional Diesel Fuel Tank (Available on 150" WB std. cab in rail tank only) | 360.0 lbs. | \$1,940.00 |
| Extended Warranty | | | |
| WFF | 60 months / 150,000 Miles | 0.0 lbs. | \$1,550.00 |
| WFG | 60 months / 200,000 Miles | 0.0 lbs. | \$1,875.00 |
| WFI | 60 months / 250,000 Miles | 0.0 lbs. | \$2,600.00 |
| WAG | 60 months / 200,000 Miles PLUS | 0.0 lbs. | \$2,850.00 |

Current report content is based on data as of 2019-02-12 09:15:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.