

Educational Services Commission of New Jersey
 NJ State Approved Co-op #65MCESSCCPS
FINN CORPORATION DOMESTIC EQUIPMENT PRICELIST

Rev.- Effective 11-01-2020

Item	Description	MSRP <i>usd</i>
T30 HYDROSEEDER		
T30	Tank Size	335 liquid capacity, 281 working capacity
	Engine	19 hp Kohler Command Gas
	Hose Reel	electric [max storage capacity 100']
	Hose	100' x 1-1/4" rubber hose [200 psi]
	Nozzles	[1] wide fan, [1] narrow fan, [1] long distance
	Mount	skid
	Other	remote valve
T30 options		
085356	Fill Port	fillport assembly 175
061327-02	Airflush	airflush enabled system 1,140
T60 HYDROSEEDER		
T60T	Tank Size	600 liquid capacity, 500 working capacity
	Engine	23.5 hp Kohler CH730 Gas
	Hose	50' x 1-1/4" rubber hose [200 psi]
	Nozzles	[1] wide fan, [1] narrow fan, [1] long distance
	Mount	trailer w/ electric brakes & DOT lights
	Hitch	standard pintle hitch [2-5/16" ball option #061448-n/c]
	Other	remote valve & suction line valve
T60S	Tank Size	600 liquid capacity, 500 working capacity
	Engine	23.5 hp Kohler CH730 Gas
	Hose	50' x 1-1/4" rubber hose [200 psi]
	Nozzles	[1] wide fan, [1] narrow fan, [1] long distance
	Mount	skid
	Other	remote valve & suction line valve
T60 options		
061280-01	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails 3,210
061210-01	Hose Reel	electric hose reel 3,150
004832-15B	Hose	150' x 1-1/4" continuous hose [200 psi] [replaces 50' hose] 800
003309-10	Hose	100' x 1-1/4" rubber hose [200 psi] with couplers 750
061326-02	Airflush	airflush [requires connection to external air compressor] 950
061407	Spare Tire	spare tire and wheel, mounted & bolted on 690
080533	Radio Remote	remote control-pump on/off 2,000
A5558-001	Hoist System Sub-frame	11.5' HydroSeeder lift sub-frame 7,200
A5567-001	FINN Mount	FINN sub-frame mount (must include applicable sub-frame) 900
T75 HYDROSEEDER		
T75T	Tank Size	820 liquid capacity, 700 working capacity
	Engine	23.5 hp Kohler CH730 Gas
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails
	Hose Reel	electric
	Hose	150' x 1-1/4" rubber hose [200 psi]
	Nozzles	[2] wide fan, [2] narrow fan, [3] long distance
	Mount	trailer w/ electric brakes & DOT lights
	Hitch	standard pintle hitch [2-5/16" ball option #061448-n/c]
T75S	Tank Size	820 liquid capacity, 700 working capacity
	Engine	23.5 hp Kohler CH730 Gas
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails
	Hose Reel	electric
	Hose	150' x 1-1/4" rubber hose [200 psi]
	Nozzles	[2] wide fan, [2] narrow fan, [3] long distance
	Mount	skid
T75 options		
061315-01	Airflush	airflush [requires connection to external air compressor] 880
061369	Spare Tire	spare tire and wheel, mounted & bolted on 630
061411	Surge Brakes	hydraulic surge brakes with 3" lunette [new build required] 3,450
080533	Radio Remote	remote control-pump on/off 2,000
A5562-001	Hoist System Sub-frame	14.25' HydroSeeder lift sub-frame 7,800
A5567-001	FINN Mount	FINN sub-frame mount (must include applicable sub-frame) 900

Educational Services Commission of New Jersey
 NJ State Approved Co-op #65MCESCCPS
FINN CORPORATION DOMESTIC EQUIPMENT PRICELIST

Rev.- Effective 11-01-2020

Item	Description	MSRP <i>usd</i>
T90 & T120 HYDROSEEDER		
T90T	Tank Size	940 liquid capacity, 800 working capacity 57,900
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails
	Nozzles	[1] wide fan, [1] narrow fan, [2] long distance
	Controls	ground level controls
	Mount	trailer w/ electric brakes & DOT lights
	Hitch	standard pintle hitch [ball hitch not optional]
T90S	Tank Size	940 liquid capacity, 800 working capacity 52,900
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final
	Tower/Guard Rail	operator platform and gun assembly with FULL deck rails
	Nozzles	[1] wide fan, [1] narrow fan, [2] long distance
	Controls	ground level controls
	Mount	skid
T120T	Tank Size	1180 liquid capacity, 1000 working capacity 62,500
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails
	Nozzles	[1] wide fan, [1] narrow fan, [2] long distance
	Controls	ground level controls
	Mount	trailer w/ electric brakes & DOT lights
	Hitch	standard pintle hitch [ball hitch not optional]
T120GN	Tank Size	1180 liquid capacity, 1000 working capacity 66,500
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails
	Nozzles	[1] wide fan, [1] narrow fan, [2] long distance
	Controls	ground level controls
	Mount	gooseneck
T120S	Tank Size	1180 liquid capacity, 1000 working capacity 57,900
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails
	Nozzles	[1] wide fan, [1] narrow fan, [2] long distance
	Controls	ground level controls
	Mount	skid
T90/T120 options		
061273H-1-1/4-02	Hose Reel Package	hydraulic hose reel, 200' x 1-1/4" hose [300 psi], nozzles, valve 6,760
061401-01	Airflush	airflush [requires connection to external air compressor] 885
061023	Hardened Pump	nitride treated pump case, impeller, wear plate [new build req'd] 1,070
061111	Railing	T90T full deck railing [new build required] 1,735
061406	Skid Plate	engine compartment skid plate [new build required] 970
061445	Hitch Extension	T90T/T120 hitch extension 20" long 775
061405	Spare Tire	T90T spare wheel/tire, mounted 550
061274	Spare Tire	T120T spare wheel/tire, mounted 550
061040	Spare Tire	T120GN spare wheel/tire, mounted 550
A5563-001	T90S Hoist System Sub-frame	11.5' HydroSeeder lift sub-frame w./ bracket kit 7,400
A5564-001	T120S Hoist System Sub-frame	14.25' HydroSeeder lift sub-frame w./ bracket kit 8,000
A5567-001	FINN Mount	FINN sub-frame mount (must include applicable sub-frame) 900
LF120 HYDROSEEDER		
LF120	Tank Size	1180 liquid capacity, 1000 working capacity 69,400
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails
	Nozzles	[1] wide fan, [1] narrow fan, [2] long distance
	Controls	ground level controls
	Mount	trailer on heavy duty axles and high flotation tires
	Hitch	standard pintle hitch [ball hitch not optional]
	Other	engine/fuel tank skid plates, full deck railings, 20" hitch extension
LF120 options		
061273H-1-1/4-02	Hose Reel Package	hydraulic hose reel, 200' x 1-1/4" hose [300 psi], nozzles, valve 6,760
061401-01	Airflush	airflush [requires connection to external air compressor] 885
061023	Hardened Pump	nitride treated pump case, impeller, wear plate [new build req'd] 1,070
061296	Foam Fill Service	foam filling service for [4] high flotation tubeless tires 5,650

Educational Services Commission of New Jersey
 NJ State Approved Co-op #65MCESECCPS
FINN CORPORATION DOMESTIC EQUIPMENT PRICELIST

Rev. - Effective 11-01-2020

Item	Description		MSRP <i>usd</i>
T170 HYDROSEEDER			
T170	Tank Size	1750 liquid capacity, 1500 working capacity	75,900
	Engine	65hp Cummins Turbo Diesel QSF2.8 Tier IV Final	
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails	
	Nozzles	[2] wide fan, [2] narrow fan, [2] long distance	
	Mount	skid [truck mounting optional]	
T170 options			
061436	Stainless T170	tank & lid [stainless is blast finish, carbon parts painted black]	16,900
061437	Stainless T170	agitators	5,600
061329H-1-1/4-01	Hose Reel Package	hydraulic hose reel [3 position pivoting, UV shield] 200' x 1-1/4" rubber hose [300 psi], nozzles, remote valve	8,215
061329H-1-1/2-01	Hose Reel Package	hydraulic hose reel [3 position pivoting, UV shield] 200' x 1-1/2" rubber hose [300 psi], nozzles, remote valve	8,600
061409-01	Ground Level Controls	engine throttle and clutch control from ground, with standard platform location	1,375
061356-01	Airflush	airflush system [requires truck air supply & addition of 3-5 gallon auxiliary tank for proper flushing]	1,175
061306	Hardened Pump	nitride treated pump case, impeller, wear plate [new build req'd]	1,175
061300	Fill Port Add	add second fill port on drivers side at front of tank	1,175
011562	Truck Mount Kit	truck spring mount kit	890
T330 HYDROSEEDER			
T330	Tank Size	3350 liquid capacity, 3000 working capacity	110,790
	Engine	134HP John Deere 4045HFC04 Tier IV Final turbo diesel	
	Tower/Guard Rail	operator platform and discharge gun assembly with guard rails	
	Nozzles	[2] wide fan, [2] narrow fan, [2] long distance	
	Mount	skid	
	Other	5" X 2.5" centrifugal pump 38 gal. fuel tank reversible, variable speed agitators with liquid recirculation ground level controls truck spring mount kit is included (FINN P/N:011562)	
T330 options			
T330SST	Stainless T330	tank & lid [stainless is blast finish, carbon parts painted black]	17,500
T330SSA	Stainless T330	agitators	11,500
T330HR125	Hose Reel Package	hydraulic hose reel, 200' x 1-1/4" rubber hose [300psi], nozzles, remote valve	8,215
T330HR150	Hose Reel Package	hydraulic hose reel, 200' x 1-1/2" rubber hose [300psi], nozzles, remote valve	8,600
T330RR	Radio Remote	remote control for throttle and pump functions	2,500
T330AF	Airflush	airflush system [requires truck air supply & addition of 3-5 gallon auxiliary tank for proper flushing]	1,200
T330HP	Hardened Pump	nitride treated pump case, impeller, wear plate [new build req'd]	1,175
T330FPA	Fill Port Add	add second fill port on drivers side at front of tank [not available on stainless steel]	1,510
T330SB	Rear Spray Bar	pressurized rear spray bar [3 nozzles]	4,750

Rev.- Effective 11-01-2020

Item	Description		MSRP <i>usd</i>
TITAN HYDROSEEDER			
HT330	Tank Size	3350 gal. liquid capacity, 3000 gal. working capacity	159,900
	Engine	173HP John Deere 4045HFC09 Tier IV Final turbo diesel	
	Tower / Guard Rail	operator platform and discharge gun assembly with full guard rails	
	Nozzles	[2] wide fan, [2] narrow fan, [1] brass long distance, [1] LongShot	
	Mount	skid	
	Other	[4] function/radio remote control operation [pump speed, in/out power hose reel, on/off pump, horn] 6" X 3" centrifugal pump and optional 6" X 3" vortex pump Hydrostatically powered machine functions [2] variable speed and reversible helical agitators 50 gal. fuel tank low maintenance agitator bearings centralized lubrication banks	
HT400	Tank Size	3975 Gal. liquid capacity, 3600 Gal. working capacity	164,900
	Engine	173HP John Deere 4045HFC09 Tier IV Final turbo diesel	
	Tower / Guard Rail	operator platform and discharge gun assembly with full guard rails	
	Nozzles	[2] wide fan, [2] narrow fan, [1] brass long distance, [1] LongShot	
	Mount	skid	
	Other	[4] function/radio remote control operation [pump speed, in/out power hose reel, on/off pump, horn] 6" X 3" centrifugal pump and optional 6" X 3" vortex pump Hydrostatically powered machine functions [2] variable speed and reversible helical agitators 50 gal. fuel tank low maintenance agitator bearings centralized lubrication banks	
Titan Options			
VP	Vortex Pump Conversion	6" X 3", 465 gpm @ 150 psi , 1.25" solid clearance vortex pump (replaces standard centrifugal pump)	860
SPA	Secondary Pump Add	6" X 3", 465 gpm @ 150 psi , 1.25" solid clearance vortex pump add [shipped loose]	8,350
B	Boom	second boom [includes [1] 50 deg wide fan, [1] 25 deg narrow fan, [1] brass long distance]	5,450
HR125	Hose Reel Package	hydraulic hose reel, 200' X 1-1/4" rubber hose [300 psi], nozzles, remote valve	8,250
HR150	Hose Reel Package	hydraulic hose reel, 200' X 1-1/2" rubber hose [300 psi], nozzles, remote valve	8,625
AF	Air Flush	airflush system [requires truck air supply & addition of 3-5 gal. aux. tank for proper flushing]	1,240
FPA	Fill Port Add	adds second fill port on drivers side tank rear	1,300
HP	Hardened Pump	pump hardening process adder	2,100
SS1	Stainless HT330	tank [stainless is painted beige, carbon parts are painted black]	18,000
SS2	Stainless HT330	agitators [2]	13,000
SS3	Stainless HT400	tank [stainless is painted beige, carbon parts are painted black]	19,000
SS4	Stainless HT400	agitators [2]	14,000
HTLP	Lighting Package	integrated work light package, with operator's platform scene lighting	1,000
SB	Spray Bar	pressurized, 3 nozzle spray bar	6,680
FFP	Front Flusher Package	includes [2] flushers mounted on tank, deluxe cab controls mounted in a free standing box w/ truck mounted air tap	15,400
A4924-018	LongShot Nozzle	secondary LongShot nozzle [Distance Optimized for HT only]	1,190

Educational Services Commission of New Jersey
 NJ State Approved Co-op #65MCECCPS
FINN CORPORATION DOMESTIC EQUIPMENT PRICELIST

Rev. - Effective 11-01-2020

Item	Description	MSRP <i>usd</i>
BB302 MATERIAL BLOWER		
BB302	Hopper Capacity	1.5 cu. yd. with built in feed chute 63,910
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final
	Blower	500 cfm @ 10 psi
	Mount	trailer with electric brakes and DOT lights and hitch extension
	Hose	manual reel w/ 100' x 4" and 50' x 4" standard duty hoses w/ quick couplers [reel comfortably fits 100']
	Other	12v electrical system, 3 function/radio remote control operation [engine rpm and material feed] 4" poly diffuse cone
5 SERIES MATERIAL BLOWER		
5 SERIES	Hopper Capacity	5 cu. yd. with optional feed chute 101,900
	Engine	65HP Cummins QSF2.8T Tier IV Final
	Blower	750 cfm @ 12 psi
	Mount	trailer with electric brakes and DOT lights
	Hose	hydraulic reel w/ 100' x 4" and 50' x 4" standard duty hoses w/ quick couplers
	Other	[3] function/radio remote control operation [engine rpm, material feed on/off, variable material control]
		6' x 4" hot air lead hose and electric tarp
5 Series options		
052952	Severe Duty Hose	50' x 4" severe duty extension flex hose 1,080
055348	Hitch Extension	20" hitch extension 790
061450	Hose Swap	removes 4" hose [100' & 50'], replaces with [3 x 50'] 4" severe duty 450
A2255-001	Hose Swap	removes 4" hose [100' & 50'], replaces with [2 x 50'] 5" standard duty 1,125
061451	Feed Chute	feed chute 815
061378	Dust Suppression	5 series on-board liquid injection 1,930
MBH6 MATERIAL BLOWER		
MBH6	Hopper Capacity	6 cu. yd. 105,530
A2548-001	Engine	67HP Yanmar 4TNV98CT Tier IV Final
	Blower	750 cfm @ 12 psi
	Mount	Skid
	Hose	hydraulic reel w/ 100' x 4" and 50' x 4" standard duty hoses w/ quick couplers
	Other	[3] function/radio remote control operation [engine rpm, material feed on/off, variable material control]
		6' x 4" hot air lead hose and electric tarp
		dust suppression (requires external water source)
MBH6 Options		
052952	Severe Duty Hose	50' x 4" severe duty extension flex hose 1,080
A2578-002	Hose Swap	removes 4" hose [100' & 50'], replaces with [2 x 50'] 5" standard duty 1,125
A2578-003	Hose Swap	removes 4" hose [100' & 50'], replaces with [1 x 50'] and [1 x 100'] 4" severe duty 410
A2578-004	Hose Swap	removes 4" hose [100' & 50'], replaces with [2 x 50'] 5" severe duty 1,440
A5466-001	Lighting Package	integrated work light package 1,000
A2567-002	Hardened Airlock	airlock hardening process adder 3,100

Rev. - Effective 11-01-2020

Item	Description	MSRP <i>usd</i>
MBX MATERIAL BLOWER		
MBX	Hopper Capacity	10 cu. yd. 186,700
	Engine	134HP John Deere 4045HFC04 Tier IV Final turbo diesel
	Blower	1250 cfm @ 14 psi
	Mount	skid <i>see chassis recommendations below</i>
	Hose	hydraulic reel w/ [1] 100' and [2] 50' sections x 4" standard duty hoses w/ quick couplers
	Other	[6] function/radio remote control operation [blower rpm, material feed on/off, variable floor speed, in/out power hose reel, on/off seed injection and emergency stop]
		6' x 4" hot air lead hose
		electric tarp
		dust suppression [requires external water source or addition of on-board water option below]
MBX Options		
HC2	Hose Conversion	removes 4" standard duty hose [1] 100' & [2] 50', replaces with 5" standard duty hose [1] 100' & [2] 50' 1,700
HC3	Hose Conversion	removes 4" standard duty hose [1] 100' & [2] 50', replaces with 4" severe duty hose [1] 100' & [2] 50' 2,425
HC4	Hose Conversion	removes 4" standard duty hose [1] 100' & [2] 50', replaces with 5" severe duty hose [4] 50' 2,880
EXT6	Extension Kit	6 cu. yd. extension kit 8,000
EXT6-SL	Extension Kit	6 cu. yd. extension kit w/ side loading doors 9,000
EXT12	Extension Kit	[2] 6 cu. yd. extension kits for 12 cu. yd. additional capacity 16,000
EXT12-SL	Extension Kit	[2] 6 cu. yd. extension kits for 12 cu. yd. additional capacity w/ side loading doors 18,000
F-EU	Fenders	EU export fender package N/C
F-AU	Fenders	Australia export fender package N/C
Floor	Floor	belt floor replaces chain floor 2,870
HA	Hardened Airlock	airlock hardening process adder 3,600
OBT	On-Board Tank	75 gal. on-board water tank for dust suppression 2,140
SI	Seed Injection	seed injection 12,000
MBLP	Lighting Package	integrated work light package 1,000
SP	Skid Plate	drop-out pan skid plate 1,180
Chassis Requirements:	MBX 10 cu. yd.	class 7 (will require class 8 if future extensions are added)
	MBX 10 cu. yd. + 6 cu. yd.	class 8
	MBX 10 cu. yd. + [2] 6 cu. yd.	class 8
MATERIAL BLOWER HOSES AND CONNECTORS		
HC4"	Hose Connector	4" threaded hose to hose spin-on connector 315
HC4"HA	Hose Connector	4" spin-on connector to hot air hose connection 375
HC5"	Hose Connector	5" threaded hose to hose spin-on connector 360
HC5"HA	Hose Connector	5" spin-on connector to hot air hose connection 550
	055398B	standard duty 50' x 4" hose with ends w/ quick couplers 960
	055399B	standard duty 100' x 4" hose with ends w/ quick couplers 1,695
	052744B	standard duty 50' x 5" hose with ends w/ quick couplers 1,730
	052745B	standard duty 100' x 5" hose with ends w/ quick couplers 2,730
	052952	severe duty 50' x 4" hose with ends w/ quick couplers 1,140
	052965	severe duty 100' x 4" hose with ends w/ quick couplers 1,930
	052958	severe duty 50' x 5" hose with ends w/ quick couplers 1,865
Material Blower Hose Weights		
4" FINN Standard Duty Hose = 1.16 lbs. / ft.		
4" FINN Severe Duty Hose = 1.48 lbs. / ft.		
5" FINN Standard Duty Hose = 1.7 lbs. / ft.		
5" FINN Severe Duty Hose = 1.85 lbs. / ft.		

Educational Services Commission of New Jersey
 NJ State Approved Co-op #65MCECCPS
FINN CORPORATION DOMESTIC EQUIPMENT PRICELIST

Rev. - Effective 11-01-2020

Item	Description	MSRP <i>usd</i>
B40 STRAW BLOWER		
B40	Discharge Head	360° rotation, 50° vertical travel 11,300
	Engine	20.5 hp Kohler Command Gas, electric start
	Feed Tray	horizontal, collapsible feed tray
	Mount	skid with forklift channels
	Blower	17" blower fan with 6 fan blades
B40 options		
061361	Custom Trailer Package	independent suspension, 2500 lb. rubber torsion axle, 20.5 x 8 x 10 highway tread tires, fenders, DOT highway lights, expanded metal grating, safety rails, parking jack, 2" ball hitch, electric brakes w/ breakaway switch 4,250
061452	Discharge Hose	100' x 6" w/ clamp and handle 1,835
061105	Discharge Hose	50' x 6" w/ clamp and handle 920
B70 STRAW BLOWER		
B70T	Discharge Head	360° rotation, 50° vertical travel 32,650
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final
	Feed Tray	horizontal, collapsible feed tray adjustable height
	Mount	trailer with electric brakes and DOT lights
	Blower	21" blower fan with 6 fan blades
	Hitch	standard pintle hitch [2" ball option #061449-n/c]
B70RH	Discharge Head	360° rotation, 50° vertical travel 30,200
	Engine	35.1 hp Yanmar 3TNV88C-DYEM Tier IV Final
	Feed Tray	right hand feed horizontal, collapsible feed tray adjustable height
	Mount	skid mounted
	Blower	21" blower fan with 6 fan blades
B70 options		
031303	Discharge Hose	50' x 8" w/ clamp and handle 1,720
B230 STRAW BLOWER		
B230	Discharge Head	359° horizontal rotation, 40° vertical travel 62,930
A5803-001	Engine	72 hp (53.7 kW) YANMAR 4TNV98CT-NVT Turbo Diesel
	Production Capacity	up to 20 tons/ hr
	Discharge Distance	90 ft.
	Feed Tray	hydraulic powered conveyor chain
	Trailer	TANDEM rubber torsion axles w/ electric brakes, DOT lights and ST225/90D16 load range E tires
	Blower	dynamically balanced 30" blower fan with 6 fan blades
	Other	pintle hitch
B230 options		
A5808-001	Seat Belt	seat belt 100
A5807-001	Spare Tire	spare tire and wheel mounted 425
KRIMPER		
KR6PQ	Coulter Blades	9 blades spaced at 8" 6,500
	Ballast Boxes	2 boxes constructed from 3/16" steel
	Axle	1" square carbon steel gangbolt w/ locking nut and tension washer
	Axle Bearings	3 bearings
	Model	6' krimper w/ 3-point hitch
KR8PQ	Coulter Blades	12 blades spaced at 8" 8,990
	Ballast Boxes	2 boxes constructed from 3/16" steel
	Axle	1" square carbon steel gangbolt w/ locking nut and tension washer
	Axle Bearings	4 bearings
	Model	8' krimper w/ 3-point hitch
KR8HQ	Coulter Blades	12 blades spaced at 8" 10,750
	Ballast Boxes	2 boxes constructed from 3/16" steel
	Axle	1" square carbon steel gangbolt w/ locking nut and tension washer
	Axle Bearings	4 bearings
	Model	8' hydraulic krimper w/ hoses and tires
KR16HQ	Coulter Blades	24 blades [12 on main frame, 6 on each wing] 23,790
	Ballast Boxes	2 boxes constructed from 3/16" steel
	Axle	1" square carbon steel gangbolt w/ locking nut and tension washer
	Axle Bearings	10 bearings [6 on main frame and 2 on each wing]
	Model	16' hydraulic krimper w/ hoses and tires

Educational Services Commission of New Jersey
 NJ State Approved Co-op #65MCECCPS
FINN CORPORATION DOMESTIC EQUIPMENT PRICELIST

Rev.- Effective 11-01-2020

Item	Description		MSRP <i>USD</i>
GT Series - Tractor Ground Preparation Attachments			
GTH65	Attachment Method	Category 1 tractor 3-point hitch	6,299
Pro Model	Req'd. Carrier Vehicle HP	24 - 65 hp.	
	Finish Rake Width	78"	
	Scarifiers	(6) hydraulically adjusted scarifiers with ripping depth of 0 - 6" and 45" scarifying width	
	Hydraulic Ports Required	(1) set of ports required (minimum)	
	Grading	55" wide free floating leveling blade and rake	
	Weight	925 lbs.	
	Pro Features	Hydraulic powered scarifiers	
	Other	12" Foam filled gage tires, leveling rake and finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth	
GTM65	Attachment Method	Category 1 tractor 3-point hitch	5,699
	Req'd. Carrier Vehicle HP	24 - 65 hp.	
	Finish Rake Width	78"	
	Scarifiers	(6) manually adjusted scarifiers with ripping depth of 0 - 6" and 45" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Grading	55" wide free floating leveling blade and rake	
	Weight	925 lbs.	
	Other	12" Foam filled gage tires, leveling rake and finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth	
GTH75	Attachment Method	Category 1 tractor 3-point hitch	6,799
Pro Model	Req'd. Carrier Vehicle HP	35 - 75hp.	
	Finish Rake Width	89"	
	Scarifiers	(8) hydraulically adjusted scarifiers with ripping depth of 0 - 6" and 57" scarifying width	
	Hydraulic Ports Required	(1) set of ports required (minimum)	
	Grading	66" wide free floating leveling blade and rake	
	Weight	1,100 lbs.	
	Pro Features	Hydraulic powered scarifiers	
	Other	12" Foam filled gage tires, leveling rake and finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth	
GTM75	Attachment Method	Category 1 tractor 3-point hitch	6,299
	Req'd. Carrier Vehicle HP	35 - 75hp.	
	Finish Rake Width	89"	
	Scarifiers	(8) manually adjusted scarifiers with ripping depth of 0 - 6" and 57" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Grading	66" wide free floating leveling blade and rake	
	Weight	1,100 lbs.	
	Other	12" Foam filled gage tires, leveling rake and finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth	
GTH85-1	Attachment Method	Category 1 tractor 3-point hitch	7,299
Pro Model	Req'd. Carrier Vehicle HP	48 - 75hp.	
	Finish Rake Width	101"	
	Scarifiers	(10) hydraulically adjusted scarifiers with ripping depth of 0 - 6" and 70" scarifying width	
	Hydraulic Ports Required	(1) set of ports required (minimum)	
	Grading	77" wide free floating leveling blade and rake	
	Weight	1,300 lbs.	
	Pro Features	Hydraulic powered scarifiers	
	Other	12" Foam filled gage tires, leveling rake and finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth	

Educational Services Commission of New Jersey
 NJ State Approved Co-op #65MCECCPS
FINN CORPORATION DOMESTIC EQUIPMENT PRICELIST

Rev. - Effective 11-01-2020

Item	Description	MSRP <i>usd</i>
GTM85-1	Attachment Method	Category 1 tractor 3-point hitch
	Req'd. Carrier Vehicle HP	48 - 75hp.
	Finish Rake Width	101"
	Scarifiers	(10) manually adjusted scarifiers with ripping depth of 0 - 6" and 70" scarifying width
	Hydraulic Ports Required	(0) set of ports required
	Grading	77" wide free floating leveling blade and rake
	Weight	1,300 lbs.
	Other	12" Foam filled gage tires, leveling rake and finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth
GTH85-2	Attachment Method	Category 2 tractor 3-point hitch
Pro Model	Req'd. Carrier Vehicle HP	48 - 105 hp.
	Finish Rake Width	101"
	Scarifiers	(10) hydraulically adjusted scarifiers with ripping depth of 0 - 6" and 70" scarifying width
	Hydraulic Ports Required	(1) set of ports required (minimum)
	Grading	77" wide free floating leveling blade and rake
	Weight	1,350 lbs.
	Pro Features	Hydraulic powered scarifiers
	Other	12" Foam filled gage tires, leveling rake and finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth
GTM85-2	Attachment Method	Category 2 tractor 3-point hitch
	Req'd. Carrier Vehicle HP	48 - 105 hp.
	Finish Rake Width	101"
	Scarifiers	(10) manually adjusted scarifiers with ripping depth of 0 - 6" and 70" scarifying width
	Hydraulic Ports Required	(0) set of ports required
	Grading	77" wide free floating leveling blade and rake
	Weight	1,350 lbs.
	Other	12" Foam filled gage tires, leveling rake and finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth
GT Series options		
A5240-001	Hydraulic Top Link	Tractor 3-point hitch hydraulic powered top link kit (Available for Cat. 1 3-point hitch configuration and requires a dedicated set of hydraulic ports)
		299
GS Series - Skid Steer Ground Preparation Attachments		
GSM65	Attachment Method	Skid Steer
	Req'd. Carrier Vehicle HP	30 - 60hp.
	Finish Rake Width	78"
	Scarifiers	(8) manually adjusted scarifiers with ripping depth of 0 - 5" and 66" scarifying width
	Hydraulic Ports Required	(0) set of ports required
	Weight	460 lbs.
	Other	Finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth
GSH75	Attachment Method	Skid Steer
Pro Model	Req'd. Carrier Vehicle HP	40 - 100hp.
	Finish Rake Width	89"
	Scarifiers	(10) hydraulically adjusted scarifiers with ripping depth of 0 - 6" and 79" scarifying width
	Hydraulic Ports Required	(1) set of ports required (minimum)
	Grading	66" wide free floating leveling blade and rake
	Weight	1,300 lbs.
	Pro Features	Hydraulic powered scarifiers, 16" foam filled gage tires and 3/4" AR steel leveling rake
	Other	Finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth

Rev. - Effective 11-01-2020

Item	Description		MSRP <i>usd</i>
GM Series - Mini Skid Steer Ground Preparation Attachments			
GM45-1B	Attachment Method	Mini Skid Steer	1,999
	Skid Steer Mount Plate	Bobcat Mini Skid Steer Specific	
	Req'd. Carrier Vehicle HP	24 - 60hp.	
	Finish Rake Width	54"	
	Scarifiers	(6) manually adjusted scarifiers with ripping depth of 0 - 5" and 46" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Weight	340 lbs.	
	Other	Finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth	
GM45-1U	Attachment Method	Mini Skid Steer	1,999
	Skid Steer Mount Plate	Universal Mini Skid Steer Mount plate (Excludes Bobcat)	
	Req'd. Carrier Vehicle HP	24 - 60hp.	
	Finish Rake Width	54"	
	Scarifiers	(6) manually adjusted scarifiers with ripping depth of 0 - 5" and 46" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Weight	340 lbs.	
	Other	Finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth	
GM45-3B	Attachment Method	Mini Skid Steer	2,999
Pro Model	Skid Steer Mount Plate	Bobcat Mini Skid Steer Specific	
	Req'd. Carrier Vehicle HP	24 - 60hp.	
	Finish Rake Width	54"	
	Scarifiers	(6) manually adjusted scarifiers with ripping depth of 0 - 5" and 46" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Grading	38" wide free floating leveling blade and rake	
	Weight	540 lbs.	
	Pro Features	16" Air filled gage tires and 3/4" AR steel leveling rake	
	Other	Finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth	
GM45-3U	Attachment Method	Mini Skid Steer	2,999
Pro Model	Skid Steer Mount Plate	Universal Mini Skid Steer Mount plate (Excludes Bobcat)	
	Req'd. Carrier Vehicle HP	24 - 60hp.	
	Finish Rake Width	54"	
	Scarifiers	(6) manually adjusted scarifiers with ripping depth of 0 - 5" and 46" scarifying width	
	Hydraulic Ports Required	(0) set of ports required	
	Grading	38" wide free floating leveling blade and rake	
	Weight	540 lbs.	
	Pro Features	16" Air filled gage tires and 3/4" AR steel leveling rake	
	Other	Finish rake constructed of 3/4" AR steel (replaceable in sections) and easily replaceable bolt on scarifier teeth	
GM Series options			
A5241-001	Conversion Kit	GM45-1B to GM45-3B & GM45-1U to GM45-3U Conversion Kit	1,999