



## FM1012R Rear Discharge Flex-Wing Grooming Mower with Light Bar

Code	Description	List price(USD)
	<b>FM1012R Rear Discharge Flex-Wing Grooming Mower with Light Bar</b>	
	<p>Type: Flex Wing, Rear Discharge            Transport Width: 8 Ft. 3 In.            Cutting Width: 12 Ft.            Transport Tongue Weight: 700 lbs.            Transport Tires: (2) 20.5 x 8-10            Transport Length: 13 Ft. 2 In.            Transport Height: 6 Ft.            Tractor PTO Speed: 540 RPM            Tractor Horsepower: 30 to 80 HP            Splitter Gearbox HP: 100 HP            Shipping Weight: 2960 lbs.            Overall Width: 12 Ft. 2 In.            Operating Tongue Weight: 310 lbs.            Mower Deck Gearbox HP: 40 HP            Maximum Overall Length:            14 Ft. 5 In.            Mainframe Construction:            3 In. Square Tubing            Input Driveline:            Category III Constant Velocity            Hitch: Drawbar Category I            Hitch Adjustment:            Self-Leveling, Multi-Position            Ground Pressure: 9.0 PSI            Gearbox Ratio: 1:1.92            Driveline: Category III            Drive Type: Gearbox Over V-Belt            Deck Thickness: 8 Gauge Steel Plate            Deck Overlap: 6 In.            Deck Lift Cylinders:            3-1/2 In. x 10 In. Single Acting            Cutting Height Range: 1 In. to 5 In.            Cutting Height Adjustment:            Spacer On Caster            Center Deck Cutting Width: 5 Ft.            Wing Deck Cutting Width: 4 Ft.            Caster Wheels:</p>	

**FM1012R Rear Discharge Flex-Wing Grooming Mower with Light Bar**

Code	Description	List price(USD)
	(8) 15 x 6-6 Pneumatic Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 16,950 FPM Average Blade Spindles: (7) Cast Iron Blade Spindle Bearings: Tapered Roller Blade Overlap: 1-1/2 In. Blade Dimensions: (7) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 75 Minutes (Approximate) Approximate Operating Weight: 2900 lbs. Front Roller Kit: Wing Decks (Optional Attachment, 1 Required) Front Roller Kit: Rear Deck (Optional Attachment, 1 Required) Approximate Operating Angles: 25 Degrees Up and 15 Degrees Down	
	<b>BASE MACHINE</b>	
0421XF	FM1012R Rear Discharge Flex-Wing Grooming Mower with Light Bar	\$26,368.00
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
5WD1004116	Anti Streaking Kit (FM10 Series)	\$178.20
5WD1003635	Rigid Clevis Hitch (FM10 Series)	\$244.20
5WD1006421	Front Roller Kit - Contains 1 Roller (FM1012 Wing Decks Only)	\$270.60
5WD1031818	FM10 Series Rear Roller Kit	\$129.80
5WD1032454	FM10 Series Hydraulic Unlock System	\$827.20
5WD1031385	Light Bar Kit (FM10 Series and FM3012)	\$883.31



## FM1012R Rear Discharge Flex-Wing Grooming Mower with Light Bar

Code	Description	List price(USD)
	<i>Serial Number 1XFFM10XAB0000106 and above on the FM10 Series and all FM30 Series Mowers.</i>	
5WD1006417	Front Roller Kit, Contains 1 Roller <i>FM1012 Center Deck Only, FM1015 and FM1017 Fits all Decks, GM1060, GM1072 and GM1084.</i>	\$149.60
5WD1004486	Light Bar Kit (FM10 Series) <i>Serial Number 1XFFM10XAB0000105 and below.</i>	\$748.00

**FM1015R Rear Discharge Flex-Wing Grooming Mower with Light Bar**

Code	Description	List price(USD)
	<b>FM1015R Rear Discharge Flex-Wing Grooming Mower with Light Bar</b>	
	Type: Flex Wing, Rear Discharge Transport Width: 8 Ft. 4 In. Cutting Width: 15 Ft. Transport Tongue Weight: 720 lbs. Transport Tires: (2) 20.5 x 8 - 10 Transport Length: 13 Ft. 5 In. Transport Height: 7 Ft. 9 In. Tractor PTO Speed: 540 RPM Tractor Horsepower: 35 to 80 HP Splitter Gearbox HP: 100 HP Shipping Weight: 3200 lbs. Overall Width: 15 Ft. 2 In. Operating Tongue Weight: 330 lbs. Mower Deck Gearbox HP: 40 HP Maximum Overall Length: 14 Ft. 8 In. Mainframe Construction: 3 In. Square Tubing Input Driveline: Category III Constant Velocity Hitch: Drawbar Category II Hitch Adjustment: Self-Leveling, Multi-Position Ground Pressure: 9.7 lbs. PSI Gearbox Ratio: 1:1.92 Driveline: Category III Drive Type: Gearbox Over V-Belt Deck Thickness: 8 Gauge Steel Plate Deck Overlap: 6 In. Deck Lift Cylinders: 3-1/2 In. x 10 In. Single Acting Cutting Height Range: 1 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Center Deck Cutting Width: 6 Ft. Wing Deck Cutting Width: 5 Ft.	

**FM1015R Rear Discharge Flex-Wing Grooming Mower with Light Bar**

Code	Description	List price(USD)
	Caster Wheels: (8) 15 x 6-6 Pneumatic Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 16,950 FPM Average Blade Spindles: (9) Cast Iron Blade Spindle Bearings: Tapered Roller Blade Overlap: 1-1/2 In. Blade Dimensions: (9) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 75 Minutes (Approximate) Approximate Operating Weight: 3,200 lbs. Front Roller Kit: (Optional Attachment, 3 required) Approximate Operating Angles: 25 Degrees Up and 15 Degrees Down	
	<b>BASE MACHINE</b>	
0422XF	FM1015R Rear Discharge Flex-Wing Grooming Mower with Light Bar	\$28,359.00
	<b>MISCELLANEOUS ATTACHMENTS FOR FIELD CONVERSION MISCELLANEOUS</b>	
5WD1003635	Rigid Clevis Hitch (FM10 Series)	\$244.20
5WD1004116	Anti Streaking Kit (FM10 Series)	\$178.20
5WD1031818	FM10 Series Rear Roller Kit	\$129.80
5WD1032454	FM10 Series Hydraulic Unlock System	\$827.20
5WD1006417	Front Roller Kit, Contains 1 Roller <i>FM1012 Center Deck Only, FM1015 and FM1017 Fits all Decks, GM1060, GM1072 and GM1084.</i>	\$149.60
5WD1031385	Light Bar Kit (FM10 Series and FM3012)	\$883.31



## FM1015R Rear Discharge Flex-Wing Grooming Mower with Light Bar

Code	Description	List price(USD)
5WD1004486	<p><i>Serial Number 1XFFM10XAB0000106 and above on the FM10 Series and all FM30 Series Mowers.</i></p> <p>Light Bar Kit (FM10 Series)</p> <p><i>Serial Number 1XFFM10XAB0000105 and below.</i></p>	\$748.00

**FM1017R Rear Discharge Flex-Wing Grooming Mower with Light Bar**

Code	Description	List price(USD)
	<b>FM1017R Rear Discharge Flex-Wing Grooming Mower with Light Bar</b>	
	<p>Type: Flex Wing, Rear Discharge  Transport Width: 8 Ft. 3 In.  Cutting Width: 17 Ft.  Transport Tongue Weight: 800 lbs.  Transport Tires: (2) 20.5 x 8 - 10  Transport Length: 13 Ft. 5 In.  Transport Height: 8 Ft. 9 In.  Tractor PTO Speed: 540 RPM  Tractor Horsepower: 40 to 80 HP  Splitter Gearbox HP: 100 HP  Shipping Weight: 3340 lbs.  Overall Width: 17 Ft. 2 In.  Operating Tongue Weight: 400 lbs.  Mower Deck Gearbox HP: 40 HP  Maximum Overall Length:  14 Ft. 8 In.  Mainframe Construction:  3 In. Square Tubing  Input Driveline:  Category III Constant Velocity  Hitch: Drawbar - Category II  Hitch Adjustment:  Self-Leveling, Multi-Position  Ground Pressure: 10.2 lbs. PSI  Gearbox Ratio: 1:1.92  Driveline: Category III  Drive Type: Gearbox Over V-Belt  Deck Thickness: 8 Gauge Steel Plate  Deck Overlap: 6 In.  Deck Lift Cylinders:  3-1/2 In. x 10 In. Single Acting  Cutting Height Range: 1 In. to 5 In.  Cutting Height Adjustment:  Spacer On Caster  Center Deck Cutting Width: 6 Ft.  Wing Deck Cutting Width: 6 Ft.  Caster Wheels:</p>	

**FM1017R Rear Discharge Flex-Wing Grooming Mower with Light Bar**

Code	Description	List price(USD)
	(8) 15 x 6-6 Pneumatic Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 16,950 FPM Average Blade Spindles: (9) Cast Iron Blade Spindle Bearings: Tapered Roller Blade Overlap: 1-1/2 In. Blade Dimensions: (9) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 75 Minutes (Approximate) Approximate Operating Weight: 3340 lbs. Front Roller Kit: (Optional Attachment, 3 Required) Approximate Operating Angles: 25 Degrees Up and 15 Degrees Down	
	<b>BASE MACHINE</b>	
0423XF	FM1017R Rear Discharge Flex-Wing Grooming Mower with Light Bar	\$31,451.00
	<b>MISCELLANEOUS ATTACHMENTS FOR FIELD CONVERSION MISCELLANEOUS</b>	
5WD1003635	Rigid Clevis Hitch (FM10 Series)	\$244.20
5WD1004116	Anti Streaking Kit (FM10 Series)	\$178.20
5WD1031818	FM10 Series Rear Roller Kit	\$129.80
5WD1032454	FM10 Series Hydraulic Unlock System	\$827.20
5WD1006417	Front Roller Kit, Contains 1 Roller <i>FM1012 Center Deck Only, FM1015 and FM1017 Fits all Decks, GM1060, GM1072 and GM1084.</i>	\$149.60
5WD1031385	Light Bar Kit (FM10 Series and FM3012) <i>Serial Number 1XFFM10XAB0000106 and above on the FM10 Series and all FM30 Series Mowers.</i>	\$883.31





## FM1017R Rear Discharge Flex-Wing Grooming Mower with Light Bar

Code	Description	List price(USD)
5WD1004486	Light Bar Kit (FM10 Series) <i>Serial Number 1XFFM10XAB0000105 and below.</i>	\$748.00



## GM1060 Rear Discharge Grooming Mower

Code	Description	List price(USD)
<b>GM1060 Rear Discharge Grooming Mower</b>		
	Tractor Horsepower: 15 to 40 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Shipping Weight: 743 lbs. Mower Deck Gearbox HP: 60 HP Hitch: Category I Gearbox Ratio: 1:1.92 Driveline: Category III Drive Type: Gearbox Over V-Belt Deck Thickness: 8 Gauge Steel Plate Cutting Width: 60 In. Cutting Height Range: 1 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 18,100 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Tapered Roller Blade Overlap: 1-1/2 In. Blade Dimensions: (3) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 20 Minutes (Approximate) Approximate Operating Weight: 611 lbs. Front Roller Kit: Optional	
<b>BASE MACHINE</b>		
0451XF	<i>iMatch and iMatch conversion kit ordered separately.</i> GM1060 Rear Discharge Grooming Mower	\$5,600.00
<b>FRAME</b>		
<b>Basic Factory Options</b>		
<b>CHAIN ENCLOSURES</b>		



## GM1060 Rear Discharge Grooming Mower

Code	Description	List price(USD)
2000	Rear Chain Shield	No Added Cost
2095	Less Rear Chain Shield	(\$168.00)
	<b>Field Installed Options</b>	
	<b>CONVERSION KIT</b>	
9000	iMatch Conversion Kit <i>Excludes economy series.</i>	\$307.00
	<b>ROLLERS</b>	
9010	Front Roller Kit <i>Contains 1 roller.</i>	\$136.00
	<b>WHEELS AND TIRES</b>	
	<b>Basic Factory Options</b>	
	<b>WHEELS AND TIRES</b>	
3000	Pneumatic Tires	(\$56.00)
3010	Solid Tires	In Base Price
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	\$275.00
	<i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5WD55348	Rear Chain Shield Kit - Rear Discharge	\$213.40
5WD1006417	Front Roller Kit, Contains 1 Roller <i>FM1012 Center Deck Only, FM1015 and FM1017 Fits all Decks, GM1060, GM1072 and GM1084.</i>	\$149.60
5WD1005400	iMatch Conversion Kit <i>For GM10 Series.</i>	\$336.60



## GM1072 Rear Discharge Grooming Mower

Code	Description	List price(USD)
<b>GM1072 Rear Discharge Grooming Mower</b>		
	Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 20 to 40 HP Shipping Weight: 806 lbs. Mower Deck Gearbox HP: 60 HP Hitch: Category I Gearbox Ratio: 1:1.92 Driveline: Category III Drive Type: Gearbox Over V-Belt Deck Thickness: 8 Gauge Steel Plate Cutting Width: 72 In. Cutting Height Range: 1 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 18,000 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Tapered Roller Blade Overlap: 1-1/2 In. Blade Dimensions: (3) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 20 Minutes (Approximate) Approximate Operating Weight: 678 lbs. Front Roller Kit: Optional	
<b>BASE MACHINE</b>		
0453XF	<i>iMatch and iMatch conversion kit ordered separately.</i> GM1072 Rear Discharge Grooming Mower	\$5,850.00
<b>FRAME</b>		
<b>Basic Factory Options</b>		
<b>CHAIN ENCLOSURES</b>		



## GM1072 Rear Discharge Grooming Mower

Code	Description	List price(USD)
2000	Rear Chain Shield	No Added Cost
2095	Less Rear Chain Shield	(\$189.00)
	<b>Field Installed Options</b>	
	<b>CONVERSION KIT</b>	
9000	iMatch Conversion Kit <i>Excludes economy series.</i>	\$307.00
	<b>ROLLERS</b>	
9010	Front Roller Kit <i>Contains 1 roller.</i>	\$136.00
	<b>WHEELS AND TIRES</b>	
	<b>Basic Factory Options</b>	
	<b>WHEELS AND TIRES</b>	
3000	Pneumatic Tires	(\$56.00)
3010	Solid Tires	In Base Price
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	\$275.00
	<i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5WD53566	Rear Chain Shield Kit - Rear Discharge	\$217.80
5WD1005400	iMatch Conversion Kit <i>For GM10 Series.</i>	\$336.60
5WD1006417	Front Roller Kit, Contains 1 Roller <i>FM1012 Center Deck Only, FM1015 and FM1017 Fits all Decks, GM1060, GM1072 and GM1084.</i>	\$149.60



## GM1084 Rear Discharge Grooming Mower

Code	Description	List price(USD)
<b>GM1084 Rear Discharge Grooming Mower</b>		
	Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 25 to 40 HP Shipping Weight: 991 lbs. Mower Deck Gearbox HP: 60 HP Hitch: Category I Gearbox Ratio: 1:1.92 Driveline: Category III Drive Type: Gearbox Over V-Belt Deck Thickness: 8 Gauge Steel Plate Cutting Width: 84 In. Cutting Height Range: 1 In. to 4-1/2 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 17,900 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Tapered Roller Blade Overlap: 2 In. Blade Dimensions: (3) 5/16 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 20 Minutes (Approximate) Approximate Operating Weight: 774 lbs. Front Roller Kit: Optional	
<b>BASE MACHINE</b>		
0455XF	<i>iMatch and iMatch conversion kit ordered separately.</i> GM1084 Rear Discharge Grooming Mower	\$6,688.00
<b>FRAME</b>		
<b>Basic Factory Options</b>		

**GM1084 Rear Discharge Grooming Mower**

Code	Description	List price(USD)
	<b>CHAIN ENCLOSURES</b>	
2000	Rear Chain Shield	No Added Cost
2095	Less Rear Chain Shield	(\$225.00)
	<b>Field Installed Options</b>	
	<b>CONVERSION KIT</b>	
9000	iMatch Conversion Kit <i>Excludes economy series.</i>	\$307.00
	<b>ROLLERS</b>	
9010	Front Roller Kit <i>Contains 1 roller.</i>	\$136.00
	<b>WHEELS AND TIRES</b>	
	<b>Basic Factory Options</b>	
	<b>WHEELS AND TIRES</b>	
3000	Pneumatic Tires	(\$56.00)
3010	Solid Tires	In Base Price
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	\$275.00
	<i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5WD52856	Rear Chain Shield Kit - Rear Discharge (GM1084)	\$270.60
5WD1006417	Front Roller Kit, Contains 1 Roller <i>FM1012 Center Deck Only, FM1015 and FM1017 Fits all Decks, GM1060, GM1072 and GM1084.</i>	\$149.60
5WD1005400	iMatch Conversion Kit <i>For GM10 Series.</i>	\$336.60



## GM1048E Economy Rear Discharge Grooming Mower

Code	Description	List price(USD)
<b>GM1048E Economy Rear Discharge Grooming Mower</b>		
	4 Rubber Swivel Tires 11 Gauge Reinforced Deck Spindle Shafts Greased from the Top for Easy Service Single Belt Drive with Automatic Belt Idler Rugged 30-HP Gearbox One Piece Balanced Steel Pulleys High Blade Speed Floating Top Hitch iMatch Compatible (Quick-Attach System) Working Width: 48 In. Overall Machine Width: 51 In. Machine Weight: 340 lbs. HP Requirements: 16 - 30 HP Deck Thickness: 11 Gauge Cutting Height from 1 In. to 4 In. Category I Hitch Blade Tip Speed: 13,188 Ft./Minute Type: Rear Discharge Front Antiscalping Roller: Optional Mulching Kit: Optional Rotor RPM: 3,037 RPM Driveline: 1-3/8 In. ASAE Category II Shipping Weight: 398 lbs. Set-up Time: 30 Minute 1 Year Warranty	
<b>BASE MACHINE</b>		
0461XF	<i>iMatch and iMatchconversion kit ordered separately.</i> GM1048E Economy Rear Discharge Grooming Mower	\$3,733.00
<b>FRAME</b>		
<b>Field Installed Options</b>		
<b>ROLLERS</b>		
9450	Front Anti-Scalping Roller	\$169.00
<b>CONVERSION KIT</b>		
9630	I-Match Conversion Kit	\$538.00





## GM1048E Economy Rear Discharge Grooming Mower

Code	Description	List price(USD)
<b>CUTTING UNITS</b> <b>Field Installed Options</b> <b>MULCH KITS</b>		
9690	Mulching Kit <i>For GM1048E.</i>	\$428.00
<b>DESTINATION AND LANGUAGE</b> <b>Field Installed Options</b> <b>OPERATOR'S MANUAL AND DECALS</b>		
9200	French Operators Manual and Decal Kit (GM10E Series)	No Added Cost
<b>MISCELLANEOUS</b> <b>ATTACHMENTS FOR FIELD CONVERSION</b> <b>MISCELLANEOUS</b>		
5BP001600	Front Antiscalping Roller	\$185.91
5BP004600	Mulching Kit (GM1048E)	\$470.80
5BP006750	iMatch Conversion Kit <i>Fits GM1048E, GM1060E, and GM1072E. Must also order longer 5BP0500404 driveline from parts for GM1048E or GM1060E.</i>	\$621.51
5BP950959B	French Manual Decal (GM10E Series)	\$0.00
BLV11199	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	\$275.00
	<p><i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i></p> <p><i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i></p>	



## GM1060E Economy Rear Discharge Grooming Mower

Code	Description	List price(USD)
<b>GM1060E Economy Rear Discharge Grooming Mower</b>		
	4 Rubber Swivel Tires 11 Gauge Reinforced Deck Spindle Shafts Greased from the Top for Easy Service Single Belt Drive with Automatic Belt Idler Rugged 30-HP Gearbox One Piece Balanced Steel Pulleys High Blade Speed Floating Top Hitch iMatch Compatible (Quick-Attach System) Working Width: 60 In. Overall Machine Width: 63 In. Machine Weight: 375 lbs. HP Requirements: 18 - 30 HP Deck Thickness: 11 Gauge Cutting Height from 1 In. to 4 In. Category I Hitch Blade Tip Speed: 14,763 Ft./Minute Type: Rear Discharge Front Antiscalping Roller: Optional Mulching Kit: Optional Rotor RPM: 2,803 RPM Driveline: 1-3/8 In. ASAE Category II Shipping Weight: 470 lbs. Set-up Time: 30 Minute 1 Year Warranty	
<b>BASE MACHINE</b>		
0462XF	<i>iMatch and iMatchconversion kit ordered separately.</i> GM1060E Economy Rear Discharge Grooming Mower	\$3,850.00
<b>FRAME</b>		
<b>Field Installed Options</b>		
<b>ROLLERS</b>		
9450	Front Anti-Scalping Roller	\$169.00
<b>CONVERSION KIT</b>		
9630	I-Match Conversion Kit	\$538.00



## GM1060E Economy Rear Discharge Grooming Mower

Code	Description	List price(USD)
<b>CUTTING UNITS</b> <b>Field Installed Options</b> <b>MULCH KITS</b>		
9690	Mulching Kit <i>For GM1060E.</i>	\$489.00
<b>DESTINATION AND LANGUAGE</b> <b>Field Installed Options</b> <b>OPERATOR'S MANUAL AND DECALS</b>		
9200	French Operators Manual and Decal Kit (GM10E Series)	No Added Cost
<b>MISCELLANEOUS</b> <b>ATTACHMENTS FOR FIELD CONVERSION</b> <b>MISCELLANEOUS</b>		
5BP001600	Front Antiscalping Roller	\$185.91
5BP005600	Mulching Kit (GM1060E)	\$536.80
5BP006750	iMatch Conversion Kit <i>Fits GM1048E, GM1060E, and GM1072E. Must also order longer 5BP0500404 driveline from parts for GM1048E or GM1060E.</i>	\$621.51
5BP950959B	French Manual Decal (GM10E Series)	\$0.00
BLV11199	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	\$275.00
<p><i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i></p> <p><i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i></p>		



## GM1072E Economy Rear Discharge Grooming Mower

Code	Description	List price(USD)
<b>GM1072E Economy Rear Discharge Grooming Mower</b>		
	4 Rubber Swivel Tires 11 Gauge Reinforced Deck Spindle Shafts Greased from the Top for Easy Service Single Belt Drive with Automatic Belt Idler Rugged 30-HP Gearbox One Piece Balanced Steel Pulleys High Blade Speed Floating Top Hitch iMatch Compatible (Quick-Attach System) Working Width: 60 In. Overall Machine Width: 63 In. Machine Weight: 375 lbs. HP Requirements: 18 - 30 HP Deck Thickness: 11 Gauge Cutting Height from 1 In. to 4 In. Category I Hitch Blade Tip Speed: 14,763 Ft./Minute Type: Rear Discharge Front Antiscalping Roller: Optional Mulching Kit: Optional Rotor RPM: 2,803 RPM Driveline: 1-3/8 In. ASAE Category II Shipping Weight: 470 lbs. Set-up Time: 30 Minute 1 Year Warranty	
<b>BASE MACHINE</b>		
0463XF	<i>iMatch and iMatchconversion kit ordered separately.</i> GM1072E Economy Rear Discharge Grooming Mower	\$4,240.00
<b>FRAME</b>		
<b>Field Installed Options</b>		
<b>ROLLERS</b>		
9450	Front Anti-Scalping Roller	\$169.00
<b>CONVERSION KIT</b>		
9630	I-Match Conversion Kit	\$538.00

**GM1072E Economy Rear Discharge Grooming Mower**

Code	Description	List price(USD)
	<b>CUTTING UNITS</b>	
	<b>Field Installed Options</b>	
	<b>MULCH KITS</b>	
9690	Mulching Kit <i>For GM1072E.</i>	\$530.00
	<b>DESTINATION AND LANGUAGE</b>	
	<b>Field Installed Options</b>	
	<b>OPERATOR'S MANUAL AND DECALS</b>	
9200	French Operators Manual and Decal Kit (GM10E Series)	No Added Cost
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
5BP001600	Front Antiscalping Roller	\$185.91
5BP006600	Mulching Kit (GM1072E)	\$583.00
5BP006750	iMatch Conversion Kit <i>Fits GM1048E, GM1060E, and GM1072E. Must also order longer 5BP0500404 driveline from parts for GM1048E or GM1060E.</i>	\$621.51
5BP950959B	French Manual Decal (GM10E Series)	\$0.00
BLV11199	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	\$275.00
	<i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	



## GM1190 Rear Discharge Grooming Mower with Chain Shield

Code	Description	List price(USD)
<b>GM1190 Rear Discharge Grooming Mower with Chain Shield</b>		
	Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 25 to 50 HP Shipping Weight: 1347 lbs. Mower Deck Gearbox HP: 50 HP Hitch: Category I Gearbox Ratio: 1:1.69 Driveline: Category IV Drive Type: Gearbox Over (2) V-Belts Deck Thickness: 7 Gauge Steel Plate Cutting Width: 90 In. Cutting Height Range: 1-1/2 In. to 8 In. Cutting Height Adjustment: Adjustable Arm Caster Wheels: (4) 13 In. x 5 In. Solid Caster Wheel Bearings: Tapered Roller Bearings Blade Tip Speed: 15,570 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Tapered Roller Blade Overlap: 1-1/4 In. Blade Dimensions: (6) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: Power Band, B Section, Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 45 Minutes (Approximate) Approximate Operating Weight: 1,200 lbs. Front Center Roller Kit: Optional	
<b>BASE MACHINE</b>		
0471XF	<i>iMatch and iMatch conversion kit ordered separately.</i> GM1190 Rear Discharge Grooming Mower with Chain Shield	\$8,845.00
<b>FRAME</b>		

**GM1190 Rear Discharge Grooming Mower with Chain Shield**

Code	Description	List price(USD)
	<b>Field Installed Options</b>	
	<b>CONVERSION KIT</b>	
9000	iMatch Conversion Kit <i>Excludes economy series.</i>	\$265.00
	<b>ROLLERS</b>	
9010	Front Roller Kit <i>Contains 1 roller.</i>	\$184.00
	<b>WHEELS AND TIRES</b>	
	<b>Basic Factory Options</b>	
	<b>WHEELS AND TIRES</b>	
3000	Pneumatic Tires	No Added Cost
3010	Solid Tires	In Base Price
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
5WD1005400	iMatch Conversion Kit <i>For GM1190. Serial Number 1XFGM11XKB0000120 and below.</i>	\$336.60
5WD1032828	Front Roller Kit - Contains 1 Roller (GM1190) <i>Serial Number 1XFGM11XKB0000121 and above.</i>	\$201.31
5WD1032830	iMatch Conversion Kit <i>For GM1190. Serial Number 1XFGM11XKB0000121 and above.</i>	\$290.40
5WD24650	Front Roller Kit - Contains 1 Roller (GM1190) <i>Serial Number 1XFGM11XKB0000120 and below.</i>	\$212.31



## GM2060R Rear Discharge Grooming Mower with Rear Chain Shields

Code	Description	List price(USD)
	<b>GM2060R Rear Discharge Grooming Mower with Rear Chain Shields</b>	
	<p>High Blade Speed iMatch Compatible (Quick-Attach System) 4 Swivel Tires - Solid or Pneumatic Spindle Shafts Greased from the Top for Easy Service 20 to 50 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Shipping Weight: 609 lbs. Mower Deck Gearbox HP: 50 HP Hitch: Category I Gearbox Ratio: 1:3:09 (Spiral Gears) Driveline: 1-3/8 In. ASAE Category III Drive Type: Gear Box over V/Belt Deck Thickness: 8 Gauge Reinforced Deck Cutting Width: 60 In. Cutting Height Range: 1 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3.2 In. Solid or 11 In. x 4 In. (4 Ply, with Tubes) Pneumatic Caster Wheel Bearings: Shielded Roller Bearings Blade Tip Speed: 16,929 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Shielded Ball Bearings (2) Per Spindle Blade Composition: Heat-Treated Alloy Steel Blade Overlap: 1-1/8 In. Blade Dimensions: (3) 20-3/16 In. x 2 In. x 1/4 In. Belts: 5VX, Polyester/Cogged</p>	



**GM2060R Rear Discharge Grooming Mower with Rear Chain Shields**

Code	Description	List price(USD)
	Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Front Roller Kit: Optional Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 550 lbs. Mulching Kit Available 1 Year Warranty	
	<b>BASE MACHINE</b>	
0481XF	<i>iMatch and iMatchconversion kit ordered separately.</i> GM2060R Rear Discharge Grooming Mower with Rear Chain Shields	\$5,143.00
	<b>WHEELS AND TIRES</b>	
	<b>Basic Factory Options</b>	
	<b>WHEELS AND TIRES</b>	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	\$100.00
	<b>FRAME</b>	
	<b>Field Installed Options</b>	
	<b>ROLLERS</b>	
9450	Front Anti-Scalping Roller	\$192.00
	<b>CONVERSION KIT</b>	
9630	I-Match Conversion Kit	\$486.00
	<b>CUTTING UNITS</b>	
	<b>Field Installed Options</b>	
	<b>MULCH KITS</b>	
9690	Mulching Kit GM2060	\$494.00
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
5BP002800	iMatch Conversion Kit	\$534.60
5BP0099915	Front Antiscalping Roller	\$210.11
5BP045700	Mulching Kit (GM2060)	\$543.40

**GM2060R Rear Discharge Grooming Mower with Rear Chain Shields**

Code	Description	List price(USD)
BLV11200	<p>John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i></p> <p><i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i></p> <p><i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i></p>	\$275.00

**GM2072R Rear Discharge Grooming Mower with Rear Chain Shields**

Code	Description	List price(USD)
	<b>GM2072R Rear Discharge Grooming Mower with Rear Chain Shields</b>	
	<p>Spindle Shafts Greased from the Top for Easy Service  iMatch Compatible (Quick-Attach System)  4 Swivel Tires - Solid or Pneumatic  Type: Rear Discharge  Tractor PTO Speed: 540 RPM  Tractor Horsepower: 20 to 50 HP  Shipping Weight: 676 lbs.  Mower Deck Gearbox HP: 50 HP  Hitch: Category I  Gearbox Ratio: 1:3:09 (Spiral Gears)  Driveline: Category III  Drive Type: Gearbox Over V-Belt  Deck Thickness: 8 Gauge Steel Plate  Cutting Width: 72 In.  Cutting Height Range: 1 In. to 5 In.  Cutting Height Adjustment:  Spacer on Caster  Caster Wheels:  (4) 10 In. x 3.2 In. Solid or 11 In. x 4 In. (4 Ply, with Tubes) Pneumatic  Caster Wheel Bearings:  Shielded Roller Bearings  Blade Tip Speed: 16,732 FPM  Blade Spindles: 3 Cast Iron  Blade Spindle Bearings:  Shielded Ball Bearings (2) Per Spindle  Blade Composition:  Heat-Treated Alloy Steel  Blade Overlap: 1-1/8 In.  Blade Dimensions:  (3) 24-1/2 In. x 2-1/4 In. x 1/4 In.  Belts: 5VX, Polyester/Cogged  Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers  Front Roller Kit: Optional</p>	

**GM2072R Rear Discharge Grooming Mower with Rear Chain Shields**

Code	Description	List price(USD)
	Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 600 lbs. Mulching Kit Available 1 Year Warranty	
	<b>BASE MACHINE</b>	
0482XF	<i>iMatch and iMatchconversion kit ordered separately.</i> GM2072R Rear Discharge Grooming Mower with Rear Chain Shields	\$5,556.00
	<b>WHEELS AND TIRES</b>	
	<b>Basic Factory Options</b>	
	<b>WHEELS AND TIRES</b>	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	\$100.00
	<b>FRAME</b>	
	<b>Field Installed Options</b>	
	<b>ROLLERS</b>	
9450	Front Anti-Scalping Roller	\$192.00
	<b>CONVERSION KIT</b>	
9630	I-Match Conversion Kit	\$486.00
	<b>CUTTING UNITS</b>	
	<b>Field Installed Options</b>	
	<b>MULCH KITS</b>	
9690	Mulching Kit GM2072	\$575.00
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
5BP002800	iMatch Conversion Kit	\$534.60
5BP0099915	Front Antiscalping Roller	\$210.11
5BP046700	Mulching Kit (GM2072)	\$632.51
BLV11200	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	\$275.00



## GM2072R Rear Discharge Grooming Mower with Rear Chain Shields

Code	Description	List price(USD)
	<p><i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i></p> <p><i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i></p>	

**GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller**

Code	Description	List price(USD)
	<b>GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller</b>	
	<p>Three High-Suction Blades Standard iMatch Compatible (Quick-Attach System) 4 Swivel Tires - Solid or Pneumatic Spindle Shafts Greased from the Top for Easy Service Type: Rear Discharge Tractor PTO Speed: 540 RPM Tractor Horsepower: 25 to 50 HP Shipping Weight: 769 lbs. Mower Deck HP: 50 HP Hitch: Category I Gearbox Ratio: 1:3:09 (Spiral Gears) Driveline: 1-3/8 In. ASAE Category III Drive Type: Gearbox Over V/Belt Deck Thickness: 8 Gauge Reinforced Deck Cutting Width: 84 In. Cutting Height Range: 1 In. to 5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3.2 In. Solid or 11 In. x 4 In. (4 Ply, with Tubes) Pneumatic Caster Wheel Bearings: Shielded Roller Bearings Blade Tip Speed: 16,338 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Shielded Ball Bearings (2) Per Spindle Blade Composition: Heat-Treated Alloy Steel Blade Overlap: 1-1/2 In. Blade Dimensions: (3) 28-1/2 In. x 2-1/4 In. Belts: 5VX, Polyester/Cogged</p>	



## GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price(USD)
	Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Front Roller Kit: Standard Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 690 lbs. Mulching Kit Available 1 Year Warranty	
	<b>BASE MACHINE</b>	
0483XF	<i>iMatch and iMatchconversion kit ordered separately.</i> GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller	\$6,314.00
	<b>WHEELS AND TIRES</b>	
	<b>Basic Factory Options</b>	
	<b>WHEELS AND TIRES</b>	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	\$100.00
	<b>FRAME</b>	
	<b>Field Installed Options</b>	
	<b>CONVERSION KIT</b>	
9630	I-Match Conversion Kit	\$486.00
	<b>CUTTING UNITS</b>	
	<b>Field Installed Options</b>	
	<b>MULCH KITS</b>	
9690	Mulching Kit <i>GM2084</i>	\$670.00
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
5BP002800	iMatch Conversion Kit	\$534.60
5BP047700	Mulching Kit (GM2084)	\$737.00
BLV11200	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	\$275.00
	<i>At least one tractor receiver bundle is needed per tractor.</i>	



## GM2084R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller

Code	Description	List price(USD)
	<p><i>This bundle is removable and can be used on various tractors within the compatibility.</i></p> <p><i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i></p>	



**GM2109R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller**

Code	Description	List price(USD)
	<b>GM2109R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller</b>	
	<p>Free Swinging Kick Back Blades  Double Belt Drive with No Idler  One Piece Balanced Steel Pulleys  iMatch Compatible (Quick-Attach System)  4 Swivel Tires - Solid or Pneumatic  Type: Rear Discharge  Tractor PTO Speed: 540 RPM  Tractor Horsepower: 30 to 70 HP  Shipping Weight: 1608 lbs.  Mower Deck Gearbox HP: 70 HP  Hitch: Category I  Gearbox Ratio: 1:2:08  Driveline:  1-3/8 In. ASAE Category III  Drive Type: Gearbox Over V/Belt  Deck Thickness:  8 Gauge Reinforced Deck  Cutting Width: 110 In.  Cutting Height Range:  From 1.3 In. to 5.3 In.  Cutting Height Adjustment:  Spacer On Caster  Caster Wheels:  (4) 12 In. x 4 In. Solid or  13 In. x 6.5 In. (4 Ply, with  Tubes) Air  Caster Wheel Bearings:  Shielded Roller Bearings  Blade Tip Speed: 14,998 FPM  Blade Spindles: (3) Cast Iron  Blade Spindle Bearings:  Shielded Tapered Bearings (2) Per Spindle  Blade Composition:  Heat-Treated Alloy Steel  Blade Overlap: 1-1/8 In.  Blade Dimensions:  (6) 15-7/8 In. x 2-3/4 In. x 1/4 In.</p>	

**GM2109R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller**

Code	Description	List price(USD)
	Belts: CX, Polyester/Cogged Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 1490 lbs. Front Center Roller Kit: Standard 1 Year Warranty	
	<b>BASE MACHINE</b>	
0491XF	<i>iMatch and iMatchconversion kit ordered separately.</i> GM2109R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller	\$11,118.00
	<b>WHEELS AND TIRES</b>	
	<b>Basic Factory Options</b>	
	<b>WHEELS AND TIRES</b>	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	\$237.00
	<b>FRAME</b>	
	<b>Field Installed Options</b>	
	<b>CONVERSION KIT</b>	
9630	I-Match Conversion Kit	\$486.00
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	\$275.00
	<i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5BP002800	iMatch Conversion Kit	\$534.60



**GM2190R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller**

Code	Description	List price(USD)
	<p><b>GM2190R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller</b></p> <p>Free Swinging Kick Back Blades                      Double Belt Drive with No Idler                      One Piece Balanced Steel Pulleys                      iMatch Compatible (Quick-Attach System)                      4 Swivel Tires - Solid or Pneumatic                      Type: Rear Discharge                      Tractor PTO Speed: 540 RPM                      Tractor Horsepower: 30 to 70 HP                      Shipping Weight: 1198 lbs.                      Mower Deck Gearbox HP: 70 HP                      Hitch: Category I                      Gearbox Ratio: 1:2:08                      Driveline:                      1-3/8 In. ASAE Category III                      Drive Type: Gearbox Over V/Belt                      Deck Thickness:                      8 Gauge Reinforced Deck                      Cutting Width: 90 In.                      Cutting Height Range:                      From 1.3 In. to 5.3 In.                      Cutting Height Adjustment:                      Spacer On Caster                      Caster Wheels:                      (4) 12 In. x 4 In. Solid or                      13 In. x 6.5 In. (4 Ply, with                      Tubes) Air                      Caster Wheel Bearings:                      Shielded Roller Bearings                      Blade Tip Speed: 14,106 FPM                      Blade Spindles: (3) Cast Iron                      Blade Spindle Bearings:                      Shielded Tapered Bearings (2) Per Spindle                      Blade Composition:                      Heat-Treated Alloy Steel                      Blade Overlap: 1-3/8 In.                      Blade Dimensions:                      (6) 13 In. x 2-3/4 In. x 1/4 In.</p>	

**GM2190R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller**

Code	Description	List price(USD)
	Belts: CX, Polyester/Cogged Belt Adjustment: Single Point, Slotted Track Adjustment - No Idlers Assembly/Set-Up Time: 30 Minutes (Approximate) Approximate Operating Weight: 1102 lbs. Front Center Roller Kit: Standard 1 Year Warranty	
	<b>BASE MACHINE</b>	
0492XF	<i>iMatch and iMatchconversion kit ordered separately.</i> GM2190R Rear Discharge Grooming Mower with Rear Chain Shields and Front Antiscalping Roller	\$9,516.00
	<b>WHEELS AND TIRES</b>	
	<b>Basic Factory Options</b>	
	<b>WHEELS AND TIRES</b>	
3050	Solid Gauge Wheel Tires	In Base Price
3040	Pneumatic Gauge Wheel Tires	\$237.00
	<b>FRAME</b>	
	<b>Field Installed Options</b>	
	<b>CONVERSION KIT</b>	
9630	I-Match Conversion Kit	\$486.00
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	\$275.00
	<i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5BP002800	iMatch Conversion Kit	\$534.60



## RC2048 Lift-Type Rotary Cutter

Code	Description	List price(USD)
	<p><b>RC2048 Lift-Type Rotary Cutter</b></p> <p>Cutting Width: 48 In. (1220 mm)</p> <p>Cutting Height: 1.5 to 9 In. (38 to 229 mm)</p> <p>Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm)</p> <p>Cutting Chamber Depth: 7.5 In. (190 mm)</p> <p>Tractor PTO HP Range: 18 - 45 HP</p> <p>Tractor PTO: 540 RPM</p> <p>Implement PTO: ASABE Category III PTO</p> <p>Hitch: Lift-Type Category I, Adaptable to II, iMatch, and AutoHitch Compatible</p> <p>Overall Width: 51 In. (1,291.4 mm)</p> <p>Overall Length: 86.6 In. (2,199.6 mm)</p> <p>Deck Shape: Flat-open Round Back</p> <p>Deck Type: Single</p> <p>Deck Thickness: 11 Gauge (3 mm)</p> <p>Skirt Thickness: 11 Gauge (3 mm)</p> <p>PTO Driveline Options: Shear Bolt or Slip Clutch Drivelines Available</p> <p>Gear Case HP Rating: 45 HP</p> <p>Blade Type: Heat Treated, Suction Type Blades</p> <p>Blade Thickness: 0.5 In. (13 mm)</p> <p>Blade Width: 3 In. (76 mm)</p> <p>Blade Tip Speed: 13,090 fpm (66.5 m/s)</p> <p>Blade Pan Type: Round Pan-Type Blade Holder</p> <p>Blade Pan Diameter: 22.3 In. (567 mm)</p> <p>Laminated Tire</p> <p>Use front and rear enclosures in areas where thrown objects could be hazardous.</p> <p>iMatch Hitch required with 2305 Tractor to facilitate driveline length.</p>	



## RC2048 Lift-Type Rotary Cutter

Code	Description	List price(USD)
	iMatch Hitch required if going on a 4M or 4R tractor equipped with R3/R4 tires to avoid possible interference between tractor tires and cutter front shield	
	<b>BASE MACHINE</b>	
0511XF	<i>Includes solid laminated tire kit</i> RC2048 Lift-Type Rotary Cutter	\$2,170.00
	<b>DRIVELINES</b>	
	<b>Basic Factory Options</b>	
	<b>DRIVELINES</b>	
1000	Driveline with Slip Clutch <i>Recommended.</i>	\$191.00
1010	Driveline with Shear Bolt	In Base Price
	<b>FRAME AND FEATURES</b>	
	<b>Basic Factory Options</b>	
	<b>ENCLOSURES</b>	
	<i>Use enclosures in areas where thrown objects could be hazardous.</i>	
2000	Front and Rear Chain Enclosure <i>Recommended.</i>	\$279.00
2010	Front Rubber with Foot Guards and Rear Metal Enclosure	In Base Price
2020	Front Chain and No Rear Enclosure	\$68.00
2030	Front Rubber with Foot Guards and No Rear Enclosure	(\$41.00)
2040	No Front or Rear Enclosure	(\$71.00)
	<b>DESTINATION AND LANGUAGE</b>	
	<b>Field Installed Options</b>	
	<b>OPERATOR'S MANUAL AND DECALS</b>	
904N	French OM & Decal Kit (RC20)	\$161.00
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
5TIFC711289	French Operator's Manual and Decal Kit for RC20 Series Rotary Cutters	\$177.11
BLV11201	John Deere Quik-Knect Driveline Yoke Bundle	\$275.00



## RC2048 Lift-Type Rotary Cutter

Code	Description	List price(USD)
	<p><i>BLV11201 is compatible with:</i></p> <ul style="list-style-type: none"> <li>- RC2048 w/ Slip Clutch Driveline Serial Number Range 048199 &amp; up</li> <li>- RC2048 w/ Shear Pin Driveline Serial Number Range 040602 &amp; up</li> </ul> <p><i>Tractor Receiver Part number: BLV10953</i></p> <p><i>At least one tractor receiver bundle is needed per tractor.                      This bundle is removable and can be used on various tractors within the compatibility.</i></p> <p><i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i></p>	



### RC2060 Lift-Type Rotary Cutter

Code	Description	List price(USD)
<b>RC2060 Lift-Type Rotary Cutter</b>		
	Cutting Width: 60 In. (1524 mm) Cutting Height: 1.5 to 9 In. (38 to 229 mm) Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm) Cutting Chamber Depth: 7.5 In. (190 mm) Tractor PTO HP Range: 19 - 65 HP Tractor PTO: 540 RPM Implement PTO: ASABE Category III PTO Hitch: Lift-Type Category I, Adaptable to II, iMatch, and AutoHitch Compatible Overall Width: 63 In. (1,600.2 mm) Overall Length: 101.2 In. (2,570.5 mm) Deck Shape: Flat-open Round Back Deck Type: Single Deck Thickness: 11 Gauge (3 mm) Skirt Thickness: 11 Gauge (3 mm) PTO Driveline Options: Shear Bolt or Slip Clutch Drivelines Available Gear Case HP Rating: 65 HP Blade Type: Heat Treated, Suction Type Blades Blade Thickness: 0.5 In. (13 mm) Blade Width: 3 In. (76 mm) Blade Tip Speed: 14,355 fpm (72.8 m/s) Blade Pan Type: Round Pan-Type Blade Holder Blade Pan Diameter: 22.3 In. (567 mm) Laminated Tire iMatch Hitch required if going on a 4M or 4R tractor equipped with R3/R4 tires to avoid possible interference between tractor tires and cutter front shield	
<b>BASE MACHINE</b>		
0512XF	Includes solid laminated tire kit RC2060 Lift-Type Rotary Cutter	\$2,441.00





## RC2060 Lift-Type Rotary Cutter

Code	Description	List price(USD)
<b>DRIVELINES</b> <b>Basic Factory Options</b> <b>DRIVELINES</b>		
1000	Driveline with Slip Clutch <i>Recommended.</i>	\$207.00
1010	Driveline with Shear Bolt	In Base Price
<b>FRAME AND FEATURES</b> <b>Basic Factory Options</b> <b>ENCLOSURES</b> <i>Use enclosures in areas where thrown objects could be hazardous.</i>		
2000	Front and Rear Chain Enclosure <i>Recommended.</i>	\$337.00
2010	Front Rubber with Foot Guards and Rear Metal Enclosure	In Base Price
2020	Front Chain and No Rear Enclosure	\$83.00
2030	Front Rubber with Foot Guards and No Rear Enclosure	(\$44.00)
2040	No Front or Rear Enclosure	(\$67.00)
<b>DESTINATION AND LANGUAGE</b> <b>Field Installed Options</b> <b>OPERATOR'S MANUAL AND DECALS</b>		
904N	French OM & Decal Kit (RC20)	\$161.00
<b>MISCELLANEOUS</b> <b>ATTACHMENTS FOR FIELD CONVERSION</b> <b>MISCELLANEOUS</b>		
5TIFC711289	French Operator's Manual and Decal Kit for RC20 Series Rotary Cutters	\$177.11
BLV11201	John Deere Quik-Knect Driveline Yoke Bundle <i>BLV11201 is compatible with:</i> - RC2060 and RC2072 w/ Slip Clutch Driveline Serial Number Range 063419 & up - RC2060 and RC2072 w/ Shear Pin Driveline Serial Number Range 048269 & up Tractor Receiver Part number: BLV10953  <i>At least one tractor receiver bundle is needed per tractor.</i>	\$275.00



### RC2060 Lift-Type Rotary Cutter

Code	Description	List price(USD)
	<p><i>This bundle is removable and can be used on various tractors within the compatibility.</i></p> <p><i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i></p>	



## RC2072 Lift-Type Rotary Cutter

Code	Description	List price(USD)
	<p><b>RC2072 Lift-Type Rotary Cutter</b></p> <p>Cutting Width: 72 In. (1,830 mm)</p> <p>Cutting Height: 1.5 to 9 In. (38 to 229 mm)</p> <p>Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm)</p> <p>Cutting Chamber Depth: 7.5 In. (190 mm)</p> <p>Tractor PTO HP Range: 25 - 65 HP</p> <p>Tractor PTO: 540 RPM</p> <p>Implement PTO: ASABE Category III PTO</p> <p>Hitch: Lift-Type Category I, Adaptable to II, iMatch, and AutoHitch Compatible</p> <p>Overall Width: 75 In. (1,905 mm)</p> <p>Overall Length: 111.5 In. (2,832.1 mm)</p> <p>Deck Shape: Flat-open Round Back</p> <p>Deck Type: Single</p> <p>Deck Thickness: 11 Gauge (3 mm)</p> <p>Skirt Thickness: 11 Gauge (3 mm)</p> <p>PTO Driveline Options: Shear Bolt or Slip Clutch Drivelines Available</p> <p>Gear Case HP Rating: 65 HP</p> <p>Blade Type: Heat Treated, Suction Type Blades</p> <p>Blade Thickness: 0.5 In. (13 mm)</p> <p>Blade Width: 3 In. (76 mm)</p> <p>Blade Tip Speed: 14,955 fpm (76 m/s)</p> <p>Blade Pan Type: Round Pan-Type Blade Holder</p> <p>Blade Pan Diameter: 28.5 In. (723.9 mm)</p> <p>Laminated Tire iMatch Hitch required if going on a 4M or 4R tractor equipped with R3/R4 tires to avoid possible interference between tractor tires and cutter front shield</p>	
	<p><b>BASE MACHINE</b></p> <p><i>Includes solid laminated tire kit</i></p>	



## RC2072 Lift-Type Rotary Cutter

Code	Description	List price(USD)
0513XF	RC2072 Lift-Type Rotary Cutter	\$2,802.00
	<b>DRIVELINES</b> <b>Basic Factory Options</b> <b>DRIVELINES</b>	
1000	Driveline with Slip Clutch <i>Recommended.</i>	\$207.00
1010	Driveline with Shear Bolt	In Base Price
	<b>FRAME AND FEATURES</b> <b>Basic Factory Options</b> <b>ENCLOSURES</b> <i>Use enclosures in areas where thrown objects could be hazardous.</i>	
2000	Front and Rear Chain Enclosure <i>Recommended.</i>	\$469.00
2010	Front Rubber with Foot Guards and Rear Metal Enclosure	In Base Price
2020	Front Chain and No Rear Enclosure	\$125.00
2030	Front Rubber with Foot Guards and No Rear Enclosure	(\$57.00)
2040	No Front or Rear Enclosure	(\$81.00)
	<b>DESTINATION AND LANGUAGE</b> <b>Field Installed Options</b> <b>OPERATOR'S MANUAL AND DECALS</b>	
904N	French OM & Decal Kit (RC20)	\$161.00
	<b>MISCELLANEOUS</b> <b>ATTACHMENTS FOR FIELD CONVERSION</b> <b>MISCELLANEOUS</b>	
5TIFC711289	French Operator's Manual and Decal Kit for RC20 Series Rotary Cutters	\$177.11
BLV11201	John Deere Quik-Knect Driveline Yoke Bundle <i>BLV11201 is compatible with:</i> <i>- RC2060 and RC2072 w/ Slip Clutch Driveline Serial Number Range 063419 &amp; up</i> <i>- RC2060 and RC2072 w/ Shear Pin Driveline Serial Number Range 048269 &amp; up</i> <i>Tractor Receiver Part number: BLV10953</i>	\$275.00



### RC2072 Lift-Type Rotary Cutter

Code	Description	List price(USD)
	<p><i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i></p> <p><i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i></p>	



## RC2084 Lift-Type Rotary Cutter

Code	Description	List price(USD)
	<p><b>RC2084 Lift-Type Rotary Cutter</b></p> <p>Cutting Width: 84 In. (2,134 mm)</p> <p>Cutting Height: 1.75 to 11 In. (44.45 to 279.4 mm)</p> <p>Cutting Capacity (Diameter): 0 to 1 In. (0 to 25 mm)</p> <p>Cutting Chamber Depth: 9.75 In. (248 mm)</p> <p>Tractor PTO HP Range: 45 - 90 HP</p> <p>Tractor PTO: 540 RPM</p> <p>Implement PTO: ASABE Category III PTO</p> <p>Hitch: Lift-Type Category II, Category II Quick Hitch Compatible</p> <p>Overall Width: 88 In. (2,235 mm)</p> <p>Overall Length: 124 In. (3,150 mm)</p> <p>Deck Shape: Flat-open Round Back</p> <p>Deck Type: Single</p> <p>Deck Thickness: 10 Gauge (3.4 mm)</p> <p>Skirt Thickness: 10 Gauge (3.4 mm)</p> <p>PTO Driveline Options: Slip Clutch Standard</p> <p>Gear Case HP Rating: 90 HP</p> <p>Blade Type: Heat Treated, Suction Type Blades</p> <p>Blade Thickness: 0.5 In. (13 mm)</p> <p>Blade Width: 3 In. (76 mm)</p> <p>Blade Tip Speed: 14,380 fpm (73 m/s)</p> <p>Blade Pan Type: Round Pan-Type Blade Holder</p> <p>Blade Pan Diameter: 32.5 In. (825.5 mm)</p> <p>Tire Options: Single or Dual Laminated Tire</p> <p>iMatch Hitch required if going on a 4M or 4R tractor equipped with R3/R4 tires to avoid possible interference between tractor tires and cutter front shield</p>	
	<b>BASE MACHINE</b>	



## RC2084 Lift-Type Rotary Cutter

Code	Description	List price(USD)
0514XF	RC2084 Lift-Type Rotary Cutter	\$5,200.00
	<b>FRAME AND FEATURES</b>	
	<b>Basic Factory Options</b>	
	<b>ENCLOSURES</b>	
	<i>Use enclosures in areas where thrown objects could be hazardous.</i>	
2000	Front and Rear Chain Enclosure <i>Recommended.</i>	In Base Price
2010	Front Rubber with Foot Guards and Rear Metal Enclosure	(\$306.00)
2020	Front Chain and No Rear Enclosure	(\$222.00)
2030	Front Rubber with Foot Guards and No Rear Enclosure	(\$387.00)
2040	No Front or Rear Enclosure	(\$471.00)
	<b>WHEELS AND TIRES</b>	
	<b>Basic Factory Options</b>	
	<b>WHEELS AND TIRES</b>	
3000	Laminated Tire	In Base Price
3010	Dual Tire Laminated	\$147.00
	<b>DESTINATION AND LANGUAGE</b>	
	<b>Field Installed Options</b>	
	<b>OPERATOR'S MANUAL AND DECALS</b>	
904N	French OM & Decal Kit (RC20)	\$161.00
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
5TIFC711289	French Operator's Manual and Decal Kit for RC20 Series Rotary Cutters	\$177.11
BLV11203	John Deere Quik-Knect Driveline Yoke Bundle <i>BLV11203 is compatible with RC2084 w/ Slip Clutch Driveline Serial Number Range 105933 &amp; up</i> <i>Tractor Receiver Part number: BLV10953</i>	\$275.00
	<i>At least one tractor receiver bundle is needed per tractor.</i> <i>This bundle is removable and can be used on various tractors within the compatibility.</i>	



### RC2084 Lift-Type Rotary Cutter

Code	Description	List price(USD)
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	





## FM3012 Rear Discharge Flex-Wing Grooming Mower with Light Bar

Code	Description	List price(USD)
<b>FM3012 Rear Discharge Flex-Wing Grooming Mower with Light Bar</b>		
	10 ea. 10 x 4 in. Solid Rubber Gauge Wheels 2 ea. 20.5 x 8.75 in. Non-Highway Speed Rated Transport Tires 10 Gauge Reinforced Deck Wing Float: 20 degrees up / 15 degrees down Deck Overlap: 6 In. Blade Overlap: 1.5 In. Blade Spindles: (9) Cast Iron Blade Dimensions: (9) .25 x 2.5 In. Belts: B-Section, Kevlar Tractor PTO Speed: 540 RPM Overall Machine Width: 12 Ft. 7 In. Working Machine Width: 12 Ft. 5 In. Transport Width: 7 Ft. 9 In. Transport Length: 10 Ft. 6 In. Machine Weight: 1,750 lbs. HP Requirements: 25 - 60 HP Cutting Height from 1 In. to 4.5 In. Blade Tip Speed: 16,200 Ft./Minute Type: Rear Discharge Front Antiscalping Roller: Standard (3 per deck) Input Driveline: Gear Box over V-Belt Input Driveline: ASAE Category III CV Wing Driveline: ASAE Category III Shipping Weight: 2,095 lbs. Set-up Time: 1.25 Hrs. 1 Year Machine Warranty 3 Year Residential Gear Box Warranty	
<b>BASE MACHINE</b>		
0551XF	FM3012 Rear Discharge Flex-Wing Grooming Mower with Light Bar	\$22,166.00
<b>FRAME</b> <b>Basic Factory Options</b> <b>CHAIN ENCLOSURES</b>		
2000	Rear Chain Shield	No Added Cost
2095	Less Rear Chain Shield	(\$466.00)

**FM3012 Rear Discharge Flex-Wing Grooming Mower with Light Bar**

Code	Description	List price(USD)
	<b>WHEELS AND TIRES</b>	
	<b>Basic Factory Options</b>	
	<b>WHEELS AND TIRES</b>	
3000	Highway Rated Tires	In Base Price
3010	Non-Highway Rated Tires	(\$257.00)
	<b>HYDRAULICS</b>	
	<b>Field Installed Options</b>	
	<b>HYDRAULIC KITS</b>	
9000	Hydraulic Wing Latch Release Kit	\$798.00
	<b>MISCELLANEOUS</b>	
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
5WD1031385	Light Bar Kit (FM10 Series and FM3012) <i>Serial Number 1XFFM10XAB0000106 and above on the FM10 Series and all FM30 Series Mowers.</i>	\$883.31
5WD1029535	Hydraulic Wing Latch Release Kit (FM3012)	\$877.80
5WD1008038	Rear Chain Shield Kit - Rear Discharge (GM3054 & FM3012) <i>Quantity of (3) required for FM3012 as each deck requires quantity of (1).</i>	\$166.11



### GM4060E Rear Discharge Grooming Mower

Code	Description	List price(USD)
<b>GM4060E Rear Discharge Grooming Mower</b>		
Tractor PTO Horsepower: 15 to 35 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Operating Weight: 481 lbs. Hitch: Category I Driveline: Category 2 Drive Type: Gearbox Over V-Belt Deck Thickness: 8 Gauge Steel Plate Cutting Width: 60 In. Cutting Height Range: 1 In. to 4.5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 18,030 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Ball Bearings Blade Overlap: 1-1/2 In. Blade Dimensions: (3) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 15 Minutes (Approximate) Approximate Operating Weight: 503 lbs. Front Roller Kit: Optional		
<b>BASE MACHINE</b>		
0591XF	GM4060E Rear Discharge Grooming Mower	\$4,239.00
<b>DESTINATION AND LANGUAGE</b>		
<b>Basic Factory Options</b>		
<b>DESTINATION</b>		
0202	United States	No Added Cost
<b>OPERATOR'S MANUAL AND DECALS</b>		

**GM4060E Rear Discharge Grooming Mower**

Code	Description	List price(USD)
0409	English OM	No Added Cost
0413	French OM & Decal Kit	No Added Cost
0437	Spanish OM & Decal Kit	No Added Cost
	<b>MISCELLANEOUS</b>	
	<b>Field Installed Options</b>	
	<b>MISCELLANEOUS</b>	
9640	Front anti-scalp roller kit	\$140.00
9641	Rear anti-scalp roller kit	\$86.00
9642	GM4060E Rear chain shield	\$161.00
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	\$275.00
	<i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5WD616079	FRONT ANTI-SCALP ROLLER KIT	\$154.00
5WD616090	SPANISH OM and DECAL KIT	\$580.80
5WD618210	REAR ANTI-SCALP ROLLER KIT	\$94.60
5WD613747	FRENCH OM and DECAL KIT	\$580.80
5WD616077	REAR CHAIN SHIELD (60)	\$177.11
5WD616076	REAR CHAIN SHIELD (72)	\$200.20
BLV10953	John Deere Quik Knect™ PTO receiver	\$205.70



## GM4072E Rear Discharge Grooming Mower

Code	Description	List price(USD)
<b>GM4072E Rear Discharge Grooming Mower</b>		
	Tractor Horsepower: 20 to 35 HP Type: Rear Discharge Tractor PTO Speed: 540 RPM Shipping Weight: 689 lbs. Mower Deck Gearbox HP: 35 HP Hitch: Category I Gearbox Ratio: 1:1.92 Driveline: Category III Drive Type: Gearbox Over V-Belt Deck Thickness: 8 Gauge Steel Plate Cutting Width: 72 In. Cutting Height Range: 1 In. to 4.5 In. Cutting Height Adjustment: Spacer On Caster Caster Wheels: (4) 10 In. x 3-1/4 In. Solid Caster Wheel Bearings: Roller Bearings Blade Tip Speed: 18,000 FPM Blade Spindles: 3 Cast Iron Blade Spindle Bearings: Ball Bearings Blade Overlap: 1 1/2 In. Blade Dimensions: (3) 1/4 In. x 2-1/2 In. Blade Composition: Heat-Treated Alloy Steel Belts: B Section, Aramid/Kevlar Belt Adjustment: Spring-Loaded Idler Assembly/Set-Up Time: 15 Minutes (Approximate) Approximate Operating Weight: 603 lbs. Front Roller Kit: Optional	
<b>BASE MACHINE</b>		
0611XF	GM4072E Rear Discharge Grooming Mower	\$4,569.00
<b>DESTINATION AND LANGUAGE</b>		
<b>Basic Factory Options</b>		
<b>DESTINATION</b>		



## GM4072E Rear Discharge Grooming Mower

Code	Description	List price(USD)
0202	United States	No Added Cost
	<b>OPERATOR'S MANUAL AND DECALS</b>	
0409	English OM	No Added Cost
0413	French OM & Decal Kit	No Added Cost
0437	Spanish OM & Decal Kit	No Added Cost
	<b>MISCELLANEOUS</b>	
	<b>Field Installed Options</b>	
	<b>MISCELLANEOUS</b>	
9640	Front anti-scalp roller kit	\$140.00
9641	Rear anti-scalp roller kit	\$86.00
9643	GM4072E Rear chain shield	\$182.00
	<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
	<b>MISCELLANEOUS</b>	
BLV11178	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i>	\$275.00
	<i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i>	
	<i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	
5WD616090	SPANISH OM and DECAL KIT	\$580.80
5WD618210	REAR ANTI-SCALP ROLLER KIT	\$94.60
5WD616076	REAR CHAIN SHIELD (72)	\$200.20
5WD613747	FRENCH OM and DECAL KIT	\$580.80
5WD616079	FRONT ANTI-SCALP ROLLER KIT	\$154.00
5WD616077	REAR CHAIN SHIELD (60)	\$177.11
BLV10953	John Deere Quik Knect™ PTO receiver	\$205.70



## Material Collection System - 14-Bu 3-Bag

Code	Description	List price(USD)
<b>Material Collection System - 14-Bu 3-Bag</b>		
	14-BU 3-BAG Material Collection System 3-Bag Collection Hopper Capacity: 14 Bushels Hitch: CAT I 3-point Mounted iMatch Compatible Rear PTO Gearbox Driven Blower 5 Blade High Efficiency Synthetic 15" Impeller Impeller Speed: 2250 RPM Steel Impeller Housing Boot to Blower Hose Diameter: 8 inches Bag Material: Frame Material: Sight Glass Fill Indicator or Wireless Fill Alarm Sensor Option High Efficiency Blow Molded Inducer and Transition Chute Easy-To-Empty Bags Fully and Evenly Filled Bags Tool-less access to chute for easy clog removal Tool-less boot removal and installation for quick changing of implements	
<b>BASE MACHINE</b>		
0721XF	Material Collection System - 14-Bu 3-Bag	\$4,570.00
<b>DESTINATION AND LANGUAGE</b>		
<b>Basic Factory Options</b>		
<b>DESTINATION</b>		
0202	United States	No Added Cost
0184	Canada	No Added Cost
0205	Quebec, Canada	No Added Cost
<b>OPERATOR'S MANUAL</b>		
0409	English OM	No Added Cost
0413	French OM	No Added Cost
0437	Spanish OM	No Added Cost
<b>DECK BOOT</b>		
<b>Basic Factory Options</b>		
<b>DECK BOOT</b>		
	<i>Includes boot, hardware, and hose</i>	



### Material Collection System - 14-Bu 3-Bag

Code	Description	List price(USD)
2963	54D DECK BOOT KIT (MY19 and Older) <i>Only Available with 2551 Electric DFS</i>	(\$48.00)
2964	54D DECK BOOT KIT (MY20+) <i>Only Available with 2551 Electric DFS</i>	(\$61.00)
2962	60D DECK BOOT KIT	No Added Cost
	<b>MISCELLANEOUS</b>	
	<b>Additional Factory Options</b>	
	<b>MISCELLANEOUS</b>	
9702	Fill Sensor (Wireless)	\$172.00
9315	Caster Wheel Storage Kit	\$68.00
9701	Road Lighting Kit (1E, 1R, 2R) <i>Note: Includes ROPS light extension brackets and extension harnesses, SMV</i>	\$233.00





## Material Collection System - 20-Bu Dump from Seat

Code	Description	List price(USD)
	<p><b>Material Collection System - 20-Bu Dump from Seat</b>            20-BU Dump from Seat - Material Collection System            Aluminum Hopper Capacity: 20 Bushels            Hitch: CAT I 3-point Mounted            iMatch Compatible            Mechanical Dump From Operator Seat or Electric Option            Rear PTO Gearbox Driven Blower            5 Blade High Efficiency Synthetic 15" Impeller            Impeller Speed: 2250-3250 RPM            Steel Impeller Housing            Boot to Blower Hose Diameter: 8 inches            Frame Material:            Sight Glass Fill Indicator or Wireless Fill Alarm Sensor Option            High Efficiency Blow Molded Inducer and Transition Chute            Tool-less access to chute for easy clog removal            Tool-less boot removal and installation for quick changing of implements</p>	
	<b>BASE MACHINE</b>	
0731XF	Material Collection System - 20-Bu Dump from Seat	\$6,043.00
	<b>DESTINATION AND LANGUAGE</b>	
	<b>Basic Factory Options</b>	
	<b>DESTINATION</b>	
0202	United States	No Added Cost
0184	Canada	No Added Cost
0205	Quebec, Canada	No Added Cost
	<b>OPERATOR'S MANUAL</b>	
0409	English OM	No Added Cost
0413	French OM	No Added Cost
0437	Spanish OM	No Added Cost
	<b>DECK BOOT</b>	
	<b>Basic Factory Options</b>	
	<b>DECK BOOT</b>	
	<i>Includes boot, hardware, and hose</i>	
2963	54D DECK BOOT KIT (MY19 and Older) <i>Only Available with 2551 Electric DFS</i>	(\$48.00)



## Material Collection System - 20-Bu Dump from Seat

Code	Description	List price(USD)
2964	54D DECK BOOT KIT (MY20+) <i>Only Available with 2551 Electric DFS</i>	(\$61.00)
2962	60D DECK BOOT KIT	No Added Cost
2961	72D DECK BOOT KIT (2RLC,3R)	(\$50.00)
<b>UNLOAD MATERIAL</b> <b>Basic Factory Options</b> <b>DUMP FROM SEAT</b>		
2251	ELECTRIC DUMP-FROM-SEAT (1E, 1R, 2R) <i>Includes Wiring harness and Switch for 1E, 1R, 2R Tractors and Electric Actuator</i>	No Added Cost
2252	ELECTRIC DUMP-FROM-SEAT (3R) <i>Includes Wiring harness and Switch for 3R Tractors and Electric Actuator</i>	(\$72.00)
<b>MISCELLANEOUS</b> <b>Additional Factory Options</b> <b>MISCELLANEOUS</b>		
9702	Fill Sensor (Wireless)	\$172.00
9315	Caster Wheel Storage Kit	\$68.00
9701	Road Lighting Kit (1E, 1R, 2R) <i>Note: Includes ROPS light extension brackets and extension harnesses, SMV</i>	\$233.00
9700	Road Lighting Kit (3R) <i>Note: Includes 7-pin connector, tail lamps, and SMV sign</i>	\$560.00