

**HP2025 - Hydraulic Power Unit, 25 HP - U.S.**

| Code | Description | List price(USD) |
|--------|--|-----------------|
| | HP2025 - Hydraulic Power Unit, 25 HP - U.S. Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes | |
| | BASE MACHINE <i>Must be used with SB2164 Snowblower and SW2160 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes rear tractor wiring harness. Front implement wiring harness is not included in base.</i> HP2025 - Hydraulic Power Unit, 25 HP - U.S. | |
| 1601XF | | \$9,301.00 |
| | HYDRAULIC AND ELECTRICAL Basic Factory Options OIL COOLER | |
| 2000 | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | In Base Price |
| 2095 | Less Oil Cooler | (\$2,376.00) |
| | Field Installed Options WIRING HARNESS | |
| 9040 | Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | \$132.00 |
| | MISCELLANEOUS | |



HP2025 - Hydraulic Power Unit, 25 HP - U.S.

| Code | Description | List price(USD) |
|---|--|-----------------|
| ATTACHMENTS FOR FIELD CONVERSION | | |
| MISCELLANEOUS | | |
| 5RDF0036 | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | \$2,613.60 |
| 5RDF0038 | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | \$145.20 |
| 5RDF0078 | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i> | \$202.40 |

**HP2134 - Hydraulic Power Unit, 34 HP - U.S.**

| Code | Description | List price(USD) |
|--------|---|-----------------|
| | HP2134 - Hydraulic Power Unit, 34 HP - U.S. Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes | |
| | BASE MACHINE <i>Must be used with SB2176 Snowblower and SW2184 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes rear tractor wiring harness. Front implement wiring harness is not included in base.</i> | |
| 1611XF | HP2134 - Hydraulic Power Unit, 34 HP - U.S. | \$9,462.00 |
| | HYDRAULIC AND ELECTRICAL | |
| | Basic Factory Options | |
| | OIL COOLER | |
| 2000 | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | In Base Price |
| 2095 | Less Oil Cooler | (\$2,376.00) |
| | Field Installed Options | |
| | WIRING HARNESS | |
| 9040 | Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | \$132.00 |
| | MISCELLANEOUS | |

**HP2134 - Hydraulic Power Unit, 34 HP - U.S.**

| Code | Description | List price(USD) |
|---|--|-----------------|
| ATTACHMENTS FOR FIELD CONVERSION | | |
| MISCELLANEOUS | | |
| 5RDF0036 | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | \$2,613.60 |
| 5RDF0038 | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | \$145.20 |
| 5RDF0078 | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i> | \$202.40 |

**AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier**

| Code | Description | List price(USD) |
|-------------|--|-----------------|
| | AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier Cutting Width: 73.75 In. Loader Series: 300 and 400 Only (Not 500 Series) Dimensions: W74.5 In. x H30.75 In. x D34 In. Capacity: 3.5 Cubic Foot Operational Weight: 440 lbs. Shipping Weight: 490 lbs. | |
| 2191XF | BASE MACHINE <i>Fixed cutting edge is rubber.</i> <i>Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i> AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier | \$2,693.00 |
| 9200 | DESTINATION AND LANGUAGE Field Installed Options OPERATOR'S MANUAL AND DECAL KIT French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push | No Added Cost |
| 5MP43052 | MISCELLANEOUS ATTACHMENTS FOR FIELD CONVERSION MISCELLANEOUS FRENCH OM/DECAL-LDR ATTACHMENTS | \$134.32 |
| 5MP76312XES | French Operator's Manual and Decal Kit | See Parts |



AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

| Code | Description | List price(USD) |
|-------------|--|-----------------|
| | <p>AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier</p> <p>Cutting Width: 85.75 In. Loader Series: 300 and 400 Only (Not 500 Series) Dimensions: W86.25 In. x H30.75 In. x D34 In. Capacity: 4 Cubic Foot Operational Weight: 477 lbs. Shipping Weight: 527 lbs.</p> | |
| | <p>BASE MACHINE</p> <p><i>Fixed cutting edge is rubber. Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i></p> | |
| 2192XF | AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier | \$2,984.00 |
| | <p>DESTINATION AND LANGUAGE</p> <p>Field Installed Options</p> <p>OPERATOR'S MANUAL AND DECAL KIT</p> | |
| 9200 | French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push | No Added Cost |
| | <p>MISCELLANEOUS</p> <p>ATTACHMENTS FOR FIELD CONVERSION</p> <p>MISCELLANEOUS</p> | |
| 5MP43052 | FRENCH OM/DECAL-LDR ATTACHMENTS | \$134.32 |
| 5MP76312XES | French Operator's Manual and Decal Kit | See Parts |



AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier

| Code | Description | List price(USD) |
|-------------|--|-----------------|
| | <p>AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier</p> <p>Cutting Width: 85.75 In. Loader Series: 300 and 400 Only (Not 500 Series) Dimensions: W86.25 In. x H30.75 In. x D34 In. Capacity: 4 Cubic Foot Operational Weight: 477 lbs. Shipping Weight: 527 lbs.</p> | |
| | <p>BASE MACHINE</p> <p><i>Fixed cutting edge is rubber. Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i></p> | |
| 2193XF | AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier | \$3,299.00 |
| | <p>DESTINATION AND LANGUAGE</p> <p>Field Installed Options</p> <p>OPERATOR'S MANUAL AND DECAL KIT</p> | |
| 9200 | French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push | No Added Cost |
| | <p>MISCELLANEOUS</p> <p>ATTACHMENTS FOR FIELD CONVERSION</p> <p>MISCELLANEOUS</p> | |
| 5MP43052 | FRENCH OM/DECAL-LDR ATTACHMENTS | \$134.32 |
| 5MP76312XES | French Operator's Manual and Decal Kit | See Parts |

**AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier**

| Code | Description | List price(USD) |
|----------|--|-----------------|
| | AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier Cutting Width: 98 In. Loader Series: 300, 400, and 500 Dimensions: W98.38 In. x H39.8 In. x D41.5 In. Capacity: 7 Cubic Foot Optional Bolt-on Pull Back Kit Weight: 163 lbs. Operational Weight: 900 lbs. Shipping Weight: 950 lbs. | |
| | BASE MACHINE <i>Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i> AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier | \$4,772.00 |
| | DESTINATION AND LANGUAGE Field Installed Options OPERATOR'S MANUAL AND DECAL KIT | |
| 9200 | French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push | No Added Cost |
| | MISCELLANEOUS Field Installed Options BACK DRAG ATTACHMENT | |
| 9000 | Back Drag Attachment <i>For 8 Ft. Model</i> | \$960.00 |
| | RUBBER EDGE KIT | |
| 9010 | Rubber Edge Kit <i>8 Ft. Back Drag attachment required.</i> | \$513.00 |
| | ATTACHMENTS FOR FIELD CONVERSION MISCELLANEOUS | |
| 5FP10730 | Back Drag Attachment for 8 Ft. AS11E (Less Rubber Edge) | \$1,412.15 |
| 5FP10733 | Rubber Edge Kit for 8 Ft. AS11E <i>5FP10730 - 8 Ft. Back Drag attachment required.</i> | \$695.70 |



AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

| Code | Description | List price(USD) |
|-------------|--|-----------------|
| 5MP43052 | FRENCH OM/DECAL-LDR ATTACHMENTS | \$134.32 |
| 5MP76312XES | French Operator's Manual and Decal Kit | See Parts |

**AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier**

| Code | Description | List price(USD) |
|----------|--|-----------------|
| | AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier Cutting Width: 110 In. Loader Series: 300, 400, and 500 Dimensions: W110.38 In. x H39.8 In. x D41.5 In. Capacity: 7.8 Cubic Foot Optional Bolt-on Pull Back Kit Weight: 175 lbs. Operational Weight: 943 lbs. Shipping Weight: 993 lbs. | |
| | BASE MACHINE <i>Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i> AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier | \$5,250.00 |
| | DESTINATION AND LANGUAGE Field Installed Options OPERATOR'S MANUAL AND DECAL KIT | |
| 9200 | French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push | No Added Cost |
| | MISCELLANEOUS Field Installed Options BACK DRAG ATTACHMENT | |
| 9000 | Back Drag Attachment <i>For 9 Ft. Model</i> | \$997.00 |
| | RUBBER EDGE KIT | |
| 9010 | Rubber Edge Kit <i>9 Ft. Back Drag attachment required.</i> | \$571.00 |
| | ATTACHMENTS FOR FIELD CONVERSION MISCELLANEOUS | |
| 5FP10731 | Back Drag Attachment for 9 Ft. AS11E (Less Rubber Edge) | \$1,039.40 |
| 5FP10734 | Rubber Edge Kit for 9 Ft. AS11E <i>5FP10731 - 9 Ft. Back Drag attachment required.</i> | \$595.32 |



AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

| Code | Description | List price(USD) |
|-------------|--|-----------------|
| 5MP43052 | FRENCH OM/DECAL-LDR ATTACHMENTS | \$134.32 |
| 5MP76312XES | French Operator's Manual and Decal Kit | See Parts |

**AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier**

| Code | Description | List price(USD) |
|----------|---|-----------------|
| | AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier Cutting Width: 119.5 In. Loader Series: 300, 400, and 500 Dimensions: W110.875 In. x H39.8 In. x D41.5 In. Capacity: 8.5 Cubic Foot Optional Bolt-on Pull Back Kit Weight: 185 lbs. Operational Weight: 980 lbs. Shipping Weight: 1030 lbs. | |
| | BASE MACHINE <i>Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i> AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier | \$5,714.00 |
| 2203XF | | |
| | DESTINATION AND LANGUAGE Field Installed Options OPERATOR'S MANUAL AND DECAL KIT | |
| 9200 | French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push | No Added Cost |
| | MISCELLANEOUS Field Installed Options BACK DRAG ATTACHMENT | |
| 9000 | Back Drag Attachment <i>For 10 Ft. Model</i> | \$1,045.00 |
| | RUBBER EDGE KIT | |
| 9010 | Rubber Edge Kit <i>10 Ft. Back Drag attachment required.</i> | \$626.00 |
| | ATTACHMENTS FOR FIELD CONVERSION MISCELLANEOUS | |
| 5FP10732 | Back Drag Attachment for 10 Ft. AS11E (Less Rubber Edge) | \$1,090.22 |
| 5FP10735 | Rubber Edge Kit for 10 Ft. AS11E <i>5FP10732 - 10 Ft. Back Drag attachment required.</i> | \$652.20 |



AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

| Code | Description | List price(USD) |
|-------------|--|-----------------|
| 5MP43052 | FRENCH OM/DECAL-LDR ATTACHMENTS | \$134.32 |
| 5MP76312XES | French Operator's Manual and Decal Kit | See Parts |

**AS10F - 48 in. Snow Push**

| Code | Description | List price(USD) |
|--------------|---|-----------------|
| | AS10F - 48 in. Snow Push Cutting Width: 48 In. Base unit includes: Steel cutting edge, steel skid shoes Loader Compatibility: D120/H120/120R Dimensions: 19.3"Hx21.6"Dx50.6"W Capacity: 11.6 cu ft Operational Weight: 142 lbs. Shipping Weight: lbs. | |
| | BASE MACHINE | |
| 2411XF | AS10F - 48 in. Snow Push | \$961.00 |
| | DESTINATION AND LANGUAGE Basic Factory Options DESTINATION AND LANGUAGE | |
| 0202 | United States | In Base Price |
| 0184 | Canada | No Added Cost |
| | OPERATOR'S MANUAL AND DECAL KIT | |
| 0409 | English Operator's Manual and Decal Kit | In Base Price |
| 0437 | Spanish Operator's Manual and Decal Kit | No Added Cost |
| 0413 | French Operator's Manual and Decal Kit | No Added Cost |
| | MISCELLANEOUS Field Installed Options BACK DRAG ATTACHMENT | |
| 9205 | Back Drag Kit with Steel Edge - 48 in. | \$213.00 |
| 9206 | Back Drag Kit with Rubber Edge - 48 in. | \$257.00 |
| | RUBBER EDGE KIT | |
| 9843 | Rubber Edge Kit - 48 in. | \$177.00 |
| | SKID SHOES | |
| 9863 | Poly Skid Shoes Kit (2 included) | \$275.00 |
| | ATTACHMENTS FOR FIELD CONVERSION MISCELLANEOUS | |
| 5MP43052 | FRENCH OM/DECAL-LDR ATTACHMENTS | \$134.32 |
| 5FP110404804 | AS10F (48 in.) Back Drag Kit with Steel Edge | \$277.33 |
| 5FP110434804 | AS10F (48 in.) Rubber Edge Kit | \$234.00 |

**AS10F - 48 in. Snow Push**

| Code | Description | List price(USD) |
|--------------|---|-----------------|
| 5FP110414804 | AS10F (48 in.) Back Drag Kit with Rubber Edge | \$341.25 |
| 5FP281104204 | AS10F Poly Skid Shoe Kit | \$364.79 |
| 5MP76312XES | French Operator's Manual and Decal Kit | See Parts |

**AS10F - 60 in. Snow Push**

| Code | Description | List price(USD) |
|--------------|---|-----------------|
| | AS10F - 60 in. Snow Push Cutting Width: 60 In. Base unit includes: Steel cutting edge, steel skid shoes Loader Series: 200X/200CX/H130/220R/D160/305/H160/H165 Dimensions: 19.3"Hx21.6"Dx62.6"W Capacity: 14.5 cu ft Operational Weight: 160 lbs. Shipping Weight: lbs. | |
| | BASE MACHINE | |
| 2412XF | AS10F - 60 in. Snow Push | \$1,025.00 |
| | DESTINATION AND LANGUAGE Basic Factory Options DESTINATION AND LANGUAGE | |
| 0202 | United States | In Base Price |
| 0184 | Canada | No Added Cost |
| | OPERATOR'S MANUAL AND DECAL KIT | |
| 0409 | English Operator's Manual and Decal Kit | In Base Price |
| 0437 | Spanish Operator's Manual and Decal Kit | No Added Cost |
| 0413 | French Operator's Manual and Decal Kit | No Added Cost |
| | MISCELLANEOUS Field Installed Options BACK DRAG ATTACHMENT | |
| 9207 | Back Drag Kit with Steel Edge - 60 in. | \$222.00 |
| 9208 | Back Drag Kit with Rubber Edge - 60 in. | \$280.00 |
| | RUBBER EDGE KIT | |
| 9844 | Rubber Edge Kit - 60 in. | \$200.00 |
| | SKID SHOES | |
| 9863 | Poly Skid Shoes Kit (2 included) | \$275.00 |
| | ATTACHMENTS FOR FIELD CONVERSION MISCELLANEOUS | |
| 5MP43052 | FRENCH OM/DECAL-LDR ATTACHMENTS | \$134.32 |
| 5FP281104204 | AS10F Poly Skid Shoe Kit | \$364.79 |
| 5FP110416004 | AS10F (60 in.) Back Drag Kit with Rubber Edge | \$373.10 |



AS10F - 60 in. Snow Push

| Code | Description | List price(USD) |
|--------------|--|-----------------|
| 5FP110406004 | AS10F (60 in.) Back Drag Kit with Steel Edge | \$294.25 |
| 5FP110436004 | AS10F (60 in.) Rubber Edge Kit | \$263.81 |
| 5MP76312XES | French Operator's Manual and Decal Kit | See Parts |

**SB1148 - 48 In. 3-Point Medium Snowblower - U.S.**

| Code | Description | List price(USD) |
|------|---|-----------------|
| | SB1148 - 48 In. 3-Point Medium Snowblower - U.S. | |
| | Function: Snow Removal Working Width: 48 In. Transport Width: 48.5 In. Working Height: 24 5/8 In. Length: 38.5 In. Single/Dual Auger: Single Auger Diameter: 15 In. Auger Flighting Thickness: 1/4 In. Impeller Diameter: 20 In. Impeller Width: 6 In. Impeller Shaft Diameter: 1 In. Number of Impeller Blades: 4 Roller Chain: 50 Drive Sprocket: 17 Teeth Driven Sprocket: 36 Teeth Chain Idler: Manual Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model L-25J Gear Box HP (Through Gears): 11 Gear Box HP (Straight Through): 30 Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 20 PTO Clutch Setting (Number): 900 Shearbolt Bolt Size and Grade (PTO): M6 8.8 Metric Shearbolt Bolt Size and Grade (Auger): 1/4 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. Back Plate Thickness: 12 Gauge Impeller Housing Thickness: 12 Gauge Impeller Blade Thickness: 3/16 In. Side Panel Bottom Thickness: 3/16 In. Cutting Edge: Welded | |



SB1148 - 48 In. 3-Point Medium Snowblower - U.S.

| Code | Description | List price(USD) |
|--------|---|-----------------|
| | Cutting Edge Dimension: 3/8 In. x 2 In. Chute Diameter: 8 In. Chute Base: Standard Chute Rotation: 215 Degrees Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible HP Requirements (Minimum-Maximum HP): 16-35 HP Operating Weight: 375 lbs. Shipping Weight: 415 lbs. Approximate Set-up Time: 60 Minutes Chute Deflector Adjustment (Standard): Manual Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 5 In.) Including Brackets, Hoses, and Tips Electric Actuator (5 In.) Including Hardware, Switch, and Electric Cable Chute Rotation (Standard): Must Choose an Option, Manual or Hydraulic Chute Rotation Options: Manual, Worm Gear with Crank Hydraulic: Motor, Including Flow Restrictors, Hoses, and Tips Chute: Two Part ONLY Dual Auger: N/A Rotating Drum (Including Hoses and Tips): N/A | |
| | BASE MACHINE | |
| 3801XF | SB1148 - 48 In. 3-Point Medium Snowblower - U.S. | \$3,855.00 |
| | HYDRAULIC AND ELECTRICAL Basic Factory Options CHUTES | |
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | \$552.00 |

**SB1148 - 48 In. 3-Point Medium Snowblower - U.S.**

| Code | Description | List price(USD) |
|-----------|---|-----------------|
| | Field Installed Options | |
| | HYDRAULIC CYLINDER KIT | |
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | \$445.00 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i> | \$1,291.00 |
| | MISCELLANEOUS | |
| | ATTACHMENTS FOR FIELD CONVERSION | |
| | MISCELLANEOUS | |
| 5RDF0047 | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | \$909.71 |
| 5RDF0048A | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | \$489.51 |
| 5RDF0049A | Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | \$1,420.11 |
| BLV11199 | John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i> | \$275.00 |
| | <i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i> | |
| | <i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i> | |
| 5RDF0016 | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial numbers 1XFSB11XB0111287 and below.</i> | \$242.00 |
| 5RDF0017 | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | \$782.11 |
| 5RDF0019 | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | \$435.60 |



SB1148 - 48 In. 3-Point Medium Snowblower - U.S.

| Code | Description | List price(USD) |
|----------|---|-----------------|
| 5RDF0046 | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | \$242.00 |

**SB1154 - 54 In. 3-Point Medium Snowblower - U.S.**

| Code | Description | List price(USD) |
|------|--|-----------------|
| | SB1154 - 54 In. 3-Point Medium Snowblower - U.S. | |
| | Function: Snow Removal Working Width: 54 In. Transport Width: 54.5 In. Working Height: 26 In. Length: 41 In. Single/Dual Auger: Single Auger Diameter: 15 In. Auger Flighting Thickness: 5/16 In. Impeller Diameter: 24 In. Impeller Width: 7 In. Impeller Shaft Diameter: 1-3/8 In. Number of Impeller Blades: 4 Roller Chain: 60 Drive Sprocket: 10 Teeth Driven Sprocket: 32 Teeth Chain Idler: Manual Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-281A Gear Box HP (Through Gears): 23 HP Gear Box HP (Straight Through): 60 HP Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 40 PTO Clutch Setting (Number): 1300 Shearbolt Bolt Size and Grade (PTO): M10 8.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. Back Plate Thickness: 12 Gauge Impeller Housing Thickness: 12 Gauge Impeller Blade Thickness: 3/16 In. Side Panel Bottom Thickness: 3/16 In. Cutting Edge: Welded | |



SB1154 - 54 In. 3-Point Medium Snowblower - U.S.

| Code | Description | List price(USD) |
|--------|--|-----------------|
| | Cutting Edge Dimension: 3/8 In. x 2 In. Chute Diameter: 8 In. Chute Base: Standard Chute Rotation: 215 Degrees Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible HP Requirements (Minimum-Maximum HP): 16-35 HP Operating Weight: 455 lbs. Shipping Weight: 495 lbs. Approximate Set-up Time: 60 Minutes Chute Deflector Adjustment (Standard): Manual Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 5 In.) Including Brackets, Hoses, and Tips Electric Actuator (5 In.) Including Hardware, Switch, and Electric Cable Chute Rotation (Standard): Must Choose an Option - Manual or Hydraulic Chute Rotation Options: Manual, Worm Gear with Crank Hydraulic: Motor Including Flow Restrictors, Hoses, and Tips Chute: Two Part ONLY Dual Auger: MN/A Rotating Drum (Including Hoses and Tips): N/A | |
| | BASE MACHINE | |
| 3802XF | SB1154 - 54 In. 3-Point Medium Snowblower - U.S. | \$4,283.00 |
| | HYDRAULIC AND ELECTRICAL Basic Factory Options CHUTES | |
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | \$552.00 |

**SB1154 - 54 In. 3-Point Medium Snowblower - U.S.**

| Code | Description | List price(USD) |
|-----------|---|-----------------|
| | Field Installed Options | |
| | HYDRAULIC CYLINDER KIT | |
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | \$445.00 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i> | \$1,291.00 |
| | MISCELLANEOUS | |
| | ATTACHMENTS FOR FIELD CONVERSION | |
| | MISCELLANEOUS | |
| BLV11178 | John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i> | \$275.00 |
| | <i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i> | |
| | <i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i> | |
| 5RDF0047 | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB011288 and above.</i> | \$909.71 |
| 5RDF0048A | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB011288 and above.</i> | \$489.51 |
| 5RDF0049A | Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB011288 and above.</i> | \$1,420.11 |
| 5RDF0016 | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial numbers 1XFSB11XB011287 and below.</i> | \$242.00 |
| 5RDF0017 | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB011287 and below.</i> | \$782.11 |
| 5RDF0019 | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB011287 and below.</i> | \$435.60 |

**SB1154 - 54 In. 3-Point Medium Snowblower - U.S.**

| Code | Description | List price(USD) |
|----------|--|-----------------|
| 5RDF0020 | Electric Kit for Chute Deflector - Includes 4 In. Actuator <i>For snowblowers with serial number 1XFSB11XAB0111287 and below.</i> | \$1,442.11 |
| 5RDF0046 | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | \$242.00 |

**SB1164 - 64 In. 3-Point Medium Snowblower - U.S.**

| Code | Description | List price(USD) |
|------|--|-----------------|
| | SB1164 - 64 In. 3-Point Medium Snowblower - U.S. | |
| | Function: Snow Removal Working Width: 64 In. Transport Width: 64.5 In. Working Height: 26 In. Length: 41 In. Single/Dual Auger: Single Auger Diameter: 15 In. Auger Flighting Thickness: 5/16 In. Impeller Diameter: 24 In. Impeller Width: 7 In. Impeller Shaft Diameter: 1-3/8 In. Number of Impeller Blades: 4 Roller Chain: 60 Drive Sprocket: 10 Teeth Driven Sprocket: 32 Teeth Chain Idler: Manual Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-281A Gear Box HP (Through Gears): 23 HP Gear Box HP (Straight Through): 60 HP Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 40 PTO Clutch Setting (Number): 1300 Shearbolt Bolt Size and Grade (PTO): M10 8.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. Back Plate Thickness: 12 Gauge Impeller Housing Thickness: 12 Gauge Impeller Blade Thickness: 3/16 In. Side Panel Bottom Thickness: 3/16 In. Cutting Edge: Welded | |



SB1164 - 64 In. 3-Point Medium Snowblower - U.S.

| Code | Description | List price(USD) |
|--------|---|-----------------|
| | Cutting Edge Dimension: 3/8 In. x 2 In. Chute Diameter: 8 In. Chute Base: Standard Chute Rotation: 215 Degrees Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible HP Requirements (Minimum-Maximum HP): 20-50 HP Operating Weight: 479 lbs. Shipping Weight: 519 lbs. Approximate Set-Up Time: 60 Minutes Chute Deflector Adjustment (Standard): Manual Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 5 In.) Including Brackets, Hoses, and Tips Electric Actuator (5 In.) Including Hardware, Switch, and Electric Cable Chute Rotation (Standard): Must Choose an Option - Manual or Hydraulic Chute Rotation Options: Manual, Worm Gear with Crank Hydraulic: Motor Including Flow Restrictors, Hoses, and Tips Chute: Two Part ONLY Dual Auger: N/A Rotating Drum (Including Hoses and Tips): N/A | |
| | BASE MACHINE | |
| 3803XF | SB1164 - 64 In. 3-Point Medium Snowblower - U.S. | \$4,412.00 |
| | HYDRAULIC AND ELECTRICAL Basic Factory Options CHUTES | |
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | \$552.00 |

**SB1164 - 64 In. 3-Point Medium Snowblower - U.S.**

| Code | Description | List price(USD) |
|-----------|---|-----------------|
| | Field Installed Options | |
| | HYDRAULIC CYLINDER KIT | |
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | \$445.00 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i> | \$1,291.00 |
| | MISCELLANEOUS | |
| | ATTACHMENTS FOR FIELD CONVERSION | |
| | MISCELLANEOUS | |
| BLV11178 | John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i> | \$275.00 |
| | <i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i> | |
| | <i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i> | |
| 5RDF0047 | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | \$909.71 |
| 5RDF0048A | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | \$489.51 |
| 5RDF0049A | Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | \$1,420.11 |
| 5RDF0016 | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial numbers 1XFSB11XB0111287 and below.</i> | \$242.00 |
| 5RDF0017 | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | \$782.11 |
| 5RDF0019 | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i> | \$435.60 |

**SB1164 - 64 In. 3-Point Medium Snowblower - U.S.**

| Code | Description | List price(USD) |
|----------|--|-----------------|
| 5RDF0020 | Electric Kit for Chute Deflector - Includes 4 In. Actuator <i>For snowblowers with serial number 1XFSB11XAB0111287 and below.</i> | \$1,442.11 |
| 5RDF0046 | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | \$242.00 |

**SB1174 - 74 In. 3-Point Medium Snowblower - U.S.**

| Code | Description | List price(USD) |
|------|---|-----------------|
| | SB1174 - 74 In. 3-Point Medium Snowblower - U.S. | |
| | Function: Snow Removal Working Width: 74 In. Transport Width: 74.5 In. Working Height: 26 In. Length: 47.5 In. Single/Dual Auger: Single Auger Diameter: 15 In. Auger Flighting Thickness: 5/16 In. Impeller Diameter: 24 In. Impeller Width: 9 In. Impeller Shaft Diameter: 1-3/8 In. Number of Impeller Blades: 4 Roller Chain: 60 Drive Sprocket: 10 Teeth Driven Sprocket: 32 Teeth Chain Idler: Manual Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-281A Gear Box HP (Through Gears): 23 HP Gear Box HP (Straight Through): 60 HP Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 50 PTO Clutch Setting (Number): 1700 Shearbolt Bolt Size and Grade (PTO): M10 8.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. Back Plate Thickness: 11 Gauge Impeller Housing Thickness: 11 Gauge Impeller Blade Thickness: 1/4 In. Side Panel Bottom Thickness: 3/16 In. Cutting Edge: Welded | |



SB1174 - 74 In. 3-Point Medium Snowblower - U.S.

| Code | Description | List price(USD) |
|--------|---|-----------------|
| | Cutting Edge Dimension: 3/8 In. x 2 In. Chute Diameter: 12 In. Chute Base: Standard Chute Rotation: 215 Degrees Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible HP Requirements (Minimum-Maximum HP): 20-50 HP Operating Weight: 590 lbs. Shipping Weight: 635 lbs. Approximate Set-Up Time: 60 Minutes Chute Deflector Adjustment (Standard): Manual Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 5 In.) Including Brackets, Hoses and Tips Electric Actuator (8 In.) Including Hardware, Switch, and Electric Cable Chute Rotation (Standard): Must Choose an Option - Manual or Hydraulic Manual, Worm Gear with Crank Hydraulic: Motor Including Flow Restrictor, Hoses, and Tips Chute: Two Part ONLY Dual Auger: N/A Rotating Drum (Including Hoses and Tips): N/A | |
| | BASE MACHINE | |
| 3804XF | SB1174 - 74 In. 3-Point Medium Snowblower - U.S. | \$5,558.00 |
| | HYDRAULIC AND ELECTRICAL | |
| | Basic Factory Options | |
| | CHUTES | |
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | \$552.00 |
| | Field Installed Options | |

**SB1174 - 74 In. 3-Point Medium Snowblower - U.S.**

| Code | Description | List price(USD) |
|-----------|--|-----------------|
| | HYDRAULIC CYLINDER KIT | |
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | \$445.00 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i> | \$1,291.00 |
| | MISCELLANEOUS ATTACHMENTS FOR FIELD CONVERSION MISCELLANEOUS | |
| BLV11178 | John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i> <i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i> <i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i> | \$275.00 |
| 5RDF0021 | Electric Kit for Chute Deflector - Includes 8 In. Actuator | \$1,420.11 |
| 5RDF0071 | Hydraulic Cylinder Kit for Chute Deflector | \$456.51 |
| 5RDF0047 | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | \$909.71 |
| 5RDF0048A | Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | \$489.51 |
| 5RDF0016 | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial numbers 1XFSB11XB0111287 and below.</i> | \$242.00 |
| 5RDF0018 | Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial numbers 1XFSB11XB0111287 and below.</i> | \$1,019.71 |
| 5RDF0046 | Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i> | \$242.00 |



SB1184 - 84 In. 3-Point Medium Snowblower - U.S.

| Code | Description | List price(USD) |
|------|--|-----------------|
| | SB1184 - 84 In. 3-Point Medium Snowblower - U.S. | |
| | Function: Snow Removal Working Width: 84 In. Transport Width: 85.5 In. Working Height: 34 In. Length: 55.5 In. Single/Dual Auger: Single Auger Diameter: 20 In. Auger Flighting Thickness: 3/8 In. Impeller Diameter: 27-1/2 In. Impeller Width: 10.5 In. Impeller Shaft Diameter: 1-9/16 In. Number of Impeller Blades: 4 Roller Chain: 60 Drive Sprocket: 12 Teeth Driven Sprocket: 38 Teeth Chain Idler: Manual Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-27D Gear Box HP (Through Gears): 55 HP Gear Box HP (Straight Through): 105 HP Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 60 PTO Clutch Setting (Number): 1900 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. Back Plate Thickness: 11 Gauge Impeller Housing Thickness: 11 Gauge Impeller Blade Thickness: 3/8 In. Side Panel Bottom Thickness: 3/16 In. Cutting Edge: Welded | |



SB1184 - 84 In. 3-Point Medium Snowblower - U.S.

| Code | Description | List price(USD) |
|--------|--|-----------------|
| | Cutting Edge Dimension: 1/2 In. x 3 In. Chute Diameter: 12 In. Chute Base: Standard Chute Rotation: 215 Degrees Parking Stand: Standard Hitch Category: Category I/II Quick Hitch Compatibility: iMatch Compatible and Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 35-90 HP Operating Weight: 958 lbs. Shipping Weight: 1003 lbs. Approximate Set-Up Time: 60 Minutes Chute Deflector Adjustment (Standard): Manual Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Electric Actuator (8 In.) Including Hardware, Switch, and Electric Cable Chute Rotation (Standard): Must choose an Option - Manual or Hydraulic Chute Rotation Options: Manual, Worm Gear with Crank Hydraulic: Cylinder (2 In. x 8 In.), Including Bracket, Hoses, and Tips Chute: Two Part ONLY Dual Auger: N/A Rotating Drum (Including Hoses and Tips): N/A | |
| | BASE MACHINE | |
| 3805XF | SB1184 - 84 In. 3-Point Medium Snowblower - U.S. | \$7,680.00 |
| | HYDRAULIC AND ELECTRICAL Basic Factory Options CHUTES | |
| 1000 | Manual Chute Rotation Kit | In Base Price |



SB1184 - 84 In. 3-Point Medium Snowblower - U.S.

| Code | Description | List price(USD) |
|----------|---|-----------------|
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | \$693.00 |
| | Field Installed Options | |
| | HYDRAULIC CYLINDER KIT | |
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | \$473.00 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i> | \$1,291.00 |
| | MISCELLANEOUS | |
| | ATTACHMENTS FOR FIELD CONVERSION | |
| | MISCELLANEOUS | |
| 5RDF0021 | Electric Kit for Chute Deflector - Includes 8 In. Actuator | \$1,420.11 |
| 5RDF0071 | Hydraulic Cylinder Kit for Chute Deflector | \$456.51 |
| BLV11202 | John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i> | \$275.00 |
| | <i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i> | |
| | <i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i> | |
| 5RDF0016 | Manual Chute Rotation Kit (SB11) | \$242.00 |
| 5RDF0018 | Hydraulic Cylinder Kit for Chute Rotation | \$1,019.71 |

**SB1194 - 94 In. 3-Point Medium Snowblower - U.S.**

| Code | Description | List price(USD) |
|------|---|-----------------|
| | SB1194 - 94 In. 3-Point Medium Snowblower - U.S. | |
| | Function: Snow Removal Working Width: 94 In. (2,387.6 mm) Transport Width: 95.5 In. (2,425.7 mm) Working Height: 34 In. (863.6 mm) Length: 55.5 In. (1,409.7 mm) Single/Dual Auger: Single Auger Diameter: 20 In. (508 mm) Auger Flighting Thickness: 3/8 In. (9.5 mm) Impeller Diameter: 27-1/2 In. (698.5 mm) Impeller Width: 10.5 In. (266.7 mm) Impeller Shaft Diameter: 1-9/16 In. (39.7 mm) Number of Impeller Blades: 4 Roller Chain: 60 Drive Sprocket: 10 Teeth Driven Sprocket: 32 Teeth Chain Idler: Manual Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-27D Gear Box HP (Through Gears): 55 HP (41 kW) Gear Box HP (Straight Through): 105 HP (78.3 kW) Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 60 PTO Clutch Setting (Number): 1900 N-m Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. (4.8 mm) Back Plate Thickness: 11 Gauge (3.18 mm) Impeller Housing Thickness: 11 Gauge (3.18 mm) Impeller Blade Thickness: 3/8 In. (9.5 mm) Side Panel Bottom Thickness: 3/16 In. (4.8 mm) Cutting Edge: Welded | |

**SB1194 - 94 In. 3-Point Medium Snowblower - U.S.**

| Code | Description | List price(USD) |
|--------|--|-----------------|
| | Cutting Edge Dimension: 1/2 In. x 3 In. (12.7 x 76.2 mm) Chute Diameter: 12 In. (304.8 mm) Chute Base: Standard Chute Rotation: 215 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 35-90 HP (26.1 kW - 67.1 kW) Operating Weight: 1,121 lbs. (508.5 kg) Shipping Weight: 1,166 lbs. (528.9 kg) Approximate Set-Up Time: 60 Minutes Chute Deflector Adjustment (Standard): Manual Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Electric Actuator (8 In.) Including Hardware, Switch, and Electric Cable Chute Rotation (Standard): Must choose an Option - Manual or Hydraulic Chute Rotation Options: Manual, Worm Gear with Crank Hydraulic: Cylinder (2 In. x 8 In.), Including Bracket, Hoses, and Tips Chute: Two Part ONLY Dual Auger: N/A Rotating Drum (Including Hoses and Tips): N/A | |
| | BASE MACHINE | |
| 3806XF | SB1194 - 94 In. 3-Point Medium Snowblower - U.S. | \$7,969.00 |
| | HYDRAULIC AND ELECTRICAL Basic Factory Options CHUTES | |
| 1000 | Manual Chute Rotation Kit | In Base Price |
| 1010 | Hydraulic Cylinder Kit for Chute Rotation | \$693.00 |



SB1194 - 94 In. 3-Point Medium Snowblower - U.S.

| Code | Description | List price(USD) |
|---|---|-----------------|
| Field Installed Options HYDRAULIC CYLINDER KIT | | |
| 9000 | Hydraulic Cylinder Kit for Chute Deflector | \$473.00 |
| 9010 | Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i> | \$1,291.00 |
| MISCELLANEOUS ATTACHMENTS FOR FIELD CONVERSION MISCELLANEOUS | | |
| 5RDF0021 | Electric Kit for Chute Deflector - Includes 8 In. Actuator | \$1,420.11 |
| 5RDF0071 | Hydraulic Cylinder Kit for Chute Deflector | \$456.51 |
| 5RDF0016 | Manual Chute Rotation Kit (SB11) | \$242.00 |
| 5RDF0018 | Hydraulic Cylinder Kit for Chute Rotation | \$1,019.71 |



**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
 Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|------|--|-----------------|
| | <p>SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.</p> | |
| | <p>Function: Snow Removal Working Width: 98 In. Transport Width: 99 In. Working Height: 44 In. Length: 67 In. Single/Dual Auger: Single/Dual Auger Diameter: 24 In. Auger Flighting Thickness: 7/16 In. Impeller Diameter: 31-1/2 In. Impeller Width: 14 In. Impeller Shaft Diameter: 2 In. Number of Impeller Blades: 6 Roller Chain: 80 Drive Sprocket: 12 Teeth Driven Sprocket: 34 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-279A Gear Box HP (Through Gears): 100 HP Gear Box HP (Straight Through): 185 HP Tractor RPM: 540/1000 RPM Optional Impeller RPM: 540 RPM Auger RPM: 190 RPM PTO Manufacturer: Comer PTO Description: 80 PTO Clutch Setting (Number): 3000 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 5/16 In. Back Plate Thickness: 10 Gauge Impeller Housing Thickness: 3/16 In. Impeller Blade Thickness: 1/2 In.</p> | |



**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
 Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|--------|--|-----------------|
| | Side Panel Bottom Thickness: 5/8 In. Cutting Edge: Bolt-on/Reversible Cutting Edge Dimension: 1/2 In. x 4 In. Chute Diameter: 14-7/8 In. Chute Base: Heavy Duty Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category II/III Quick Hitch Compatibility: Quick Hitch Compatible HP Requirements (Minimum-Maximum HP): 90-180 HP Operating Weight: 2233 lbs. Shipping Weight: 2280 lbs. Approximate Set-Up Time: 100 Minutes Chute Deflector Adjustment (Standard): Manual - Must Choose a Chute Option Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Chute Rotation (Standard): Hydraulic Motor Chute Rotation Including Hoses and Tips Chute Rotation Options: N/A Chute: Two Part, Includes Manual Deflector Three Part, Includes Cylinder (2 In. x 8 In.), Hoses, and Tips Dual Auger: 15 In. Diameter Auger Rotating Drum (Including Hoses and Tips): Standard | |
| | BASE MACHINE | |
| 3812XF | SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | \$16,757.00 |
| | HYDRAULIC AND ELECTRICAL Basic Factory Options CHUTES | |

**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|--------------------------------|--|-----------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | \$771.00 |
| Field Installed Options | | |
| HYDRAULIC CYLINDER KIT | | |
| 9030 | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | \$415.00 |
| HYDRAULIC ELECTRIC KIT | | |
| 9040 | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | \$4,260.00 |
| 9050 | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | \$352.00 |
| 9060 | Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i> | \$1,027.00 |
| AUGER | | |
| Field Installed Options | | |
| AUGER KIT | | |
| 9010 | 2nd Auger Kit <i>15 In. diameter.</i> | \$1,945.00 |
| MAIN AUGER | | |
| 9012 | Serrated Main Auger | \$3,726.00 |
| CUTTING EDGE | | |
| Field Installed Options | | |
| CUTTING EDGE | | |
| 9000 | Cutting Edge - CHT400 Steel | \$409.00 |
| 9002 | Cutting Edge - Tivar <i>Fully Plastic - Wear & Rust Resistant.</i> | \$874.00 |
| 9003 | Cutting Edge - Stainless Steel | \$849.00 |
| MISCELLANEOUS | | |

**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|----------|--|-----------------|
| | Field Installed Options | |
| | DRIFT CUTTERS | |
| 9020 | Drift Cutters | \$483.00 |
| | SKID SHOES | |
| 9070 | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | \$707.00 |
| | ATTACHMENTS FOR FIELD CONVERSION | |
| | MISCELLANEOUS | |
| 5RDF0074 | Drift Cutters | \$531.31 |
| 5RDF0071 | Hydraulic Cylinder Kit for Chute Deflector | \$456.51 |
| 5RDF0062 | Stainless Steel Pivoting Skid Shoes | \$776.60 |
| 5RDF0069 | Serrated Main Auger for SB1308 & SB1308R | \$4,098.60 |
| 5RDF0065 | 2nd Auger Kit - 15 In. Diameter | \$2,139.51 |
| 5RDF0052 | Cutting Edge - CHT400 Steel | \$449.91 |
| 5RDF0075 | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | \$1,129.71 |
| 5RDF0080 | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | \$4,687.11 |
| 5RDF0023 | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | \$388.31 |



**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
 Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|------|---|-----------------|
| | <p>SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.</p> <p>Function: Snow Removal Working Width: 104 In. Transport Width: 105 In. Working Height: 44 In. Length: 67 In. Single/Dual Auger: Single/Dual Auger Diameter: 24 In. Auger Flighting Thickness: 7/16 In. Impeller Diameter: 31-1/2 In. Impeller Width: 14 In. Impeller Shaft Diameter: 2 In. Number of Impeller Blades: 6 Roller Chain: 80 Drive Sprocket: 12 Teeth Driven Sprocket: 34 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-279A Gear Box HP (Through Gears): 100 HP Gear Box HP (Straight Through): 185 HP Tractor RPM: 540/1000 RPM Impeller RPM: 540 RPM Auger RPM: 190 RPM PTO Manufacturer: Comer PTO Description: 80 PTO Clutch Setting (Number): 3000 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 5/16 In. Back Plate Thickness: 10 Gauge Impeller Housing Thickness: 3/16 In. Impeller Blade Thickness: 1/2 In.</p> | |



**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
 Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|--------|---|-----------------|
| | Side Panel Bottom Thickness: 5/8 In. Cutting Edge: Bolt-on/Reversible Cutting Edge Dimension: 1/2 In. x 4 In. Chute Diameter: 14-7/8 In. Chute Base: Heavy Duty Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category II/III Quick Hitch Compatibility: Quick Hitch Compatible HP Requirements (Minimum-Maximum HP): 90-180 HP Operating Weight: 2336 lbs. Shipping Weight: 2385 lbs. Approximate Set-Up Time: 100 Minutes Chute Deflector Adjustment (Standard): Manual - Must Choose a Chute Option Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Chute Rotation (Standard): Hydraulic Motor Chute Rotation Including Hoses and Tips Chute Rotation Options: N/A Chute: Two Part, Includes Manual Deflector Three Part, Includes Cylinder (2 In. x 8 In.), Hoses and Tips Dual Auger: 15 In. Diameter Auger Rotating Drum (Including Hoses and Tips): Standard | |
| | BASE MACHINE | |
| 3813XF | SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | \$17,158.00 |
| | HYDRAULIC AND ELECTRICAL Basic Factory Options CHUTES | |



SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

| Code | Description | List price(USD) |
|--------------------------------|--|-----------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | \$771.00 |
| Field Installed Options | | |
| HYDRAULIC CYLINDER KIT | | |
| 9030 | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | \$415.00 |
| HYDRAULIC ELECTRIC KIT | | |
| 9040 | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | \$4,260.00 |
| 9050 | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | \$352.00 |
| 9060 | Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i> | \$1,027.00 |
| AUGER | | |
| Field Installed Options | | |
| AUGER KIT | | |
| 9010 | 2nd Auger Kit <i>15 In. diameter.</i> | \$1,967.00 |
| MAIN AUGER | | |
| 9012 | Serrated Main Auger | \$3,854.00 |
| CUTTING EDGE | | |
| Field Installed Options | | |
| CUTTING EDGE | | |
| 9000 | Cutting Edge - CHT400 Steel | \$439.00 |
| 9002 | Cutting Edge - Tivar <i>Fully Plastic - Wear & Rust Resistant.</i> | \$912.00 |
| 9003 | Cutting Edge - Stainless Steel | \$860.00 |
| MISCELLANEOUS | | |

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|----------|---|-----------------|
| | Field Installed Options | |
| | DRIFT CUTTERS | |
| 9020 | Drift Cutters | \$483.00 |
| | SKID SHOES | |
| 9070 | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | \$707.00 |
| | ATTACHMENTS FOR FIELD CONVERSION | |
| | MISCELLANEOUS | |
| 5RDF0074 | Drift Cutters | \$531.31 |
| 5RDF0071 | Hydraulic Cylinder Kit for Chute Deflector | \$456.51 |
| 5RDF0062 | Stainless Steel Pivoting Skid Shoes | \$776.60 |
| 5RDF0066 | 2nd Auger Kit - 15 In. Diameter | \$2,162.60 |
| 5RDF0053 | Cutting Edge - CHT400 Steel | \$484.00 |
| 5RDF0061 | Cutting Edge for SB1309R - Stainless Steel | \$946.00 |
| 5RDF0070 | Serrated Main Auger for SB1309R | \$4,238.31 |
| 5RDF0057 | Cutting Edge for SB1309R - Tivar <i>Fully Plastic - Wear and Rust Resistant</i> | \$1,003.20 |
| 5RDF0075 | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | \$1,129.71 |
| 5RDF0080 | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | \$4,687.11 |
| 5RDF0023 | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | \$388.31 |



SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

| Code | Description | List price(USD) |
|------|--|-----------------|
| | SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | |
| | Function: Snow Removal Working Width: 88 In. Transport Width: 88.5 In. Working Height: 40 In. Length: 61 In. Single/Dual Auger: Single/Dual Auger Diameter: 22 In. Auger Flighting Thickness: 7/16 In. Impeller Diameter: 28-1/2 In. Impeller Width: 12 In. Impeller Shaft Diameter: 1-9/16 In. Number of Impeller Blades: 4 Roller Chain: 80 Drive Sprocket: 11 Teeth Driven Sprocket: 34 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-27D Gear Box HP (Through Gears): 55 HP Gear Box HP (Straight Through): 105 HP Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 175 RPM PTO Manufacturer: Comer PTO Description: 60 PTO Clutch Setting (Number): 1900 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 1/4 In. Back Plate Thickness: 11 Gauge Impeller Housing Thickness: 1/4 In. Impeller Blade Thickness: 3/8 In. Side Panel Bottom Thickness: 5/8 In. | |



SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

| Code | Description | List price(USD) |
|--------|--|-----------------|
| | Cutting Edge: Bolt-on/Reversible Cutting Edge Dimension: 1/2 In. x 4 In. Chute Diameter: 12-3/4 In. Chute Base: Heavy Duty Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 45-95 HP Operating Weight: 1552 lbs. Shipping Weight: 1597 lbs. Approximate Set-Up Time: 90 Minutes Chute Deflector Adjustment (Standard): Manual - Must Choose a Chute Option Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Chute Rotation (Standard): Hydraulic Motor Chute Rotation Including Hoses and Tips Chute Rotation Options: N/A Chute: Two Part, Includes Manual Deflector Three Part, Includes Cylinder (2 In. x 8 In.), Hoses and Tips Dual Auger: 14 In. Diameter Auger Rotating Drum (Including Hoses and Tips): N/A | |
| | BASE MACHINE | |
| 3814XF | SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | \$11,420.00 |
| | HYDRAULIC AND ELECTRICAL Basic Factory Options CHUTES | |
| 1000 | 2 Part Chute | In Base Price |

**SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|---|---|-----------------|
| 1010 | <i>Includes manual deflector.</i> 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection.</i> <i>(Not available with option 9030).</i> | \$841.00 |
| Field Installed Options | | |
| HYDRAULIC CYLINDER KIT | | |
| 9030 | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | \$415.00 |
| HYDRAULIC ELECTRIC KIT | | |
| 9060 | Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch.</i> <i>For 13-Series Snowblower except SB1388 and SB1388R.</i> | \$899.00 |
| AUGER | | |
| Field Installed Options | | |
| AUGER KIT | | |
| 9010 | 2nd Auger Kit <i>14 In. diameter.</i> | \$1,816.00 |
| MAIN AUGER | | |
| 9012 | Serrated Main Auger | \$3,532.00 |
| CUTTING EDGE | | |
| Field Installed Options | | |
| CUTTING EDGE | | |
| 9000 | Cutting Edge - CHT400 Steel | \$355.00 |
| 9002 | Cutting Edge - Tivar <i>Fully Plastic - Wear & Rust Resistant.</i> | \$809.00 |
| 9003 | Cutting Edge - Stainless Steel | \$822.00 |
| MISCELLANEOUS | | |
| Field Installed Options | | |
| DRIFT CUTTERS | | |
| 9020 | Drift Cutters | \$483.00 |
| SKID SHOES | | |
| 9070 | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | \$707.00 |
| ATTACHMENTS FOR FIELD CONVERSION | | |
| MISCELLANEOUS | | |



SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

| Code | Description | List price(USD) |
|----------|--|-----------------|
| 5RDF0074 | Drift Cutters | \$531.31 |
| 5RDF0071 | Hydraulic Cylinder Kit for Chute Deflector | \$456.51 |
| 5RDF0062 | Stainless Steel Pivoting Skid Shoes | \$776.60 |
| 5RDF0067 | Serrated Main Auger for SB1388 & SB1388R | \$3,885.20 |
| 5RDF0063 | 2nd Auger Kit - 14 In. Diameter | \$1,998.71 |
| 5RDF0050 | Cutting Edge - CHT400 Steel | \$390.51 |
| 5RDF0058 | Cutting Edge for SB1388 & SB1388R - Stainless Steel | \$904.20 |
| 5RDF0054 | Cutting Edge for SB1388 & SB1388R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | \$891.00 |
| 5RDF0077 | Quick Hitch Kit for SB1388 and SB1388R Snowblower <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | \$1,035.11 |

**SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|------|---|-----------------|
| | SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | |
| | Function: Snow Removal Working Width: 88 In. Transport Width: 88.5 In. Working Height: 40 In. Length: 62.5 In. Single/Dual Auger: Single/Dual Auger Diameter: 22 In. Auger Flighting Thickness: 7/16 In. Impeller Diameter: 28-1/2 In. Impeller Width: 12 In. Impeller Shaft Diameter: 1-9/16 In. Number of Impeller Blades: 4 Roller Chain: 80 Drive Sprocket: 11 Teeth Driven Sprocket: 34 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-27D Gear Box HP (Through Gears): 55 HP Gear Box HP (Straight Through): 105 HP Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 175 RPM PTO Manufacturer: Comer PTO Description: 60 PTO Clutch Setting (Number): 1900 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 1/4 In. Back Plate Thickness: 11 Gauge Impeller Housing Thickness: 3/16 In. Impeller Blade Thickness: 3/8 In. | |



**SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
 Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|--------|---|-----------------|
| | Side Panel Bottom Thickness: 5/8 In. Cutting Edge: Bolt-on/Reversible Cutting Edge Dimension: 1/2 In. x 4 In. Chute Diameter: 12 3/4 In. Chute Base: Heavy Duty Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 45-95 HP Operating Weight: 1670 lbs. Shipping Weight: 1715 lbs. Approximate Set-Up Time: 90 Minutes Chute Deflector Adjustment (Standard): Manual - Must Choose a Chute Option Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Chute Rotation (Standard): Hydraulic Motor Chute Rotation Including Hoses and Tips Chute Rotation Options: N/A Chute: Two Part, Includes Manual Deflector Three Part, Includes Cylinder (2 In. x 8 In.), Hoses and Tips Dual Auger: 14 In. Diameter Auger Rotating Drum (Including Hoses and Tips): Standard | |
| | BASE MACHINE | |
| 3815XF | SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | \$13,448.00 |
| | HYDRAULIC AND ELECTRICAL | |
| | Basic Factory Options | |
| | CHUTES | |

**SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|--------------------------------|--|-----------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | \$841.00 |
| Field Installed Options | | |
| HYDRAULIC CYLINDER KIT | | |
| 9030 | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | \$415.00 |
| HYDRAULIC ELECTRIC KIT | | |
| 9060 | Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For 13-Series Snowblower except SB1388 and SB1388R.</i> | \$899.00 |
| AUGER | | |
| Field Installed Options | | |
| AUGER KIT | | |
| 9010 | 2nd Auger Kit <i>14 In. diameter.</i> | \$1,816.00 |
| MAIN AUGER | | |
| 9012 | Serrated Main Auger | \$3,532.00 |
| CUTTING EDGE | | |
| Field Installed Options | | |
| CUTTING EDGE | | |
| 9000 | Cutting Edge - CHT400 Steel | \$355.00 |
| 9002 | Cutting Edge - Tivar <i>Fully Plastic - Wear & Rust Resistant.</i> | \$809.00 |
| 9003 | Cutting Edge - Stainless Steel | \$822.00 |
| MISCELLANEOUS | | |
| Field Installed Options | | |
| DRIFT CUTTERS | | |
| 9020 | Drift Cutters | \$483.00 |
| SKID SHOES | | |
| 9070 | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | \$707.00 |

**SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|---|--|-----------------|
| ATTACHMENTS FOR FIELD CONVERSION | | |
| MISCELLANEOUS | | |
| 5RDF0074 | Drift Cutters | \$531.31 |
| 5RDF0071 | Hydraulic Cylinder Kit for Chute Deflector | \$456.51 |
| 5RDF0062 | Stainless Steel Pivoting Skid Shoes | \$776.60 |
| 5RDF0067 | Serrated Main Auger for SB1388 & SB1388R | \$3,885.20 |
| 5RDF0063 | 2nd Auger Kit - 14 In. Diameter | \$1,998.71 |
| 5RDF0050 | Cutting Edge - CHT400 Steel | \$390.51 |
| 5RDF0058 | Cutting Edge for SB1388 & SB1388R - Stainless Steel | \$904.20 |
| 5RDF0054 | Cutting Edge for SB1388 & SB1388R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | \$891.00 |
| 5RDF0077 | Quick Hitch Kit for SB1388 and SB1388R Snowblower <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | \$1,035.11 |

**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|------|--|-----------------|
| | SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | |
| | Function: Snow Removal Working Width: 92 In. Transport Width: 93 In. Working Height: 44 In. Length: 67 In. Single/Dual Auger: Single/Dual Auger Diameter: 24 In. Auger Flighting Thickness: 7/16 In. Impeller Diameter: 31-1/2 In. Impeller Width: 14 In. Impeller Shaft Diameter: 2 In. Number of Impeller Blades: 6 Roller Chain: 80 Drive Sprocket: 12 Teeth Driven Sprocket: 34 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-279A Gear Box HP (Through Gears): 100 HP Gear Box HP (Straight Through): 185 HP Tractor RPM: 540/1000 RPM Impeller RPM: 540 RPM Auger RPM: 190 RPM PTO Manufacturer: Comer PTO Description: 80 PTO Clutch Setting (Number): 3000 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 5/16 In. Back Plate Thickness: 10 Gauge Impeller Housing Thickness: 3/16 In. Impeller Blade Thickness: 1/2 In. | |



**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
 Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|--------|--|-----------------|
| | Side Panel Bottom Thickness: 5/8 In. Cutting Edge: Bolt-on/Reversible Cutting Edge Dimension: 1/2 In. x 4 In. Chute Diameter: 14-7/8 In. Chute Base: Heavy Duty Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 75-125 HP Operating Weight: 2183 lbs. Shipping Weight: 2230 lbs. Approximate Set-Up Time: 100 Minutes Chute Deflector Adjustment (Standard): Manual - Must Choose a Chute Option Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Chute Rotation (Standard): Hydraulic Motor Chute Rotation Including Hoses and Tips Chute Rotation Options: N/A Chute: Two Part, Includes Manual Deflector Three Part, Includes Cylinder (2 In. x 8 In.), Hoses, and Tips Dual Auger: 15 In. Diameter Auger Rotating Drum (Including Hoses and Tips): Standard | |
| | BASE MACHINE | |
| 3817XF | SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | \$16,030.00 |
| | HYDRAULIC AND ELECTRICAL Basic Factory Options CHUTES | |

**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|--------------------------------|--|-----------------|
| 1000 | 2 Part Chute <i>Includes manual deflector.</i> | In Base Price |
| 1010 | 3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i> | \$771.00 |
| Field Installed Options | | |
| HYDRAULIC CYLINDER KIT | | |
| 9030 | Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i> | \$415.00 |
| HYDRAULIC ELECTRIC KIT | | |
| 9040 | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i> | \$4,260.00 |
| 9050 | Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | \$352.00 |
| 9060 | Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i> | \$1,027.00 |
| AUGER | | |
| Field Installed Options | | |
| AUGER KIT | | |
| 9010 | 2nd Auger Kit <i>15 In. diameter.</i> | \$1,840.00 |
| MAIN AUGER | | |
| 9012 | Serrated Main Auger | \$3,596.00 |
| CUTTING EDGE | | |
| Field Installed Options | | |
| CUTTING EDGE | | |
| 9000 | Cutting Edge - CHT400 Steel | \$374.00 |
| 9002 | Cutting Edge - Tivar <i>Fully Plastic - Wear & Rust Resistant.</i> | \$835.00 |
| 9003 | Cutting Edge - Stainless Steel | \$835.00 |
| MISCELLANEOUS | | |

**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute
Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|----------|---|-----------------|
| | Field Installed Options | |
| | DRIFT CUTTERS | |
| 9020 | Drift Cutters | \$483.00 |
| | SKID SHOES | |
| 9070 | Stainless Steel Pivoting Skid Shoes (13-Series Snowblower) | \$707.00 |
| | ATTACHMENTS FOR FIELD CONVERSION | |
| | MISCELLANEOUS | |
| 5RDF0074 | Drift Cutters | \$531.31 |
| 5RDF0071 | Hydraulic Cylinder Kit for Chute Deflector | \$456.51 |
| 5RDF0062 | Stainless Steel Pivoting Skid Shoes | \$776.60 |
| 5RDF0068 | Serrated Main Auger for SB1392 & SB1392R | \$3,955.60 |
| 5RDF0064 | 2nd Auger Kit - 15 In. Diameter | \$2,024.00 |
| 5RDF0051 | Cutting Edge - CHT400 Steel | \$410.31 |
| 5RDF0059 | Cutting Edge for SB1392 & SB1392R - Stainless Steel | \$918.51 |
| 5RDF0055 | Cutting Edge for SB1392 & SB1392R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i> | \$918.51 |
| 5RDF0075 | Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 & Cat 3 Quick-Hitch</i> | \$1,129.71 |
| 5RDF0080 | Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309) | \$4,687.11 |
| 5RDF0023 | Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i> | \$388.31 |

**SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower**

| Code | Description | List price(USD) |
|------|--|-----------------|
| | <p>SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower</p> <p>Function: Snow Removal Working Width: 76 In. (1,931.4 mm) Transport Width: 76 In. (1,931.4 mm) Working Height: 27 In. (685.8 mm) Single/Dual Auger: Single Auger Diameter: 15 In. Auger Flighting Thickness: 5/16 In. (8 mm) Impeller Diameter: 24 In. (609.6 mm) Impeller Width: 8.5 In. (215.9 mm) Impeller Shaft Diameter: 1.25 In. (31.75 mm) Number of Impeller Blades: 4 Auger Drive: Hydraulic Impeller Drive: Hydraulic Impeller RPM: 580 RPM Auger RPM: 180 RPM Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. (4.8 mm) Back Plate Thickness: 11 Gauge (3.18 mm) Impeller Housing Thickness: 3/16 In. (4.8 mm) Impeller Blade Thickness: 5/16 In. (8 mm) Side Panel Bottom Thickness: 1/2 In. (12.7 mm) Cutting Edge: Replaceable Cutting Edge Dimension: 1/2 In. x 3 In. (12.7 mm x 76.2 mm) Chute Diameter: 12 In. (0.3m) Chute Base: Standard Chute Rotation: 270 Degrees Operating Weight: 760 lbs. (344.7 kg) Shipping Weight: 840 lbs. (381 kg) Approximate Set-Up Time: 120 Minutes Chute Deflector Adjustment (Standard): Must Choose an option Manual or Hydraulic Adjustable Tie Rod or Hydraulic Chute Deflector Adjustment Options: Electric Solenoid Valve, Switch, Wiring Harness and Hydraulic Cylinder Chute: Two Part ONLY</p> | |

**SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower**

| Code | Description | List price(USD) |
|--------|---|-----------------|
| | Dual Auger: N/A Rotating Drum (Including Hoses and Tips): N/A Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes | |
| | BASE MACHINE | |
| 3821XF | <i>With Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - U.S. Must only be used with HP2134 Hydraulic Power Unit.</i> SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower | \$19,190.00 |
| | HYDRAULIC AND ELECTRICAL | |
| | Basic Factory Options | |
| | HYDRAULIC POWER UNITS | |
| 1095 | Less Hydraulic Power Unit <i>HP2134</i> | (\$9,462.00) |
| 1010 | HP2134 - Hydraulic Power Unit, 34 HP <i>Includes wiring harness 5RDF0078 to control the loader mounted implement.</i> | In Base Price |
| | OIL COOLER | |
| 2000 | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat. Not available with option Code 1095.</i> | In Base Price |



SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower

| Code | Description | List price(USD) |
|---|--|-----------------|
| 2095 | Less Oil Cooler | (\$2,376.00) |
| CHUTES | | |
| 3000 | SB21 Manual Chute Deflection <i>Includes manual deflector.</i> | In Base Price |
| 3010 | Hydraulic Chute Deflection <i>Includes cylinders, hoses and fittings.</i> | \$813.00 |
| Field Installed Options | | |
| HYDRAULIC ELECTRIC KIT | | |
| 9040 | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Not available with option Code 1095.</i> | \$132.00 |
| MISCELLANEOUS | | |
| Field Installed Options | | |
| DRIFT CUTTERS | | |
| 9020 | Drift Cutters (SB21) | \$194.00 |
| ATTACHMENTS FOR FIELD CONVERSION | | |
| MISCELLANEOUS | | |
| 5RDF0025 | Kit for Hydraulic Chute Deflector (SB2176) | \$893.20 |
| 5RDF0026 | Drift Cutters (SB21) | \$213.40 |
| 5RDF0036 | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | \$2,613.60 |
| 5RDF0038 | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | \$145.20 |
| 5RDF0078 | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i> | \$202.40 |

**SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower**

| Code | Description | List price(USD) |
|------|---|-----------------|
| | SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower | |
| | Function: Snow Removal Working Width: 64 In. (1,625.6 mm) Transport Width: 64 In. (1,625.6 mm) Working Height: 27 In. (685.8 mm) Single/Dual Auger: Single Auger Diameter: 15 In. Auger Flighting Thickness: 5/16 In. (8 mm) Impeller Diameter: 24 In. (609.6 mm) Impeller Width: 7 In. (177.8 mm) Impeller Shaft Diameter: 1.25 In. (31.75 mm) Number of Impeller Blades: 4 Auger Drive: Hydraulic Impeller Drive: Hydraulic Impeller RPM: 680 RPM Auger RPM: 200 RPM Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. (4.8 mm) Back Plate Thickness: 11 Gauge (3.18 mm) Impeller Housing Thickness: 3/16 In. (4.8 mm) Impeller Blade Thickness: 1/4 In. (6.4 mm) Side Panel Bottom Thickness: 1/2 In. (12.7 mm) Cutting Edge: Replaceable Cutting Edge Dimension: 3/8 In. x 2 In. (9.5 mm x 50.8 mm) Chute Diameter: 8.25 In. (209.6 mm) Chute Base: Standard Chute Rotation: 270 Degrees Operating Weight: 760 lbs. (344.7 kg) Shipping Weight: 840 lbs. (381 kg) Approximate Set-Up Time: 120 Minutes Chute Deflector Adjustment (Standard): Must Choose an option Manual Tie Rod or Hydraulic Cylinder Chute Deflector Adjustment Options: Electric Solenoid Valve, Switch, and Hydraulic Cylinder Chute: Two Part ONLY Dual Auger: N/A Rotating Drum (Including Hoses and Tips): | |

**SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower**

| Code | Description | List price(USD) |
|--------|---|-----------------|
| | <p>N/A Function: Hydraulic Power Unit Pressure: 2700 psi Flow: 16 gpm Reservoir Capacity: 15 gal. System Capacity: 17 gal. System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch Hoses, Tips, and Brackets included Tractor RPM: 540 RPM PTO Manufacturer: Comer Parking Stand: Standard Hitch Category: Category I Quick Hitch Compatibility: iMatch Compatible Approximate Set-Up Time: 120 Minutes</p> | |
| | BASE MACHINE | |
| 3822XF | <p><i>With Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit - U.S.</i> <i>Must only be used with HP2025 Hydraulic Power Unit.</i> SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower</p> | \$18,657.00 |
| | HYDRAULIC AND ELECTRICAL | |
| | Basic Factory Options | |
| | HYDRAULIC POWER UNITS | |
| 1000 | <p>HP2025 - Hydraulic Power Unit, 25 HP <i>Includes wiring harness 5RDF0078 to control the loader mounted implement.</i></p> | In Base Price |
| 1095 | <p>Less Hydraulic Power Unit HP2025</p> | (\$9,301.00) |
| | OIL COOLER | |
| 2000 | <p>Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> <i>Not available with option Code 1095.</i></p> | In Base Price |
| 2095 | <p>Less Oil Cooler</p> | (\$2,376.00) |



SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower

| Code | Description | List price(USD) |
|----------|--|-----------------|
| | CHUTES | |
| 3000 | SB21 Manual Chute Deflection <i>Includes manual deflector.</i> | In Base Price |
| 3010 | Hydraulic Chute Deflection <i>Includes cylinders, hoses and fittings.</i> | \$813.00 |
| | Field Installed Options | |
| | HYDRAULIC ELECTRIC KIT | |
| 9040 | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Not available with option Code 1095.</i> | \$132.00 |
| | MISCELLANEOUS | |
| | Field Installed Options | |
| | DRIFT CUTTERS | |
| 9020 | Drift Cutters (SB21) | \$194.00 |
| | ATTACHMENTS FOR FIELD CONVERSION | |
| | MISCELLANEOUS | |
| 5RDF0026 | Drift Cutters (SB21) | \$213.40 |
| 5RDF0027 | Kit for Hydraulic Chute Deflector (SB2164) | \$893.20 |
| 5RDF0036 | Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i> | \$2,613.60 |
| 5RDF0038 | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i> | \$145.20 |
| 5RDF0078 | Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i> | \$202.40 |

**SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|------|---|-----------------|
| | SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | |
| | Function: Snow Removal Working Width: 74 In. (1,879.6 mm) Transport Width: 74.5 In. (1892.3 mm) Working Height: 30 In. (762 mm) Single/Dual Auger: Single Auger Diameter: 20 In. (508 mm) Auger Flighting Thickness: 3/8 In. (9.53 mm) Impeller Diameter: 26 In. (660.4 mm) Impeller Width: 10.5 In. (266.7 mm) Impeller Shaft Diameter: 1 9/16 In. (39.69 mm) Number of Impeller Blades: 4 Roller Chain: 60 Drive Sprocket: 10 Teeth Driven Sprocket: 32 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-27D Gear Box HP (Through Gears): 55 HP (41 kW) Gear Box HP (Straight Through): 105 HP (78.3 kW) Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 50 PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft) Shearbolt Bolt Size and Grade (PTO): M10 8.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. (4.8mm) Back Plate Thickness: 11 Gauge Impeller Housing Thickness: 3/16 In. (4.8mm) Impeller Blade Thickness: 5/16 In. (7.9mm) Side Panel Bottom Thickness: 1/2 In. (12.7 mm) Cutting Edge: Replacable | |

**SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|----------|--|-----------------|
| | Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm) Chute Base: Standard Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category I & II Quick Hitch Compatibility: iMatch & Cat. II Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 30-80 HP (22.4-59.7kW) Operating Weight: 835 lbs. (378.7 kg) Shipping Weight: 875 lbs. (396.9 kg) Approximate Set-up Time: 60 Minutes Chute Deflector Adjustment (Standard): Hydraulic Cylinder Chute Rotation (Standard): Hydraulic Motor Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses, and tips Rotating Drum (Including Hoses and Tips): N/A | |
| | BASE MACHINE | |
| 3831XF | <i>Includes 2" x 4" cylinder, hoses, and tips for chute deflection.</i> SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | \$8,907.00 |
| | MISCELLANEOUS | |
| | ATTACHMENTS FOR FIELD CONVERSION | |
| | MISCELLANEOUS | |
| 5RDF0028 | Cutting Edge - CHT400 Steel | \$401.51 |
| BLV11202 | John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i> | \$275.00 |
| | <i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i> <i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i> | |

**SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.**

| Code | Description | List price(USD) |
|------|--|-----------------|
| | SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | |
| | Function: Snow Removal Working Width: 80 In. (2,032 mm) Transport Width: 80.5 In. (2,044.7 mm) Working Height: 30 In. (762 mm) Single/Dual Auger: Single Auger Diameter: 20 In. (508 mm) Auger Flighting Thickness: 3/8 In. (9.53 mm) Impeller Diameter: 26 In. (660.4 mm) Impeller Width: 10.5 In. (266.7 mm) Impeller Shaft Diameter: 1 9/16 In. (39.69 mm) Number of Impeller Blades: 4 Roller Chain: 60 Drive Sprocket: 10 Teeth Driven Sprocket: 32 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-27D Gear Box HP (Through Gears): 55 HP (41 kW) Gear Box HP (Straight Through): 105 HP (78.3 kW) Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 170 RPM PTO Manufacturer: Comer PTO Description: 50 PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft) Shearbolt Bolt Size and Grade (PTO): M10 8.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 3/16 In. (4.8mm) Back Plate Thickness: 11 Gauge Impeller Housing Thickness: 3/16 In. (4.8mm) Impeller Blade Thickness: 5/16 In. (7.9mm) Side Panel Bottom Thickness: 1/2 In. (12.7 mm) Cutting Edge: Replacable | |



SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

| Code | Description | List price(USD) |
|----------|--|-----------------|
| | Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm) Chute Base: Standard Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category I & II Quick Hitch Compatibility: iMatch & Cat. II Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 30-80 HP (22.4-59.7kW) Operating Weight: 895 lbs. (406 kg) Shipping Weight: 935 lbs. (424.1 kg) Approximate Set-up Time: 60 Minutes Chute Deflector Adjustment (Standard): Hydraulic Cylinder Chute Rotation (Standard): Hydraulic Motor Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses, and tips Rotating Drum (Including Hoses and Tips): N/A | |
| | BASE MACHINE | |
| 3832XF | <i>Includes 2" x 4" cylinder, hoses, and tips for chute deflection.</i> SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. | \$9,169.00 |
| | MISCELLANEOUS | |
| | ATTACHMENTS FOR FIELD CONVERSION | |
| | MISCELLANEOUS | |
| 5RDF0029 | Cutting Edge - CHT400 Steel | \$442.20 |
| BLV11202 | John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953</i> | \$275.00 |
| | <i>At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility.</i> | |
| | <i>One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i> | |