

## FRONTIER PRODUCTS

## Snow Products

**HP2025 - Hydraulic Power Unit, 25 HP - U.S.**  
Equipment for Base Machine

Function: Hydraulic Power Unit  
 Pressure: 2700 psi  
 Flow: 16 gpm  
 Reservoir Capacity: 15 gal.  
 System Capacity: 17 gal.  
 System Features: Pressure relieve valve, filter,  
 temperature and oil level gauge, and thermal  
 protection switch  
 Hoses, Tips, and Brackets included  
 Tractor RPM: 540 RPM  
 PTO Manufacturer: Comer

Parking Stand: Standard  
 Hitch Category: Category I  
 Quick Hitch Compatibility:  
 iMatch Compatible  
 Approximate Set-Up Time: 120 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

1601XF		HP2025 - Hydraulic Power Unit, 25 HP - U.S. <i>Must be used with SB2164 Snowblower and SW2160 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes rear tractor wiring harness. Front implement wiring harness is not included in base.</i>	7,785.00
--------	--	---	----------

**OIL COOLER**

2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	In Base Price
2095		Less Oil Cooler	-1,989.00

**WIRING HARNESS**

9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	110.00
------	--	--	--------

**ATTACHMENTS FOR FIELD CONVERSION**

<b>Miscellaneous</b>			
5RDF0036		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	2,063.60
5RDF0038		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	114.40
5RDF0078		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i>	159.51

**FRONTIER PRODUCTS**

**Snow Products**

---

**HP2025 - Hydraulic Power Unit, 25 HP - U.S.**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

## FRONTIER PRODUCTS

## Snow Products

**HP2134 - Hydraulic Power Unit, 34 HP - U.S.**  
Equipment for Base Machine

Function: Hydraulic Power Unit  
 Pressure: 2700 psi  
 Flow: 16 gpm  
 Reservoir Capacity: 15 gal.  
 System Capacity: 17 gal.  
 System Features: Pressure relieve valve, filter,  
 temperature and oil level gauge, and thermal  
 protection switch  
 Hoses, Tips, and Brackets included  
 Tractor RPM: 540 RPM  
 PTO Manufacturer: Comer

Parking Stand: Standard  
 Hitch Category: Category I  
 Quick Hitch Compatibility:  
 iMatch Compatible  
 Approximate Set-Up Time: 120 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

1611XF		HP2134 - Hydraulic Power Unit, 34 HP - U.S. <i>Must be used with SB2176 Snowblower and SW2184 Rotary Broom. Can be used with SW2172 Rotary Broom and BL2130 Debris Blower. Includes rear tractor wiring harness. Front implement wiring harness is not included in base.</i>	7,919.00
--------	--	---	----------

**OIL COOLER**

2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	In Base Price
2095		Less Oil Cooler	-1,989.00

**WIRING HARNESS**

9040		Additional Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	110.00
------	--	--	--------

**ATTACHMENTS FOR FIELD CONVERSION**

<b>Miscellaneous</b>			
5RDF0036		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	2,063.60
5RDF0038		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	114.40
5RDF0078		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i>	159.51

**FRONTIER PRODUCTS**

**Snow Products**

---

**HP2134 - Hydraulic Power Unit, 34 HP - U.S.**  
Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**FRONTIER PRODUCTS****Snow Products****AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier**

Equipment for Base Machine

Cutting Width: 73.75 In.

Shipping Weight: 490 lbs.

Loader Series:

300 and 400 Only (Not 500 Series)

Dimensions:

W74.5 In. x H30.75 In. x D34 In.

Capacity:

3.5 Cubic Foot

Operational Weight: 440 lbs.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category
---

**BASE MACHINE**

2191XF		AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier <i>Fixed cutting edge is rubber. Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i>	2,254.00
--------	--	---	----------

**OPERATOR'S MANUAL AND DECAL KIT**

9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Added Cost
------	--	--	---------------

**ATTACHMENTS FOR FIELD CONVERSION**

Miscellaneous			
5MP43052	FRENCH OM/DECAL-LDR ATTACHMENTS		0.00
5MP76312XES	French Operator's Manual and Decal Kit		See Parts

**FRONTIER PRODUCTS**

**Snow Products**

---

**AS10H - 6 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series  
Carrier**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**Snow Products**

**AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier**  
 Equipment for Base Machine

Cutting Width: 85.75 In.  
 Loader Series:  
 300 and 400 Only (Not 500 Series)  
 Dimensions:  
 W86.25 In. x H30.75 In. x D34 In.  
 Capacity:  
 4 Cubic Foot  
 Operational Weight: 477 lbs.

Shipping Weight: 527 lbs.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

2192XF		AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier <i>Fixed cutting edge is rubber.                      Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i>	2,497.00
--------	--	--	----------

**OPERATOR'S MANUAL AND DECAL KIT**

9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Added Cost
------	--	--	---------------

**ATTACHMENTS FOR FIELD CONVERSION**

	<b>Miscellaneous</b>		
5MP43052		FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
5MP76312XES		French Operator's Manual and Decal Kit	See Parts

**FRONTIER PRODUCTS**

**Snow Products**

---

**AS10H - 7 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series  
Carrier**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---



**Snow Products**

**AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier**  
 Equipment for Base Machine

Cutting Width: 85.75 In.  
 Loader Series:  
 300 and 400 Only (Not 500 Series)  
 Dimensions:  
 W86.25 In. x H30.75 In. x D34 In.  
 Capacity:  
 4 Cubic Foot  
 Operational Weight: 477 lbs.

Shipping Weight: 527 lbs.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

2193XF		AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series Carrier <i>Fixed cutting edge is rubber.                      Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i>	2,761.00
--------	--	--	----------

**OPERATOR'S MANUAL AND DECAL KIT**

9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Added Cost
------	--	--	---------------

**ATTACHMENTS FOR FIELD CONVERSION**

	<b>Miscellaneous</b>		
5MP43052		FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
5MP76312XES		French Operator's Manual and Decal Kit	See Parts

**FRONTIER PRODUCTS**

**Snow Products**

---

**AS10H - 8 Ft. Standard Duty Snow Push with Fixed Edge fits Current 300 and 400 Series  
Carrier**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

## FRONTIER PRODUCTS

## Snow Products

## AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

Equipment for Base Machine

Cutting Width: 98 In.  
 Loader Series:  
 300, 400, and 500  
 Dimensions:  
 W98.38 In. x H39.8 In. x D41.5 In.  
 Capacity:  
 7 Cubic Foot  
 Optional Bolt-on Pull Back Kit Weight:  
 163 lbs.

Operational Weight: 900 lbs.  
 Shipping Weight: 950 lbs.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

### BASE MACHINE

2201XF		AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier <i>Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i>	3,994.00
--------	--	--	----------

### OPERATOR'S MANUAL AND DECAL KIT

9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Added Cost
------	--	--	---------------

### BACK DRAG ATTACHMENT

9000		Back Drag Attachment <i>For 8 Ft. Model</i>	803.00
------	--	--	--------

### RUBBER EDGE KIT

9010		Rubber Edge Kit <i>8 Ft. Back Drag attachment required.</i>	429.00
------	--	--	--------

### ATTACHMENTS FOR FIELD CONVERSION

<b>Miscellaneous</b>			
5FP10730		Back Drag Attachment for 8 Ft. AS11E (Less Rubber Edge)	1,132.08
5MP43052		FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
5MP76312XES		French Operator's Manual and Decal Kit	See Parts
5FP10733		Rubber Edge Kit for 8 Ft. AS11E <i>5FP10730 - 8 Ft. Back Drag attachment required.</i>	560.57

**FRONTIER PRODUCTS**

**Snow Products**

---

**AS11E - 8 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

## FRONTIER PRODUCTS

## Snow Products

## AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

Equipment for Base Machine

Cutting Width: 110 In.  
 Loader Series:  
 300, 400, and 500  
 Dimensions:  
 W110.38 In. x H39.8 In. x D41.5 In.  
 Capacity:  
 7.8 Cubic Foot  
 Optional Bolt-on Pull Back Kit Weight:  
 175 lbs.

Operational Weight: 943 lbs.  
 Shipping Weight: 993 lbs.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

### BASE MACHINE

2202XF		AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier <i>Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i>	4,394.00
--------	--	--	----------

### OPERATOR'S MANUAL AND DECAL KIT

9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Added Cost
------	--	--	---------------

### BACK DRAG ATTACHMENT

9000		Back Drag Attachment <i>For 9 Ft. Model</i>	834.00
------	--	--	--------

### RUBBER EDGE KIT

9010		Rubber Edge Kit <i>9 Ft. Back Drag attachment required.</i>	478.00
------	--	--	--------

### ATTACHMENTS FOR FIELD CONVERSION

<b>Miscellaneous</b>			
5FP10731		Back Drag Attachment for 9 Ft. AS11E (Less Rubber Edge)	1,368.78
5MP43052		FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
5MP76312XES		French Operator's Manual and Decal Kit	See Parts
5FP10734		Rubber Edge Kit for 9 Ft. AS11E <i>5FP10731 - 9 Ft. Back Drag attachment required.</i>	496.11

**FRONTIER PRODUCTS**

**Snow Products**

---

**AS11E - 9 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

## FRONTIER PRODUCTS

## Snow Products

## AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier

Equipment for Base Machine

Cutting Width: 119.5 In.  
 Loader Series:  
 300, 400, and 500  
 Dimensions:  
 W110.875 In. x H39.8 In. x D41.5 In.  
 Capacity:  
 8.5 Cubic Foot  
 Optional Bolt-on Pull Back Kit Weight:  
 185 lbs.

Operational Weight: 980 lbs.  
 Shipping Weight: 1030 lbs.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

### BASE MACHINE

2203XF		AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier <i>Reference Frontier Loader Attachment Compatibility Chart for specific loader compatibility.</i>	4,783.00
--------	--	---	----------

### OPERATOR'S MANUAL AND DECAL KIT

9200		French Operator's Manual and Decal Kit for AS10, AS11 Series Snow Push	No Added Cost
------	--	--	---------------

### BACK DRAG ATTACHMENT

9000		Back Drag Attachment <i>For 10 Ft. Model</i>	875.00
------	--	---	--------

### RUBBER EDGE KIT

9010		Rubber Edge Kit <i>10 Ft. Back Drag attachment required.</i>	524.00
------	--	---	--------

### ATTACHMENTS FOR FIELD CONVERSION

<b>Miscellaneous</b>		
5FP10732	Back Drag Attachment for 10 Ft. AS11E (Less Rubber Edge)	907.51
5MP43052	FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
5MP76312XES	French Operator's Manual and Decal Kit	See Parts
5FP10735	Rubber Edge Kit for 10 Ft. AS11E <i>5FP10732 - 10 Ft. Back Drag attachment required.</i>	682.10

**FRONTIER PRODUCTS**

**Snow Products**

---

**AS11E - 10 Ft. Medium Duty Snow Push with Trip Edge fits Current 300, 400, and 500 Series Carrier**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---



**FRONTIER PRODUCTS****Snow Products****AS10F - 48 in. Snow Push**  
Equipment for Base Machine

Cutting Width: 48 In. Shipping Weight: lbs.  
 Base unit includes: Steel cutting edge, steel skid shoes  
 Loader Compatibility: D120/H120/120R  
 Dimensions: 19.3"Hx21.6"Dx50.6"W  
 Capacity: 11.6 cu ft  
 Operational Weight: 142 lbs.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category
---

**BASE MACHINE**

2411XF		AS10F - 48 in. Snow Push	805.00
--------	--	--------------------------	--------

**DESTINATION AND LANGUAGE**

0202		United States	In Base Price
0184		Canada	No Added Cost

**OPERATOR'S MANUAL AND DECAL KIT**

0409		English Operator's Manual and Decal Kit	In Base Price
0437		Spanish Operator's Manual and Decal Kit	No Added Cost
0413		French Operator's Manual and Decal Kit	No Added Cost

**BACK DRAG ATTACHMENT**

9205		Back Drag Kit with Steel Edge - 48 in.	178.00
9206		Back Drag Kit with Rubber Edge - 48 in.	215.00

**RUBBER EDGE KIT**

9843		Rubber Edge Kit - 48 in.	148.00
------	--	--------------------------	--------

**SKID SHOES**

9863		Poly Skid Shoes Kit (2 included)	230.00
------	--	----------------------------------	--------

**ATTACHMENTS FOR FIELD CONVERSION****Miscellaneous**

5FP110414804		AS10F (48 in.) Back Drag Kit with Rubber Edge	223.31
5FP110404804		AS10F (48 in.) Back Drag Kit with Steel Edge	184.80
5FP110434804		AS10F (48 in.) Rubber Edge Kit	154.00
5FP281104204		AS10F Poly Skid Shoe Kit	238.71

**FRONTIER PRODUCTS****Snow Products****AS10F - 48 in. Snow Push**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>	
	5MP43052	FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
	5MP76312XES	French Operator's Manual and Decal Kit	See Parts

**FRONTIER PRODUCTS****Snow Products****AS10F - 60 in. Snow Push**  
Equipment for Base Machine

Cutting Width: 60 In. Shipping Weight: lbs.  
 Base unit includes: Steel cutting edge, steel skid shoes  
 Loader Series:  
 200X/200CX/H130/220R/D160/305/H160/H165  
 Dimensions: 19.3"Hx21.6"Dx62.6"W  
 Capacity: 14.5 cu ft  
 Operational Weight: 160 lbs.

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category
---

**BASE MACHINE**

2412XF		AS10F - 60 in. Snow Push	858.00
--------	--	--------------------------	--------

**DESTINATION AND LANGUAGE**

0202		United States	In Base Price
0184		Canada	No Added Cost

**OPERATOR'S MANUAL AND DECAL KIT**

0409		English Operator's Manual and Decal Kit	In Base Price
0437		Spanish Operator's Manual and Decal Kit	No Added Cost
0413		French Operator's Manual and Decal Kit	No Added Cost

**BACK DRAG ATTACHMENT**

9207		Back Drag Kit with Steel Edge - 60 in.	186.00
9208		Back Drag Kit with Rubber Edge - 60 in.	234.00

**RUBBER EDGE KIT**

9844		Rubber Edge Kit - 60 in.	167.00
------	--	--------------------------	--------

**SKID SHOES**

9863		Poly Skid Shoes Kit (2 included)	230.00
------	--	----------------------------------	--------

**ATTACHMENTS FOR FIELD CONVERSION****Miscellaneous**

5FP110416004		AS10F (60 in.) Back Drag Kit with Rubber Edge	243.11
5FP110406004		AS10F (60 in.) Back Drag Kit with Steel Edge	192.51
5FP110436004		AS10F (60 in.) Rubber Edge Kit	173.80
5FP281104204		AS10F Poly Skid Shoe Kit	238.71

**FRONTIER PRODUCTS**

**Snow Products**

**AS10F - 60 in. Snow Push**  
 Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>	
	5MP43052	FRENCH OM/DECAL-LDR ATTACHMENTS	0.00
	5MP76312XES	French Operator's Manual and Decal Kit	See Parts

**FRONTIER PRODUCTS**

**Snow Products**

**SB1148 - 48 In. 3-Point Medium Snowblower - U.S.**  
 Equipment for Base Machine

Function: Snow Removal  
 Working Width: 48 In.  
 Transport Width: 48.5 In.  
 Working Height: 24 5/8 In.  
 Length: 38.5 In.  
 Single/Dual Auger: Single  
 Auger Diameter: 15 In.  
 Auger Flighting Thickness: 1/4 In.  
 Impeller Diameter: 20 In.  
 Impeller Width: 6 In.  
 Impeller Shaft Diameter: 1 In.  
 Number of Impeller Blades: 4  
 Roller Chain: 50  
 Drive Sprocket: 17 Teeth  
 Driven Sprocket: 36 Teeth  
 Chain Idler: Manual Adjustment  
 Gear Box Manufacturer: Comer  
 Gear Box Description: Model L-25J  
 Gear Box HP (Through Gears): 11  
 Gear Box HP (Straight Through): 30  
 Tractor RPM: 540 RPM  
 Impeller RPM: 540 RPM  
 Auger RPM: 170 RPM  
 PTO Manufacturer: Comer  
 PTO Description: 20  
 PTO Clutch Setting (Number): 900  
 Shearbolt Bolt Size and Grade (PTO):  
 M6 8.8 Metric  
 Shearbolt Bolt Size and Grade (Auger):  
 1/4 In. 5 SAE  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel  
 End Plate Thickness: 3/16 In.  
 Back Plate Thickness: 12 Gauge  
 Impeller Housing Thickness: 12 Gauge  
 Impeller Blade Thickness: 3/16 In.  
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded  
 Cutting Edge Dimension: 3/8 In. x 2 In.  
 Chute Diameter: 8 In.  
 Chute Base: Standard  
 Chute Rotation: 215 Degrees  
 Parking Stand: Standard  
 Hitch Category: Category I  
 Quick Hitch Compatibility:  
 iMatch Compatible  
 HP Requirements (Minimum-Maximum HP):  
 16-35 HP  
 Operating Weight: 375 lbs.  
 Shipping Weight: 415 lbs.  
 Approximate Set-up Time: 60 Minutes  
 Chute Deflector Adjustment (Standard):  
 Manual  
 Chute Deflector Adjustment Options:  
 Hydraulic Cylinder (2 In. x 5 In.)  
 Including Brackets, Hoses, and Tips  
 Electric Actuator (5 In.)  
 Including Hardware, Switch, and Electric Cable  
 Chute Rotation (Standard): Must Choose  
 an Option, Manual or Hydraulic  
 Chute Rotation Options:  
 Manual, Worm Gear with Crank  
 Hydraulic: Motor,  
 Including Flow Restrictors, Hoses, and Tips  
 Chute: Two Part ONLY  
 Dual Auger: N/A  
 Rotating Drum (Including Hoses and Tips):  
 N/A

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3801XF		SB1148 - 48 In. 3-Point Medium Snowblower - U.S.	3,077.00
--------	--	--	----------

**CHUTES**

1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	441.00

**HYDRAULIC CYLINDER KIT**

9000		Hydraulic Cylinder Kit for Chute Deflector	355.00
9010		Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i>	1,030.00

**ATTACHMENTS FOR FIELD CONVERSION**

## FRONTIER PRODUCTS

## Snow Products

## SB1148 - 48 In. 3-Point Medium Snowblower - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
<b>Miscellaneous</b>			
5RDF0049A		Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	1,069.20
5RDF0048A		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	368.51
5RDF0019		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	327.80
5RDF0017		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	589.60
5RDF0047		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	685.31
BLV11199		John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility. One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	275.00
5RDF0016		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial numbers 1XFSB11XB0111287 and below.</i>	182.60
5RDF0046		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	182.60

**FRONTIER PRODUCTS****Snow Products****SB1154 - 54 In. 3-Point Medium Snowblower - U.S.**  
Equipment for Base Machine

Function: Snow Removal  
 Working Width: 54 In.  
 Transport Width: 54.5 In.  
 Working Height: 26 In.  
 Length: 41 In.  
 Single/Dual Auger: Single  
 Auger Diameter: 15 In.  
 Auger Flighting Thickness: 5/16 In.  
 Impeller Diameter: 24 In.  
 Impeller Width: 7 In.  
 Impeller Shaft Diameter: 1-3/8 In.  
 Number of Impeller Blades: 4  
 Roller Chain: 60  
 Drive Sprocket: 10 Teeth  
 Driven Sprocket: 32 Teeth  
 Chain Idler: Manual Adjustment  
 Gear Box Manufacturer: Comer  
 Gear Box Description: Model T-281A  
 Gear Box HP (Through Gears): 23 HP  
 Gear Box HP (Straight Through): 60 HP  
 Tractor RPM: 540 RPM  
 Impeller RPM: 540 RPM  
 Auger RPM: 170 RPM  
 PTO Manufacturer: Comer  
 PTO Description: 40  
 PTO Clutch Setting (Number): 1300  
 Shearbolt Bolt Size and Grade (PTO):  
 M10 8.8 Metric  
 Shearbolt Bolt Size and Grade (Auger):  
 5/16 In. 5 SAE  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel  
 End Plate Thickness: 3/16 In.  
 Back Plate Thickness: 12 Gauge  
 Impeller Housing Thickness: 12 Gauge  
 Impeller Blade Thickness: 3/16 In.  
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded  
 Cutting Edge Dimension: 3/8 In. x 2 In.  
 Chute Diameter: 8 In.  
 Chute Base: Standard  
 Chute Rotation: 215 Degrees  
 Parking Stand: Standard  
 Hitch Category: Category I  
 Quick Hitch Compatibility:  
 iMatch Compatible  
 HP Requirements (Minimum-Maximum HP):  
 16-35 HP  
 Operating Weight: 455 lbs.  
 Shipping Weight: 495 lbs.  
 Approximate Set-up Time: 60 Minutes  
 Chute Deflector Adjustment (Standard):  
 Manual  
 Chute Deflector Adjustment Options:  
 Hydraulic Cylinder (2 In. x 5 In.)  
 Including Brackets, Hoses, and Tips  
 Electric Actuator (5 In.)  
 Including Hardware, Switch, and Electric Cable  
 Chute Rotation (Standard): Must Choose an  
 Option - Manual or Hydraulic  
 Chute Rotation Options:  
 Manual, Worm Gear with Crank  
 Hydraulic: Motor  
 Including Flow Restrictors, Hoses, and Tips  
 Chute: Two Part ONLY  
 Dual Auger: MN/A  
 Rotating Drum (Including Hoses and Tips):  
 N/A

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3802XF		SB1154 - 54 In. 3-Point Medium Snowblower - U.S.	3,419.00
--------	--	--	----------

**CHUTES**

1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	441.00

**HYDRAULIC CYLINDER KIT**

9000		Hydraulic Cylinder Kit for Chute Deflector	355.00
9010		Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i>	1,030.00

**ATTACHMENTS FOR FIELD CONVERSION**

## FRONTIER PRODUCTS

## Snow Products

## SB1154 - 54 In. 3-Point Medium Snowblower - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
5RDF0020		Electric Kit for Chute Deflector - Includes 4 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	1,085.71
5RDF0049A		Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	1,069.20
5RDF0048A		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	368.51
5RDF0019		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	327.80
5RDF0017		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	589.60
5RDF0047		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	685.31
BLV11178		John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility. One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	275.00
5RDF0016		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial numbers 1XFSB11XB0111287 and below.</i>	182.60
5RDF0046		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	182.60



**FRONTIER PRODUCTS****Snow Products****SB1164 - 64 In. 3-Point Medium Snowblower - U.S.**  
Equipment for Base Machine

Function: Snow Removal  
 Working Width: 64 In.  
 Transport Width: 64.5 In.  
 Working Height: 26 In.  
 Length: 41 In.  
 Single/Dual Auger: Single  
 Auger Diameter: 15 In.  
 Auger Flighting Thickness: 5/16 In.  
 Impeller Diameter: 24 In.  
 Impeller Width: 7 In.  
 Impeller Shaft Diameter: 1-3/8 In.  
 Number of Impeller Blades: 4  
 Roller Chain: 60  
 Drive Sprocket: 10 Teeth  
 Driven Sprocket: 32 Teeth  
 Chain Idler: Manual Adjustment  
 Gear Box Manufacturer: Comer  
 Gear Box Description: Model T-281A  
 Gear Box HP (Through Gears): 23 HP  
 Gear Box HP (Straight Through): 60 HP  
 Tractor RPM: 540 RPM  
 Impeller RPM: 540 RPM  
 Auger RPM: 170 RPM  
 PTO Manufacturer: Comer  
 PTO Description: 40  
 PTO Clutch Setting (Number): 1300  
 Shearbolt Bolt Size and Grade (PTO):  
 M10 8.8 Metric  
 Shearbolt Bolt Size and Grade (Auger):  
 5/16 In. 5 SAE  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel  
 End Plate Thickness: 3/16 In.  
 Back Plate Thickness: 12 Gauge  
 Impeller Housing Thickness: 12 Gauge  
 Impeller Blade Thickness: 3/16 In.  
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded  
 Cutting Edge Dimension: 3/8 In. x 2 In.  
 Chute Diameter: 8 In.  
 Chute Base: Standard  
 Chute Rotation: 215 Degrees  
 Parking Stand: Standard  
 Hitch Category: Category I  
 Quick Hitch Compatibility:  
 iMatch Compatible  
 HP Requirements (Minimum-Maximum HP):  
 20-50 HP  
 Operating Weight: 479 lbs.  
 Shipping Weight: 519 lbs.  
 Approximate Set-Up Time: 60 Minutes  
 Chute Deflector Adjustment (Standard):  
 Manual  
 Chute Deflector Adjustment Options:  
 Hydraulic Cylinder (2 In. x 5 In.)  
 Including Brackets, Hoses, and Tips  
 Electric Actuator (5 In.)  
 Including Hardware, Switch, and Electric Cable  
 Chute Rotation (Standard): Must Choose an  
 Option - Manual or Hydraulic  
 Chute Rotation Options:  
 Manual, Worm Gear with Crank  
 Hydraulic: Motor  
 Including Flow Restrictors, Hoses, and Tips  
 Chute: Two Part ONLY  
 Dual Auger: N/A  
 Rotating Drum (Including Hoses and Tips):  
 N/A

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3803XF		SB1164 - 64 In. 3-Point Medium Snowblower - U.S.	3,521.00
--------	--	--	----------

**CHUTES**

1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	441.00

**HYDRAULIC CYLINDER KIT**

9000		Hydraulic Cylinder Kit for Chute Deflector	355.00
9010		Electric Kit for Chute Deflector <i>Includes 5 In. actuator.</i>	1,030.00

**ATTACHMENTS FOR FIELD CONVERSION**

**Snow Products****SB1164 - 64 In. 3-Point Medium Snowblower - U.S.**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
5RDF0020		Electric Kit for Chute Deflector - Includes 4 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	1,085.71
5RDF0049A		Electric Kit for Chute Deflector - Includes 5 In. Actuator <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	1,069.20
5RDF0048A		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	368.51
5RDF0019		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	327.80
5RDF0017		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111287 and below.</i>	589.60
5RDF0047		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	685.31
BLV11178		John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility. One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	275.00
5RDF0016		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial numbers 1XFSB11XB0111287 and below.</i>	182.60
5RDF0046		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	182.60

**FRONTIER PRODUCTS**

**Snow Products**

**SB1174 - 74 In. 3-Point Medium Snowblower - U.S.**  
 Equipment for Base Machine

Function: Snow Removal  
 Working Width: 74 In.  
 Transport Width: 74.5 In.  
 Working Height: 26 In.  
 Length: 47.5 In.  
 Single/Dual Auger: Single  
 Auger Diameter: 15 In.  
 Auger Flighting Thickness: 5/16 In.  
 Impeller Diameter: 24 In.  
 Impeller Width: 9 In.  
 Impeller Shaft Diameter: 1-3/8 In.  
 Number of Impeller Blades: 4  
 Roller Chain: 60  
 Drive Sprocket: 10 Teeth  
 Driven Sprocket: 32 Teeth  
 Chain Idler: Manual Adjustment  
 Gear Box Manufacturer: Comer  
 Gear Box Description: Model T-281A  
 Gear Box HP (Through Gears): 23 HP  
 Gear Box HP (Straight Through): 60 HP  
 Tractor RPM: 540 RPM  
 Impeller RPM: 540 RPM  
 Auger RPM: 170 RPM  
 PTO Manufacturer: Comer  
 PTO Description: 50  
 PTO Clutch Setting (Number): 1700  
 Shearbolt Bolt Size and Grade (PTO):  
 M10 8.8 Metric  
 Shearbolt Bolt Size and Grade (Auger):  
 5/16 In. 5 SAE  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel  
 End Plate Thickness: 3/16 In.  
 Back Plate Thickness: 11 Gauge  
 Impeller Housing Thickness: 11 Gauge  
 Impeller Blade Thickness: 1/4 In.  
 Side Panel Bottom Thickness: 3/16 In.

Cutting Edge: Welded  
 Cutting Edge Dimension: 3/8 In. x 2 In.  
 Chute Diameter: 12 In.  
 Chute Base: Standard  
 Chute Rotation: 215 Degrees  
 Parking Stand: Standard  
 Hitch Category: Category I  
 Quick Hitch Compatibility:  
 iMatch Compatible  
 HP Requirements (Minimum-Maximum HP):  
 20-50 HP  
 Operating Weight: 590 lbs.  
 Shipping Weight: 635 lbs.  
 Approximate Set-Up Time: 60 Minutes  
 Chute Deflector Adjustment (Standard):  
 Manual  
 Chute Deflector Adjustment Options:  
 Hydraulic Cylinder (2 In. x 5 In.)  
 Including Brackets, Hoses and Tips  
 Electric Actuator (8 In.)  
 Including Hardware, Switch, and Electric Cable  
 Chute Rotation (Standard): Must Choose an  
 Option - Manual or Hydraulic  
 Manual, Worm Gear with Crank  
 Hydraulic: Motor  
 Including Flow Restrictor, Hoses, and Tips  
 Chute: Two Part ONLY  
 Dual Auger: N/A  
 Rotating Drum (Including Hoses and Tips):  
 N/A

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3804XF		SB1174 - 74 In. 3-Point Medium Snowblower - U.S.	4,436.00
--------	--	--	----------

**CHUTES**

1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	441.00

**HYDRAULIC CYLINDER KIT**

9000		Hydraulic Cylinder Kit for Chute Deflector	355.00
9010		Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i>	1,030.00

**ATTACHMENTS FOR FIELD CONVERSION**

## Snow Products

**SB1174 - 74 In. 3-Point Medium Snowblower - U.S.**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
<b>Miscellaneous</b>			
5RDF0021		Electric Kit for Chute Deflector - Includes 8 In. Actuator	1,069.20
5RDF0048A		Hydraulic Cylinder Kit for Chute Deflector <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	368.51
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	359.89
5RDF0018		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial numbers 1XFSB11XB0111287 and below.</i>	767.80
5RDF0047		Hydraulic Cylinder Kit for Chute Rotation <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	685.31
BLV11178		John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility. One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	275.00
5RDF0016		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial numbers 1XFSB11XB0111287 and below.</i>	182.60
5RDF0046		Manual Chute Rotation Kit (SB11) <i>For snowblowers with serial number 1XFSB11XB0111288 and above.</i>	182.60

**FRONTIER PRODUCTS**

**Snow Products**

**SB1184 - 84 In. 3-Point Medium Snowblower - U.S.**  
 Equipment for Base Machine

Function: Snow Removal  
 Working Width: 84 In.  
 Transport Width: 85.5 In.  
 Working Height: 34 In.  
 Length: 55.5 In.  
 Single/Dual Auger: Single  
 Auger Diameter: 20 In.  
 Auger Flighting Thickness: 3/8 In.  
 Impeller Diameter: 27-1/2 In.  
 Impeller Width: 10.5 In.  
 Impeller Shaft Diameter: 1-9/16 In.  
 Number of Impeller Blades: 4  
 Roller Chain: 60  
 Drive Sprocket: 12 Teeth  
 Driven Sprocket: 38 Teeth  
 Chain Idler: Manual Adjustment  
 Gear Box Manufacturer: Comer  
 Gear Box Description: Model T-27D  
 Gear Box HP (Through Gears): 55 HP  
 Gear Box HP (Straight Through): 105 HP  
 Tractor RPM: 540 RPM  
 Impeller RPM: 540 RPM  
 Auger RPM: 170 RPM  
 PTO Manufacturer: Comer  
 PTO Description: 60  
 PTO Clutch Setting (Number): 1900  
 Shearbolt Bolt Size and Grade (PTO):  
 M10 6.8 Metric  
 Shearbolt Bolt Size and Grade (Auger):  
 5/16 In. 5 SAE  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel  
 End Plate Thickness: 3/16 In.  
 Back Plate Thickness: 11 Gauge  
 Impeller Housing Thickness: 11 Gauge  
 Impeller Blade Thickness: 3/8 In.  
 Side Panel Bottom Thickness: 3/16 In.  
 Cutting Edge: Welded

Cutting Edge Dimension: 1/2 In. x 3 In.  
 Chute Diameter: 12 In.  
 Chute Base: Standard  
 Chute Rotation: 215 Degrees  
 Parking Stand: Standard  
 Hitch Category: Category I/II  
 Quick Hitch Compatibility:  
 iMatch Compatible and  
 Quick Coupler Compatible  
 HP Requirements (Minimum-Maximum HP):  
 35-90 HP  
 Operating Weight: 958 lbs.  
 Shipping Weight: 1003 lbs.  
 Approximate Set-Up Time: 60 Minutes  
 Chute Deflector Adjustment (Standard):  
 Manual  
 Chute Deflector Adjustment Options:  
 Hydraulic Cylinder (2 In. x 8 In.)  
 Including Hoses and Tips  
 Electric Actuator (8 In.)  
 Including Hardware, Switch, and Electric Cable  
 Chute Rotation (Standard): Must choose an  
 Option - Manual or Hydraulic  
 Chute Rotation Options:  
 Manual, Worm Gear with Crank  
 Hydraulic: Cylinder (2 In. x 8 In.),  
 Including Bracket, Hoses, and Tips  
 Chute: Two Part ONLY  
 Dual Auger: N/A  
 Rotating Drum (Including Hoses and Tips):  
 N/A

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3805XF		SB1184 - 84 In. 3-Point Medium Snowblower - U.S.	6,130.00
--------	--	--	----------

**CHUTES**

1000		Manual Chute Rotation Kit	In Base Price
1010		Hydraulic Cylinder Kit for Chute Rotation	553.00

**HYDRAULIC CYLINDER KIT**

9000		Hydraulic Cylinder Kit for Chute Deflector	377.00
9010		Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i>	1,030.00

**ATTACHMENTS FOR FIELD CONVERSION**

## FRONTIER PRODUCTS

## Snow Products

**SB1184 - 84 In. 3-Point Medium Snowblower - U.S.**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
5RDF0021		Electric Kit for Chute Deflector - Includes 8 In. Actuator	1,069.20
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	359.89
5RDF0018		Hydraulic Cylinder Kit for Chute Rotation	767.80
BLV11202		John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility. One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	275.00
5RDF0016		Manual Chute Rotation Kit (SB11)	182.60

**FRONTIER PRODUCTS**

**Snow Products**

**SB1194 - 94 In. 3-Point Medium Snowblower - U.S.**  
 Equipment for Base Machine

Function: Snow Removal	Cutting Edge Dimension: 1/2 In. x 3 In. (12.7 x 76.2 mm)
Working Width: 94 In. (2,387.6 mm)	Chute Diameter: 12 In. (304.8 mm)
Transport Width: 95.5 In. (2,425.7 mm)	Chute Base: Standard
Working Height: 34 In. (863.6 mm)	Chute Rotation: 215 Degrees
Length: 55.5 In. (1,409.7 mm)	Parking Stand: Standard
Single/Dual Auger: Single	Hitch Category: Category II
Auger Diameter: 20 In. (508 mm)	Quick Hitch Compatibility:
Auger Flighting Thickness: 3/8 In. (9.5 mm)	Quick Coupler Compatible
Impeller Diameter: 27-1/2 In. (698.5 mm)	HP Requirements (Minimum-Maximum HP):
Impeller Width: 10.5 In. (266.7 mm)	35-90 HP (26.1 kW - 67.1 kW)
Impeller Shaft Diameter: 1-9/16 In. (39.7 mm)	Operating Weight: 1,121 lbs. (508.5 kg)
Number of Impeller Blades: 4	Shipping Weight: 1,166 lbs. (528.9 kg)
Roller Chain: 60	Approximate Set-Up Time: 60 Minutes
Drive Sprocket: 10 Teeth	Chute Deflector Adjustment (Standard):
Driven Sprocket: 32 Teeth	Manual
Chain Idler: Manual Adjustment	Chute Deflector Adjustment Options:
Gear Box Manufacturer: Comer	Hydraulic Cylinder (2 In. x 8 In.)
Gear Box Description: Model T-27D	Including Hoses and Tips
Gear Box HP (Through Gears): 55 HP (41 kW)	Electric Actuator (8 In.)
Gear Box HP (Straight Through): 105 HP (78.3 kW)	Including Hardware, Switch, and Electric Cable
Tractor RPM: 540 RPM	Chute Rotation (Standard): Must choose an
Impeller RPM: 540 RPM	Option - Manual or Hydraulic
Auger RPM: 170 RPM	Chute Rotation Options:
PTO Manufacturer: Comer	Manual, Worm Gear with Crank
PTO Description: 60	Hydraulic: Cylinder (2 In. x 8 In.),
PTO Clutch Setting (Number): 1900 N-m	Including Bracket, Hoses, and Tips
Shearbolt Bolt Size and Grade (PTO):	Chute: Two Part ONLY
M10 6.8 Metric	Dual Auger: N/A
Shearbolt Bolt Size and Grade (Auger):	Rotating Drum (Including Hoses and Tips):
5/16 In. 5 SAE	N/A
Skid Shoe: Adjustable	
Skid Shoe Material: Steel	
End Plate Thickness: 3/16 In. (4.8 mm)	
Back Plate Thickness: 11 Gauge (3.18 mm)	
Impeller Housing Thickness: 11 Gauge (3.18 mm)	
Impeller Blade Thickness: 3/8 In. (9.5 mm)	
Side Panel Bottom Thickness: 3/16 In. (4.8 mm)	
Cutting Edge: Welded	

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3806XF	SB1194 - 94 In. 3-Point Medium Snowblower - U.S.	6,361.00
--------	--	----------

**CHUTES**

1000	Manual Chute Rotation Kit	In Base Price
1010	Hydraulic Cylinder Kit for Chute Rotation	553.00

**HYDRAULIC CYLINDER KIT**

9000	Hydraulic Cylinder Kit for Chute Deflector	377.00
9010	Electric Kit for Chute Deflector <i>Includes 8 In. actuator.</i>	1,030.00

**ATTACHMENTS FOR FIELD CONVERSION**

**FRONTIER PRODUCTS****Snow Products****SB1194 - 94 In. 3-Point Medium Snowblower - U.S.**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>			
		<b>Miscellaneous</b>	
5RDF0021		Electric Kit for Chute Deflector - Includes 8 In. Actuator	1,069.20
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	359.89
5RDF0018		Hydraulic Cylinder Kit for Chute Rotation	767.80
5RDF0016		Manual Chute Rotation Kit (SB11)	182.60



**FRONTIER PRODUCTS**

**Snow Products**

**SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.  
 Equipment for Base Machine**

Function: Snow Removal  
 Working Width: 74 In. (1,879.6 mm)  
 Transport Width: 74.5 In. (1892.3 mm)  
 Working Height: 30 In. (762 mm)  
 Single/Dual Auger: Single  
 Auger Diameter: 20 In. (508 mm)  
 Auger Flighting Thickness: 3/8 In. (9.53 mm)  
 Impeller Diameter: 26 In. (660.4 mm)  
 Impeller Width: 10.5 In. (266.7 mm)  
 Impeller Shaft Diameter: 1 9/16 In. (39.69 mm)  
 Number of Impeller Blades: 4  
 Roller Chain: 60  
 Drive Sprocket: 10 Teeth  
 Driven Sprocket: 32 Teeth  
 Chain Idler: Automatic Adjustment  
 Gear Box Manufacturer: Comer  
 Gear Box Description: Model T-27D  
 Gear Box HP (Through Gears): 55 HP (41 kW)  
 Gear Box HP (Straight Through): 105 HP (78.3 kW)  
 Tractor RPM: 540 RPM  
 Impeller RPM: 540 RPM  
 Auger RPM: 170 RPM  
 PTO Manufacturer: Comer  
 PTO Description: 50  
 PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft)  
 Shearbolt Bolt Size and Grade (PTO):  
 M10 8.8 Metric  
 Shearbolt Bolt Size and Grade (Auger):  
 5/16 In. 5 SAE  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel

End Plate Thickness: 3/16 In. (4.8mm)  
 Back Plate Thickness: 11 Gauge  
 Impeller Housing Thickness: 3/16 In. (4.8mm)  
 Impeller Blade Thickness: 5/16 In. (7.9mm)  
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)  
 Cutting Edge: Replacable  
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm)  
 Chute Base: Standard  
 Chute Rotation: 270 Degrees  
 Parking Stand: Standard  
 Hitch Category: Category I & II  
 Quick Hitch Compatibility:  
 iMatch & Cat. II Quick Coupler Compatible  
 HP Requirements (Minimum-Maximum HP):  
 30-80 HP (22.4-59.7kW)  
 Operating Weight: 835 lbs. (378.7 kg)  
 Shipping Weight: 875 lbs. (396.9 kg)  
 Approximate Set-up Time: 60 Minutes  
 Chute Deflector Adjustment (Standard): Hydraulic  
 Cylinder Chute Rotation (Standard): Hydraulic Motor  
 Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses,  
 and tips Rotating Drum (Including Hoses and Tips):  
 N/A

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3831XF		SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. <i>Includes 2" x 4" cylinder, hoses, and tips for chute deflection.</i>	7,455.00
--------	--	--	----------

**ATTACHMENTS FOR FIELD CONVERSION**

5RDF0028	<b>Miscellaneous</b> Cutting Edge - CHT400 Steel	340.10
BLV11202	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility. One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	275.00

**FRONTIER PRODUCTS**

**Snow Products**

---

**SB1274 - 74 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation  
and Single Auger - U.S.**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**FRONTIER PRODUCTS**

**Snow Products**

**SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.  
 Equipment for Base Machine**

Function: Snow Removal  
 Working Width: 80 In. (2,032 mm)  
 Transport Width: 80.5 In. (2,044.7 mm)  
 Working Height: 30 In. (762 mm)  
 Single/Dual Auger: Single  
 Auger Diameter: 20 In. (508 mm)  
 Auger Flighting Thickness: 3/8 In. (9.53 mm)  
 Impeller Diameter: 26 In. (660.4 mm)  
 Impeller Width: 10.5 In. (266.7 mm)  
 Impeller Shaft Diameter: 1 9/16 In. (39.69 mm)  
 Number of Impeller Blades: 4  
 Roller Chain: 60  
 Drive Sprocket: 10 Teeth  
 Driven Sprocket: 32 Teeth  
 Chain Idler: Automatic Adjustment  
 Gear Box Manufacturer: Comer  
 Gear Box Description: Model T-27D  
 Gear Box HP (Through Gears): 55 HP (41 kW)  
 Gear Box HP (Straight Through): 105 HP (78.3 kW)  
 Tractor RPM: 540 RPM  
 Impeller RPM: 540 RPM  
 Auger RPM: 170 RPM  
 PTO Manufacturer: Comer  
 PTO Description: 50  
 PTO Clutch Setting: 1,700 Nm (1,253.9 lbf-ft)  
 Shearbolt Bolt Size and Grade (PTO):  
     M10 8.8 Metric  
 Shearbolt Bolt Size and Grade (Auger):  
     5/16 In. 5 SAE  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel

End Plate Thickness: 3/16 In. (4.8mm)  
 Back Plate Thickness: 11 Gauge  
 Impeller Housing Thickness: 3/16 In. (4.8mm)  
 Impeller Blade Thickness: 5/16 In. (7.9mm)  
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)  
 Cutting Edge: Replacable  
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7mm x 76.2 mm) Chute Diameter: 10.5 In. (266.7 mm)  
 Chute Base: Standard  
 Chute Rotation: 270 Degrees  
 Parking Stand: Standard  
 Hitch Category: Category I & II  
 Quick Hitch Compatibility:  
     iMatch & Cat. II Quick Coupler Compatible  
 HP Requirements (Minimum-Maximum HP):  
     30-80 HP (22.4-59.7kW)  
 Operating Weight: 895 lbs. (406 kg)  
 Shipping Weight: 935 lbs. (424.1 kg)  
 Approximate Set-up Time: 60 Minutes  
 Chute Deflector Adjustment (Standard): Hydraulic  
 Cylinder Chute Rotation (Standard): Hydraulic Motor  
 Chute: Three Part ONLY w/ 2" x 4" cylinder, hoses,  
 and tips Rotating Drum (Including Hoses and Tips):  
     N/A

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3832XF		SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. <i>Includes 2" x 4" cylinder, hoses, and tips for chute deflection.</i>	7,674.00
--------	--	--	----------

**ATTACHMENTS FOR FIELD CONVERSION**

5RDF0029	<b>Miscellaneous</b> Cutting Edge - CHT400 Steel	375.09
BLV11202	John Deere Quik-Knect Driveline Yoke Bundle <i>Tractor Receiver Part number: BLV10953At least one tractor receiver bundle is needed per tractor. This bundle is removable and can be used on various tractors within the compatibility. One implement driveline yoke bundle is needed per implement, and remains with implement at all times (field install required).</i>	275.00

**FRONTIER PRODUCTS**

**Snow Products**

---

**SB1280 - 80 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation  
and Single Auger - U.S.**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**FRONTIER PRODUCTS**

**Snow Products**

**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
 Chute Rotation and Single Auger - U.S.  
 Equipment for Base Machine**

Function: Snow Removal  
 Working Width: 98 In.  
 Transport Width: 99 In.  
 Working Height: 44 In.  
 Length: 67 In.  
 Single/Dual Auger: Single/Dual  
 Auger Diameter: 24 In.  
 Auger Flighting Thickness: 7/16 In.  
 Impeller Diameter: 31-1/2 In.  
 Impeller Width: 14 In.  
 Impeller Shaft Diameter: 2 In.  
 Number of Impeller Blades: 6  
 Roller Chain: 80  
 Drive Sprocket: 12 Teeth  
 Driven Sprocket: 34 Teeth  
 Chain Idler: Automatic Adjustment  
 Gear Box Manufacturer: Comer  
 Gear Box Description: Model T-279A  
 Gear Box HP (Through Gears): 100 HP  
 Gear Box HP (Straight Through): 185 HP  
 Tractor RPM: 540/1000 RPM Optional  
 Impeller RPM: 540 RPM  
 Auger RPM: 190 RPM  
 PTO Manufacturer: Comer  
 PTO Description: 80  
 PTO Clutch Setting (Number): 3000  
 Shearbolt Bolt Size and Grade (PTO):  
 M10 6.8 Metric  
 Shearbolt Bolt Size and Grade (Auger):  
 5/16 In. 5 SAE  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel  
 End Plate Thickness: 5/16 In.  
 Back Plate Thickness: 10 Gauge  
 Impeller Housing Thickness: 3/16 In.  
 Impeller Blade Thickness: 1/2 In.  
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible  
 Cutting Edge Dimension: 1/2 In. x 4 In.  
 Chute Diameter: 14-7/8 In.  
 Chute Base: Heavy Duty  
 Chute Rotation: 270 Degrees  
 Parking Stand: Standard  
 Hitch Category: Category II/III  
 Quick Hitch Compatibility:  
 Quick Hitch Compatible  
 HP Requirements (Minimum-Maximum HP):  
 90-180 HP  
 Operating Weight: 2233 lbs.  
 Shipping Weight: 2280 lbs.  
 Approximate Set-Up Time: 100 Minutes  
 Chute Deflector Adjustment (Standard):  
 Manual - Must Choose a Chute Option  
 Chute Deflector Adjustment Options:  
 Hydraulic Cylinder (2 In. x 8 In.)  
 Including Hoses and Tips  
 Chute Rotation (Standard):  
 Hydraulic Motor Chute Rotation  
 Including Hoses and Tips  
 Chute Rotation Options: N/A  
 Chute:  
 Two Part, Includes Manual Deflector  
 Three Part, Includes Cylinder  
 (2 In. x 8 In.), Hoses, and Tips  
 Dual Auger: 15 In. Diameter Auger  
 Rotating Drum (Including Hoses and Tips):  
 Standard

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3812XF		SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	14,025.00
--------	--	---	-----------

**CHUTES**

1000		2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010		3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	646.00

**HYDRAULIC CYLINDER KIT**

9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	348.00
------	--	--	--------

## FRONTIER PRODUCTS

## Snow Products

## SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>HYDRAULIC ELECTRIC KIT</b>			
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,566.00
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	295.00
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i>	860.00
<b>AUGER KIT</b>			
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,628.00
<b>MAIN AUGER</b>			
9012		Serrated Main Auger	3,119.00
<b>CUTTING EDGE</b>			
9000		Cutting Edge - CHT400 Steel	342.00
9002		Cutting Edge - Tivar <i>Fully Plastic - Wear &amp; Rust Resistant.</i>	731.00
9003		Cutting Edge - Stainless Steel	710.00
<b>DRIFT CUTTERS</b>			
9020		Drift Cutters	404.00
<b>SKID SHOES</b>			
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	591.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Miscellaneous</b>			
5RDF0065		2nd Auger Kit - 15 In. Diameter	1,943.45
5RDF0052		Cutting Edge - CHT400 Steel	417.40
5RDF0074		Drift Cutters	419.11
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	359.89
5RDF0075		Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 &amp; Cat 3 Quick-Hitch</i>	892.11

## FRONTIER PRODUCTS

## Snow Products

---

**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
Chute Rotation and Single Auger - U.S.**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>	
	5RDF0023	Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	305.80
	5RDF0076	Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309)	3,741.14
	5RDF0069	Serrated Main Auger for SB1308 & SB1308R	3,454.04
	5RDF0062	Stainless Steel Pivoting Skid Shoes	741.87

**FRONTIER PRODUCTS**

**Snow Products**

---

**SB1308R - 8 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
Chute Rotation and Single Auger - U.S.**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---



**FRONTIER PRODUCTS**

**Snow Products**

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
 Chute Rotation and Single Auger - U.S.  
 Equipment for Base Machine**

Function: Snow Removal  
 Working Width: 104 In.  
 Transport Width: 105 In.  
 Working Height: 44 In.  
 Length: 67 In.  
 Single/Dual Auger: Single/Dual  
 Auger Diameter: 24 In.  
 Auger Flighting Thickness: 7/16 In.  
 Impeller Diameter: 31-1/2 In.  
 Impeller Width: 14 In.  
 Impeller Shaft Diameter: 2 In.  
 Number of Impeller Blades: 6  
 Roller Chain: 80  
 Drive Sprocket: 12 Teeth  
 Driven Sprocket: 34 Teeth  
 Chain Idler: Automatic Adjustment  
 Gear Box Manufacturer: Comer  
 Gear Box Description: Model T-279A  
 Gear Box HP (Through Gears): 100 HP  
 Gear Box HP (Straight Through): 185 HP  
 Tractor RPM: 540/1000 RPM  
 Impeller RPM: 540 RPM  
 Auger RPM: 190 RPM  
 PTO Manufacturer: Comer  
 PTO Description: 80  
 PTO Clutch Setting (Number): 3000  
 Shearbolt Bolt Size and Grade (PTO):  
 M10 6.8 Metric  
 Shearbolt Bolt Size and Grade (Auger):  
 5/16 In. 5 SAE  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel  
 End Plate Thickness: 5/16 In.  
 Back Plate Thickness: 10 Gauge  
 Impeller Housing Thickness: 3/16 In.  
 Impeller Blade Thickness: 1/2 In.  
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible  
 Cutting Edge Dimension: 1/2 In. x 4 In.  
 Chute Diameter: 14-7/8 In.  
 Chute Base: Heavy Duty  
 Chute Rotation: 270 Degrees  
 Parking Stand: Standard  
 Hitch Category: Category II/III  
 Quick Hitch Compatibility:  
 Quick Hitch Compatible  
 HP Requirements (Minimum-Maximum HP):  
 90-180 HP  
 Operating Weight: 2336 lbs.  
 Shipping Weight: 2385 lbs.  
 Approximate Set-Up Time: 100 Minutes  
 Chute Deflector Adjustment (Standard):  
 Manual - Must Choose a Chute Option  
 Chute Deflector Adjustment Options:  
 Hydraulic Cylinder (2 In. x 8 In.)  
 Including Hoses and Tips  
 Chute Rotation (Standard):  
 Hydraulic Motor Chute Rotation  
 Including Hoses and Tips  
 Chute Rotation Options: N/A  
 Chute:  
 Two Part, Includes Manual Deflector  
 Three Part, Includes Cylinder  
 (2 In. x 8 In.), Hoses and Tips  
 Dual Auger: 15 In. Diameter Auger  
 Rotating Drum (Including Hoses and Tips):  
 Standard

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3813XF		SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	14,361.00
--------	--	---	-----------

**CHUTES**

1000		2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010		3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	646.00

**HYDRAULIC CYLINDER KIT**

9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	348.00
------	--	--	--------

## Snow Products

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
Chute Rotation and Single Auger - U.S.**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>HYDRAULIC ELECTRIC KIT</b>			
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,566.00
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	295.00
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i>	860.00
<b>AUGER KIT</b>			
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,646.00
<b>MAIN AUGER</b>			
9012		Serrated Main Auger	3,226.00
<b>CUTTING EDGE</b>			
9000		Cutting Edge - CHT400 Steel	368.00
9002		Cutting Edge - Tivar <i>Fully Plastic - Wear &amp; Rust Resistant.</i>	763.00
9003		Cutting Edge - Stainless Steel	720.00
<b>DRIFT CUTTERS</b>			
9020		Drift Cutters	404.00
<b>SKID SHOES</b>			
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	591.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
		<b>Miscellaneous</b>	
	5RDF0066	2nd Auger Kit - 15 In. Diameter	1,780.20
	5RDF0053	Cutting Edge - CHT400 Steel	390.63
	5RDF0061	Cutting Edge for SB1309R - Stainless Steel	798.49
	5RDF0057	Cutting Edge for SB1309R - Tivar <i>Fully Plastic - Wear and Rust Resistant</i>	792.00
	5RDF0074	Drift Cutters	419.11
	5RDF0071	Hydraulic Cylinder Kit for Chute Deflector	359.89

## Snow Products

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
Chute Rotation and Single Auger - U.S.**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>	
5RDF0075		Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 &amp; Cat 3 Quick-Hitch</i>	892.11
5RDF0023		Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	305.80
5RDF0076		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309)	3,741.14
5RDF0070		Serrated Main Auger for SB1309R	3,575.94
5RDF0062		Stainless Steel Pivoting Skid Shoes	741.87

**FRONTIER PRODUCTS**

**Snow Products**

---

**SB1309R - 9 Ft. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
Chute Rotation and Single Auger - U.S.**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**FRONTIER PRODUCTS**

**Snow Products**

**SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
Chute Rotation and Single Auger - U.S.  
Equipment for Base Machine**

Function: Snow Removal  
 Working Width: 88 In.  
 Transport Width: 88.5 In.  
 Working Height: 40 In.  
 Length: 62.5 In.  
 Single/Dual Auger: Single/Dual  
 Auger Diameter: 22 In.  
 Auger Flighting Thickness: 7/16 In.  
 Impeller Diameter: 28-1/2 In.  
 Impeller Width: 12 In.  
 Impeller Shaft Diameter: 1-9/16 In.  
 Number of Impeller Blades: 4  
 Roller Chain: 80  
 Drive Sprocket: 11 Teeth  
 Driven Sprocket: 34 Teeth  
 Chain Idler: Automatic Adjustment  
 Gear Box Manufacturer: Comer  
 Gear Box Description: Model T-27D  
 Gear Box HP (Through Gears): 55 HP  
 Gear Box HP (Straight Through): 105 HP  
 Tractor RPM: 540 RPM  
 Impeller RPM: 540 RPM  
 Auger RPM: 175 RPM  
 PTO Manufacturer: Comer  
 PTO Description: 60  
 PTO Clutch Setting (Number): 1900  
 Shearbolt Bolt Size and Grade (PTO):  
 M10 6.8 Metric  
 Shearbolt Bolt Size and Grade (Auger):  
 5/16 In. 5 SAE  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel  
 End Plate Thickness: 1/4 In.  
 Back Plate Thickness: 11 Gauge  
 Impeller Housing Thickness: 3/16 In.  
 Impeller Blade Thickness: 3/8 In.  
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible  
 Cutting Edge Dimension: 1/2 In. x 4 In.  
 Chute Diameter: 12 3/4 In.  
 Chute Base: Heavy Duty  
 Chute Rotation: 270 Degrees  
 Parking Stand: Standard  
 Hitch Category: Category II  
 Quick Hitch Compatibility:  
 Quick Coupler Compatible  
 HP Requirements (Minimum-Maximum HP):  
 45-95 HP  
 Operating Weight: 1670 lbs.  
 Shipping Weight: 1715 lbs.  
 Approximate Set-Up Time: 90 Minutes  
 Chute Deflector Adjustment (Standard):  
 Manual - Must Choose a Chute Option  
 Chute Deflector Adjustment Options:  
 Hydraulic Cylinder (2 In. x 8 In.)  
 Including Hoses and Tips  
 Chute Rotation (Standard):  
 Hydraulic Motor Chute Rotation  
 Including Hoses and Tips  
 Chute Rotation Options: N/A  
 Chute:  
 Two Part, Includes Manual Deflector  
 Three Part, Includes Cylinder  
 (2 In. x 8 In.), Hoses and Tips  
 Dual Auger: 14 In. Diameter Auger  
 Rotating Drum (Including Hoses and Tips):  
 Standard

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3815XF		SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	11,255.00
--------	--	--	-----------

**CHUTES**

1000		2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010		3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	704.00

**HYDRAULIC CYLINDER KIT**

9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	348.00
------	--	--	--------

## Snow Products

**SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
Chute Rotation and Single Auger - U.S.**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		<b>HYDRAULIC ELECTRIC KIT</b>	
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For 13-Series Snowblower except SB1388 and SB1388R.</i>	753.00
		<b>AUGER KIT</b>	
9010		2nd Auger Kit <i>14 In. diameter.</i>	1,520.00
		<b>MAIN AUGER</b>	
9012		Serrated Main Auger	2,956.00
		<b>CUTTING EDGE</b>	
9000		Cutting Edge - CHT400 Steel	297.00
9002		Cutting Edge - Tivar <i>Fully Plastic - Wear &amp; Rust Resistant.</i>	677.00
9003		Cutting Edge - Stainless Steel	688.00
		<b>DRIFT CUTTERS</b>	
9020		Drift Cutters	404.00
		<b>SKID SHOES</b>	
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	591.00
		<b>ATTACHMENTS FOR FIELD CONVERSION</b>	
		<b>Miscellaneous</b>	
	5RDF0063	2nd Auger Kit - 14 In. Diameter	1,813.15
	5RDF0050	Cutting Edge - CHT400 Steel	324.55
	5RDF0058	Cutting Edge for SB1388 & SB1388R - Stainless Steel	730.73
	5RDF0054	Cutting Edge for SB1388 & SB1388R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i>	717.13
	5RDF0074	Drift Cutters	419.11
	5RDF0071	Hydraulic Cylinder Kit for Chute Deflector	359.89
	5RDF0077	Quick Hitch Kit for SB1388 and SB1388R Snowblower <i>Required for Cat 2 &amp; Cat 3 Quick-Hitch</i>	781.00
	5RDF0067	Serrated Main Auger for SB1388 & SB1388R	3,277.28
	5RDF0062	Stainless Steel Pivoting Skid Shoes	741.87

**FRONTIER PRODUCTS**

**Snow Products**

---

**SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
Chute Rotation and Single Auger - U.S.**

Continued

**FRONTIER PRODUCTS**

**Snow Products**

---

**SB1388R - 88 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
Chute Rotation and Single Auger - U.S.**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---



**FRONTIER PRODUCTS**

**Snow Products**

**SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S. Equipment for Base Machine**

Function: Snow Removal Working Width: 88 In. Transport Width: 88.5 In. Working Height: 40 In. Length: 61 In. Single/Dual Auger: Single/Dual Auger Diameter: 22 In. Auger Flighting Thickness: 7/16 In. Impeller Diameter: 28-1/2 In. Impeller Width: 12 In. Impeller Shaft Diameter: 1-9/16 In. Number of Impeller Blades: 4 Roller Chain: 80 Drive Sprocket: 11 Teeth Driven Sprocket: 34 Teeth Chain Idler: Automatic Adjustment Gear Box Manufacturer: Comer Gear Box Description: Model T-27D Gear Box HP (Through Gears): 55 HP Gear Box HP (Straight Through): 105 HP Tractor RPM: 540 RPM Impeller RPM: 540 RPM Auger RPM: 175 RPM PTO Manufacturer: Comer PTO Description: 60 PTO Clutch Setting (Number): 1900 Shearbolt Bolt Size and Grade (PTO): M10 6.8 Metric Shearbolt Bolt Size and Grade (Auger): 5/16 In. 5 SAE Skid Shoe: Adjustable Skid Shoe Material: Steel End Plate Thickness: 1/4 In. Back Plate Thickness: 11 Gauge Impeller Housing Thickness: 1/4 In. Impeller Blade Thickness: 3/8 In. Side Panel Bottom Thickness: 5/8 In.	Cutting Edge: Bolt-on/Reversible Cutting Edge Dimension: 1/2 In. x 4 In. Chute Diameter: 12-3/4 In. Chute Base: Heavy Duty Chute Rotation: 270 Degrees Parking Stand: Standard Hitch Category: Category II Quick Hitch Compatibility: Quick Coupler Compatible HP Requirements (Minimum-Maximum HP): 45-95 HP Operating Weight: 1552 lbs. Shipping Weight: 1597 lbs. Approximate Set-Up Time: 90 Minutes Chute Deflector Adjustment (Standard): Manual - Must Choose a Chute Option Chute Deflector Adjustment Options: Hydraulic Cylinder (2 In. x 8 In.) Including Hoses and Tips Chute Rotation (Standard): Hydraulic Motor Chute Rotation Including Hoses and Tips Chute Rotation Options: N/A Chute: Two Part, Includes Manual Deflector Three Part, Includes Cylinder (2 In. x 8 In.), Hoses and Tips Dual Auger: 14 In. Diameter Auger Rotating Drum (Including Hoses and Tips): N/A
--	---

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3814XF	SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.		9,558.00
--------	---	--	----------

**CHUTES**

1000	2 Part Chute <i>Includes manual deflector.</i>		In Base Price
1010	3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>		704.00

**HYDRAULIC CYLINDER KIT**

9030	Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>		348.00
------	--	--	--------

## Snow Products

**SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation  
and Single Auger - U.S.**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>HYDRAULIC ELECTRIC KIT</b>			
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For 13-Series Snowblower except SB1388 and SB1388R.</i>	753.00
<b>AUGER KIT</b>			
9010		2nd Auger Kit <i>14 In. diameter.</i>	1,520.00
<b>MAIN AUGER</b>			
9012		Serrated Main Auger	2,956.00
<b>CUTTING EDGE</b>			
9000		Cutting Edge - CHT400 Steel	297.00
9002		Cutting Edge - Tivar <i>Fully Plastic - Wear &amp; Rust Resistant.</i>	677.00
9003		Cutting Edge - Stainless Steel	688.00
<b>DRIFT CUTTERS</b>			
9020		Drift Cutters	404.00
<b>SKID SHOES</b>			
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	591.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Miscellaneous</b>			
5RDF0063		2nd Auger Kit - 14 In. Diameter	1,813.15
5RDF0050		Cutting Edge - CHT400 Steel	324.55
5RDF0058		Cutting Edge for SB1388 & SB1388R - Stainless Steel	730.73
5RDF0054		Cutting Edge for SB1388 & SB1388R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i>	717.13
5RDF0074		Drift Cutters	419.11
5RDF0071		Hydraulic Cylinder Kit for Chute Deflector	359.89
5RDF0077		Quick Hitch Kit for SB1388 and SB1388R Snowblower <i>Required for Cat 2 &amp; Cat 3 Quick-Hitch</i>	781.00
5RDF0067		Serrated Main Auger for SB1388 & SB1388R	3,277.28
5RDF0062		Stainless Steel Pivoting Skid Shoes	741.87

**FRONTIER PRODUCTS**

**Snow Products**

---

**SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation  
and Single Auger - U.S.**

Continued

**FRONTIER PRODUCTS**

**Snow Products**

---

**SB1388 - 88 In. 3-Point Commercial Snowblower with Hydraulic Motor Chute Rotation  
and Single Auger - U.S.**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---

**FRONTIER PRODUCTS**

**Snow Products**

**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
 Chute Rotation and Single Auger - U.S.  
 Equipment for Base Machine**

Function: Snow Removal  
 Working Width: 92 In.  
 Transport Width: 93 In.  
 Working Height: 44 In.  
 Length: 67 In.  
 Single/Dual Auger: Single/Dual  
 Auger Diameter: 24 In.  
 Auger Flighting Thickness: 7/16 In.  
 Impeller Diameter: 31-1/2 In.  
 Impeller Width: 14 In.  
 Impeller Shaft Diameter: 2 In.  
 Number of Impeller Blades: 6  
 Roller Chain: 80  
 Drive Sprocket: 12 Teeth  
 Driven Sprocket: 34 Teeth  
 Chain Idler: Automatic Adjustment  
 Gear Box Manufacturer: Comer  
 Gear Box Description: Model T-279A  
 Gear Box HP (Through Gears): 100 HP  
 Gear Box HP (Straight Through): 185 HP  
 Tractor RPM: 540/1000 RPM  
 Impeller RPM: 540 RPM  
 Auger RPM: 190 RPM  
 PTO Manufacturer: Comer  
 PTO Description: 80  
 PTO Clutch Setting (Number): 3000  
 Shearbolt Bolt Size and Grade (PTO):  
 M10 6.8 Metric  
 Shearbolt Bolt Size and Grade (Auger):  
 5/16 In. 5 SAE  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel  
 End Plate Thickness: 5/16 In.  
 Back Plate Thickness: 10 Gauge  
 Impeller Housing Thickness: 3/16 In.  
 Impeller Blade Thickness: 1/2 In.  
 Side Panel Bottom Thickness: 5/8 In.

Cutting Edge: Bolt-on/Reversible  
 Cutting Edge Dimension: 1/2 In. x 4 In.  
 Chute Diameter: 14-7/8 In.  
 Chute Base: Heavy Duty  
 Chute Rotation: 270 Degrees  
 Parking Stand: Standard  
 Hitch Category: Category II  
 Quick Hitch Compatibility:  
 Quick Coupler Compatible  
 HP Requirements (Minimum-Maximum HP):  
 75-125 HP  
 Operating Weight: 2183 lbs.  
 Shipping Weight: 2230 lbs.  
 Approximate Set-Up Time: 100 Minutes  
 Chute Deflector Adjustment (Standard):  
 Manual - Must Choose a Chute Option  
 Chute Deflector Adjustment Options:  
 Hydraulic Cylinder (2 In. x 8 In.)  
 Including Hoses and Tips  
 Chute Rotation (Standard):  
 Hydraulic Motor Chute Rotation  
 Including Hoses and Tips  
 Chute Rotation Options: N/A  
 Chute:  
 Two Part, Includes Manual Deflector  
 Three Part, Includes Cylinder  
 (2 In. x 8 In.), Hoses, and Tips  
 Dual Auger: 15 In. Diameter Auger  
 Rotating Drum (Including Hoses and Tips):  
 Standard

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3817XF		SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor Chute Rotation and Single Auger - U.S.	13,416.00
--------	--	--	-----------

**CHUTES**

1000		2 Part Chute <i>Includes manual deflector.</i>	In Base Price
1010		3 Part Chute <i>Includes cylinders, hoses, and tips for hydraulic chute deflection. (Not available with option 9030).</i>	646.00

**HYDRAULIC CYLINDER KIT**

9030		Hydraulic Cylinder Kit for Chute Deflector <i>(Not available with option 1010).</i>	348.00
------	--	--	--------

## Snow Products

**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
Chute Rotation and Single Auger - U.S.**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>HYDRAULIC ELECTRIC KIT</b>			
9040		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 Series Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0023 is needed to complete kit.</i>	3,566.00
9050		Quick Disconnect Yoke Series 08, 1-3/4 In., 20 Splines for Series 13 Snowblowers, Models (SB1392, SB1308, SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	295.00
9060		Quick Hitch Kit <i>Required for Cat 2 and Cat 3 Quick-Hitch. For SB1388 and SB1388R Snowblower.</i>	860.00
<b>AUGER KIT</b>			
9010		2nd Auger Kit <i>15 In. diameter.</i>	1,540.00
<b>MAIN AUGER</b>			
9012		Serrated Main Auger	3,009.00
<b>CUTTING EDGE</b>			
9000		Cutting Edge - CHT400 Steel	313.00
9002		Cutting Edge - Tivar <i>Fully Plastic - Wear &amp; Rust Resistant.</i>	699.00
9003		Cutting Edge - Stainless Steel	699.00
<b>DRIFT CUTTERS</b>			
9020		Drift Cutters	404.00
<b>SKID SHOES</b>			
9070		Stainless Steel Pivoting Skid Shoes (13-Series Snowblower)	591.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Miscellaneous</b>			
	5RDF0064	2nd Auger Kit - 15 In. Diameter	1,866.16
	5RDF0051	Cutting Edge - CHT400 Steel	342.04
	5RDF0059	Cutting Edge for SB1392 & SB1392R - Stainless Steel	724.91
	5RDF0055	Cutting Edge for SB1392 & SB1392R - Tivar <i>Fully Plastic - Wear and Rust Resistant.</i>	724.91
	5RDF0074	Drift Cutters	419.11
	5RDF0071	Hydraulic Cylinder Kit for Chute Deflector	359.89

**Snow Products****SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
Chute Rotation and Single Auger - U.S.**

Continued

<b>Code</b>	<b>Attachment Identifier</b>	<b>Description</b>	<b>List Price Suggested USD (\$)</b>
		<b>ATTACHMENTS FOR FIELD CONVERSION ...Continued...</b>	
5RDF0075		Quick Hitch Kit for SB13 Series Snowblowers except SB1388 & SB1388R <i>Required for Cat 2 &amp; Cat 3 Quick-Hitch</i>	892.11
5RDF0023		Quick disconnect Yoke series 08, 1-3/4", 20 splines for series 13 snowblowers, models (SB1392, SB1308, and SB1309) <i>Bundle Number 5RDF0022 is needed to complete kit.</i>	305.80
5RDF0076		Reducer 1000 RPM Tractor PTO to 540 RPM for 13 series snowblowers, models (SB1392, SB1308, and SB1309)	3,741.14
5RDF0068		Serrated Main Auger for SB1392 & SB1392R	3,336.19
5RDF0062		Stainless Steel Pivoting Skid Shoes	741.87

**FRONTIER PRODUCTS**

**Snow Products**

---

**SB1392R - 92 In. 3-Point Commercial Rotating Drum Snowblower with Hydraulic Motor  
Chute Rotation and Single Auger - U.S.**

Continued

---

THIS PAGE INTENTIONALLY LEFT BLANK

---



**FRONTIER PRODUCTS**

**Snow Products**

**SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower**  
 Equipment for Base Machine

Function: Snow Removal  
 Working Width: 64 In. (1,625.6 mm)  
 Transport Width: 64 In. (1,625.6 mm)  
 Working Height: 27 In. (685.8 mm)  
 Single/Dual Auger: Single  
 Auger Diameter: 15 In.  
 Auger Flighting Thickness: 5/16 In. (8 mm)  
 Impeller Diameter: 24 In. (609.6 mm)  
 Impeller Width: 7 In. (177.8 mm)  
 Impeller Shaft Diameter: 1.25 In. (31.75 mm)  
 Number of Impeller Blades: 4  
 Auger Drive: Hydraulic  
 Impeller Drive: Hydraulic  
 Impeller RPM: 680 RPM  
 Auger RPM: 200 RPM  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel  
 End Plate Thickness: 3/16 In. (4.8 mm)  
 Back Plate Thickness: 11 Gauge (3.18 mm)  
 Impeller Housing Thickness: 3/16 In. (4.8 mm)  
 Impeller Blade Thickness: 1/4 In. (6.4 mm)  
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)  
 Cutting Edge: Replaceable  
 Cutting Edge Dimension: 3/8 In. x 2 In. (9.5 mm x 50.8 mm)  
 Chute Diameter: 8.25 In. (209.6 mm)  
 Chute Base: Standard  
 Chute Rotation: 270 Degrees  
 Operating Weight: 760 lbs. (344.7 kg)  
 Shipping Weight: 840 lbs. (381 kg)  
 Approximate Set-Up Time: 120 Minutes  
 Chute Deflector Adjustment (Standard):

Must Choose an option Manual Tie Rod or Hydraulic Cylinder  
 Chute Deflector Adjustment Options:  
 Electric Solenoid Valve, Switch, and Hydraulic Cylinder  
 Chute: Two Part ONLY  
 Dual Auger: N/A  
 Rotating Drum (Including Hoses and Tips): N/A  
 Function: Hydraulic Power Unit  
 Pressure: 2700 psi  
 Flow: 16 gpm  
 Reservoir Capacity: 15 gal.  
 System Capacity: 17 gal.  
 System Features: Pressure relieve valve, filter, temperature and oil level gauge, and thermal protection switch  
 Hoses, Tips, and Brackets included  
 Tractor RPM: 540 RPM  
 PTO Manufacturer: Comer  
 Parking Stand: Standard  
 Hitch Category: Category I  
 Quick Hitch Compatibility: iMatch Compatible  
 Approximate Set-Up Time: 120 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

**BASE MACHINE**

3822XF		SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower <i>With Hydraulic Chute Rotation and HP2025 Hydraulic Power Unit - U.S.                  Must only be used with HP2025 Hydraulic Power Unit.</i>	15,615.00
--------	--	--	-----------

**HYDRAULIC POWER UNITS**

1000		HP2025 - Hydraulic Power Unit, 25 HP <i>Includes wiring harness 5RDF0078 to control the loader mounted implement.</i>	In Base Price
1095		Less Hydraulic Power Unit <i>HP2025</i>	-7,785.00

**OIL COOLER**

2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.                  Not available with option Code 1095.</i>	In Base Price
2095		Less Oil Cooler	-1,989.00

## FRONTIER PRODUCTS

## Snow Products

**SB2164 - 64 In Hydraulic, 300 Series Carrier Loader Mount Snowblower**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>CHUTES</b>			
3000		SB21 Manual Chute Deflection <i>Includes manual deflector.</i>	In Base Price
3010		Hydraulic Chute Deflection <i>Includes cylinders, hoses and fittings.</i>	681.00
<b>HYDRAULIC ELECTRIC KIT</b>			
9040		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Not available with option Code 1095.</i>	110.00
<b>DRIFT CUTTERS</b>			
9020		Drift Cutters (SB21)	162.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Miscellaneous</b>			
5RDF0026		Drift Cutters (SB21)	168.31
5RDF0027		Kit for Hydraulic Chute Deflector (SB2164)	754.06
5RDF0036		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	2,063.60
5RDF0038		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	114.40
5RDF0078		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i>	159.51

**FRONTIER PRODUCTS**

**Snow Products**

**SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower**  
 Equipment for Base Machine

Function: Snow Removal  
 Working Width: 76 In. (1,931.4 mm)  
 Transport Width: 76 In. (1,931.4 mm)  
 Working Height: 27 In. (685.8 mm)  
 Single/Dual Auger: Single  
 Auger Diameter: 15 In.  
 Auger Flighting Thickness: 5/16 In. (8 mm)  
 Impeller Diameter: 24 In. (609.6 mm)  
 Impeller Width: 8.5 In. (215.9 mm)  
 Impeller Shaft Diameter: 1.25 In. (31.75 mm)  
 Number of Impeller Blades: 4  
 Auger Drive: Hydraulic  
 Impeller Drive: Hydraulic  
 Impeller RPM: 580 RPM  
 Auger RPM: 180 RPM  
 Skid Shoe: Adjustable  
 Skid Shoe Material: Steel  
 End Plate Thickness: 3/16 In. (4.8 mm)  
 Back Plate Thickness: 11 Gauge (3.18 mm)  
 Impeller Housing Thickness: 3/16 In. (4.8 mm)  
 Impeller Blade Thickness: 5/16 In. (8 mm)  
 Side Panel Bottom Thickness: 1/2 In. (12.7 mm)  
 Cutting Edge: Replaceable  
 Cutting Edge Dimension: 1/2 In. x 3 In. (12.7 mm x 76.2 mm)  
 Chute Diameter: 12 In. (0.3m)  
 Chute Base: Standard  
 Chute Rotation: 270 Degrees  
 Operating Weight: 760 lbs. (344.7 kg)  
 Shipping Weight: 840 lbs. (381 kg)  
 Approximate Set-Up Time: 120 Minutes  
 Chute Deflector Adjustment (Standard):

Must Choose an option Manual or Hydraulic  
 Adjustable Tie Rod or Hydraulic  
 Chute Deflector Adjustment Options:  
 Electric Solenoid Valve, Switch, Wiring Harness  
 and Hydraulic Cylinder  
 Chute: Two Part ONLY  
 Dual Auger: N/A  
 Rotating Drum (Including Hoses and Tips):  
 N/A  
 Function: Hydraulic Power Unit  
 Pressure: 2700 psi  
 Flow: 16 gpm  
 Reservoir Capacity: 15 gal.  
 System Capacity: 17 gal.  
 System Features: Pressure relieve valve, filter,  
 temperature  
 and oil level gauge, and thermal protection switch  
 Hoses, Tips, and Brackets included  
 Tractor RPM: 540 RPM  
 PTO Manufacturer: Comer  
 Parking Stand: Standard  
 Hitch Category: Category I  
 Quick Hitch Compatibility:  
 iMatch Compatible  
 Approximate Set-Up Time: 120 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
<b>BASE MACHINE</b>			
3821XF		SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower <i>With Hydraulic Chute Rotation and HP2134 Hydraulic Power Unit - U.S. Must only be used with HP2134 Hydraulic Power Unit.</i>	16,061.00
<b>HYDRAULIC POWER UNITS</b>			
1095		Less Hydraulic Power Unit <i>HP2134</i>	-7,919.00
1010		HP2134 - Hydraulic Power Unit, 34 HP <i>Includes wiring harness 5RDF0078 to control the loader mounted implement.</i>	In Base Price
<b>OIL COOLER</b>			
2000		Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat. Not available with option Code 1095.</i>	In Base Price
2095		Less Oil Cooler	-1,989.00

## FRONTIER PRODUCTS

## Snow Products

**SB2176 - 76 In. Hydraulic, 400 Series Carrier Loader Mount Snowblower**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
<b>CHUTES</b>			
3000		SB21 Manual Chute Deflection <i>Includes manual deflector.</i>	In Base Price
3010		Hydraulic Chute Deflection <i>Includes cylinders, hoses and fittings.</i>	681.00
<b>HYDRAULIC ELECTRIC KIT</b>			
9040		Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Not available with option Code 1095.</i>	110.00
<b>DRIFT CUTTERS</b>			
9020		Drift Cutters (SB21)	162.00
<b>ATTACHMENTS FOR FIELD CONVERSION</b>			
<b>Miscellaneous</b>			
	5RDF0026	Drift Cutters (SB21)	168.31
	5RDF0025	Kit for Hydraulic Chute Deflector (SB2176)	706.07
	5RDF0036	Oil Cooler for HP2025 and HP2134 Hydraulic Power Units <i>Includes high efficiency oil cooler, electric fan, bolted support, hoses, fittings and installation instructions. Recommended for application generating high heat.</i>	2,063.60
	5RDF0038	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units for Open Operator Station Tractors <i>Includes complete wiring harness from battery to switch in the console.</i>	114.40
	5RDF0078	Wiring Harness for HP2025 and HP2134 Hydraulic Power Units to control Loader Mounted Attachment <i>Includes complete wiring harness from switch in the console to 3 cavities connectors for front implements.</i>	159.51