

FRONTIER PRODUCTS

Tillage

RC2210 - 121 In. Medium Duty Row Crop Tiller

Equipment for Base Machine

Working Width:
121 In. (3,073.4 mm)
Tractor PTO Speed: 1000 RPM
Tractor PTO HP (Minimum): 100 HP
Tractor PTO HP (Maximum): 170 HP
Blade Shape: L
Skid Shoes: Adjustable
Side Drive: Gear
Rear Door Support:
Metal Rod with Double Spring
Parking Stand Included
Gearbox Speed: 2 + 2 Speed
Rotor Speed:
181-246-300 RPM
Rotor Flanges: 11

Blades/Rotor: 6
Working Depth (Maximum):
11 In. (279.4 mm)
Driveline Protection: Friction Clutch
Tillage Depth Control: Skid Shoes
Hitch:
Category II and Category III Narrow,
Quick Hitch Compatible

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

1691XF		RC2210 - 121 In. Medium Duty Row Crop Tiller	18,925.00
--------	--	--	-----------

DEPTH CONTROL SYSTEM

4500		Skid Shoe (RC2210)	In Base Price
4510		Cage Roller Manual Control (RC2210)	3,141.00
4520		Cage Roller Hydraulic Control (RC2210)	3,389.00

DEPTH CONTROL SYSTEM

8000		Right Disc <i>For RT22, RT23, RC13, and RC22 Series.</i>	836.00
8010		Left Disc <i>For RT22, RT23, RC13, and RC22 Series.</i>	836.00

MISCELLANEOUS

9400		Flange Reinforcement Kit <i>For RC2210.</i>	1,037.00
------	--	--	----------

ATTACHMENTS FOR FIELD CONVERSION

	Miscellaneous		
5MH99530575		Flange Reinforcement Kit (RC2210)	1,075.80

Tillage

RC2210 - 121 In. Medium Duty Row Crop Tiller
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage

DH1048 - 4 Ft. Disk Harrow with 12 Blades on 7.5 In. Spacing
 Equipment for Base Machine

3-Point Hitch: Category I
 Working Width: 48 In.
 Blade Spacing: 7.5 In.
 Tractor HP (Max): 28 HP
 Shipping Weight: 452 lbs.
 Approximate Operating Weight: 388 lbs.
 Number of Blades: 12
 Blade Size: 16 In. Diameter
 Blade Thickness: 3 mm (0.118 In.)
 Front Gang Blade Type: Notched
 Rear Gang Blade Type: Notched
 Frame Tubing: 2 In. Square
 Gang Tubing: 2 In. Square
 Bearing Hanger:

3/8 In. Formed Plate with 1/2 In. U-bolt
 Bearing Type:
 Self Aligning Sealed Ball Bearing
 in Pre-Riveted Flange
 Gang Axle: 1 In. Square
 Front Gang Angles: 2, 6, 12, 18 Degrees
 Rear Gang Angles: 10, 14, 18, 23 Degrees
 Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3311XF	DH1048 - 4 Ft. Disk Harrow with 12 Blades on 7.5 In. Spacing	1,774.00
--------	--	----------

Attachment Information is not available in MOCI for the base code 3311XF

Tillage

DH1048 - 4 Ft. Disk Harrow with 12 Blades on 7.5 In. Spacing

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage

DH1066 - 5 Ft. 6 In. Disk Harrow with 16 Blades on 7.5 In. Spacing
 Equipment for Base Machine

3-Point Hitch: Category I
 Working Width: 66 In.
 Blade Spacing: 7.5 In.
 Tractor HP (Maximum): 28 HP
 Shipping Weight: 540 lbs.
 Approximate Operating Weight: 445 lbs.
 Number of Blades: 16
 Blade Size: 16 In. Diameter
 Blade Thickness: 3 mm (0.118 In.)
 Front Gang Blade Type: Notched
 Rear Gang Blade Type: Notched
 Frame Tubing: 2 In. Square
 Gang Tubing: 2 In. Square
 Bearing Hanger:

3/8 In. Formed Plate with 1/2 In. U-bolt
 Bearing Type:
 Self Aligning Sealed Ball Bearing
 in Pre-Riveted Flange
 Gang Axle: 1 In. Square
 Front Gang Angles: 2, 6, 12, 18 Degrees
 Rear Gang Angles: 10, 14, 18, 23 Degrees
 Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3312XF		DH1066 - 5 Ft. 6 In. Disk Harrow with 16 Blades on 7.5 In. Spacing	1,962.00
--------	--	--	----------

Attachment Information is not available in MOCI for the base code 3312XF

Tillage

DH1066 - 5 Ft. 6 In. Disk Harrow with 16 Blades on 7.5 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH1166 - 5 Ft. 6 In. 3-Point Disk Harrow with 16 Blades on 7.5 In. Spacing**
Equipment for Base Machine

3-Point Hitch: Category I
 Working Width: 66 In.
 Blade Spacing: 7.5 In.
 Tractor HP (Maximum): 45 HP
 Shipping Weight: 755 lbs.
 Approximate Operating Weight: 660 lbs.
 Number of Blades: 16
 Blade Size: 18 In. Diameter
 Blade Thickness: 3 mm (0.118 In.)
 Frame Tubing: 3 In. Square
 Gang Tubing: 3 In. Square
 Bearing Hanger:
 1/2 In. Formed Plate with Reinforcement
 and 2 x - 5/8 In. U-bolts

Bearing Type:
 Self Aligning Sealed Ball Bearing
 in Pre-Riveted Flange
 Gang Axle: 1 In. Square
 Front Gang Angles: 2, 9, 13, 24 Degrees
 Rear Gang Angles: 5, 11, 20, 27 Degrees
 Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3321XF		DH1166 - 5 Ft. 6 In. 3-Point Disk Harrow with 16 Blades on 7.5 In. Spacing	2,442.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>18 In. Diameter for 1 In. Shaft (3mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>18 In. Diameter for 1 In. Shaft (3mm Thick)</i>	37.00
1020		Notched Front and Smooth Rear Disk Blades <i>18 In. Diameter for 1 In. Shaft (3mm Thick)</i>	18.00

ATTACHMENTS FOR FIELD CONVERSION

5TLRSK716	Miscellaneous Scraper Kit (DH1166)	455.40
-----------	--	--------

Tillage

DH1166 - 5 Ft. 6 In. 3-Point Disk Harrow with 16 Blades on 7.5 In. Spacing

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH1176 - 6 Ft. 4 In. 3-Point Disk Harrow with 16 Blades on 9 In. Spacing**
Equipment for Base Machine

3-Point Hitch: Category I
 Working Width: 76 In.
 Blade Spacing: 9 In.
 Tractor HP (Maximum): 45 HP
 Shipping Weight: 814 lbs.
 Approximate Operating Weight: 705 lbs.
 Number of Blades: 16
 Blade Size: 18 In. Diameter
 Blade Thickness: 3 mm (0.118 In.)
 Frame Tubing: 3 In. Square
 Gang Tubing: 3 In. Square
 Bearing Hanger:
 1/2 In. Formed Plate with Reinforcement
 and 2 x - 5/8 In. U-bolts

Bearing Type:
 Self Aligning Sealed Ball Bearing
 in Pre-Riveted Flange
 Gang Axle: 1 In. Square
 Front Gang Angles: 2, 9, 13, 24 Degrees
 Rear Gang Angles: 5, 11, 20, 27 Degrees
 Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3322XF		DH1176 - 6 Ft. 4 In. 3-Point Disk Harrow with 16 Blades on 9 In. Spacing	2,530.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>18 In. Diameter for 1 In. Shaft (3mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>18 In. Diameter for 1 In. Shaft (3mm Thick)</i>	37.00
1020		Notched Front and Smooth Rear Disk Blades <i>18 In. Diameter for 1 In. Shaft (3mm Thick)</i>	18.00

ATTACHMENTS FOR FIELD CONVERSION

5TLRSK916	Miscellaneous Scraper Kit (DH1176)	473.00
-----------	--	--------

Tillage

DH1176 - 6 Ft. 4 In. 3-Point Disk Harrow with 16 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH1180 - 6 Ft. 8 In. 3-Point Disk Harrow with 20 Blades on 7.5 In. Spacing**
Equipment for Base Machine

3-Point Hitch: Category I
 Working Width: 80 In.
 Blade Spacing: 7.5 In.
 Tractor HP (Maximum): 45 HP
 Shipping Weight: 820 lbs.
 Approximate Operating Weight: 735 lbs.
 Number of Blades: 20
 Blade Size: 18 In. Diameter
 Blade Thickness: 3 mm (0.118 In.)
 Frame Tubing: 3 In. Square
 Gang Tubing: 3 In. Square
 Bearing Hanger:
 1/ In. Formed Plate with Reinforcement
 and 2 x - 5/8 In. U-bolts

Bearing Type:
 Self Aligning Sealed Ball Bearing
 in Pre-Riveted Flange
 Gang Axle: 1 In. Square
 Front Gang Angles: 2, 9, 13, 24 Degrees
 Rear Gang Angles: 5, 11, 20, 27 Degrees
 Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3323XF		DH1180 - 6 Ft. 8 In. 3-Point Disk Harrow with 20 Blades on 7.5 In. Spacing	2,743.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>18 In. Diameter for 1 In. Shaft (3mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>18 In. Diameter for 1 In. Shaft (3mm Thick)</i>	48.00
1020		Notched Front and Smooth Rear Disk Blades <i>18 In. Diameter for 1 In. Shaft (3mm Thick)</i>	22.00

ATTACHMENTS FOR FIELD CONVERSION

5TLRSK720	Miscellaneous	Scrapper Kit for base machine DH1180 (No Furrow Fillers)	521.40
-----------	----------------------	--	--------

Tillage

DH1180 - 6 Ft. 8 In. 3-Point Disk Harrow with 20 Blades on 7.5 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH1276 - 6 Ft. 4 In. 3-Point Disk Harrow with 16 Blades on 9 In. Spacing**
Equipment for Base Machine

3-Point Hitch: Category I
 Working Width: 76 In.
 Blade Spacing: 9 In.
 Tractor HP (Maximum): 55 HP
 Shipping Weight: 935 lbs.
 Approximate Operating Weight: 890 lbs.
 Number of Blades: 16
 Blade Size: 20 In. Diameter
 Blade Thickness: 3.5 mm (0.138 In.)
 Frame Tubing: 3 In. Square
 Gang Tubing: 3 In. Square
 Bearing Hanger:
 High Strength 3 In. Channel Steel Hangers
 with 5/8 In. Bolts and Plate

Bearing Type:
 Self Aligning Sealed Ball Bearing
 in Pillow Block
 Gang Axle: 1-1/8 In. Square
 Front Gang Angles: 13, 16, 19, 23 Degrees
 Rear Gang Angles: 8, 11, 19, 23 Degrees
 Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3331XF		DH1276 - 6 Ft. 4 In. 3-Point Disk Harrow with 16 Blades on 9 In. Spacing	3,382.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	77.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	38.00

ATTACHMENTS FOR FIELD CONVERSION

	Miscellaneous		
5TL11477		Center Sweep Kit (all DH12 Series Models)	342.11
5TLRB1276		DH1276 Rolling Basket	1,850.20
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLSK916H		Scraper Kit with 9 In. Spacing for base machine DH1276 (No Furrow Fillers)	710.60

Tillage

DH1276 - 6 Ft. 4 In. 3-Point Disk Harrow with 16 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH1280 - 6 Ft. 8 In. 3-Point Disk Harrow with 20 Blades on 7.5 In. Spacing**
Equipment for Base Machine

3-Point Hitch: Category I
 Working Width: 80 In.
 Blade Spacing: 7.5 In.
 Tractor HP (Maximum): 55 HP
 Shipping Weight: 978 lbs.
 Approximate Operating Weight: 942 lbs.
 Number of Blades: 20
 Blade Size: 20 In. Diameter
 Blade Thickness: 3.5 mm (0.138 In.)
 Frame Tubing: 3 In. Square
 Gang Tubing: 3 In. Square
 Bearing Hanger:
 High Strength 3 In. Channel Steel Hangers
 with 5/8 In. Bolts and Plate

Bearing Type:
 Self Aligning Sealed Ball Bearing
 in Pillow Block
 Gang Axle: 1-1/8 In. Square
 Front Gang Angles: 13, 16, 19, 23 Degrees
 Rear Gang Angles: 8, 11, 19, 23 Degrees
 Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3332XF		DH1280 - 6 Ft. 8 In. 3-Point Disk Harrow with 20 Blades on 7.5 In. Spacing	3,746.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	98.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	49.00

ATTACHMENTS FOR FIELD CONVERSION

	Miscellaneous		
5TL11477		Center Sweep Kit (all DH12 Series Models)	342.11
5TLRB1280		DH1280 Rolling Basket	1,850.20
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLSK720H		Scraper Kit with 7.5 In. Spacing (DH1280)	831.60

Tillage

DH1280 - 6 Ft. 8 In. 3-Point Disk Harrow with 20 Blades on 7.5 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage**

DH1280 - 6 Ft. 8 In. 3-Point Disk Harrow with 18 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear
Equipment for Base Machine

3-Point Hitch: Category I
 Working Width: 80 In.
 Blade Spacing:
 9 In. Front and 7.5 In. Rear
 Tractor HP (Maximum): 55 HP
 Shipping Weight: 969 lbs.
 Approximate Operating Weight: 915 lbs.
 Number of Blades: 18
 Blade Size: 20 In. Diameter
 Blade Thickness: 3.5 mm (0.138 In.)
 Frame Tubing: 3 In. Square
 Gang Tubing: 3 In. Square
 Bearing Hanger:
 High Strength 3 In. Channel Steel Hangers

with 5/8 In. Bolts and Plate
 Bearing Type:
 Self Aligning Sealed Ball Bearing
 in Pillow Block
 Gang Axle: 1-1/8 In. Square
 Front Gang Angles: 13, 16, 19, 23 Degrees
 Rear Gang Angles: 8, 11, 19, 23 Degrees
 Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3335XF		DH1280 - 6 Ft. 8 In. 3-Point Disk Harrow with 18 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear	3,636.00
--------	--	---	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	87.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	49.00

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous		
5TL11477	Center Sweep Kit (all DH12 Series Models)	342.11
5TLRB1280	DH1280 Rolling Basket	1,850.20
5TLT70316	Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TL9718H	Scraper Kit with 9 In. Front Spacing and 7.5 In. Rear Spacing for base machine DH1280 (No Furrow Fillers)	786.51

Tillage

DH1280 - 6 Ft. 8 In. 3-Point Disk Harrow with 18 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH1296 - 8 Ft. 3-Point Disk Harrow with 20 Blades on 9 In. Spacing**
Equipment for Base Machine

3-Point Hitch: Category I
 Working Width: 96 In.
 Blade Spacing: 9 In.
 Tractor HP (Maximum): 55 HP
 Shipping Weight: 1040 lbs.
 Approximate Operating Weight: 968 lbs.
 Number of Blades: 20
 Blade Size: 20 In. Diameter
 Blade Thickness: 3.5 mm (0.138 In.)
 Frame Tubing: 3 In. Square
 Gang Tubing: 3 In. Square
 Bearing Hanger:
 High Strength 3 In. Channel Steel Hangers
 with 5/8 In. Bolts and Plate

Bearing Type:
 Self Aligning Sealed Ball Bearing
 in Pillow Block
 Gang Axle: 1-1/8 In. Square
 Front Gang Angles: 13, 16, 19, 23 Degrees
 Rear Gang Angles: 8, 11, 19, 23 Degrees
 Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3333XF		DH1296 - 8 Ft. 3-Point Disk Harrow with 20 Blades on 9 In. Spacing	3,888.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	98.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	49.00

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous		
5TL11477	Center Sweep Kit (all DH12 Series Models)	342.11
5TLRB1296	DH1296 Rolling Basket	2,234.11
5TLT70316	Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLSK920H	Scraper Kit with 9 In. Spacing for base machine DH1296 (No Furrow Filler)	883.31

Tillage

DH1296 - 8 Ft. 3-Point Disk Harrow with 20 Blades on 9 In. Spacing

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH1296 - 8 Ft. 3-Point Disk Harrow with 24 Blades on 7.5 In. Spacing**
Equipment for Base Machine

3-Point Hitch: Category I
 Working Width: 96 In.
 Blade Spacing: 7.5 In.
 Tractor HP (Maximum): 55 HP
 Shipping Weight: 1066 lbs.
 Approximate Operating Weight: 1038 lbs.
 Number of Blades: 24
 Blade Size: 20 In. Diameter
 Blade Thickness: 3.5 mm (0.138 In.)
 Frame Tubing: 3 In. Square
 Gang Tubing: 3 In. Square
 Bearing Hanger:
 High Strength 3 In. Channel Steel Hangers
 with 5/8 In. Bolts and Plate

Bearing Type:
 Self Aligning Sealed Ball Bearing
 in Pillow Block
 Gang Axle: 1-1/8 In. Square
 Front Gang Angles: 13, 16, 19, 23 Degrees
 Rear Gang Angles: 8, 11, 19, 23 Degrees
 Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3334XF		DH1296 - 8 Ft. 3-Point Disk Harrow with 24 Blades on 7.5 In. Spacing	4,360.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	117.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	59.00

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous		
5TL11477	Center Sweep Kit (all DH12 Series Models)	342.11
5TLRB1296	DH1296 Rolling Basket	2,234.11
5TLT70316	Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLSK724H	Scraper Kit with 7.5 In. Spacing for base machine DH1296 (No Furrow Fillers)	1,031.80

Tillage

DH1296 - 8 Ft. 3-Point Disk Harrow with 24 Blades on 7.5 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Tillage

DH1376 - 6 Ft. 4 In. 3-Point Disk Harrow with 16 Blades on 9 In. Spacing

Equipment for Base Machine

3-Point Hitch: Category I and II
(Quick Hitch Compatible)
Working Width: 76 In.
Blade Spacing: 9 In.
Tractor HP (Maximum): 75 HP
Shipping Weight: 1229 lbs.
Approximate Operating Weight: 1109 lbs.
Number of Blades: 16
Blade Size: 22 In. Diameter
Blade Thickness: 4 mm (0.157 In.)
Frame Tubing: 4 In. x 3 In.
Gang Tubing: 4 In. x 3 In.
Bearing Hanger:
2 In. x 4 In. Steel Tubing

with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed Ball Bearing
in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles: 9, 12, 15, 18 Degrees
Rear Gang Angles: 9, 12, 15, 18 Degrees
Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3341XF		DH1376 - 6 Ft. 4 In. 3-Point Disk Harrow with 16 Blades on 9 In. Spacing	4,250.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	74.00
1020		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	36.00

ATTACHMENTS FOR FIELD CONVERSION

	Miscellaneous		
5TL11476		Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1376		DH1376 Rolling Basket	1,833.71
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TLSK91643		Scraper Kit with 9 In. Spacing (DH1376)	720.51

Tillage

DH1376 - 6 Ft. 4 In. 3-Point Disk Harrow with 16 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH1380 - 6 Ft. 8 In. 3-Point Disk Harrow with 20 Blades on 7.5 In. Spacing**
Equipment for Base Machine

3-Point Hitch: Category I and II
(Quick Hitch Compatible)
Working Width: 80 In.
Blade Spacing: 7.5 In.
Tractor HP (Maximum): 75 HP
Shipping Weight: 1326 lbs.
Approximate Operating Weight: 1206 lbs.
Number of Blades: 20
Blade Size: 22 In. Diameter
Blade Thickness: 4 mm (0.157 In.)
Frame Tubing: 4 In. x 3 In.
Gang Tubing: 4 In. x 3 In.
Bearing Hanger:
2 In. x 4 In Steel Tubing

with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed Ball Bearing
in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles: 9, 12, 15, 18 Degrees
Rear Gang Angles: 9, 12, 15, 18 Degrees
Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3342XF		DH1380 - 6 Ft. 8 In. 3-Point Disk Harrow with 20 Blades on 7.5 In. Spacing	4,806.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	93.00
1020		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	47.00

ATTACHMENTS FOR FIELD CONVERSION

	Miscellaneous		
5TL11476		Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1380		DH1380 Rolling Basket	1,833.71
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TLSK72043		Scraper Kit with 7.5 In. Spacing (DH1380)	831.60

Tillage

DH1380 - 6 Ft. 8 In. 3-Point Disk Harrow with 20 Blades on 7.5 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage**DH1396 - 8 Ft. 3-Point Disk Harrow with 20 Blades on 9 In. Spacing**
Equipment for Base Machine

3-Point Hitch: Category I and II
(Quick Hitch Compatible)
Working Width: 96 In.
Blade Spacing: 9 In.
Tractor HP (Maximum): 75 HP
Shipping Weight: 1376 lbs.
Approximate Operating Weight: 1256 lbs.
Number of Blades: 20
Blade Size: 22 In. Diameter
Blade Thickness: 4 mm (0.157 In.)
Frame Tubing: 4 In. x 3 In.
Gang Tubing: 4 In. x 3 In.
Bearing Hanger:
2 In. x 4 In. Steel Tubing

with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed Ball Bearing
in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles: 9, 12, 15, 18 Degrees
Rear Gang Angles: 9, 12, 15, 18 Degrees
Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3343XF		DH1396 - 8 Ft. 3-Point Disk Harrow with 20 Blades on 9 In. Spacing	4,893.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	93.00
1020		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	47.00

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous		
5TL11476	Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1396	DH1396 Rolling Basket	2,222.00
5TLT70318	Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TLSK92043	Scraper Kit with 9 In. Spacing (DH1396)	885.51

Tillage

DH1396 - 8 Ft. 3-Point Disk Harrow with 20 Blades on 9 In. Spacing

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage**DH1396 - 8 Ft. 3-Point Disk Harrow with 24 Blades on 7.5 In. Spacing**
Equipment for Base Machine

3-Point Hitch: Category I and II
(Quick Hitch Compatible)
Working Width: 96 In.
Blade Spacing: 7.5 In.
Tractor HP (Maximum): 75 HP
Shipping Weight: 1466 lbs.
Approximate Operating Weight: 1346 lbs.
Number of Blades: 24
Blade Size: 22 In. Diameter
Blade Thickness: 4 mm (0.157 In.)
Frame Tubing: 4 In. x 3 In.
Gang Tubing: 4 In. x 3 In.
Bearing Hanger:
2 In. x 4 In. Steel Tubing

with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed Ball Bearing
in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles: 9, 12, 15, 18 Degrees
Rear Gang Angles: 9, 12, 15, 18 Degrees
Approximate Assembly Time: 15 Minutes

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3344XF		DH1396 - 8 Ft. 3-Point Disk Harrow with 24 Blades on 7.5 In. Spacing	5,376.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	111.00
1020		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	55.00

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous		
5TL11476	Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1396	DH1396 Rolling Basket	2,222.00
5TLT70318	Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TLSK72443	Scraper Kit with 7.5 In. Spacing (DH1396)	1,023.00

Tillage

DH1396 - 8 Ft. 3-Point Disk Harrow with 24 Blades on 7.5 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH1508 - 8 Ft. Drawn Disk Harrow with 24 Blades on 7.5 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 3 In. x 8 In. Cylinder
with 150 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (9.5L-15 6 Ply)
Working Width: 8 Ft.
Blade Spacing: 7.5 In.
Tractor HP: 35-55 HP
Shipping Weight: 2018 lbs.
Approximate Operating Weight: 1943 lbs.
Number of Blades: 24
Blade Size: 20 In. or 22 In. Diameter
Blade Thickness: 3.5 mm (0.138 In.) with
20 In. or 4 mm (0.157 In.) with 22 In.
Frame Tubing: 3 In. Square
Gang Tubing: 3 In. Square

Bearing Hanger:
2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed or Lubricated
Ball Bearing in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles:
9, 13, 14, 16, 19, 20, 23, 24, 26 Degrees
Rear Gang Angles:
8, 11, 13, 15, 16, 19, 21, 23, 27 Degrees
Approximate Assembly Time: 4 Hours

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3351XF		DH1508 - 8 Ft. Drawn Disk Harrow with 24 Blades on 7.5 In. Spacing	9,020.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	116.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	58.00
1040		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	555.00
1060		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	670.00
1080		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	552.00

DISK GANG BEARING STYLE

2000		Relube Bearings for 1.125 In. Gang Beam Shaft	98.00
2010		Sealed Bearings for 1.125 In. Gang Beam Shaft	In Base Price

SCRAPERS

9000		Scraper Kit <i>7.5 In. Spacing with 24 Blades.</i>	840.00
------	--	---	--------

FRONTIER PRODUCTS

Tillage

DH1508 - 8 Ft. Drawn Disk Harrow with 24 Blades on 7.5 In. Spacing

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		SCRAPERS ...Continued...	
9030		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 Series Models)	136.00
		MIDDLE BREAKER	
9020		Middle Breaker Kit <i>For all DH1508 and DH1509 Models.</i>	316.00
		MISCELLANEOUS	
9010		Furrow Filler Kit for all Units with 20 In. Blades	286.00
9015		Furrow Filler Kit for all Units with 22 In. Blades	292.00
905G		DH1508 Rolling Basket with mounts and weight kit	2,396.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
5TL14177		Center Sweep Kit (all DH1508 and DH1509 Models)	327.80
5TLRB1508		DH1508 Rolling Basket	2,486.00
5TL15745		French Kit - Includes Operator's Manual and Safety Decals (DH15 Series)	61.60
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80
5TL7245		Scraper Kit with 7.5 In. Spacing with 24 Blades for base machine DH1508 (No Furrow Fillers)	871.20

FRONTIER PRODUCTS**Tillage****DH1508 - 8 Ft. Drawn Disk Harrow with 20 Blades on 9 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 3 In. x 8 In. Cylinder
with 150 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (9.5L-15 6 Ply)
Working Width: 8 Ft.
Blade Spacing: 9 In.
Tractor HP: 35-55 HP
Shipping Weight: 1908 lbs.
Approximate Operating Weight: 1833 lbs.
Number of Blades: 20
Blade Size: 20 In. or 22 In. Diameter
Blade Thickness: 3.5 mm (0.138 In.) with
20 In. or 4 mm (0.157 In.) with 22 In.
Frame Tubing: 3 In. Square
Gang Tubing: 3 In. Square

Bearing Hanger:
2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed or Lubricated
Ball Bearing in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles:
9, 13, 14, 16, 19, 20, 23, 24, 26 Degrees
Rear Gang Angles:
8, 11, 13, 15, 16, 19, 21, 23, 27 Degrees
Approximate Assembly Time: 4 Hours

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3352XF		DH1508 - 8 Ft. Drawn Disk Harrow with 20 Blades on 9 In. Spacing	8,338.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	98.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	49.00
1040		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	463.00
1060		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	559.00
1080		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	509.00

DISK GANG BEARING STYLE

2000		Relube Bearings for 1.125 In. Gang Beam Shaft	98.00
2010		Sealed Bearings for 1.125 In. Gang Beam Shaft	In Base Price

SCRAPERS

9000		Scraper Kit <i>9 In. Spacing with 20 Blades.</i>	819.00
------	--	---	--------

FRONTIER PRODUCTS

Tillage

DH1508 - 8 Ft. Drawn Disk Harrow with 20 Blades on 9 In. Spacing

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		SCRAPERS ...Continued...	
9030		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 Series Models)	136.00
		MIDDLE BREAKER	
9020		Middle Breaker Kit <i>For all DH1508 and DH1509 Models.</i>	316.00
		MISCELLANEOUS	
9010		Furrow Filler Kit for all Units with 20 In. Blades	286.00
9015		Furrow Filler Kit for all Units with 22 In. Blades	292.00
905G		DH1508 Rolling Basket with mounts and weight kit	2,396.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
5TL14177		Center Sweep Kit (all DH1508 and DH1509 Models)	327.80
5TLRB1508		DH1508 Rolling Basket	2,486.00
5TL15745		French Kit - Includes Operator's Manual and Safety Decals (DH15 Series)	61.60
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80
5TL9205		Scraper Kit with 9 In. Spacing with 20 Blades for base machine DH1508 (No Furrow Fillers)	850.31

FRONTIER PRODUCTS**Tillage****DH1508 - 8 Ft. Drawn Disk Harrow with 22 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear**

Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 3 In. x 8 In. Cylinder
with 150 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (9.5L-15 6 Ply)
Working Width: 8 Ft.
Blade Spacing: 9 In. Front and 7.5 In. Rear
Tractor HP: 35-55 HP
Shipping Weight: 1943 lbs.
Approximate Operating Weight: 1868 lbs.
Number of Blades: 22
Blade Size: 20 In. or 22 In. Diameter
Blade Thickness: 3.5 mm (0.138 In.) with
20 In. or 4 mm (0.157 In.) with 22 In.
Frame Tubing: 3 In. Square
Gang Tubing: 3 In. Square

Bearing Hanger:
2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed or Lubricated
Ball Bearing in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles:
9, 13, 14, 16, 19, 20, 23, 24, 26 Degrees
Rear Gang Angles:
8, 11, 13, 15, 16, 19, 21, 23, 27 Degrees
Approximate Assembly Time: 4 Hours

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3353XF		DH1508 - 8 Ft. Drawn Disk Harrow with 22 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear	8,765.00
--------	--	---	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	107.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	58.00
1040		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	508.00
1060		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	614.00
1080		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	566.00

DISK GANG BEARING STYLE

2000		Relube Bearings for 1.125 In. Gang Beam Shaft	98.00
2010		Sealed Bearings for 1.125 In. Gang Beam Shaft	In Base Price

SCRAPERS

Tillage

DH1508 - 8 Ft. Drawn Disk Harrow with 22 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		SCRAPERS ...Continued...	
9000		Scraper Kit <i>9 In. Front Spacing and 7.5 In. Rear Spacing with 22 Blades (DH1508).</i>	872.00
9030		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 Series Models)	136.00
		MIDDLE BREAKER	
9020		Middle Breaker Kit <i>For all DH1508 and DH1509 Models.</i>	316.00
		MISCELLANEOUS	
9010		Furrow Filler Kit for all Units with 20 In. Blades	286.00
9015		Furrow Filler Kit for all Units with 22 In. Blades	292.00
905G		DH1508 Rolling Basket with mounts and weight kit	2,396.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
5TL14177		Center Sweep Kit (all DH1508 and DH1509 Models)	327.80
5TLRB1508		DH1508 Rolling Basket	2,486.00
5TL15745		French Kit - Includes Operator's Manual and Safety Decals (DH15 Series)	61.60
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80
5TLSK97225		Scraper Kit with 9 In. Front Spacing and 7.5 In. Rear Spacing with 22 Blades for base machine DH1508 (No Furrow Fillers)	905.31

FRONTIER PRODUCTS**Tillage****DH1509 - 9 Ft. 6 In. Drawn Disk Harrow with 28 Blades on 7.5 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 3 In. x 8 In. Cylinder
with 150 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (9.5L-15 6 Ply)
Working Width: 9 Ft. 6 In.
Blade Spacing: 7.5 In.
Tractor HP: 40-65 HP
Shipping Weight: 2100 lbs.
Approximate Operating Weight: 2025 lbs.
Number of Blades: 28
Blade Size: 20 In. or 22 In. Diameter
Blade Thickness: 3.5 mm (0.138 In.) with
20 In. or 4 mm (0.157 In.) with 22 In.
Frame Tubing: 3 In. Square

Gang Tubing: 3 In. Square
Bearing Hanger: 2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed or Lubricated
Ball Bearing in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles:
9, 13, 14, 16, 19, 20, 23, 24, 26 Degrees
Rear Gang Angles:
8, 11, 13, 15, 16, 19, 21, 23, 27 Degrees
Approximate Assembly Time: 4 Hours

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3354XF		DH1509 - 9 Ft. 6 In. Drawn Disk Harrow with 28 Blades on 7.5 In. Spacing	9,397.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	136.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	68.00
1040		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	649.00
1060		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	783.00
1080		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	714.00

DISK GANG BEARING STYLE

2000		Relube Bearings for 1.125 In. Gang Beam Shaft	98.00
2010		Sealed Bearings for 1.125 In. Gang Beam Shaft	In Base Price

SCRAPERS

9000		Scraper Kit <i>7.5 In. Spacing with 28 Blades.</i>	1,024.00
------	--	---	----------

Tillage

DH1509 - 9 Ft. 6 In. Drawn Disk Harrow with 28 Blades on 7.5 In. Spacing
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
SCRAPERS ...Continued...			
9030		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 Series Models)	136.00
MIDDLE BREAKER			
9020		Middle Breaker Kit <i>For all DH1508 and DH1509 Models.</i>	316.00
MISCELLANEOUS			
9010		Furrow Filler Kit for all Units with 20 In. Blades	286.00
9015		Furrow Filler Kit for all Units with 22 In. Blades	292.00
905H		DH1509 Rolling Basket with mounts and weight kit	2,696.00
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous			
5TL14177		Center Sweep Kit (all DH1508 and DH1509 Models)	327.80
5TLRB1509		DH1509 Rolling Basket	2,797.31
5TL15745		French Kit - Includes Operator's Manual and Safety Decals (DH15 Series)	61.60
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80
5TLSK7285		Scraper Kit with 7.5 In. Spacing with 28 Blades for base machine DH1509 (No Furrow Fillers)	1,062.60

FRONTIER PRODUCTS**Tillage****DH1509 - 9 Ft. 6 In. Drawn Disk Harrow with 24 Blades on 9 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 3 In. x 8 In. Cylinder
with 150 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (9.5L-15 6 Ply)
Working Width: 9 Ft. 6 In.
Blade Spacing: 9 In.
Tractor HP: 40-65 HP
Shipping Weight: 2028 lbs.
Approximate Operating Weight: 1953 lbs.
Number of Blades: 24
Blade Size: 20 In. or 22 In. Diameter
Blade Thickness: 3.5 mm (0.138 In.) with
20 In. or 4 mm (0.157 In.) with 22 In.
Frame Tubing: 3 In. Square

Gang Tubing: 3 In. Square
Bearing Hanger: 2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed or Lubricated
Ball Bearing in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles:
9, 13, 14, 16, 19, 20, 23, 24, 26 Degrees
Rear Gang Angles:
8, 11, 13, 15, 16, 19, 21, 23, 27 Degrees
Approximate Assembly Time: 4 Hours

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3355XF		DH1509 - 9 Ft. 6 In. Drawn Disk Harrow with 24 Blades on 9 In. Spacing	9,238.00
--------	--	--	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	116.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	58.00
1040		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	555.00
1060		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	670.00
1080		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	613.00

DISK GANG BEARING STYLE

2000		Relube Bearings for 1.125 In. Gang Beam Shaft	98.00
2010		Sealed Bearings for 1.125 In. Gang Beam Shaft	In Base Price

SCRAPERS

9000		Scraper Kit <i>9 In. Spacing with 24 Blades.</i>	941.00
9030		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 Series Models)	136.00

FRONTIER PRODUCTS

Tillage

DH1509 - 9 Ft. 6 In. Drawn Disk Harrow with 24 Blades on 9 In. Spacing

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
SCRAPERS ...Continued...			
MIDDLE BREAKER			
9020		Middle Breaker Kit <i>For all DH1508 and DH1509 Models.</i>	316.00
MISCELLANEOUS			
9010		Furrow Filler Kit for all Units with 20 In. Blades	286.00
9015		Furrow Filler Kit for all Units with 22 In. Blades	292.00
905H		DH1509 Rolling Basket with mounts and weight kit	2,696.00
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous			
5TL14177		Center Sweep Kit (all DH1508 and DH1509 Models)	327.80
5TLRB1509		DH1509 Rolling Basket	2,797.31
5TL15745		French Kit - Includes Operator's Manual and Safety Decals (DH15 Series)	61.60
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80
5TL9245		Scraper Kit with 9 In. Spacing with 24 Blades for base machine DH1509 (No Furrow Fillers)	976.80

FRONTIER PRODUCTS**Tillage**

DH1509 - 9 Ft. 6 In. Drawn Disk Harrow with 26 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear

Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 3 In. x 8 In. Cylinder
with 150 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (9.5L-15 6 Ply)
Working Width: 9 Ft. 6 In.
Blade Spacing: 9 In. Front and 7.5 In. Rear
Tractor HP: 40-65 HP
Shipping Weight: 1993 lbs.
Approximate Operating Weight: 2068 lbs.
Number of Blades: 26
Blade Size: 20 In. or 22 In. Diameter
Blade Thickness: 3.5 mm (0.138 In.) with
20 In. or 4 mm (0.157 In.) with 22 In.
Frame Tubing: 3 In. Square

Gang Tubing: 3 In. Square
Bearing Hanger: 2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed or Lubricated
Ball Bearing in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles:
9, 13, 14, 16, 19, 20, 23, 24, 26 Degrees
Rear Gang Angles:
8, 11, 13, 15, 16, 19, 21, 23, 27 Degrees
Approximate Assembly Time: 4 Hours

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3356XF		DH1509 - 9 Ft. 6 In. Drawn Disk Harrow with 26 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear	9,663.00
--------	--	---	----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	126.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	68.00
1040		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	602.00
1060		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	727.00
1080		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	669.00

DISK GANG BEARING STYLE

2000		Relube Bearings for 1.125 In. Gang Beam Shaft	98.00
2010		Sealed Bearings for 1.125 In. Gang Beam Shaft	In Base Price

SCRAPERS

9000		Scraper Kit	979.00
------	--	-------------	--------

Tillage

DH1509 - 9 Ft. 6 In. Drawn Disk Harrow with 26 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
SCRAPERS ...Continued...			
<i>9 In. Front Spacing and 7.5 In. Rear Spacing with 26 Blades (DH1509).</i>			
9030		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 Series Models)	136.00
MIDDLE BREAKER			
9020		Middle Breaker Kit <i>For all DH1508 and DH1509 Models.</i>	316.00
MISCELLANEOUS			
9010		Furrow Filler Kit for all Units with 20 In. Blades	286.00
9015		Furrow Filler Kit for all Units with 22 In. Blades	292.00
905H		DH1509 Rolling Basket with mounts and weight kit	2,696.00
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous			
5TL14177		Center Sweep Kit (all DH1508 and DH1509 Models)	327.80
5TLRB1509		DH1509 Rolling Basket	2,797.31
5TL15745		French Kit - Includes Operator's Manual and Safety Decals (DH15 Series)	61.60
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80
5TLSK97265		Scraper Kit with 9 In. Front Spacing and 7.5 In. Rear Spacing with 22 Blades for base machine DH1509 (No Furrow Fillers)	1,016.40

FRONTIER PRODUCTS**Tillage****DH1510 - 10 Ft. 6 In. Drawn Disk Harrow with 32 Blades on 7.5 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 3 In. x 8 In. Cylinder
with 150 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (9.5L-15 6 Ply)
Working Width: 10 Ft. 6 In.
Blade Spacing: 7.5 In.
Tractor HP: 45-75 HP
Shipping Weight: 2555 lbs.
Approximate Operating Weight: 2480 lbs.
Number of Blades: 32
Blade Size: 20 In. or 22 In. Diameter
Blade Thickness: 3.5 mm (0.138 In.) with
20 In. or 4 mm (0.157 In.) with 22 In.
Frame Tubing:
4 In. x 3 In. and 5 In. x 3 In.

Gang Tubing: 4 In. x 3 In.
Bearing Hanger: 2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed or Lubricated
Ball Bearing in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles: 9, 11, 12, 14, 15,
16, 19, 22, 25 Degrees
Rear Gang Angles: 5, 8, 9, 11, 12, 14,
15, 17, 20, 23 Degrees
Approximate Assembly Time: 4 Hours

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3357XF		DH1510 - 10 Ft. 6 In. Drawn Disk Harrow with 32 Blades on 7.5 In. Spacing	11,257.00
--------	--	---	-----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	155.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	77.00
1040		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	741.00
1060		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	894.00
1080		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	818.00

DISK GANG BEARING STYLE

2000		Relube Bearings for 1.125 In. Gang Beam Shaft	144.00
2010		Sealed Bearings for 1.125 In. Gang Beam Shaft	In Base Price

SCRAPERS

9000		Scraper Kit	1,189.00
------	--	-------------	----------

Tillage

DH1510 - 10 Ft. 6 In. Drawn Disk Harrow with 32 Blades on 7.5 In. Spacing

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
SCRAPERS ...Continued...			
<i>7.5 In. Spacing with 32 Blades.</i>			
9030		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 Series Models)	136.00
MIDDLE BREAKER			
9020		Middle Breaker Kit <i>For all DH1510 and DH1512 Models.</i>	329.00
MISCELLANEOUS			
9010		Furrow Filler Kit for all Units with 20 In. Blades	286.00
9015		Furrow Filler Kit for all Units with 22 In. Blades	292.00
905I		DH1510 Rolling Basket with mounts and weight kit	2,996.00
WHEELS AND TIRES			
9040		Dual Wheel Kit with Tires (all DH1510 and DH1512 Models)	1,049.00
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous			
5TL11476		Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1510		DH1510 Rolling Basket	3,108.60
5TL13160		Dual Wheel Kit with Tires (all DH1510 and DH1512 Models)	1,089.00
5TL15745		French Kit - Includes Operator's Manual and Safety Decals (DH15 Series)	61.60
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80
5TLSK7325		Scraper Kit with 7.5 In. Spacing with 32 Blades for base machine DH1510 (No Furrow Fillers)	1,234.20

FRONTIER PRODUCTS**Tillage****DH1510 - 10 Ft. 6 In. Drawn Disk Harrow with 28 Blades on 9 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 3 In. x 8 In. Cylinder
with 150 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (9.5L-15 6 Ply)
Working Width: 10 Ft. 6 In.
Blade Spacing: 9 In.
Tractor HP: 45-75 HP
Shipping Weight: 2473 lbs.
Approximate Operating Weight: 2398 lbs.
Number of Blades: 28
Blade Size: 20 In. or 22 In. Diameter
Blade Thickness: 3.5 mm (0.138 In.) with
20 In. or 4 mm (0.157 In.) with 22 In.
Frame Tubing:
4 In. x 3 In. and 5 In. x 3 In.

Gang Tubing: 4 In. x 3 In.
Bearing Hanger: 2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed or Lubricated
Ball Bearing in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles: 9, 11, 12, 14, 15,
16, 19, 22, 25 Degrees
Rear Gang Angles: 5, 8, 9, 11, 12, 14,
15, 17, 20, 23 Degrees
Approximate Assembly Time: 4 Hours

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3358XF		DH1510 - 10 Ft. 6 In. Drawn Disk Harrow with 28 Blades on 9 In. Spacing	10,699.00
--------	--	---	-----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	136.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	68.00
1040		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	649.00
1060		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	783.00
1080		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	714.00

DISK GANG BEARING STYLE

2000		Relube Bearings for 1.125 In. Gang Beam Shaft	144.00
2010		Sealed Bearings for 1.125 In. Gang Beam Shaft	In Base Price

SCRAPERS

9000		Scraper Kit	1,118.00
------	--	-------------	----------

Tillage

DH1510 - 10 Ft. 6 In. Drawn Disk Harrow with 28 Blades on 9 In. Spacing

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
SCRAPERS ...Continued...			
<i>9 In. Spacing with 28 Blades.</i>			
9030		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 Series Models)	136.00
MIDDLE BREAKER			
9020		Middle Breaker Kit <i>For all DH1510 and DH1512 Models.</i>	329.00
MISCELLANEOUS			
9010		Furrow Filler Kit for all Units with 20 In. Blades	286.00
9015		Furrow Filler Kit for all Units with 22 In. Blades	292.00
905I		DH1510 Rolling Basket with mounts and weight kit	2,996.00
WHEELS AND TIRES			
9040		Dual Wheel Kit with Tires (all DH1510 and DH1512 Models)	1,049.00
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous			
5TL11476		Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1510		DH1510 Rolling Basket	3,108.60
5TL13160		Dual Wheel Kit with Tires (all DH1510 and DH1512 Models)	1,089.00
5TL15745		French Kit - Includes Operator's Manual and Safety Decals (DH15 Series)	61.60
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80
5TL9285		Scraper Kit with 9 In. Spacing with 28 Blades for base machine DH1510 (No Furrow Fillers)	1,160.51

Tillage

**DH1510 - 10 Ft. 6 In. Drawn Disk Harrow with 30 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear
 Equipment for Base Machine**

Hitch: Drawn Level Lift
 with Clevis and Jack
 Hitch Safety Chain: Standard
 Hydraulics: 3 In. x 8 In. Cylinder
 with 150 In. of Hydraulic Hose
 Depth Control:
 Center Mounted Pin Adjustment
 Tires: Standard (9.5L-15 6 Ply)
 Working Width: 10 Ft. 6 In.
 Blade Spacing: 9 In. Front and 7.5 In. Rear
 Tractor HP: 45-75 HP
 Shipping Weight: 2515 lbs.
 Approximate Operating Weight: 2440 lbs.
 Number of Blades: 30
 Blade Size: 20 In. or 22 In. Diameter
 Blade Thickness: 3.5 mm (0.138 In.) with
 20 In. or 4 mm (0.157 In.) with 22 In.
 Frame Tubing:
 4 In. x 3 In. and 5 In. x 3 In.

Gang Tubing: 4 In. x 3 In.
 Bearing Hanger: 2 In. x 4 In. Steel Tubing
 with 3/4 In. U-bolt
 Bearing Type:
 Self Aligning Sealed or Lubricated
 Ball Bearing in a Trunion Mount
 Gang Axle: 1-1/8 In. Square
 Front Gang Angles: 9, 11, 12, 14, 15,
 16, 19, 22, 25 Degrees
 Rear Gang Angles: 5, 8, 9, 11, 12, 14,
 15, 17, 20, 23 Degrees
 Approximate Assembly Time: 4 Hours

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3359XF		DH1510 - 10 Ft. 6 In. Drawn Disk Harrow with 30 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear	11,058.00
--------	--	--	-----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	144.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	77.00
1040		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	693.00
1060		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	837.00
1080		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	770.00

DISK GANG BEARING STYLE

2000		Relube Bearings for 1.125 In. Gang Beam Shaft	144.00
2010		Sealed Bearings for 1.125 In. Gang Beam Shaft	In Base Price

SCRAPERS

Tillage

**DH1510 - 10 Ft. 6 In. Drawn Disk Harrow with 30 Blades on 9 In. Spacing on Front and
7.5 In. Spacing on Rear**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		SCRAPERS ...Continued...	
9000		Scraper Kit <i>9 In. Front Spacing and 7.5 In. Rear Spacing with 30 Blades.</i>	1,156.00
9030		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 Series Models)	136.00
		MIDDLE BREAKER	
9020		Middle Breaker Kit <i>For all DH1510 and DH1512 Models.</i>	329.00
		MISCELLANEOUS	
9010		Furrow Filler Kit for all Units with 20 In. Blades	286.00
9015		Furrow Filler Kit for all Units with 22 In. Blades	292.00
9051		DH1510 Rolling Basket with mounts and weight kit	2,996.00
		WHEELS AND TIRES	
9040		Dual Wheel Kit with Tires (all DH1510 and DH1512 Models)	1,049.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
5TL11476		Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1510		DH1510 Rolling Basket	3,108.60
5TL13160		Dual Wheel Kit with Tires (all DH1510 and DH1512 Models)	1,089.00
5TL15745		French Kit - Includes Operator's Manual and Safety Decals (DH15 Series)	61.60
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80
5TLSK97305		Scraper Kit with 9 In. Front Spacing and 7.5 In. Rear Spacing with 30 Blades for base machine DH1510 (No Furrow Fillers)	1,200.11

FRONTIER PRODUCTS**Tillage****DH1512 - 12 Ft. Drawn Disk Harrow with 36 Blades on 7.5 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with clevis and jack
Hitch Safety Chain: Standard
Hydraulics: 3 In. x 8 In. Cylinder
with 150 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (9.5L-15 6 Ply)
Working Width: 12 Ft.
Blade Spacing: 7.5 In.
Tractor HP: 55-85 HP
Shipping Weight: 3113 lbs.
Approximate Operating Weight: 3038 lbs.
Number of Blades: 36
Blade Size: 20 In. or 22 In. Diameter
Blade Thickness: 3.5 mm (0.138 In.) with
20 In. or 4 mm (0.157 In.) with 22 In.
Frame Tubing:
4 In. x 3 In. and 5 In. x 3 In.

Gang Tubing: 4 In. x 3 In.
Bearing Hanger: 2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed or Lubricated
Ball Bearing in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles: 9, 11, 12, 14, 15,
16, 19, 22, 25 Degrees
Rear Gang Angles: 5, 8, 9, 11, 12, 14,
15, 17, 20, 23 Degrees
Approximate Assembly Time: 4 Hours

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

335AXF		DH1512 - 12 Ft. Drawn Disk Harrow with 36 Blades on 7.5 In. Spacing	12,786.00
--------	--	---	-----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	175.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	86.00
1040		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	833.00
1060		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	1,007.00
1080		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	920.00

DISK GANG BEARING STYLE

2000		Relube Bearings for 1.125 In. Gang Beam Shaft	144.00
2010		Sealed Bearings for 1.125 In. Gang Beam Shaft	In Base Price

SCRAPERS

9000		Scraper Kit <i>7.5 In. Spacing with 36 Blades.</i>	1,497.00
------	--	---	----------

Tillage

DH1512 - 12 Ft. Drawn Disk Harrow with 36 Blades on 7.5 In. Spacing

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		SCRAPERS ...Continued...	
9030		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 Series Models)	136.00
		MIDDLE BREAKER	
9020		Middle Breaker Kit <i>For all DH1510 and DH1512 Models.</i>	329.00
		MISCELLANEOUS	
9010		Furrow Filler Kit for all Units with 20 In. Blades	286.00
9015		Furrow Filler Kit for all Units with 22 In. Blades	292.00
905K		DH1512 Rolling Basket with mounts and weight kit	3,593.00
		WHEELS AND TIRES	
9040		Dual Wheel Kit with Tires (all DH1510 and DH1512 Models)	1,049.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
5TL11476		Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1512		DH1512 Rolling Basket	3,729.00
5TL13160		Dual Wheel Kit with Tires (all DH1510 and DH1512 Models)	1,089.00
5TL15745		French Kit - Includes Operator's Manual and Safety Decals (DH15 Series)	61.60
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80
5TL7365		Scraper Kit with 7.5 In. Spacing with 36 Blades for base machine DH1512 (No Furrow Fillers)	1,553.20

FRONTIER PRODUCTS**Tillage****DH1512 - 12 Ft. Drawn Disk Harrow with 32 Blades on 9 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 3 In. x 8 In. Cylinder
with 150 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (9.5L-15 6 Ply)
Working Width: 12 Ft.
Blade Spacing: 9 In.
Tractor HP: 55-85 HP
Shipping Weight: 3023 lbs.
Approximate Operating Weight: 2948 lbs.
Number of Blades: 32
Blade Size: 20 In. or 22 In. Diameter
Blade Thickness: 3.5 mm (0.138 In.) with
20 In. or 4 mm (0.157 In.) with 22 In.
Frame Tubing:
4 In. x 3 In. and 5 In. x 3 In.

Gang Tubing: 4 In. x 3 In.
Bearing Hanger: 2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type: Self Aligning Sealed
or Lubricated
Ball Bearing in a Trunion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles: 9, 11, 12, 14, 15,
16, 19, 22, 25 Degrees
Rear Gang Angles: 5, 8, 9, 11, 12, 14,
15, 17, 20, 23 Degrees
Approximate Assembly Time: 4 Hours

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

335BXF		DH1512 - 12 Ft. Drawn Disk Harrow with 32 Blades on 9 In. Spacing	11,944.00
--------	--	---	-----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	155.00
1020		Notched Front and Smooth Rear Disk Blades <i>20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)</i>	77.00
1040		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	741.00
1060		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	894.00
1080		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter for 1.125 In. Shaft (4mm Thick)</i>	818.00

DISK GANG BEARING STYLE

2000		Relube Bearings for 1.125 In. Gang Beam Shaft	144.00
2010		Sealed Bearings for 1.125 In. Gang Beam Shaft	In Base Price

SCRAPERS

9000		Scraper Kit <i>9 In. Spacing with 32 Blades.</i>	1,405.00
------	--	---	----------

Tillage

DH1512 - 12 Ft. Drawn Disk Harrow with 32 Blades on 9 In. Spacing

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		SCRAPERS ...Continued...	
9030		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 Series Models)	136.00
		MIDDLE BREAKER	
9020		Middle Breaker Kit <i>For all DH1510 and DH1512 Models.</i>	329.00
		MISCELLANEOUS	
9010		Furrow Filler Kit for all Units with 20 In. Blades	286.00
9015		Furrow Filler Kit for all Units with 22 In. Blades	292.00
905K		DH1512 Rolling Basket with mounts and weight kit	3,593.00
		WHEELS AND TIRES	
9040		Dual Wheel Kit with Tires (all DH1510 and DH1512 Models)	1,049.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
5TL11476		Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1512		DH1512 Rolling Basket	3,729.00
5TL13160		Dual Wheel Kit with Tires (all DH1510 and DH1512 Models)	1,089.00
5TL15745		French Kit - Includes Operator's Manual and Safety Decals (DH15 Series)	61.60
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80
5TL5K9325		Scraper Kit with 9 In. Spacing with 32 Blades for base machine DH1512 (No Furrow Fillers)	1,457.51

Tillage

DH1512 - 12 Ft. Drawn Disk Harrow with 34 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear
 Equipment for Base Machine

Hitch: Drawn Level Lift
 with Clevis and Jack
 Hitch Safety Chain: Standard
 Hydraulics: 3 In. x 8 In. Cylinder
 with 150 In. of Hydraulic Hose
 Depth Control:
 Center Mounted Pin Adjustment
 Tires: Standard (9.5L-15 6 Ply)
 Working Width: 12 Ft.
 Blade Spacing:
 9 In. Front and 7.5 In. Rear
 Tractor HP: 55-85 HP
 Shipping Weight: 3073 lbs.
 Approximate Operating Weight: 2998 lbs.
 Number of Blades: 34
 Blade Size: 20 In. or 22 In. Diameter
 Blade Thickness: 3.5 mm (0.138 In.) with
 20 In. or 4 mm (0.157 In.) with 22 In.
 Frame Tubing:

4 In. x 3 In. and 5 In. x 3 In.
 Gang Tubing: 4 In. x 3 In.
 Bearing Hanger: 2 In. x 4 In. Steel Tubing
 with 3/4 In. U-bolt
 Bearing Type: Self Aligning Sealed
 or Lubricated Ball Bearing in a
 Trunion Mount
 Gang Axle: 1-1/8 In. Square
 Front Gang Angles: 9, 11, 12, 14, 15,
 16, 19, 22, 25 Degrees
 Rear Gang Angles: 5, 8, 9, 11, 12, 14,
 15, 17, 20, 23 Degrees
 Approximate Assembly Time: 4 Hours

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

335CXF		DH1512 - 12 Ft. Drawn Disk Harrow with 34 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear	12,237.00
--------	--	--	-----------

DISK BLADES

1000		Notched Front and Notched Rear Disk Blades 20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)	In Base Price
1010		Smooth Front and Smooth Rear Disk Blades 20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)	164.00
1020		Notched Front and Smooth Rear Disk Blades 20 In. Diameter for 1.125 In. Shaft (3.5mm Thick)	86.00
1040		Notched Front and Notched Rear Disk Blades 22 In. Diameter for 1.125 In. Shaft (4mm Thick)	788.00
1060		Smooth Front and Smooth Rear Disk Blades 22 In. Diameter for 1.125 In. Shaft (4mm Thick)	950.00
1080		Notched Front and Smooth Rear Disk Blades 22 In. Diameter for 1.125 In. Shaft (4mm Thick)	873.00

DISK GANG BEARING STYLE

2000		Relube Bearings for 1.125 In. Gang Beam Shaft	144.00
2010		Sealed Bearings for 1.125 In. Gang Beam Shaft	In Base Price

SCRAPERS

Tillage

DH1512 - 12 Ft. Drawn Disk Harrow with 34 Blades on 9 In. Spacing on Front and 7.5 In. Spacing on Rear

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
		SCRAPERS ...Continued...	
9000		Scraper Kit <i>9 In. Front Spacing and 7.5 In. Rear Spacing with 34 Blades.</i>	1,459.00
9030		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 Series Models)	136.00
		MIDDLE BREAKER	
9020		Middle Breaker Kit <i>For all DH1510 and DH1512 Models.</i>	329.00
		MISCELLANEOUS	
9010		Furrow Filler Kit for all Units with 20 In. Blades	286.00
9015		Furrow Filler Kit for all Units with 22 In. Blades	292.00
905K		DH1512 Rolling Basket with mounts and weight kit	3,593.00
		WHEELS AND TIRES	
9040		Dual Wheel Kit with Tires (all DH1510 and DH1512 Models)	1,049.00
		ATTACHMENTS FOR FIELD CONVERSION	
		Miscellaneous	
5TL11476		Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1512		DH1512 Rolling Basket	3,729.00
5TL13160		Dual Wheel Kit with Tires (all DH1510 and DH1512 Models)	1,089.00
5TL15745		French Kit - Includes Operator's Manual and Safety Decals (DH15 Series)	61.60
5TLT70316		Furrow Filler Kit for all Units with 20 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	297.00
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80
5TL5K97345		Scraper Kit with 9 In. Front Spacing and 7.5 In. Rear Spacing with 34 Blades for base machine DH1512 (No Furrow Fillers)	1,513.60

FRONTIER PRODUCTS**Tillage****DH1610 - 10 Ft 6 In. Drawn Disk Harrow with 28 Blades on 9 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 4 In. x 8 In. Cylinder
with 160 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (Dual 9.5L-15 6 Ply)
Working Width: 10 Ft. 6 In.
Blade Spacing: 9 In.
Tractor HP: 60-80 HP
Shipping Weight: 4228 lbs.
Approximate Operating Weight: 3953 lbs.
Number of Blades: 28
Blade Size: 22 In. Diameter
Blade Thickness: 4.5 mm (0.177 In.)
Frame Tubing: Combination 4 In. X 6 In. and 4 In. X
4 In Tubular Frame
Gang Tubing: 4 In. Square Tubing
Bearing Hanger:

2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed
Ball Bearing in a Trunnion Mount
Gang Axle: 1-1/2 In. Square
Front Gang Angles:
5, 8, 9, 11, 13, 14, 16, 18, 19, 21, 22, 25
Degrees
Rear Gang Angles:
5, 8, 10, 12, 13, 14, 16, 17, 19, 20, 21, 24
Degrees
Approximate Assembly Time: 4 hrs

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3511XF		DH1610 - 10 Ft 6 In. Drawn Disk Harrow with 28 Blades on 9 In. Spacing	14,674.00
--------	--	--	-----------

DISK BLADES

1000		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .177 In. Thick (4.5mm Thick) for 1.5 In. Shaft</i>	In Base Price
1010		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .177 In. Thick (4.5mm Thick) for 1.5 In. Shaft</i>	No Added Cost
1020		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .177 In. Thick (4.5mm Thick) for 1.5 In. Shaft</i>	No Added Cost
1030		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .236 In. Thick (6mm Thick) for 1.5 In. Shaft</i>	566.00
1040		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .236 In. Thick (6mm Thick) for 1.5 In. Shaft</i>	594.00
1050		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .236 In. Thick (6mm Thick) for 1.5 In. Shaft</i>	617.00

DISK GANG BEARING STYLE

2000		Sealed Bearings for 1.50 In. Gang Beam Shaft	In Base Price
2010		Relube Bearings for 1.50 In. Gang Beam Shaft	104.00

DISK GANG BEARING HANGER

3000		Rigid Tubular Bearing Hanger	In Base Price
------	--	------------------------------	---------------

FRONTIER PRODUCTS

Tillage

DH1610 - 10 Ft 6 In. Drawn Disk Harrow with 28 Blades on 9 In. Spacing

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
3010		DISK GANG BEARING HANGER ...Continued... C-Spring Bearing Hanger	1,235.00
SCRAPERS			
9000		Adjustable Scraper Kit for base machine (No Furrow Fillers)	1,147.00
9030		Scraper for Furrow Fillers <i>Furrow Filler Scraper Kit contains two scrapers for 18 In. furrow filler blades. Machines must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	130.00
MIDDLE BREAKER			
9020		Middle Breaker Kit <i>All DH16 Series Models.</i>	316.00
MISCELLANEOUS			
9010		Furrow Filler Kit for 22 In. Diameter Disk Gangs <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	280.00
905J		DH1610 Rolling Basket with mounts and weight kit	2,855.00
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous			
5TLSK9286		Adjustable Scraper Kit for base machine DH1610 (No Furrow Fillers)	1,190.20
5TL11476		Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1610		DH1610 Rolling Basket	2,962.31
5TL15802		French Kit - Includes Operator's Manual and Safety Decals (DH16 Series)	59.40
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80

Tillage**DH1612 - 12 Ft Drawn Disk Harrow with 32 Blades on 9 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 4 In. x 8 In. Cylinder
with 160 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (Dual 9.5L-15 6 Ply)
Working Width: 12 Ft. 0 In.
Blade Spacing: 9 In.
Tractor HP: 75-115 HP
Shipping Weight: 4573 lbs.
Approximate Operating Weight: 4298 lbs.
Number of Blades: 32
Blade Size: 22 In. Diameter
Blade Thickness: 4.5 mm (0.177 In.)
Frame Tubing: Combination 4 In. X 6 In. and 4 In. X
4 In Tubular Frame
Gang Tubing: 4 In. Square Tubing
Bearing Hanger:

2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed
Ball Bearing in a Trunnion Mount
Gang Axle: 1-1/2 In. Square
Front Gang Angles:
5, 8, 9, 11, 13, 14, 16, 18, 19, 21, 22, 25
Degrees
Rear Gang Angles:
5, 8, 10, 12, 13, 14, 16, 17, 19, 20, 21, 24
Degrees
Approximate Assembly Time: 4 hrs

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3512XF		DH1612 - 12 Ft Drawn Disk Harrow with 32 Blades on 9 In. Spacing	16,457.00
--------	--	--	-----------

DISK BLADES

1000		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .177 In. Thick (4.5mm Thick) for 1.5 In. Shaft</i>	In Base Price
1010		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .177 In. Thick (4.5mm Thick) for 1.5 In. Shaft</i>	No Added Cost
1020		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .177 In. Thick (4.5mm Thick) for 1.5 In. Shaft</i>	No Added Cost
1030		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .236 In. Thick (6mm Thick) for 1.5 In. Shaft</i>	648.00
1040		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .236 In. Thick (6mm Thick) for 1.5 In. Shaft</i>	679.00
1050		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .236 In. Thick (6mm Thick) for 1.5 In. Shaft</i>	706.00

DISK GANG BEARING STYLE

2000		Sealed Bearings for 1.50 In. Gang Beam Shaft	In Base Price
2010		Relube Bearings for 1.50 In. Gang Beam Shaft	104.00

DISK GANG BEARING HANGER

3000		Rigid Tubular Bearing Hanger	In Base Price
------	--	------------------------------	---------------

FRONTIER PRODUCTS

Tillage

DH1612 - 12 Ft Drawn Disk Harrow with 32 Blades on 9 In. Spacing

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
3010		DISK GANG BEARING HANGER ...Continued... C-Spring Bearing Hanger	1,235.00
SCRAPERS			
9000		Adjustable Scraper Kit for base machine (No Furrow Fillers)	1,249.00
9030		Scraper for Furrow Fillers <i>Furrow Filler Scraper Kit contains two scrapers for 18 In. furrow filler blades. Machines must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	130.00
MIDDLE BREAKER			
9020		Middle Breaker Kit <i>All DH16 Series Models.</i>	316.00
MISCELLANEOUS			
9010		Furrow Filler Kit for 22 In. Diameter Disk Gangs <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	280.00
905L		DH1612 Rolling Basket with mounts and weight kit	3,425.00
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous			
5TLSK9326		Adjustable Scraper Kit for base machine DH1612 (No Furrow Fillers)	1,295.80
5TL11476		Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1612		DH1612 Rolling Basket	3,554.11
5TL15802		French Kit - Includes Operator's Manual and Safety Decals (DH16 Series)	59.40
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80

Tillage**DH1613 - 13 Ft 6 In. Drawn Disk Harrow with 36 Blades on 9 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 4 In. x 8 In. Cylinder
with 160 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (Dual 9.5L-15 6 Ply)
Working Width: 13 Ft. 6 In.
Blade Spacing: 9 In.
Tractor HP: 75-125 HP
Shipping Weight: 4889 lbs.
Approximate Operating Weight: 4614 lbs.
Number of Blades: 36
Blade Size: 22 In. Diameter
Blade Thickness: 4.5 mm (0.177 In.)
Frame Tubing: Combination 4 In. X 6 In. and 4 In. X
4 In Tubular Frame
Gang Tubing: 4 In. Square Tubing

Bearing Hanger:
2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed
Ball Bearing in a Trunnion Mount
Gang Axle: 1-1/2 In. Square
Front Gang Angles:
6, 8, 10, 12, 14, 16, 17, 19, 22 Degrees
Rear Gang Angles:
8, 11, 12, 14, 16, 17, 19, 20, 22, 24 Degrees
Approximate Assembly Time: 4 hrs

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3513XF		DH1613 - 13 Ft 6 In. Drawn Disk Harrow with 36 Blades on 9 In. Spacing	17,589.00
--------	--	--	-----------

DISK BLADES

1000		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .177 In. Thick (4.5mm Thick) for 1.5 In. Shaft</i>	In Base Price
1010		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .177 In. Thick (4.5mm Thick) for 1.5 In. Shaft</i>	No Added Cost
1020		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .177 In. Thick (4.5mm Thick) for 1.5 In. Shaft</i>	No Added Cost
1030		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .236 In. Thick (6mm Thick) for 1.5 In. Shaft</i>	727.00
1040		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .236 In. Thick (6mm Thick) for 1.5 In. Shaft</i>	764.00
1050		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .236 In. Thick (6mm Thick) for 1.5 In. Shaft</i>	794.00

DISK GANG BEARING STYLE

2000		Sealed Bearings for 1.50 In. Gang Beam Shaft	In Base Price
2010		Relube Bearings for 1.50 In. Gang Beam Shaft	147.00

DISK GANG BEARING HANGER

3000		Rigid Tubular Bearing Hanger	In Base Price
3010		C-Spring Bearing Hanger	1,684.00

FRONTIER PRODUCTS

Tillage

DH1613 - 13 Ft 6 In. Drawn Disk Harrow with 36 Blades on 9 In. Spacing

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DISK GANG BEARING HANGER ...Continued...			
SCRAPERS			
9000		Adjustable Scraper Kit for base machine (No Furrow Fillers)	1,353.00
9030		Scraper for Furrow Fillers <i>Furrow Filler Scraper Kit contains two scrapers for 18 In. furrow filler blades. Machines must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	130.00
MIDDLE BREAKER			
9020		Middle Breaker Kit <i>All DH16 Series Models.</i>	316.00
MISCELLANEOUS			
9010		Furrow Filler Kit for 22 In. Diameter Disk Gangs <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	280.00
905M		DH1613 Rolling Basket with mounts and weight kit	3,711.00
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous			
5TLSK9366		Adjustable Scraper Kit for base machine DH1613 (No Furrow Fillers)	1,403.60
5TL11476		Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1613		DH1613 Rolling Basket	3,851.11
5TL15802		French Kit - Includes Operator's Manual and Safety Decals (DH16 Series)	59.40
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80

Tillage**DH1615 - 15 Ft Drawn Disk Harrow with 40 Blades on 9 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 4 In. x 8 In. Cylinder
with 160 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (Dual 9.5L-15 6 Ply)
Working Width: 15 Ft. 0 In.
Blade Spacing: 9 In.
Tractor HP: 80-140 HP
Shipping Weight: 5222 lbs.
Approximate Operating Weight: 4947 lbs.
Number of Blades: 40
Blade Size: 22 In. Diameter
Blade Thickness: 4.5 mm (0.177 In.)
Frame Tubing: Combination 4 In. X 6 In. and 4 In. X
4 In Tubular Frame
Gang Tubing: 4 In. Square Tubing

Bearing Hanger:
2 In. x 4 In. Steel Tubing
with 3/4 In. U-bolt
Bearing Type:
Self Aligning Sealed
Ball Bearing in a Trunnion Mount
Gang Axle: 1-1/2 In. Square
Front Gang Angles:
6, 8, 10, 12, 14, 16, 17, 19, 22 Degrees
Rear Gang Angles:
8, 11, 12, 14, 16, 17, 19, 20, 22, 24 Degrees
Approximate Assembly Time: 4 hrs

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3514XF		DH1615 - 15 Ft Drawn Disk Harrow with 40 Blades on 9 In. Spacing	18,337.00
--------	--	--	-----------

DISK BLADES

1000		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .177 In. Thick (4.5mm Thick) for 1.5 In. Shaft</i>	In Base Price
1010		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .177 In. Thick (4.5mm Thick) for 1.5 In. Shaft</i>	No Added Cost
1020		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .177 In. Thick (4.5mm Thick) for 1.5 In. Shaft</i>	No Added Cost
1030		Smooth Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .236 In. Thick (6mm Thick) for 1.5 In. Shaft</i>	848.00
1040		Notched Front and Smooth Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .236 In. Thick (6mm Thick) for 1.5 In. Shaft</i>	848.00
1050		Notched Front and Notched Rear Disk Blades <i>22 In. Diameter, 9 In. spacing, .236 In. Thick (6mm Thick) for 1.5 In. Shaft</i>	883.00

DISK GANG BEARING STYLE

2000		Sealed Bearings for 1.50 In. Gang Beam Shaft	In Base Price
2010		Relube Bearings for 1.50 In. Gang Beam Shaft	147.00

DISK GANG BEARING HANGER

3000		Rigid Tubular Bearing Hanger	In Base Price
3010		C-Spring Bearing Hanger	1,684.00

FRONTIER PRODUCTS

Tillage

DH1615 - 15 Ft Drawn Disk Harrow with 40 Blades on 9 In. Spacing

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DISK GANG BEARING HANGER ...Continued...			
SCRAPERS			
9000		Adjustable Scraper Kit for base machine (No Furrow Fillers)	1,446.00
9030		Scraper for Furrow Fillers <i>Furrow Filler Scraper Kit contains two scrapers for 18 In. furrow filler blades. Machines must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	130.00
MIDDLE BREAKER			
9020		Middle Breaker Kit <i>All DH16 Series Models.</i>	316.00
MISCELLANEOUS			
9010		Furrow Filler Kit for 22 In. Diameter Disk Gangs <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	280.00
905N		DH1615 Rolling Basket with mounts and weight kit	4,282.00
ATTACHMENTS FOR FIELD CONVERSION			
Miscellaneous			
5TLSK9406		Adjustable Scraper Kit for base machine DH1615 (No Furrow Fillers)	1,500.40
5TL11476		Center Sweep Kit (all DH13 and DH16 Series, DH1510 and DH1512 Models)	341.00
5TLRB1615		DH1615 Rolling Basket	4,444.00
5TL15802		French Kit - Includes Operator's Manual and Safety Decals (DH16 Series)	59.40
5TLT70318		Furrow Filler Kit for all Units with 22 In. Blades <i>Kit contains two 18 In. furrow filler blades, mounting spools and hardware.</i>	302.51
5TL15169		Scraper Blade Assembly for Furrow Filler Kits - 2 Per Kit (all DH15 and DH16 Series Models) <i>Furrow Filler Scraper Kit contains two scrapers for the 18 In. furrow filler blades. Machine must be equipped with furrow fillers and base machine scrapers to be compatible with this option.</i>	140.80

FRONTIER PRODUCTS**Tillage****TM5118 - 18 Ft. Tandem Wing Fold Ag Disk Harrow with 46 Blades - U.S.**
Equipment for Base Machine

Class: General Purpose
 Frame: 6 in. x 4 in. x 3/8 in. High Strength Steel
 Tube
 Disk Blades:
 26 in. x 5/16 in. Notched (Smooth optional)
 28 in. x 5/16 in. Notched (Smooth optional)
 Weight Per Disk Blade: 369 lbs/blade
 Gang Axles:
 1-5/8 or 2-1/8 in. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 46
 Approximate Net Weight: 15,500 lbs
 Approximate Width of Cut: 18 ft.
 Transport Width: 13 ft. 8 in.
 Disk Spacing: 10-1/2 in.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 160-180 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (8) 11L x 15 in. 8 ply Implement
 Front and Rear Gang Angles: Fixed
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: (3) 5 in. Hydraulic Lift Cylinders
 Hitch Type: Spade
 Set Up Time: 4-6 Hrs For Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3561XF		TM5118 - 18 Ft. Tandem Wing Fold Ag Disk Harrow with 46 Blades - U.S.	77,243.00
--------	--	---	-----------

DISK BLADES

1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	1,920.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	1,920.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	1,920.00
1080		26 In. Wavy Front and Rear Disk Blades	703.00
1090		28 In. Wavy Front and Rear Disk Blades	2,824.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost

SCRAPERS

5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	2,141.00

Tillage

TM5118 - 18 Ft. Tandem Wing Fold Ag Disk Harrow with 46 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Disk Gang Axle Components	In Base Price
2010		2-1/8 In. Disk Gang Axle Components	8,703.00
REAR HITCH			
9000		Rear Hitch (TM51 Series)	952.00
ATTACHMENTS FOR FIELD CONVERSION			
		Miscellaneous	
	5KB3063278A	Rear Hitch (TM 51 Series)	987.80

Tillage

TM5120 - 19 Ft. 6 In. Tandem Wing Fold Ag Disk Harrow with 50 Blades - U.S.
 Equipment for Base Machine

Class: General Purpose
 Frame: 6 in. x 4 in. x 3/8 in. High Strength Steel
 Tube
 Disk Blades:
 26 in. x 5/16 in. Notched (Smooth optional)
 28 in. x 5/16 in. Notched (Smooth optional)
 Weight Per Disk Blade: 345 lbs/blade
 Gang Axles:
 1-5/8 or 2-1/8 in. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 50
 Approximate Net Weight: 15,850 lbs
 Approximate Width of Cut: 19 ft. 6 in.
 Transport Width: 13 ft. 8 in.
 Disk Spacing: 10-1/2 in.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 170-200 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (8) 11L x 15 in. 8 ply Implement
 Front and Rear Gang Angles: Fixed
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: (3) 5 in. Hydraulic Lift Cylinders
 Hitch Type: Spade
 Set Up Time: 4-6 Hrs For Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3562XF		TM5120 - 19 Ft. 6 In. Tandem Wing Fold Ag Disk Harrow with 50 Blades - U.S.	77,383.00
--------	--	---	-----------

DISK BLADES

1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	2,104.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	2,104.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	2,104.00
1080		26 In. Wavy Front and Rear Disk Blades	763.00
1090		28 In. Wavy Front and Rear Disk Blades	3,086.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost

SCRAPERS

5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	2,329.00

Tillage

TM5120 - 19 Ft. 6 In. Tandem Wing Fold Ag Disk Harrow with 50 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Disk Gang Axle Components	In Base Price
2010		2-1/8 In. Disk Gang Axle Components	9,196.00
REAR HITCH			
9000		Rear Hitch (TM51 Series)	952.00
ATTACHMENTS FOR FIELD CONVERSION			
		Miscellaneous	
	5KB3063278A	Rear Hitch (TM 51 Series)	987.80

FRONTIER PRODUCTS**Tillage****TM5121 - 21 Ft. Tandem Wing Fold Ag Disk Harrow with 54 Blades - U.S.**
Equipment for Base Machine

Class: General Purpose
 Frame: 6 in. x 4 in. x 3/8 in. High Strength Steel
 Tube
 Disk Blades:
 26 in. x 5/16 in. Notched (Smooth optional)
 28 in. x 5/16 in. Notched (Smooth optional)
 Weight Per Disk Blade: 322 lbs/blade
 Gang Axles:
 1-5/8 or 2-1/8 in. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 54
 Approximate Net Weight: 16,100 lbs
 Approximate Width of Cut: 21 ft.
 Transport Width: 13 ft. 8 in.
 Disk Spacing: 10-1/2 in.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 190-210 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (8) 11L x 15 in. 8 ply Implement
 Front and Rear Gang Angles: Fixed
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: (3) 5 in. Hydraulic Lift Cylinders
 Hitch Type: Spade
 Set Up Time: 4-6 Hrs For Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3563XF		TM5121 - 21 Ft. Tandem Wing Fold Ag Disk Harrow with 54 Blades - U.S.	77,710.00
--------	--	---	-----------

DISK BLADES

1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	2,306.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	2,306.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	2,306.00
1080		26 In. Wavy Front and Rear Disk Blades	825.00
1090		28 In. Wavy Front and Rear Disk Blades	3,364.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost

SCRAPERS

5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	2,514.00

Tillage

TM5121 - 21 Ft. Tandem Wing Fold Ag Disk Harrow with 54 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Disk Gang Axle Components	In Base Price
2010		2-1/8 In. Disk Gang Axle Components	9,703.00
REAR HITCH			
9000		Rear Hitch (TM51 Series)	952.00
ATTACHMENTS FOR FIELD CONVERSION			
		Miscellaneous	
	5KB3063278A	Rear Hitch (TM 51 Series)	987.80

FRONTIER PRODUCTS**Tillage****TM5124 - 23 Ft. 6 In. Tandem Wing Fold Ag Disk Harrow with 58 Blades - U.S.**
Equipment for Base Machine

Class: General Purpose
 Frame: 6 in. x 4 in. x 3/8 in. High Strength Steel
 Tube
 Disk Blades:
 26 in. x 5/16 in. Notched (Smooth optional)
 28 in. x 5/16 in. Notched (Smooth optional)
 Weight Per Disk Blade: 320 lbs/blade
 Gang Axles:
 1-5/8 or 2-1/8 in. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 58
 Approximate Net Weight: 17,290 lbs
 Approximate Width of Cut: 23 ft. 6 in.
 Transport Width: 13 ft. 8 in.
 Disk Spacing: 10-1/2 in.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 220+ HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (8) 11L x 15 in. 8 ply Implement
 Front and Rear Gang Angles: Fixed
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: (3) 5 in. Hydraulic Lift Cylinders
 Hitch Type: Spade
 Set Up Time: 4-6 Hrs For Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3564XF		TM5124 - 23 Ft. 6 In. Tandem Wing Fold Ag Disk Harrow with 58 Blades - U.S.	81,736.00
--------	--	---	-----------

DISK BLADES

1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	2,497.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	2,497.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	2,497.00
1080		26 In. Wavy Front and Rear Disk Blades	885.00
1090		28 In. Wavy Front and Rear Disk Blades	3,635.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost

SCRAPERS

5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	2,701.00

Tillage

TM5124 - 23 Ft. 6 In. Tandem Wing Fold Ag Disk Harrow with 58 Blades - U.S.

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Disk Gang Axle Components	In Base Price
2010		2-1/8 In. Disk Gang Axle Components	11,450.00
REAR HITCH			
9000		Rear Hitch (TM51 Series)	952.00
ATTACHMENTS FOR FIELD CONVERSION			
		Miscellaneous	
	5KB3063278A	Rear Hitch (TM 51 Series)	987.80

FRONTIER PRODUCTS**Tillage****TM5129 - 29 Ft. Tandem Wing Fold Ag Disk Harrow with 74 Blades - U.S.**
Equipment for Base Machine

Class: General Purpose
 Frame: 6 in. x 4 in. x 3/8 in. High Strength Steel
 Tube
 Disk Blades:
 26 in. x 5/16 in. Notched (Smooth optional)
 28 in. x 5/16 in. Notched (Smooth optional)
 Weight Per Disk Blade: 314 lbs/blade
 Gang Axles:
 1-5/8 or 2-1/8 in. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 74
 Approximate Net Weight: 22,000 lbs
 Approximate Width of Cut: 29 ft.
 Transport Width: 19 ft.
 Disk Spacing: 10-1/2 in.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 260+ HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (8) 11L x 15 in. 8 ply Implement
 Front and Rear Gang Angles: Fixed
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: (3) 5 in. Hydraulic Lift Cylinders
 Hitch Type: Spade
 Set Up Time: 6-8 Hrs For Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
BASE MACHINE			
3565XF		TM5129 - 29 Ft. Tandem Wing Fold Ag Disk Harrow with 74 Blades - U.S.	109,404.00
DISK BLADES			
1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	3,441.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	3,441.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	3,441.00
1080		26 In. Wavy Front and Rear Disk Blades	1,130.00
1090		28 In. Wavy Front and Rear Disk Blades	4,894.00
DISK BLADE CONCAVITY			
3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost
SCRAPERS			
5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	3,446.00

Tillage

TM5129 - 29 Ft. Tandem Wing Fold Ag Disk Harrow with 74 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Disk Gang Axle Components	In Base Price
2010		2-1/8 In. Disk Gang Axle Components	11,373.00
REAR HITCH			
9000		Rear Hitch (TM51 Series)	952.00
ATTACHMENTS FOR FIELD CONVERSION			
		Miscellaneous	
	5KB3063278A	Rear Hitch (TM 51 Series)	987.80

FRONTIER PRODUCTS**Tillage****TM5132 - 32 Ft. Tandem Wing Fold Ag Disk Harrow with 82 Blades - U.S.**
Equipment for Base Machine

Class: General Purpose
 Frame: 6 in. x 4 in. x 3/8 in. High Strength Steel
 Tube
 Disk Blades:
 26 in. x 5/16 in. Notched (Smooth optional)
 28 in. x 5/16 in. Notched (Smooth optional)
 Weight Per Disk Blade: 309 lbs/blade
 Gang Axles:
 1-5/8 or 2-1/8 in. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 82
 Approximate Net Weight: 24,100 lbs
 Approximate Width of Cut: 32 ft.
 Transport Width: 19 ft.
 Disk Spacing: 10-1/2 in.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 280+ HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (8) 11L x 15 in. 8 ply Implement
 Front and Rear Gang Angles: Fixed
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: (3) 5 in. Hydraulic Lift Cylinders
 Hitch Type: Spade
 Set Up Time: -6-8 Hrs For Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
BASE MACHINE			
3566XF		TM5132 - 32 Ft. Tandem Wing Fold Ag Disk Harrow with 82 Blades - U.S.	111,542.00
DISK BLADES			
1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	3,833.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	3,833.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	3,833.00
1080		26 In. Wavy Front and Rear Disk Blades	1,253.00
1090		28 In. Wavy Front and Rear Disk Blades	5,444.00
DISK BLADE CONCAVITY			
3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost
SCRAPERS			
5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	3,819.00

Tillage

TM5132 - 32 Ft. Tandem Wing Fold Ag Disk Harrow with 82 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Disk Gang Axle Components	In Base Price
2010		2-1/8 In. Disk Gang Axle Components	11,963.00
REAR HITCH			
9000		Rear Hitch (TM51 Series)	952.00
ATTACHMENTS FOR FIELD CONVERSION			
		Miscellaneous	
	5KB3063278A	Rear Hitch (TM 51 Series)	987.80

Tillage

DH3263 - 5 Ft. 3 In. 3-Point Offset Disk Harrow with 14 Blades on 9 In. Spacing
 Equipment for Base Machine

3-Point Hitch: Category I and II
 iMatch and Quick Coupler Compatible
 (Quick-Attach System)
 Working Width: 63 In.
 Tractor HP Recommendation:
 35 to 75 HP
 Blade Spacing: 9 In.
 Blade Size: 20 In.
 Number of Blades: 14
 Blade Type: Notched
 Sealed Ball Bearings
 Axles: 1-1/8 In. Hi-Strength Steel

Duty: Standard Duty
 Assembly/Set-Up Time: 15 Minutes
 Approximate Operating Weight: 996 lbs.
 Shipping Weight: 1146 lbs.
 1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3471XF		DH3263 - 5 Ft. 3 In. 3-Point Offset Disk Harrow with 14 Blades on 9 In. Spacing	3,933.00
--------	--	---	----------

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous 5TSL0914 Scraper Kit (DH3263)	667.71
--	--	---	--------

Tillage

DH3263 - 5 Ft. 3 In. 3-Point Offset Disk Harrow with 14 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage

DH3272 - 6 Ft. 3-Point Offset Disk Harrow with 16 Blades on 9 In. Spacing
 Equipment for Base Machine

3-Point Hitch: Category I and II
 iMatch and Quick Coupler Compatible
 (Quick-Attach System)
 Working Width: 72 In.
 Tractor HP Recommendation:
 35 to 75 HP
 Blade Spacing: 9 In.
 Blade Size: 20 In.
 Number of Blades: 16
 Blade Type: Notched
 Sealed Ball Bearings
 Axles: 1-1/8 In. Hi-Strength Steel

Duty: Standard Duty
 Assembly/Set-Up Time: 15 Minutes
 Approximate Operating Weight: 1101 lbs.
 Shipping Weight: 1251 lbs.
 1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3472XF		DH3272 - 6 Ft. 3-Point Offset Disk Harrow with 16 Blades on 9 In. Spacing	4,509.00
--------	--	---	----------

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous 5TSL0916 Scraper Kit (DH3272)	739.20
--	--	---	--------

Tillage

DH3272 - 6 Ft. 3-Point Offset Disk Harrow with 16 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage

DH3280 - 6 Ft. 8 In. 3-Point Offset Disk Harrow with 18 Blades on 9 In. Spacing
 Equipment for Base Machine

3-Point Hitch: Category I and II
 iMatch and Quick Coupler Compatible
 (Quick-Attach System)
 Working Width: 80 In.
 Tractor HP Recommendation:
 35 to 75 HP
 Blade Spacing: 9 In.
 Blade Size: 20 In.
 Number of Blades: 18
 Blade Type: Notched
 Sealed Ball Bearings
 Axles: 1-1/8 In. Hi-Strength Steel

Duty: Standard Duty
 Assembly/Set-Up Time: 15 Minutes
 Approximate Operating Weight: 1185 lbs.
 Shipping Weight: 1335 lbs.
 1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3473XF		DH3280 - 6 Ft. 8 In. 3-Point Offset Disk Harrow with 18 Blades on 9 In. Spacing	4,635.00
--------	--	---	----------

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous 5TLSLO918 Scraper Kit (DH3280)	877.80
--	--	--	--------

Tillage

DH3280 - 6 Ft. 8 In. 3-Point Offset Disk Harrow with 18 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH3290 - 7 Ft. 6 In. 3-Point Offset Disk Harrow with 20 Blades on 9 In. Spacing**
Equipment for Base Machine

3-Point Hitch: Category I and II
 iMatch and Quick Coupler Compatible
 (Quick-Attach System)
 Working Width: 90 In.
 Tractor HP Recommendation:
 35 to 75 HP
 Blade Spacing: 9 In.
 Blade Size: 20 In.
 Number of Blades: 20
 Blade Type: Notched
 Sealed Ball Bearings
 Axles: 1-1/8 In. Hi-Strength Steel

Duty: Standard Duty
 Assembly/Set-Up Time: 15 Minutes
 Approximate Operating Weight: 1250 lbs.
 Shipping Weight: 1400 lbs.
 1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3474XF		DH3290 - 7 Ft. 6 In. 3-Point Offset Disk Harrow with 20 Blades on 9 In. Spacing	4,728.00
--------	--	---	----------

ATTACHMENTS FOR FIELD CONVERSION

	5TSL0920	Miscellaneous Scraper Kit (DH3290)	894.24
--	----------	--	--------

Tillage

DH3290 - 7 Ft. 6 In. 3-Point Offset Disk Harrow with 20 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage

DH3299 - 8 Ft. 4 In. 3-Point Offset Disk Harrow with 22 Blades on 9 In. Spacing
 Equipment for Base Machine

3-Point Hitch: Category I and II
 iMatch and Quick Coupler Compatible
 (Quick-Attach System)
 Working Width: 100 In.
 Tractor HP Recommendation:
 35 to 75 HP
 Blade Spacing: 9 In.
 Blade Size: 20 In.
 Number of Blades: 22
 Blade Type: Notched
 Sealed Ball Bearings
 Axles: 1-1/8 In. Hi-Strength Steel

Duty: Standard Duty
 Assembly/Set-Up Time: 15 Minutes
 Approximate Operating Weight: 1318 lbs.
 Shipping Weight: 1468 lbs.
 1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3475XF		DH3299 - 8 Ft. 4 In. 3-Point Offset Disk Harrow with 22 Blades on 9 In. Spacing	5,294.00
--------	--	---	----------

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous 5TLSLO922 Scraper Kit (DH3299)	933.91
--	--	--	--------

Tillage

DH3299 - 8 Ft. 4 In. 3-Point Offset Disk Harrow with 22 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage

DH3409 - 9 Ft. 3-Point Offset Disk Harrow with 24 Blades on 9 In. Spacing
 Equipment for Base Machine

3-Point Hitch: Category II and III
 Category II and III Quick Coupler
 Compatible (Quick-Attach System)
 Working Width: 108 In.
 Tractor HP Recommendation:
 60 to 130 HP
 Blade Spacing: 9 In.
 Blade Size: 24 In.
 Number of Blades: 24
 Blade Type: Notched
 Sealed Ball Bearings
 Axles: 1-1/2 In. Cold Drawn Steel

Duty: Medium Duty
 Assembly/Set-Up Time: 45 Minutes
 Approximate Operating Weight: 2362 lbs.
 Shipping Weight: 2512 lbs.
 1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3481XF		DH3409 - 9 Ft. 3-Point Offset Disk Harrow with 24 Blades on 9 In. Spacing	10,293.00
--------	--	---	-----------

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous 5TL924SK Scraper Kit (DH3409)	1,155.00
--	--	---	----------

Tillage

DH3409 - 9 Ft. 3-Point Offset Disk Harrow with 24 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage

DH3474 - 6 Ft. 2 In. 3-Point Offset Disk Harrow with 16 Blades on 9 In. Spacing
 Equipment for Base Machine

3-Point Hitch: Category II and III
 Category II and III Quick Coupler
 Compatible (Quick-Attach System)
 Working Width: 74 In.
 Tractor HP Recommendation:
 60 to 130 HP
 Blade Spacing: 9 In.
 Blade Size: 24 In.
 Number of Blades: 16
 Blade Type: Notched
 Sealed Ball Bearings
 Axles: 1-1/2 In. Cold Drawn Steel

Duty: Medium Duty
 Assembly/Set-Up Time: 45 Minutes
 Approximate Operating Weight: 1725 lbs.
 Shipping Weight: 1875 lbs.
 1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3482XF		DH3474 - 6 Ft. 2 In. 3-Point Offset Disk Harrow with 16 Blades on 9 In. Spacing	7,327.00
--------	--	---	----------

ATTACHMENTS FOR FIELD CONVERSION

5TL916SK	Miscellaneous	Scraper Kit (DH3474)	836.00
----------	----------------------	----------------------	--------

Tillage

DH3474 - 6 Ft. 2 In. 3-Point Offset Disk Harrow with 16 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage

DH3480 - 6 Ft. 8 In. 3-Point Offset Disk Harrow with 18 Blades on 9 In. Spacing
 Equipment for Base Machine

3-Point Hitch: Category II and III
 Category II and III Quick Coupler
 Compatible (Quick-Attach System)
 Working Width: 80 In.
 Tractor HP Recommendation:
 60 to 130 HP
 Blade Spacing: 9 In.
 Blade Size: 24 In.
 Number of Blades: 18
 Blade Type: Notched
 Sealed Ball Bearings
 Axles: 1-1/2 In. Cold Drawn Steel

Duty: Medium Duty
 Assembly/Set-Up Time: 45 Minutes
 Approximate Operating Weight: 1830 lbs.
 Shipping Weight: 1980 lbs.
 1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3483XF		DH3480 - 6 Ft. 8 In. 3-Point Offset Disk Harrow with 18 Blades on 9 In. Spacing	7,594.00
--------	--	---	----------

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous 5TL918SK Scraper Kit (DH3480)	881.11
--	--	---	--------

Tillage

DH3480 - 6 Ft. 8 In. 3-Point Offset Disk Harrow with 18 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage

DH3490 - 7 Ft. 6 In. 3-Point Offset Disk Harrow with 20 Blades on 9 In. Spacing
 Equipment for Base Machine

3-Point Hitch: Category II and III
 Category II and III Quick Coupler
 Compatible (Quick-Attach System)
 Working Width: 90 In.
 Tractor HP Recommendation:
 60 to 130 HP
 Blade Spacing: 9 In.
 Blade Size: 24 In.
 Number of Blades: 20
 Blade Type: Notched
 Sealed Ball Bearings
 Axles: 1-1/2 In. Cold Drawn Steel

Duty: Medium Duty
 Assembly/Set-Up Time: 45 Minutes
 Approximate Operating Weight: 2018 lbs.
 Shipping Weight: 2168 lbs.
 1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3484XF		DH3490 - 7 Ft. 6 In. 3-Point Offset Disk Harrow with 20 Blades on 9 In. Spacing	8,355.00
--------	--	---	----------

ATTACHMENTS FOR FIELD CONVERSION

		Miscellaneous 5TL920SK Scraper Kit (DH3490)	973.51
--	--	---	--------

Tillage

DH3490 - 7 Ft. 6 In. 3-Point Offset Disk Harrow with 20 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage

DH3499 - 8 Ft. 4 In. 3-Point Offset Disk Harrow with 22 Blades on 9 In. Spacing
 Equipment for Base Machine

3-Point Hitch: Category II and III
 Category II and III Quick Coupler
 Compatible (Quick-Attach System)
 Working Width: 99 In.
 Tractor HP Recommendation:
 60 to 130 HP
 Blade Spacing: 9 In.
 Blade Size: 24 In.
 Number of Blades: 22
 Blade Type: Notched
 Sealed Ball Bearings
 Axles: 1-1/2 In. Cold Drawn Steel

Duty: Medium Duty
 Assembly/Set-Up Time: 45 Minutes
 Approximate Operating Weight: 2150 lbs.
 Shipping Weight: 2300 lbs.
 1 Year Warranty

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3485XF		DH3499 - 8 Ft. 4 In. 3-Point Offset Disk Harrow with 22 Blades on 9 In. Spacing	8,870.00
--------	--	---	----------

ATTACHMENTS FOR FIELD CONVERSION

5TL922SK	Miscellaneous	Scraper Kit (DH3499)	1,039.51
----------	----------------------	----------------------	----------

Tillage

DH3499 - 8 Ft. 4 In. 3-Point Offset Disk Harrow with 22 Blades on 9 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH5108 - 8 Ft. Rigid Single Offset Ag Disk with 19 Blades - U.S.**
Equipment for Base Machine

Class: General Purpose
 Frame: 5 In. x 5 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 26 In. x 5/16 In. Notched (Smooth Optional)
 28 In. x 5/16 In. Notched (Smooth Optional)
 Weight Per Disk Blade: 323 lbs/blade
 Gang Axles:
 1-5/8 In. or 2-1/8 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 19
 Approximate Net Weight: 5,500 Lbs.
 Approximate Width of Cut: 8 Ft.
 Transport Width: 9 Ft.
 Disk Spacing: 10-1/2 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 80-90 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 6-Bolt Hubs
 Tires: (4) 9.5L x 15 In. 8 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 8 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
BASE MACHINE			
3571XF		DH5108 - 8 Ft. Rigid Single Offset Ag Disk with 19 Blades - U.S.	29,206.00
DISK BLADES			
1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	810.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	810.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	810.00
1080		26 In. Wavy Front and Wavy Rear Blades	288.00
1090		28 In. Wavy Front and Wavy Rear Blades	1,181.00
DISK BLADE CONCAVITY			
3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost
SCRAPERS			
5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	922.00

Tillage

DH5108 - 8 Ft. Rigid Single Offset Ag Disk with 19 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	2,518.00

Attachment Information is not available in MOCI for the base code 3571XF

FRONTIER PRODUCTS**Tillage****DH5110 - 10 Ft. Rigid Single Offset Ag Disk with 23 Blades - U.S.**
Equipment for Base Machine

Class: General Purpose
 Frame: 5 In. x 5 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 26 In. x 5/16 In. Notched (Smooth Optional)
 28 In. x 5/16 In. Notched (Smooth Optional)
 Weight Per Disk Blade: 282 lbs/blade
 Gang Axles:
 1-5/8 In. or 2-1/8 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 23
 Approximate Net Weight: 5,925 Lbs.
 Approximate Width of Cut: 10 Ft.
 Transport Width: 11 Ft.
 Disk Spacing: 10-1/2 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 90-110 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 6-Bolt Hubs
 Tires: (4) 9.5L x 15 In. 8 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 8 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3572XF		DH5110 - 10 Ft. Rigid Single Offset Ag Disk with 23 Blades - U.S.	30,634.00
--------	--	---	-----------

DISK BLADES

1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	1,001.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	1,001.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	1,001.00
1080		26 In. Wavy Front and Wavy Rear Blades	348.00
1090		28 In. Wavy Front and Wavy Rear Blades	1,449.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost

SCRAPERS

5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	1,117.00

Tillage

DH5110 - 10 Ft. Rigid Single Offset Ag Disk with 23 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	3,514.00

Attachment Information is not available in MOCI for the base code 3572XF

FRONTIER PRODUCTS**Tillage****DH5112 - 12 Ft. Rigid Single Offset Ag Disk with 27 Blades - U.S.**
Equipment for Base Machine

Class: General Purpose
 Frame: 5 In. x 5 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 26 In. x 5/16 In. Notched (Smooth Optional)
 28 In. x 5/16 In. Notched (Smooth Optional)
 Weight Per Disk Blade: 255 lbs/blade
 Gang Axles:
 1-5/8 In. or 2-1/8 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 27
 Approximate Net Weight: 6,365 Lbs.
 Approximate Width of Cut: 12 Ft.
 Transport Width: 13 Ft.
 Disk Spacing: 10-1/2 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 110-135 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 6-Bolt Hubs
 Tires: (4) 9.5L x 15 In. 8 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 8 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3573XF		DH5112 - 12 Ft. Rigid Single Offset Ag Disk with 27 Blades - U.S.	30,755.00
--------	--	---	-----------

DISK BLADES

1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	1,191.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	1,191.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	1,191.00
1080		26 In. Wavy Front and Wavy Rear Blades	409.00
1090		28 In. Wavy Front and Wavy Rear Blades	1,718.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost

SCRAPERS

5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	1,312.00

Tillage

DH5112 - 12 Ft. Rigid Single Offset Ag Disk with 27 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	3,876.00

Attachment Information is not available in MOCI for the base code 3573XF

Tillage

DH5114 - 14 Ft. Rigid Single Offset Ag Disk with 33 Blades - U.S.
 Equipment for Base Machine

Class: General Purpose
 Frame: 5 In. x 5 In. x 3/8 In. High Strength Steel Tube
 Disk Blades:
 26 In. x 5/16 In. Notched (Smooth Optional)
 28 In. x 5/16 In. Notched (Smooth Optional)
 Weight Per Disk Blade: 248 lbs/blade
 Gang Axles:
 1-5/8 In. or 2-1/8 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 33
 Approximate Net Weight: 7,700 Lbs.
 Approximate Width of Cut: 14 Ft.
 Transport Width: 15 Ft.
 Disk Spacing: 10-1/2 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 140-160 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 6-Bolt Hubs
 Tires: (4) 9.5L x 15 In. 8 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 8 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3574XF		DH5114 - 14 Ft. Rigid Single Offset Ag Disk with 33 Blades - U.S.	33,656.00
--------	--	---	-----------

DISK BLADES

1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	1,478.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	1,478.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	1,478.00
1080		26 In. Wavy Front and Wavy Rear Blades	501.00
1090		28 In. Wavy Front and Wavy Rear Blades	2,121.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost

SCRAPERS

5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	1,602.00

Tillage

DH5114 - 14 Ft. Rigid Single Offset Ag Disk with 33 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	4,403.00

Attachment Information is not available in MOCI for the base code 3574XF

FRONTIER PRODUCTS**Tillage****DH5116 - 16 Ft. Rigid Single Offset Ag Disk with 37 Blades - U.S.**
Equipment for Base Machine

Class: General Purpose
 Frame: 5 In. x 5 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 26 In. x 5/16 In. Notched (Smooth Optional)
 28 In. x 5/16 In. Notched (Smooth Optional)
 Weight Per Disk Blade: 242 lbs/blade
 Gang Axles:
 1-5/8 In. or 2-1/8 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 37
 Approximate Net Weight: 8,500 Lbs.
 Approximate Width of Cut: 16 Ft.
 Transport Width: 17 Ft.
 Disk Spacing: 10-1/2 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 160-180 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 6-Bolt Hubs
 Tires: (4) 9.5L x 15 In. 8 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 8 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3575XF		DH5116 - 16 Ft. Rigid Single Offset Ag Disk with 37 Blades - U.S.	35,609.00
--------	--	---	-----------

DISK BLADES

1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	1,667.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	1,667.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	1,667.00
1080		26 In. Wavy Front and Wavy Rear Blades	562.00
1090		28 In. Wavy Front and Wavy Rear Blades	2,390.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost

SCRAPERS

5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	1,796.00

Tillage

DH5116 - 16 Ft. Rigid Single Offset Ag Disk with 37 Blades - U.S.
 Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	8,102.00

Attachment Information is not available in MOCI for the base code 3575XF

FRONTIER PRODUCTS**Tillage****DH5210 - 10 Ft. Rigid Single Offset Ag Disk with 23 Blades - U.S.**
Equipment for Base Machine

Class: Medium Duty
 Frame: 6 In. x 6 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 26 In. x 5/16 In. Notched (Smooth Optional)
 28 In. x 5/16 In. Notched (Smooth Optional)
 Weight Per Disk Blade: 341 lbs/blade
 Gang Axles:
 1-5/8 In. or 2-1/8 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 23
 Approximate Net Weight: 7,170 Lbs.
 Approximate Width of Cut: 10 Ft.
 Transport Width: 11 Ft.
 Disk Spacing: 10-1/2 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 100-120 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 11L x 15 In. 8 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 16 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
BASE MACHINE			
3581XF		DH5210 - 10 Ft. Rigid Single Offset Ag Disk with 23 Blades - U.S.	35,767.00
DISK BLADES			
1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	1,001.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	1,001.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	1,001.00
1080		26 In. Wavy Front and Wavy Rear Blades	348.00
1090		28 In. Wavy Front and Wavy Rear Blades	1,449.00
DISK BLADE CONCAVITY			
3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost
SCRAPERS			
5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	1,117.00

Tillage

DH5210 - 10 Ft. Rigid Single Offset Ag Disk with 23 Blades - U.S.
 Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	2,624.00

Attachment Information is not available in MOCI for the base code 3581XF

FRONTIER PRODUCTS**Tillage****DH5212 - 12 Ft. Rigid Single Offset Ag Disk with 27 Blades - U.S.**
Equipment for Base Machine

Class: Medium Duty
 Frame: 6 In. x 6 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 26 In. x 5/16 In. Notched (Smooth Optional)
 28 In. x 5/16 In. Notched (Smooth Optional)
 Weight Per Disk Blade: 308 lbs/blade
 Gang Axles:
 1-5/8 In. or 2-1/8 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 27
 Approximate Net Weight: 7,690 Lbs.
 Approximate Width of Cut: 12 Ft.
 Transport Width: 13 Ft.
 Disk Spacing: 10-1/2 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 100-135 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 11L x 15 In. 8 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 16 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
BASE MACHINE			
3582XF		DH5212 - 12 Ft. Rigid Single Offset Ag Disk with 27 Blades - U.S.	37,968.00
DISK BLADES			
1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	1,191.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	1,191.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	1,191.00
1080		26 In. Wavy Front and Wavy Rear Blades	409.00
1090		28 In. Wavy Front and Wavy Rear Blades	1,718.00
DISK BLADE CONCAVITY			
3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost
SCRAPERS			
5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	1,312.00

Tillage

DH5212 - 12 Ft. Rigid Single Offset Ag Disk with 27 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	3,827.00

Attachment Information is not available in MOCI for the base code 3582XF

FRONTIER PRODUCTS**Tillage****DH5214 - 14 Ft. Rigid Single Offset Ag Disk with 33 Blades - U.S.**
Equipment for Base Machine

Class: Medium Duty
 Frame: 6 In. x 6 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 26 In. x 5/16 In. Notched (Smooth Optional)
 28 In. x 5/16 In. Notched (Smooth Optional)
 Weight Per Disk Blade: 274 lbs/blade
 Gang Axles:
 1-5/8 In. or 2-1/8 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 33
 Approximate Net Weight: 8,500 Lbs.
 Approximate Width of Cut: 14 Ft.
 Transport Width: 15 Ft.
 Disk Spacing: 10-1/2 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 125-155 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 11L x 15 In. 8 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 16 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
BASE MACHINE			
3583XF		DH5214 - 14 Ft. Rigid Single Offset Ag Disk with 33 Blades - U.S.	40,641.00
DISK BLADES			
1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	1,478.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	1,478.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	1,478.00
1080		26 In. Wavy Front and Wavy Rear Blades	501.00
1090		28 In. Wavy Front and Wavy Rear Blades	2,121.00
DISK BLADE CONCAVITY			
3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost
SCRAPERS			
5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	1,602.00

Tillage

DH5214 - 14 Ft. Rigid Single Offset Ag Disk with 33 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	4,446.00

Attachment Information is not available in MOCI for the base code 3583XF

FRONTIER PRODUCTS**Tillage****DH5216 - 16 Ft. Rigid Single Offset Ag Disk with 37 Blades - U.S.**
Equipment for Base Machine

Class: Medium Duty
 Frame: 6 In. x 6 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 26 In. x 5/16 In. Notched (Smooth Optional)
 28 In. x 5/16 In. Notched (Smooth Optional)
 Weight Per Disk Blade: 288 lbs/blade
 Gang Axles:
 1-5/8 In. or 2-1/8 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 37
 Approximate Net Weight: 10,100 Lbs.
 Approximate Width of Cut: 16 Ft.
 Transport Width: 17 Ft.
 Disk Spacing: 10-1/2 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 150-165 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 12.5L x 15 In. 10 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 16 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
BASE MACHINE			
3584XF		DH5216 - 16 Ft. Rigid Single Offset Ag Disk with 37 Blades - U.S.	44,036.00
DISK BLADES			
1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	1,667.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	1,667.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	1,667.00
1080		26 In. Wavy Front and Wavy Rear Blades	562.00
1090		28 In. Wavy Front and Wavy Rear Blades	2,390.00
DISK BLADE CONCAVITY			
3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost
SCRAPERS			
5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	1,796.00

Tillage

DH5216 - 16 Ft. Rigid Single Offset Ag Disk with 37 Blades - U.S.
 Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	5,875.00

Attachment Information is not available in MOCI for the base code 3584XF

FRONTIER PRODUCTS**Tillage****DH5217 - 17 Ft. Rigid Single Offset Ag Disk with 41 Blades - U.S.**
Equipment for Base Machine

Class: Medium Duty
 Frame: 6 In. x 6 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 26 In. x 5/16 In. Notched (Smooth Optional)
 28 In. x 5/16 In. Notched (Smooth Optional)
 Weight Per Disk Blade: 270 lbs/blade
 Gang Axles:
 1-5/8 In. or 2-1/8 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 41
 Approximate Net Weight: 10,550 Lbs.
 Approximate Width of Cut: 17 Ft.
 Transport Width: 18 Ft.
 Disk Spacing: 10-1/2 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 160-180 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 12.5L x 15 In. 10 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 16 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
BASE MACHINE			
3585XF		DH5217 - 17 Ft. Rigid Single Offset Ag Disk with 41 Blades - U.S.	45,338.00
DISK BLADES			
1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	1,858.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	1,858.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	1,858.00
1080		26 In. Wavy Front and Wavy Rear Blades	622.00
1090		28 In. Wavy Front and Wavy Rear Blades	2,658.00
DISK BLADE CONCAVITY			
3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost
SCRAPERS			
5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	1,993.00

Tillage

DH5217 - 17 Ft. Rigid Single Offset Ag Disk with 41 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	5,693.00

Attachment Information is not available in MOCI for the base code 3585XF

FRONTIER PRODUCTS**Tillage****DH5219 - 19 Ft. Rigid Single Offset Ag Disk with 45 Blades - U.S.**
Equipment for Base Machine

Class: Medium Duty
 Frame: 6 In. x 6 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 26 In. x 5/16 In. Notched (Smooth Optional)
 28 In. x 5/16 In. Notched (Smooth Optional)
 Weight Per Disk Blade: 257 lbs/blade
 Gang Axles:
 1-5/8 In. or 2-1/8 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 45
 Approximate Net Weight: 11,050 Lbs.
 Approximate Width of Cut: 19 Ft.
 Transport Width: 20 Ft.
 Disk Spacing: 10-1/2 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 170-200 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 12.5L x 15 In. 10 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 16 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3586XF		DH5219 - 19 Ft. Rigid Single Offset Ag Disk with 45 Blades - U.S.	46,325.00
--------	--	---	-----------

DISK BLADES

1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	2,049.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	2,049.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	2,049.00
1080		26 In. Wavy Front and Wavy Rear Blades	684.00
1090		28 In. Wavy Front and Wavy Rear Blades	2,928.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost

SCRAPERS

5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	2,187.00

Tillage

DH5219 - 19 Ft. Rigid Single Offset Ag Disk with 45 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	6,656.00

Attachment Information is not available in MOCI for the base code 3586XF

FRONTIER PRODUCTS**Tillage****DH5221 - 21 Ft. Rigid Single Offset Ag Disk with 49 Blades - U.S.**
Equipment for Base Machine

Class: Medium Duty
 Frame: 6 In. x 6 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 26 In. x 5/16 In. Notched (Smooth Optional)
 28 In. x 5/16 In. Notched (Smooth Optional)
 Weight Per Disk Blade: 249 lbs/blade
 Gang Axles:
 1-5/8 In. or 2-1/8 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 49
 Approximate Net Weight: 11,700 Lbs.
 Approximate Width of Cut: 21 Ft.
 Transport Width: 22 Ft.
 Disk Spacing: 10-1/2 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 180-210 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 12.5L x 15 In. 10 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 16 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
BASE MACHINE			
3587XF		DH5221 - 21 Ft. Rigid Single Offset Ag Disk with 49 Blades - U.S.	47,385.00
DISK BLADES			
1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	2,240.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	2,240.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	2,240.00
1080		26 In. Wavy Front and Wavy Rear Blades	744.00
1090		28 In. Wavy Front and Wavy Rear Blades	3,196.00
DISK BLADE CONCAVITY			
3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost
SCRAPERS			
5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	2,380.00

Tillage

DH5221 - 21 Ft. Rigid Single Offset Ag Disk with 49 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	7,014.00

Attachment Information is not available in MOCI for the base code 3587XF

FRONTIER PRODUCTS**Tillage****DH5221F - 21 Ft. Folding Single Offset Ag Disk with 49 Blades - U.S.**
Equipment for Base Machine

Class: Medium Duty
 Frame: 6 in. x 6 in. x 3/8 in. High Strength Steel Tube
 Disk Blades:
 26 in. x 5/16 in. Notched (Smooth optional)
 28 in. x 5/16 in. Notched (Smooth optional)
 Weight Per Disk Blade: 300 lbs/blade
 Gang Axles:
 1-5/8 or 2-1/8 in. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 49
 Approximate Net Weight: 14,100 lbs
 Approximate Width of Cut: 20 ft. 9 in.
 Transport Width: 12.5 ft.
 Disk Spacing: 10-1/2 in.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 180-220 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 12.5L x 15 in. 10 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 in. x 16 in. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 4-6 Hrs For Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3588XF		DH5221F - 21 Ft. Folding Single Offset Ag Disk with 49 Blades - U.S.	77,741.00
--------	--	--	-----------

DISK BLADES

1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	2,240.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	2,240.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	2,240.00
1080		26 In. Wavy Front and Wavy Rear Blades	744.00
1090		28 In. Wavy Front and Wavy Rear Blades	3,196.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost

SCRAPERS

5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	2,380.00

Tillage

DH5221F - 21 Ft. Folding Single Offset Ag Disk with 49 Blades - U.S.
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	9,136.00

Attachment Information is not available in MOCI for the base code 3588XF

FRONTIER PRODUCTS**Tillage****DH5222F - 22 Ft. Folding Single Offset Ag Disk with 53 Blades - U.S.**
Equipment for Base Machine

Class: Medium Duty
 Frame: 6 in. x 6 in. x 3/8 in. High Strength Steel
 Tube
 Disk Blades:
 26 in. x 5/16 in. Notched (Smooth optional)
 28 in. x 5/16 in. Notched (Smooth optional)
 Weight Per Disk Blade: 285 lbs/blade
 Gang Axles:
 1-5/8 or 2-1/8 in. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 53
 Approximate Net Weight: 14,550 lbs
 Approximate Width of Cut: 22 ft. 4 in.
 Transport Width: 12.5 ft.
 Disk Spacing: 10-1/2 in.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 190-240 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 12.5L x 15 in. 10 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 in. x 16 in. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 4-6 Hrs For Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
BASE MACHINE			
3589XF		DH5222F - 22 Ft. Folding Single Offset Ag Disk with 53 Blades - U.S.	81,445.00
DISK BLADES			
1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	2,431.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	2,431.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	2,431.00
1080		26 In. Wavy Front and Wavy Rear Blades	805.00
1090		28 In. Wavy Front and Wavy Rear Blades	3,465.00
DISK BLADE CONCAVITY			
3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost
SCRAPERS			
5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	2,574.00

Tillage

DH5222F - 22 Ft. Folding Single Offset Ag Disk with 53 Blades - U.S.
 Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	9,505.00

Attachment Information is not available in MOCI for the base code 3589XF

FRONTIER PRODUCTS**Tillage****DH5224F - 24 Ft. Folding Single Offset Ag Disk with 57 Blades - U.S.**
Equipment for Base Machine

Class: Medium Duty
 Frame: 6 in. x 6 in. x 3/8 in. High Strength Steel
 Tube
 Disk Blades:
 26 in. x 5/16 in. Notched (Smooth optional)
 28 in. x 5/16 in. Notched (Smooth optional)
 Weight Per Disk Blade: 273 lbs/blade
 Gang Axles:
 1-5/8 or 2-1/8 in. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 57
 Approximate Net Weight: 15,000 lbs
 Approximate Width of Cut: 24 ft.
 Transport Width: 12.5 ft.
 Disk Spacing: 10-1/2 in.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 200-260 HP

Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 12.5L x 15 in. 10 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 in. x 16 in. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 4-6 Hrs For Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

358AXF		DH5224F - 24 Ft. Folding Single Offset Ag Disk with 57 Blades - U.S.	83,861.00
--------	--	--	-----------

DISK BLADES

1000		26 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		26 In. Smooth Front and Smooth Rear Disk Blades	No Added Cost
1020		26 In. Notched Front and Smooth Rear Disk Blades	No Added Cost
1030		28 In. Notched Front and Notched Rear Disk Blades	2,621.00
1040		28 In. Smooth Front and Smooth Rear Disk Blades	2,621.00
1050		28 In. Notched Front and Smooth Rear Disk Blades	2,621.00
1080		26 In. Wavy Front and Wavy Rear Blades	864.00
1090		28 In. Wavy Front and Wavy Rear Blades	3,733.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
3050		Low Concavity Blades	No Added Cost

SCRAPERS

5620		Rigid Scrapers	In Base Price
5621		Paddle Scrapers	2,769.00

Tillage

DH5224F - 24 Ft. Folding Single Offset Ag Disk with 57 Blades - U.S.
 Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
GANG AXLE COMPONENTS			
2000		1-5/8 In. Axle Components	In Base Price
2010		2-1/8 In. Axle Components	9,900.00

Attachment Information is not available in MOCI for the base code 358AXF

FRONTIER PRODUCTS**Tillage****DH5308 - 8 Ft. Rigid Single Offset Ag Disk with 17 Blades - U.S.**
Equipment for Base Machine

Class: Heavy Duty
 Frame: 6 In. x 6 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 28 In. x 3/8 In. Notched
 30 In. x 3/8 In. Notched
 32 In. x 3/8 In. Notched
 Weight Per Disk Blade: 533 lbs/blade
 Gang Axles:
 2-1/2 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 17
 Approximate Net Weight: 8,000 Lbs.
 Approximate Width of Cut: 8 Ft.
 Transport Width: 9 Ft.
 Disk Spacing: 12 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable

Recommended Drawbar HP: 100-130 HP
 Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 12.5L x 15 In. 10 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 16 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3591XF		DH5308 - 8 Ft. Rigid Single Offset Ag Disk with 17 Blades - U.S.	44,001.00
--------	--	--	-----------

DISK BLADES

1030		28 In. Notched Front and Notched Rear Disk Blades	In Base Price
1060		30 In. Notched Front and Notched Rear Disk Blades	1,524.00
1070		32 In. Notched Front and Notched Rear Disk Blades	1,789.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
------	--	--------------------------	---------------

GANG AXLE COMPONENTS

2020		2-1/2 In. Axle Components	In Base Price
------	--	---------------------------	---------------

Attachment Information is not available in MOCI for the base code 3591XF

Tillage

DH5308 - 8 Ft. Rigid Single Offset Ag Disk with 17 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH5310 - 10 Ft. Rigid Single Offset Ag Disk with 21 Blades - U.S.**
Equipment for Base Machine

Class: Heavy Duty
 Frame: 6 In. x 6 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 28 In. x 3/8 In. Notched
 30 In. x 3/8 In. Notched
 32 In. x 3/8 In. Notched
 Weight Per Disk Blade: 449 lbs/blade
 Gang Axles:
 2-1/2 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 21
 Approximate Net Weight: 8,525 Lbs.
 Approximate Width of Cut: 10 Ft.
 Transport Width: 11 Ft.
 Disk Spacing: 12 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable

Recommended Drawbar HP: 120-150 HP
 Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 12.5L x 15 In. 10 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 16 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3592XF		DH5310 - 10 Ft. Rigid Single Offset Ag Disk with 21 Blades - U.S.	48,688.00
--------	--	---	-----------

DISK BLADES

1030		28 In. Notched Front and Notched Rear Disk Blades	In Base Price
1060		30 In. Notched Front and Notched Rear Disk Blades	1,667.00
1070		32 In. Notched Front and Notched Rear Disk Blades	1,855.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
------	--	--------------------------	---------------

GANG AXLE COMPONENTS

2020		2-1/2 In. Axle Components	In Base Price
------	--	---------------------------	---------------

Attachment Information is not available in MOCI for the base code 3592XF

Tillage

DH5310 - 10 Ft. Rigid Single Offset Ag Disk with 21 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH5312 - 12 Ft. Rigid Single Offset Ag Disk with 25 Blades - U.S.**
Equipment for Base Machine

Class: Heavy Duty
 Frame: 6 In. x 6 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 28 In. x 3/8 In. Notched
 30 In. x 3/8 In. Notched
 32 In. x 3/8 In. Notched
 Weight Per Disk Blade: 397 lbs/blade
 Gang Axles:
 2-1/2 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 25
 Approximate Net Weight: 9,140 Lbs.
 Approximate Width of Cut: 12 Ft.
 Transport Width: 13 Ft.
 Disk Spacing: 12 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable

Recommended Drawbar HP: 140-170 HP
 Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 12.5L x 15 In. 10 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 16 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3593XF		DH5312 - 12 Ft. Rigid Single Offset Ag Disk with 25 Blades - U.S.	49,190.00
--------	--	---	-----------

DISK BLADES

1030		28 In. Notched Front and Notched Rear Disk Blades	In Base Price
1060		30 In. Notched Front and Notched Rear Disk Blades	1,291.00
1070		32 In. Notched Front and Notched Rear Disk Blades	2,054.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
------	--	--------------------------	---------------

GANG AXLE COMPONENTS

2020		2-1/2 In. Axle Components	In Base Price
------	--	---------------------------	---------------

Attachment Information is not available in MOCI for the base code 3593XF

Tillage

DH5312 - 12 Ft. Rigid Single Offset Ag Disk with 25 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH5314 - 14 Ft. Rigid Single Offset Ag Disk with 29 Blades - U.S.**
Equipment for Base Machine

Class: Heavy Duty
 Frame: 6 In. x 6 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 28 In. x 3/8 In. Notched
 30 In. x 3/8 In. Notched
 32 In. x 3/8 In. Notched
 Weight Per Disk Blade: 362 lbs/blade
 Gang Axles:
 2-1/2 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 29
 Approximate Net Weight: 10,450 Lbs.
 Approximate Width of Cut: 14 Ft.
 Transport Width: 15 Ft.
 Disk Spacing: 12 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable

Recommended Drawbar HP: 170-200 HP
 Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 12.5L x 15 In. 10 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 16 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3594XF		DH5314 - 14 Ft. Rigid Single Offset Ag Disk with 29 Blades - U.S.	52,658.00
--------	--	---	-----------

DISK BLADES

1030		28 In. Notched Front and Notched Rear Disk Blades	In Base Price
1060		30 In. Notched Front and Notched Rear Disk Blades	1,901.00
1070		32 In. Notched Front and Notched Rear Disk Blades	2,505.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
------	--	--------------------------	---------------

GANG AXLE COMPONENTS

2020		2-1/2 In. Axle Components	In Base Price
------	--	---------------------------	---------------

Attachment Information is not available in MOCI for the base code 3594XF

Tillage

DH5314 - 14 Ft. Rigid Single Offset Ag Disk with 29 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH5316 - 16 Ft. Rigid Single Offset Ag Disk with 33 Blades - U.S.**
Equipment for Base Machine

Class: Heavy Duty
 Frame: 6 In. x 6 In. x 3/8 In. High Strength Steel
 Tube
 Disk Blades:
 28 In. x 3/8 In. Notched
 30 In. x 3/8 In. Notched
 32 In. x 3/8 In. Notched
 Weight Per Disk Blade: 337 lbs/blade
 Gang Axles:
 2-1/2 In. Round
 Heat Treated High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 33
 Approximate Net Weight: 11,100 Lbs.
 Approximate Width of Cut: 16 Ft.
 Transport Width: 17 Ft.
 Disk Spacing: 12 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable

Recommended Drawbar HP: 180-210 HP
 Wheel Hub Bearings: Dual Tapered Roller Bearings
 Wheels: 8-Bolt Hubs
 Tires: (4) 12.5L x 15 In. 10 ply Implement
 Front and Rear Gang Angles: 2 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 16 In. Hydraulic Lift Cylinder
 Hitch Type: Spade
 Set Up Time: 2-3 Hours for Two People

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3595XF		DH5316 - 16 Ft. Rigid Single Offset Ag Disk with 33 Blades - U.S.	58,270.00
--------	--	---	-----------

DISK BLADES

1030		28 In. Notched Front and Notched Rear Disk Blades	In Base Price
1060		30 In. Notched Front and Notched Rear Disk Blades	2,106.00
1070		32 In. Notched Front and Notched Rear Disk Blades	2,836.00

DISK BLADE CONCAVITY

3000		Regular Concavity Blades	In Base Price
------	--	--------------------------	---------------

GANG AXLE COMPONENTS

2020		2-1/2 In. Axle Components	In Base Price
------	--	---------------------------	---------------

Attachment Information is not available in MOCI for the base code 3595XF

Tillage

DH5316 - 16 Ft. Rigid Single Offset Ag Disk with 33 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH5410 - 10 Ft. Rigid Single Offset Disk with 18 Blades - U.S.**
Equipment for Base Machine

Class: Construction Duty
 Frame: 7 In. x 7 In. x 3/8 In.
 High Strength Steel Tube
 Disk Blades:
 30 In. x 1/2 In. Notched
 32 In. x 1/2 In. Notched
 Weight Per Disk Blade: 583 Lbs./Blade
 Gang Axles:
 2-1/2 In. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 18
 Approximate Net Weight: 10,500 Lbs.
 Approximate Width of Cut: 10 Ft.
 Transport Width: 11 Ft.
 Disk Spacing: 13 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 175-225 HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings

Wheels: 10-Bolt Hubs
 Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic
 Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3601XF		DH5410 - 10 Ft. Rigid Single Offset Disk with 18 Blades - U.S.	68,113.00
--------	--	--	-----------

DISK BLADES

1000		30 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		32 In. Notched Front and Notched Rear Disk Blades	967.00

Attachment Information is not available in MOCI for the base code 3601XF

Tillage

DH5410 - 10 Ft. Rigid Single Offset Disk with 18 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH5411 - 11 Ft. Rigid Single Offset Disk with 20 Blades - U.S.**
Equipment for Base Machine

Class: Construction Duty
 Frame: 7 In. x 7 In. x 3/8 In.
 High Strength Steel Tube
 Disk Blades:
 30 In. x 1/2 In. Notched
 32 In. x 1/2 In. Notched
 Weight Per Disk Blade: 543 Lbs./Blade
 Gang Axles:
 2-1/2 In. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 20
 Approximate Net Weight: 10,875 Lbs.
 Approximate Width of Cut: 11 Ft.
 Transport Width: 12 Ft.
 Disk Spacing: 13 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 200-225 HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings

Wheels: 10-Bolt Hubs
 Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic
 Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3611XF		DH5411 - 11 Ft. Rigid Single Offset Disk with 20 Blades - U.S.	68,505.00
--------	--	--	-----------

DISK BLADES

1000		30 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		32 In. Notched Front and Notched Rear Disk Blades	1,100.00

Attachment Information is not available in MOCI for the base code 3611XF

Tillage

DH5411 - 11 Ft. Rigid Single Offset Disk with 20 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Tillage

DH5412 - 12 Ft. Rigid Single Offset Disk with 22 Blades - U.S.
 Equipment for Base Machine

Class: Construction Duty
 Frame: 7 In. x 7 In. x 3/8 In.
 High Strength Steel Tube
 Disk Blades:
 30 In. x 1/2 In. Notched
 32 In. x 1/2 In. Notched
 Weight Per Disk Blade: 534 Lbs./Blade
 Gang Axles:
 2-1/2 In. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 22
 Approximate Net Weight: 11,755 Lbs.
 Approximate Width of Cut: 12 Ft.
 Transport Width: 13 Ft.
 Disk Spacing: 13 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 225-250 HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings

Wheels: 10-Bolt Hubs
 Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic
 Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3621XF		DH5412 - 12 Ft. Rigid Single Offset Disk with 22 Blades - U.S.	69,581.00
--------	--	--	-----------

DISK BLADES

1000		30 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		32 In. Notched Front and Notched Rear Disk Blades	1,100.00

Attachment Information is not available in MOCI for the base code 3621XF

Tillage

DH5412 - 12 Ft. Rigid Single Offset Disk with 22 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Tillage

DH5413 - 13 Ft. Rigid Single Offset Disk with 24 Blades - U.S.
 Equipment for Base Machine

Class: Construction Duty
 Frame: 7 In. x 7 In. x 3/8 In.
 High Strength Steel Tube
 Disk Blades:
 30 In. x 1/2 In. Notched
 32 In. x 1/2 In. Notched
 Weight Per Disk Blade: 527 Lbs./Blade
 Gang Axles:
 2-1/2 In. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 24
 Approximate Net Weight: 12,650 Lbs.
 Approximate Width of Cut: 13 Ft.
 Transport Width: 14 Ft.
 Disk Spacing: 13 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 275-300 HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings

Wheels: 10-Bolt Hubs
 Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic
 Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3631XF		DH5413 - 13 Ft. Rigid Single Offset Disk with 24 Blades - U.S.	71,004.00
--------	--	--	-----------

DISK BLADES

1000		30 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		32 In. Notched Front and Notched Rear Disk Blades	1,262.00

Attachment Information is not available in MOCI for the base code 3631XF

Tillage

DH5413 - 13 Ft. Rigid Single Offset Disk with 24 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage

DH5414 - 14 Ft. Rigid Single Offset Disk with 26 Blades - U.S.
 Equipment for Base Machine

Class: Construction Duty
 Frame: 7 In. x 7 In. x 3/8 In.
 High Strength Steel Tube
 Disk Blades:
 30 In. x 1/2 In. Notched
 32 In. x 1/2 In. Notched
 Weight Per Disk Blade: 503 Lbs./Blade
 Gang Axles:
 2-1/2 In. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 26
 Approximate Net Weight: 13,100 Lbs.
 Approximate Width of Cut: 14 Ft.
 Transport Width: 15 Ft.
 Disk Spacing: 13 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 300+ HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings

Wheels: 10-Bolt Hubs
 Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3641XF		DH5414 - 14 Ft. Rigid Single Offset Disk with 26 Blades - U.S.	72,064.00
--------	--	--	-----------

DISK BLADES

1000		30 In. Notched Front and Notched Rear Disk Blades	In Base Price
1010		32 In. Notched Front and Notched Rear Disk Blades	1,382.00

Attachment Information is not available in MOCI for the base code 3641XF

Tillage

DH5414 - 14 Ft. Rigid Single Offset Disk with 26 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Tillage

DH5510 - 10 Ft. Rigid Single Offset Disk with 18 Blades - U.S.
 Equipment for Base Machine

Class: Construction Duty
 Frame: 8 In. x 8 In. x 1/2 In.
 High Strength Steel Tube
 Disk Blades:
 32 In. x 1/2 In. Notched
 Weight Per Disk Blade: 639 Lbs/Blade
 Gang Axles:
 2-1/2 In. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 18
 Approximate Net Weight: 11,500 Lbs.
 Approximate Width of Cut: 10 Ft.
 Transport Width: 11 Ft.
 Disk Spacing: 14 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 200+ HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings
 Wheels: 10-Bolt Hubs

Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic
 Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3651XF		DH5510 - 10 Ft. Rigid Single Offset Disk with 18 Blades - U.S.	70,805.00
--------	--	--	-----------

DISK BLADES

1010		32 In. Notched Front and Notched Rear Disk Blades	In Base Price
------	--	---	---------------

Attachment Information is not available in MOCI for the base code 3651XF

Tillage

DH5510 - 10 Ft. Rigid Single Offset Disk with 18 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH5511 - 11 Ft. Rigid Single Offset Disk with 20 Blades - U.S.**
Equipment for Base Machine

Class: Construction Duty
 Frame: 8 In. x 8 In. x 1/2 In.
 High Strength Steel Tube
 Disk Blades:
 32 In. x 1/2 In. Notched
 Weight Per Disk Blade: 600 Lbs/Blade
 Gang Axles:
 2-1/2 In. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 20
 Approximate Net Weight: 12,000 Lbs.
 Approximate Width of Cut: 11 Ft.
 Transport Width: 12 Ft.
 Disk Spacing: 14 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 225+ HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings
 Wheels: 10-Bolt Hubs

Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic
 Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3661XF		DH5511 - 11 Ft. Rigid Single Offset Disk with 20 Blades - U.S.	72,255.00
--------	--	--	-----------

DISK BLADES

1010		32 In. Notched Front and Notched Rear Disk Blades	In Base Price
------	--	---	---------------

Attachment Information is not available in MOCI for the base code 3661XF

Tillage

DH5511 - 11 Ft. Rigid Single Offset Disk with 20 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Tillage

DH5513 - 12 Ft. 6 In. Rigid Single Offset Disk with 22 Blades - U.S.
 Equipment for Base Machine

Class: Construction Duty
 Frame: 8 In. x 8 In. x 1/2 In.
 High Strength Steel Tube
 Disk Blades:
 32 In. x 1/2 In. Notched
 Weight Per Disk Blade: 568 Lbs/Blade
 Gang Axles:
 2-1/2 In. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 22
 Approximate Net Weight: 12,500 Lbs.
 Approximate Width of Cut: 12 Ft. 6 In.
 Transport Width: 13 Ft. 6 In.
 Disk Spacing: 14 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 250+ HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings
 Wheels: 10-Bolt Hubs

Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic
 Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3671XF		DH5513 - 12 Ft. 6 In. Rigid Single Offset Disk with 22 Blades - U.S.	74,575.00
--------	--	--	-----------

DISK BLADES

1010		32 In. Notched Front and Notched Rear Disk Blades	In Base Price
------	--	---	---------------

Attachment Information is not available in MOCI for the base code 3671XF

Tillage

DH5513 - 12 Ft. 6 In. Rigid Single Offset Disk with 22 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Tillage

DH5514 - 13 Ft. 9 In. Rigid Single Offset Disk with 24 Blades - U.S.
 Equipment for Base Machine

Class: Construction Duty
 Frame: 8 In. x 8 In. x 1/2 In.
 High Strength Steel Tube
 Disk Blades:
 32 In. x 1/2 In. Notched
 Weight Per Disk Blade: 554 Lbs./Blade
 Gang Axles:
 2-1/2 In. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 24
 Approximate Net Weight: 13,300 Lbs.
 Approximate Width of Cut: 13 Ft. 9 In.
 Transport Width: 14 Ft. 9 In.
 Disk Spacing: 14 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 300+ HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings
 Wheels: 10-Bolt Hubs

Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic
 Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3681XF		DH5514 - 13 Ft. 9 In. Rigid Single Offset Disk with 24 Blades - U.S.	76,955.00
--------	--	--	-----------

DISK BLADES

1010		32 In. Notched Front and Notched Rear Disk Blades	In Base Price
------	--	---	---------------

Attachment Information is not available in MOCI for the base code 3681XF

Tillage

DH5514 - 13 Ft. 9 In. Rigid Single Offset Disk with 24 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Tillage

DH5610 - 10 Ft. Rigid Single Offset Disk with 16 Blades - U.S.
 Equipment for Base Machine

Class: Construction Duty
 Frame: 8 In. x 8 In. x 1/2 In.
 High Strength Steel Tube
 Disk Blades:
 36 In. x 1/2 In. Notched
 Weight Per Disk Blade: 868 Lbs./Blade
 Gang Axles:
 2-1/2 In. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 16
 Approximate Net Weight: 13,900 Lbs.
 Approximate Width of Cut: 10 Ft.
 Transport Width: 11 Ft.
 Disk Spacing: 17 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 225+ HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings
 Wheels: 10-Bolt Hubs

Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic
 Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3691XF		DH5610 - 10 Ft. Rigid Single Offset Disk with 16 Blades - U.S.	73,969.00
--------	--	--	-----------

DISK BLADES

1020		36 In. Notched Front and Notched Rear Disk Blades	In Base Price
------	--	---	---------------

Attachment Information is not available in MOCI for the base code 3691XF

Tillage

DH5610 - 10 Ft. Rigid Single Offset Disk with 16 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH5612 - 11 Ft. 6 In. Rigid Single Offset Disk with 18 Blades - U.S.**
Equipment for Base Machine

Class: Construction Duty
 Frame: 8 In. x 8 In. x 1/2 In.
 High Strength Steel Tube
 Disk Blades:
 36 In. x 1/2 In. Notched
 Weight Per Disk Blade: 806 Lbs./Blade
 Gang Axles:
 2-1/2 In. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 18
 Approximate Net Weight: 14,500 Lbs.
 Approximate Width of Cut: 11 Ft. 6 In.
 Transport Width: 12 Ft. 6 In.
 Disk Spacing: 17 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 275+ HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings
 Wheels: 10-Bolt Hubs

Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic
 Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3701XF		DH5612 - 11 Ft. 6 In. Rigid Single Offset Disk with 18 Blades - U.S.	77,326.00
--------	--	--	-----------

DISK BLADES

1020		36 In. Notched Front and Notched Rear Disk Blades	In Base Price
------	--	---	---------------

Attachment Information is not available in MOCI for the base code 3701XF

Tillage

DH5612 - 11 Ft. 6 In. Rigid Single Offset Disk with 18 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Tillage

DH5613 - 13 Ft. Rigid Single Offset Disk with 20 Blades - U.S.
 Equipment for Base Machine

Class: Construction Duty
 Frame: 8 In. x 8 In. x 1/2 In.
 High Strength Steel Tube
 Disk Blades:
 36 In. x 1/2 In. Notched
 Weight Per Disk Blade: 760 Lbs./Blade
 Gang Axles:
 2-1/2 in. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 20
 Approximate Net Weight: 15,200 Lbs.
 Approximate Width of Cut: 13 Ft.
 Transport Width: 14 Ft.
 Disk Spacing: 17 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 325+ HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings
 Wheels: 10-Bolt Hubs

Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic
 Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3711XF		DH5613 - 13 Ft. Rigid Single Offset Disk with 20 Blades - U.S.	78,231.00
--------	--	--	-----------

DISK BLADES

1020		36 In. Notched Front and Notched Rear Disk Blades	In Base Price
------	--	---	---------------

Attachment Information is not available in MOCI for the base code 3711XF

Tillage

DH5613 - 13 Ft. Rigid Single Offset Disk with 20 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****DH5615 - 14 Ft. 6 In. Rigid Single Offset Disk with 22 Blades - U.S.**
Equipment for Base Machine

Class: Construction Duty
 Frame: 8 In. x 8 In. x 1/2 In.
 High Strength Steel Tube
 Disk Blades:
 36 In. x 1/2 In. Notched
 Weight Per Disk Blade: 722 Lbs./Blade
 Gang Axles:
 2-1/2 in. Round Heat Treated
 High Strength Alloy Steel
 Threaded on Both Ends
 Number of Disks: 22
 Approximate Net Weight: 15,900 Lbs.
 Approximate Width of Cut: 14 Ft. 6 In.
 Transport Width: 15 Ft. 6 In.
 Disk Spacing: 17 In.
 Disk Standards: Rigid, Welded Reinforced
 Disk Scrapers: Rigid, Adjustable
 Recommended Drawbar HP: 350+ HP
 Wheel Hub Bearings:
 Dual Tapered Roller Bearings
 Wheels: 10-Bolt Hubs

Tires: (2) 385/65R22.5 Super Single
 Radial, Heavy Industrial
 Front and Rear Gang Angles: 3 Positions
 Disk Gang Bearing Type:
 Oil Bath in Heavy Ductile Iron Cast Housing
 Back to Back Timken Tapered Roller Bearings
 Floating Duo-Cone Seals
 Bearing Wear Plates: Standard
 Hydraulics: 5 In. x 20 In. Hydraulic
 Lift Cylinder
 Hitch Type: Pintle
 Set Up Time: 2-3 Hrs. For Two People
 Warranty: 6 Months Construction /
 1 Year Agricultural

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

3721XF		DH5615 - 14 Ft. 6 In. Rigid Single Offset Disk with 22 Blades - U.S.	80,860.00
--------	--	--	-----------

DISK BLADES

1020		36 In. Notched Front and Notched Rear Disk Blades	In Base Price
------	--	---	---------------

Attachment Information is not available in MOCI for the base code 3721XF

Tillage

DH5615 - 14 Ft. 6 In. Rigid Single Offset Disk with 22 Blades - U.S.
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage**SR1201 - Single Shank Category 1 Shank Ripper**
Equipment for Base Machine

Shank Quantity: 1
Hitch: Category 1
Weight: 222 lbs Standard, 236 lbs Option
Shank Length: 24 in., Optional 28 in.
Max. Working Depth: 14 in., 18 in. with 28 in. long
shank
Shank Type: Parabolic
Shank Thickness: 1 1/4 in.
Frame Size: 7 in. X 5 in. Rectangular Tube

Shear Bolt Protected: Yes
Ripper Point Material: Heat Treated Steel
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2571XF		SR1201 - Single Shank Category 1 Shank Ripper	1,256.00
--------	--	---	----------

SHANK SIZE

7301		SR12 24 IN. LONG SHANK	No Added Cost
------	--	------------------------	---------------

7302		SR12 28 IN. LONG SHANK	41.00
------	--	------------------------	-------

DESTINATION

0202		UNITED STATES	No Added Cost
------	--	---------------	---------------

0184		CANADA	No Added Cost
------	--	--------	---------------

0205		QUEBEC, CANADA	No Added Cost
------	--	----------------	---------------

OPERATOR'S MANUAL AND DECALS

0409		SR12 ENGLISH OM/DECAL KIT	No Added Cost
------	--	---------------------------	---------------

0413		SR12 FRENCH OM/DECAL KIT	No Added Cost
------	--	--------------------------	---------------

0437		SR12 SPANISH OM/DECAL KIT	No Added Cost
------	--	---------------------------	---------------

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous		
5TL16324	SR12 24 IN. LONG SHANK	332.20
5TL16325	SR12 28 IN. LONG SHANK	375.11
5TL16337	SR12 FRENCH OM/DECAL KIT	58.31
5TL16338	SR12 SPANISH OM/DECAL KIT	58.31

Tillage

SR1201 - Single Shank Category 1 Shank Ripper
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****SR1202 - Two Shank Category 2 Shank Ripper**
Equipment for Base Machine

Shank Quantity: 2
 Hitch: Category 2
 Weight: 466 lbs Standard, 494 lbs Option
 Shank Length: 24 in., Optional 28 in.
 Max. Working Depth: 14 in., 18 in. with 28 in. long
 shank
 Shank Type: Parabolic
 Shank Thickness: 1 1/4 in.
 Frame Size: 7 in. X 5 in. Rectangular Tube

Shear Bolt Protected: Yes
 Ripper Point Material: Heat Treated Steel
 Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2581XF		SR1202 - Two Shank Category 2 Shank Ripper	2,184.00
--------	--	--	----------

SHANK SIZE

7301		SR12 24 IN. LONG SHANK	No Added Cost
------	--	------------------------	---------------

7302		SR12 28 IN. LONG SHANK	82.00
------	--	------------------------	-------

DESTINATION

0202		UNITED STATES	No Added Cost
------	--	---------------	---------------

0184		CANADA	No Added Cost
------	--	--------	---------------

0205		QUEBEC, CANADA	No Added Cost
------	--	----------------	---------------

OPERATOR'S MANUAL AND DECALS

0409		SR12 ENGLISH OM/DECAL KIT	No Added Cost
------	--	---------------------------	---------------

0413		SR12 FRENCH OM/DECAL KIT	No Added Cost
------	--	--------------------------	---------------

0437		SR12 SPANISH OM/DECAL KIT	No Added Cost
------	--	---------------------------	---------------

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous		
5TL16324	SR12 24 IN. LONG SHANK	332.20
5TL16325	SR12 28 IN. LONG SHANK	375.11
5TL16337	SR12 FRENCH OM/DECAL KIT	58.31
5TL16338	SR12 SPANISH OM/DECAL KIT	58.31

Tillage

SR1202 - Two Shank Category 2 Shank Ripper
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage**SR1203 - Three Shank Category 2 Shank Ripper**
Equipment for Base Machine

Shank Quantity: 3
Hitch: Category 2
Weight: 892 lbs Standard, 934 lbs Option
Shank Length: 24 in., Optional 28 in.
Max. Working Depth: 14 in., 18 in. with 28 in. long
shank
Shank Type: Parabolic
Shank Thickness: 1 1/4 in.
Frame Size: Double Bar 7 in. x 5 in. & 5 in. x 3
in.

Shear Bolt Protected: Yes
Ripper Point Material: Heat Treated Steel
Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2591XF		SR1203 - Three Shank Category 2 Shank Ripper	3,598.00
--------	--	--	----------

SHANK SIZE

7301		SR12 24 IN. LONG SHANK	No Added Cost
7302		SR12 28 IN. LONG SHANK	123.00

DESTINATION

0202		UNITED STATES	No Added Cost
0184		CANADA	No Added Cost
0205		QUEBEC, CANADA	No Added Cost

OPERATOR'S MANUAL AND DECALS

0409		SR12 ENGLISH OM/DECAL KIT	No Added Cost
0413		SR12 FRENCH OM/DECAL KIT	No Added Cost
0437		SR12 SPANISH OM/DECAL KIT	No Added Cost

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous			
5TL16324	SR12 24 IN. LONG SHANK		332.20
5TL16325	SR12 28 IN. LONG SHANK		375.11
5TL16337	SR12 FRENCH OM/DECAL KIT		58.31
5TL16338	SR12 SPANISH OM/DECAL KIT		58.31

Tillage

SR1203 - Three Shank Category 2 Shank Ripper
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Tillage

CP1148L - 4 ft. Cultipacker with 9.5 in. Wheels

Equipment for Base Machine

Working Width: 4 ft.
 Hitch: Limited Category 1
 Tractor HP Range: 20-40 hp
 Overall Dimensions: H 32 in. x W 56 in. x L 19 in.
 Weight: 310 lbs
 Wheel Size: 9.5 in.
 Wheel Material: Cast Iron
 Wheel Type: Notched

Main Frame: Heavy Duty 2" Square Tube Steel
 Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2501XF		CP1148L - 4 ft. Cultipacker with 9.5 in. Wheels	1,362.00
--------	--	---	----------

DESTINATION

0202		U.S. CP11L/CP15-Series	In Base Price
0184		Canada CP11L/CP15-Series	No Added Cost
0205		Quebec, Canada CP11L/CP15-Series	No Added Cost

OPERATOR'S MANUAL AND DECALS

0409		CP11L/CP15 ENGLISH OM/DECAL KIT	In Base Price
0413		CP11L/CP15 FRENCH OM/DECAL KIT	No Added Cost
0437		CP11L/CP15 SPANISH OM/DECAL KIT	No Added Cost

ATTACHMENTS - ORDER AS DESIRED

905P		SCRAPER KIT CP1148L SCRAPER KIT - 5TSLKCP1148L	293.00
905R		Tongue and Wheel Kit CP1148L & CP1172L - 5TL16320	391.00

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous			
5TSLKCP1148L	CP1148L SCRAPER KIT		303.60
5TL16335	CP11L/CP15 FRENCH OM/DECAL KIT		58.31
5TL16336	CP11L/CP15 SPANISH OM/DECAL KIT		58.31
5TL16320	Tongue and Wheel Kit		405.91

Tillage

CP1148L - 4 ft. Cultipacker with 9.5 in. Wheels
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Tillage

CP1172L - 6 ft. Cultipacker with 9.5 in. Wheels

Equipment for Base Machine

Working Width: 6 ft.
 Hitch: Limited Category 1
 Tractor HP Range: 20-40 hp
 Overall Dimensions: H 32 in. x W 80 in. x L 19 in.
 Weight: 412 lbs
 Wheel Size: 9.5 in.
 Wheel Material: Cast Iron
 Wheel Type: Notched

Main Frame: Heavy Duty 2" Square Tube Steel
 Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2511XF		CP1172L - 6 ft. Cultipacker with 9.5 in. Wheels	2,113.00
--------	--	---	----------

DESTINATION

0202		U.S. CP11L/CP15-Series	In Base Price
0184		Canada CP11L/CP15-Series	No Added Cost
0205		Quebec, Canada CP11L/CP15-Series	No Added Cost

OPERATOR'S MANUAL AND DECALS

0409		CP11L/CP15 ENGLISH OM/DECAL KIT	In Base Price
0413		CP11L/CP15 FRENCH OM/DECAL KIT	No Added Cost
0437		CP11L/CP15 SPANISH OM/DECAL KIT	No Added Cost

ATTACHMENTS - ORDER AS DESIRED

905P		SCRAPER KIT CP1172L SCRAPER KIT - 5TSLKCP1172L	376.00
905R		Tongue and Wheel Kit CP1148L & CP1172L - 5TL16320	391.00

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous			
5TSLKCP1172L	CP1172L SCRAPER KIT		390.51
5TL16335	CP11L/CP15 FRENCH OM/DECAL KIT		58.31
5TL16336	CP11L/CP15 SPANISH OM/DECAL KIT		58.31
5TL16320	Tongue and Wheel Kit		405.91

Tillage

CP1172L - 6 ft. Cultipacker with 9.5 in. Wheels
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****CP1572 - 6 ft. Cultipacker with 16 in. Wheels**
Equipment for Base Machine

Working Width: 6 ft.
 Hitch: Category 1
 Tractor HP Range: 30-70 hp
 Overall Dimensions: H 45 in. x W 83 in. x L 22 in.
 Weight: 860 lbs
 Wheel Size: 16 in.
 Wheel Material: Cast Iron
 Wheel Type: Notched

Main Frame: Heavy Duty 4" Square Tube Steel
 Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2531XF		CP1572 - 6 ft. Cultipacker with 16 in. Wheels	3,186.00
--------	--	---	----------

DESTINATION

0202		U.S. CP11L/CP15-Series	In Base Price
0184		Canada CP11L/CP15-Series	No Added Cost
0205		Quebec, Canada CP11L/CP15-Series	No Added Cost

OPERATOR'S MANUAL AND DECALS

0409		CP11L/CP15 ENGLISH OM/DECAL KIT	In Base Price
0413		CP11L/CP15 FRENCH OM/DECAL KIT	No Added Cost
0437		CP11L/CP15 SPANISH OM/DECAL KIT	No Added Cost

ATTACHMENTS - ORDER AS DESIRED

905P		SCRAPER KIT CP1572 SCRAPER KIT - 5TLSKCP1572	222.00
------	--	---	--------

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous			
5TL16335	CP11L/CP15 FRENCH OM/DECAL KIT		58.31
5TL16336	CP11L/CP15 SPANISH OM/DECAL KIT		58.31
5TLSKCP1572	CP1572 SCRAPER KIT		229.91

Tillage

CP1572 - 6 ft. Cultipacker with 16 in. Wheels
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****CP1596 - 8 ft. Cultipacker with 16 in. Wheels**
Equipment for Base Machine

Working Width: 8 ft.
 Hitch: Category 1 & 2
 Tractor HP Range: 30-125 hp
 Overall Dimensions: H 45 in. x W 107 in. x L 22 in.
 Weight: 1068 lbs
 Wheel Size: 16 in.
 Wheel Material: Cast Iron
 Wheel Type: Notched

Main Frame: Heavy Duty 4" Square Tube Steel
 Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2541XF		CP1596 - 8 ft. Cultipacker with 16 in. Wheels	3,850.00
--------	--	---	----------

DESTINATION

0202		U.S. CP11L/CP15-Series	In Base Price
0184		Canada CP11L/CP15-Series	No Added Cost
0205		Quebec, Canada CP11L/CP15-Series	No Added Cost

OPERATOR'S MANUAL AND DECALS

0409		CP11L/CP15 ENGLISH OM/DECAL KIT	In Base Price
0413		CP11L/CP15 FRENCH OM/DECAL KIT	No Added Cost
0437		CP11L/CP15 SPANISH OM/DECAL KIT	No Added Cost

ATTACHMENTS - ORDER AS DESIRED

905P		SCRAPER KIT CP1596 SCRAPER KIT - 5TLSKCP1596	299.00
------	--	---	--------

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous		
5TL16335	CP11L/CP15 FRENCH OM/DECAL KIT	58.31
5TL16336	CP11L/CP15 SPANISH OM/DECAL KIT	58.31
5TLSKCP1596	CP1596 SCRAPER KIT	310.20

Tillage

CP1596 - 8 ft. Cultipacker with 16 in. Wheels
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS

Tillage

CP1512 - 12 ft. Cultipacker with 16 in. Wheels

Equipment for Base Machine

Working Width: 12 ft.
 Hitch: Category 2
 Tractor HP Range: 50-125 hp
 Overall Dimensions: H 45 in. x W 161 in. x L 22 in.
 Weight: 1640 lbs
 Wheel Size: 16 in.
 Wheel Material: Cast Iron
 Wheel Type: Notched

Main Frame: Heavy Duty 4" Square Tube Steel
 Warranty: 1 Year

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

2521XF		CP1512 - 12 ft. Cultipacker with 16 in. Wheels	7,110.00
--------	--	--	----------

DESTINATION

0202		U.S. CP11L/CP15-Series	In Base Price
0184		Canada CP11L/CP15-Series	No Added Cost
0205		Quebec, Canada CP11L/CP15-Series	No Added Cost

OPERATOR'S MANUAL AND DECALS

0409		CP11L/CP15 ENGLISH OM/DECAL KIT	In Base Price
0413		CP11L/CP15 FRENCH OM/DECAL KIT	No Added Cost
0437		CP11L/CP15 SPANISH OM/DECAL KIT	No Added Cost

ATTACHMENTS - ORDER AS DESIRED

905P		SCRAPER KIT CP1512 SCRAPER KIT - 5TLSKCP1512	437.00
905W		Safety Light Kit CP1512 - 5TL16323	606.00

ATTACHMENTS FOR FIELD CONVERSION

Miscellaneous			
5TL16335		CP11L/CP15 FRENCH OM/DECAL KIT	58.31
5TL16336		CP11L/CP15 SPANISH OM/DECAL KIT	58.31
5TLSKCP1512		CP1512 SCRAPER KIT	453.20
5TL16323		Safety Light Kit	629.20

FRONTIER PRODUCTS

Tillage

CP1512 - 12 ft. Cultipacker with 16 in. Wheels
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****VT1710 - 10 Ft. 6 In. Vertical Tillage Tool with 32 Blades on 7.5 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 4 In. x 8 In. Cylinder
with 160 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (Dual 11L-15)
Working Width: 10 Ft. 6 In.
Transport Width: 11 Ft. 8 In.
Blade Spacing: 7.5 In.
Tractor HP: 80-110 HP
Shipping Weight: 6380 lbs.
Approximate Operating Weight: 5980 lbs.
Number of Blades: 32
Blade Size: 20 or 22 In. Diameter
Blade Thickness: 5 mm (0.197 In.) or 6 mm (0.236)
Frame: 4 In. X 6 In. X 0.25 In. Front and 4 In. X 4
In. X 0.25 In. Rear, Square Tube Frame
Gang Tubing: 4 In. X 4 In. X 0.25 In. Square Tube

Bearing Hanger:
Shock Flex C-Hanger
2 Bolt Front 1 Bolt Rear
Bearing Type:
Self Aligning Sealed
Ball Bearing in a Trunnion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles:
0, 3, 6, 9, 12, 15 Degrees
Rear Gang Angles:
0, 3, 6, 9, 12, 15 Degrees
14" Rolling Basket with adjustable downpressure
Light Kit
Approximate Assembly Time: 6 hrs

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
BASE MACHINE			
1801XF		VT1710 - 10 Ft. 6 In. Vertical Tillage Tool with 32 Blades on 7.5 In. Spacing	23,373.00
DISK BLADES			
5701		VT17 22"X.197" Sharp Concave Disk	3,932.00
5711		VT17 20"X.296" Flat Fluted Disk	2,831.00
DESTINATION			
0202		United States	In Base Price
0184		Canada	No Added Cost
0205		Quebec, Canada	No Added Cost
OPERATOR'S MANUAL AND DECALS			
0409		English Operator's Manual and Decal Kit	In Base Price
0413		French Operator's Manual and Decal Kit	No Added Cost
0437		Spanish Operator's Manual and Decal Kit	No Added Cost
DISK GANG BEARING STYLE			
5911		VT17 BEARING 1.125" SHAFT SEALED	In Base Price
5901		VT17 BEARING 1.125" SHAFT RELUBE-12	432.00

Tillage**VT1710 - 10 Ft. 6 In. Vertical Tillage Tool with 32 Blades on 7.5 In. Spacing**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DISK GANG ANGLE OPTION			
7240		0-12 Degree Gang Angle	In Base Price
7241		0-5 Degree Gang Angle for VT1710 and VT1712	No Added Cost
SCRAPERS			
9891		Scraper Kit for Disk Blades	1,176.00
9881		Scraper Kit for Furrow Fillers	134.00
OPERATOR'S MANUAL AND DECALS			
904J		FRENCH OM/DECAL KIT	59.00
904V		SPANISH OM/DECAL KIT	59.00
MIDDLE BREAKER			
9221		Middle Breaker	324.00
MISCELLANEOUS			
9473		Furrow Filler Kit - 20" Disk Blade <i>Furrow Fill Kit is only to be ordered with 20" Blade Options (5TL220236VTF)</i>	280.00
9474		Furrow Filler Kit - 22" Disk Blade <i>Furrow Filler Kit is only to be ordered with 22" Blade Options (5TL222197VTR)</i>	286.00
ATTACHMENTS FOR FIELD CONVERSION			
5TL16249		Disk Gang Angle Option 0-5 Degree Gang Angle for VT1710 or VT1712	56.11
5TL11476VT		Middle Breaker VT17 Series Middle Breaker	336.60
5TLT70316VT		Miscellaneous VT17 Series Furrow Fillers for 20 in. Blade	290.40
5TLT70318VT		VT17 Series Furrow Fillers for 22" Blade	297.00
5TL15169VT		VT17 Series Scraper Kit for Furrow Fillers	See Parts
5TL16159		Operator's Manual and Decals VT17 Series French Operator's Manual and Decal Kit	61.60
5TL16160		VT17 Series Spanish Operator's Manual and Decal Kit	61.60

Tillage

VT1710 - 10 Ft. 6 In. Vertical Tillage Tool with 32 Blades on 7.5 In. Spacing
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
		Scrapers	
	5TLSK7327	VT1710 Scraper Kit	1,219.91

Tillage

VT1710 - 10 Ft. 6 In. Vertical Tillage Tool with 32 Blades on 7.5 In. Spacing

Continued

THIS PAGE INTENTIONALLY LEFT BLANK

Tillage

VT1712 - 12 Ft Vertical Tillage Tool with 36 Blades on 7.5 In. Spacing
 Equipment for Base Machine

Hitch: Drawn Level Lift
 with Clevis and Jack
 Hitch Safety Chain: Standard
 Hydraulics: 4 In. x 8 In. Cylinder
 with 160 In. of Hydraulic Hose
 Depth Control:
 Center Mounted Pin Adjustment
 Tires: Standard (Dual 11L-15)
 Working Width: 12 Ft. 0 In.
 Transport Width: 13 Ft. 8 In.
 Blade Spacing: 7.5 In.
 Tractor HP: 95-120 HP
 Shipping Weight: 7264 lbs.
 Approximate Operating Weight: 6864 lbs.
 Number of Blades: 36
 Blade Size: 20 or 22 In. Diameter
 Blade Thickness: 5 mm (0.197 In.) or 6 mm (0.236)
 Frame: 4 In. X 6 In. X 0.25 In. Front and 4 In. X 4
 In. X 0.25 In. Rear, Square Tube Frame
 Gang Tubing: 4 In. X 4 In. X 0.25 In. Square Tube

Bearing Hanger:
 Shock Flex C-Hanger
 2 Bolt Front 1 Bolt Rear
 Bearing Type:
 Self Aligning Sealed
 Ball Bearing in a Trunnion Mount
 Gang Axle: 1-1/8 In. Square
 Front Gang Angles:
 0, 3, 6, 9, 12, 15 Degrees
 Rear Gang Angles:
 0, 3, 6, 9, 12, 15 Degrees
 14" Rolling Basket with adjustable downpressure
 Light Kit
 Approximate Assembly Time: 6 hrs

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

1812XF		VT1712 - 12 Ft Vertical Tillage Tool with 36 Blades on 7.5 In. Spacing	24,067.00
--------	--	--	-----------

DISK BLADES

5701		VT17 22"X.197" Sharp Concave Disk	4,422.00
5711		VT17 20"X.296" Flat Fluted Disk	3,185.00

DESTINATION

0202		United States	In Base Price
0184		Canada	No Added Cost
0205		Quebec, Canada	No Added Cost

OPERATOR'S MANUAL AND DECALS

0409		English Operator's Manual and Decal Kit	In Base Price
0413		French Operator's Manual and Decal Kit	No Added Cost
0437		Spanish Operator's Manual and Decal Kit	No Added Cost

DISK GANG BEARING STYLE

5911		VT17 BEARING 1.125" SHAFT SEALED	In Base Price
5901		VT17 BEARING 1.125" SHAFT RELUBE-12	432.00

DISK GANG ANGLE OPTION

7240		0-12 Degree Gang Angle	In Base Price
------	--	------------------------	---------------

Tillage

VT1712 - 12 Ft Vertical Tillage Tool with 36 Blades on 7.5 In. Spacing
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DISK GANG ANGLE OPTION ...Continued...			
7241		0-5 Degree Gang Angle for VT1710 and VT1712	No Added Cost
SCRAPERS			
9891		Scraper Kit for Disk Blades	1,280.00
9881		Scraper Kit for Furrow Fillers	134.00
OPERATOR'S MANUAL AND DECALS			
904J		FRENCH OM/DECAL KIT	59.00
904V		SPANISH OM/DECAL KIT	59.00
MIDDLE BREAKER			
9221		Middle Breaker	324.00
MISCELLANEOUS			
9473		Furrow Filler Kit - 20" Disk Blade <i>Furrow Fill Kit is only to be ordered with 20" Blade Options (5TL220236VTF)</i>	280.00
9474		Furrow Filler Kit - 22" Disk Blade <i>Furrow Filler Kit is only to be ordered with 22" Blade Options (5TL222197VTR)</i>	286.00
ATTACHMENTS FOR FIELD CONVERSION			
5TL16249		Disk Gang Angle Option 0-5 Degree Gang Angle for VT1710 or VT1712	56.11
5TL11476VT		Middle Breaker VT17 Series Middle Breaker	336.60
5TLT70316VT		Miscellaneous VT17 Series Furrow Fillers for 20 in. Blade	290.40
5TLT70318VT		VT17 Series Furrow Fillers for 22" Blade	297.00
5TL15169VT		VT17 Series Scraper Kit for Furrow Fillers	See Parts
5TL16159		Operator's Manual and Decals VT17 Series French Operator's Manual and Decal Kit	61.60
5TL16160		VT17 Series Spanish Operator's Manual and Decal Kit	61.60
5TLSK7367		Scrapers VT1712 Scraper Kit	1,328.80

FRONTIER PRODUCTS**Tillage****VT1713 - 13 Ft 4 In. Vertical Tillage Tool with 40 Blades on 7.5 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 4 In. x 8 In. Cylinder
with 160 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (Dual 11L-15)
Working Width: 13 Ft. 4 In.
Transport Width: 14 Ft. 8 In.
Blade Spacing: 7.5 In.
Tractor HP: 105-130 HP
Shipping Weight: 8260 lbs.
Approximate Operating Weight: 7760 lbs.
Number of Blades: 40
Blade Size: 20 or 22 In. Diameter
Blade Thickness: 5 mm (0.197 In.) or 6 mm (0.236)
Frame: 4 In. X 6 In. X 0.25 In. Front and 4 In. X 4
In. X 0.25 In. Rear, Square Tube Frame
Gang Tubing: 4 In. X 4 In. X 0.25 In. Square Tube

Bearing Hanger:
Shock Flex C-Hanger
2 Bolt Front 1 Bolt Rear
Bearing Type:
Self Aligning Sealed
Ball Bearing in a Trunnion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles:
0, 3, 6, 9, 12, 15 Degrees
Rear Gang Angles:
0, 3, 6, 9, 12, 15 Degrees
14" Rolling Basket with adjustable downpressure
Light Kit
Approximate Assembly Time: 6 hrs

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
Select One Code From Each Required Category			
BASE MACHINE			
1823XF		VT1713 - 13 Ft 4 In. Vertical Tillage Tool with 40 Blades on 7.5 In. Spacing	24,881.00
DISK BLADES			
5701		VT17 22"X.197" Sharp Concave Disk	4,914.00
5711		VT17 20"X.296" Flat Fluted Disk	3,537.00
DESTINATION			
0202		United States	In Base Price
0184		Canada	No Added Cost
0205		Quebec, Canada	No Added Cost
OPERATOR'S MANUAL AND DECALS			
0409		English Operator's Manual and Decal Kit	In Base Price
0413		French Operator's Manual and Decal Kit	No Added Cost
0437		Spanish Operator's Manual and Decal Kit	No Added Cost
DISK GANG BEARING STYLE			
5911		VT17 BEARING 1.125" SHAFT SEALED	In Base Price
5902		VT17 BEARING 1.125" RELUBE-16	578.00

Tillage**VT1713 - 13 Ft 4 In. Vertical Tillage Tool with 40 Blades on 7.5 In. Spacing**

Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DISK GANG ANGLE OPTION			
7240		0-12 Degree Gang Angle	In Base Price
7242		0-5 Degree Gang Angle for VT1713 and VT1715	No Added Cost
SCRAPERS			
9891		Scraper Kit for Disk Blades	1,388.00
9881		Scraper Kit for Furrow Fillers	134.00
OPERATOR'S MANUAL AND DECALS			
904J		FRENCH OM/DECAL KIT	59.00
904V		SPANISH OM/DECAL KIT	59.00
MIDDLE BREAKER			
9221		Middle Breaker	324.00
MISCELLANEOUS			
9473		Furrow Filler Kit - 20" Disk Blade <i>Furrow Fill Kit is only to be ordered with 20" Blade Options (5TL220236VTF)</i>	280.00
9474		Furrow Filler Kit - 22" Disk Blade <i>Furrow Filler Kit is only to be ordered with 22" Blade Options (5TL222197VTR)</i>	286.00
ATTACHMENTS FOR FIELD CONVERSION			
5TL16250		Disk Gang Angle Option 0-5 Degree Gang Angle for VT1713 or VT1715	56.11
5TL11476VT		Middle Breaker VT17 Series Middle Breaker	336.60
5TLT70316VT		Miscellaneous VT17 Series Furrow Fillers for 20 in. Blade	290.40
5TLT70318VT		VT17 Series Furrow Fillers for 22" Blade	297.00
5TL15169VT		VT17 Series Scraper Kit for Furrow Fillers	See Parts
5TL16159		Operator's Manual and Decals VT17 Series French Operator's Manual and Decal Kit	61.60
5TL16160		VT17 Series Spanish Operator's Manual and Decal Kit	61.60

Tillage

VT1713 - 13 Ft 4 In. Vertical Tillage Tool with 40 Blades on 7.5 In. Spacing
 Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
ATTACHMENTS FOR FIELD CONVERSION ...Continued...			
5TLSK7407	Scrapers VT1713 Scraper Kit	1,439.91	

Tillage

VT1713 - 13 Ft 4 In. Vertical Tillage Tool with 40 Blades on 7.5 In. Spacing
Continued

THIS PAGE INTENTIONALLY LEFT BLANK

FRONTIER PRODUCTS**Tillage****VT1715 - 15 Ft Vertical Tillage Tool with 44 Blades on 7.5 In. Spacing**
Equipment for Base Machine

Hitch: Drawn Level Lift
with Clevis and Jack
Hitch Safety Chain: Standard
Hydraulics: 4 In. x 8 In. Cylinder
with 160 In. of Hydraulic Hose
Depth Control:
Center Mounted Pin Adjustment
Tires: Standard (Dual 11L-15)
Working Width: 15 Ft. 0 In.
Transport Width: 16 Ft. 6 In.
Blade Spacing: 7.5 In.
Tractor HP: 115-150 HP
Shipping Weight: 8575 lbs.
Approximate Operating Weight: 8075 lbs.
Number of Blades: 44
Blade Size: 20 or 22 In. Diameter
Blade Thickness: 5 mm (0.197 In.) or 6 mm (0.236)
Frame: 4 In. X 6 In. X 0.25 In. Front and 4 In. X 4
In. X 0.25 In. Rear, Square Tube Frame
Gang Tubing: 4 In. X 4 In. X 0.25 In. Square Tube

Bearing Hanger:
Shock Flex C-Hanger
2 Bolt Front 1 Bolt Rear
Bearing Type:
Self Aligning Sealed
Ball Bearing in a Trunnion Mount
Gang Axle: 1-1/8 In. Square
Front Gang Angles:
0, 3, 6, 9, 12, 15 Degrees
Rear Gang Angles:
0, 3, 6, 9, 12, 15 Degrees
14" Rolling Basket with adjustable downpressure
Light Kit
Approximate Assembly Time: 6 hrs

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
------	-----------------------	-------------	-------------------------------

Select One Code From Each Required Category

BASE MACHINE

1833XF		VT1715 - 15 Ft Vertical Tillage Tool with 44 Blades on 7.5 In. Spacing	26,765.00
--------	--	--	-----------

DISK BLADES

5701		VT17 22"X.197" Sharp Concave Disk	5,406.00
5711		VT17 20"X.296" Flat Fluted Disk	3,892.00

DESTINATION

0202		United States	In Base Price
0184		Canada	No Added Cost
0205		Quebec, Canada	No Added Cost

OPERATOR'S MANUAL AND DECALS

0409		English Operator's Manual and Decal Kit	In Base Price
0413		French Operator's Manual and Decal Kit	No Added Cost
0437		Spanish Operator's Manual and Decal Kit	No Added Cost

DISK GANG BEARING STYLE

5911		VT17 BEARING 1.125" SHAFT SEALED	In Base Price
5902		VT17 BEARING 1.125" RELUBE-16	578.00

DISK GANG ANGLE OPTION

7240		0-12 Degree Gang Angle	In Base Price
------	--	------------------------	---------------

Tillage

VT1715 - 15 Ft Vertical Tillage Tool with 44 Blades on 7.5 In. Spacing
Continued

Code	Attachment Identifier	Description	List Price Suggested USD (\$)
DISK GANG ANGLE OPTION ...Continued...			
7242		0-5 Degree Gang Angle for VT1713 and VT1715	No Added Cost
SCRAPERS			
9891		Scraper Kit for Disk Blades	1,482.00
9881		Scraper Kit for Furrow Fillers	134.00
OPERATOR'S MANUAL AND DECALS			
904J		FRENCH OM/DECAL KIT	59.00
904V		SPANISH OM/DECAL KIT	59.00
MIDDLE BREAKER			
9221		Middle Breaker	324.00
MISCELLANEOUS			
9473		Furrow Filler Kit - 20" Disk Blade <i>Furrow Fill Kit is only to be ordered with 20" Blade Options (5TL220236VTF)</i>	280.00
9474		Furrow Filler Kit - 22" Disk Blade <i>Furrow Filler Kit is only to be ordered with 22" Blade Options (5TL222197VTR)</i>	286.00
ATTACHMENTS FOR FIELD CONVERSION			
5TL16250		Disk Gang Angle Option 0-5 Degree Gang Angle for VT1713 or VT1715	56.11
5TL11476VT		Middle Breaker VT17 Series Middle Breaker	336.60
5TLT70316VT		Miscellaneous VT17 Series Furrow Fillers for 20 in. Blade	290.40
5TLT70318VT		VT17 Series Furrow Fillers for 22" Blade	297.00
5TL15169VT		VT17 Series Scraper Kit for Furrow Fillers	See Parts
5TL16159		Operator's Manual and Decals VT17 Series French Operator's Manual and Decal Kit	61.60
5TL16160		VT17 Series Spanish Operator's Manual and Decal Kit	61.60
5TLSK7447		Scrapers VT1715 Scraper Kit	1,537.80