



15-Jun-2022

Code	Description	324L - FOUR WHEEL DRIVE LOADER	QTY	List Price (USD)
------	-------------	--------------------------------	-----	------------------

OAGOT	324L - FOUR WHEEL DRIVE LOADER		1	\$127,000.00
-------	--------------------------------	--	---	--------------

ENGINE:

Yanmar 4TNV98CT
70 SAE Net Horsepower (52 kW)
Isolation Mounted
Turbocharged
Glow Plugs
Engine Coolant -34 Degree F (-37 Degree C)
Coolant Recovery Tank
Proportional Speed Hydraulic Driven Cooling Fan
Spin-On Engine Oil and Fuel Filters
Oil-to-Water Engine Oil Cooler
Dual Safety Element Dry-Type Air Cleaner with Dust Evacuator
Valve and Pre-Screener
Muffler, Under Hood, with Exhaust Stack
Enclosed Safety Fan Guard (Conforms to SAE J1308)

ELECTRICAL:

12 Volt System
80 Amp Sealed Alternator
(1) 12 Volt, 925 CCA
Master Electrical Disconnect Switch
Blade-Type Multi-Fused Circuits
Sealed External Electrical Connections
Electrical Load Center In Operator Station
Bypass Start Safety Cover on Starter
Positive Terminal Battery Covers
Lights (Conforms to SAE J99):
(2) Driving / (2) Front Working Halogen Lights
(2) Front and (2) Rear Turn/Flashing
(2) Rear Stop Lights
(2) Rear Reflectors
(2) Rear Work Lights

HYDRAULIC SYSTEM:

Joystick FNR Control with Third Function Control Lever
24 GPM (91 L/Min) Engine Mounted Gear Pump - Open Center
Combined Hydrostatic/Hydraulic Oil Reservoir with Sight Glass

TRANSMISSION:

Single Lever Shift Control, F-N-R and 2 Speed automatic gear box
Hydrostatic Transmission with Infinite Speed Control
Inching Pedal
Vertical Filter Element

AXLES:

Heavy-Duty Outboard Planetary Final Drives
100% Manual (Push Button) Front Diff/Lock and Rear Std.
Differential
Grease Bank for Oscillating Rear Axle

BRAKES:

Service Brakes; Hydraulically Actuated, Self Adjusting
internal Wet Disc Brake and Driveline Drum Brake
Park Brake; Automatic Spring-Applied, Hydraulic-Released
internal Wet Disc Brake

STEERING:

Hydraulic Stereo Steer:
56 Degrees Articulation (28 Degree in Each Direction) Plus
an Additional 26
Degree Rear Wheel Steer

OPERATOR'S STATION:

Modular Design ROPS/FOPS Cab, heat and air conditioning
standard.
Isolation Mounted (Conforms to SAE J1040, J231, ISO 3471,
ISO 3449)
Steel Roof
Left and Right Side Access Walk Through Cab
Slip-Resistant Steps and Ergonomically Located Handholds
(Conforms to SAE J185)
3-Way Tilt and telescopic Steering Console
Steering Wheel with Spinner
Seat, Deep Foam, Fabric, Mechanical Suspension for
Weight/Height, Fore-Aft Adjustment, Backrest Tilts and
Adjustable Arm Rests, 2 In. (51 mm) Seat Belt with Retractor
(Conforms to SAE J386)
Electronic Monitor System with Audible and Visual Warning:
Engine Oil Pressure
Engine Coolant Temperature
HST Transmission Oil Temperature
Indicator Lights:
Engine Air Filter
Fasten Seat Belt
Park Brake Actuated
Forward-Reverse Travel
I or II Speed Range
Fuel Gauge
Speedometer
Hourmeter
Turn Signal and Hazard Lights
High Beam Indicator
Floormat
Horn, Electric (Conforms to SAE J994, J1446)
Key Start Switch with Electric Fuel Shut-Off
Power Port
Interior Mounted Rearview Convex Mirror (Conforms to SAE
J985)
Two Exterior Convex Mirrors (Conforms to SAE J985)
Built-In Operator's Manual Storage Compartment and
Manual

Pre-wired for Beacon and Radio
Cab includes Radio Speakers and Antenna

LOADER:
Powered Attachment Coupler
Z-Bar Linkage
Three Function Hydraulics, with Joystick Pilot Control for Boom and Bucket and 3rd function electrohydraulic mini joystick built in
Boom Float
Return to Dig (Bucket Leveling) Feature
Loader Boom Service Lock (Conforms to SAE J38)

OVERALL VEHICLE:
Articulation Locking Pin (Conforms to SAE J276)
Oscillating Frame Articulation System
Front and Rear Fenders
Integral Loader Frame Lift & Tie Down Eyes
Integral Engine Frame Lift & Tie Down Eyes
Full Counterweight
Drawbar with Pin
Rear Bottom Guard
Environmental Fluid Drains
Vandal Protection Locking for:
Engine Enclosure
Operator Enclosure
Rear Engine Access Door
Fuel Fill
21.5 Gallon (80 L)
Fuel Tank
Reverse Warning Alarm (Conforms to SAE J994, J1446)
Refer to Service Administration Manual for Foam Filled or Solid Tire applications

OAGOT	324L - FOUR WHEEL DRIVE LOADER	1	\$127,000.00
-------	--------------------------------	---	--------------

OPERATOR'S STATION AND CONTROLS

	Seat		Basic Factory Options - Required
--	------	--	----------------------------------

2210	Standard Cloth Seat, Mid-Back, Mechanical Suspension		No Added Cost
------	--	--	---------------

2230	Deluxe Cloth Seat, Air Suspension, High-Back with Headrest, Heated, and Lumbar		\$2,306.00
------	--	--	------------

	Controls		Basic Factory Options - Required
--	----------	--	----------------------------------

2410	Standard Control Package		No Added Cost
------	--------------------------	--	---------------

Includes Rimpull Control and Inching Pedal.

2430	Attachment Assist (Creep Control & Throttle Lock) Includes Rimpull Control and Inching Pedal.	\$1,391.00
------	--	------------

ENGINE

Engine Basic Factory Options - Required

0924	Engine Yanmar 4TNV98CT 3.3 L 4 Cylinder Turbo-Charged 73 Gross HP (54 kW) 71 Net HP (52 kW) Meets EPA Final Tier 4 Emissions	\$4,537.00
------	---	------------

HYDRAULICS

Hydraulic System and Coupler Basic Factory Options - Required

2840	Three Function, Joystick w/FNR Control 1 lever controls boom and bucket, mini-EH thumb joystick proportionally controls auxiliary function. Includes third function lines to the coupler. Includes third function detent.	No Added Cost
------	--	---------------

2842	Three Function w/High Flow Option, Joystick w/FNR Control 1 lever controls boom and bucket, mini-EH thumb joystick proportionally controls auxiliary function. Includes third function lines to the coupler. Includes third function detent.	\$4,388.00
------	---	------------

28A1	Four Spool Valve (ISO Coupler)	\$3,500.00
------	--------------------------------	------------

Ride Control Basic Factory Options - Required

3000	Less Ride Control	No Added Cost
------	-------------------	---------------

3010	Ride Control	\$2,346.00
------	--------------	------------

WHEELS AND TIRES

Wheels and Tires Basic Factory Options - Required

4020	405/70R18 Firestone Duraforce This tire option gives total machine height of 9 ft 1 in (2774 mm)	\$1,219.00
4025	Mitas EM01 405/70R20 This tire option gives total machine height of 9 ft 2 in (2804 mm)	No Added Cost
4030	400/70R20 Michelin XMCL This tire option gives total machine height of 9 ft 2 in (2804 mm)	\$2,277.00
4035	400/70R20 Michelin Bibload L3 This tire option gives total machine height of 9 ft 2 in (2798 mm)	\$2,584.00
40F1	Nokian HakkaPeliitta TRI 400/70R20EM	\$2,679.00

LINKAGE

Linkage Basic Factory Options - Required

2010	Standard Z-bar linkage Height to Hinge Pin 132 in.	No Added Cost
2020	High Lift Z-bar linkage Height to Hinge Pin 149 in.	\$2,067.00

ELECTRICAL

Work Lights Basic Factory Options - Required

7120	Halogen Work Lights - Cab 2x Front, 2x Rear Halogen WorkLights			\$256.00
------	---	--	--	----------

7140	Less Work Lights (LED Kit Ready) Dealer will need to order and install BYT10522 (2xspot) and/or BYT10523 (2xflood)			No Added Cost
------	---	--	--	---------------

WORK TOOLS AND COUPLERS

Buckets and Couplers	Basic Factory Options - Required
----------------------	----------------------------------

8545	Less Coupler / Coupler Ready Dealer must order and install AT412608 Integrated Skid Steer Compatible Quik Tatch Coupler or BYT11760 ISO Integrated Coupler. Must also order a bucket if desired.			No Added Cost
------	---	--	--	---------------

8550	Less Bucket ISO Coupler included.			\$1,727.00
------	--------------------------------------	--	--	------------

Other Work Tools	Field Installed Attachments - Optional
------------------	--

9200	Pallet Forks for Standard ISO Coupler Frame width 48 in. (~1200 mm) Tines, 4 in. x 1.8 in. x 48 in. (100 x 45 x 1200 mm)			\$1,774.00
------	--	--	--	------------

9420	Front Windshield Guard Long Lead Time Item. For factory equivalent field installed kit please order the following: 244L/324L - BYT10741 344L - BYT11488			\$2,201.00
------	---	--	--	------------

Buckets & Pallet Forks	Field Installed Attachments - Optional
------------------------	--

BYT11466	Pallet Forks for ISO Coupler Class ITA 2B fork frame Frame width 49 in. (1.2m) Tires, 4 in. x 1.8 in. x 48 in. (100 x 45 x 1200 mm) Replace kit AT321215			\$2,440.00
----------	--	--	--	------------

BYT11584	2.6 cu. yd. (2.0 cu. m.) Light Material Bucket with Skid Shoes and Bolt-On Cutting Edge for ISO Coupler			\$4,636.00
----------	---	--	--	------------

94.5 in. (2.4 m) overall width
Includes 2 built-in lift loops
Requires BYT11996 Bucket Dump Speed Control Kit

MISCELLANEOUS

Miscellaneous Field Installed Attachments - Optional

AT390659	Electrical Attachment Control Kit Provides both 3 pin and 14 pin connectors and a control box.	\$530.00
----------	---	----------

BYT11293	Boom Height Kick-Out Boom Height Kick-out	\$709.00
----------	--	----------

BYT11225	Reversing Fan (Field Installed)	\$2,328.00
----------	---------------------------------	------------

BYT10744	JDLINK Ultimate Kit	\$999,999.00
----------	---------------------	--------------

Kits & Accessories Field Installed Attachments - Optional

AT357576	ISO Adapter to Quik Tatch Coupler Adapter for ISO Coupler to use Skid Steer Attachments AT357576 ISO Adapter to Quik Tatch Coupler - Adapter for Standard Coupler to use Compact Attachments - For 244L/324L Compact Loader machines not ordered Quik-Tatch™ ready from factory, also order: - AT218580 Relay (Quantity 2) - LW12241469 Quik-Tatch™ Rocker Switch - LW12834096 Quik-Tatch™ Extension Harness - LW12858760 Quik-Tatch™ Extension Harness (324L High Lift Machines) - 57M7146 30 A Fuse	\$1,584.00
----------	--	------------

BYT11996	Bucket Dump Speed Control Kit Kit includes spool stops for dump control valve to protect the linkage components from damage when using buckets weighing >1100 lbs (500 kg), including: 1.4 cu. yd. (1.1 cu. m.) General Purpose Bucket with Skid Shoes and Bolt-On Cutting Edge for Quik Tatch (AT413237) 2.1 cu. yd. (1.6 cu. m.) Light Material Bucket with Skid Shoes and Bolt-on Cutting Edge for Quik Tatch (AT413238) 2.1 cu. yd. (1.6 cu. m.) Light Material Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler (AT320636 & BYT11583) 2.6 cu. yd. (2.0 cu. m.) Light Material Bucket with Skid Shoes and Bolt-on Cutting Edge for ISO Coupler (AT320638 & BYT11584)	\$325.00
----------	--	----------

AT427686	Block Heater Kit	\$115.00
----------	------------------	----------

BYT10523	LED Worklight Kit (Flood)	\$196.00
----------	---------------------------	----------

BYT10522	LED Worklight Kit (Spot)	\$196.00
----------	--------------------------	----------

LW9069320	Beacon Light	\$206.00
-----------	--------------	----------

AT337325	Air Intake Pre-cleaner Kit	\$182.00
----------	----------------------------	----------

BYT11761	Creep Control and Throttle Lock Field Kit	\$1,443.00
----------	---	------------

	Field Installed Attachments - Optional
--	--

BYT11760	ISO COUPLER KIT	\$1,690.00
----------	-----------------	------------

BUCKETS

	Field Installed Attachments - Optional
--	--

AT413237	1.4 cu. yd. (1.1 cu. m.) General Purpose Bucket (Quik-Tatch) Includes Skid Shoes and Bolt-on Cutting Edge 86.6 in. (2.2 m) overall width Includes 2 built-in lift loops. Requires BYT11995 Bucket Dump Speed Control Kit	\$3,964.00
----------	---	------------

AT413238	2.1 cu. yd. (1.6 cu. m.) Light Material Bucket (Quik-Tatch) Includes Skid Shoes and Bolt-on Cutting Edge 94.5 in. (2.4 m) overall width Includes 2 built-in lift loops. Requires BYT11995 Bucket Dump Speed Control Kit	\$5,660.00
----------	--	------------

AT413236	1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket (Quik-Tatch) Includes Skid Shoes and Bolt-on Cutting Edge 74.8 in. (1.90 m) overall width Includes 2 built-in lift loops	\$2,484.00
----------	--	------------

BYT11583	2.1 cu. yd. (1.6 cu. m.) Light Material Bucket (Hook/Euro)	\$3,757.00
	Includes Skid Shoes and Bolt-on Cutting Edge	
	94.5 in. (2.4 m) overall width	
	Includes 2 built-in lift loops	
	Requires BYT11996 Bucket Dump Speed Control Kit	

BYT11581	1.0 cu. yd. (0.8 cu. m.) General Purpose Bucket (Hook/Euro)	\$2,063.00
	Includes Skid Shoes and Bolt-on Cutting Edge	
	74.8 in. (1.90 m) overall width	
	Includes 2 built-in lift loops	

BYT11582	1.4 cu. yd. (1.1 cu. m.) General Purpose Bucket (Hook/Euro)	\$2,870.00
	Includes Skid Shoes and Bolt-on Cutting Edge	
	86.6 in. (2.2 m) overall width	
	Includes 2 built-in lift loops	

FORK TINES

Fork Tines	Field Installed Attachments - Optional
------------	--

BYT10083	Class 3 Fork Frame with 48" Fork Tines (Quik-Tatch)	\$2,485.00
	Pallet Fork Frame Kit, 48" Forks Class ITA 3B Fork Frame Frame Width 60 in. (1.5m) Tines, 4-3/4 in. x 2in x 48in (120mm x 50mm x 1220mm) Overall Length Fork Frame + Forks: 57in (1445mm)	

BYT10092	Class 3 Fork Frame with 60" Fork Tines (Quik-Tatch)	\$2,726.00
	Pallet Fork Frame Kit, 60" Forks Class ITA 3B Fork Frame Frame Width 60 in. (1.5m) Tines, 4-1/2 in. x 2in x 60in (116mm x 50mm x 1524mm) Overall Length Fork Frame + Forks: 69in (1750mm)	

HYDRAULIC COUPLERS

Hydraulic Couplers	Field Installed Attachments - Optional
--------------------	--

AT412608	Skid Steer Compatible Quik-Tatch Coupler	\$1,500.00
----------	--	------------

BYT10470	Skid Steer Quik-Tatch Coupler Cover	\$131.00
----------	-------------------------------------	----------

Manufacturer's Suggested List Price shown. Retail prices may vary by dealer. Unless stated otherwise, taxes, freight, setup, delivery and other dealer specific charges not included in the pricing. Options/items noted with anything other than price will have additional costs. Pricing, availability, and specifications subject to change without notice. Special program pricing may be available on certain models. See dealer for details. Prices shown are in U.S. dollars and valid only in the U.S.