

450K CRAWLER DOZER



JOHN DEERE

01-Mar-2022

Code	Description	QTY	List Price (USD)
23A0T	<p>450K CRAWLER DOZER</p> <p>450K Standard Equipment</p> <p>ENGINE: John Deere PowerTech PWS 4.5L-meets FT4 / Stage IV emissions 80 SAE Net hp (60 kw) Turbocharged with Charge Air Cooler Isolation-Mounted Electronic Controlled Fuel Injection Electric Fuel Shut-off with Keyless Start Vertical Spin-on Engine Oil Filter Pressure system with full-flow spin-on filter and oil-to-water cooler Dual-stage dry tube with tangential unloader Enclosed Safety Fan Guard (Conforms to SAE J1308)</p> <p>ELECTRICAL: 24 Volt System 100 Amp Sealed Alternator Two Batteries with 190 Minute Reserve Capacity and 950 CCA Master Electric Disconnect Switch Bypass Start Safety Cover on Starter Positive Terminal Battery Covers Pre-wired for Work Lights, Underseat Heater and Low Pressure Indicator (2) High Intensity Grille Mounted and (2) Rear Work Light</p> <p>HYDRAULICS: 21 GPM (80 L/Min) Fixed Displacement Hydraulic Gear Pump Hydraulic/Hydrostatic Oil Reservoir with Sight Gauge Vertical Spin-on Hydraulic Oil Filter Three-function direct-acting T-bar joystick with pushbutton angle function "O" Ring Face Seal Connectors</p> <p>POWER TRAIN: Dual Path Hydrostatic Transmission Single-Lever Speed in Grip Steering with Counter Rotation and Horn Decelerator/Brake Pedal Automatic Power Management (w/ Manual Override) for Matching Ground Speed Infinite Ground Speed Selection Automatic Straight Ahead Tracking Adjustable Ground Speed When Shifting from Forward to Reverse Dynamic Braking (Anti-Free Wheel) Transmission Neutral Lock with Safety Start Switch Automatic Spring Applied, Hydraulically Released Parking Brake Hydraulic/Hydrostatic Oil Reservoir with Sight Gauge Vertical Spin-on Transmission Filter Oil to Air Transmission Oil Cooler Triple Reduction Final Drives with Wet Multi-Disk Brakes</p> <p>UNDERCARRIAGE: 57 In. (1450 mm) Standard Track Gauge w/ 6 Bottom Rollers Maximum life Undercarriage with 37 Link, SC2 Bushings and 16 in. (406mm) Moderate Service Shoes</p>	1	\$139,777.00

Sealed Track Chain
 Single Flange Rollers
 Full Length Smooth Surface Track Frame Covers
 Front and Rear Chain Guides
 Solid Sprocket with Bolt-on Sprocket Guards

OPERATOR STATION:

JDLink Ultimate with Three-Year Service Contract
 Modular Design ROPS/FOPS Canopy, Isolation Mounted (Conforms to SAE J1040)
 Left and Right Front Access
 Slip-Resistant Steps and Ergonomically Located Handholds (Conforms to SAE J185)
 Suspension Vinyl Seat:
 Height and Weight and Fore-Aft Adjustments (Conforms to SAE J899)
 Adjustable Leg Support
 3 In. (76 mm) Retractable Seat Belt (Conforms to SAE J386)
 Adjustable Footrests
 Adjustable Full Length Arm Rests
 Headliner and Floormat
 Electronic Monitor System with Audible and Visual Warning:
 Low Alternator Voltage
 Engine Oil Pressure
 Engine Coolant Temperature
 Engine RPM Indicator
 Hydraulic Oil Filter Restriction
 Transmission Oil Filter Restriction
 Transmission Oil Temperature
 Transmission Speed Indicator
 Engine Air Restriction Indicator
 Fasten Seat Belt/Park Brake Warning
 Fuel Gauge, Electric, Illuminated
 Hourmeter, Electric, Illuminated
 Transmission Oil Pressure Indicator
 Horn, Electric(Conforms to SAE J994, J1446)
 Built-in Operators Manual Storage Compartment and Manual
 Convex Rearview Mirror
 12 Volt Power Port

OVERALL VEHICLE:

One Piece Unitized Mainframe
 Front Tow Loop
 Reinforced Engine and Mid-frame Bottom Guards
 Integral Transmission Guard
 Perforated Engine Side Shields
 Heavy Duty Louvered Front Grille
 Less C-Frame and Blade
 Vandal Protection Locking for:
 Engine Access Door-Requires Padlock
 Side Tanks Access Doors- Require Padlocks
 Instrument Panel - Requires Padlock on ROPS Canopy
 Transmission & Hydraulic Reservoir - Requires Wrench
 Wide Mouth Fuel Filler Cap - Requires Padlock
 53 Gallon (202 Liter) Fuel Tank
 Reverse Warning Alarm with Guarding (Conforms to SAE J994, J1446)

23A0T	450K CRAWLER DOZER	1	\$139,777.00
-------	--------------------	---	--------------

ENGINE

	Engine	Basic Factory Options - Required
0940	John Deere PowerTech PWS 4.5L (274 cu. in.) 4 Cyl EPA FT4/EU Stage IV Compliant	\$1,092.00
	Fuel Filtration	Field Installed Attachments - Optional
9060	Severe-Duty Fuel Filter Do not order with Tier 2 engines as severe-duty fuel filtration and water separation is included. Available for Tier 3 engines only.	\$531.00
	Exhaust	Field Installed Attachments - Optional
9065	Chrome Exhaust	\$139.00
	Air Pre-Cleaner	Field Installed Attachments - Optional
9130	Engine Air Precleaner	\$501.00
	Miscellaneous	Field Installed Attachments - Optional
9070	Fluid Sampling Ports	\$292.00
9075	Quick Service Bank for Transmission, Hydraulic, Engine oil & Engine Coolant Fluid changes	\$900.00
	Coolant Heater	Field Installed Attachments - Optional
9530	Coolant Heater, Electric	\$144.00

Cold Start

Field Installed Attachments - Optional

AT211191	110 Volt Engine Coolant Heater (1000 Watt) Average installation, 0.5 hour	\$98.00
----------	--	---------

UNDERCARRIAGE

Track Frame

Basic Factory Options - Required

1075	Gauge Low Ground Pressure (LGP) Track Frame 1650 mm (65 In.) (6) bottom roller	\$2,032.00
------	--	------------

1045	1450 mm (57 In.) Gauge, Long-Track (LT) Frame (6 roller)	No Added Cost
------	--	---------------

1046	1450 mm (57 In.) Gauge, Standard Track Frame with Front Idler Guards (6 roller)	\$311.00
------	---	----------

1076	Gauge Low Ground Pressure (LGP) Track Frame with Front Idler Guards 1650 mm (65 In.) (6 bottom rollers)	\$2,342.00
------	---	------------

Track Shoes and Chain

Basic Factory Options - Required

Long Track Only

4550	40 Link with 16 in. (406 mm) Moderate Service Shoes	(\$5,885.00)
------	---	--------------

4650	Extended life Undercarriage with 40 Link-Extended Life SC2 Bushings and 16 in. (406mm) Moderate Service Shoes	(\$1,286.00)
------	--	--------------

4750	Maximum life Undercarriage with 37 Link-Extended Life SC2 Bushings and 16 in. (406mm) Moderate Service Shoes	No Added Cost
------	---	---------------

Low Ground Pressure Only

4570 Moderate Service Shoes (\$4,515.00)
40 Link with 24 in. (610 mm) Moderate Service Shoes

4770 Maximum life Undercarriage \$1,472.00
with 37 Link-Extended Life SC2 Bushings and 24 in. (610mm) Moderate Service Shoes

4670 Extended life Undercarriage (\$644.00)
with 40 Link-Extended Life SC2 Bushings and 24 in. (610 mm) Moderate Service Shoes

Extra Long Track or Low Ground Pressure Track

Sealed and Lubed Tracks except as noted.
Full Width and Closed Center Single Bar Grousers except as noted.

Chain Guides or Rock Guards

Basic Factory Options - Required

4825 Chain Guides No Added Cost
Front and Rear Chain Guides for XLT or LGP Track

4850 Full-Length Rock Guards \$1,390.00
Requires code 1055 or 1075
Recommended for slope and rocky conditions

BLADE

Dozer Blade

Basic Factory Options - Required

Blades or C-Frames are Not Included In Base Price. All C-Frame Options Include Remote C-Frame Pivot Grease Banks and Integrally Protected Hoses with Replaceable Hoses. All Blades have Manual adjustable blade pitch.

7015 Heavy Duty Inside All Hydraulic C-Frame Less Blade \$2,640.00
Includes lift cylinders with Cordura-covered hoses.
Includes tilt cylinder hoses with cable and Cordura covers.
Includes angle cylinders and hoses with steel and Cordura covers.
To convert an H-series blade to fit this unit, refer to instruction T205831
Does not include attaching pins and hardware. Refer to Installation instructions T177581 to attach non-Deere attachments.
When using root rake or front attachments, recommend % Frame Reinforcement Conversion Kit in the referral section.

7065	115 in. X 37.6 in. (2.92 m X .96 m) Blade with All Hydraulic Heavy Duty C-Frame (Blade NOT Installed) Blade shipped with machine but not installed Includes lift cylinders with Cordura covered hoses Includes tilt cylinder hoses with cable and Cordura covers Includes angle cylinders and hoses with steel and Cordura covers When using root rake or front attachments, recommend ☒ Frame Reinforcement Conversion Kit in the referral section	\$4,266.00
7075	Blade Requires Code 1075 or 1076, LGP Track Frame Blade shipped with machine but not installed Includes lift cylinders with Cordura covered hoses Includes tilt cylinder hoses with cable and Cordura covers Includes angle cylinders and hoses with steel and Cordura covers When using root rake or front attachments, recommend ☒ Frame Reinforcement Conversion Kit in the referral section 124 in. X 35.2 in. (3.15 m X .894 m) Blade with All Hydraulic Heavy Duty C-Frame (Blade NOT Installed)	\$4,451.00
7055	Blade with Inside All Hydraulic Heavy-Duty C-Frame Requires Code 1055 Standard Track only. Includes lift cylinders with Cordura-covered hoses Includes tilt cylinder hoses with cable and Cordura covers Includes angle cylinders and hoses with steel and Cordura covers When using root rake or front attachments, recommend C Frame Reinforcement Conversion Kit in the referral section 105 in. X 37.6 in.(2.67 m x .96 m)	\$4,044.00
7025	90 in. X 37.6 in. (2.29 m X .96 m) Blade with Inside All Hydraulic Standard C-Frame Requires Code 1045, Standard Track Will not cut overall track width when fully angled Includes lift cylinders with Cordura covered hoses Includes tilt cylinder hoses with cable and Cordura covers Includes angle cylinders and hoses with steel and Cordura covers Not recommended for front attachments mounted on blade	\$3,352.00
7045	97 in. x 37.6 in. (2.46 m X .96 m) Blade with Inside All Hydraulic Standard C-Frame Requires Code 1045, Standard Track Includes lift cylinders with Cordura covered hoses Includes tilt cylinder hoses with cable and Cordura covers Includes angle cylinders and hoses with steel and Cordura covers Not recommended for front attachments mounted on blade	\$3,422.00

HYDRAULICS

Hydraulics for Dozer Blade and Attachments

Basic Factory Options - Required

7725	3 Function Hydraulic Control Valve	No Added Cost
7750	3 Function Electro-Hydraulics (EH) for Power-Angle-Tilt (PAT) Grade Control Ready (EH) Hydraulics. Grade Control Recommendations: Trimble Ready Installation AT455318 for Cab Units or Trimble Ready Installation AT352426 for Canopy units or Topcon Ready Installation AT338879 for Cab and Canopy or Leica Ready Installation AT538592 for Cab and Canopy units.	\$3,631.00
7775	4 Function Hydraulic Control for Power-Angle-Tilt (PAT) 4th function (without Float). Does include circuit reliefs. Work port plugged.	\$960.00

Includes auxiliary rear plumbing for ripper.

7760	4 Function Electro-Hydraulics (EH) for Power-Angle-Tilt (PAT) and Rear Attachment w/ Rear Auxiliary Plumbing Grade Control Ready (EH) Hydraulics. Grade Control Recommendations: Trimble Ready Installation AT338871 for Cab Units or Trimble Ready Installation AT352426 for Canopy units or Topcon Ready Installation AT338879 for Cab and Canopy or Leica Ready Installation AT408427 for Cab and Canopy units.	\$5,071.00
------	---	------------

Hydraulic Pump	Basic Factory Options - Required
----------------	----------------------------------

7925	Hydraulic Pump Does not Includes external spline for mechanical drive winch or auxiliary pump. for use without Winch	No Added Cost
------	---	---------------

7975	Hydraulic Pump For use with Deere 4000S Winch (mechanical drive) Includes external spline for winch or auxiliary pump. for use w/ Winch	\$453.00
------	---	----------

Greases, Fuel, Oil, & Coolant	Basic Factory Options - Required
-------------------------------	----------------------------------

8010	Hydraulic And Hydrostatic Oil - Hydrau Standard Factory Fill. Provides All-Season Capability in Ambient Temperatures Ranging From -25C (-13F) to 50C (122F).	No Added Cost
------	--	---------------

8020	Hydraulic And Hydrostatic Oil - Hydrau XR Optional Factory Fill. Intended for Colder Climates with Extreme Cold Ambient Temperatures down to -40C (-40F) Provides All-Season Capability in Ambient Temperature Ranging from -40C to 40C (-40F to 104F).	\$578.00
------	--	----------

Hydraulic Valve	Field Installed Attachments - Optional
-----------------	--

9400	Hydraulic Track Adjuster Yoke Relief Valve Recommended for severe operating conditions (for example, forestry or rock). Replaces grease zerk in track adjusters.	\$214.00
------	--	----------

Winch	Field Installed Attachments - Optional
-------	--

9401	Model 4000 Standard Speed Winch - Power In, Free Spool Out	\$20,019.00
------	--	-------------

Requires Code 7975, 9450 or 9455.
Not for Use with Code 9187, 9345 or 9355.
Can not be used with Trimble or TopCon interface field Kits.

9402 Model 4000 Standard Speed Winch - Power In, Power Out \$22,592.00

Requires Code 7975, 9450 or 9455.
Not for Use with Code 9187, 9345 or 9355.
Cannot be used with Trimble or TopCon interface field Kits.

9403 Model 4000 Low Speed Winch - Power In, Power Out \$23,537.00

Requires Code 7975, 9450 or 9455.
Not for Use with Code 9187, 9345 or 9355.
Cannot be used with Trimble or TopCon interface field Kits.

9410 4000 Winch Fairlead, Four Roller \$4,135.00

For use with winch.
Requires Code 9401, 9402 or 9403.

9440 Extended Drawbar, 4000 Winch with Pin & Hardware \$1,123.00

For use with winch.
Requires Code 9401, 9402 or 9403.

Hydraulics

Field Installed Attachments - Optional

AT219741 Auxiliary Fifth Function Valve (without Float), Lever and Linkage \$482.00

Installation instructions T177350.
Average installation, 5 hours.
Converts four function control valve to five function.
Can be used with AT207568, Auxiliary Fourth Function Valve Section, to convert three function control valve to five function.
Work ports plugged, without circuit reliefs.

AT385271 Auxiliary Fourth Function Valve Section (without Float), Lever and Linkage \$482.00

Average installation, 5 hours.
Converts three function control valve to four function.
Work ports plugged without circuit reliefs.

AT451993 Electro-Hydraulics (EH) Auxiliary Hydraulic Function kit (FT4) \$1,374.00

Kit Will Convert Code 7750 3 hyd. functions to a 4 hyd.Functions.

AT451247 Rear Auxiliary Plumbing for use with 4000 Winch \$482.00

For Crawler Tractors with 3 function hydraulics.
Average installation, 1 hour.
For use with rear mounted or pull type equipment.
Includes two hoses and fittings from fourth or fifth function auxiliary valve to rear cover plate.
Not for use with Paccar winch.

AT451249 Rear Auxiliary Plumbing (FT4) \$122.00

For Crawler Tractors with 3 function hydraulics.
 Average installation, 1 hour.
 For use with rear mounted or pull type equipment.
 Includes two hoses and fittings from fourth or fifth function auxiliary valve to rear cover plate.

OPERATOR'S STATION AND CONTROLS

Operator's Station Basic Factory Options - Required

5025 Canopy No Added Cost
 Requires Code 5826, 5845, or 5855 Vinyl Seat.

5085 Cab with Roof Mounted Air Conditioner/Heater \$12,394.00
 Fresh air intake 18,000 BTU heater/defroster/ pressurizer with air pre-cleaner
 24,000 BTU air conditioner
 30,000 BTU under-seat heater
 AM/FM/WB Radio and Digital Clock
 Dome light
 Deluxe headliner
 Tinted safety glass all around
 Front windshield and doors with (3) single-speed wipers and washers
 100 amp alternator
 Pre-wired for Work Lights, rear wiper & washer
 Requires either code 5885 or 5890, Cloth Seat.

Seat Basic Factory Options - Required

5885 Air Suspension Comfort Control High Back Fabric Seat No Added Cost
 3 in. (76 mm) retractable seat belt.
 Adjustable armrests, backrest tilt, thigh support, lumbar, height, weight and fore-aft positioning
 Requires Cab.

5855 Air Suspension Comfort Control High Back Vinyl Seat No Added Cost
 3 in. (76 mm) retractable seat belt.
 Adjustable armrests, backrest tilt, thigh support, lumbar, height, weight and fore-aft positioning.
 Requires Code 5025.

5890 Heated Air Suspension Comfort Control High Back Fabric Seat \$662.00
 3 In. (76 mm) retractable seat belt.
 Adjustable armrests, backrest tilt, thigh support, lumbar, height, weight and fore-aft positioning.
 Restricted to cab use only.

Seat Field Installed Attachments - Optional

9125	Under- Seat Canopy Heater Requires Canopy 30,000 BTU	\$1,304.00
	Washer and Wiper	Field Installed Attachments - Optional
9380	Rear Wiper / Washer Requires Code 5085	\$684.00
	Lighting	Field Installed Attachments - Optional
9168	Deluxe LED Work Lights	\$343.00
	Radio	Field Installed Attachments - Optional
9501	Premium Radio with Bluetooth	\$1,120.00
	Miscellaneous	Field Installed Attachments - Optional
9355	Extended Rigid Drawbar with Pin Recommended for pull-type implements that require turning clearance - extends 11.3 In. (288 mm) to rear. Cannot be used with Code 9345, Retrieval Hitch Cannot be used with 4000S Winch Can be used with rear counterweight	\$529.00
	Rear Screen	Field Installed Attachments - Optional
9450	Rear Screen for Canopy (Grey) Requires code 5025 or 5035.	\$1,058.00
9455	Rear Screen Cab (Grey)	\$1,357.00

Requires code 5085 or 5095.

JOHN DEERE WORKSIGHT™

Machine Connectivity

Basic Factory Options - Required

Machine connectivity functions require cellular coverage. Usage of JDLink System requires customer's acceptance of the terms of the John Deere Telematics System Contract.

Option availability limited by specific geographical regions. Please refer to region specific price pages for appropriate ordering codes.

170K	JDLink™ Includes integrated cab wiring harness, antenna, and JDLink Modem (MTG). JDLink connectivity is enabled separately through the JDLink Website. Connectivity service is subject to country availability.	No Added Cost
------	---	---------------

170R	JDLink™ Satellite Includes integrated cab wiring harness, antenna, and JDLink Modem's (Cellular MTG & Satellite MTG). JDLink connectivity is enabled separately through the JDLink Website. Connectivity service is subject to country availability.	\$3,000.00
------	--	------------

Grade Control

Basic Factory Options - Required

2500	Topcon Grade Control Base Kit Installed Requires code 7750 or 7760. Factory installed and includes additional brackets and wiring harnesses that further enhances and simplifies the addition of a Topcon grade control system. This also enables the Topcon 3D-MC2 Grade Control Systems to be ordered.	\$7,497.00
------	--	------------

2575	No Topcon Grade Control Base Kit Installed Order for no blade control or Trimble or Leica Blade control field installations. Requires No Topcon Radio Installation code 2775	No Added Cost
------	--	---------------

Topcon Grade Control System

Basic Factory Options - Required

Kit includes the following equivalent parts from Topcon 3DMC2 system:

- Password, MC-R3 Full Auto
- OAF Bundle, MC-R3 3DMC2
- Kit, GX-55 GPS
- Kit, Common 3D Dozer GPS
- OEM, Antenna Config Kit
- Kit, OEM MC2 Sensor
- Assy, MC-R3 NO-OAF
- Full Assembly and Final Calibration On Site

2775	No Topcon Radio Installation	No Added Cost
------	------------------------------	---------------

Grade Control Field Installed Attachments - Optional

9700	Slope Control Slope Control automatically controls the cross slope and/or mainfall angle without the need for additional equipment (e.g. GNSS, laser reference, etc.). An upgraded 7" color LCD displays grade information and replaces the standard primary vehicle display. Please note: SmartGrade is not available on 450K or 550K dozers.	\$6,400.00
------	--	------------

DESTINATION AND LANGUAGE

Operator's Manual and Decals Basic Factory Options - Required

2605	English Operator Manual	No Added Cost
2610	Spanish Operator Manual	No Added Cost
2615	French Operator Manual	No Added Cost
2630	Australian Operator Manual & Compliance Certificate	No Added Cost

FRAME

Grille Field Installed Attachments - Optional

9325	Grille Heavy gauge plate grille also protects lights Protects fittings on both ends of front hydraulic hoses Replaces heavy-duty grille Extreme-Duty Grille with Hose Protection	\$1,340.00
------	--	------------

RIPPER

Ripper Field Installed Attachments - Optional

9187 Heavy Duty Parallelogram Ripper with 5 Shank Pockets and (3) Shank/Teeth \$11,711.00
 Requires code 7760 or 7775 Hydraulics.
 Cannot be used with 9345 or 9355.

HITCHES

Hitches Field Installed Attachments - Optional

9345 Retrieval Hitch with Pin \$283.00
 Recommended for pull-type implements - drawbar extends 6.1 l. (155 mm) to rear
 Cannot be used with Code 9355, Extended Rigid Drawbar
 Cannot be used with 4000S Winch
 Can be used with rear counterweight

MISCELLANEOUS

Operator Environment Field Installed Attachments - Optional

BYT10774 LED Cab Light Field Kit \$331.00

Frame Attachment Field Installed Attachments - Optional

AT451797 Heavy Duty Parallelogram Ripper with 5 Shank Pockets and (3) Shank/Teeth \$13,366.00
 Requires 4 Function Hydraulics and Auxiliary Plumbing.

AT222827 Extended Drawbar, 4000 Winch with Pin and Hardware \$932.00
 For use with Winch Fairlead
 Average installation, 1 hour
 Requires 4000S Winch
 Extends 32 In. to rear

AT311768 C-Frame Tilt Clevis Kit \$391.00

AT310522 C-Frame Steps \$225.00
 For use on units S/N 106533 and below.
 Installation instructions T208092
 Average installation, 1.0 hour

AT451157 Front Counterweight, 94 kg. (207 lb.) \$539.00

Winches Field Installed Attachments - Optional

AT411565 Linkage and Controls for Power In/Power Out Winches \$447.00
 For use on 450K, 550K & 650K models only. Requires AT460040 and AT460042.

AT411564 Linkage and Controls for Power In/Free Spool Out Winches \$447.00
 For use on 450K, 550K & 650K models only. Requires AT460040 and AT460042.

AT460040 External lines with Accumulator for Power In/Power Out Winches on 450K, 550K and 650K Only \$1,167.00
 Requires AT460042 and AT4311564 or AT411565.
 450K: (S.N. 304771—)
 550K: (S.N. 305398—)
 650K: (S.N. 305399—)

AT460042 Mounting Bracket and Hardware for Model 4000S Winch on 450K, 550K and 650K Only \$1,444.00
 Requires AT460040 and AT411564 or AT411565. 450K: (S.N. 304771—) 550K: (S.N. 305398—) 650K: (S.N. 305399—)

Overall Vehicle Field Installed Attachments - Optional

T174346 Rear Counterweight, 330 Lb. (150 Kg) \$717.00

BYT10775 LED Grille Light Field Kit \$238.00

Grade Control Field Installed Attachments - Optional

AT438592 Leica Grade Control Interface Package, Paladin-Installed for Cab or Canopy \$7,316.00
 Requires code 7750 or 7760.

AT455318	Trimble Grade Control Interface Package, Paladin-Installed Requires code 7750 or 7760.	\$6,961.00
<p>G.R.Mfg. Field Installed Attachments - Optional</p> <p>G.R. Manufacturing, Inc. * Kits listed below must be ordered through John Deere. * F.O.B. Trussville, Alabama * All kits include installation instructions * All warranty, repair parts, technical support and assistance, and sales support and assistance will be the responsibility of G.R. Manufacturing, Inc., and will be handled directly between the Dealer and G.R. Manufacturing, Inc. G.R. Manufacturing, Inc. 4800 Commerce Drive Trussville, Alabama 35173 Phone: (800)841-8001 Fax: (205)655-8005</p>		
AT320934	Lift Cylinder Guards (FT4) Average installation, 1 hour. Bolt-on. Formed plates bolt to top of lift cylinders and protect the hydraulic hose and fittings.	\$307.00
AT343935	Brush Guard, Full Width, 90 - 97" Blade	\$1,096.00
AT343936	Brush Guard, Full Width, 105 in.(2667mm) Blade For J-Series crawler S/N 139433 and above.	\$1,258.00
AT343937	41" Center Brush Guard for the 450J, 550J, and 650J Fits blades up to 115" length. For J crawlers above S/N 139432, and all K's.	\$760.00
AT353099	Root Rake for 115 in. blade with S/N 139433 and above	\$5,630.00
AT343938	Heavy Duty Root Rake w/ Brush Guard, 98" For use with 97" and 105" blades For crawler S/N 139433 and above Root rake has integral guarding which prohibits use w/ blade equipped w/ brush guard	\$7,624.00
AT343939	Heavy Duty Root Rake w/ Brush Guard, 114" For use with 115" blades For crawler S/N 139433 and above Root rake has integral guarding which prohibits use w/ blade equipped w/ brush guard	\$7,930.00
AT364288	Brush Guard, Full Width for 115 in. X 37.6 in. (2.92 m X .96 m) Blade For J-Series crawler S/N 139433 and above.	\$1,346.00
AT369894	Heavy Duty 124 in.(3.15m) Root Rake for S/n above 139433 For 124 in blade crawlers with S/n 139433 and above.	\$7,972.00

AT369893	Standard Duty 124 in.(3.15m) Root Rake for S/n above 139433 For 124 in blade crawlers with S/n 139433 and above.	\$5,620.00
AT413011	Side Screens, Cab	\$1,726.00
AT413184	Rear Screen, Canopy	\$1,020.00
AT413012	Side Screens, Canopy	\$1,320.00
AT413183	Rear Screen, Cab	\$1,491.00
AT446908	Screens, Cab Guard for A/C Average installation, 1 hour. Bolt-on. Plate covers top, rear and sides of A/C module for complete protection in forestry applications. Requires cab rear screen. Cannot be ordered with SmartGrade	\$1,116.00
BYT10165	Limb Risers, Arched (Curved) – ROPS Canopy and Cab Tractors	\$2,360.00
BYT10166	Full Enclosure, Cab (FT4)	\$9,523.00
BYT10409	Full Enclosure, Canopy	\$7,380.00
BYT10412	Limb Risers, PTP	\$2,830.00
BYT10411	Front Enclosure, Cab Standard only Note: For SN 305399-- Cannot be ordered with SmartGrade	\$2,830.00
BYT10413	Tank Guard LGP (FT4)	\$2,480.00

PACCAR Winch Div Field Installed Attachments - Optional

Contact PACCAR for below Winch installation instructions
 (Carco Winch)
 800 E. Dallas, P.O. Box 547
 Broken Arrow, OK 74013-0547
 Phone: 918-251-8511
 www.paccarwinch.com

AT336215	3 Roller Fairlead Kit for Hydraulic Winch For use with PACCAR winch	\$4,003.00
----------	--	------------

Powertrain & Cooling Field Installed Attachments - Optional

AT451244	Quick Service Bank for Transmission, Hydraulic, Engine oil & Engine Coolant Fluid changes Remote Service Bank is inside engine compartment and includes Industry Standard Quick Disconnect Couplers.	\$732.00
----------	---	----------

Powertrain Field Installed Attachments - Optional

AT466342	Severe Duty Fuel Filter kit	\$362.00
----------	-----------------------------	----------

Guards Field Installed Attachments - Optional

BYT10770	Tank Guards, LT and XLT	\$2,480.00
----------	-------------------------	------------

Manufacturer's Suggested List Price shown. Retail prices may vary by dealer. Unless stated otherwise, taxes, freight, setup, delivery and other dealer specific charges not included in the pricing. Options/items noted with anything other than price will have additional costs. Pricing, availability, and specifications subject to change without notice. Special program pricing may be available on certain models. See dealer for details. Prices shown are in U.S. dollars and valid only in the U.S.