

**JOHN DEERE**

Current Date 06Jan2021

550K CRAWLER DOZER**550K Standard Equipment****ENGINE:**John Deere PowerTech PWS
4.5L meets FT4 / Stage IV
emissions

92 SAE Net hp (69 kw)

Turbocharged with Charge
Air Cooler

Isolation-Mounted

Electronic Controlled Fuel
InjectionElectric Fuel Shut-off with
Key Start SwitchVertical Spin-on Engine Oil
FilterVertical Spin-on Primary Fuel
Filter with Water SeparatorVertical Spin-on Final Fuel
FilterOil-to-Water Engine Oil
CoolerDual Safety Element Dry-
Type Air Cleaner with Built-in
Precleaner withEvacuator Valve
Above HoodPrescreener/Raincap
Eco ModeEnclosed Safety Fan Guard
(Conforms to SAE J1308)**COOLING SYSTEM:**Engine Driven Cooling Fan
Engine Coolant -34 Degree F

(-37 Degree C)

Coolant Surge Tank

10-Fin/in. Trash Resistant
Engine Coolant Radiator10-Fin/in. Hydrostatic Oil-to-
Air Cooler10-Fin/in. Air to Air Charge
Air CoolerEnclosed Safety Fan Guard
(Conforms to SAE J1308 -
ISO 3457)

Tilt Out Heavy-Duty

Louvered Front Grille and
Radiator with Hose

Blade Control

O Ring Face Seal Connectors

POWER TRAIN:

Dual Path Hydrostatic

Transmission

Variable displacement piston
pump and variable

displacement motor

combination for each track

Hydrostatic Transmission

Diagnostic Remote Test
PortsSingle-Lever Speed in Grip
Steering with Counter

Rotation and Horn

Decelerator/Brake Pedal

Automatic Power

Management (w/ Manual
Override) for Matching

Ground

Speed

Infinite Ground Speed

Selection

Automatic Straight-Ahead

Tracking

Adjustable Ground Speed

When Shifting from Forward
to ReverseDynamic Braking (Anti-Free
Wheel)Transmission Neutral Lock
with Safety Start SwitchAutomatic Spring-Applied,
Hydraulically-Released

Parking Brake

Independent Transmission

Oil Reservoir with Sight
Gauge

Vertical Spin-on

Transmission Filter

Oil-to-Air Transmission Oil
CoolerTriple Reduction Final Drives
with Wet Multi-Disk Brakes**UNDERCARRIAGE:**

61 In. (1549 mm) Standard

Adjustable Leg Support

3 In. (76 mm) Retractable
Seat Belt (Conforms to SAE
J386)

Adjustable Footrests

Adjustable Full-length Arm
Rests

Side Console Leg Cushions

Cup and Lunch Box Holder

Headliner and Floor Mat

Electronic Monitor System
with Audible and Visual

Warning:

Low Alternator Voltage

Engine Oil Pressure

Engine Coolant Temperature

Engine RPM Indicator

Hydraulic Oil Filter

Restriction

Transmission Oil Filter

Restriction

Transmission Oil

Temperature

Engine Air Restriction

Indicator

Fasten Seat Belt/Park Brake

Warning

Transmission Speed

Indicator

Fuel Gauge, Electric,

Illuminated

Hourmeter, Electric

Transmission Oil Pressure

Indicator

Horn, Electric

(Conforms to SAE J994,
J1446)Operators Manual Storage
Compartment and Manual

Convex Rearview Mirror

12 Volt Power Port

OVERALL VEHICLE:

One-Piece Unitized

Mainframe

Front Tow Loop (Bolt-on)

Reinforced Engine and Mid-

Protection	Track Gauge w/ 6 Bottom	frame Bottom Guards
ELECTRICAL:	Rollers	Integral Transmission Guard
24 Volt System	Maximum Life Undercarriage	Perforated Engine Side
100 Amp Alternator	with 37 Link, SC2 Bushings	Shields
Dual Batteries with 190	and 18 in.	Hinged Bottom Access
Minute Reserve Capacity and	(457mm) Moderate Service	Covers (Bolt-On)
950 CCA	Shoes	Less C-Frame and Blade
Master Electric Disconnect	Double Flange Rollers	Vandal Protection Locking
Switch	Full-Length, Smooth Surface	for:
Bypass Start Safety Cover	Track Frame Covers	Engine Access Door-Requires
on Starter	Front and Rear Chain Guides	Padlock
Positive Terminal Battery	Solid Sprockets with Bolt-on	Side Tanks Access Doors-
Covers	Sprocket Guards	Require Padlocks
Pre-wired for Work Lights,	OPERATOR STATION:	Wide Mouth Filler Cap -
Underseat Heater and Low	JDLink Ultimate Machine	Requires Padlock
Pressure Indicator	Monitoring System w/ 3-year	Environmental Drains
(2) Grille Mounted and (2)	Message Service	Instrument Panel Requires
Rear Mounted Lights w/ (2)	Modular Design ROPS/FOPS	Padlock on ROPS Canopy
reflectors	Canopy, Isolation-Mounted	Transmission & Hydraulic
HYDRAULICS:	(Conforms to SAE	Reservoirs
15 GPM (56.8 L/Min) Fixed	J1040)	Lockable Grease Gun and
Displacement Hydraulic Gear	Left and Right Front Access	Tool Storage in Right Access
Pump	Slip-Resistant Steps and	Door
Independent Hydraulic Oil	Ergonomically- Located	53.45 Gallon (202 Liter) Fuel
Reservoir with Sight Gauge	Handholds (Conforms to	Tank
Hydraulic Oil Cooler	SAE J185)	Ground level Fueling
Vertical Spin-on Hydraulic Oil	Suspension Vinyl Seat:	Reverse Warning Alarm with
Filter	Height and Weight and Fore-	Guarding (Conforms to SAE
Three-Function Hydraulic	Aft Adjustments (Conforms	J994, J1446)
Valve with Low Effort Single-	to SAE J899)	
Lever (T-Bar)		

Required - You must select one from each category

BASE MACHINE

Ex-Works Dubuque, Iowa, United States of America

As not all option codes have field kits, please review your order option codes and available kits prior to placing a machine order.

Description	Code	Price
550K CRAWLER DOZER	02G0T	\$136,433.00

ENGINE

Description	Code	Price
John Deere PowerTech	0940	\$2,362.00

PWS 4.5L (274 cu. in.) 4 Cyl EPA FT4/EU Stage IV Compliant

TRACK FRAME

Description	Code	Price
1549 mm (61 In.) Gauge, Standard Track Frame (6 Roller)	1053	(\$1,231.00)

1549 mm (61 In.) Gauge, Standard Track Frame with Front Idler Guards (6 Roller)	1054	(\$978.00)
1753 mm (69 In.) Gauge Low Ground Pressure (LGP) Track Frame (6 Roller)	1073	\$3,420.00
1753 mm (69 In.) Gauge Low Ground Pressure (LGP) Track Frame With Front Idler Guards (6 Roller)	1074	\$3,932.00

TRACK SHOES AND CHAIN

Description	Code	Price
<u>Low Ground Pressure Only</u>		
Moderate Service Shoes	4570	(\$5,905.00)
40 Link with 24 in. (610 mm) Moderate Service Shoes		
Maximum life Undercarriage	4770	\$883.00
Extended life Undercarriage	4670	(\$1,197.00)
with 40 Link-Extended Life SC2 Bushings and 24 in. (610 mm) Moderate Service Shoes		
<u>Extra Long Track or Low Ground Pressure Track</u>		
Sealed and Lubed Tracks except as noted. Full Width and Closed Center Single Bar Grousers except as noted.		
40 Link with 18 in. (457 mm) Moderate Service Shoes	4560	(\$6,749.00)
Maximum life Undercarriage with 37-Link, Extended-Life SC2 Bushings and 18 in. (457mm) Moderate Service Shoes	4760	No Added Cost
Extended life Undercarriage with 40-Link, Extended-Life SC2 Bushings and 18 in. (450mm) Moderate Service Shoes	4660	(\$1,848.00)

CHAIN GUIDES OR ROCK GUARDS

Description	Code	Price
Chain Guides	4825	No Added Cost
Front and Rear Chain Guides for XLT or LGP Track		
Full-Length Rock Guards	4850	\$1,390.00
Requires code 1053 or 1073. Recommended for slope and rocky conditions.		

DOZER BLADE

Blades or C-Frames are Not Included In Base Price. All C-Frame Options Include Remote C-Frame Pivot Grease Banks and Integrally Protected Hoses with Replaceable Hoses. All Blades have Manual adjustable blade pitch.

Description	Code	Price
Heavy Duty Inside All Hydraulic C-Frame Less Blade	7015	\$10,405.00

Includes lift cylinders with Cordura-covered hoses.
Includes tilt cylinder hoses with cable and Cordura covers.
Includes angle cylinders and hoses with steel and Cordura covers.
To convert an H-series blade to fit this unit, refer to instruction T205831
Does not include attaching pins and hardware. Refer to Installation instructions T177581 to attach non-Deere attachments.
When using root rake or front attachments, recommend C Frame Reinforcement Conversion Kit in the referral section.

115 in. X 37.6 in. (2.92 m X .96 m) Blade with All Hydraulic Heavy Duty C-Frame (Blade NOT Installed)	7065	\$15,351.00
---	------	-------------

Blade shipped with machine but not installed
Includes lift cylinders with Cordura covered hoses
Includes tilt cylinder hoses with cable and Cordura covers
Includes angle cylinders and hoses with steel and Cordura covers
When using root rake or front attachments, recommend C Frame Reinforcement Conversion Kit in the referral section

Blade	7075	\$15,813.00
-------	------	-------------

124 in. X 35.2 in. (3.15 m X .894 m) Blade with All Hydraulic Heavy Duty C-Frame (Blade NOT Installed)
Requires Code 1073, LGP Track Frame. Blade shipped with machine but not installed. Includes lift cylinders with Cordura covered hoses. Includes tilt cylinder hoses with cable and Cordura covers. Includes angle cylinders and hoses with steel and Cordura covers. When using root rake or front attachments, recommend C Frame Reinforcement Conversion Kit in the referral section.

Blade with Inside All Hydraulic Heavy-Duty C-Frame	7055	\$15,009.00
--	------	-------------

105 in. X 37.6 in.(2.67 m x .96 m)
Requires Code 1053 Standard Track only. Includes lift cylinders with Cordura-covered hoses. Includes tilt cylinder hoses with cable and Cordura covers. Includes angle cylinders and hoses with steel and Cordura covers.
When using root rake or front attachments, recommend C Frame Reinforcement Conversion Kit in the referral section.

HYDRAULICS FOR DOZER BLADE AND ATTACHMENTS

Description	Code	Price
3 Function Hydraulic Control Valve	7725	No Added Cost

3 Function Electro-Hydraulics (EH) for Power-Angle-Tilt (PAT)	7750	\$3,631.00
---	------	------------

Grade Control Ready (EH) Hydraulics.
Grade Control Recommendations:
Topcon Ready Installation -Sales Code 2500.
Trimble Ready Installation AT455318.
Leica Ready Installation AT438592.

4 Function Hydraulic Control for Power-Angle-Tilt (PAT)	7775	\$960.00
---	------	----------

4th function (without Float).
Does include circuit reliefs.
Work port plugged.
Includes auxiliary rear plumbing for ripper.

4 Function Electro-Hydraulics (EH) for Power-Angle-Tilt (PAT) and Rear Attachment w/ Rear Auxiliary Plumbing	7760	\$5,071.00
--	------	------------

Grade Control Ready (EH) Hydraulics
Grade Control Recommendations:
Topcon Ready Installation - Sales Code 2500.
Trimble Ready Installation AT455318.
Leica Ready Installation AT438592.

HYDRAULIC PUMP

Description	Code	Price
Hydraulic Pump	7925	No Added Cost

for use without Winch
Does not Includes external spline for mechanical drive winch or auxiliary pump.

Hydraulic Pump	7975	\$453.00
----------------	------	----------

for use w/ Winch
For use with Deere 4000S Winch (mechanical drive)
Includes external spline for winch or auxiliary pump.

GREASES, FUEL, OIL, & COOLANT

Description	Code	Price
Hydraulic And Hydrostatic Oil - Hydrau	8010	No Added Cost

Standard Factory Fill.
Provides All-Season Capability in Ambient Temperatures Ranging From
-25C (-13F) to 50C (122F).

Hydraulic And Hydrostatic Oil - Hydrau XR	8020	\$578.00
---	------	----------

Optional Factory Fill.
Intended for Colder Climates with Extreme Cold Ambient Temperatures
down to -40C (-40F)
Provides All-Season Capability in Ambient Temperature Ranging from
-40C to 40C (-40F to 104F).

OPERATOR'S STATION

Description	Code	Price
Canopy	5025	No Added Cost

Requires Code 5826, 5845, or 5855 Vinyl Seat.

Cab with Roof Mounted Air Conditioner/Heater	5085	\$15,320.00
--	------	-------------

Fresh air intake 18,000 BTU heater/defroster/ pressurizer with air pre-cleaner
24,000 BTU air conditioner
30,000 BTU under-seat heater
AM/FM/WB Radio and Digital Clock
Dome light
Deluxe headliner
Tinted safety glass all around
Front windshield and doors with (3) single-speed wipers and washers
100 amp alternator
Pre-wired for Work Lights, rear wiper & washer
Requires either code 5885 or 5890, Cloth Seat.

**SEAT**

Description	Code	Price
Air Suspension Comfort Control High Back Fabric Seat	5885	No Added Cost

3 in. (76 mm) retractable seat belt.
Adjustable armrests, backrest tilt, thigh support, lumbar, height, weight and fore-aft positioning
Requires Cab.

Air Suspension Comfort Control High Back Vinyl Seat	5855	No Added Cost
---	------	---------------

3 in. (76 mm) retractable seat belt.
Adjustable armrests, backrest tilt, thigh support, lumbar, height, weight and fore-aft positioning.
Requires Code 5025.

Heated Air Suspension Comfort Control High Back Fabric Seat	5890	\$662.00
---	------	----------

3 In. (76 mm) retractable seat belt.
Adjustable armrests, backrest tilt, thigh support, lumbar, height, weight and fore-aft positioning.
Restricted to cab use only.

**MACHINE CONNECTIVITY**

Machine connectivity functions require cellular coverage. Usage of JDLINK System requires customer's acceptance of the terms of the John Deere Telematics System Contract.

Option availability limited by specific geographical regions. Please refer to region specific price pages for appropriate ordering codes.

Description	Code	Price
JDLINK Ultimate 5 Year Subscription	170C	No Added Cost

Includes JDLINK hardware: integrated cab wiring harness, antenna, modular telematics gateway (MTG), and now includes all Ultimate Connectivity features Wireless Data Transfer (WDT) enabling automatic data transfer from TimberMatic and Waratah H16 Measuring Systems to TimberManager and MyJohnDeere, supporting TimberOffice 5 Software. Additionally, Ultimate now includes Limited Internet features supporting optional ForestSight Solutions such as advance mapping systems and Remote Display Access (RDA) features supported by TeamViewer applications. JDLINK utilizes cellular and satellite technology infrastructure that is outside the control of John Deere. Changes to that infrastructure may require customers to purchase compatible JDLINK hardware to restore functionality. Includes 5 year subscription. Annual subscription renewal required after 5 years for continued functionality. JDLINK customer account must be created to access JDLINK Ultimate data. Go to www.StellarSupport.com to renew or update JDLINK subscriptions. Use of this service, and all rights and obligations of John Deere and the Customer (as identified in the applicable agreement), are governed by the terms and conditions outlined in the applicable Services and Software agreements available at www.JohnDeere.com/Agreements. If these terms and conditions are not agreeable do not proceed and do not use the service.

JDLINK Ultimate Dual 5 Year Subscription	170J	\$1,936.00
--	------	------------

Includes JDLink hardware: integrated cab wiring harness, antenna, modular telematics gateway (MTG), and now includes all cellular dependent Ultimate Connectivity features Wireless Data Transfer (WDT) enabling automatic data transfer from TimberMatic and Waratah H16 Measuring Systems to TimberManager and MyJohnDeere, supporting TimberOffice 5 Software. Additionally, Ultimate Dual now includes Limited Internet features supporting optional ForestSight Solutions such as advance mapping systems and Remote Display Access (RDA) features supported by TeamViewer applications when cellular signal is available. JD Link Ultimate Dual works with the 4G LTE MTG to automatically transmit compressed summary data over a satellite network when a cellular network is not available. JDLink utilizes cellular and satellite technology infrastructure that is outside the control of John Deere. Changes to that infrastructure may require customers to purchase compatible JDLink hardware to restore functionality. Includes 5 year subscription. Annual subscription renewal required after 5 years for continued functionality. JDLink customer account must be created to access JDLink Ultimate data. Go to www.StellarSupport.com to renew or update JDLink subscriptions. Use of this service, and all rights and obligations of John Deere and the Customer (as identified in the applicable agreement), are governed by the terms and conditions outlined in the applicable Services and Software agreements available at www.JohnDeere.com/Agreements. If these terms and conditions are not agreeable do not proceed and do not use the service.

GRADE CONTROL

Description	Code	Price
Topcon Grade Control Base Kit Installed	2500	\$7,497.00

Requires code 7750 or 7760.
Factory installed and includes additional brackets and wiring harnesses that further enhances and simplifies the addition of a Topcon grade control system. This also enables the Topcon 3D-MC2 Grade Control Systems to be ordered.

No Topcon Grade Control Base Kit Installed	2575	No Added Cost
--	------	---------------

Order for no blade control or Trimble or Leica Blade control field installations.
Requires No Topcon Radio Installation code 2775

TOPCON GRADE CONTROL SYSTEM

Kit includes the following equivalent parts from Topcon 3DMC2 system:

Password, MC-R3 Full Auto
OAF Bundle, MC-R3 3DMC2
Kit, GX-55 GPS
Kit, Common 3D Dozer GPS
OEM, Antenna Config Kit
Kit, OEM MC2 Sensor
Assy, MC-R3 NO-OAF
Full Assembly and Final Calibration On Site

Description	Code	Price
No Topcon Radio Installation	2775	No Added Cost

OPERATOR'S MANUAL AND DECALS

Description	Code	Price
-------------	------	-------

English Operator Manual	2605	No Added Cost
Spanish Operator Manual	2610	No Added Cost
French Operator Manual	2615	No Added Cost
Australian Operator Manual & Compliance Certificate	2630	No Added Cost

Optional - Select as desired

FUEL FILTRATION

Description	Code	Price
Severe-Duty Fuel Filter	9060	\$531.00



EXHAUST

Description	Code	Price
Chrome Exhaust	9065	\$139.00



AIR PRE-CLEANER

Description	Code	Price
Engine Air Precleaner	9130	\$501.00



MISCELLANEOUS

Description	Code	Price
Fluid Sampling Ports	9070	\$292.00
Quick Service Bank for Transmission, Hydraulic, Engine oil & Engine Coolant Fluid changes	9075	\$900.00



COOLANT HEATER

Description	Code	Price
Coolant Heater, Electric	9530	\$144.00



HYDRAULIC VALVE

Description	Code	Price
Hydraulic Track Adjuster Yoke Relief Valve	9400	No Added Cost

Recommended for severe operating conditions (for example, forestry or rock).
Replaces grease zerk in track adjusters.



WINCH

Description	Code	Price
Model 4000 Standard Speed Winch - Power In, Free Spool Out	9401	\$19,065.00

Requires Code 7975, 9450 or 9455.
Not for Use with Code 9187, 9345 or 9355.
Can not be used with Trimble or TopCon interface field Kits.

Model 4000 Standard Speed Winch - Power In, Power Out 9402 \$21,516.00

Requires Code 7975, 9450 or 9455.
 Not for Use with Code 9187, 9345 or 9355.
 Cannot be used with Trimble or TopCon interface field Kits.

Model 4000 Low Speed Winch - Power In, Power Out 9403 \$22,416.00

Requires Code 7975, 9450 or 9455.
 Not for Use with Code 9187, 9345 or 9355.
 Cannot be used with Trimble or TopCon interface field Kits.

4000 Winch Fairlead, Four Roller 9410 \$3,938.00

For use with winch.
 Requires Code 9401, 9402 or 9403.

Extended Drawbar, 4000 Winch with Pin & Hardware 9440 \$1,069.00

For use with winch.
 Requires Code 9401, 9402 or 9403.

SEAT

Description	Code	Price
Under- Seat Canopy Heater	9125	\$1,304.00

Requires Canopy
 30,000 BTU

WASHER AND WIPER

Description	Code	Price
Rear Wiper / Washer	9380	\$684.00

Requires Code 5085

LIGHTING

Description	Code	Price
Deluxe LED Work Lights	9168	\$343.00

RADIO

Description	Code	Price
Premium Radio with Bluetooth	9501	\$1,120.00

MISCELLANEOUS

Description	Code	Price
Extended Rigid Drawbar with Pin	9355	\$503.00

Recommended for pull-type implements that require turning clearance -
 extends 11.3 In. (288 mm) to rear.
 Cannot be used with Code 9345, Retrieval Hitch
 Cannot be used with 4000S Winch
 Can be used with rear counterweight

▼ REAR SCREEN

Description	Code	Price
Rear Screen for Canopy (Grey)	9450	\$1,058.00

Requires code 5025.

Rear Screen Cab (Grey)	9455	\$1,357.00
------------------------	------	------------

Requires code 5085.

▼ GRILLE

Description	Code	Price
Grille	9325	\$1,276.00

Extreme-Duty Grille with Hose Protection
Heavy gauge plate grille also protects lights
Protects fittings on both ends of front hydraulic hoses
Replaces heavy-duty grille

▼ RIPPER

Description	Code	Price
Heavy Duty Parallelogram Ripper with 5 Shank Pockets and (3) Shank/Teeth	9187	\$11,153.00

Requires code 7760 or 7775 Hydraulics.
Cannot be used with 9345 or 9355.

▼ HITCHES

Description	Code	Price
Retrieval Hitch with Pin	9345	\$269.00

Recommended for pull-type implements - drawbar extends 6.1 in. (155 mm) to rear.
Not For Use With Codes 9187 or 9355.
Cannot be used with 4000S Winch.
Can be used with rear counterweight.

▼ RUST PROTECTION

Description	Code	Price
Non-Export Rust Preventive Coating	9909	\$151.00

Coating protects exposed unpainted surfaces from road salt during shipment.

▼ ATTACHMENTS FOR FIELD CONVERSION

Description	Code	Price
Cold Start		
110 Volt Engine Coolant Heater (1000 Watt)	AT211191	\$98.00

Average installation, 0.5 hour

Frame Attachment

C-Frame Steps	AT310522	\$214.00
For use on units S/N 106533 and below. Installation instructions T208092 Average installation, 1.0 hour		
C-Frame Tilt Clevis Kit	AT311768	\$372.00
Extended Drawbar, 4000 Winch with Pin and Hardware	AT222827	\$887.00
For use with Winch Fairlead Average installation, 1 hour Requires 4000S Winch Extends 32 In. to rear		
Front Counterweight, 94 kg. (207 lb.)	AT451157	\$513.00
Heavy Duty Parallelogram Ripper with 5 Shank Pockets and (3) Shank/Teeth	AT451797	\$12,492.00
Requires 4 Function Hydraulics and Auxiliary Plumbing.		
<u>G.R.Mfg.</u>		
41" Center Brush Guard for the 450J, 550J, and 650J	AT343937	\$714.00
Fits blades up to 115" length. For J crawlers above S/N 139432, and all K's.		
Brush Guard, Full Width for 115 in. X 37.6 in. (2.92 m X .96 m) Blade	AT364288	\$1,263.00
For J-Series crawler S/N 139433 and above.		
Brush Guard, Full Width, 105 in.(2667mm) Blade	AT343936	\$1,263.00
For J-Series crawler S/N 139433 and above.		
Brush Guard, Full Width, 90 - 97" Blade	AT343935	\$1,023.00
Front Enclosure, Cab	BYT10411	\$2,298.00
Standard only Note: For SN 305398--		
Full Enclosure, Cab (FT4)	BYT10166	\$7,756.00
Includes Arched Limb Riser, Side Screens, Rear Screen, Doors, Front Screen & AC Condensor Guard. Not for use with SmartGrade. 550K: (S.N. 305398—)		
Full Enclosure, Canopy	BYT10409	\$6,457.00
Note: For SN 305398--		
Heavy Duty 124 in.(3.15m) Root Rake for S/n above 139433	AT369894	\$5,937.00
For 124 in blade crawlers with S/n 139433 and above.		

John Deere - 2021 Price List	Educational Services Commission of New Jersey NJ State Approved Co-op #65MCESCCPS	Grounds Equipment - Bid #ESCNJ 18/19-25
Heavy Duty Root Rake w/ Brush Guard, 114"	AT343939	\$6,072.00
For use with 115" blades For crawler S/N 139433 and above Root rake has integral guarding which prohibits use w/ blade equipped w/ brush guard		
Heavy Duty Root Rake w/ Brush Guard, 98"	AT343938	\$5,751.00
For use with 97" and 105" blades For crawler S/N 139433 and above Root rake has integral guarding which prohibits use w/ blade equipped w/ brush guard		
Lift Cylinder Guards (FT4)	AT320934	\$265.00
Average installation, 1 hour. Bolt-on. Formed plates bolt to top of lift cylinders and protect the hydraulic hose and fittings.		
Limb Risers, Arched (Curved) – ROPS Canopy and Cab Tractors	BYT10165	\$1,955.00
550K: (S.N. 305398—)		
Limb Risers, PTP	BYT10412	\$2,444.00
Note: For SN 305398--		
Point to Point Limb Riser (GR#705561)	AT435076	\$2,263.00
Rear Screen, Cab	AT413183	\$1,221.00
Rear Screen, Canopy	AT413184	\$952.00
Root Rake for 115 in. blade with S/N 139433 and above	AT353099	\$4,170.00
Screens, Cab Guard for A/C	AT446908	\$939.00
Average installation, 1 hour. Bolt-on. Plate covers top, rear and sides of A/C module for complete protection in forestry applications. Requires cab rear screen.		
Side Screens, Cab	AT413011	\$1,346.00
Side Screens, Canopy	AT413012	\$1,257.00
Standard Duty 124 in.(3.15m) Root Rake for S/n above 139433	AT369893	\$4,333.00
For 124 in blade crawlers with S/n 139433 and above.		
Tank Guard LGP (FT4)	BYT10413	\$2,482.00
For units with S/N 305398 and above.		
<u>Grade Control</u>		

Leica Grade Control Interface Package, Paladin-Installed for Cab or Canopy AT438592 \$7,316.00

Requires code 7750 or 7760.

Trimble Grade Control Interface Package, Paladin-Installed AT455318 \$6,961.00

Requires code 7750 or 7760.

Guards

Tank Guards, LT and XLT BYT10770 \$2,535.00

Hydraulics

Auxiliary Fifth Function Valve (without Float), Lever and Linkage AT219741 \$482.00

Installation instructions T177350.
 Average installation, 5 hours.
 Converts four function control valve to five function.
 Can be used with AT207568, Auxiliary Fourth Function Valve Section, to convert three function control valve to five function.
 Work ports plugged, without circuit reliefs.

Auxiliary Fourth Function Valve Section (without Float), Lever and Linkage AT385271 \$482.00

Average installation, 5 hours.
 Converts three function control valve to four function.
 Work ports plugged without circuit reliefs.

Electro-Hydraulics (EH) Auxiliary Hydraulic Function kit AT451993 \$1,374.00

Kit Will Convert Code 7750 3 hyd. functions to a 4 hyd.Functions.

Rear Auxiliary Plumbing AT451249 \$122.00

For Crawler Tractors with 3 function hydraulics.
 Average installation, 1 hour.
 For use with rear mounted or pull type equipment.
 Includes two hoses and fittings from fourth or fifth function auxiliary valve to rear cover plate.

Rear Auxiliary Plumbing for use with 4000 Winch AT451247 \$482.00

For Crawler Tractors with 3 function hydraulics.
 Average installation, 1 hour.
 For use with rear mounted or pull type equipment.
 Includes two hoses and fittings from fourth or fifth function auxiliary valve to rear cover plate.
 Not for use with Paccar winch.

Operator Environment

LED Cab Light Field Kit BYT10774 \$331.00

Universal XM-Tuner Installation Kit BYT11328 \$358.00

Includes hardware and brackets to add XM capability to radio.

Overall Vehicle

LED Grille Light Field Kit	BYT10775	\$238.00
Rear Counterweight, 330 Lb. (150 Kg)	T174346	\$682.00
<u>PACCAR Winch Div</u>		
3 Roller Fairlead Kit for Hydraulic Winch	AT336215	\$3,699.00
For use with PACCAR winch		
4th Roller Kit for Hydraulic Winch Fairlead	AT336216	\$934.00
Requires 3 Roller Fairlead Kit for Hydraulic Winch		
<u>Powertrain</u>		
Severe Duty Fuel Filter kit	AT466342	\$362.00
<u>Powertrain & Cooling</u>		
Quick Service Bank for Transmission, Hydraulic, Engine oil & Engine Coolant Fluid changes	AT451244	\$732.00
Remote Service Bank is inside engine compartment and includes Industry Standard Quick Disconnect Couplers.		
<u>Winches</u>		
External lines with Accumulator for Power In/Power Out Winches on 450K, 550K and 650K Only	AT460040	\$1,167.00
Requires AT460042 and AT4311564 or AT411565. 450K: (S.N. 304771—) 550K: (S.N. 305398—) 650K: (S.N. 305399—)		
External lines with Accumulator for Power In/Power Out Winches on 460J, 500J and 650J Only	AT182314	\$1,215.00
Fairlead, 4000 Winch Four Roller	AT175529	\$2,984.00
Average installation, 1 hour Bolt-on Can be used with Extended Winch Drawbar Requires 4000S Winch		
Linkage and Controls for Power In/Free Spool Out Winches	AT411564	\$447.00
For use on 450K, 550K & 650K models only. Requires AT460040 and AT460042.		
Linkage and Controls for Power In/Power Out Winches	AT411565	\$447.00
For use on 450K, 550K & 650K models only. Requires AT460040 and AT460042.		
Mounting Bracket and Hardware for Model 4000S Winch on 450K, 550K and 650K Only	AT460042	\$1,444.00
Requires AT460040 and AT411564 or AT411565. 450K: (S.N. 304771—) 550K: (S.N. 305398—) 650K: (S.N. 305399—)		

Copyright © Deere & Company. All Rights Reserved.

[About Our Site](#) | [Privacy and Data](#) | [Legal](#) | |