

CATERPILLAR MACHINE PRICE LIST

M314F

M314F HYDRAULIC WHEEL EXCAVATOR
GRENOBLE, FRANCE

Ship Weight
lbs

LIST PRICE
AT DEALER

Standard Equipment:

POWERTRAIN

- Engine:
- Cat C4.4, EPA/ARB Tier 4 final & EU
- Stage IV certified engine
- Altitude capability: 3000m/9842 ft
- Automatic starting aid

UNDERCARRIAGE

- Four wheel drive
- Heavy-duty axles with advanced disc brake system and travel motor with adjustable braking force
- Hydrostatic transmission, two speed remote greasing point
- Automatic lock mode for oscillating front axle & service brake
- Steps including tool boxes, left & right

HYDRAULICS

- Heavy lift mode
- Separate swing pump
- Load sensing hydraulic system

ELECTRICAL

- Alternator, 100 Ampere
- Roading lights (two front, two rear)
- Signal/warning horn
- Refueling pump

OPERATOR ENVIRONMENT

- Reinforced cab structure compliant with 2006/42/EC and tested according ISO 12117-2:2008
- Air conditioner heater & defroster
- 24 Volt lighter
- Bolt-on FOGS capability
- Bottom mounted, intermittent, parallel wiper and washer
- Full graphic and full color display
- Interior lighting with door switch
- Joysticks, pilot operated
- Left side console, tiltable, with lock-out for all controls
- FM radio incl. speakers
- Power supply, 12V-10A
- Steering column, adjustable angle & height
- Sunshade for windshield and skylight
- Cruise control system
- Pin code type engine start prevention
- RHS and rear view camera (incl.lights) displayed on additional cab monitor

OTHER STANDARD EQUIPMENT

- BLCV including overload warning device
- SLCV
- VA booms include FLCV
- Automatic swing brake

CATERPILLAR MACHINE PRICE LIST

M314F

M314F HYDRAULIC WHEEL EXCAVATOR
 GRENOBLE, FRANCE

Ship Weight
 lbs

LIST PRICE
 AT DEALER

**Lane 2 is reserved for the Base Order Management program.
 Please only use Lane 2 when placing orders that are part of the Base
 Order Management Program.**

512-3077 M314F WHL HEX AM-N DCA3 0 \$262,440
 LANE 1 - AVAILABLE FROM BALTIMORE PDC

Versatility for contractors and county work:
 Blade front, stabilizers rear, VA boom, 8'6" stick, high &
 medium pressure and pin grabber lines, tool control,
 joystick steering , 315 linkage compatible.

The following attachments MUST be selected from Lane 1
 Mandatory section : 0P9001 , 0G9240 .
 Undercarriage attachments are welded on and are therefore
 permanent part of the lower frame. It is not possible to
 add/remove or to change any outrigger or blade undercarriage

INCLUDES:

- 501-3131 M314F WHEEL EXCAVATOR
- 503-4940 BOOM, VA, A-LUBE
- 490-6087 STICK, 2.6M (8'6") A-LUBE
- 511-8480 UC BLADE R FRONT / OUT. REAR
- 474-7221 TIRES, MITAS 10.00-20 DUAL
- 489-2995 CAB, 70/30
- 374-5098 WIPER, 70/30
- 373-6030 SEAT COMFORT W/51 MM (W/2") SEAT BELT
- 123-4968 PIN, BUCKET, ADJ
- 438-7855 CONTROL, 1PC & VA
- 491-8396 LIGHTS, LED
- 383-3964 PEDAL, HPF/HAMMER
- 494-0903 SETTING, QC CTRL, PIN GRABBER
- 422-9762 BEACON, ROTATING, REMOVABLE
- 497-1005 JOYSTICK, 1-SLIDER
- 431-9304 CONTROL, JOYSTICK STEERING
- 491-1065 MIRROR, VA/MH
- 473-2982 DECALS, NORTH AMERICA (ANSI)
- 443-7981 COUNTERWEIGHT, 3300 KG (7275 LBS)
- 453-7125 COOLING SYSTEM, STANDARD
- 454-2154 STEPS, UC
- 505-5366 ALARM, BACK-UP
- 459-6004 PRODUCT LINK, CELLULAR PL641
- 492-8465 CONTROLLER, ELECTRONIC XL
- 463-3881 SPEED 37 KPH (23 MPH)
- 465-1383 BLCV, VA & OFFSET
- 465-1387 HYDRAULIC OIL, MINERAL
- 503-4005 JOYSTICK PATTERN, CHANGEABLE

NOTE: Please refer to the Lane 1 section to complete your order.

501-3131 M314F WHEEL EXCAVATOR 0 \$179,120
 LANE 2 - AVAILABLE FROM GRENOBLE FACTORY
 LANE 3 - AVAILABLE FROM GRENOBLE FACTORY
 AVAILABLE FOR: AM-N, EU, ISRAEL, ANZ-A, KOREA.

CATERPILLAR MACHINE PRICE LIST

M314F

M314F HYDRAULIC WHEEL EXCAVATOR
GRENOBLE, FRANCE

Ship Weight
lbs

LIST PRICE
AT DEALER

0G-0543

M314F MISCELLANEOUS MATERIAL 0
AVAILABLE FROM GRENOBLE FACTORY

NC

Only reference numbers that have the text
"ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a Misc order.

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	--------------------	-------------------------

NOTE

IF NO REFERENCE NUMBER IS LISTED, FTO CONFIGURATION IS NOT AVAILABLE

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	LANE 1 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-------------------------	-----------------	----------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS

LANE SELECTION

0P-9001	LANE 1 ORDER 0 ONLY FOR USE WITH: Distribution Center Arrangements (DCA) from PDC	NC
---------	---	-----------

EXPORT PACKING

0G-9240	COMPLETE STORAGE PROTECTION 0 Includes CILIX and foam protection on all cylinders Machines from the factory have been sprayed with Fluid Film TM. This product is added for corrosion protection while shipping and for extended storage periods. This product will need to be power washed with soapy water prior to shipment to the customer. Cilix and foam protection on all cylinders are also included in this storage protection procedure. Includes operator protections in cab Required for: Shipping by sea from Grenoble France Recommended for: all type of long distance shipment	\$383 NET
---------	---	------------------

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER	0	NC

REGIONAL PACKAGES

ENGINE

L	583-6716	ENGINE	0	NC
		ONLY FOR USE WITH: AM-N, AUSTRALIA, KOREA Dealers		

BOOMS, STICKS, AND LINKAGES

BOOM ARRANGEMENTS

Arrangements for standard sticks

L	503-4075	BOOM, 1PC, A-LUBE	0	\$35,150
		Includes: Cab controlled Automatic Lubrication System for front linkage and swing bearing. High pressure 2-way tool control circuit boom lines. Medium pressure auxiliary hydraulic circuit boom lines. CW & Pin Grabber Quick coupler control boom lines. One piece boom 4.815M / 15' 10"		
		ONLY FOR USE WITH: LANE 3 ONLY CANNOT BE USED WITH: Drop nose stick 440-3173		
L	503-4940	BOOM, VA, A-LUBE	0	\$37,170
		Includes: Cab controlled Automatic Lubrication System for front linkage and swing bearing. High pressure 2-way tool control circuit boom lines. Medium pressure auxiliary hydraulic circuit boom lines. CW & Pin Grabber Quick coupler control boom lines. Two piece boom 5.028M / 16' 6"		
		CANNOT BE USED WITH: Drop nose stick 440-3173		

Arrangements for drop nose sticks

STICK ARRANGEMENTS

L	490-6083	STICK, 7'5", A-LUBE	0	\$14,520
		Includes: Bucket linkage and cylinder. High pressure auxiliary hydraulic circuit stick lines. Medium pressure auxiliary hydraulic circuit stick lines. with CVC type quick disconnect couplings Quick coupler control stick lines. Automatic Lubrication System stick lines.		
		ONLY FOR USE WITH: Boom Arrangement for standard sticks		

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

BOOMS, STICKS, AND LINKAGES (CONT.)

STICK ARRANGEMENTS (Cont.)

L	490-6087	STICK, 8'6", A-LUBE 0		\$14,910
		Includes: Bucket linkage and cylinder. High pressure auxiliary hydraulic circuit stick lines. Medium pressure auxiliary hydraulic circuit stick lines. with CVC type quick disconnect couplings Quick coupler control stick lines. Automatic Lubrication System stick lines. ONLY FOR USE WITH: Boom Arrangement for standard sticks CANNOT BE USED WITH: Offset boom		

DROP NOSE STICKS WITHOUT BUCKET LINKAGE

SMARTBOOM & RIDE CONTROL

The Ride Control feature improves operator comfort by reducing machine bouncing when travelling. Smartboom eases operations and improves operator comfort. It is useful and recommended for Hammering, Rock-cleaning and smooth leveling.

Includes:
Boom lowering control device, reducing boom drift, and overload warning device, which signals a hydraulic overload with an acoustical warning in the cab.

Arrangements including Ride Control

L	475-5702	RIDE CONTROL, 1PC 0		\$4,355
		Arrangement including Ride Control & BLCV Note: Smartboom not included ONLY FOR USE WITH: One piece boom (1PC) LANE 3 ONLY CANNOT BE USED WITH: Drop nose stick		
L	475-5703	RIDE CONTROL, VA 0		\$5,500
		Arrangement including Ride Control & BLCV Note: Smartboom not included ONLY FOR USE WITH: Two piece boom (VA) CANNOT BE USED WITH: Drop nose stick		
L	475-5706	RC, 1PC INCL. SMARTBOOM 0		\$7,230
		Arrangement including Ride Control & BLCV Includes: Smartboom ONLY FOR USE WITH: One piece boom (1PC) LANE 3 ONLY CANNOT BE USED WITH: Drop nose stick		

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

BOOMS, STICKS, AND LINKAGES (CONT.)

SMARTBOOM & RIDE CONTROL (Cont.)

L	465-1385	RC, VA INCL. SMARTBOOM 0		\$8,350
		Arrangement including Ride Control & BLCV Includes: Smartboom ONLY FOR USE WITH: Two piece boom (VA) CANNOT BE USED WITH: Drop nose stick		

Arrangements without Ride Control

L	463-3913	BLCV, 1PC 0		NC
		Note: Smartboom not included without Ride Control ONLY FOR USE WITH: One piece boom (1PC) LANE 3 only		
L	465-1383	BLCV, VA & OFFSET 0		\$1,125
		Note: Smartboom not included without Ride Control ONLY FOR USE WITH: Two piece boom (VA & Offset)		

POWERTRAIN

TRAVEL SPEED

Includes:
48 degrees C / 118.8 degrees F cooling capability

L	463-3881	SPEED 23 MPH 0		NC
		Travel speed 37kph / 23mph CANNOT BE USED WITH: Cooling Package Fine Mesh Solid Rubber Tires		
L	463-3882	SPEED 12.4 MPH, FINE MESH 0		NC
		Travel speed 20kph / 12.4mph ONLY FOR USE WITH: Cooling Package Fine Mesh		
L	463-3884	SPEED 23 MPH, FINE MESH 0		NC
		Travel speed 37kph / 23mph ONLY FOR USE WITH: Cooling Package Fine Mesh CANNOT BE USED WITH: Solid Rubber Tires		

UNDERCARRIAGE

UNDERCARRIAGE ARRANGEMENTS

NOTE: Undercarriage attachments are welded on and are therefore a permanent part of the machine. It is not possible to add or change dozer blade or outrigger attachments.

Axle width 2.5M / 8' 2"

L	511-8479	UC BLADE R REAR 0		\$9,190
		Includes: Welded undercarriage No front attachment Radial blade rear remote greasing (width: 2.55M / 8' 4") Axle width 2.5M / 8' 2"		

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

UNDERCARRIAGE (CONT.)

UNDERCARRIAGE ARRANGEMENTS (Cont.)

L	503-3998	UC BLADE R REAR, TRAILER READY 0 Includes: Welded undercarriage No front attachment Radial blade rear remote greasing (width: 2.55M / 8' 4") Axle width 2.5M / 8' 2" Trailer preparation (bracket for trailer hook at blade , electrical & hydraulic ports at undercarriage)		\$16,190
L	511-8480	UC BLADE R FRONT / OUT. REAR 0 Includes: Welded undercarriage Outriggers rear Radial blade front remote greasing (width: 2.55M / 8' 4") Axle width 2.5M / 8' 2"		\$19,860
L	511-8481	UC OUT. FRONT / BLADE R REAR 0 Includes: Welded undercarriage Outriggers front Radial blade rear remote greasing (width: 2.55M / 8' 4") Axle width 2.5M / 8' 2" ONLY FOR USE WITH: LANE 3 ONLY		\$20,600
L	511-8482	UC OUT. FRONT & REAR. 0 Includes: Welded undercarriage Outriggers front Outriggers rear Axle width 2.5M / 8' 2"		\$23,560

STEPS & FENDERS

L	454-2154	STEPS, UC 0 Uppercarriage access steps with integrated toolbox. CANNOT BE USED WITH: 459-3893 GERMAN ROADING PACKAGE 30KPH		\$260
L	455-7171	STEPS, UC, INCL. FENDERS 0 Uppercarriage access steps with integrated toolbox. Includes: One set of four fenders reducing dirt and water spray from tires onto machine. REQUIRED BY: 459-3893 GERMAN ROADING PACKAGE 30KPH		\$2,745

TIRES

DUAL TIRES

L	474-7221	TIRES, MITAS 10.00-20 DUAL 0 MITAS NB38, BIAS (DIAGONAL/CROSS PLY), PR16. Spacer rings are included.		\$1,660
L	478-6660	TIRES, MITAS EM23 10.00-20 DUAL 0 MITAS EM23, BIAS (DIAGONAL/CROSS PLY), PR16. Higher resistance to puncture and tread wear due to higher filling of tread area. Special tread pattern for stony and hard terrain. Spacer rings are included.		\$2,860
L	558-3760	TIRES, TRELLEBORG 10.00-20 DUAL 0 TRELLEBORG T-900, PR16 Gripping allround tire with high resistance to puncture and tread wear Spacer rings are included		\$7,610

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

UNDERCARRIAGE (CONT.)

TIRES (Cont.)

L	474-7226	TIRES,SOLID RUB.10.00-20 DUAL 0 SOLID RUBBER Tires for industrial applications. Requires: 20kph / 12.4mph travel speed Spacer rings are included.		\$15,630
---	----------	---	--	----------

SINGLE TIRES

L	304-9736	TIRES,MICH.18R19.5 XF SINGLE 1,349 MICHELIN XF, 445/70R 19.5 Radial single tire with aggressive directional tread designed to deliver exceptional traction and performance.		\$6,140
---	----------	---	--	---------

HYDRAULICS

MEDIUM PRESSURE AUXILIARY HYDRAULIC CONTROLS

L	431-8614	CONTROL, MPF 0 Provides medium pressure circuit for tool rotation/tilt. ONLY FOR USE WITH: One piece boom (1PC) Two piece boom (VA)		\$1,300
L	431-9304	CONTROL, JOYSTICK STEERING 0 Provides medium pressure circuit for tool rotation/tilt. Enables steering of the machine while travelling in first gear by using the sliding switch on the right hand joystick. Includes: Auxiliary medium pressure control circuit ONLY FOR USE WITH: One piece boom (1PC) Two piece boom (VA)		\$3,445

OPERATOR ENVIRONMENT

CAB WINDSHIELD

L	486-0957	CAB, 1-PC 0 Fixed, one piece laminated glass windshield (10MM / 0.4", EN356 P5A) Laminated glass top window (10MM / 0.4", EN356 P5A). Tempered glass side & rear windows.		NC
L	489-2995	CAB, 70/30 0 Openable, 70/30 split, laminated glass windshield (Tempered glass lower window 4MM / 0.16" Laminated glass upper window 7MM / 0.28") Laminated glass top window and tempered glass side and rear windows.		NC

WINDSHIELD WIPER

L	374-5097	WIPER, 1-PC 0 ONLY FOR USE WITH: 1-PC windshield		NC
L	374-5098	WIPER, 70/30 0 ONLY FOR USE WITH: 70/30 windshield		NC

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

SEATS & SEAT-BELTS

Comfort Seat

L	373-6030	SEAT COMFORT W/2" SEAT BELT 0 The Comfort Seat features vertical air suspension (low-frequency), horizontal suspension, automatic weight adjustment, mechanical lumbar support, passive climate system, seat cushion length and angle adjustment and a seat heater Includes: 2"/51mm retractable seat belt		\$840
L	393-1386	SEAT COMFORT W/3" SEAT BELT 0 The Comfort Seat features vertical air suspension (low-frequency), horizontal suspension, automatic weight adjustment, mechanical lumbar support, passive climate system, seat cushion length and angle adjustment and a seat heater Includes: 3"/76mm retractable seat belt		\$840

Deluxe Seat

L	377-4501	SEAT DELUXE W/2" SEAT BELT 0 The Deluxe Seat features vertical air suspension (low-frequency), horizontal suspension, automatic height & weight adjustment, active climate system (two step heating & body sweat removal), premium microfibre seat fabric, pneumatic lumbar support, seat cushion length and angle adjustment and adjustable dampening. Includes: 2"/51mm retractable seat belt		\$2, 530
L	393-1387	SEAT DELUXE W/3" SEAT BELT 0 The Deluxe Seat features vertical air suspension (low-frequency), horizontal suspension, automatic height & weight adjustment, active climate system (two step heating & body sweat removal), premium microfibre seat fabric, pneumatic lumbar support, seat cushion length and angle adjustment and adjustable dampening. Includes: 3"/76mm retractable seat belt		\$2, 530

AUXILIARY HYDRAULIC PEDAL

L	261-3608	NO PEDAL 2 Floorboard cover required if HPF/Hammer pedal is not selected.		NC
L	383-3964	PEDAL, HPF/HAMMER 0 HPF/Hammer Pedal allows secondary operation of auxiliary high pressure control circuit in addition to the standard slider control on the right joystick. CANNOT BE USED WITH: Drop nose stick		\$1, 030

HYDRAYLIC JOYSTICK PATTERN

L	503-4005	JOYSTICK PATTERN, CHANGEABLE 0 Provides ability to change from the standard excavator joystick control pattern (SAE) for hydraulic functions to the backhoe joystick control pattern (ISO).		\$945
---	----------	---	--	--------------

HYDRAULIC JOYSTICK

L	497-1005	JOYSTICK, 1-SLIDER 0 Provides standard joysticks with 1 slider and 4 buttons.		NC
---	----------	---	--	-----------

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

HYDRAULIC JOYSTICK (Cont.)

L	488-1890	JOYSTICK, 2-SLIDER 0 Provides enhanced joysticks with 2 sliders and 5 buttons. REQUIRED BY: 5099875 CONTROL, 2ND HPF, 1PC 5099876 CONTROL, 2ND HPF, VA		\$1,265
---	----------	---	--	---------

CONTROLLERS

L	337-5820	CONTROLLER, ELECTRONIC. 0 Provides a control unit to activate and control electrical functions of hydraulic components. CANNOT BE USED WITH: Offset Boom, Ride Control, Joystick Steering 2nd High Pressure Control, Smartboom		NC
L	492-8465	CONTROLLER, ELECTRONIC XL. 0 Provides a control unit to activate and control electrical functions of hydraulic components. ONLY FOR USE WITH: Offset Boom, Ride Control, Joystick Steering 2nd High Pressure Control, Smartboom		NC

CONTROL MAIN VALVE

L	438-7855	CONTROL, 1PC & VA. 0 Implement Control Valve including 2-way tool control. ONLY FOR USE WITH: Boom Arrangements for standard sticks		NC
---	----------	---	--	----

TECHNOLOGY PRODUCTS

PRODUCT LINK COMMUNICATIONS

Product Link enables the remote transmission of information about the the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country. Please contact your Cat marketing representative with questions.

L	459-6004	PRODUCT LINK, CELLULAR PL641 0 Product Link Pro series PL641 uses UMTS and CDMA 3G cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		NC
L	459-6005	PRODUCT LINK, SATELLITE PL631 0 Product Link Pro series PL631 uses satellite network to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. For use in areas with poor or no cellular coverage.		\$439

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

SAFETY AND SECURITY

LIGHTING / CAB GUARD

Arrangements without Cab Guard

L	491-8396	LIGHTS, LED 0 Provides LED type cab working lights Includes cab rain visor. Without Cab Guard		NC
---	----------	--	--	-----------

Arrangements Including Cab Guard

L	491-8397	FOGS, LED 0 Provides LED type cab working lights Includes cab guards front and roof.		\$4,810
---	----------	---	--	----------------

MIRRORS

L	489-4672	MIRROR, ELECTRIC, VA/MH 0 Provides rearview mirrors on cab and on RH side of machine. Heated Mirrors adjustable from Cab		\$1,005
---	----------	---	--	----------------

L	489-4673	MIRROR, ELECTRIC, 1PC. 0 Provides rearview mirrors on cab and on RH side of machine. Heated Mirrors adjustable from Cab ONLY FOR USE WITH: Two piece booms (VA & Offset)		\$1,005
---	----------	--	--	----------------

L	491-1065	MIRROR, VA/MH 0 Provides rearview mirrors on cab and on RH side of machine. ONLY FOR USE WITH: Two piece booms (VA & Offset)		NC
---	----------	---	--	-----------

L	491-1066	MIRROR, 1PC. 0 Provides rearview mirrors on cab and on RH side of machine. ONLY FOR USE WITH: LANE 3 ONLY One piece booms		NC
---	----------	---	--	-----------

COOLING

COOLING PACKAGE

L	453-7125	COOLING SYSTEM, STANDARD 0		NC
---	----------	---	--	-----------

L	463-7086	COOLING SYSTEM, FINE MESH 0 Provides improved protection to the radiator, the ATAAC, the A/C condenser to prevent clogging, when working with the machine in dusty environments. Includes an additional engine air pre-cleaner.		\$920
---	----------	---	--	--------------

FRAMES

COUNTERWEIGHTS

L	443-7980	COUNTERWEIGHT, 6170 LBS 0 Standard Counterweight 2800KG / 6150LBS		\$570
---	----------	---	--	--------------

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FRAMES (CONT.)

COUNTERWEIGHTS (Cont.)

L	443-7981	COUNTERWEIGHT, 7275 LBS 0		\$665
		Heavy Counterweight 3300KG / 7250LBS		
		Recommended for use with: Two piece boom and blade only undercarriage arrangements		

FLUIDS

LUBRICATIONS

L	465-1387	HYDRAULIC OIL, MINERAL 0		NC
		Filling with Cat HYDO Advanced 10 oil		

INSTRUCTIONS

INTERNATIONAL INSTRUCTIONS

L	473-2982	DECALS, NORTH AMERICA (ANSI) 0		NC
---	----------	--	--	----

PACKING

EXPORT PACKING

	0G-9240	COMPLETE STORAGE PROTECTION 0		\$383 NET
		Includes CILIX and foam protection on all cylinders		
		Machines from the factory have been sprayed with Fluid Film TM.		
		This product is added for corrosion protection while shipping and for extended storage periods. This product will need to be power washed with soapy water prior to shipment to the customer.		
		Cilix and foam protection on all cylinders are also included in this storage protection procedure.		
		Includes operator protections in cab		
		Required for: Shipping by sea from Grenoble France		
		Recommended for: all type of long distance shipment		

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

HYDRAULICS

SECOND HIGH PRESSURE HYDRAULIC CIRCUIT CONTROL GROUP

Provides additional two way high or medium pressure function for worktools requiring additional hydraulic circuits for tilting or rotating, such as tilt-rotators.
Must order control and stick lines to complete auxiliary circuit.

REQUIRES 2- Slider Joystick

If CAT TILTROTATOR SUPPORT is selected ,2ND HPF Control will be optimized for usage with a Cat Tiltrotator.In this case only one way flow with minimized return line back pressure will be provided

L	509-9875	CONTROL, 2ND HPF, 1PC 0 Second high pressure control valve. ONLY FOR USE WITH: One piece boom & 2-slider joystick LANE 3 ONLY CANNOT BE USED WITH: Drop nose stick		\$5,960
L	509-9876	CONTROL, 2ND HPF, VA 0 ONLY FOR USE WITH: Two piece boom (VA) & 2-slider joystick CANNOT BE USED WITH: Drop nose stick		\$5,650

SECOND HIGH PRESSURE HYDRAULIC CIRCUIT STICK LINES

Must order stick lines to complete auxiliary circuit.

L	254-2615	LINES, 2ND HPF, 7'7" STICK 26 Second high pressure lines for stick 2.3M / 7' 7". REQUIRED BY: CONTROL 2ND HPF		\$745
L	254-2616	LINES, 2ND HPF, 8'6" STICK 29 Second high pressure lines for stick 2.6M / 8' 6". REQUIRED BY: CONTROL 2ND HPF		\$850

COUPLINGS CIRCUIT

P	176-6765	COUPLING, QUICK DISC MPF DC 2 "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" Provides a set of two adapters (CVC type coupling to internal thread M22 x 1.5) for stick lines medium pressure, side (bucket tilt)		\$340 NI
---	----------	--	--	----------

QUICK COUPLER CONTROL SETTINGS

L	494-0903	SETTING, QC CTRL, PIN GRABBER 0 Provides control strategy and pressure settings appropriate for Cat Pin Grabber quick coupler. CANNOT BE USED WITH: Cat Tiltrotator Support Drop nose stick, CW-type quick coupler		NC
---	----------	--	--	----

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

ELECTRICAL

ALARM

L	505-5366	ALARM, BACK-UP 0 REQUIRED BY: USA & Canada dealers Acoustical warning signal when moving the machine .		\$745
---	----------	--	--	-------

SAFETY AND SECURITY

BEACON

L	422-9762	BEACON, ROTATING, REMOVABLE 0 Orange beacon light with cable and magnet foot.		\$299
---	----------	--	--	-------

MACHINE SECURITY SYSTEM

L	422-9723	SECURITY SYSTEM, MACHINE 0 Advanced, programmable system to manage access to machine. Requires special Machine Security System keys. Machine shipped with system inactive but with two of these keys already programmed into system. Requires Caterpillar Service Tool Electronic Technician (ET) to activate and to program system for additional keys. Additional keys available through Parts Distribution.		\$1,430
---	----------	---	--	---------

BUCKETS

BUCKET RETENTION PINS

Note: PIN, BUCKET, TDP bucket retention pins are not compatible with pin-on CAT Tilt-Rotator System (TRS) models.
If the machine will be equipped with a pin-on TRS model please select PIN, BUCKET, ADJ.

P	123-4968	PIN, BUCKET, ADJ 68 "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" CANNOT BE USED WITH: Drop nose stick	68	\$367 \$367 NI
---	----------	--	----	-------------------

EXCAVATION BUCKETS (CW Coupler Buckets)

These buckets cannot be ordered with MISC Material Order. Dealers in AM-N can place miscellaneous bucket orders by consulting Cat Work Tools at 1-800- 255-2372 for bucket options, availability and appropriate ordering instructions.

FIELD INSTALLED ATTACHMENTS

Kits for field installation.
Please contact Product Group if further details are required.

CATERPILLAR MACHINE PRICE LIST

M314F

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FIELD INSTALLED ATTACHMENTS (CONT.)

L	473-7060	KIT, CAB GUARD, FOGS 0 Provides cab guards front and top for field installation. "ALSO AVAILABLE ON A MISCELLANEOUS ORDER"		\$4,960 NI
---	----------	---	--	-------------------

PACKING

Export Packing

	0G-3565	PACKING -SEA/TRUCK MISC.MATER.. 0 ONLY FOR USE WITH: only with Not installed Misc.Mater (Ni)		\$220 NET
	0G-3561	PACKING - SEA/TRUCK BH BUCKET 0 ONLY FOR USE WITH: Only with Not installed bucket (Ni)		\$287 NET