



October 4, 2019

PRODUCT AND PRICING BULLETIN

NEW HOLLAND BRAND PRODUCTS, U.S. NO. 19-53A

NEW HOLLAND AG DEALERS WITH MRT AGREEMENT

SUBJECT: WORKMASTER™ 55, 65, 75: PRICE & DATA PAGES EFFECTIVE 1/1/20

The agricultural industry is constantly evolving to meet the world's shifting needs. Here at New Holland, we're focused on matching pace with those changes to help you get the job done. Together, we can make our customers' jobs easier and raise industry standards along the way.



We have updated the WORKMASTER 55, 65, 75 product offering to include new Fast Pick Packages. These packages have been designed to provide you and your customer with just what they need in simple common configurations that make it easy for you and your customer to get exactly what is needed in a utility tractor. Please review these price and data pages to understand the contents of each of the below packages:

- Standard Cab Fast Pick
- Standard Cab HiVis Fast Pick
- Deluxe Cab Fast Pick
- Deluxe Cab HiVis Fast Pick
- Standard ROPS Fast Pick
- Deluxe ROPS Fast Pick

A la carte orders can still be placed, but will be at a premium price compared to the fast pick packages as each package will have a discount applied that will maintain the Model Year 2020 pricing that is effective October 1, 2019.

This bulletin and the price pages may be accessed via the Dealer Portal if you have the MRT agreement with New Holland. Log on to the Dealer Portal. With the "Wholegoods" button displayed, click on "Pricing," click on "Tractors," and then click on "WORKMASTER Series." The latest published items will appear at the top of the list. Please replace your current P&D pages with those attached to this bulletin.

Christine Chleboun
Director, Commercial Marketing
New Holland, North America

Dan Valen
Director, Product Marketing
New Holland, North America

Attachment

CNH Industrial America LLC
500 Diller Avenue, P.O. Box 1895
New Holland, PA 17557-0903
Telephone: (717) 355-1121
www.newholland.com/na



WORKMASTER™ Series Tractor Index

<u>EQUIPMENT DESCRIPTION</u>	<u>LATEST REVISION</u>	<u>PAGE NUMBER</u>
<u>Index</u>	01/01/20	1
<u>Models</u>		
WORKMASTER 55, 65, 75 STANDARD CAB FAST PICK	01/01/20	2
WORKMASTER 55, 65, 75 STANDARD CAB HAVIS FAST PICK	01/01/20	6
WORKMASTER 55, 65, 75 DELUXE CAB FAST PICK	01/01/20	10
WORKMASTER 55, 65, 75 DELUXE CAB HAVIS FAST PICK	01/01/20	15
WORKMASTER 75 STANDARD ROPS FAST PICK	01/01/20	20
WORKMASTER 75 DELUXE ROPS FAST PICK	01/01/20	24
WORKMASTER 55, 65, 75 WEST COAST FAST PICK	01/01/20	28
WORKMASTER 55, 65, 75 CAB A LA CARTE	01/01/20	32
WORKMASTER 75 ROPS A LA CARTE	01/01/20	38
WORKMASTER 55, 65, 75 Special Order	01/01/20	43
PARTS DIVISION SUPPLIED ACCESSORIES	01/01/20	45



**WORKMASTER 55-75 STANDARD CAB FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:

(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

HYDRAULIC SYSTEM:

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55-75 STANDARD CAB FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

CAB LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS
ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer style bucket attach
72" Bucket



**WORKMASTER 55-75 STANDARD CAB FAST PICK
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB	9040939P08	\$52,486.00
WORKMASTER 65 T4A	Cab	6,239 LB	9042944P46	\$55,057.00
WORKMASTER 75 T4A	Cab	6,239 LB	9044949P84	\$57,628.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

X0590XX	Standard Cab Fast Pick Standard Cab Fast Pick pricing includes: Cab with openable Black-Out panel 2 rear remotes 550LU NSL loader with SSL quick attach and 72" bucket Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Rear weights: 4 rear wheel weights OR NO rear wheel weights		(902028P00)	(\$2,600.00)
---------	---	--	-------------	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)		9000522P60	\$670.00



**WORKMASTER 55-75 STANDARD CAB FAST PICK
 US PRICE LIST**

REAR

SD_T4950 REAR WHEELS AND TIRES

	8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
	8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)		9000241P02	\$309.00

WEIGHTS

REAR

SD_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights Two weights per side (110 lbs each) = 440 lbs total		9000476P58	\$611.00
--	--------	---	--	------------	----------

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 55-75 STD CAB H1VIS FAST PIC
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab - HiVis panel
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

HYDRAULIC SYSTEM:

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55-75 STD CAB HIVIS FAST PIC
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

CAB LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS
ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, high visibility
panel, front wiper and washer, rear
wiper and washer, two doors with
locks, two external mirrors, hinged rear
window (opens completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer style bucket attach
72" Bucket



**WORKMASTER 55-75 STD CAB H1VIS FAST PIC
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB	9040939P08	\$52,486.00
WORKMASTER 65 T4A	Cab	6,239 LB	9042944P46	\$55,057.00
WORKMASTER 75 T4A	Cab	6,239 LB	9044949P84	\$57,628.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

X0592XX	Standard Cab HiVis Fast Pick Standard Cab HiVis Fast Pick pricing includes: Cab with openable Clear HiVis panel 2 rear remotes 550LU NSL loader with SSL quick attach and 72" bucket Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Rear weights: 4 rear wheel weights OR NO rear wheel weights		(901735P50)	(\$2,225.00)
---------	---	--	-------------	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)		9000522P60	\$670.00



**WORKMASTER 55-75 STD CAB HIVIS FAST PIC
 US PRICE LIST**

REAR

SD_T4950 REAR WHEELS AND TIRES

	8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
	8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)		9000241P02	\$309.00

WEIGHTS

REAR

SD_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights Two weights per side (110 lbs each) = 440 lbs total		9000476P58	\$611.00
--	--------	---	--	------------	----------

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 55-75 DELUXE CAB FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

HYDRAULIC SYSTEM:

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(3) Open Center Remote Valves with

Detent & Kickout on #2 & #3

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55-75 DELUXE CAB FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

CAB LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
4 x 110 lb Rear Wheel Weights
Toolbox

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS
ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

WARRANTY:

New Holland Standard Warranty Applies



**WORKMASTER 55-75 DELUXE CAB FAST PICK
US PRICE LIST**

Standard Equipment

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer or Euro style bucket attach
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 3,086 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 20.8"
Reach @ Ground Level: 79.9"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style bucket attach
72" Bucket



**WORKMASTER 55-75 DELUXE CAB FAST PICK
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB	9040939P08	\$52,486.00
WORKMASTER 65 T4A	Cab	6,239 LB	9042944P46	\$55,057.00
WORKMASTER 75 T4A	Cab	6,239 LB	9044949P84	\$57,628.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

X0591XX	Deluxe Cab Fast Pick Deluxe Cab Fast Pick pricing includes: Cab with openable Black-Out panel 3 rear remotes 4 rear wheel weights Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Loader: 550LU NSL loader with SSL quick attach and 72" bucket OR 555LU MSL loader with EURO quick attach and 72" bucket		(900925P08)	(\$1,186.00)
---------	--	--	-------------	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)		9000522P60	\$670.00



**WORKMASTER 55-75 DELUXE CAB FAST PICK
 US PRICE LIST**

REAR

SD_T4950 REAR WHEELS AND TIRES

	8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
	8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)		9000241P02	\$309.00

LOADER

LOADER

SD_T8110 LOADER BRACKETS

	344739	LOADER-NSL.2F.SSLWGG 550LU Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344742	LOADER-MSL-2F-EU-WGG 555LU Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000856P44	\$1,098.00

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab - HiVis panel
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

HYDRAULIC SYSTEM:

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(3) Open Center Remote Valves with

Detent & Kickout on #2 & #3

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

CAB LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
4 x 110 lb Rear Wheel Weights
Toolbox

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS

ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, high visibility
panel, front wiper and washer, rear
wiper and washer, two doors with
locks, two external mirrors, hinged rear
window (opens completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

WARRANTY:

New Holland Standard Warranty Applies



**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK
US PRICE LIST**

Standard Equipment

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer or Euro style bucket attach
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 3,086 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 20.8"
Reach @ Ground Level: 79.9"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style bucket attach
72" Bucket



**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB	9040939P08	\$52,486.00
WORKMASTER 65 T4A	Cab	6,239 LB	9042944P46	\$55,057.00
WORKMASTER 75 T4A	Cab	6,239 LB	9044949P84	\$57,628.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

X0593XX	Deluxe Cab HiVis Fast Pick Deluxe Cab HiVis Fast Pick pricing includes: Cab with openable Clear HiVis panel 3 rear remotes 4 rear wheel weights Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Loader: 550LU NSL loader with SSL quick attach and 72" bucket OR 555LU MSL loader with EURO quick attach and 72" bucket		(900632P58)	(\$811.00)
---------	--	--	-------------	------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)		9000522P60	\$670.00



**WORKMASTER 55-75 DLX CAB HIVIS FAST PICK
 US PRICE LIST**

REAR

SD_T4950 REAR WHEELS AND TIRES

	8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
	8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)		9000241P02	\$309.00

LOADER

LOADER

SD_T8110 LOADER BRACKETS

	344739	LOADER-NSL.2F.SSLWGG 550LU Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344742	LOADER-MSL-2F-EU-WGG 555LU Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000856P44	\$1,098.00

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 75 STANDARD ROPS FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value ROPS platform
- Mechanical suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 75
74 Gross Engine hp
60 PTO hp @ 2300 rpm
3 Cyl Turbocharged Engine
179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Vertical Exhaust
21.6 gal Fuel Tank
2 function mid mount valve & joystick
16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted
Power Shuttle
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 25 mph (40 KPH)
Speed varies with tire selection
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Adjustable Tread Width from 51.5 in.
to 79.4 in.

REAR AXLE

Flange Type
Adjustable Tread Width 60.1 in.
to 76.0 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 12.5 gpm (47.7 L)
Steering Pump: 7.6 gpm (28.7 L)
Total Flow: 20.1 gpm (76.4 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
4WD power shuttle:
-540 RPM hydraulic wet clutch
-Hydraulic engagement
-Wet clutch
1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends



**WORKMASTER 75 STANDARD ROPS FAST PICK
US PRICE LIST**

Standard Equipment

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

ROPS LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:**ROPS MODELS**

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Vinyl mechanical suspension,
operator's presence sensor,
retractable seat belts and arm rests
Suspended pedals
Locking brake pedals

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:**550LU NON SELF-LEVELING**

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer style bucket attach
72" Bucket



**WORKMASTER 75 STANDARD ROPS FAST PICK
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 75 T4A	Rops	6,239 LB	9038725P44	\$49,648.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

X0588XX	Standard ROPS Fast Pick Standard ROPS Fast Pick pricing includes: 2 rear remotes 550LU NSL loader with SSL quick attach and 72" bucket Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Rear weights: 4 rear wheel weights OR NO rear wheel weights		(902028P00)	(\$2,600.00)
---------	--	--	-------------	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)		9000522P60	\$670.00

REAR

SD_T4950 REAR WHEELS AND TIRES

8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
---------	---	--	--	-----------



**WORKMASTER 75 STANDARD ROPS FAST PICK
 US PRICE LIST**

	8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)		9000241P02	\$309.00
--	---------	---	--	------------	----------

WEIGHTS

REAR

SD_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights Two weights per side (110 lbs each) = 440 lbs total		9000476P58	\$611.00
--	--------	---	--	------------	----------

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 75 DELUXE ROPS FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value ROPS platform
- Mechanical suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 75
74 Gross Engine hp
60 PTO hp @ 2300 rpm
3 Cyl Turbocharged Engine
179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Vertical Exhaust
21.6 gal Fuel Tank
2 function mid mount valve & joystick
16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted
Power Shuttle
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 25 mph (40 KPH)
Speed varies with tire selection
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Adjustable Tread Width from 51.5 in.
to 79.4 in.

REAR AXLE

Flange Type
Adjustable Tread Width 60.1 in.
to 76.0 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 12.5 gpm (47.7 L)
Steering Pump: 7.6 gpm (28.7 L)
Total Flow: 20.1 gpm (76.4 L)
(3) Open Center Remote Valves with
Detent & Kickout on #2 & #3

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard
4WD power shuttle:
-540 RPM hydraulic wet clutch
-Hydraulic engagement
-Wet clutch
1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends



**WORKMASTER 75 DELUXE ROPS FAST PICK
US PRICE LIST**

Standard Equipment

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

ROPS LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Vinyl mechanical suspension,
operator's presence sensor,
retractable seat belts and arm rests
Suspended pedals
Locking brake pedals

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
4 x 110 lb Rear Wheel Weights
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer or Euro style bucket attach
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 3,086 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 20.8"
Reach @ Ground Level: 79.9"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style bucket attach
72" Bucket



**WORKMASTER 75 DELUXE ROPS FAST PICK
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 75 T4A	Rops	6,239 LB	9038725P44	\$49,648.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

X0589XX	Deluxe ROPS Fast Pick Deluxe ROPS Fast Pick pricing includes: 3 rear remotes 4 rear wheel weights Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR 19.5L-24 R4 rear with 12.5/80-18 R4 front Loader: 550LU NSL loader with SSL quick attach and 72" bucket OR 555LU MSL loader with EURO quick attach and 72" bucket		(900925P08)	(\$1,186.00)
---------	---	--	-------------	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)		9000522P60	\$670.00

REAR

SD_T4950 REAR WHEELS AND TIRES

8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
---------	---	--	--	-----------



**WORKMASTER 75 DELUXE ROPS FAST PICK
 US PRICE LIST**

	8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)		9000241P02	\$309.00
--	---------	---	--	------------	----------

LOADER

LOADER

SD_T8110 LOADER BRACKETS

	344739	LOADER-NSL.2F.SSLWGG 550LU Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344742	LOADER-MSL-2F-EU-WGG 555LU Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000856P44	\$1,098.00

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 55-75 WEST COAST FAST PICK
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab & ROPS platform
- 12x12 power shuttle transmission
- Lift-O-Matic
- 1 Auxiliary lift ram (4,000 lbs)
- 8 Front weights
- 3 Rear remotes

DIESEL ENGINE

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

HYDRAULIC SYSTEM:

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55-75 WEST COAST FAST PICK
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
4,000 Pounds Lift Capacity with
1 Auxiliary Lift Ram
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

CAB LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

ROPS LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS
ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

ROPS MODELS

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Vinyl mechanical suspension,
operator's presence sensor,
retractable seat belts and arm rests
Suspended pedals
Locking brake pedals

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies



**WORKMASTER 55-75 WEST COAST FAST PICK
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB	9040939P08	\$52,486.00
WORKMASTER 65 T4A	Cab	6,239 LB	9042944P46	\$55,057.00
WORKMASTER 75 T4A	Cab	6,239 LB	9044949P84	\$57,628.00
WORKMASTER 75 T4A	Rops	6,239 LB	9038725P44	\$49,648.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

PACKAGE SELECTION

SD_T9980 PACKAGING

X0596XX	West Coast Less Loader West Coast Less Loader Fast Pick pricing includes: 3 rear remotes Less loader and mid mount valve 8 front weights Auxiliary lift ram Cab Models: Cab with openable Black-Out panel Allows for choice of the following: Tires: 16.9x30 R1 rear with 11.2x24 R1 front OR Front and rear shipping wheels Rear weights: 4 rear wheel weights OR NO rear wheel weights		(906209P58)	(\$7,961.00)
---------	---	--	-------------	--------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

8299801	Non-Return Ship Wheels - 4WD		(900595P14)	(\$763.00)
8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge



**WORKMASTER 55-75 WEST COAST FAST PICK
 US PRICE LIST**

REAR

SD_T4950 REAR WHEELS AND TIRES

	8399801	Non-Returnable Shipping Wheel		(901152P06)	(\$1,477.00)
	8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge

WEIGHTS

REAR

SD_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights Two weights per side (110 lbs each) = 440 lbs total		9000476P58	\$611.00
--	--------	---	--	------------	----------

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 55, 65, 75 CAB A LA CARTE
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value cab
- Instructor seat
- Air suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 55

54 Gross Engine hp

40 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 65

64 Gross Engine hp

50 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

Workmaster 75

74 Gross Engine hp

60 PTO hp @ 2300 rpm

3 Cyl Turbocharged Engine

179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)

Electronic Injection Bosch

High-pressure Common Rail System

Electric Engine Shutoff

Hand and Foot Throttle Controls

Grid Heater Starting Aid

Powercore Dry Air Cleaner

Under Hood Muffler

Vertical Exhaust

21.6 gal Fuel Tank

2 function mid mount valve & joystick

16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted

Power Shuttle

12 Forward and 12 Reverse Speeds

(4) Synchronized Gears

(3) Non-synchronized Ranges

(2) clutches, 5 wet disc plates

FWD - 25 mph (40 KPH)

Speed varies with tire selection

Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering

Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip

Electro-Hydraulic engagement standard

Adjustable Tread Width from 51.5 in.

to 79.4 in.

REAR AXLE

Flange Type

Adjustable Tread Width 60.1 in.

to 76.0 in.

HYDRAULIC SYSTEM:

Open Center Gear Pump System

Dual Pumps Flow: 20.1 gpm (76.4 L)

Implement Pump: 12.5 gpm (47.7 L)

Steering Pump: 7.6 gpm (28.7 L)

(2) Open Center Remote Valves with

Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent

Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch

-Hydraulic engagement

-Wet clutch

1-3/8 in. 6 splines



**WORKMASTER 55, 65, 75 CAB A LA CARTE
US PRICE LIST**

Standard Equipment

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

CAB LIGHTING:

Front: (2) Halogen Headlights
(2) cab mounted worklights
Rear: (2) cab mounted worklights
Turn Signals/Flashers/Rear Lights

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

OPERATOR PROTECTIVE STRUCTURE:

CAB MODELS
ROPS protected, 4 post, flat deck
platform with heat and air
conditioning, tinted windshield,
retractable sun screen, front wiper
and washer, rear wiper and washer,
two doors with locks, two external
mirrors, hinged rear window (opens
completely)
Steering Wheel - adjustable tilt
Seat - Cloth covered air suspension,
operator's presence sensor,
retractable seat belt and arm rests
Instructor Seat
Suspended pedals
Radio, speakers, and antenna

WARRANTY:

New Holland Standard Warranty Applies



**WORKMASTER 55, 65, 75 CAB A LA CARTE
US PRICE LIST**

Standard Equipment

LOADER:

550LU NON SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer or Euro style bucket attach
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 3,086 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 20.8"
Reach @ Ground Level: 79.9"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style bucket attach
72" Bucket



**WORKMASTER 55, 65, 75 CAB A LA CARTE
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 55 T4A	Cab	6,239 LB	9040939P08	\$52,486.00
WORKMASTER 65 T4A	Cab	6,239 LB	9042944P46	\$55,057.00
WORKMASTER 75 T4A	Cab	6,239 LB	9044949P84	\$57,628.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

OPERATOR PLATFORM

SD_T9200 OPERATOR STRUCTURE #1

	333606	CAB FIX SCREEN OPEN Cab with openable high visibility panel		9000292P50	\$375.00
--	--------	---	--	------------	----------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

	8299801	Non-Return Ship Wheels - 4WD		(900595P14)	(\$763.00)
	8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
	8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)		9000522P60	\$670.00

REAR

SD_T4950 REAR WHEELS AND TIRES

	8399801	Non-Returnable Shipping Wheel		(901152P06)	(\$1,477.00)
	8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
	8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)		9000241P02	\$309.00



**WORKMASTER 55, 65, 75 CAB A LA CARTE
 US PRICE LIST**

HYDRAULICS

REAR REMOTES

SD_T8270 REAR REMOTES

	335413	2 Rem. Valve (1 S/D) 2 rear remote valves Float, Detent and kickout on 2nd remote			No Charge
	335640	3 REMOTE VALVE 3 rear remote valves Float, Detent and kickout on 2nd and 3rd remotes		9000626P34	\$803.00

LOADER

LOADER

SD_T8110 LOADER BRACKETS

	344739	LOADER-NSL.2F.SSLWGG 550LU Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344743	LOADER-NSL-2F-EU-WGG 550LU Non self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344738	LOADER-MSL.2F.SSLWGG 555LU Mechanical self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000856P44	\$1,098.00



**WORKMASTER 55, 65, 75 CAB A LA CARTE
 US PRICE LIST**

	344742	LOADER-MSL-2F-EU-WGG 555LU Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000856P44	\$1,098.00
--	--------	---	--	------------	------------

3-POINT HITCH

REAR 3 POINT HITCH

SD_T8200 HITCH

	332785	MDC Hitch aux lift ram 1 Auxiliary lift ram = 4,000 lbs total lift capacity		9000354P90	\$455.00
--	--------	---	--	------------	----------

WEIGHTS

REAR

SD_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights Two weights per side (110 lbs each) = 440 lbs total		9000476P58	\$611.00
--	--------	---	--	------------	----------

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 75 ROPS A LA CARTE
US PRICE LIST**

Standard Equipment

KEY SELLING POINTS:

- Best-in-Class value ROPS platform
- Mechanical suspensions seat
- 12x12 power shuttle transmission
- Lift-O-Matic
- Factory installed loader

DIESEL ENGINE

Workmaster 75
74 Gross Engine hp
60 PTO hp @ 2300 rpm
3 Cyl Turbocharged Engine
179 cu in (2.9 L) Displacement

ALL MODELS:

Tier B Emissions Compliant:
(CEGR + DOC)
Electronic Injection Bosch
High-pressure Common Rail System
Electric Engine Shutoff
Hand and Foot Throttle Controls
Grid Heater Starting Aid
Powercore Dry Air Cleaner
Under Hood Muffler
Vertical Exhaust
21.6 gal Fuel Tank
2 function mid mount valve & joystick
16.9X30 rear and 11.2X24 front tires

TRANSMISSION:

LH side steering column mounted
Power Shuttle
12 Forward and 12 Reverse Speeds
(4) Synchronized Gears
(3) Non-synchronized Ranges
(2) clutches, 5 wet disc plates
FWD - 25 mph (40 KPH)
Speed varies with tire selection
Hand Operated Park Brake

STEERING/BRAKES:

Hydrostatic Power Steering
Brakes- Hydraulically assisted wet disc

4WD FRONT AXLE:

Limited Slip
Electro-Hydraulic engagement standard
Adjustable Tread Width from 51.5 in.
to 79.4 in.

REAR AXLE

Flange Type
Adjustable Tread Width 60.1 in.
to 76.0 in.

HYDRAULIC SYSTEM:

Open Center System
Dual Gear Pumps
Implement Pump: 12.5 gpm (47.7 L)
Steering Pump: 7.6 gpm (28.7 L)
Total Flow: 20.1 gpm (76.4 L)
(2) Open Center Remote Valves with
Detent & Kickout on #2

REAR DIFFERENTIAL LOCK:

Mechanically Engaged

PTO:

Fully Independent
Flip-up PTO Shaft Guard

4WD power shuttle:

-540 RPM hydraulic wet clutch
-Hydraulic engagement
-Wet clutch
1-3/8 in. 6 splines

3-POINT LIFT SYSTEM:

Right hand console mounted
lever control
Mechanical Draft Control
3,500 Pounds Lift Capacity
Category II Ends
Telescopic Stabilizers
Flexible Lower Link Ends



**WORKMASTER 75 ROPS A LA CARTE
US PRICE LIST**

Standard Equipment

ELECTRICAL:

(1) 840 cca Heavy-Duty Battery
120 amp Alternator
7-pin Outlet for trailer/implement lighting
and signals
25 amp socket
12V power socket (cigarette lighter)

INSTRUMENTATION:

Analog Instrumentation with warning
lights for turn signals, high beam,
work lights, side lights, rear PTO,
4WD, differential lock, low fuel,
alternator, oil pressure, brake fluid,
grid heater & hand brake
Gauges for fuel level, engine
temperature and tachometer
Digital Readout for PTO speed,
ground speed, battery & hours

ROPS LIGHTING:

Front: (2) Halogen Headlights
Rear: (1) Right hand fender
mounted worklights
Turn Signals/Flashers/Rear Lights

OPERATOR PROTECTIVE STRUCTURE:**ROPS MODELS**

2-Post Foldable ROPS with ISO-
mounted flat deck platform
Steering Wheel - adjustable tilt
Seat - Vinyl mechanical suspension,
operator's presence sensor,
retractable seat belts and arm rests
Suspended pedals
Locking brake pedals

TIRES:

11.2x24 R1 Front
16.9X30 R1 Rear

MISCELLANEOUS:

Pivoting Engine Hood
SMV Emblem
Toolbox

WARRANTY:

New Holland Standard Warranty Applies

LOADER:**550LU NON SELF-LEVELING**

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 2,425 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 23.7"
Reach @ Ground Level: 85.8"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 58 degrees
Skid Steer or Euro style bucket attach
72" Bucket

555LU MECHANICAL SELF-LEVELING

Maximum Lift Height @
pivot pin: 131.8"
Dump Clearance @ 45 deg: 98.8"
Digging Depth: 5.9"
Lift Capacity @ 800mm: 3,086 LBS
Breakout Force @ 800mm: TBC LBS
Reach @ Max Lift Height @ 45
deg: 20.8"
Reach @ Ground Level: 79.9"
Bucket Rollback Angle: 42 degrees
Bucket Dump Angle: 60 degrees
Skid Steer or Euro style bucket attach
72" Bucket



**WORKMASTER 75 ROPS A LA CARTE
 US PRICE LIST**

Models

COMMERCIAL MODEL	VERSION	Weight	Factory Data	List Price
WORKMASTER 75 T4A	Rops	6,239 LB	9038725P44	\$49,648.00

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

TIRES

FRONT

SD_T4940 FRONT WHEELS AND TIRES

	8299801	Non-Return Ship Wheels - 4WD		(900595P14)	(\$763.00)
	8232304	11.2 x 24 6PR R1 Matching rear tires = 16.9-30 (8355304)			No Charge
	8290904	12.5/80-18 10PR R4 Matching rear tires = 19.5L-24 10 PR R4 (8391904)		9000522P60	\$670.00

REAR

SD_T4950 REAR WHEELS AND TIRES

	8399801	Non-Returnable Shipping Wheel		(901152P06)	(\$1,477.00)
	8355304	16.9-30 6PR R1 Matching front tires = 11.2-24 (8232304)			No Charge
	8391904	19.5L-24 10 PR R4 Matching front tires = 12.5/80-18 10PR R4 (8290904)		9000241P02	\$309.00

HYDRAULICS

REAR REMOTES

SD_T8270 REAR REMOTES

	335413	2 Rem. Valve (1 S/D) 2 rear remote valves Float, Detent and kickout on 2nd remote			No Charge
	335640	3 REMOTE VALVE 3 rear remote valves Float, Detent and kickout on 2nd and 3rd remotes		9000626P34	\$803.00



**WORKMASTER 75 ROPS A LA CARTE
 US PRICE LIST**

LOADER

LOADER

SD_T8110 LOADER BRACKETS

	344739	LOADER-NSL.2F.SSLWGG 550LU Non self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344743	LOADER-NSL-2F-EU-WGG 550LU Non self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars			No Charge
	344738	LOADER-MSL.2F.SSLWGG 555LU Mechanical self leveling with skid steer style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000856P44	\$1,098.00
	344742	LOADER-MSL-2F-EU-WGG 555LU Mechanical self leveling with euro style attachment Includes: -2 Function mid mount valve and joystick -72" Bucket -Grill guard with two cross bars		9000856P44	\$1,098.00

3-POINT HITCH

REAR 3 POINT HITCH

SD_T8200 HITCH

	332785	MDC Hitch aux lift ram 1 Auxiliary lift ram = 4,000 lbs total lift capacity		9000354P90	\$455.00
--	--------	---	--	------------	----------



**WORKMASTER 75 ROPS A LA CARTE
 US PRICE LIST**

WEIGHTS

REAR

SD_T4961 REAR BALLAST

	330470	4 x 110 lb Rear Wheel Weights Two weights per side (110 lbs each) = 440 lbs total		9000476P58	\$611.00
--	--------	---	--	------------	----------

OPERATOR'S MANUALS

SD_T9802 OPERATORS MANUAL

	330986	Spanish Operators Manual			No Charge
--	--------	--------------------------	--	--	-----------

SD_T9803 FRENCH OPERATOR MANUAL

	330982	French Operators Manual			No Charge
--	--------	-------------------------	--	--	-----------



**WORKMASTER 55, 65, 75 SPECIAL ORDER
 US PRICE LIST**

Standard Equipment

Special Custom Order Options

Requires YSR, YRT or YGR order codes.

Please place an order in the system with the configuration as close as possible to your desired configuration and then contact Dealer Sales Support with the following information to get the order configuration changed:

1. Vehicle Number(s)
2. Order Code(s) desired for each vehicle number

The orders will then be sent to have the order configurations changed to include your desired order code(s).

Factory Supplied Options

Order Code	Description	Weight	Factory Data	List Price
------------	-------------	--------	--------------	------------

OPERATOR PLATFORM

SD_T8520 INSTRUCTIONAL SEAT				
	390865	Less Instructional Seat Removes instructor seat option from Cab Models	(900418P08)	(\$536.00)



**WORKMASTER 55, 65, 75 SPECIAL ORDER
 US PRICE LIST**

LOADER

LOADER

SD_T8110 LOADER BRACKETS

		391489	Less Loader Bracket No Loader Removes mid mount valve, loader & bucket		(905981P82)	(\$7,669.00)
--	--	--------	---	--	-------------	--------------

WEIGHTS

FRONT

SD_T2150 FRONT BALLAST

		330183	FRONT WEIGHT 8X30KG Front weight carrier (42 lbs) + 8 front weights (66 lbs) = 572 lbs NOT COMPATIBLE with front loader		9000819P00	\$1,050.00
--	--	--------	--	--	------------	------------

PARTS DIVISION SUPPLIED ACCESSORIES FOR WORKMASTER 55, 65 & 75 Tractors				
Part Number	Description	WORKMASTER 75	WORKMASTER 55, 65, 75	Notes
	HYDRAULICS	ROPS	CAB	
TBD	3 Rear Remotes	X	X	
	ELECTRICAL			
731231551	Rotary Beacon Kit	X		Connects to 12V power socket
731231552	Rotary Beacon Kit		X	Connects to 12V power socket
719216551	Engine Block Heater Kit	X	X	
	PLATFORM			
718130551	Monitor Mounting Bracket		X	Requires Cab
710857552	Canopy	X		
	LOADER			
731200551	3rd Function Diverter Valve	X	X	
731197551	Loader Suspension	X	X	
731198551	3rd Function Diverter Valve + Loader Suspension	X	X	