

November 1, 2021
 BOBCAT Retail Price Pages



Utility Work Machine



*Machine shown with optional equipment - photo may not reflect the base configuration.

Standard Equipment

Engine

- 61HP 2.4L Bobcat Engine
- Automatically Activated Glow Plugs

Drive System

- Limited Slip Transaxle
- Two-Speed Transmission
- Parking Brake, automatic
- Full-time Four-Wheel Drive
- All-Wheel Steer
- Horsepower Management
- Speed Management

Steering & Suspension

- Suspension, 4-wheel independent
- Power Steering with Tilt Steering Wheel

Operator Comfort

- Enclosed cab with HVAC
- Front Windshield Wiper
- Adjustable Driver Seat
- Seat Belts, Shoulder Harness
- Beverage Holders
- Cruise Control

Front Work Group

- Bob-Tach™ Mounting System
- Auxiliary Hydraulics: Variable Flow with dual direction detent
- Boom Float
- Lift Arm Support

Tires

- Tires: 27 x 10.5-15 (8 ply), Lug Tread

Electrical

- LED Front Work Lights
- Combo Type A and Type C USB charging port
- Dome Light
- Toolcat Interlock Control System (TICS)™

Instrumentation

- 5" Display with Jog Shuttle
- Following are shown in display: Hourmeter, Speedometer, Tachometer, Fuel Gauge, Engine Temperature Gauge, Service and Error Codes
- Engine and Hydraulic Monitor with Shutdown

Frame & Cargo Box

- Rear Receiver Hitch
- Hydraulic Dump Box
- Cargo Box Support
- Radiator Screen
- Lower Engine Cover

Warranty

- Machine Warranty: 12 Months, Unlimited Hours
- Bobcat Engine Warranty: Additional 12 months or total of 2000 hours after initial 12 month warranty

Roll Over Protective Structure (ROPS) – Meets Requirements of SAE-J1040 & ISO 3471
 Falling Object Protective Structure (FOPS) – Meets Requirements of SAE-J1043 & ISO3449, Level I

UW56
 Utility Work Machine

Quick Specs

Engine Model.....	2.4L Bobcat Engine
Horsepower	61
Engine Fuel/Cooling.....	Diesel/Liquid
Hydraulic Flow-Attachment.....	18.9 GPM
Hydraulic Flow-Attachment/High Flow.....	27.9 GPM
Hydraulic Pressure.....	3000 PSI
Travel Speed (Low).....	0-8 MPH
Travel Speed (High).....	0-17 MPH
Travel Speed (Reverse).....	0-8 MPH
Operating Weight.....	5680 lbs.
Fuel Capacity.....	20 gal.
Dimensions (Length x Width x Height)-27 in. Tires.....	145 in. x 60 in. x 81 in.
Dimensions (Length x Width x Height)- 29 in. Tires.....	145 in. x 64 in. x 82 in.
Ground Clearance – with 27 in. tires.....	8 in.
Ground Clearance – with 29 in. tires.....	9 in.
Cargo Box Specifications.....	
Inside Dimensions (Length x Width x Height).....	56 in. x 51 in. x 10 in.
Bed Height from Ground.....	38 in.
Cargo Box Maximum Load.....	2000 lbs.
Turning Diameter-outside in AWS mode.....	17.5 ft.
Lift Height.....	83 in.
Maximum Reach.....	45 in.
Rated Operating Capacity.....	1500 lbs.
Tow Rating.....	4000 lbs.
Machine Rated Capacity	
(combined weight of load on lift-arm, cargo box load, operator and passenger).....	2200 lbs.
Total Rated Capacity	
(combined weight of load on lift-arm, cargo box load, operator, passenger and tow weigh	4200 lbs.

Part Number	Description	Utility Work Machine	etail Price In US	PDI & Delivery:
M1225	UW56 Utility Work Machine.....		\$ 69,548	\$ -

Part Number	Description	Factory Installed Options	etail Price In US	PDI & Delivery:
-------------	-------------	---------------------------	-------------------	-----------------

Individual Options

M1225-R08-C02	Attachment Control.....		\$236.00	\$ -
M1225-P01-C01	Deluxe Road Package..... Includes back-up alarm, turn signals, flashers, taillights, brake lights, rear view mirror, side mirrors, horn, rear work light, and headlights <i>Allows Work Machine to meet most regulations for driving on local roadways. Check with local DMV to confirm all requirements for off-highway machinery on your local roads. Toolcat machines are not "automobiles" and thus do not need to be licensed to drive on local roads, but usually require lighting and mirrors included in this package.</i>		\$2,895.00	\$ -
M1225-R07-C02	Heavy Duty Battery.....		\$97.00	\$ -
M1225-R03-C02	High Flow Package..... Includes high flow valve, larger auxiliary hoses, and high flow switch in cab; Provides 27.9 GPM for attachment operation; Must also order 7-Pin Attachment Control		\$1,736.00	\$ -
M1225-A01-C04	Interior Trim..... Insulation for left and right-side panels of center console		\$205.00	\$ -
M1225-R14-C03	Power Bob-Tach.....		\$1,099.00	\$ -
M1225-R15-C02	Radio Option..... Features Aux mini jack for MP-3, Weatherproof design, NOAA Weather Bands, 6 AM & 5 FM presets, Time & Date, Job Clock, Backlit display, 3.5 mm headphone jack, 12volt DC power outlet		\$533.00	\$ -
M1225-R16-C02	Traction Control..... Senses wheel speed variation during limited traction, applies braking to increase torque to wheels in traction, Includes switch in cab for system deactivation		\$545.00	\$ -
M1225-R20-C01	Rearview Camera..... Rearview camera mounted on the back of the cab		\$360.00	\$ -
M1225-A01-C02	Block Heater.....		\$130.00	\$ -

Tire Options Set of 4 Tires

Set of 4 Tires – In Place of Base Equipment

M1225-R05-C04	29 x 10.5, 8 PR, Trac Tires..... Work Machine Width – 60"		\$546.00	\$ -
M1225-R05-C05	29 x 12.5, 8 PR, Turf Tires..... Work Machine Width – 64"; Includes wide fenders		\$786.00	\$ -

UW53
Utility Work Machine
Standard Equipment

- | | |
|--|--|
| <p>Engine</p> <ul style="list-style-type: none"> - 61HP 2.4L Bobcat Engine - Automatically Activated Glow Plugs <p>Drive System</p> <ul style="list-style-type: none"> - Limited Slip Transaxle - Two-Speed Transmission - Parking Brake, automatic - Full-time Four-Wheel Drive - All-Wheel Steer - Horsepower Management - Speed Management <p>Steering & Suspension</p> <ul style="list-style-type: none"> Suspension, 4-wheel independent Power Steering with Tilt Steering Wheel <p>Operator Comfort</p> <ul style="list-style-type: none"> - Enclosed cab with HVAC - Radio W/Aux Input & Headphone Jack - Front Windshield Wiper - Driver Adjustable Vinyl Seats - Seat Belts, Shoulder Harness - Beverage Holders - Cruise Control - Deluxe Road Package: Backup alarm, turn signals, flashers, tail lights, brake lights, and rear work lights - Interior Trim <p>Front Work Group</p> <ul style="list-style-type: none"> - Power Bob-Tach™ Mounting System | <p>Tires</p> <ul style="list-style-type: none"> - Tires: 27 x 10.5-15 (8 ply), Lug Tread <p>Electrical</p> <ul style="list-style-type: none"> - LED Front Work Lights - Combo Type A and Type C USB charging port - Dome Light - Toolcat Interlock Control System (TICS)™ <p>Instrumentation</p> <ul style="list-style-type: none"> - 5" Display with Jog Shuttle - Following are shown in display: Hourmeter, Speedometer, Tachometer, Fuel Gauge, Engine Temperature Gauge, Service and Error Codes - Engine and Hydraulic Monitor with Shutdown <p>Frame & Rear</p> <ul style="list-style-type: none"> - Rear Receiver Hitch - Rear PTO- 540 PTO, PTO Shield, PTO Tachometer - Rear Remote Package: One set of poppet-style couplers, (for use with implement hydraulics) - Radiator Screen - Lower Engine Cover - Three-Point Hitch Package: Category 1 Three-Point, Depth Position Gauge <p>Warranty</p> <ul style="list-style-type: none"> - Machine Warranty: 12 Months, Unlimited Hours - Bobcat Engine Warranty: Additional 12 months or total of 2000 hours after initial 12 month warranty |
|--|--|

- Auxiliary High Flow Hydraulics: Variable Flow with dual direction detent
- Attachment Control Kit
- Boom Float
- Lift Arm Support

Roll Over Protective Structure (ROPS) – Meets Requirements of SAE-J1040 & ISO 3471
Falling Object Protective Structure (FOPS) – Meets Requirements of SAE-J1043 & ISO3449, Level I

UW53
Utility Work Machine

Quick Specs

Engine Model.....	2.4L Bobcat Engine
Horsepower	61
Engine Fuel/Cooling.....	Diesel/Liquid
Hydraulic Flow-Attachment.....	18.9 GPM
Hydraulic Flow-Attachment/High Flow.....	27.9 GPM
Hydraulic Pressure.....	3000 PSI
PTO Horsepower.....	25 HP
PTO RPM.....	540
Travel Speed (Low).....	0-8 MPH
Travel Speed (High).....	0-17 MPH
Travel Speed (Reverse).....	0-8 MPH
Operating Weight.....	5710 lbs.
Fuel Capacity.....	20 gal.
Dimensions (Length x Width x Height)-27 in. Tires.....	154 in. x 60 in. x 81 in.
Dimensions (Length x Width x Height)- 29 in. Tires.....	154 in. x 64 in. x 82 in.
Ground Clearance – with 27 in. tires.....	8 in.
Ground Clearance – with 29 in. tires.....	9 in.
Turning Diameter-outside in AWS mode.....	17.5 ft.
Lift Height.....	83 in.
Maximum Reach.....	45 in.
Rated Operating Capacity.....	1500 lbs.
Three-Point Hitch Lift Capacity at 24 inches behind lift point with loader.....	1775 lbs.
Tow Rating.....	4000 lbs.
Machine Rated Capacity	2200 lbs.
#####	
Total Rated Capacity	4200 lbs.
(combined weight of load on lift-arm, three point, storage bins, operator, passenger, and tow weight)	

Part Number	Description	Utility Work Machine	etail Price In US	PDI & Delivery:
M1227	UW53 Utility Work Machine.....		\$82,028.57	\$ -

Part Number	Description	Factory Installed Options	etail Price In US	PDI & Delivery:
<i><u>Tire Options</u></i>				
<i>Set of 4 Tires– In Place of Base Equipment</i>				
M1225-R05-C04	29 x 10.5, 8 PR, Trac Tires.....		\$546.00	\$ -
	Work Machine Width – 60"			
M1225-R05-C05	29 x 12.5, 8 PR, Turf Tires.....		\$786.00	\$ -
	Work Machine Width – 64"; Includes wide fenders			