

CATERPILLAR MACHINE PRICE LIST

PM622PM622 COLD PLANER
MINERBIO, ITALYShip Weight
lbsLIST PRICE
AT DEALER

Standard Equipment:

POWERTRAIN

CAT C18, inline 6-cylinder,
turbocharged, aftercooled
diesel engine
Power and torque curve optimized for
fuel efficiency
Engine diagnostic connector
(for CAT ET)
Air cleaner, dry type dual element with
integral precleaner
Belt, automatic tensioner
Fuel filter/water separator
Hydrostatic transmission
Computerized load control
Four tracks each with polyurethane
track pads
Dual pump propel system
with opposite track traction control
Alignment controlled steering system
with four steering modes:
-front, rear, crab & coordinated steer
-alignment is optimized for selected
mode
Auto Tensioning Tracks

ELECTRICAL

Backup alarm
Alternator, 100-amp
Batteries, two maintenance free
1400 CCA each
Horn, forward warning
Ground located horn, operator warning
Electrical system, 24-volt
Work lights (4 fixed, 10 pole mount)
Remote jump start receptacle
Machine diagnostic connector
(for CAT ET)
Self diagnostic system
Product Link ready

OPERATOR ENVIRONMENT

Dual operating positions, on the left
and right of the operators platform
Operator platform with visibility to
both crawlers of the machine
Machine health monitoring system
Lockable vandalism guards for all
control panels
Platform handrails/guardrails
Control and propel console with
LED backlit panels and joystick
propel and steering
Electronic machine management system
Digital graphic display for diagnostic
and operating instructions

LED wake-up mode with floor light
Integrated grade control
Silver-class touch screen display
Ramp-in, ramp-out function
Digital moldboard control
3 rotor speed selectable on control
panels
Two level warning system with action
light and horn (warning, critical
warning)
Quick detach fuse/relay/controller/
Automatic throttle control
Camera ready display

APPLICATION SPECIFIC COMPONENTS

ROTOR AND CHAMBER SYSTEM
2235 mm (88") wide cutting system
Hydraulically powered floating side
plates
Dry clutch, belt transmission with
automatic tensioner
Three electronically selectable rotor
speeds
Water spray system for cutting tool
cooling and dust control
Curb clearance right side plate
Moldboard with float, lock,
service height and adjustable
down pressure settings
Hydraulically powered and floating
anti-slab
CONVEYORS
Front loading
850 mm (33.5") belt width collecting
conveyor
850 mm (33.5") belt width discharge
conveyor
Dual stage, infinitely variable speed,
with independent reversing
60-degree swing either side of center
for discharging conveyor
Conveyor speed boost function

FLUIDS

Extended life coolant with protection
to -34C (-29F)

OTHER STANDARD EQUIPMENT

Doors, service access, hinged, locking
Fuel tank 1,108 L (293 gal)
Pressure test ports with quick connect
Water tank 3,400 L (898 gal)
Sound suppression insulation kit
Sight gauges (water, hydraulic oil,
filter restriction)

CATERPILLAR MACHINE PRICE LIST

PM622PM622 COLD PLANER
MINERBIO, ITALYShip Weight
lbsLIST PRICE
AT DEALER**OTHER STANDARD EQUIPMENT (CONT.)**

Steering guide
 Mirrors
 Rear water fill
 12-volt ports at operator station
 Air system
 S.O.S. sampling ports
 Auxiliary electro-hydraulic power
 package for operational and service
 functions
 Operational functions:
 -electro-hydraulic powered canopy and
 engine hood uplift
 Service functions:
 -spring applied brakes releasing
 -various auxiliary system functions
 Air filter restriction electric indicator
 Compressed air lubricator and pressure
 regulator unit
 On board winterization system
 Rear water hose hooks
 Compressed air connection at operator
 station

CATERPILLAR MACHINE PRICE LIST

PM622

PM622 COLD PLANER
MINERBIO, ITALY

Ship Weight
lbs

LIST PRICE
AT DEALER

**Lane 2 is reserved for the Base Order Management Program.
Please use Lane 2 when placing orders that are part of the Base
Orders Management Program.**

0G-0527	PM622 MISC MATL 0 AVAILABLE FROM MINERBIO FACTORY	NC
----------------	---	-----------

Only reference numbers that have the text
"ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a MISC order

CATERPILLAR MACHINE PRICE LIST

PM622

USE	REF NO.	MANDATORY ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT

OPERATOR STATION

L	374-1443	CANOPY, FOLDING, HYDRAULIC	0	\$10,440
			0	\$10,440 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Hydraulically folding canopy with extendible side wings and integrated LED lighting.		

GRADE AND SLOPE

L	380-3870	CONTROL, CAT G&S SYSTEM	0	\$7,690
		Measures grade from the position of side plates, using position sensing cylinders. Provides information to machine displays for operation of grade control.		

OTHER ATTACHMENTS

STEERING GUIDE

P	397-8284	GUIDE, TELESCOPING STEERING	0	NC
			0	\$660 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides two telescoping steering guides with multi point adjustment for advanced steering marker placement.		
P	501-0412	GUIDE, STANDARD STEERING	0	NC
			0	\$610 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Provides two standard steering guides with lateral adjustment of pendulum markers.		

COMMISSIONING

NOTE: It is recommended that startup and commissioning of machines be included as part of the machine sale. The net charge covers a three day commissioning event. Trained personnel cover proper machine setup, basic maintenance, operation and application on a customer's jobsite. To request and schedule a machine commissioning event, dealers will need to contact the Caterpillar Paving Technical Training group by filling out the online request form.
 URL: <https://dealer.cat.com/PavingOnDemand>

L	0P-2586	COMMISSIONING, NEEDED	0	\$6,520 NET
		Commissioning Needed, trained personnel are required to properly commission the machine. AVAILABLE FOR: AM-N and AM-S		
L	0P-2587	COMMISSIONING, NOT NEEDED	0	NC
		Commissioning training not needed - Special Case, only to be used by qualified dealers who meet GCI's standard requirements to self-commission machines with customers. For questions, please consult your local GCI Paving Territory Manager		

CATERPILLAR MACHINE PRICE LIST

PM622

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
ELECTRICAL				
P	363-7444	LIGHT, HAZARD, CANOPY 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Two rotating amber beacon lights, magnetically mounted.		\$349 NI
P	394-0410	LIGHT, HAZARD 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Two rotating amber beacon lights mounted to the conveyor and rear of the machine.	0	\$725 \$725 NI
P	376-4129	LIGHT, TRUCK SIGNAL 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Red / Green light to communicate with truck driver	0	\$565 \$565 NI
P	594-8849	LAMP, LED (MAGNETIC MOUNT) 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Single LED Lamp with magnetic mounting.	0	\$360 NI
OPERATOR ENVIRONMENT				
P	374-1445	UMBRELLA 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Includes two umbrellas to provide operator or ground crew protection from sun and rain. Single umbrella measures 1352 mm (54"x54") and is collapsible. Includes support shaft and mounting hardware to be installed on machine at customer direction.		\$710 NI
P	532-7658	WINDSCREEN 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Collapsible windscreens mount to and move with the canopy. Rear windscreen can fold up into canopy cavity when not in use. ONLY FOR USE WITH: 374-1443 CANOPY, FOLDING, HYDRAULIC	0	\$7,190 \$5,360 NI
TECHNOLOGY PRODUCTS				
GRADE AND SLOPE CONTROLS				
P	376-4136	SENSOR, SONIC, AVERAGING 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Sonic averaging ski for mounting on the LH or RH side, consisting of two sonic sensors (in addition to the machine grade control base system or the optional inboard consisting of two sonic sensors (in addition to the base system) with adjustable mounting arms ONLY FOR USE WITH: 380-3870 CONTROL, CAT G&S SYSTEM		\$10,380 NI
P	416-2036	SENSOR, SONIC, FOR STRING LINE 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Include bracket, (1) ultrasonic sensor and cables for mounting at the center of the machine ONLY FOR USE WITH: 380-3870 CONTROL, CAT G&S SYSTEM		\$4,170 NI

CATERPILLAR MACHINE PRICE LIST

PM622

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS

VISIBILITY ENHANCEMENTS

P	376-4123	CAMERA, AUX 0		\$760 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Camera with cable and magnetic mount. Can be placed anywhere within cable length.		

MISC ATTACHMENTS

P	594-5583	HOLDER, SPRAY PAINT CAN 0		\$222 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Magnetically mounted spray paint can holder. Multiple holders may be ordered at one time.		
P	376-4126	PUMP, FUEL TRANSFER 0		\$1,670
		ONLY FOR USE WITH: 602-4287 PM622 02B COLD PLANER	0	\$1,670 NI
		ALSO AVAILABLE ON A MISCELLANEOUS ORDER Allows for transfer of fuel from non-pump container		

FIELD INSTALLED ATTACHMENTS

The following field attachments can be ordered through Machine Order as a miscellaneous order.

C	517-1709	ROTOR, K STD - 15 MM, FLD 0		\$43,880 NI
		CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY AVAILABLE FROM MINERBIO FACTORY AND BALTIMORE PDC Latest Design tool holder system with 2235 mm (88") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 15 mm. Includes: 185 Bits		
C	567-0904	ROTOR, K FINE - 8 MM, FLD 0		\$63,630 NI
		CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY AVAILABLE FROM MINERBIO FACTORY AND BALTIMORE PDC Latest design tool holder system with 2235 mm (88") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 8 mm. Includes: 304 bits		
C	558-6381	ROTOR, K COARSE - 18 MM, FLD 0		\$41,690 NI
		CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest design tool holder system with 2235 mm (88") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 18 mm. Includes: 162 bits		
C	582-8826	ROTOR, K COARSE - 25 MM, FLD 0		\$38,750 NI
		ONLY FOR USE WITH: LANE 3 CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest Design tool holder system with 2010 mm (79.1") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 25 mm. Includes: 131 Bits		

CATERPILLAR MACHINE PRICE LIST

PM622

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

FIELD INSTALLED ATTACHMENTS (CONT.)

C	575-7467	ROTOR, K MICRO - 6MM, FLD 0 CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest design tool holder system for Micro Milling with 2235 mm (88") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, and tooth spacing of 6 mm to provide micro finish. Includes: 386 Bits		\$78,980 NI
C	511-5050	ROTOR, H MICRO - 6X2 MM, FLD 0 CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Weld on tool holders for micro milling with 2235 mm (88") cut width. Advanced design of weld on bit blocks to allow micro finish with a tooth spacing 6X2 mm. Includes: 748 Bits		\$112,840 NI

DOCUMENTATION

CERTIFICATES

0F-5109	CERTIFICATE OF ORIGIN..... 0	\$90 NET
---------	------------------------------	----------

PACKING

0G-0068	PACK, MISCELLANEOUS MATERIAL..... 0	NC
---------	-------------------------------------	----