

# KUBOTA

---

## L SERIES

---

### WHOLEGOODS PRICE LIST EFFECTIVE May 19, 2022

Please replace all pages of this section of the current price book. These pages are a complete revision of this section. All prices are effective as of May 19, 2022

5/19/2022 Added L7291, L7292 and L7293



# L SERIES

PAGE NO.	DESCRIPTION	PTO HP	FACTORY NUMBER	SUGGESTED LIST PRICE	
STANDARD L SERIES	8-4 L2501F	20.5	K12B372B00	\$15,465.00	
	8-4 L2501DT	20.5	K14B146B40	\$17,683.00	
	8-4 L2501HST	19.0	K15B250B40	\$19,063.00	
	8-7 L3301F	27.7	K15B000B80	\$18,751.00	
	8-7 L3301DT	27.7	K16B514B40	\$20,643.00	
	8-7 L3301HST	26.2	K17B340B80	\$21,676.00	
	8-10 L3302DT	27.7	K17B944B00	\$22,430.00	
	8-10 L3302HST	26.2	K18B962B40	\$23,703.00	
	8-12 L3901F	32.1	K15B863B20	\$19,829.00	
	8-12 L3901DT	32.1	K18B275B20	\$22,844.00	
	8-12 L3901HST	30.6	K19B101B60	\$23,877.00	
	8-15 L3902DT	32.1	K19B737B60	\$24,672.00	
	8-15 L3902HST	30.6	K20B756B00	\$25,945.00	
	8-17 L4701F	39.3	K17B889B60	\$22,362.00	
	8-17 L4701DT	39.3	K23B174B40	\$28,968.00	
	8-17 L4701HST	37.8	K24B454B40	\$30,568.00	
	8-20	Standard L Series Dealer Installed Accessories			
	8-24	Standard L Series Front End Loader			
	8-25	Standard L Series Backhoe and Accessories			
	8-26	Standard L Series Snowblowers			
	GRAND L 60 SERIES	8-27 L3560DT	29.5	K21B312B80	\$26,641.00
		8-27 L3560GST	29.5	K22B364B00	\$27,955.00
		8-27 L3560HST	28.0	K22B685B60	\$28,357.00
		8-28 L3560HSTC	28.0	K30B235B20	\$37,794.00
		8-29 L3560HST-LE	28.0	K21B323B20	\$26,654.00
		8-29 L3560HSTC-LE	28.0	K27B712B80	\$34,641.00
8-31 L4060DT		34.0	K24B327B20	\$30,409.00	
8-31 L4060GST		34.0	K25B378B40	\$31,723.00	
8-31 L4060HST		32.5	K25B723B20	\$32,154.00	
8-32 L4060HSTC		32.5	K33B272B80	\$41,591.00	
8-33 L4060HST-LE		32.5	K24B361B60	\$30,452.00	
8-33 L4060HSTC-LE		32.5	K30B750B40	\$38,438.00	
8-35 L4760GST		41.0	K30B071B20	\$37,589.00	
8-35 L4760HST		39.5	K30B407B20	\$38,009.00	
8-36 L4760HSTC		39.5	K37B956B80	\$47,446.00	
8-38 L5060GST		44.0	K32B092B00	\$40,115.00	
8-40 L5460HST		46.5	K32B545B60	\$40,682.00	
8-41 L5460HSTC		46.5	K40B095B20	\$50,119.00	
8-43 L6060HST		53.0	K34B283B20	\$42,854.00	
8-44 L6060HSTC		53.0	K41B832B80	\$52,291.00	
8-46		Grand L 60 Dealer Installed Accessories			
8-50		Grand L 60 Front Loaders			
8-53		Grand L 60 Front Quick Hitch & Front Quick Hitch Implements			
8-54		Grand L 60 Front QH Mounted Blades and Accessories			
8-55		Grand L 60 Front QH Mounted Utility Snow Blowers and Accessories			
8-56		Grand L 60 Front QH Mounted Commercial Snow Blowers and Accessories			
8-57	Grand L 60 Front QH Mounted Rotary Sweepers and Accessories				
8-58	Grand L 60 Front QH Mounted Flail Mower and Accessories				
8-59	Grand L 60 Backhoes and Accessories				
8-61	Grand L 60 Rear Mount Snow Blowers and Accessories				



---

## L SERIES

---

### ASSEMBLY CHARGES

Starting in March 2013, KIE and Lodi assembly operations will offer L3200, L3800, L3301, L3901 and L4701 tractors fully assembled. Initially we will offer only basic tractor assembly with loader installation. All other units offered for tractor and loader will remain to be dealer installed. These assembly units will be shipped together with other assembly M and TLB models.

Dealers in Northern, Southeast, and Central (Eastern District) Division will receive assembled L-Series from our KIE location and will be handled by the same team currently responsible for M-Series assembly.

Dealers in Western and Central (Western District) Divisions will receive assembly tractors from Kubota Tractor Corp. in Lodi, CA.

Assembly fee for L Series Tractor . . . . . \$105.00 (tractor assembled with wheel and tires)  
Assembly fee for Loader Installation. . . . . \$125.00

**ALL OTHER KITS ARE FIELD INSTALLED ONLY.**



**L01 Series**

**L2501 F / DT / HST**

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

**DIESEL ENGINE**

Kubota Diesel Engine  
 3 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 40 Amps  
 12V – 490 CCA  
 Optional Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

No Exhaust After Treatment Required

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 10.1 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At Lift Point 1918 lbs.  
 24" Behind 1389 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Transmission Driven with  
 Over-Running Clutch - F / DT  
 Live PTO - HST  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 1911 Eng. Rpm - F / DT  
 540 rpm @ 2106 Eng. Rpm - HST

**TRANSMISSION - F / DT**

Sliding Gear Constant Mesh  
 Rear Differential Lock  
 8 Forward Speeds  
 4 Reverse Speeds  
 Single-Stage Clutch  
 Wet Disc Brakes

**TRANSMISSION - HST**

Hydrostatic Drive  
 Rear Differential Lock  
 3 Ranges  
 Optional Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Tubular Steel Beam 2WD  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 10.0 gal.  
 Cooling System 6.3 qts.  
 Crankcase 6.0 qts.  
 Transmission and  
 Hydraulics  
     F 7.1 gal.  
     DT 7.3 gal.  
     HST 6.2 gal.  
 Front Axle 4.8 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Oil Pressure  
 Fuel Gauge  
 Coolant Temperature

**FEATURES**

Illuminated Instrument Panel  
 Steel Hood and Fenders  
 Tool Box  
 Cup Holder  
 Left Hand Fender Grip

**SAFETY EQUIPMENT**

2-Post Foldable ROPS w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

**Model Specifications**

<b>L2501F 2WD</b>	<b>L2501DT 4WD</b>	<b>L2501HST 4WD</b>
SAE Gross HP: 24.8	SAE Gross HP: 24.8	SAE Gross HP: 24.8
Engine Net HP: 23.9	Engine Net HP: 23.9	Engine Net HP: 23.9
PTO HP: 20.5	PTO HP: 20.5	PTO HP: 19
Engine Model: D1703	Engine Model: D1703	Engine Model: D1703
Displacement: 100.47 Cu. In.	Displacement: 100.47 Cu. In.	Displacement: 100.47 Cu. In.



**L01 Series L2501 F**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
------------	-------------	----------------	------------------	----------------------

\*\*\* STANDARD MACHINE \*\*\*

L2501F	2WD Compact Tractor - 2 Post Foldable ROPS	K12B372B00	2822 lbs	\$15,465.00
--------	--	------------	----------	-------------

L2501 F		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>TIRES AND WHEELS<sup>†</sup></b>				
<b>AG</b>				
ALR8865*	F-TIRE 5.00-15 F2 Goodyear Triple Rib	28 lbs		In Base Price
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs		
ALR8852A	F-TIRE 7.5L-15 F2 Firestone Guide Grip	68 lbs	B134B40	Add \$ 168.00
ALR9494	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs		
<b>TURF</b>				
ALR8890A	F-TIRE 23x8.50-12 R3 Titan Multi Trac	36 lbs	B68B80	Add \$ 86.00
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs		

<sup>†</sup> See Tire Section for Individual Tire Pricing and Information  
 \* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L2501 F		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGGESTED LIST PRICE
<b>TIRES AND WHEELS (priced per piece)</b>				
<b>AG</b>				
ALR8865*	F-TIRE 5.00-15 F2 Goodyear Triple Rib	28 lbs	B106B40	\$ 133.00
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs	B390B40	\$ 488.00
ALR8852A	F-TIRE 7.5L-15 F2 Firestone Guide Grip	68 lbs	B173B60	\$ 217.00
ALR9494	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs	B390B40	\$ 488.00
<b>TURF</b>				
ALR8890A	F-TIRE 23x8.50-12 R3 Titan Multi Trac	36 lbs	B148B00	\$ 185.00
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs	B383B20	\$ 479.00



**L01 Series L2501 DT / HST**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***				
L2501DT	4WD Compact Tractor - 2 Post Foldable ROPS	K14B146B40	3210 lbs	\$17,683.00
L2501HST	4WD Compact Tractor - 2 Post Foldable ROPS	K15B250B40	3249 lbs	\$19,063.00

L2501 DT/HST		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>TIRES AND WHEELS<sup>†</sup></b>				
<b>AG</b>				
ALR8866D*	F-TIRE 7.2-16 R1 Goodyear Power Torque	52 lbs		In Base Price
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs		
<b>TURF</b>				
ALR8893A	F-TIRE 25x8.50-14 HF-1Goodyear SofTrac	53 lbs	B110B40	Less \$ (138.00)
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs		
<b>INDUSTRIAL</b>				
AMR8977A	F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL	48 lbs	B582B40	Add \$ 728.00
ALR8809	R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset	201 lbs		
<b>AG/INDUSTRIAL HYBRID</b>				
ALR8596	FT TITN 29X9.50-15 R14T STL 6BLT	60 lbs	B838B40	Add \$ 1,048.00
ALR8597	RT TITN 43X16.00-20NHS R14T STL 6BLT	200 lbs		
ALR8696	F-TIRE 27X8.50-15 R14T GOODYEAR SST	60 lbs	B712B00	Add \$ 890.00
ALR8697	R-TIRE 15-19.5 R14T GOODYEAR SST	200 lbs		

<sup>†</sup> See Tire Section for Individual Tire Pricing and Information  
 \* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L2501 DT/HST		TIRES AND WHEELS (priced per piece)		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGGESTED LIST PRICE
<b>AG</b>				
ALR8866D*	F-TIRE 7.2-16 R1 Goodyear Power Torque	52 lbs	B234B40	\$ 293.00
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs	B390B40	\$ 488.00
<b>TURF</b>				
ALR8893A	F-TIRE 25x8.50-14 HF-1Goodyear SofTrac	53 lbs	B186B40	\$ 233.00
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs	B383B20	\$ 479.00
<b>INDUSTRIAL</b>				
AMR8977A	F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL	48 lbs	B224B80	\$ 281.00
ALR8809	R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset	201 lbs	B691B20	\$ 864.00
<b>AG/INDUSTRIAL HYBRID</b>				
ALR8596	FT TITN 29X9.50-15 R14T STL 6BLT	60 lbs	B274B40	\$ 343.00
ALR8597	RT TITN 43X16.00-20NHS R14T STL 6BLT	200 lbs	B769B60	\$ 962.00
ALR8696	F-TIRE 27X8.50-15 R14T GOODYEAR SST	60 lbs	B248B00	\$ 310.00
ALR8697	R-TIRE 15-19.5 R14T GOODYEAR SST	200 lbs	B732B80	\$ 916.00



**L01 Series**

**L3301 F / DT / HST**

**\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\***

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 3 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 40 Amps  
 12V – 580 CCA  
 Optional Dual Air Cleaner Element  
 Electronic Throttle

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 10.1 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At lift Point 1998 lbs.  
 24" Behind 1435 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Transmission Driven with  
 Over-Running Clutch - F / DT  
 Live PTO - HST  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2430 Eng. Rpm - F / DT  
 540 rpm @ 2580 Eng. Rpm - HST

**TRANSMISSION - F / DT**

Synchro Shuttle with Sliding Gear  
 Rear Differential Lock  
 8 Forward Speeds  
 8 Reverse Speeds  
 Single-Stage Clutch  
 Wet Disc Brakes

**TRANSMISSION - HST**

Hydrostatic Drive  
 Rear Differential Lock  
 3 Ranges  
 Optional Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Tubular Steel Beam 2WD  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank	11.1 gal.
Cooling System	6.3 qts.
Crankcase	7.1 qts.
Transmission and Hydraulics	
F	7.4 gal.
DT	7.5 gal.
HST	6.2 gal.
Front Axle	4.8 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Oil Pressure  
 Fuel Gauge  
 Coolant Temperature

**FEATURES**

Illuminated Instrument Panel  
 Steel Hood and Fenders  
 Tool Box  
 Cup Holder  
 Left Hand Fender Grip  
 Default to Auto Regen; w/ Parked and Inhibit Buttons for DPF

**SAFETY EQUIPMENT**

2-Post Foldable ROPS w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

**Model Specifications**

<b>L3301F 2WD</b>		<b>L3301DT 4WD</b>		<b>L3301HST 4WD</b>	
SAE Gross HP:	33.0	SAE Gross HP:	33.0	SAE Gross HP:	33.0
Engine Net HP:	31.4	Engine Net HP:	31.4	Engine Net HP:	31.4
PTO HP:	27.7	PTO HP:	27.7	PTO HP:	26.2
Engine Model:	D1803	Engine Model:	D1803	Engine Model:	D1803
Displacement:	111.4 Cu. In.	Displacement:	111.4 Cu. In.	Displacement:	111.4 Cu. In.



**L01 Series L3301 F**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
------------	-------------	----------------	------------------	----------------------

\*\*\* STANDARD MACHINE \*\*\*

L3301F	2WD Compact Tractor - 2 Post Foldable ROPS	K15B000B80	2158 lbs	\$18,751.00
--------	--	------------	----------	-------------

L3301 F		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>TIRES AND WHEELS†</b>				
<b>AG</b>				
ALR8865*	F-TIRE 5.00-15 F2 Goodyear Triple Rib	28 lbs		In Base Price
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs		
ALR8852A	F-TIRE 7.5L-15 F2 Firestone Guide Grip	68 lbs	B134B40	Add \$ 168.00
ALR9494	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs		
<b>TURF</b>				
ALR8890A	F-TIRE 23x8.50-12 R3 Titan Multi Trac	36 lbs	B68B80	Add \$ 86.00
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs		

† See Tire Section for Individual Tire Pricing and Information  
 \* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L3301 F		TIRES AND WHEELS (priced per piece)		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGGESTED LIST PRICE
<b>AG</b>				
ALR8865*	F-TIRE 5.00-15 F2 Goodyear Triple Rib	28 lbs	B106B40	\$ 133.00
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs	B390B40	\$ 488.00
ALR8852A	F-TIRE 7.5L-15 F2 Firestone Guide Grip	68 lbs	B173B60	\$ 217.00
ALR9494	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs	B390B40	\$ 488.00
<b>TURF</b>				
ALR8890A	F-TIRE 23x8.50-12 R3 Titan Multi Trac	36 lbs	B148B00	\$ 185.00
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs	B383B20	\$ 479.00





**L01 Series L3301 DT / HST**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***				
L3301DT	4WD Compact Tractor - 2 Post Foldable ROPS	K16B514B40	2308 lbs	\$20,643.00
L3301HST	4WD Compact Tractor - 2 Post Foldable ROPS	K17B340B80	2322 lbs	\$21,676.00

L3301 DT/HST		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>TIRES AND WHEELS<sup>†</sup></b>				
<b>AG</b>				
ALR8866D*	F-TIRE 7.2-16 R1 Goodyear Power Torque	52 lbs	BB0	Add In Base Price
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs		
<b>TURF</b>				
ALR8893A	F-TIRE 25x8.50-14 HF-1Goodyear SofTrac	53 lbs	B110B40	Less \$ (138.00)
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs		
<b>INDUSTRIAL</b>				
AMR8977A	F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL	48 lbs	B582B40	Add \$ 728.00
ALR8809	R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset	201 lbs		
<b>AG/INDUSTRIAL HYBRID</b>				
ALR8596	FT TITN 29X9.50-15 R14T STL 6BLT	60 lbs	B838B40	Add \$ 1,048.00
ALR8597	RT TITN 43X16.00-20NHS R14T STL 6BLT	200 lbs		
ALR8696	F-TIRE 27X8.50-15 R14T GOODYEAR SST	60 lbs	B712B00	Add \$ 890.00
ALR8697	R-TIRE 15-19.5 R14T GOODYEAR SST	200 lbs		

<sup>†</sup> See Tire Section for Individual Tire Pricing and Information  
 \* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L3301 DT/HST		TIRES AND WHEELS (priced per piece)		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST PRICE
<b>AG</b>				
ALR8866D*	F-TIRE 7.2-16 R1 Goodyear Power Torque	52 lbs	B234B40	\$ 293.00
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs	B390B40	\$ 488.00
<b>TURF</b>				
ALR8893A	F-TIRE 25x8.50-14 HF-1Goodyear SofTrac	53 lbs	B186B40	\$ 233.00
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs	B383B20	\$ 479.00
<b>INDUSTRIAL</b>				
AMR8977A	F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL	48 lbs	B224B80	\$ 281.00
ALR8809	R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset	201 lbs	B691B20	\$ 864.00
<b>AG/INDUSTRIAL HYBRID</b>				
ALR8596	FT TITN 29X9.50-15 R14T STL 6BLT	60 lbs	B274B40	\$ 343.00
ALR8597	RT TITN 43X16.00-20NHS R14T STL 6BLT	200 lbs	B769B60	\$ 962.00
ALR8696	F-TIRE 27X8.50-15 R14T GOODYEAR SST	60 lbs	B248B00	\$ 310.00
ALR8697	R-TIRE 15-19.5 R14T GOODYEAR SST	200 lbs	B732B80	\$ 916.00



**L02 Series**

**L3302 DT / HST**

**\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\***

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 3 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 45 Amps  
 12V – 580 CCA (DT) / 600 CCA (HST)  
 Optional Dual Air Cleaner Element  
 Electronic Throttle

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 10.1 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At lift Point 1985 lbs.  
 24" Behind 1433 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Transmission Driven with  
 Over-Running Clutch - DT  
 Live Independent PTO with  
 Hydraulic Clutch- HST  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2430 Eng. Rpm - DT  
 540 rpm @ 2470 Eng. Rpm - HST

**TRANSMISSION - DT**

Synchro Shuttle with Sliding Gear  
 Rear Differential Lock  
 8 Forward Speeds  
 8 Reverse Speeds  
 Single-Stage Clutch  
 Wet Disc Brakes

**TRANSMISSION - HST**

Hydrostatic Drive  
 Rear Differential Lock  
 3 Ranges  
 Optional Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Tubular Steel Beam 2WD  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank	11.1 gal.
Cooling System	6.3 qts.
Crankcase	7.1 qts.
Transmission and Hydraulics	
DT	7.5 gal.
HST	6.2 gal.
Front Axle	4.8 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Oil Pressure  
 Fuel Gauge  
 Coolant Temperature

**FEATURES**

Illuminated Instrument Panel  
 Steel Hood and Fenders  
 Tool Box  
 Cup Holder  
 Left Hand Fender Grip  
 Default to Auto Regen; w/ Parked and  
 Inhibit Buttons for DPF

**SAFETY EQUIPMENT**

2-Post Foldable ROPS w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

Model Specifications	
<b><u>L3302DT 4WD</u></b>	<b><u>L3302HST 4WD</u></b>
SAE Gross HP: 33.0	SAE Gross HP: 33.0
Engine Net HP: 31.4	Engine Net HP: 31.4
PTO HP: 27.7	PTO HP: 26.2
Engine Model: D1803	Engine Model: D1803
Displacement: 111.4 Cu. In.	Displacement: 111.4 Cu. In.





**L01 Series**

**L3901 F / DT / HST**

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 3 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 40 Amps  
 12V – 580 CCA  
 Optional Dual Air Cleaner Element  
 Electronic Throttle

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 10.1 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At lift Point 1998 lbs.  
 24" Behind 1435 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Mechanically Operated with  
 Dual Stage Clutch - F/DT  
 Mechanically Operated with  
 Single Stage Clutch - HST  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2425 Eng. Rpm - F / DT  
 540 rpm @ 2580 Eng. Rpm - HST

**TRANSMISSION - F / DT**

Synchro Shuttle with Sliding Gear  
 Rear Differential Lock  
 8 Forward Speeds  
 4 Reverse Speeds  
 Dual Stage Clutch  
 Wet Disc Brakes

**TRANSMISSION - HST**

Hydrostatic Drive  
 Rear Differential Lock  
 3 Ranges  
 Optional Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Tubular Steel Beam 2WD  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 11.1 gal.  
 Cooling System 6.3 qts.  
 Crankcase 7.1 qts.  
 Transmission and  
 Hydraulics  
     F 7.4 gal.  
     DT 7.5 gal.  
     HST 6.2 gal.  
 Front Axle 4.8 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Oil Pressure  
 Fuel Gauge  
 Coolant Temperature

**FEATURES**

Illuminated Instrument Panel  
 Steel Hood and Fenders  
 Tool Box  
 Cup Holder  
 Left Hand Fender Grip  
 Default to Auto Regen; w/ Parked and  
 Inhibit Buttons for DPF

**SAFETY EQUIPMENT**

2-Post Foldable ROPS w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

**Model Specifications**

<u>L3901F 2WD</u>	<u>L3901DT 2WD</u>	<u>L3901HST 2WD</u>
SAE Gross HP: 37.5	SAE Gross HP: 37.5	SAE Gross HP: 37.5
Engine Net HP: 36.3	Engine Net HP: 36.3	Engine Net HP: 36.3
PTO HP: 32.1	PTO HP: 32.1	PTO HP: 30.6
Engine Model: D1803	Engine Model: D1803	Engine Model: D1803
Displacement: 111.4 Cu. In.	Displacement: 111.4 Cu. In.	Displacement: 111.4 Cu. In.



**L01 Series**

**L3901 F**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
------------	-------------	----------------	------------------	----------------------

\*\*\* STANDARD MACHINE \*\*\*

L3901F	2WD Compact Tractor - 2 Post Foldable ROPS	K15B863B20	2198 lbs	\$19,829.00
--------	--	------------	----------	-------------

L3901F		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>TIRES AND WHEELS<sup>†</sup></b>				
<b>AG</b>				
ALR8865*	F-TIRE 5.00-15 F2 Goodyear Triple Rib	28 lbs		In Base Price
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs		
ALR8852A	F-TIRE 7.5L-15 F2 Firestone Guide Grip	68 lbs	B134B40	Add \$ 168.00
ALR9494	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs		
<b>TURF</b>				
ALR8890A	F-TIRE 23x8.50-12 R3 Titan Multi Trac	36 lbs	B68B80	Add \$ 86.00
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs		

<sup>†</sup> See Tire Section for Individual Tire Pricing and Information

\* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L3901F		TIRES AND WHEELS (priced per piece)			
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST PRICE	
<b>AG</b>					
ALR8865*	F-TIRE 5.00-15 F2 Goodyear Triple Rib	28 lbs	B106B40	\$	133.00
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs	B390B40	\$	488.00
ALR8852A	F-TIRE 7.5L-15 F2 Firestone Guide Grip	68 lbs	B173B60	\$	217.00
ALR9494	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs	B390B40	\$	488.00
<b>TURF</b>					
ALR8890A	F-TIRE 23x8.50-12 R3 Titan Multi Trac	36 lbs	B148B00	\$	185.00
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs	B383B20	\$	479.00



**L01 Series L3901 DT / HST**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***				
L3901DT	4WD Compact Tractor - 2 Post Foldable ROPS	K18B275B20	2343 lbs	\$22,844.00
L3901HST	4WD Compact Tractor - 2 Post Foldable ROPS	K19B101B60	2381 lbs	\$23,877.00

L3901 DT/HST		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>TIRES AND WHEELS<sup>†</sup></b>				
<b>AG</b>				
ALR8866D*	F-TIRE 7.2-16 R1 Goodyear Power Torque	52 lbs		In Base Price
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs		
<b>TURF</b>				
ALR8893A	F-TIRE 25x8.50-14 HF-1Goodyear SofTrac	53 lbs	B110B40	Less \$ (138.00)
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs		
<b>INDUSTRIAL</b>				
AMR8977A	F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL	48 lbs	B582B40	Add \$ 728.00
ALR8809	R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset	201 lbs		
<b>AG/INDUSTRIAL HYBRID</b>				
ALR8596	FT TITN 29X9.50-15 R14T STL 6BLT	60 lbs	B838B40	Add \$ 1,048.00
ALR8597	RT TITN 43X16.00-20NHS R14T STL 6BLT	200 lbs		
ALR8696	F-TIRE 27X8.50-15 R14T GOODYEAR SST	60 lbs	B712B00	Add \$ 890.00
ALR8697	R-TIRE 15-19.5 R14T GOODYEAR SST	200 lbs		

<sup>†</sup> See Tire Section for Individual Tire Pricing and Information  
\* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L3901 DT/HST		TIRES AND WHEELS (priced per piece)		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST PRICE
<b>AG</b>				
ALR8866D*	F-TIRE 7.2-16 R1 Goodyear Power Torque	52 lbs	B234B40	\$ 293.00
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs	B390B40	\$ 488.00
<b>TURF</b>				
ALR8893A	F-TIRE 25x8.50-14 HF-1Goodyear SofTrac	53 lbs	B186B40	\$ 233.00
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs	B383B20	\$ 479.00
<b>INDUSTRIAL</b>				
AMR8977A	F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL	48 lbs	B224B80	\$ 281.00
ALR8809	R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset	201 lbs	B691B20	\$ 864.00
<b>AG/INDUSTRIAL HYBRID</b>				
ALR8596	FT TITN 29X9.50-15 R14T STL 6BLT	60 lbs	B274B40	\$ 343.00
ALR8597	RT TITN 43X16.00-20NHS R14T STL 6BLT	200 lbs	B769B60	\$ 962.00
ALR8696	F-TIRE 27X8.50-15 R14T GOODYEAR SST	60 lbs	B248B00	\$ 310.00
ALR8697	R-TIRE 15-19.5 R14T GOODYEAR SST	200 lbs	B732B80	\$ 916.00



**L02 Series**

**L3902 DT / HST**

**\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\***

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 3 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 45 Amps  
 12V – 580 CCA (DT) / 600 CCA (HST)  
 Optional Dual Air Cleaner Element  
 Electronic Throttle

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 10.1 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At lift Point 1985 lbs.  
 24" Behind 1433 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Transmission Driven with  
 Over-Running Clutch - DT  
 Live Independent PTO with  
 Hydraulic Clutch - HST  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2425 Eng. Rpm - DT  
 540 rpm @ 2470 Eng. Rpm - HST

**TRANSMISSION - DT**

Synchro Shuttle with Sliding Gear  
 Rear Differential Lock  
 8 Forward Speeds  
 4 Reverse Speeds  
 Dual Stage Clutch  
 Wet Disc Brakes

**TRANSMISSION - HST**

Hydrostatic Drive  
 Rear Differential Lock  
 3 Ranges  
 Optional Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank	11.1 gal.
Cooling System	6.3 qts.
Crankcase	7.1 qts.
Transmission and Hydraulics	
DT	7.5 gal.
HST	6.2 gal.
Front Axle	4.8 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Oil Pressure  
 Fuel Gauge  
 Coolant Temperature

**FEATURES**

Illuminated Instrument Panel  
 Steel Hood and Fenders  
 Tool Box  
 Cup Holder  
 Left Hand Fender Grip  
 Default to Auto Regen; w/ Parked and  
 Inhibit Buttons for DPF

**SAFETY EQUIPMENT**

2-Post Foldable ROPS w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

**Model Specifications**

<b>L3902DT 2WD</b>		<b>L3902HST 2WD</b>	
SAE Gross HP:	37.5	SAE Gross HP:	37.5
Engine Net HP:	36.3	Engine Net HP:	36.3
PTO HP:	32.1	PTO HP:	30.6
Engine Model:	D1803	Engine Model:	D1803
Displacement:	111.4 Cu. In.	Displacement:	111.4 Cu. In.



**L02 Series L3902 DT / HST**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***				
L3902DT	4WD Compact Tractor - 2 Post Foldable ROPS	K19B737B60	2899 lbs	\$24,672.00
L3902HST	4WD Compact Tractor - 2 Post Foldable ROPS	K20B756B00	2921 lbs	\$25,945.00

L3902 DT/HST		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>TIRES AND WHEELS<sup>†</sup></b>				
<b>AG</b>				
ALR8866D*	F-TIRE 7.2-16 R1 Goodyear Power Torque	52 lbs		In Base Price
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs		
<b>TURF</b>				
ALR8893A	F-TIRE 25x8.50-14 HF-1Goodyear SofTrac	53 lbs	B110B40	Less \$ (138.00)
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs		
<b>INDUSTRIAL</b>				
AMR8977A	F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL	48 lbs	B582B40	Add \$ 728.00
ALR8809	R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset	201 lbs		
<b>AG/INDUSTRIAL HYBRID</b>				
ALR8596	FT TITN 29X9.50-15 R14T STL 6BLT	60 lbs	B838B40	Add \$ 1,048.00
ALR8597	RT TITN 43X16.00-20NHS R14T STL 6BLT	200 lbs		
ALR8696	F-TIRE 27X8.50-15 R14T GOODYEAR SST	60 lbs	B712B00	Add \$ 890.00
ALR8697	R-TIRE 15-19.5 R14T GOODYEAR SST	200 lbs		

<sup>†</sup> See Tire Section for Individual Tire Pricing and Information  
\* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L3902 DT/HST		TIRES AND WHEELS (priced per piece)		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST PRICE
<b>AG</b>				
ALR8866D*	F-TIRE 7.2-16 R1 Goodyear Power Torque	52 lbs	B234B40	\$ 293.00
ALR9494*	R-TIRE 11.2-24 R1 Hi Pwr Lug 2.94"offset	159 lbs	B390B40	\$ 488.00
<b>TURF</b>				
ALR8893A	F-TIRE 25x8.50-14 HF-1Goodyear SofTrac	53 lbs	B186B40	\$ 233.00
ALR8804A	R-TIRE 13.6-16 R3 Titan Multi Trac TL	127 lbs	B383B20	\$ 479.00
<b>INDUSTRIAL</b>				
AMR8977A	F-TIRE 27x8.50-15 R4 Titan Trac Lodr TL	48 lbs	B224B80	\$ 281.00
ALR8809	R-TIRE 15-19.5 R4 Trac Ldr 3.6"offset	201 lbs	B691B20	\$ 864.00
<b>AG/INDUSTRIAL HYBRID</b>				
ALR8596	FT TITN 29X9.50-15 R14T STL 6BLT	60 lbs	B274B40	\$ 343.00
ALR8597	RT TITN 43X16.00-20NHS R14T STL 6BLT	200 lbs	B769B60	\$ 962.00
ALR8696	F-TIRE 27X8.50-15 R14T GOODYEAR SST	60 lbs	B248B00	\$ 310.00
ALR8697	R-TIRE 15-19.5 R14T GOODYEAR SST	200 lbs	B732B80	\$ 916.00





**L01 Series**

**L4701 F / DT / HST**

**\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\***

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 4 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 40 Amps  
 12V – 600 CCA  
 Dual Air Cleaner Element  
 Electronic Throttle

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 13.5 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At lift Point 2870 lbs.  
 24" Behind 2310 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2475 Eng. Rpm - F / DT  
 540 rpm @ 2640 Eng. Rpm - HST  
 Electric over Hydraulic PTO Switch - HST

**TRANSMISSION - F / DT**

Synchro Shuttle with Constant Mesh  
 Rear Differential Lock  
 8 Forward Speeds  
 4 Reverse Speeds  
 Single-Stage Clutch  
 Wet Disc Brakes

**TRANSMISSION - HST**

Hydrostatic Drive  
 Rear Differential Lock  
 3 Ranges  
 Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Tubular Steel Beam 2WD  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 6.9 qts.  
 Crankcase 8.7 qts.  
 Transmission and  
 Hydraulics 10.6 gal.  
 Front Axle 6.9 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Oil Pressure  
 Fuel Gauge  
 Coolant Temperature

**FEATURES**

Illuminated Instrument Panel  
 Steel Hood and Fenders  
 Tool Box  
 Cup Holder  
 Left Hand Fender Grip  
 Default to Auto Regen; w/ Parked and  
 Inhibit Buttons for DPF

**SAFETY EQUIPMENT**

2-Post Foldable ROPS w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

**Model Specifications**

<u>L4701F 2WD</u>	<u>L4701DT 2WD</u>	<u>L4701HST 2WD</u>
SAE Gross HP: 47.3	SAE Gross HP: 47.3	SAE Gross HP: 47.3
Engine Net HP: 44.8	Engine Net HP: 44.8	Engine Net HP: 44.8
PTO HP: 39.3	PTO HP: 39.3	PTO HP: 37.8
Engine Model: V2403	Engine Model: V2403	Engine Model: V2403
Displacement: 148.5 Cu. In.	Displacement: 148.5 Cu. In.	Displacement: 148.5 Cu. In.





**L01 Series L4701 DT / HST**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***				
L4701DT	4WD Compact Tractor - 2 Post Foldable ROPS	K23B174B40	2760 lbs	\$28,968.00
L4701HST	4WD Compact Tractor - 2 Post Foldable ROPS	K24B454B40	2840 lbs	\$30,568.00

L4701 DT/HST		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>TIRES AND WHEELS<sup>†</sup></b>				
<b>AG</b>				
ABR8753B*	F-TIRE 8.3-16 R1 OTR Traction Master	64 lbs		In Base Price
ALR6809B	R-TIRE 14.9-24 R1 Titan Hi Power Lug TL	231 lbs		
<b>TURF</b>				
ALR6828A	FT TITN 27X10.50-151MP R3 STL 6BLT	70 lbs	B488B00	Add \$ 610.00
ALR6803	R-TIRE 44x18-20 R3 Titan MultiTrac 6stud	229 lbs		
ALR6818A	F-TIRE LSW305R343 R3 Titan Grizz LSW 430	70 lbs	B643B20	Add \$ 804.00
ALR6817	R-TIRE LSW610R470 R3 Grizz LSW 430 6stud	227 lbs		
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B484B80	Add \$ 606.00
ALR6807	R-TIRE 17.5L-24 R4 TITAN INDUSTRIAL	259 lbs		

<sup>†</sup> See Tire Section for Individual Tire Pricing and Information  
 \* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L4701 DT/HST		TIRES AND WHEELS (priced per piece)		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST PRICE
<b>AG</b>				
ABR8753B*	F-TIRE 8.3-16 R1 OTR Traction Master	64 lbs	B220B80	\$ 276.00
ALR6809B	R-TIRE 14.9-24 R1 Titan Hi Power Lug TL	231 lbs	B587B20	\$ 734.00
<b>TURF</b>				
ALR6828A	FT TITN 27X10.50-151MP R3 STL 6BLT	70 lbs	B290B40	\$ 363.00
ALR6803	R-TIRE 44x18-20 R3 Titan MultiTrac 6stud	229 lbs	B761B60	\$ 952.00
ALR6818A	F-TIRE LSW305R343 R3 Titan Grizz LSW 430	70 lbs	B324B80	\$ 406.00
ALR6817	R-TIRE LSW610R470 R3 Grizz LSW 430 6stud	227 lbs	B804B80	\$ 1,006.00
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B324B80	\$ 406.00
ALR6807	R-TIRE 17.5L-24 R4 TITAN INDUSTRIAL	259 lbs	B725B60	\$ 907.00



**Standard L Series L2501 / L3301 / L3302 / L3901 / L3902 / L4701**

**DEALER INSTALLED ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>HYDRAULICS/HITCH/DRAWBAR</b>				
<b>HYDRAULIC REAR REMOTE VALVES - L2501/ L3301 / L3302 / L3901 / L3902</b>				
L7291	Base Kit and 1st Lever for L3302 & L3902 Requires L7231A, L7232A, L7233A or L7234A Not compatible with previous non "A" version valves If <u>no</u> Loader, Adapter Kit required If Backhoe, Bulkhead Bracket and Hose Extension are required	K624L00	25 lbs	\$780.00
L7292	2nd Position Stacking Kit and 2nd Lever for L3302 & L3902 Requires L7291 Base Kit and 1st Lever Not compatible with previous non "A" version valves Requires L7231A or L7233A or L7234A Not compatible with L7232A Float Detent Valve	K310L40	13 lbs	\$388.00
L7293	3rd Position Stacking Kit and 3rd Lever for L3302 & L3902 Requires Base Kit and 2nd Position Kit Not compatible with previous non "A" version valves Requires L7231A or L7233A or L7234A Not compatible with L7232A Float Detent Valve	K310L40	13 lbs	\$388.00
L7211B	Base Kit and 1st Lever for L2501, L3301 & L3901 Requires Spring Center or Float or Self-Canceling Detent Valve Not compatible with previous non "A" version valves If <u>no</u> Loader, Adapter Kit required If Backhoe, Bulkhead Bracket and Hose Extension are required	K624L00	25 lbs	\$780.00
L7212A	2nd Position Stacking Kit and 2nd Lever for L2501, L3301 & L3901 Requires Base Kit Not compatible with previous non "A" version valves Requires Spring Center or Float or Self-Canceling Detent Valve	K310L40	6 lbs	\$388.00
L7213A	3rd Position Stacking Kit and 3rd Lever for L2501, L3301 & L3901 Requires Base Kit and 2nd Position Kit Not compatible with previous non "A" version valves Requires Spring Center or Float or Self-Canceling Detent Valve	K310L40	6 lbs	\$388.00
L7231A	Spring Center Valve, No Detent	K164L00	4 lbs	\$205.00
L7232A	FD (Float Detent) Valve Section (4-Position)	K298L40	5 lbs	\$373.00
L7233A	SCD (Self-Canceling Detent) Valve Section	K337L60	6 lbs	\$422.00
L7234A	Locking Detent Valve	K299L20	5 lbs	\$374.00
<b>ADAPTER KIT</b>				
L7344A	Adapter Kit for Non-Loader Applications Requires Base Kit	K120L80	5 lbs	\$151.00
<b>ADDITIONAL REQUIREMENTS</b>				
77700-10635	Bulkhead Bracket	(Order from the Parts Department)		
77700-03798	Bulkhead Bracket Mount (Not compatible with "A" Version)	(Order from the Parts Department)		
77700-10636	Hose Extension 2 per valve section	(Order from the Parts Department)		



**Standard L Series L2501 / L3301 / L3302 / L3901 / L3902 / L4701**

**DEALER INSTALLED ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>HYDRAULICS/HITCH/DRAWBAR</b>				
<b>HYDRAULIC REAR REMOTE VALVES - L4701, OPTION 1: NOT COMPATIBLE WITH DRAFT CONTROL</b>				
L721A	Base Kit and 1st Lever Requires Spring Center or Float or Self-Canceling Detent Valve Not compatible with Draft Control Kit	K528L80	17 lbs	\$661.00
L7222	2nd Position Stacking Kit and 2nd Lever Requires Base Kit Requires Spring Center or Float or Self-Canceling Detent Valve Not compatible with Draft Control Kit	K291L20	6 lbs	\$364.00
L7223	3rd Position Stacking Kit and 3rd Lever Requires Base Kit and 2nd Position Kit Requires Spring Center or Float or Self-Canceling Detent Valve Not compatible with Draft Control Kit	K291L20	6 lbs	\$364.00
L7231A	Spring Center Valve, No Detent Not compatible with Draft Control Kit	K164L00	4 lbs	\$205.00
L7232A	FD (Float Detent) Valve Section (4-Position) Not compatible with Draft Control Kit	K298L40	5 lbs	\$373.00
L7233A	SCD (Self-Canceling Detent) Valve Section Not compatible with Draft Control Kit	K337L60	6 lbs	\$422.00
L7234A	Locking Detent Valve Not compatible with Draft Control Kit	K299L20	5 lbs	\$374.00
<b>HYDRAULIC REAR REMOTE VALVES - L4701, OPTION 2: COMPATIBLE WITH DRAFT CONTROL</b>				
L8560	Base Kit and 1st Lever Requires Double Acting Valve If Backhoe, Stays, Bolts, Hose and Manual are required	K472L80	16 lbs	\$591.00
L8562A	2nd Position Stacking Kit and 2nd Lever Requires Base Kit Requires Double Acting or Float Detent Valve	K229L60	8 lbs	\$287.00
L8563A	3rd Position Stacking Kit and 3rd Lever Requires Base Kit and 2nd Position Kit Requires Double Acting or Float Detent Valve	K229L60	8 lbs	\$287.00
L8303	Double Acting Valve	K221L60	4 lbs	\$277.00
L8304	FD (Float Detent) Valve Section (4-Position)	K278L40	4 lbs	\$348.00
<b>ADDITIONAL REQUIREMENTS</b>				
-	Stays	(Order from the Parts Department)		
-	Bolts	(Order from the Parts Department)		
-	Hose	(Order from the Parts Department)		



**Standard L Series L2501 / L3301 / L3302 / L3901 / L3902 / L4701**

**DEALER INSTALLED ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>HYDRAULICS/HITCH/DRAWBAR</b>				
<b>DRAFT CONTROL</b>				
L8311C	Draft Control Kit for L4701 only Not Compatible with L2221A, L2222, L2223 Rear Remote Lever Kits	K425L60	25 lbs	\$532.00
<b>DRAWBAR OPTIONS</b>				
BL6820	Drop Drawbar for L2501 / L3301/ L3302 / L3901 / L3902	K70B40	17 lbs	\$88.00
L6830	Drop Drawbar for L4701	K84L80	22 lbs	\$106.00
L9496G	Drawbar Clevis	K76L00	8 lbs	\$95.00
L6821	Drawbar Clevis	K68L80	8 lbs	\$86.00
LMX6800	Clevis Kit for L-MX Drop Drawbars	K43A20	7 lbs	\$54.00
<b>TELESCOPING STABILIZERS</b>				
L8430	Telescopic Stabilizers for L2501 / L3301/ L3302 / L3901 / L3902 Standard for L4701	K161L60	13 lbs	\$202.00
<b>TOP-N-TILT KIT</b>				
L8372	Top-N-Tilt Kit Requires 2 Double Acting Remote Hydraulic Valves Not Compatible with Backhoe Couplers Not Included	K697L60	44 lbs	\$872.00
<b>TRAILER HARNESS</b>				
L2219	7-Pin Electrical Trailer Harness NOTE: L3302/L3902 Models only	K92L80	16 lbs	\$116.00
<b>ROPS ACCESSORIES</b>				
<b>CANOPY</b>				
E1133	Plastic Canopy	K404B80	63 lbs	\$506.00
E1134	Fiberglass Canopy Requires Mounting Kit	K360M80	63 lbs	\$451.00
E1136	Fiberglass Canopy Mounting Kit	K178M40	29 lbs	\$223.00
<b>FRONT WORK LIGHT</b>				
E1138	Front Work Light Kit for Fiberglass Canopy Includes 2 Lights	K136A80	3 lbs	\$171.00
<b>REAR WORK LIGHT</b>				
L8327	Rear Work Light Kit (1 Light)	K78L40	4 lbs	\$98.00
<b>BALLAST</b>				
<b>BALLAST BOX</b>				
L8170	Ballast Box - 3-Point Mount Up to 1000 lbs of total weight with sand	K460L00	168 lbs	\$575.00
<b>FRONT WEIGHT BRACKETS</b>				
MX8068	Weight Bracket - up to 7 Weights, Standard for 2WD models Requires 1 BL8014 for all weight stacks of BL8069 Not Compatible with Grill Guard installed	K88M00	29 lbs	\$110.00
<b>FRONT SUITCASE WEIGHTS</b>				
BL8069	Suitcase Weight (55 lbs. Each) Requires 1 BL8049 Bolt Kit per Every Weight MAX 4 Weights Allowed w/ Grill Guard	K64B80	55 lbs	\$81.00
<b>FRONT WEIGHT BOLT KITS</b>				
BL8049	Weight Bolt Kit - 1 Kit Per Every BL8069 Weight	K6B40	1 lbs	\$8.00
BL8014	Thread Bolt & Spacing Kit 1 Required on MX8068 When Stacking BL8069 Weights	K25B60	5 lbs	\$32.00
<b>REAR WHEEL WEIGHTS</b>				
L8066A	Rear Wheel Weight Set (64 lbs. Each), 2 per set 3 Weight per Wheel Not Compatible with Turf Tires or ALR8809 Tire Combinations. Not Compatible with ALR8697 R14 Tire Combinations. Requires one Weight Bolt Kit	K116L00	128 lbs	\$145.00
<b>REAR WEIGHT BOLT KITS</b>				
L8067A	Weight Bolt Kits - 1 Kit allows up to 3 Weights per Side	K29L60	5 lbs	\$37.00





**Standard L Series L2501 / L3301 / L3302 / L3901 / L3902 / L4701**

**FRONT LOADERS**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>FRONT END LOADER</b>				
LA525	Front End Loader-Heavy Duty for L2501/L3301/L3302/L3901/L3902 Includes Mounting Kit, Valve, Grill Guard, Hydraulic Block and 2-Lever Type Quick Coupler Requires Bucket NOTE: Subject to Availability	K3L788L80	876 lbs	\$4,736.00
LA526	Front End Loader-Heavy Duty for L2501/L3301/L3302/L3901/L3902 Includes Mounting Kit, Valve, Grill Guard, Hydraulic Block and 2-Lever Type Quick Coupler Includes Built In Mounting Points for Land Pride 3rd Function Kit Requires Bucket	K4L184L00	882 lbs	\$5,230.00
LA525FL	Front End Loader-Heavy Duty for L2501/L3301/L3302/L3901/L3902 Includes Mounting Kit, Valve, Grill Guard, and 60" Bucket Cylinder and Hoses are Pre-Installed Bucket is not returnable NOTE: Subject to Availability	K3L827L20	990 lbs	\$4,784.00
LA526FL	Front End Loader-Heavy Duty for L2501/L3301/L3302/L3901/L3902 Includes Mounting Kit, Valve, Grill Guard, and 60" Bucket Cylinder and Hoses are Pre-Installed Includes Built In Mounting Points for Land Pride 3rd Function Kit Bucket is not returnable	K4L224L00	1032 lbs	\$5,280.00
<b>PIN-ON BUCKETS</b>				
L2242A	60" Pin-On Bucket	K529L60	360 lbs	\$662.00
<b>QUICK ATTACH COUPLER &amp; BUCKETS</b>				
L2217	2-Lever Type Quick Coupler for LA526 NOTE: Required for LA525 if also ordering replacement bucket L2248	K417L60	90 lbs	\$522.00
L2248	66" Quick Attach Bucket for LA526 NOTE: If ordering for LA525, L2217 is required. Not compatible with L2216	K636L80	212 lbs	\$796.00
L2256	66" Square Back QA Bucket	K591L20	212 lbs	\$739.00
L2130	Bucket Level Indicator	K60L80	5 lbs	\$76.00
TL2143	60" Bolt On Cutting Edge Requires L2242A 60" Pin-On Bucket	K205B60	60 lbs	\$257.00
TL1756	66" Bolt On Cutting Edge Requires L2248 66" Quick Attach Bucket	K200L00	65 lbs	\$250.00
<b>QUICK ATTACH PALLET FORKS</b>				
L2237	Bale Spear, 2-Lever Quick Coupler	K608L80	165 lbs	\$761.00
L2238	Pallet Fork Frame, 2-Lever Quick Coupler Requires Pallet Forks	K642L40	165 lbs	\$803.00
K9048	36" Pallet Forks	K386L40	176 lbs	\$483.00
LA765	Front End Loader - Heavy Duty for L4701 Includes Mounting Kit, Valve, Grill Guard, and 2-Lever Type Quick Coupler Requires Bucket	K4L780L00	1019 lbs	\$5,975.00
<b>QUICK ATTACH COUPLER &amp; BUCKETS</b>				
L2235A	72" Square Back QA Bucket	K654L40	346 lbs	\$818.00
L2236	72" Light Material QA Bucket	K616L00	323 lbs	\$770.00
L2296	72" Heavy Duty QA Bucket Requires Bolt On Cutting Edge	K1L016L00	400 lbs	\$1,270.00
TL1748	Bolt On Cutting Edge for 72" HD Bucket	K215L20	70 lbs	\$269.00
L2130	Bucket Level Indicator	K60L80	5 lbs	\$76.00
<b>QUICK ATTACH PALLET FORKS</b>				
L2237	Bale Spear, 2-Lever Quick Coupler	K608L80	165 lbs	\$761.00
L2238	Pallet Fork Frame, 2-Lever Quick Coupler Requires Pallet Forks	K642L40	165 lbs	\$803.00
K9048	36" Pallet Forks	K386L40	176 lbs	\$483.00
<b>OPTIONAL FRONT LOADER KITS</b>				
380-152A	3rd Function Valve Kit from Land Pride		(Order from Land Pride)	





**Standard L Series L2501 / L3301 / L3302 / L3901 / L3902 / L4701**

**BACKHOES AND ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>BACKHOES AND ACCESSORIES</b>				
<b>Requires a Front End Loader to be mounted when Backhoe is attached.</b>				
BH77	4-Pt. Mounted Quick Attach Backhoe for L2501 / L3301 / L3302 / L3901 / L3902 Requires Sub Frame Kit Not Compatible with Top-N-Tilt Kits Not Compatible with Cab Model	K6B587B20	1077 lbs	\$8,234.00
<b>SUB FRAME KITS</b>				
BH4988	Sub frame Kit for L2501 / L3301 / L3302 / L3901 / L3902 Requires Front End Loader	K714L40	213 lbs	\$893.00
<b>PIN-ON BUCKETS</b>				
BT1950A	10" Bucket — 3 Teeth	K394B40	63 lbs	\$493.00
BT1951A	12" Bucket — 3 Teeth	K464B80	69 lbs	\$581.00
BT1952A	16" Bucket — 4 Teeth	K615B20	82 lbs	\$769.00
BT1953A	24" Bucket — 5 Teeth	K804B00	118 lbs	\$1,005.00
<b>BACKHOE ACCESSORIES</b>				
BH1976	6 Position Mechanical Thumb	K450B40	51 lbs	\$563.00
L9467	Rubber Stabilizer Flip Pads Two required per Backhoe	K118L40	15 lbs	\$148.00
BH92	4-Pt. Mounted Quick Attach Backhoe for L4701 Requires Sub Frame Kit and Front Loader Not Compatible with Top-N-Tilt Kits	K7L444L00	1696 lbs	\$9,305.00
<b>SUB FRAME KITS</b>				
BH4946	Sub frame Kit for L4701	K1L080L00	330 lbs	\$1,350.00
<b>PIN-ON BUCKETS</b>				
BT3001	12" Bucket — 3 Teeth	K622L40	109 lbs	\$778.00
BT3002A	16" Bucket — 3 Teeth	K705L60	130 lbs	\$882.00
BT3003A	18" Bucket — 4 Teeth	K752L00	141 lbs	\$940.00
BT3004	24" Bucket — 5 Teeth	K875L20	172 lbs	\$1,094.00
BT3005A	30" Bucket — 6 Teeth	K1L009L60	205 lbs	\$1,262.00
BT3006	36" Bucket — 7 Teeth	K1L128L00	226 lbs	\$1,410.00
<b>QUICK ATTACH COUPLER &amp; BUCKETS</b>				
BT4550	Quick Coupler for BH92	K625L60	55 lbs	\$782.00
BT4552	12" Bucket	K754L40	117 lbs	\$943.00
BT4553	16" Bucket	K797L60	135 lbs	\$997.00
BT4554	18" Bucket	K838L40	144 lbs	\$1,048.00
BT4555	24" Bucket	K990L40	176 lbs	\$1,238.00
BT4557	36" Bucket	K1L262L40	223 lbs	\$1,578.00
<b>BACKHOE ACCESSORIES</b>				
BH4948	Hydraulic Valve Kit	K834L40	23 lbs	\$1,043.00
BT4598	Hydraulic Thumb Requires Hydraulic Valve Kit	K1L927L20	142 lbs	\$2,409.00
BH4949	6 Position Mechanical Thumb	K846L40	141 lbs	\$1,058.00
L9467	Rubber Stabilizer Flip Pads Two required per Backhoe	K118L40	15 lbs	\$148.00



**Standard L Series L2501 / L3301 / L3302 / L3901 / L3902 / L4701**

**SNOW BLOWERS**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>REAR MOUNT SNOW BLOWERS AND ACCESSORIES</b>				
<b>REAR MOUNT SNOW BLOWER</b>				
BLMX3164	64" Two-Stage Commercial Snowblower Mounts to Category I 3-Point Hitch Requires Manual Chute Rotator or Hydraulic Chute Rotator	K2B914B40	681 lbs	\$3,643.00
LMX3174	74" Two-Stage Commercial Snowblower Mounts to Category I, II, & III 3-Point Hitches Requires Manual Chute Rotator or Hydraulic Chute Rotator	K3L675L20	760 lbs	\$4,594.00
<b>REAR MOUNT SNOW BLOWER OPTIONS</b>				
BL2665	Manual Chute Rotator	K165B60	11 lbs	\$207.00
BL6399	Hydraulic Chute Rotator Requires 1 Set of Hydraulic Rear Remote Valves	K752B00	20 lbs	\$940.00
BL2666A	Hydraulic Chute Deflector Kit Requires Hydraulic Chute Rotator Includes Electric Selector Valve	K920B80	22 lbs	\$1,151.00
B2516A	Electric Chute Deflector	K608B80	9 lbs	\$761.00
L2177	Width Extension Kit, adds 5" overall cut	K108L80	27 lbs	\$136.00



**Grand L 60 Series L3560 DT / GST / HST**

**\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\***

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 3 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 40 Amps  
 12V – 582 CCA  
 Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 Total Hyd. Flow:  
     DT / GST - 13.2 gpm  
     HST - 12.8 gpm

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At Lift Point 3748 lbs.  
 24" Behind 2646 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm

**TRANSMISSION - DT**

4 Speed Manual w/Synchro Main  
 and Synchro Shuttle  
 Rear Differential Lock  
 2 Range Hi-Lo  
 8 Forward Speeds  
 8 Reverse Speeds  
 Single-Stage Clutch  
 Wet Disc Brakes

**TRANSMISSION - GST**

Glide Shift w/Synchro Shuttle  
 Rear Differential Lock  
 12 Forward Speeds  
 8 Reverse Speeds  
 Single-Stage Clutch  
 Wet Disc Brakes

**TRANSMISSION - HST**

Hydrostatic Drive - HST PLUS  
 Rear Differential Lock  
 3 Ranges  
 Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 7.9 qts.  
 Crankcase 7.1 qts.  
 Transmission and  
 Hydraulics 11.1 gal.  
 Front Axle 6.9 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols  
 HST Mode Selection

**FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Telescoping Lower Links  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder

**HST-SPECIFIC FEATURES**

Auto Throttle Advance  
 Hydro Dual Speed (H-DS)  
 HST Response Control  
 Throttle-Up Switch

**SAFETY EQUIPMENT**

2-Post Foldable ROPS w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

Model Specifications			
<b><u>L3560DT 4WD</u></b>		<b><u>L3560GST 4WD</u></b>	
SAE Gross HP:	37.0	SAE Gross HP:	37.0
Engine Net HP:	35.0	Engine Net HP:	35.0
PTO HP:	29.5	PTO HP:	29.5
Engine Model:	D1803	Engine Model:	D1803
Displacement:	111.4 Cu. In.	Displacement:	111.4 Cu. In.
		<b><u>L3560HST 4WD</u></b>	
		SAE Gross HP:	37.0
		Engine Net HP:	35.0
		PTO HP:	28
		Engine Model:	D1803
		Displacement:	111.4 Cu. In.



**Grand L 60 Series L3560HSTC**

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 3 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 60 Amps  
 12V – 582 CCA  
 Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 12.8 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At Lift Point 3748 lbs.  
 24" Behind 2646 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm  
 Electric over Hydraulic PTO Switch

**TRANSMISSION**

Hydrostatic Drive - HST PLUS  
 Rear Differential Lock  
 3 Forward Ranges  
 3 Reverse Ranges  
 Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 7.9 qts.  
 Crankcase 7.1 qts.  
 Transmission and  
 Hydraulics 11.1 gal.  
 Front Axle 6.9 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols  
 HST Mode Selection

**FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Telescoping Lower Links  
 2 Front Work Lights  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder  
 Auto Throttle Advance  
 Hydro Dual Speed (H-DS)  
 HST Response Control  
 Throttle-Up Switch  
 Front Wiper w/Washer  
 Interior Light  
 AC/Heater with Internal/External  
 Ventilation  
 Speakers and Radio Pre-Wired  
 Horn

**SAFETY EQUIPMENT**

ROPS Certified Cab w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

Model Specifications	
<b>L3560HSTC 4WD</b>	
SAE Gross HP:	37.0
Engine Net HP:	35.0
PTO HP:	28.0
Engine Model:	D1803
Displacement:	111.4 Cu. In.



**Grand L 60 Series L3560HST-LE / L3560HSTC-LE**

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 3 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 60 Amps  
 12V – 582 CCA  
 Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 12.8 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At Lift Point 3748 lbs.  
 24" Behind 2646 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm  
 Electric over Hydraulic PTO Switch

**TRANSMISSION**

Hydrostatic Drive - HST PLUS  
 Rear Differential Lock  
 3 Forward Ranges  
 3 Reverse Ranges  
 Wet Disc Brakes  
 Auto Throttle Advance  
 Hydro Dual Speed (H-DS)  
 HST Response Control  
 Throttle-Up Switch

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 7.9 qts.  
 Crankcase 7.1 qts.  
 Transmission and  
 Hydraulics 11.1 gal.  
 Front Axle 6.9 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols  
 HST Mode Selection

**ROPS FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Check Chains  
 Telescoping Lower Links  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder

**CAB FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip LH Step Only  
 ISO Mounted Platform  
 Telescoping Stabilizers & Lower Links  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder  
 Front Wiper w/Washer  
 Interior Light  
 AC/Heater w/ Internal/External  
 Ventilation  
 Speakers and Radio Pre-Wired  
 Horn

**SAFETY EQUIPMENT**

ROPS Certified Cab w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign  
 Rear View Mirror

Model Specifications	
<b>L3560HST-LE 4WD</b>	<b>L3560HSTC-LE 4WD</b>
SAE Gross HP: 37.0	SAE Gross HP: 37.0
Engine Net HP: 35.0	Engine Net HP: 35.0
PTO HP: 28.0	PTO HP: 28.0
Engine Model: D1803	Engine Model: D1803
Displacement: 111.4 Cu. In.	Displacement: 111.4 Cu. In.



**Grand L 60 Series L3560 DT / GST / HST / HSTC**

DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***			
L3560DT	4WD Compact Tractor - 2 Post Foldable ROPS	K21B312B80	3210 lbs \$26,641.00
L3560GST	4WD Compact Tractor - 2 Post Foldable ROPS	K22B364B00	3249 lbs \$27,955.00
L3560HST	4WD Compact Tractor - 2 Post Foldable ROPS	K22B685B60	3249 lbs \$28,357.00
L3560HSTC	4WD Compact Tractor - ROPS Certified Factory Cab	K30B235B20	3512 lbs \$37,794.00
L3560HST-LE	4WD Compact Tractor - 4WD HST ROPS Limited Tractor	K21B323B20	3249 lbs \$26,654.00
L3560HSTC-LE	4WD Compact Tractor - 4WD HST Cab Limited Tractor	K27B712B80	3512 lbs \$34,641.00

L3560 DT/GST/HST/HSTC/HSTC-LE		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST PRICE
<b>TIRES AND WHEELS†</b>				
<b>AG</b>				
ALR8866D*	F-TIRE 7.2-16 R1 Goodyear Power Torque	52 lbs		In Base Price
ALR8821C*	R-TIRE 12.4-24 R1 Firestone SAT II	156 lbs		
<b>TURF</b>				
ALR8868	F-TIRE 27x8.50-15 R3 Goodyear SoftTrac	53 lbs	B1B60	Add \$ 2.00
LR6804	R-TIRE 355/80D20 B-Stone Pillow Diam 4	188 lbs		
ALR8898	F-TIRE 27x10.50-15 R3 Turf Sp Armstg Whl	70 lbs	B937B60	Add \$ 1,172.00
ALR6804	R-TIRE 41x18LL-16.1 R3 Galaxy Turf Spcl	132 lbs		
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B568B00	Add \$ 710.00
ALR8855	R-TIRE 420/70-24 R4 F-Stone All Trc Util	235 lbs		

† See Tire Section for Individual Tire Pricing and Information  
 \* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L3560 DT / GST / HST / HSTC		TIRES AND WHEELS (priced per piece)		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST PRICE
<b>AG</b>				
ALR8866D*	F-TIRE 7.2-16 R1 Goodyear Power Torque	52 lbs	B234B40	\$ 293.00
ALR8821C*	R-TIRE 12.4-24 R1 Firestone SAT II	156 lbs	B522B40	\$ 653.00
<b>TURF</b>				
ALR8868	F-TIRE 27x8.50-15 R3 Goodyear SoftTrac	53 lbs	B188B00	\$ 235.00
LR6801	R-TIRE 355/80D20 B-Stone Pillow Diam 1	188 lbs	B569B60	\$ 712.00
ALR6813	F-TIRE 29x12.50-15 R3 Titan Multi Trac	78 lbs	B268B00	\$ 335.00
ALR6803	R-TIRE 44x18-20 R3 Titan MultiTrac 6stud	229 lbs	B761B60	\$ 952.00
ALR8898	F-TIRE 27x10.50-15 R3 Turf Sp Armstg Whl	70 lbs	B372B00	\$ 465.00
ALR6804	R-TIRE 41x18LL-16.1 R3 Galaxy Turf Spcl	132 lbs	B853B60	\$ 1,067.00
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B324B80	\$ 406.00
ALR8855	R-TIRE 420/70-24 R4 F-Stone All Trc Util	235 lbs	B716B00	\$ 895.00



**Grand L 60 Series L4060 DT / GST / HST**

**\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\***

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 4 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 40 Amps  
 12V – 582 CCA  
 Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 Total Hyd. Flow:  
 DT / GST - 14.7 gpm  
 HST - 14.1 gpm

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At Lift Point 3858 lbs.  
 24" Behind 2756 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm  
 Electric over Hydraulic PTO Switch

**TRANSMISSION, DT**

4 Speed Manual w/Synchro Main  
 and Synchro Shuttle  
 Rear Differential Lock  
 2 Range Hi-Lo  
 8 Forward Speeds  
 8 Reverse Speeds  
 Single-Stage Clutch  
 Wet Disc Brakes

**TRANSMISSION, GST**

Glide Shift w/Synchro Shuttle  
 Rear Differential Lock  
 12 Forward Speeds  
 8 Reverse Speeds  
 Single-Stage Clutch  
 Wet Disc Brakes

**TRANSMISSION, HST**

Hydrostatic Drive - HST PLUS  
 Rear Differential Lock  
 3 Ranges  
 Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 7.9 qts.  
 Crankcase 8.7 qts.  
 Transmission and  
 Hydraulics 11.4 gal.  
 Front Axle 6.9 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols  
 HST Mode Selection

**FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Telescoping Lower Links  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder

**HST-SPECIFIC FEATURES**

Auto Throttle Advance  
 Hydro Dual Speed (H-DS)  
 HST Response Control  
 Throttle-Up Switch

**SAFETY EQUIPMENT**

2-Post Foldable ROPS w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

**Model Specifications**

<b>L4060DT 4WD</b>	<b>L4060GST 4WD</b>	<b>L4060HST 4WD</b>
SAE Gross HP: 42.0	SAE Gross HP: 42.0	SAE Gross HP: 42.0
Engine Net HP: 40.0	Engine Net HP: 40.0	Engine Net HP: 40.0
PTO HP: 34.0	PTO HP: 34.0	PTO HP: 32.5
Engine Model: V2403	Engine Model: V2403	Engine Model: V2403
Displacement: 148.5 Cu. In.	Displacement: 148.5 Cu. In.	Displacement: 148.5 Cu. In.



**Grand L 60 Series L4060HSTC**

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 4 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 60 Amps  
 12V – 582 CCA  
 Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 14.1 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At Lift Point 3858 lbs.  
 24" Behind 2756 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm  
 Electric over Hydraulic PTO Switch

**TRANSMISSION**

Hydrostatic Drive - HST PLUS  
 Rear Differential Lock  
 3 Ranges  
 Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 7.9 qts.  
 Crankcase 8.7 qts.  
 Transmission and  
 Hydraulics 11.4 gal.  
 Front Axle 6.9 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols  
 HST Mode Selection

**FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Telescoping Lower Links  
 2 Front Work Lights  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder  
 Auto Throttle Advance  
 Hydro Dual Speed (H-DS)  
 HST Response Control  
 Throttle-Up Switch  
 Front Wiper w/Washer  
 Interior Light  
 AC/Heater with Internal/External  
 Ventilation  
 Speakers and Radio Pre-Wired  
 Horn

**SAFETY EQUIPMENT**

ROPS Certified Cab w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

Model Specifications	
<b>L4060HSTC 4WD</b>	
SAE Gross HP:	42.0
Engine Net HP:	40.0
PTO HP:	32.5
Engine Model:	V2403
Displacement:	148.5 Cu. In.





**Grand L 60 Series L4060HST-LE / L4060HSTC-LE**

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 4 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 60 Amps  
 12V – 582 CCA  
 Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 14.1 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At Lift Point 3858 lbs.  
 24" Behind 2756 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm  
 Electric over Hydraulic PTO Switch

**TRANSMISSION**

Hydrostatic Drive - HST PLUS  
 Rear Differential Lock  
 3 Forward Ranges  
 3 Reverse Ranges  
 Wet Disc Brakes  
 Auto Throttle Advance  
 Hydro Dual Speed (H-DS)  
 HST Response Control  
 Throttle-Up Switch

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 7.9 qts.  
 Crankcase 8.7 qts.  
 Transmission and  
 Hydraulics 11.4 gal.  
 Front Axle 6.9 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols  
 HST Mode Selection

**ROPS FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Check Chains  
 Telescoping Lower Links  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder

**CAB FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip LH Step Only  
 ISO Mounted Platform  
 Telescoping Stabilizers & Lower Links  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder  
 Front Wiper w/Washer  
 Interior Light  
 AC/Heater w/ Internal/External  
 Ventilation  
 Speakers and Radio Pre-Wired  
 Horn

**SAFETY EQUIPMENT**

ROPS Certified Cab w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign  
 Rear View Mirror

Model Specifications	
<b>L4060HST-LE 4WD</b>	<b>L4060HSTC-LE 4WD</b>
SAE Gross HP: 42.0	SAE Gross HP: 42.0
Engine Net HP: 40.0	Engine Net HP: 40.0
PTO HP: 32.5	PTO HP: 32.5
Engine Model: V2403	Engine Model: V2403
Displacement: 148.5 Cu. In.	Displacement: 148.5 Cu. In.



**Grand L 60 Series L4060 DT / GST / HST / HSTC**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***				
L4060DT	4WD Compact Tractor - 2 Post Foldable ROPS	K24B327B20	3324 lbs	\$30,409.00
L4060GST	4WD Compact Tractor - 2 Post Foldable ROPS	K25B378B40	3346 lbs	\$31,723.00
L4060HST	4WD Compact Tractor - 2 Post Foldable ROPS	K25B723B20	3346 lbs	\$32,154.00
L4060HSTC	4WD Compact Tractor - ROPS Certified Factory Cab	K33B272B80	3743 lbs	\$41,591.00
L4060HST-LE	4WD Compact Tractor - 4WD HST ROPS Limited Tractor	K24B361B60	3346 lbs	\$30,452.00
L4060HSTC-LE	4WD Compact Tractor - 4WD HST Cab Limited Tractor	K30B750B40	3743 lbs	\$38,438.00

L4060 DT / GST / HST / HSTC		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>TIRES AND WHEELS†</b>				
<b>AG</b>				
ABR8753B*	F-TIRE 8.3-16 R1 OTR Traction Master	64 lbs		In Base Price
ALR6809B*	R-TIRE 14.9-24 R1 Titan Hi Power Lug TL	231 lbs		
<b>TURF</b>				
ALR8898	F-TIRE 27x10.50-15 R3 Turf Sp Armstg Whl	70 lbs	B835B20	Add \$ 1,044.00
ALR6804	R-TIRE 41x18LL-16.1 R3 Galaxy Turf Spcl	132 lbs		
ALR8868	F-TIRE 27x8.50-15 R3 Goodyear SoftTrac	53 lbs	B400B80	Less \$ (126.00)
LR6801	R-TIRE 355/80D20 B-Stone Pillow Diam 1	188 lbs		
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B484B80	Add \$ 606.00
ALR6807	R-TIRE 17.5L-24 R4 TITAN INDUSTRIAL	259 lbs		

† See Tire Section for Individual Tire Pricing and Information

\* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L4060 DT / GST / HST / HSTC		Additional Price With Tire Option		
TIRES AND WHEELS (priced per piece)				
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST PRICE
<b>AG</b>				
ABR8753B*	F-TIRE 8.3-16 R1 OTR Traction Master	64 lbs	B220B80	\$ 276.00
ALR6809B*	R-TIRE 14.9-24 R1 Titan Hi Power Lug TL	231 lbs	B587B20	\$ 734.00
<b>TURF</b>				
ALR6813	F-TIRE 29x12.50-15 R3 Titan Multi Trac	78 lbs	B268B00	\$ 335.00
ALR6803	R-TIRE 44x18-20 R3 Titan MultiTrac 6stud	229 lbs	B761B60	\$ 952.00
ALR8898	F-TIRE 27x10.50-15 R3 Turf Sp Armstg Whl	70 lbs	B372B00	\$ 465.00
ALR6804	R-TIRE 41x18LL-16.1 R3 Galaxy Turf Spcl	132 lbs	B853B60	\$ 1,067.00
ALR8868	F-TIRE 27x8.50-15 R3 Goodyear SoftTrac	53 lbs	B188B00	\$ 235.00
LR6801	R-TIRE 355/80D20 B-Stone Pillow Diam 1	188 lbs	B569B60	\$ 712.00
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B324B80	\$ 406.00
ALR6807	R-TIRE 17.5L-24 R4 TITAN INDUSTRIAL	259 lbs	B725B60	\$ 907.00



**Grand L 60 Series L4760 GST / HST**

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 4 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 40 Amps  
 12V – 582 CCA  
 Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 DT / GST - 14.7 gpm  
 HST - 14.1 gpm

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At Lift Point 3858 lbs.  
 24" Behind 2956 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm  
 Electric over Hydraulic PTO Switch

**TRANSMISSION, GST**

Glide Shift w/Synchro Shuttle  
 Rear Differential Lock  
 12 Forward Speeds  
 8 Reverse Speeds  
 Single-Stage Clutch  
 Wet Disc Brakes

**TRANSMISSION, HST**

Hydrostatic Drive - HST PLUS  
 Rear Differential Lock  
 3 Ranges  
 Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 7.9 qts.  
 Crankcase 8.7 qts.  
 Transmission and  
 Hydraulics 11.4 gal.  
 Front Axle 9.5 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols  
 HST Mode Selection

**FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Telescoping Lower Links  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder

**HST-SPECIFIC FEATURES**

Auto Throttle Advance  
 Hydro Dual Speed (H-DS)  
 HST Response Control  
 Throttle-Up Switch

**SAFETY EQUIPMENT**

2-Post Foldable ROPS w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

Model Specifications			
<b>L4760GST 4WD</b>		<b>L4760HST 4WD</b>	
SAE Gross HP:	49.0	SAE Gross HP:	49.0
Engine Net HP:	47.0	Engine Net HP:	47.0
PTO HP:	41.0	PTO HP:	39.5
Engine Model:	V2403	Engine Model:	V2403
Displacement:	148.5 Cu. In.	Displacement:	148.5 Cu. In.



**Grand L 60 Series L4760HSTC**

**\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\***

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 4 Cylinder Engine  
 EPA Tier 4 Compliant  
 Charging Output 60 Amps  
 12V – 582 CCA  
 Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 14.1 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At Lift Point 3858 lbs.  
 24" Behind 2956 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm  
 Electric over Hydraulic PTO Switch

**TRANSMISSION**

Hydrostatic Drive - HST PLUS PLUS  
 Rear Differential Lock  
 3 Speed Ranges  
 Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 7.9 qts.  
 Crankcase 8.7 qts.  
 Transmission and  
 Hydraulics 11.4 gal.  
 Front Axle 6.9 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols  
 HST Mode Selection

**FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Telescoping Lower Links  
 2 Front Work Lights  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder  
 Auto Throttle Advance  
 Hydro Dual Speed (H-DS)  
 HST Response Control  
 Throttle-Up Switch  
 Front Wiper w/Washer  
 Interior Light  
 AC/Heater with Internal/External  
 Ventilation  
 Speakers and Radio Pre-Wired  
 Horn

**SAFETY EQUIPMENT**

ROPS Certified Cab w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

Model Specifications	
<b>L4760HSTC 4WD</b>	
SAE Gross HP:	49.0
Engine Net HP:	47.0
PTO HP:	39.5
Engine Model:	V2403
Displacement:	148.5 Cu. In.



**Grand L 60 Series L4760 GST / HST / HSTC**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***				
L4760GST	4WD Compact Tractor - 2 Post Foldable ROPS	K30B071B20	3430 lbs	\$37,589.00
L4760HST	4WD Compact Tractor - 2 Post Foldable ROPS	K30B407B20	3430 lbs	\$38,009.00
L4760HSTC	4WD Compact Tractor - ROPS Certified Factory Cab	K37B956B80	3752 lbs	\$47,446.00

L4760 GST / HST / HSTC				
TIRES AND WHEELS†				Additional Price With Tire Option
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>AG</b>				
ABR8753B*	F-TIRE 8.3-16 R1 OTR Traction Master	64 lbs		In Base Price
ALR6809B*	R-TIRE 14.9-24 R1 Titan Hi Power Lug TL	231 lbs		
<b>TURF</b>				
ALR8708	F-TIRE 29x12.50-15 R3 Titan Turf	83 lbs	B524B80	Add \$ 656.00
ALR6803	R-TIRE 44x18-20 R3 Titan MultiTrac 6stud	229 lbs		
ALR6818A	F-TIRE LSW305R343 R3 Titan Grizz LSW 430	70 lbs	B643B20	Add \$ 804.00
ALR6817	R-TIRE LSW610R470 R3 Grizz LSW 430 6stud	227 lbs		
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B484B80	Add \$ 606.00
ALR6807	R-TIRE 17.5L-24 R4 TITAN INDUSTRIAL	259 lbs		

† See Tire Section for Individual Tire Pricing and Information  
\* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L4760 GST / HST / HSTC				
TIRES AND WHEELS (priced per piece)				
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST PRICE
<b>AG</b>				
ABR8753B*	F-TIRE 8.3-16 R1 OTR Traction Master	64 lbs	B220B80	\$ 276.00
ALR6809B*	R-TIRE 14.9-24 R1 Titan Hi Power Lug TL	231 lbs	B587B20	\$ 734.00
<b>TURF</b>				
ALR8708	F-TIRE 29x12.50-15 R3 Titan Turf	83 lbs	B308B80	\$ 386.00
ALR6803	R-TIRE 44x18-20 R3 Titan MultiTrac 6stud	229 lbs	B761B60	\$ 952.00
ALR6818A	F-TIRE LSW305R343 R3 Titan Grizz LSW 430	70 lbs	B324B80	\$ 406.00
ALR6817	R-TIRE LSW610R470 R3 Grizz LSW 430 6stud	227 lbs	B804B80	\$ 1,006.00
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B324B80	\$ 406.00
ALR6807	R-TIRE 17.5L-24 R4 TITAN INDUSTRIAL	259 lbs	B725B60	\$ 907.00



**Grand L 60 Series L5060GST**

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 4 Cylinder Engine  
 EPA Tier 4 Compliant  
 Turbocharged Engine  
 Charging Output 45 Amps  
 12V – 582 CCA  
 Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 14.7 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I 3-Point Hitch  
 At Lift Point 3858 lbs.  
 24" Behind 2956 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm  
 Electric over Hydraulic PTO Switch

**TRANSMISSION, GST**

Glide Shift w/Synchro Shuttle  
 Rear Differential Lock  
 12 Forward Speeds  
 8 Reverse Speeds  
 Single-Stage Clutch  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 8.7 qts.  
 Crankcase 9.9 qts.  
 Transmission and  
 Hydraulics 11.9 gal.  
 Front Axle 9.5 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols

**FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Telescoping Lower Links  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder

**SAFETY EQUIPMENT**

2-Post Foldable ROPS w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

Model Specifications	
<b>L5060GST 4WD</b>	
SAE Gross HP:	52.0
Engine Net HP:	50.0
PTO HP:	44
Engine Model:	V2403
Displacement:	148.5 Cu. In.



**Grand L 60 Series L5060GST**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***				
L5060GST	4WD Compact Tractor - 2 Post Foldable ROPS	K32B092B00	3514 lbs	\$40,115.00

L5060GST		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>TIRES AND WHEELS<sup>†</sup></b>				
<b>AG</b>				
AMXR8860A*	F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud	78 lbs	In Base Price	In Base Price
AMXR8861*	R-TIRE 14.9-26 Titan Hi Power Lug TL	254 lbs		
AMXR8860A	F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud	78 lbs	In Base Price	In Base Price
AMXR8813A	R-TIRE 13.6-28 R1 Titan Hi Trac Lug TL	242 lbs		
<b>TURF</b>				
ALR8708	F-TIRE 29x12.50-15 R3 Titan Turf	83 lbs	B97B60	Add \$ 122.00
ALR6802	R-TIRE 44x18-20 R3 Titan MultiTrac 8stud	221 lbs		
ALR6818A	F-TIRE LSW305R343 R3 Titan Grizz LSW 430	70 lbs	B216B00	Add \$ 270.00
ALR6819	R-TIRE LSW610R470 R3 Grizz LSW 430 8stud	227 lbs		
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B110B40	Add \$ 138.00
AMXR8862	R-TIRE 17.5L-24 R4 Titan Ind Cont TL	257 lbs		

<sup>†</sup> See Tire Section for Individual Tire Pricing and Information  
 \* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L5060GST		TIRES AND WHEELS (priced per piece)		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST PRICE
<b>AG</b>				
AMXR8860A*	F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud	78 lbs	B254B40	\$ 318.00
AMXR8861*	R-TIRE 14.9-26 Titan Hi Power Lug TL	254 lbs	B767B20	\$ 959.00
AMXR8860A	F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud	78 lbs	B254B40	\$ 318.00
AMXR8813A	R-TIRE 13.6-28 R1 Titan Hi Trac Lug TL	242 lbs	B767B20	\$ 959.00
<b>TURF</b>				
ALR8708	F-TIRE 29x12.50-15 R3 Titan Turf	83 lbs	B308B80	\$ 386.00
ALR6802	R-TIRE 44x18-20 R3 Titan MultiTrac 8stud	221 lbs	B761B60	\$ 952.00
ALR6818A	F-TIRE LSW305R343 R3 Titan Grizz LSW 430	70 lbs	B324B80	\$ 406.00
ALR6819	R-TIRE LSW610R470 R3 Grizz LSW 430 8stud	227 lbs	B804B80	\$ 1,006.00
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B324B80	\$ 406.00
AMXR8862	R-TIRE 17.5L-24 R4 Titan Ind Cont TL	257 lbs	B752B00	\$ 940.00



**Grand L 60 Series L5460HST**

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 4 Cylinder Engine  
 EPA Tier 4 Compliant  
 Turbocharged Engine  
 Charging Output 45 Amps  
 12V – 582 CCA  
 Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 14.1 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I & II 3-Point Hitch  
 At Lift Point 3858 lbs.  
 24" Behind 2956 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm  
 Electric over Hydraulic PTO Switch

**TRANSMISSION, HST**

Hydrostatic Drive - HST PLUS  
 Rear Differential Lock  
 3 Speed Ranges  
 Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 8.7 qts.  
 Crankcase 9.9 qts.  
 Transmission and  
 Hydraulics 11.9 gal.  
 Front Axle 9.5 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols  
 HST Mode Selection

**FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Telescoping Lower Links  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder  
 Auto Throttle Advance, HST  
 Hydro Dual Speed (H-DS), HST  
 HST Response Control  
 Throttle-Up Switch

**SAFETY EQUIPMENT**

2-Post Foldable ROPS w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

Model Specifications	
<b>L5460HST 4WD</b>	
SAE Gross HP:	56.0
Engine Net HP:	54.0
PTO HP:	46.5
Engine Model:	V2403
Displacement:	148.5 Cu. In.





**Grand L 60 Series L5460HSTC**

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 4 Cylinder Engine  
 EPA Tier 4 Compliant  
 Turbocharged Engine  
 Charging Output 60 Amps  
 12V – 582 CCA  
 Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 14.1 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I & II 3-Point Hitch  
 At Lift Point 3858 lbs.  
 24" Behind 2956 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm  
 Electric over Hydraulic PTO Switch

**TRANSMISSION**

Hydrostatic Drive - HST PLUS  
 Rear Differential Lock  
 3 Speed Ranges  
 Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 8.7 qts.  
 Crankcase 9.9 qts.  
 Transmission and  
 Hydraulics 11.9 gal.  
 Front Axle 9.5 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols  
 HST Mode Selection

**FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Telescoping Lower Links  
 2 Front Work Lights  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder  
 Auto Throttle Advance  
 Hydro Dual Speed (H-DS)  
 HST Response Control  
 Throttle-Up Switch  
 Front Wiper w/Washer  
 Interior Light  
 AC/Heater with Internal/External  
 Ventilation  
 Speakers and Radio Pre-Wired  
 Horn

**SAFETY EQUIPMENT**

ROPS Certified Cab w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

Model Specifications	
<b>L5460HSTC 4WD</b>	
SAE Gross HP:	56.0
Engine Net HP:	54.0
PTO HP:	46.5
Engine Model:	V2403
Displacement:	148.5 Cu. In.



**Grand L 60 Series L5460 HST / HSTC**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***				
L5460HST	4WD Compact Tractor - 2 Post Foldable ROPS	K32B545B60	3514 lbs	\$40,682.00
L5460HSTC	4WD Compact Tractor - ROPS Certified Factory Cab	K40B095B20	3911 lbs	\$50,119.00

L5460 HST / HSTC		Additional Price With Tire Option		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>TIRES AND WHEELS<sup>†</sup></b>				
<b>AG</b>				
AMXR8860A*	F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud	78 lbs		In Base Price
AMXR8861*	R-TIRE 14.9-26 Titan Hi Power Lug TL	254 lbs		In Base Price
AMXR8860A	F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud	78 lbs		In Base Price
AMXR8813A	R-TIRE 13.6-28 R1 Titan Hi Trac Lug TL	242 lbs		In Base Price
<b>TURF</b>				
ALR8708	F-TIRE 29x12.50-15 R3 Titan Turf	83 lbs	B97B60	Add \$ 122.00
ALR6802	R-TIRE 44x18-20 R3 Titan MultiTrac 8stud	221 lbs		
ALR6818A	F-TIRE LSW305R343 R3 Titan Grizz LSW 430	70 lbs	B216B00	Add \$ 270.00
ALR6819	R-TIRE LSW610R470 R3 Grizz LSW 430 8stud	227 lbs		
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B110B40	Add \$ 138.00
AMXR8862	R-TIRE 17.5L-24 R4 Titan Ind Cont TL	257 lbs		

<sup>†</sup> See Tire Section for Individual Tire Pricing and Information  
 \* Standard Tires

**TIRES AND WHEELS (priced per piece)**

L5460 HST / HSTC		TIRES AND WHEELS (priced per piece)		
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST PRICE
<b>AG</b>				
AMXR8860A*	F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud	78 lbs	B254B40	\$ 318.00
AMXR8861*	R-TIRE 14.9-26 Titan Hi Power Lug TL	254 lbs	B767B20	\$ 959.00
AMXR8860A	F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud	78 lbs	B254B40	\$ 318.00
AMXR8813A	R-TIRE 13.6-28 R1 Titan Hi Trac Lug TL	242 lbs	B767B20	\$ 959.00
<b>TURF</b>				
ALR8708	F-TIRE 29x12.50-15 R3 Titan Turf	83 lbs	B308B80	\$ 386.00
ALR6802	R-TIRE 44x18-20 R3 Titan MultiTrac 8stud	221 lbs	B761B60	\$ 952.00
ALR6818A	F-TIRE LSW305R343 R3 Titan Grizz LSW 430	70 lbs	B324B80	\$ 406.00
ALR6819	R-TIRE LSW610R470 R3 Grizz LSW 430 8stud	227 lbs	B804B80	\$ 1,006.00
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B324B80	\$ 406.00
AMXR8862	R-TIRE 17.5L-24 R4 Titan Ind Cont TL	257 lbs	B752B00	\$ 940.00



**Grand L 60 Series L6060HST**

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 4 Cylinder Engine  
 EPA Tier 4 Compliant  
 Turbocharged Engine  
 Charging Output 45 Amps  
 12V – 582 CCA  
 Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 14.1 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I & II 3-Point Hitch  
 At Lift Point 3858 lbs.  
 24" Behind 2956 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm  
 Electric over Hydraulic PTO Switch

**TRANSMISSION, HST**

Hydrostatic Drive - HST PLUS  
 Rear Differential Lock  
 3 Forward Ranges  
 3 Reverse Ranges  
 Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 8.7 qts.  
 Crankcase 9.9 qts.  
 Transmission and  
 Hydraulics 11.9 gal.  
 Front Axle 9.5 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols  
 HST Mode Selection

**FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Telescoping Lower Links  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder  
 Auto Throttle Advance, HST  
 Hydro Dual Speed (H-DS), HST  
 HST Response Control  
 Throttle-Up Switch

**SAFETY EQUIPMENT**

2-Post Foldable ROPS w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

Model Specifications	
<b>L6060HST 4WD</b>	
SAE Gross HP:	62.0
Engine Net HP:	60.0
PTO HP:	53
Engine Model:	V2403
Displacement:	148.5 Cu. In.



**Grand L 60 Series L6060HSTC**

\*\*\* EQUIPMENT IN STANDARD MACHINE & SPECIFICATIONS \*\*\*

**DIESEL ENGINE**

Kubota Common Rail Direct Injection  
 4 Cylinder Engine  
 EPA Tier 4 Compliant  
 Turbocharged Engine  
 Charging Output 60 Amps  
 12V – 582 CCA

Dual Air Cleaner Element

**EXHAUST EMISSION CONTROL TYPE**

Diesel Particulate Filter

**HYDRAULICS / HITCH / DRAWBAR**

Open Center  
 Tandem Gear Pumps  
 14.1 gpm Total Hyd. Flow

**3-POINT HITCH & DRAWBAR**

Cat I & II 3-Point Hitch  
 At Lift Point 3858 lbs.  
 24" Behind 2956 lbs.  
 Position Control 3-Point Valve

**POWER TAKE OFF**

Live Independent with Hydraulic Clutch  
 Rear PTO – 1 Speed  
 SAE Std 1 3/8" Six Spline  
 540 rpm @ 2550 Eng. Rpm  
 Electric over Hydraulic PTO Switch

**TRANSMISSION**

Hydrostatic Drive - HST PLUS  
 Rear Differential Lock  
 3 Speed Ranges  
 Cruise Control  
 Wet Disc Brakes

**FRONT AXLE**

Hydrostatic Power Steering  
 Cast Iron with Bevel Gear 4WD  
 Tread Spacing - Nonadjustable

**FLUID CAPACITY**

Fuel Tank 13.5 gal.  
 Cooling System 8.7 qts.  
 Crankcase 9.9 qts.  
 Transmission and  
 Hydraulics 11.9 gal.  
 Front Axle 9.5 qts.

**INSTRUMENTS**

Tachometer/Hour meter  
 Digital Read for Speed, MPH, PTO  
 Speeds, Diagnostics Systems  
 and DPF System  
 Lighted Communications Symbols  
 Warning Symbols  
 HST Mode Selection

**FEATURES**

High Back Adj. Swivel Seat w/Deluxe  
 Suspension w/Arm Rests  
 Illuminated Instrument Panel  
 Large, Flat Operator's Station  
 Tilt Steering  
 Wide, Anti-Slip Step  
 ISO Mounted Platform  
 Telescoping Lower Links  
 2 Front Work Lights  
 2 Tier Halogen Head Lights  
 4 Position Loader Valve  
 Steel Hood and Fenders  
 Cup Holder  
 Auto Throttle Advance  
 Hydro Dual Speed (H-DS)  
 HST Response Control  
 Throttle-Up Switch  
 Front Wiper w/Washer  
 Interior Light  
 AC/Heater with Internal/External  
 Ventilation  
 Speakers and Radio Pre-Wired  
 Horn

**SAFETY EQUIPMENT**

ROPS Certified Cab w/Retractable  
 Seat Belt  
 Flip-Up PTO Shield  
 Safety Start Switches  
 Turn Signals / Hazard Lights  
 Electric Key Shut Off  
 Parking Brake  
 SMV Sign

Model Specifications	
<b>L6060HSTC 4WD</b>	
SAE Gross HP:	62.0
Engine Net HP:	60.0
PTO HP:	53.0
Engine Model:	V2403
Displacement:	148.5 Cu. In.



## Grand L 60 Series L6060 HST / HSTC

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
*** STANDARD MACHINE ***				
L6060HST	4WD Compact Tractor - 2 Post Foldable ROPS	K34B283B20	3536 lbs	\$42,854.00
L6060HSTC	4WD Compact Tractor - ROPS Certified Factory Cab	K41B832B80	3911 lbs	\$52,291.00

L6060 HST / HSTC				
TIRES AND WHEELS <sup>†</sup>				
				Additional Price With Tire Option
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST
<b>AG</b>				
AMXR8860A*	F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud	78 lbs		In Base Price
AMXR8861*	R-TIRE 14.9-26 Titan Hi Power Lug TL	254 lbs		
AMXR8860A	F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud	78 lbs		In Base Price
AMXR8813A	R-TIRE 13.6-28 R1 Titan Hi Trac Lug TL	242 lbs		
<b>TURF</b>				
ALR8708	F-TIRE 29x12.50-15 R3 Titan Turf	83 lbs	B97B60	Add \$ 122.00
ALR6802	R-TIRE 44x18-20 R3 Titan MultiTrac 8stud	221 lbs		
ALR6818A	F-TIRE LSW305R343 R3 Titan Grizz LSW 430	70 lbs	B216B00	Add \$ 270.00
ALR6819	R-TIRE LSW610R470 R3 Grizz LSW 430 8stud	227 lbs		
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B110B40	Add \$ 138.00
AMXR8862	R-TIRE 17.5L-24 R4 Titan Ind Cont TL	257 lbs		

<sup>†</sup> See Tire Section for Individual Tire Pricing and Information

\* Standard Tires

### TIRES AND WHEELS (priced per piece)

L6060 HST / HSTC				
TIRES AND WHEELS (priced per piece)				
ORDER CODE	DESCRIPTION	WEIGHT EACH	FACTORY NUMBER	SUGG. LIST PRICE
<b>AG</b>				
AMXR8860A*	F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud	78 lbs	B254B40	\$ 318.00
AMXR8861*	R-TIRE 14.9-26 Titan Hi Power Lug TL	254 lbs	B767B20	\$ 959.00
AMXR8860A	F-TIRE 9.5-16 R1 Gdyr Dura Torque 6stud	78 lbs	B254B40	\$ 318.00
AMXR8813A	R-TIRE 13.6-28 R1 Titan Hi Trac Lug TL	242 lbs	B767B20	\$ 959.00
<b>TURF</b>				
ALR8708	F-TIRE 29x12.50-15 R3 Titan Turf	83 lbs	B308B80	\$ 386.00
ALR6802	R-TIRE 44x18-20 R3 Titan MultiTrac 8stud	221 lbs	B761B60	\$ 952.00
ALR6818A	F-TIRE LSW305R343 R3 Titan Grizz LSW 430	70 lbs	B324B80	\$ 406.00
ALR6819	R-TIRE LSW610R470 R3 Grizz LSW 430 8stud	227 lbs	B804B80	\$ 1,006.00
<b>INDUSTRIAL</b>				
ALR8869A	F-TIRE 10-16.5 R4 Titan Trac Loader	81 lbs	B324B80	\$ 406.00
AMXR8862	R-TIRE 17.5L-24 R4 Titan Ind Cont TL	257 lbs	B752B00	\$ 940.00

**KUBOTA****Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060****DEALER INSTALLED ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>HYDRAULICS/HITCH/DRAWBAR</b>				
<b>HYDRAULIC REAR REMOTE VALVES</b>				
L8398	Base Kit and 1st Lever for ROPS models Requires Double Acting or Float Detent Valve Section	K540L80	20 lbs	\$676.00
L8396	Base Kit and 1st Lever for CAB models Requires Double Acting or Float Detent Valve Section	K540L80	16 lbs	\$676.00
L8393	2nd Position Stacking Kit and 2nd Lever Requires Base Kit Requires Double Acting or Float Detent Valve Section	K292L00	9 lbs	\$365.00
L8394	3rd Position Stacking Kit and 3rd Lever Requires Base Kit and 2nd Position Kit Requires Double Acting or Float Detent Valve Section	K292L00	8 lbs	\$365.00
L8308	Double Acting Valve Section	K221L60	4 lbs	\$277.00
L8309	FD (Float Detent) Valve Section	K278L40	4 lbs	\$348.00
<b>DRAFT CONTROL</b>				
L8395	Draft Control Kit for all L60 series	K516L80	28 lbs	\$646.00
<b>DRAWBAR OPTIONS</b>				
L9496G	Drawbar Clevis	K76L00	8 lbs	\$95.00
L6821	Drawbar Clevis (Replacing L9496G)	K68L80	8 lbs	\$86.00
LMX6800	Clevis Kit for L-MX Drop Drawbars	K43A20	7 lbs	\$54.00
L6830	Drop Drawbar for L4701/L3560	K84L80	22 lbs	\$106.00
L6840	Drop Drawbar for L4060/L4760	K84L80	22 lbs	\$106.00
L6850	Drop Drawbar for L5060-L6060	K84L80	22 lbs	\$106.00
L8325	Swinging Drawbar	K133L60	20 lbs	\$167.00
<b>HYDRAULIC DIVERTER VALVE</b>				
L8397	Hydraulic Diverter Kit Enables standard loader to be used as 2 rear hydraulic remotes Spool 1: 4-Position spool with 1st stage standard non-regenerative & 2nd stage regenerative Spool 2: 4-Position spool with detent float Not Compatible with Front Loader or Rear Hydraulic Valves	K517L60	17 lbs	\$647.00
<b>TOP-N-TILT KIT</b>				
L8388A	Top-N-Tilt Kit Requires 2 Double Acting Remote Hydraulic Valves Not Compatible with Backhoe	K804L00	41 lbs	\$1,005.00

**KUBOTA****Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060****DEALER INSTALLED ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>CAB ACCESSORIES</b>				
<b>DEFOGGER KITS</b>				
L8340	Defogger Kit, Rear Window Requires High Amp Alternator Kit	K259L20	28 lbs	\$324.00
L8381	Defogger Kit, Corner Windows Requires High Amp Alternator Kit	K283L20	18 lbs	\$354.00
<b>ALTERNATOR KITS</b>				
L5533	High Amp Alternator Kit for L3560	K427L20	15 lbs	\$534.00
L5534	High Amp Alternator Kit for L4060 / L4760 / L5460 / L6060	K427L20	15 lbs	\$534.00
<b>RADIO</b>				
Jensen Radios	3 Radios Available		(Order from the Parts Department)	
<b>REAR WIPER KIT</b>				
L8364	Rear Wiper Kit	K132L00	3 lbs	\$165.00
<b>REAR WORK LIGHT</b>				
L8333	Rear Work Light Kit, 2 Lights	K120L80	3 lbs	\$151.00
<b>FRONT WORK LIGHT</b>				
L8380	Front Work Light Kit - L60-LE Models	K120L80	3 lbs	\$151.00
<b>SIDE MIRROR KIT</b>				
MX6801	Side Mirror Kit L60-LE / MX CAB	K120M00	4 lbs	\$150.00
<b>ROPS ACCESSORIES</b>				
<b>CANOPY</b>				
E1133	Plastic Canopy	K404B80	63 lbs	\$506.00
E1134	Fiberglass Canopy Requires Mounting Bracket Kit	K360M80	63 lbs	\$451.00
E1136	Mounting Bracket Kit	K178M40	29 lbs	\$223.00
<b>FRONT WORK LIGHT</b>				
E1138	Front Work Light Kit for Fiberglass Canopy Includes 2 Lights	K136A80	3 lbs	\$171.00
<b>REAR WORK LIGHT</b>				
L8329	Rear Work Light Kit, 1 Light	K82L40	4 lbs	\$103.00



**Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060**

**DEALER INSTALLED ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>BALLAST</b>				
<b>BALLAST BOX</b>				
L8170	Ballast Box - 3-Point Mount Up to 1000 lbs of total weight with sand	K460L00	168 lbs	\$575.00
<b>FRONT WEIGHT BRACKETS</b>				
MX8068	Weight Bracket - up to 7 Weights Requires 1 BL8014 for all weight stacks of BL8069 Not Compatible with Grill Guard or Front Hitch installed	K88M00	29 lbs	\$110.00
<b>FRONT SUITCASE WEIGHTS</b>				
BL8069	Suitcase Weight (55 lbs. Each) Requires 1 BL8049 Bolt Kit per Every Weight MAX 4 Weights Allowed w/ Grill Guard	K64B80	55 lbs	\$81.00
<b>FRONT WEIGHT BOLT KITS</b>				
BL8049	Weight Bolt Kit - 1 Kit Per Every BL8069 Weight	K6B40	1 lbs	\$8.00
BL8014	Thread Bolt & Spacing Kit 1 Required on MX8068 When Stacking BL8069 Weights	K25B60	5 lbs	\$32.00
<b>REAR WHEEL WEIGHTS &amp; BOLT KITS</b>				
L8066A	Rear Wheel Weight (64 lbs. Each), set of 2 Weights for all L3560 / L4060 / L4760 models 3 Weight per Standard Tractor Bracket Not Compatible with Turf Tires Requires one Weight Bolt Kit per Set	K116L00	128 lbs	\$145.00
L8067A	Weight Bolt Kits - 1 Kit per Rear Wheel Weight for all L3560 / L4060 / L4760 models	K29L60	5 lbs	\$37.00
LM8124	Rear Wheel Weight (103 lbs. Each), set of 2 Weights for all L5060 / L5460 / L6060 models 3 Weight per Standard Tractor Bracket Not Compatible with Turf Tires Requires one Weight Bolt Kit per Set	K260M80	206 lbs	\$326.00
LM8125A	Weight Bolt Kits - 1 Kit per Rear Wheel Weight for all L5060 / L5460 / L6060 models For first set of Rear Wheel Weights	K61M60	5 lbs	\$77.00
M8121A	Weight Bolt Kits - 1 Kit per Rear Wheel Weight for all L5060 / L5460 / L6060 models For 2nd and 3rd set of Rear Wheel Weights	K27M20	8 lbs	\$34.00

**ADDITIONAL ACCESSORIES**

<b>AIR RIDE SEAT</b>				
L6023	Air Ride Seat for ROPS models Disables stationary PTO feature and swivel seat capability	K807L20	77 lbs	\$1,009.00
L6026	Air Ride Seat for CAB models Disables stationary PTO feature and swivel seat capability	K807L20	77 lbs	\$1,009.00
<b>BLOCK HEATER</b>				
70000-00297	Block Heater	(Order from the Parts Department)		
<b>HEATER KIT</b>				
L3180	CCV Heater Kit for L3560 CAB	K631L20	16 lbs	\$789.00
L6815	CCV Heater Kit for L3560 / L4060 / L4760 ROPS	K416L00	1 lbs	\$520.00
L3182	CCV Heater Kit for L4060 / L4760 CAB	K629L60	16 lbs	\$787.00
L6816	CCV Heater Kit for L5060 / L5460 / L6060 ROPS	K224L80	1 lbs	\$281.00
L3184	CCV Heater Kit for L5060 / L5460 / L6060 CAB	K484L80	16 lbs	\$606.00
<b>CREEP SPEED KIT</b>				
L8382	Creep Speed Kit for all L60 series, except HST models	K556L00	24 lbs	\$695.00





**Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060**

**DEALER INSTALLED ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>ADDITIONAL ACCESSORIES</b>				
<b>GRILL GUARD - NON LOADER APPLICATION</b>				
L2257	Grill Guard for Non-Loader Application	K254L40	61 lbs	\$318.00
<b>MID PTO KITS</b>				
L8387	Mid PTO Kit for all L60 series ROPS models require Internal Gear Kit	K356L80	20 lbs	\$446.00
L8316	Mid PTO Internal Gear Kit for L60 ROPS models Standard for Cab models Requires Mid PTO Kit	K235L20	19 lbs	\$294.00
<b>REPLACEMENT CABS</b>				
L8392	Replacement Cab for L3560HSTC	K7L284L80	850 lbs	\$9,106.00
L8391	Replacement Cab for L4060HSTC / L4760HSTC	K7L284L80	850 lbs	\$9,106.00
L8390	Replacement Cab for L5460HSTC / L6060HSTC	K7L284L80	850 lbs	\$9,106.00
<b>REPLACEMENT ROPS</b>				
SFL-F356A	Replacement ROPS for L3560DT/GST/HST	K662L40	227 lbs	\$828.00
SFL-F476A	Replacement ROPS for L4060DT/GST/HST and L4760GST/HST	K662L40	218 lbs	\$828.00
SFL-F606A	Replacement ROPS for L5060GST, L5460HST, and L6060HST models	K662L40	218 lbs	\$828.00
<b>SEAT BELT KIT</b>				
70002-06605	Extra Length Seat Belt Kit	(Order from the Parts Department)		

**KUBOTA****Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060****FRONT LOADERS**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>FRONT END LOADER AND ACCESSORIES</b>				
LA555	Front End Loader for L3560 only Includes Mounting Kit, 2-Lever Quick Coupler, Bucket Level Indicator, and Grill Guard Loader Valve is Standard Equipment on all Grand L60 Tractors Requires Bucket Not Compatible with BH92	K3L630L40	1124 lbs	\$4,538.00
<b>3RD FUNCTION VALVE</b>				
L2247	3rd Function Valve Must order hydraulic line quick couplers separately.	K852L80	55 lbs	\$1,066.00
<b>QUICK ATTACH COUPLER &amp; BUCKETS</b>				
L2256	66" Square Back QA Bucket	K591L20	212 lbs	\$739.00
L2236	72" Light Material QA Bucket	K616L00	323 lbs	\$770.00
L2244	60" 4-in-1 Bucket Requires 3rd Function Valve	K1L920L00	450 lbs	\$2,400.00
<b>QUICK ATTACH PALLET FORKS</b>				
L2237	Bale Spear, 2-Lever Quick Coupler	K608L80	165 lbs	\$761.00
L2238	Pallet Fork Frame, 2 Lever Quick Coupler Requires Pallet Forks	K642L40	165 lbs	\$803.00
K9048	36" Pallet Forks	K386L40	176 lbs	\$483.00



**Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>FRONT END LOADER AND ACCESSORIES</b>				
LA805	Front End Loader for L3560 / L4060 Includes Mounting Kit, Valve, and Grill Guard, and 2-Lever Type Quick Coupler Loader Valve is Standard Equipment on all Grand L60 Tractors Requires Bucket Loader must be installed to use Backhoe.	K4L339L20	1124 lbs	\$5,424.00
<b>QUICK ATTACH COUPLER &amp; BUCKETS</b>				
L2235A	72" Square Back QA Bucket	K654L40	346 lbs	\$818.00
L2236	72" Light Material QA Bucket	K616L00	323 lbs	\$770.00
L2244	60" 4-in-1 Bucket Requires 3rd Function Valve	K1L920L00	450 lbs	\$2,400.00
L2245	72" 4-in-1 Bucket Requires 3rd Function Valve	K2L027L20	675 lbs	\$2,534.00
L2296	72" Heavy Duty QA Bucket Requires Bolt On Cutting Edge	K1L016L00	400 lbs	\$1,270.00
TL1748	Bolt On Cutting Edge	K215L20	70 lbs	\$269.00
<b>QUICK ATTACH PALLET FORKS</b>				
L2237	Bale Spear, 2-Lever Quick Coupler	K608L80	165 lbs	\$761.00
L2238	Pallet Fork Frame, 2 Lever Quick Coupler Requires Pallet Forks	K642L40	165 lbs	\$803.00
K9048	36" Pallet Forks	K386L40	176 lbs	\$483.00
<b>HYDRAULIC 2-LEVER QUICK COUPLER</b>				
L2270	Hydraulic 2-Lever Quick Coupler Parts Required IF L2270 and L2265 ordered instead of L2272: 7J292-84240, 7J416-68180, 7J292-35220, 7J292-35430	K1L420L80	118 lbs	\$1,776.00
<b>THIRD FUNCTION VALVE</b>				
L2265	3rd Function Control Valve for Hydraulic Loader Implements (for 3rd Function <u>or</u> Hydraulic 2-Lever Coupler Must order hydraulic line quick couplers separately	K852L80	55 lbs	\$1,066.00
L2272	3rd Function Control Valve & Hydraulic 2-Lever Quick Coupler (L2270)	K2L272L80	143 lbs	\$2,841.00
<b>HYDRAULIC SPILL GUARD</b>				
L2261	Hydraulic Spill Guard, anti-spill feature for buckets	K568L00	28 lbs	\$710.00
<b>LOADER HOSE QUICK COUPLER</b>				
L2260	3rd Function Hose Quick Coupler	K564L80	9 lbs	\$706.00
L2252	Single Lever Hose Quick Coupler for Loader hoses (4 Hoses)	K659L20	16 lbs	\$824.00
L2262	Single Lever Hose Quick Coupler for Loader, 3rd Function Control Valve, and Hydraulic 2-Lever Quick Coupler (8 Hoses)	K848L80	21 lbs	\$1,061.00

**KUBOTA****Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060****FRONT LOADERS**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>FRONT END LOADER AND ACCESSORIES</b>				
LA1055	Front End Loader for L4760 / L5060 / L5460 / L6060 Includes Mounting Kit, Valve, Grill Guard, and 2-Lever Type Quick Coupler Loader Valve is Standard Equipment on all Grand L60 Tractors Requires Bucket	K4L736L80	1124 lbs	\$5,921.00
<b>QUICK ATTACH COUPLER &amp; BUCKETS</b>				
L2235A	72" Square Back QA Bucket	K654L40	346 lbs	\$818.00
L2236	72" Light Material QA Bucket	K616L00	323 lbs	\$770.00
L2245	72" 4-in-1 Bucket Requires 3rd Function Valve	K2L027L20	675 lbs	\$2,534.00
L2296	72" Heavy Duty QA Bucket Requires Bolt On Cutting Edge	K1L016L00	400 lbs	\$1,270.00
TL1748	Bolt On Cutting Edge	K215L20	70 lbs	\$269.00
<b>QUICK ATTACH PALLET FORKS</b>				
L2237	Bale Spear, 2-Lever Quick Coupler	K608L80	165 lbs	\$761.00
L2238	Pallet Fork Frame, 2 Lever Quick Coupler Requires Pallet Forks	K642L40	165 lbs	\$803.00
K9048	36" Pallet Forks	K386L40	176 lbs	\$483.00
<b>HYDRAULIC 2-LEVER QUICK COUPLER</b>				
L2270	Hydraulic 2-Lever Quick Coupler Parts Required IF L2270 and L2265 ordered instead of L2272: 7J292-84240, 7J416-68180, 7J292-35220, 7J292-35430	K1L420L80	118 lbs	\$1,776.00
<b>THIRD FUNCTION VALVE</b>				
L2265	3rd Function Control Valve for Hydraulic Loader Implements (for 3rd Function <b>or</b> Hydraulic 2-Lever Coupler Must order hydraulic line quick couplers separately.	K852L80	55 lbs	\$1,066.00
L2272	3rd Function Control Valve & Hydraulic 2-Lever Quick Coupler (L2270)	K2L272L80	143 lbs	\$2,841.00
<b>HYDRAULIC SPILL GUARD</b>				
L2271	Hydraulic Spill Guard, anti-spill feature for buckets	K568L00	29 lbs	\$710.00
<b>LOADER HOSE QUICK COUPLER</b>				
L2260	3rd Function Hose Quick Coupler	K564L80	9 lbs	\$706.00
L2252	Single Lever Hose Quick Coupler for Loader hoses (4 Hoses)	K659L20	16 lbs	\$824.00
L2262	Single Lever Hose Quick Coupler for Loader, 3rd Function Control Valve, and Hydraulic 2-Lever Quick Coupler (8 Hoses)	K848L80	21 lbs	\$1,061.00



**Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060**

**FRONT QUICK HITCH & FRONT QUICK HITCH IMPLEMENTS**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
------------	-------------	----------------	------------------	----------------------

**FRONT QUICK HITCH FRAME & COUPLER**

L4455A	Manual-Hitch Does not include Driveline Completion Kit Not compatible with Grille Guards or Front Weight Bracket Installation of the L4456 GPR is advised but not required	K2L189L60	550 lbs	\$2,737.00
L4554A	Auto-Hitch - Equipped with Auto Module Includes 4 Cylinder Driveline Completion Kit For 3 cylinder models, also order Part #70001-00623 do not order the entire 3 Cylinder Driveline Competition Kit (L4483) Not compatible with Grille Guards or Front Weight Bracket Installation of the L4456 GPR is advised but not required	K8L756L00	720 lbs	\$10,945.00

**FRONT QH DRIVELINE KITS**

L4483	Driveline Completion Kit - 3 Cylinder Engine for L3560 Tractor	K761L60	34 lbs	\$952.00
L4484	Driveline Completion Kit - 4 Cylinder Engine for L4060 and larger tractors Included in L4554A Auto Hitch Kit	K761L60	34 lbs	\$952.00

**FRONT QH OPTIONS**

L4472	Auto Module Upgrade Kit Upgrades the K1 Manual Hitch to a K3 Auto Hitch	K5L749L60	160 lbs	\$7,187.00
L4456	GPR - Ground Pressure Relief System Requires L4449 install on L4455(A) Manual Hitch	K1L814L40	66 lbs	\$2,268.00
L4449	GPR Hose Kit & Control Box Requires install L4456 (GPR) on L4455(A) Manual Hitch	K409L60	22 lbs	\$512.00
L4481	Lower Grill Guard Front Support for Grill Buar and Quick Hitch Co-installation Required loader grill guard or L2257 kit for non-loader application.	K111L20	30 lbs	\$139.00

**KUBOTA****Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060****FRONT QH MOUNTED BLADES AND ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>FRONT BLADES</b>				
L4466	60" Front Blade for <b>L3560 only</b> Includes Hyd. Lift and Angle Requires Quick Hitch Requires Blade Completion Kit for installation on L4554(A) Hitch	K2L263L20	500 lbs	\$2,829.00
L4476	72" Front Blade for all Grand L60 Models Includes Hyd. Lift and Angle Requires Quick Hitch Requires Blade Completion Kit for installation on L4554(A) Hitch	K2L404L80	555 lbs	\$3,006.00
L2172B	72" Front Blade for all Grand L60 Models Includes Hyd. Lift and Angle Requires Quick Hitch and L4446 Adapter Kit Requires Blade Completion Kit for installation on L4554(A) Hitch	K1L931L20	485 lbs	\$2,414.00
L4486	84" Front Blade, Hyd. Lift and Angle Includes Hyd. Lift and Angle Requires Quick Hitch Requires Blade Completion Kit for installation on L4554(A) Hitch	K2L762L40	590 lbs	\$3,453.00
L2184A	84" Front Blade, Hyd. Lift and Angle Includes Hyd. Lift and Angle Requires Quick Hitch and L4446 Adapter Kit Requires Blade Completion Kit for installation on L4554(A) Hitch	K2L338L40	570 lbs	\$2,923.00
<b>FRONT ADAPTER/COMPLETION KIT</b>				
L4446	Blade Adapter Kit	K608L80	83 lbs	\$761.00
L4482	Completion Kit - Full Auto-Hitch Required for use of blades on L4554A Full Auto-Hitch	K815L20	22 lbs	\$1,019.00
<b>FRONT BLADE OPTIONS</b>				
B2766	60" Front Blade Rubber Cutting Edge	K212B00	49 lbs	\$265.00
B2776	72" Front Blade Rubber Cutting Edge	K249B60	59 lbs	\$312.00
L2777	84" Front Blade Rubber Cutting Edge	K272L00	60 lbs	\$340.00



**Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060**

**FRONT QH MOUNTED UTILITY SNOW BLOWERS AND ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>FRONT QH MOUNTED UTILITY SNOW BLOWERS AND ACCESSORIES</b>				
<b>UTILITY SNOW BLOWERS</b>				
L4469	64" Two-Stage Utility Snowblower for <b>L3560 only</b> Requires Completion Kit, Quick Hitch, Driveline Kit, and Mid PTO Kit	K4L928L00	532 lbs	\$6,160.00
L4479	74" Two-Stage Utility Snowblower for all Grand L60 Models Requires Completion Kit, Quick Hitch, Driveline Kit, and Mid PTO Kit	K5L384L80	916 lbs	\$6,731.00
L2194A	62" Two-Stage Utility Snowblower for <b>L3560 only</b> Requires L4445 Adapter Kit, Quick Hitch, Driveline Kit, Completion Kit, and Mid PTO Kit	K5L176L00	812 lbs	\$6,470.00
L2195A	72" Two-Stage Utility Snowblower for L4060 - L6060 Models Requires: L4445 Adapter Kit, Quick Hitch, Driveline Kit, Completion Kit, and Mid PTO Kit	K5L616L80	896 lbs	\$7,021.00
<b>UTILITY SNOW BLOWER COMPLETION KITS</b>				
L4431	Completion Kit for Utility Snow Blower with L4455(A) Hitch Includes Drive Line Half and Hyd. Hoses	K269L60	14 lbs	\$337.00
L4432	Completion Kit for Utility Snow Blower with L4554(A) Hitch Includes Auto Module, Hyd. Cylinder for Chute Deflector, Hyd. Hoses, and PTO Coupler	K1L160L80	35 lbs	\$1,451.00
<b>UTILITY SNOW BLOWER OPTIONS</b>				
L2177	Width Extension Kit, adds 5" overall cut	K108L80	27 lbs	\$136.00
BL2666A	Hydraulic Chute Deflector Kit Includes Electric Selector Valve	K920B80	22 lbs	\$1,151.00
L4445	Snowblower Adapter Kit Required to convert L2194A or LA2195A	K470L40	60 lbs	\$588.00



**Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060**

**FRONT QH MOUNTED COMMERCIAL SNOW BLOWERS AND ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
------------	-------------	----------------	------------------	----------------------

**FRONT QH MOUNTED COMMERCIAL SNOW BLOWERS AND ACCESSORIES**

<b>COMMERCIAL SNOW BLOWERS</b>				
L4474	74" Commercial Snowblower for L4060-L6060 Models Includes Hyd. Chute Deflector and Chute Rotation Motor Requires Snowblower Completion Kit, Quick Hitch, Driveline Kit, and Mid PTO Kit	K8L231L20	1280 lbs	\$10,289.00
L4485	80" Commercial Snowblower for L4060-L6060 Models Includes Hyd. Chute Deflector and Chute Rotation Motor Requires Snowblower Completion Kit, Quick Hitch, Driveline Kit, and Mid PTO Kit	K8L444L00	1320 lbs	\$10,555.00
<b>COMMERCIAL SNOW BLOWER COMPLETION KITS</b>				
L4433	Completion Kit for Comm. Snow Blower with L4455(A) Hitch Includes Drive Line Half and Hyd. Hoses	K269L60	20 lbs	\$337.00
L4434	Completion Kit for Comm. Snow Blower with L4554(A) Hitch Includes Auto Module, Hyd. Cylinder for Chute Deflector, Hyd. Hoses, and PTO Coupler	K895L20	35 lbs	\$1,119.00
<b>COMMERCIAL SNOW BLOWER OPTIONS</b>				
L2470	74" Teflon Cutting Edge for Commercial Snowblowers	K290L40	15 lbs	\$363.00
L2471	80" Teflon Cutting Edge for Commercial Snowblowers	K323L20	16 lbs	\$404.00





**Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060**

**FRONT QH MOUNTED ROTARY SWEEPERS AND ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>FRONT QH MOUNTED ROTARY SWEEPERS AND ACCESSORIES</b>				
<b>ROTARY SWEEPERS</b>				
L4467	60" Rotary Broom w/ 22" Diameter for L3560 only Power Angle Standard, Includes Hitch Lift Limiter Requires Quick-Hitch, Driveline Kit, Completion Kit, and Mid PTO Kit	K4L108L80	460 lbs	\$5,136.00
L4477	72" Rotary Broom w/ 22" Diameter for all Grand L60 Models Power Angle Standard, Includes Hitch Lift Limiter Requires Quick-Hitch, Driveline Kit, Completion Kit, and Mid PTO Kit	K4L780L80	550 lbs	\$5,976.00
<b>ROTARY SWEEPER COMPLETION KIT</b>				
L4488	Completion Kit for Rotary Sweeper with L4455(A) Hitch Includes Drive Line Half and Hyd. Hoses	K415L20	20 lbs	\$519.00
L4475	Completion Kit for Rotary Sweeper with L4554(A) Hitch Includes Auto Module, Hyd. Hoses, and PTO Coupler	K883L20	22 lbs	\$1,104.00
<b>ROTARY SWEEPER OPTIONS</b>				
BL2178	Side Caster Wheel	K434L40	45 lbs	\$543.00
L2168	60" Rubber Dust Deflector	K155L20	31 lbs	\$194.00
L2169	72" Rubber Dust Deflector	K184L80	36 lbs	\$231.00



**Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060**

**FRONT QH MOUNTED FLAIL MOWER AND ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
------------	-------------	----------------	------------------	----------------------

**FRONT QH MOUNTED FLAIL MOWER AND ACCESSORIES**

<b>FRONT FLAIL MOWER</b>				
L4457	72" Front Flail Mower for L4060 - L6060 Models Includes Y-Knives Requires Quick Hitch, Completion Kit, Driveline Kit, and Mid PTO Kit	K8L171L20	1400 lbs	\$10,214.00
<b>FLAIL MOWER COMPLETION KITS</b>				
L4448	Completion Kit for Flail Mower with L4455(A) Hitch Includes Drive Line Half and Hyd. Hoses	K302L40	20 lbs	\$378.00
L4458	Completion Kit for Flail Mower with L4554(A) Hitch Includes Auto Module, Hyd. Hoses, and PTO Coupler	K645L60	20 lbs	\$807.00
<b>FRONT FLAIL MOWER OPTIONS</b>				
L4437	Replacement Y-Knife Set, Includes 68 Knives	K482L40	380 lbs	\$603.00
L4438	Replacement Hammer Knife Set, Includes 34 Knives	K618L40	380 lbs	\$773.00
L4439	Replacement Duck Foot Knife Set, Includes 34 Knives	K528L00	380 lbs	\$660.00

**KUBOTA****Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060****BACKHOES AND ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
------------	-------------	----------------	------------------	----------------------

**BACKHOES AND ACCESSORIES**

REQUIRES A FRONT END LOADER TO BE MOUNTED WHEN BACKHOE IS ATTACHED

<b>BACKHOE</b>				
BH77	4-Pt. Mounted Quick Attach Backhoe for L3560 ROPS <b>only</b> Requires Sub Frame Kit Not Compatible with Top-N-Tilt Kits Not Compatible with Cab Model	K6B587B20	1077 lbs	\$8,234.00
<b>SUB FRAME KITS</b>				
BH4985	Subframe Kit for L3560 ROPS Models <b>only</b> Requires LA555 Loader	K1L176L00	292 lbs	\$1,470.00
<b>BACKHOE BUCKETS</b>				
BT1950A	10" Bucket - 3 Teeth	K394B40	63 lbs	\$493.00
BT1951A	12" Bucket - 3 Teeth	K464B80	69 lbs	\$581.00
BT1952A	16" Bucket - 4 Teeth	K615B20	82 lbs	\$769.00
BT1953A	24" Bucket - 5 Teeth	K804B00	118 lbs	\$1,005.00
<b>BACKHOE ACCESSORIES</b>				
BH1976	6 Position Mechanical Thumb	K450B40	51 lbs	\$563.00
L9467	Rubber Stabilizer Flip Pads Two required per Backhoe	K118L40	15 lbs	\$148.00



**Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060**

**BACKHOES AND ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
------------	-------------	----------------	------------------	----------------------

**BACKHOES AND ACCESSORIES**

REQUIRES A FRONT END LOADER TO BE MOUNTED WHEN BACKHOE IS ATTACHED

<b>BACKHOE</b>				
BH92	4-Pt. Mounted Quick Attach Backhoe for all Grand L60 Models Requires Sub Frame Kit and Mounting Kit Not Compatible with Top-N-Tilt Kits	K7L444L00	1696 lbs	\$9,305.00
<b>SUB FRAME KITS</b>				
BH4987	Mounting Kit for L3560 ROPS Models Requires LA805 Loader and BH4999	K313L60	55 lbs	\$392.00
BH4983	Mounting Kit for L3560 Cab Models Requires LA805 Loader and BH4999	K503L20	292 lbs	\$629.00
BH4989	Mounting Kit for L4060 - L6060 ROPS Models Requires LA805/LA1055 Loader and BH4999	K345L60	67 lbs	\$432.00
BH4982	Mounting Kit for L4060 - L6060 Cab Models Requires LA805/LA1055 Loader and BH4999 NOTE: For L6060HSTC, also order (QTY: 2) 7K500-16650 for installation	K534L40	196 lbs	\$668.00
BH4999	Subframe Kit for all Grand L60 Models	K893L60	345 lbs	\$1,117.00
<b>BACKHOE PIN-ON BUCKETS</b>				
BT3001	12" Bucket	K622L40	109 lbs	\$778.00
BT3002A	16" Bucket	K705L60	130 lbs	\$882.00
BT3003A	18" Bucket	K752L00	141 lbs	\$940.00
BT3004	24" Bucket	K875L20	172 lbs	\$1,094.00
BT3005A	30" Bucket	K1L009L60	205 lbs	\$1,262.00
BT3006	36" Bucket	K1L128L00	226 lbs	\$1,410.00
<b>BACKHOE QUICK COUPLER &amp; QUICK COUPLER BUCKETS</b>				
BT4550	BH92 Quick Coupler	K625L60	55 lbs	\$782.00
BT4552	12" Bucket	K754L40	117 lbs	\$943.00
BT4553	16" Bucket	K797L60	135 lbs	\$997.00
BT4554	18" Bucket	K838L40	144 lbs	\$1,048.00
BT4555	24" Bucket	K990L40	176 lbs	\$1,238.00
BT4557	36" Bucket	K1L262L40	223 lbs	\$1,578.00
<b>BACKHOE ACCESSORIES</b>				
BH4948	Hydraulic Valve Kit	K834L40	23 lbs	\$1,043.00
BT4598	Hydraulic Thumb Requires BH4948 Valve Kit	K1L927L20	142 lbs	\$2,409.00
BH4949	6 Position Mechanical Thumb	K846L40	141 lbs	\$1,058.00
L9467	Rubber Stabilizer Flip Pads Two required per Backhoe	K118L40	15 lbs	\$148.00



**Grand L 60 Series L3560 / L4060 / L4760 / L5060 / L5460 / L6060**

**REAR MOUNT SNOW BLOWERS AND ACCESSORIES**

ORDER CODE	DESCRIPTION	FACTORY NUMBER	APPROX. SHIP WT.	SUGGESTED LIST PRICE
<b>REAR MOUNT SNOW BLOWERS AND ACCESSORIES</b>				
<b>REAR MOUNT SNOW BLOWER</b>				
BLMX3164	64" Two-Stage Commercial Snowblower Mounts to Category I 3-Point Hitch Requires Manual Rotator Chute or Hydraulic Chute Rotator	K2B914B40	681 lbs	\$3,643.00
LMX3174	74" Two-Stage Commercial Snowblower Mounts to Category I, II, and III 3-Point Hitch Requires Manual Rotator Chute or Hydraulic Chute Rotator	K3L675L20	760 lbs	\$4,594.00
<b>REAR MOUNT SNOW BLOWER OPTIONS</b>				
BL2665	Manual Chute Rotator	K165B60	11 lbs	\$207.00
BL6399	Hydraulic Chute Rotator Requires 1 Set of Hyd. Rear Remote Valves	K752B00	20 lbs	\$940.00
BL2666A	Hydraulic Chute Deflector Kit Includes Electric Selector Valve Requires Hydraulic Chute Rotator	K920B80	22 lbs	\$1,151.00
B2516A	Electric Chute Deflector	K608B80	9 lbs	\$761.00
L2177	Width Extension Kit, adds 5" overall cut	K108L80	27 lbs	\$136.00