VX-261™ Portable

Standard Package Includes:

- Standard Battery (Li-ion, 1380 mAh FNB-V133LI)
- Standard VAC-UNI Rapid Charger (CD-58 & PA-55)
- Standard Antenna (UHF: ATU-6D, VHF: ATV-8C)
- Clip 20 Belt Clip
- Standard 3 Year Warranty

Product Features:

- 16 Channels
- 2 Programmable Side Buttons
- LED Battery Indicator
- 700mW Internal Speaker
- Emergency Alert
- Lone Worker Alert
- Multi-Mode Scanning
- ARTS TM (Auto-Range Transpond System)

Analog Features:

- MDC1200 ANI Encode
- DTMF ANI Encode
- 2-Tone Encode and Decode
- 5-Tone Encode and Decode
- Fleetsync® ANI Encode
- Busy Channel Lockout, Busy Tone Lock Out
- Radio to radio cloning



Models

Model #	Band Split	Band	Power	Conv Chan	Display	Keypad	MSRP
AC128N501-MOT-NA	136-174 MHz	VHF	5W	16	No	No	\$238.70
AC128U502-MOT-NA	403-470 MHz	UHF	5W	16	No	No	\$238.70
AC128U501-MOT-NA	450-512 MHz	UHF	5W	16	No	No	\$238.70

VX-261™ Portable

Options: TO COMPLETE AN ORDER YOU MUST SELECT ONE (1) CHOICE FOR EACH OPTION

Battery Options - Both Batteries Use Standard VAC-UNI Charger

Options	Description	MSRP
STDBAT0819	Standard Battery -	\$0.00

|--|--|

Antenna Options

Options	Description
STDANT0819	Standard Antenna
QA07038	VHF Antenna, ATV-
QA07036	VHF Antenna, ATV-
QA07041	VHF Antenna, ATV-
QA07040	VHF Antenna, ATV-
QA07039	VHF Antenna, ATV-
QA07049	UHF Antenna, ATU-
QA07050	UHF Antenna, ATU-
QA07037	Omit Antenna

Charger Options

Options	Description	MSRP
STDCHG0819	Standard Charger	\$0.00
QA07043	VAC-UNI 240V, CD-	\$0.00
QA07035	Omit Standard	-\$38.1

Warranty Option

Options	Description	MSRP
QA07464	Standard 3 Year	\$0.00

THE FOLLOWING ARE

Shipping Options

Options	Description	MSRP
QA07048	Bulk Packaging	\$0.00

Microphone Options

Options	Description	MSRP
QA07044	MH-360S Compact	\$22.28
QA07045	MH-450S Medium	\$28.29
QA07046	MH-45B4B Noise	\$86.99
QA07047	MH-66A4B IP57	\$97.60

Quantity Discount Program

You may "mix and

Warranty

The VX-261 ships

FCC/IC Information:

(136-174 MHz) AXI11283020 / 109U-89FT3838 (403-470 MHz) AXI11284620 / 109U-89FT4933

Environmental Specifications:

Operating Temperature: -30° to +60° C (Radio Only)

Sealing: IP55

(450-512 MHz) AXI11284720 / 109U-89FT4941

VX-264™ Portable

Standard Package Includes:

- Standard Battery (Li-ion,1380 mAh FNB-V133LI)
- Standard VAC-UNI Rapid Charger (CD-58 & PA-55)
- Standard Antenna (UHF: ATU-6D, VHF: ATV-8C)
- Clip 20 Belt Clip
- Standard 3 Year Warranty

Product Features:

- 128 Channels
- 6 Programmable Buttons
- 8 Character Alphanumeric Display
- 700mW Internal Speaker
- Emergency Alert
- Lone Worker Alert
- Multi-Mode Scanning
- ARTS TM (Auto-Range Transpond System)

Analog Features:

- MDC1200 Encode: ANI, Call Alert, Sel Call, Emergency
- DTMF ANI Encode
- 2-Tone Encode and Decode
- 5-Tone Encode and Decode
- Fleetsync® ANI Encode
- BCLO, BTLO and TOT Functions
- Voice Inversion Encryption
- Radio to radio cloning



Models

	Conv							
Model #	Band Split	Band	Power	Chan	Display	Keypad	MSRP	
AC127N501-MOT-NA	136-174 MHz	VHF	5W	128	Yes	Limited	\$307.66	
AC127U502-MOT-NA	403-470 MHz	UHF	5W	128	Yes	Limited	\$307.66	
AC127U501-MOT-NA	450-512 MHz	UHF	5W	128	Yes	Limited	\$307.66	

VX-264™ Portable

Battery Options - Both Batteries Use Standard VAC-UNI Charger

Options: TO COMPLETE

buttery options	Dotti Datteries Ose Stand	ara vac-ora charger	
Options	Description		MSRP
STDBAT0192	Standard		\$0.00
OA07170	2300mAh Li-lon		\$21.22

Antenna Options

Options	Description	MSRP

TDANT0192	Standard	
QA07166	VHF Antenna,	
QA07164	VHF Antenna,	
QA07169	VHF Antenna,	
QA07168	VHF Antenna,	
QA07167	VHF Antenna,	
QA07180	UHF Antenna,	
QA07179	UHF Antenna,	
QA07165	Omit Antenna	

Charger Options

Options	Description	MSRI
STDCHG0192	Standard	\$0.00
QA07172	VAC-UNI 240V,	\$0.00
QA07173	Omit Standard	-\$38.1

Warranty Option

Options	Description	MSRP
QA07464	Standard 3 Year	\$0.00

THE FOLLOWING ARE

Shipping Options

Options	Description	MSRP
QA07178	Bulk Packaging	\$0.00

Microphone Options

Options	Description	MSRP
QA07174	MH-360S	\$22
QA07175	MH-450S	\$28
QA07176	MH-45B4B	\$86
QA07177	MH-66A4B IP57	\$97.

Quantity Discount Program

You may "mix and

Warranty

The VX-264 ships

FCC/IC Information:

(136-174 MHz) AXI11273020 / 109U-89FT3842 (403-470 MHz) AXI11274620 / 109U-89FT4939 (450-512 MHz) AXI11274720 / 109U-89FT4940

Environmental Specifications:

Operating Temperature: -30° to +60° C (Radio Only)

Sealing: IP55

EVX-261™ Portable

Standard Package Includes:

- Standard Battery (Li-ion,1380 mAh FNB-V133LI)
- Standard VAC-UNI Rapid Charger (CD-58 & PA-55)
- Standard Antenna (UHF: ATU-6D, VHF: ATV-8C)
- Clip 20 Belt Clip
- Standard 3 Year Warranty

Product Features:

- 16 Channels
- 12.5 kHz only Channel Spacing
- 2 Programmable Side Buttons
- LED Battery Indicator
- 700mW Internal Speaker
- Emergency Alert
- Lone Worker Alert
- Multi-Mode Scanning
- Internal VOX
- ARTS TM (Auto-Range Transpond System)

Analog Features:

- MDC1200 ANI Encode
- 2-Tone Encode and Decode
- 5-Tone Encode and Decode
- Remote Stun/Kill/Revive (5-Tone)
- CTCSS/DCS Encode and Decode
- Fleetsync® ANI

Digital Features:

- All Call/Group Call /Individual Call
- Transmit Interrupt (Decode Only)
- Dual Capacity Direct Mode
- Basic Privacy



Models

				Conv			
Model #	Band Split	Band	Power	Chan	Display	Keypad	MSRP
AC137N501-MOT-NA	136-174 MHz	VHF	5W	16	No	No	\$334.18
AC137U502-MOT-NA	403-470 MHz	UHF	5W	16	No	No	\$334.18
AC137U501-MOT-NA	450-512 MHz	UHF	5W	16	No	No	\$334.18

EVX-261™ Portable

Options: TO

Battery Options - Both Batteries Use Standard VAC-UNI Charger

Options	Description	MSRP
STDBAT0420	Standard Battery -	\$0.00
QA07208	2300mAh Li-Ion	\$21.22

Antenna Options

Options	Description	
STDANT0420	Standard Antenna	
QA07204	VHF Antenna, ATV-	
QA07205	VHF Antenna, ATV-	
QA07206	VHF Antenna, ATV-	
QA07216	UHF Antenna, ATU-	
QA07217	UHF Antenna, ATU-	
QA07218	UHF Antenna, ATU-	
QA07219	UHF Antenna, ATU-	
QA07220	UHF Antenna, ATU-	
QA07207	Omit Antenna	

Charger Options

Options	Description	
TDCHG0420	Standard Charger	
QA07210	VAC-UNI 240V	
QA07211	Omit Standard	

Charger Options

Options	Description	MSRP
QA07464	Standard 3 Year	\$0.00

Warranty Option

Options	Description	MSRP
QA07464	Standard 3 Year	\$0.00

THE FOLLOWING ARE

Shipping Options

Options	Description	MSRP
QA07215	Bulk Packaging	\$0.00

Microphone Options

Options	Description	MSRP
QA07212	MH-360S Compact	\$22.28
QA07213	MH-450S Medium	\$28.29
QA07214	MH-66A4B IP57	\$97.60

Quantity Discount Program

You may "mix and match" any combination of EVX-S24 / EVX-261 / VX-261 / VX-264 / VX-451 / VX-459 portable models ("Radio Units") on a single order and receive the appropriate

Warranty

The EVX-261 ships standard with a 3-year warranty

FCC/IC Information:

(136-174 MHz) AXI11373020 / 109U-89FT3839 (403-470 MHz) AXI11374620 / 109U-89FT4944 (450-512 MHz) AXI11374720 / 109U-89FT4934

Environmental Specifications:

Operating Temperature: -30° to +60° C (Radio Only) Sealing: IP55

EVX-S24™ Portable

Standard Package Includes:

- Standard Battery (Li-ion, 2300 mAh BT100)
- Standard Antenna (ATU-20DS)
- Standard Micro USB AC Charger (PA-57B)
- Clip 27 Belt Clip
- Standard 3 Year Warranty

Product Features:

- 256 Channels
- 4 Programmable Buttons
- 500mW Internal Speaker
- Emergency Alert
- Lone Worker Alert
- Multi-Mode Scanning
- Internal VOX
- ARTS TM (Auto-Range Transpond System)

Signaling Features:

- CTCSS/DCS Encode / Decode
- 2-Tone / 5-Tone
- Stun/Kill/Revive (5-Tone & DTMF Pager)
- MDC1200 Features
- Fleetsync® ANI

Analog Features:

- BTLO
- Voice Inversion Encryption

Digital Features:

- All Call/Group Call /Individual Call
- Transmit Interrupt (Decode Only)
- Dual Capacity Direct Mode
- Basic & Enhanced Privacy
- Site Search
- Text Messaging





Models

				Conv			
Model #	Band Split	Band	Power	Chan	Display	Keypad	MSRP
AC146U502-MOT-NA (Black)	403-470 MHz	UHF	3W	256	Yes	Limited	\$309.93
AC146U512-MOT-NA (Yellow)	403-470 MHz	UHF	3W	256	Yes	Limited	\$309.93

EVX-S24™ Portable

Options: TO COMPLETE AN	

Battery Options - Both Batteries Use VAC-UNI Charger

Options	Description	MSRP
STDBAT0007	Standard	\$0.00

Antenna Options

Options	Description	
STDANT0007	Standard	
QA07068	UHF Antenna,	
QA07069	UHF Antenna,	
QA07070	UHF Antenna,	
QA07072	UHF Antenna,	
QA07073	UHF Antenna,	
QA07074	UHF Antenna,	
QA07075	UHF Antenna,	
QA07071	Omit Antenna	

Charger Options

Options	Description
STDCHG0007	Standard
QA07079AA	Micro USB AC
QA07077	Micro USB AC
QA07078	Micro USB AC
QA07080	Omit Standard

Warranty Option

Options	Description	MSRP
QA07464	Standard 3	\$0.00

THE FOLLOWING ARE OPTIONAL

Shipping Options

Options	Description	MSRP
QA07083	Bulk Packaging	\$0.00

Microphone Options

Options	Description	MSRP
QA07081	MH-90A4B	\$33.95
QA07082	MH-66F4B	\$97.60

Quantity Discount Program

You may "mix and match" any

Warranty

The EVX-S24 ships standard with a 3-year warranty

Technology Bid-ESCNJ 18/19-03 Educational Services Commission of New Jersey
NJ State Approved Co-op #65MCESCCPS

Bid Term - 7/1/18 - 6/30/20; Extended to 6/30/22

FCC/IC Information:

(403-470 MHz) AXI11464620 / 109U-89FT4935

Environmental Specifications:

Operating Temperature: -30° to +60° C (Radio Only) Sealing: IP67

VX-451/454/459™ Portables

Standard Package Includes:

- Standard Battery (Li-ion,1380 mAh FNB-V133LI)
- Standard VAC-UNI Rapid Charger (CD-58 & PA-55)
- Standard Antenna (UHF: ATU-16D, VHF: ATV-16C)
- Clip 20 Belt Clip
- Standard 3 Year Warranty

Product Features:

- 32 channels (VX-451), 512 channels (VX-454/459)
- Programmable Buttons: 3 (VX-451), 7 (VX-454), 9 (VX-459)
- 700mW Internal Speaker
- Emergency Alert
- Lone Worker Alert
- Multi-Mode Scanning
- Internal VOX
- ARTS TM (Auto-Range Transpond System)

Analog Features:

- Embedded MDC1200 Encode/Decode
- 2-Tone Encode and Decode
- 5-Tone Encode and Decode
- Stun/Kill/Revive (5-Tone)
- CTCSS/DCS Encode and Decode
- Fleetsync® ANI
- Channel Announcement
- Voice Inversion Scrambling
- Optional Voice Storage (requires AAH88X001)
- Radio to radio cloning



Models

Model #	Band Split	Band	Power	Conv Chan	Display	Keypad	MSRP
AC095N521-MOT-NA	136-174 MHz	VHF	5W	32	No	No	\$339.49
AC095U522-MOT-NA	403-470 MHz	UHF	5W	32	No	No	\$339.49
AC095U521-MOT-NA	450-512 MHz	UHF	5W	32	No	No	\$339.49
AC094N522-MOT-NA	136-174 MHz	VHF	5W	512	Yes	Limited	\$403.14
AC094U524-MOT-NA	403-470 MHz	UHF	5W	512	Yes	Limited	\$403.14
AC094U522-MOT-NA	450-512 MHz	UHF	5W	512	Yes	Limited	\$403.14
AC094N521-MOT-NA	136-174 MHz	VHF	5W	512	Yes	Yes	\$466.80
AC094U523-MOT-NA	403-470 MHz	UHF	5W	512	Yes	Yes	\$466.80
AC094U521-MOT-NA	450-512 MHz	UHF	5W	512	Yes	Yes	\$466.80

VX-451/454/459™ Portables

Options:	TO	CON	ΛPL	ET!	E
----------	----	-----	-----	-----	---

Battery Options - Both Batteries Standard Use VAC-UNI Charger

Options	Description	MSRP
STDBAT0637	Standard Battery -	\$0.00
QA007154AA	2300mAh Li-Ion	\$31.83
QA007156	2300mAh Li-Ion	\$90.18

^{*} The VX-451, VX-454

Antenna Options

Tillia options	
Options	Description
STDANT0637	Standard Antenna
QA007150	VHF Antenna, ATV-
QA007151	VHF Antenna, ATV-
QA007153	VHF Antenna, ATV-
QA007166	UHF Antenna, ATU-
QA007167	UHF Antenna, ATU-
QA007168	UHF Antenna, ATU-
QA007169	UHF Antenna, ATU-
QA007165	UHF Antenna, ATU-
QA007152	Omit Antenna

Charger Options

Options	Description	MSR
STDCHG0637	Standard Charger	\$0.00
QA007157	VAC-UNI 240V, CD-	\$0.00
QA007158	Omit Standard	-\$38.1

Warranty Option

Options	Description	MSRP
QA07464	Standard 3 Year	\$0.00

THE FOLLOWING ARE

Shipping Options

Options	Description	MSRP
QA007163	Bulk Packaging	\$0.00

LTR Option

Options	Description	MSRP
QA007164	LTR Trunking	\$69.01

Microphone Options

Options	Description	MSRP
QA007159	MH-360S Compact	\$22.28
QA007160	MH-450S Medium	\$28.29
QA007161	MH-45B4B Noise	\$86.99
QA007162	MH-66A4B IP57	\$97.60

Quantity Discount Program

You may "mix and match" any combination of EVX-S24 / EVX-261 / VX-261 / VX-261 / VX-454 / VX-459 portable models ("Radio Units") on a single order and receive the appropriate quantity

Warranty

The VX-450 ships standard with a 3-year warranty

FCC/IC Information:

(136-174 MHz) K6610943020 / 109U-89FT3843 (403-470 MHz) K6610944620 / 109U-89FT4942 (450-512 MHz) K6610944720 / 109U-89FT4943

Environmental Specifications:

Operating Temperature: -30° to +60° C (Radio Only) Sealing: IP57

VX-2100™ Mobile

Standard Package Includes:

- Standard Microphone (MH-67A8J)
- Standard 3 Year Warranty

Product Features:

- 8 Channels
- 50W or 25W Power Output
- 6 Programmable Buttons
- CTCSS/DCS Encode / Decode
- DTMF ANI
- 2-Tone Encode/Decode
- Built-In 5 Tone Signaling
- Multi-Mode Scanning
- Emergency
- ARTS TM (Auto-Range Transpond System)
- D SUB 15 Pin Accessory Connector



Models

Model #	Band Split	Band	Power	Conv Chan	Display	MSRP
AC061N533-MOT-NA	136-174 MHz	VHF	25W	8	N/A	\$350.10
AC061N531-MOT-NA	136-174 MHz	VHF	50W	8	N/A	\$366.01
AC061U537-MOT-NA	403-470 MHz	UHF	25W	8	N/A	\$371.32
AC061U535-MOT-NA	403-470 MHz	UHF	45W	8	N/A	\$403.14
AC061U533-MOT-NA	450-512 MHz	UHF	25W	8	N/A	\$371.32
AC061U531-MOT-NA	450-512 MHz	UHF	45W	8	N/A	\$403.14

VX-2100™ Mobile

Options: TO COMPLETE

Microphone Options

microphone options					
Options	Description	MSRP			
STDMIC0649	Standard	\$0.00			
QA07200AA	DTMF	\$15.91			
QA07201	Omit	-\$42.44			

Warranty Option

Options	Description	MSRP
QA07464	Standard 3 Year	\$0.00

Quantity Discount Program

You may "mix and match" any combination of VX-2100/VX-2200 mobile models ("Radio Units") on a single order and receive the appropriate quantity discount for each model. Quantity discounts are

Warranty

The VX-2100 ships standard with a 3-year warranty

FCC/IC Information:

(136-174 MHz 25W) K6610613040 / 109U-92FT3840 (136-174 MHz 50W) K6610613040 / 109U-92FT3841 (403-470 MHz 25W) K6610614640 / 109U-92FT4946 (403-470 MHz 45W) K6610614640 / 109U-92FT4936 (450-512 MHz 25W) K6610614730 / 109U-92FT4937 (450-512 MHz 45W) K6610614730 / 109U-92FT4937

Environmental Specifications:

Operating Temperature: -30° to +60° C (Radio Only)

VX-2200™ Mobile

Standard Package Includes:

- Standard Microphone (MH-67A8J)
- Standard 3 Year Warranty

Product Features:

- 128 Channels
- 50W or 25W Power Output
- 6 Programmable Buttons
- CTCSS/DCS Encode / Decode
- DTMF ANI
- 2-Tone Encode/Decode
- Built-In 5 Tone Signaling
- Multi-Mode Scanning
- Emergency
- ARTS TM (Auto-Range Transpond System)
- D SUB 15 Pin Accessory Connector
- MDC1200/GE-Star ANI Encode (Option Board)



Models

Model #	Band Split	Band	Power	Conv Chan	Display	MSRP
AC061N534-MOT-NA	136-174 MHz	VHF	25W	128	N/A	\$392.53
AC061N532-MOT-NA	136-174 MHz	VHF	50W	128	N/A	\$419.06
AC061U538-MOT-NA	403-470 MHz	UHF	25W	128	N/A	\$413.75
AC061U536-MOT-NA	403-470 MHz	UHF	45W	128	N/A	\$445.58
AC061U534-MOT-NA	450-512 MHz	UHF	25W	128	N/A	\$413.75
AC061U532-MOT-NA	450-512 MHz	UHF	45W	128	N/A	\$445.58

VX-2200™ Mobile

Ontions	TΩ	COM	1 D I	ETE

Microphone Options

Options	Description	MSRP
STDMIC0649	Standard	\$0.00

Warranty Option

Options	Description	MSRP
QA07464	Standard 3	\$0.00

Quantity Discount Program

You may "mix and match" any combination of VX-2100/VX-2200 mobile models ("Radio Units") on a single order and receive the appropriate quantity discount for each model. Quantity

Warranty

The VX-2200 ships standard with a 3-year warranty

FCC/IC Information:

(136-174 MHz 25W) K6610613040 / 109U-92FT3840 (136-174 MHz 50W) K6610613040 / 109U-92FT3841 (403-470 MHz 25W) K6610614640 / 109U-92FT4946 (403-470 MHz 45W) K6610614640 / 109U-92FT4936 (450-512 MHz 25W) K6610614730 / 109U-92FT4937 (450-512 MHz 25W) K6610614740 / 109U-92FT4938

Environmental Specifications:

Operating Temperature: -30° to +60° C (Radio Only)

VX-5500LB™ Mobile

Standard Package Includes:

- Standard Microphone (MH-53C7A)
- Standard 3 Year Warranty

Product Features:

- 250 Channels
- 8 Digit Alphanumeric Display
- 7 Programmable Backlit Buttons
- CTCSS/DCS Encode / Decode
- DTMF Signaling & Dialing Features
- Status Quick Check
- BCLO, BTLO, TOT Functions
- Multi-Mode Scanning
- Emergency
- D SUB 25 Pin Accessory Connector



Models

I	Model #	Band Split	Band	Power	Conv Chan	Display	MSRP
	AC034L005-VX	37-50 MHz	Low Band	70W	250	N/A	\$978.68

VX-5500LB™ Mobile

Options: TO

Microphone Options

Options	Description	MSRP
QA02625	Standard	\$0.00

Warranty Option

Options	Description	MSRP
QA07464	Standard 3	\$0.00

Warranty

The VX-5500LB ships standard with a 3-year warranty

FCC/IC Information:

(37-50 MHz) K66VX-5500L / 511B-VX5500L

Environmental Specifications:

Operating Temperature: -30° to +60° C (Radio Only)

DTR650™ Portable

Standard Dackage Includes:

- Standard Rattery Lision 1500 mAh Rattery 3 61/1530611
- Standard Charger 1 Hour Panid Charger (52060)
- Dron-In Charging Tray (52062)
- Stubby 000 Antonna (85052411106)
- Cwival Balt Halstor (52061)
- CD-Rom Hear Guida
- Muick Rafaranca Card
- One Vear Warranty

Product Features:

- QOO MHz ISM Fraguancy-Honning Digital Shread Shactrum
- 12 Alart Tonac nluc VihraCall™
- Battery Meter
- Licence Free Communication
- Backlit Display
- Private Calling: One-to-One Communication
- Dublic Group Calling: One-to-Many Jun to 100 Group IDc)
- Private Group Calling, One-to-Many (selected from Contacts)
- Dublic Group Scan with Scan List
- Pamota Dicabla
- Pamota Monitorina
- Ramota Tima / Nata I Indata
- CMC (Chart Maccaging Sarvica) 5-10 Quick notes
- Contact List: Canacity 150 Shared Private / Dublic Group / Private Group
- CDC Paguirad to Modify Quick Notas

Drogrammahla Fasturasi

- Call Tones
- Monitor
- OTA fleet cloning
- Accessory Talk Darmit Tona (TET) independent volume control
- Disable Padio DTT when using accessory with remore DTT
- Ontion to disable front-nanel radio programming
- Cloning conies all configuration
- Road Drivato ID (roads fields other than just DID)



antity a new order er the fact

Deletion of units from order of cancellation of line items

Models

Model #	Band	Dand	Dower	Conv.	Display	Keypad	MSRP
Model #	Split	Band	Power	Channels	Display	кеурац	IVISKP
AAH73WCF9NA5_N	N/A	900 MHz	On-Site	N/A	Yes	Limited	\$350.00

CP200d™ Portable

Standard Dackago Includos:

- Standard Rattery (11 ion 2250 mAh 7 51/ MNTMAAQ7 R)
- Standard Charger CFC Complaint (90 Minute Panid Pate DMDN/173A)
 Standard Astenna (VIHE Helifley NADESO? D / LIHE White DMAE/1016)
 2" Polf Clin (HI NOZES)
- 2 Vaar Marranty ± 1 Vaar Carvica from the Start LITE

Product Features:

6 75a / 17 5 kHz only Channel Specing
7 Programmable Side Ruttons

LED Battory Indicator

Analog Features:

Companding V DandM Tachnology
Time Out Timer

Internal VAV

Cincle Driverity Con

Adjustable Dower Loyels

MDC1200 DTT ID (Encode)

Ouil Call II Call Alart (Decode)

Ouik Call II Salactive Call (Decode)

Digital Features:

Ontional for Analog models
Standard for Digital models
Basic Drivacy
Dadin Chack (Dacada)
Demote Monitor (Decade)
Dadin Inhibit (Decade)
Dual Driority Con
Transmit Interrunt (Decade)

Programmable Features:

Programmable Features:

Ligh / Low Dower

Channel Scan
LED Battery Indicator

Squalch Loyale

Danaster / Talkaround

Volume Scat
Tight / Normal Squalch

VOV On / Off

Nuisance Channel Dalate

Voice Announcement Scan (Digital Mode)

Pricing may be lower in MOL due to on going promotion until March 31, 2018.

Analog Models

Model #	Band Split	Band	Power	Conv Chan	Display	Keypad	MSRP
AAH01JDC9JC2_N	136-174 MHz	VHF	5W	16	No	No	\$485.00
AAH01QDC9JC2_N	403-470 MHz	UHF	4W	16	No	No	\$518.33

Digital Models

Model #	Band Split	Band	Power	Conv Chan	Display	Keypad	MSRP
AAH01JDC9JA2_N	136-174 MHz	VHF	5W	16	No	No	\$568.33
AAH01QDC9JA2_N	403-470 MHz	UHF	4W	16	No	No	\$601.67



CP200d™ Portable

Options: TO

Battery Options

Options	Description	MSRP
STDBAT0752	Stanuaru Battani Li	\$0.00
QA03815	Slim Li-lon,	\$0.00
QA03816	NiMH, 1400	\$0.00

Antenna Options

Options	Description	MSRP
STDANT0752	Standard	\$0.00
QA00194	VHF Stubby	\$0.00
QA00189	VHF Stubby	\$0.00
QA03800	UHF Stubby	\$0.00
QA00190	UHF Stubby	\$0.00
H112	Omit Antenna	-\$3.50

Charger Options

Options	Description	MSRP
STDCHG0752	Standard Charger CEC	\$0.00
H951	Omit	-\$15.00

Shipping Options

Options	Description	MSRP
STDBOX0752	Standard	\$0.00
H415	Bulk	\$0.00

Warranty Options

Options	Description	MSRP
STDRSA0752	Standard 2 Year	\$0.00
QA00510	Omit 1Year	-\$18.33

CP200d™ Portable

General Options

Options	Description		MSRP
QA00531	Remote		\$73.50
QA00532	Remote		\$75.00
QA04002	Lightweight		\$60.00
HKVN4223	Analog to		\$83.00
Q884	1 Year Service		\$34.00
H885	2 Year Service	from the Start - LITE (US Only)	\$65.00

Quantity Discount Program

You may "mix and match" any combination of \$L300/CP185/CP200d portable models and/or CM200d/CM300d mobile models ("Radio Units") on a single order and receive the appropriate quantity discount for each model. Quantity discounts are calculated and granted at the time a new order is placed ("Qualifying Order"). Additional Radio Units added to the Qualifying Order will be charged at the single Radio Unit price without discount. Deleting or cancelling Radio Units from a Qualifying Order will be viewed as a new Qualifying Order and reseller will receive the discount offered (if any) for the number of Radio Units actually shipped. All Radio Units must be shipped at the same time in order to qualify for the corresponding product models quantity discount. Change order requests or Radio Units returns that extend, stagger or otherwise change the number of Radio Units actually purchased in a single shipment, will result in a charge to the reseller's account for the difference in price between the number of units purchased and the quantity discount reseller qualified under a Qualifying Order.

Service from the Start LITE

MOTOTRBO portable and mobiles radios ship with a standard 2-year parts and labor warranty. Additionally, they ship standard with a 1-year Service from the Start -LITE (SFS) option. If you desire additional years of SFS, you may choose one of the above general options. Please note that these plans are in addition to the 2-year standard warranty and 1 year SFS that ships standard with the unit. Repairs will be made only at the designated Motorola repair depot. Local services are not included. Motorola will pay the inbound shipping charges only with use of the Motorola designated delivery service. Motorola will nay for outhound chinning via Motorola's normal chinning methods. No discounts are allowed on these ontions

FCC/IC Information: (136-174 MHz) ABZ99FT3092 / 109AB-99FT3092 (403-470 MH z) ABZ99FT4094 / 109AB-99FT4094

Environmental Specifications:Operating Temperature: -30° to +60° C (Radio Only) Sealing: IP54

CP185™ Portable

Standard Dackage Includes:

- Standard Rattery (Li-Ion 1750T mah PMNNAA76a)
- Ranid Rate Charger CFC Complaint (< 3 Hours Rase: PMPN41324 Sunply: 25009297001)
- Standard Antonna (VHE Holiflay NAD6502 R / LIHE Stubby PMAFAOO2 R) * See General Notes
- 2" Spring Action Rolt Clin (HI NORAA)
- Ouick Reference Guide (68007024011)
- 7 Vear Marranty

Product Features:

- Ruilt-in Simple Voice Scrambling
- Internal V∩Y
- 12 5 kHz only Channel Spacing
- Companding-Fypanding (Y-Dand™)
- 8-Character Alphanumeric Display
- 16 Channels
- 2 Programmable Side Ruttons
- 3 Programmable Front Ruttons
- Front Pannal Feature and Rutton Configuring Mode
- Rattery Saver
- Normal and Priority Scan (1 List)
- Multi-Channel Canability
- High Power
- Talkaround Canability
- Frannomically Decianed
- Rusy Channel Lockout
- Low Rattery Alert
- Receive Only Channel
- MDC 1200/Quik Call II/DTMF Signalling (Signalling models only)

Programmable Features

- Racklight	
- Channel Aliac	
- Channel Scan	

- Keynad Lock - Monitor

- Muicance Channel Delete - Power Level

- Reneater / Talkaround

Povorco Burct

- Scramhling Code Salact

- Scramhling On/Off

- Squelch Level

- Sticky Monitor

- TDI /DDI Fnahla

- Valuma Sat

- V/OX On / Off

Frequencies Not Allowed:

IDIN IDE IUNI DI	111000-111			
140 000	155 175	167 በ3በ	446 440	460 000
155 በ1በ	155 5በ5	160 005	116 115	167 725
155 በ5በ	150 005	17በ በበበ	155 205	467 900
155 በ2በ	160 000	170 005	/ 56 010	<i>ለ</i> 62 በ1በ
155 015	160 005	172 025	/56 N15	/6ዩ 1ን5
155 170	161 <i>4</i> 50	173 990	456 125	468 740
155 120	167 025		458 195	470 <u>000</u>
				//79 QNN



Default Francies

Additional frequencies can be added using the CP5. All frequencies must be divisible by 5.0 or 6.25 kHz.

Caution: Frequencies on the VHF band in the US have been assigned by the FCC with channel centers every 7.5 kHz, which means some of these frequencies are not evenly divisible by 6.25 kHz or 5 kHz. In order for a radio to be able to synthesize frequencies that are not evenly divisible by 6.25 kHz or 5 kHz, it requires a more sophisticated synthesizer and hardware than the one offered with this model.

Standard Models

Model #	Band Split	Band	Power	Conv	Display	Keypad
AAH03KEF8AA7 N	136-174 MHz	VHF	2-5W	16	Yes	Limited
AAH03RDF8AA7 N	435-480 MHz	UHF	2-4W	16	Yes	Limited

Signalling Models Intent to cancel in progress for these models

Model #	Band Split	Band	Power	Conv Chan	Display	Keypad
AAH03KEC4AB7 N	136-174 MHz	VHF	2-5W	16	No	No
AAH03KEF4AB7 N	136-174 MHz	VHF	2-5W	16	Yes	Limited
AAH03RDC4AB7 N	435-480 MHz	UHF	2-4W	16	No	No
AAH03RDF4AB7 N	435-480 MHz	UHF	2-4W	16	Yes	Limited

CP185™ Portable

Options: TO

Configuration Options

Options	Description
STDPKG0133	Li-Ion 1750T mAh Battery (PMNN4476) & Charger
QA01113	Li-Ion High Cap.2150 mAh Battery (PMNN4080) & Charger
QA01114	NiMH 1300 mAh Battery (PMNN4082) & Charger

General Options

Options	Description	MSRP
HA00041	Retail Temple Transducer (PMLN5003)	\$79.00
QA00531	Remote Speaker Microphone with Ear Jack, Coiled Cord and Swivel Clothing Clip (PMMN4013)	\$73.50
QA00532	Remote Speaker Microphone with IP57 Rating, Coiled Cord and Swivel Clothing Clip (PMMN4029)	\$75.00
QA04002	Lightweight Headset with Swivel Boom Microphone (PMLN6538)	\$57.00
QA01116	Lightweight Single Muff Adjustable Headset w/Swivel Boom Microphone (HMN9013)	\$57.00
QA01117	UHF Whip (16.5 cm) 430-520Mz (PMAE4016)	\$11.75
QA01315	VHF Stubby (9 cm) 136-155 MHz (PMAD4012)	\$13.25
QA01316	VHF Stubby (9 cm) 155-174 MHz (PMAD4013)	\$13.25
QA01318	VHF Heliflex 136-162 MHz (HAD9338)	\$11.75
QA04755	Swivel Earpiece with Mic/PTT (PMLN7189)	\$29.00
Q884	1 Year Service from the Start - LITE (US Only)	\$34.00
H885	2 Year Service from the Start - LITE (US Only)	\$65.00
H886	3 Year Service from the Start - LITE (US Only)	\$97.00

Quantity Discount Program

You may "mix and match" any combination of SL300/CP185/CP200d portable models and/or CM200d/CM300d mobile models ("Radio Units") on a single order and receive the appropriate quantity discount for each model. Quantity discounts are calculated and granted at the time a new order is placed ("Qualifying Order"). Additional Radio Units added to the Qualifying Order will be charged at the single Radio Unit price without discount. Deleting or cancelling Radio Units from a Qualifying Order will be viewed as a new Qualifying Order and reseller will receive the discount offered (if any) for the number of Radio Units actually shipped. All Radio Units must be shipped at the same time in order to qualify for the corresponding product models quantity discount. Change order requests or Radio Units returns that extend, stagger or otherwise change the number of Radio Units actually purchased in a single shipment, will result in a charge to the reseller's account for the difference in price between the number of units purchased and the quantity discount reseller qualified under a Qualifying Order.

Service from the Start LITE

Technology Bid-ESCNJ 18/19-03

Educational Services Commission of New Jersey NJ State Approved Co-op #65MCESCCPS

MOTOTRBO portable and mobiles radios ship with a standard 2-year parts and labor warranty. Additionally, they ship standard with a 1-year Service from the Start -LITE (SFS) option. If you desire additional years of SFS, you may choose one of the above general options. Please note that these plans are in addition to the 2-year standard warranty and 1 year SFS that ships standard with the unit. Repairs will be made only at the designated Motorola repair depot. Local services are not included. Motorola will pay the inbound shipping charges only with use of the Motorola designated delivery service. Motorola will pay for outbound shipping via Motorola's normal shipping methods. No discounts are allowed on these options.

General Notes

The UHF Stubby standard antenna PMAE4003 R, provides a coverage range of 430 to 470 MHz. Should you need coverage up to 480 MHz, the QA01117 antenna option must be ordered

FCC Information:

Environmental Specifications:

Onerating Temperature: -30° to +60° C (Radio Only)
Sealing: IP51

CM200d™ Mobile

Standard Package Includes:

- Standard Microphone (PMMNIA090)
- Standard Low Profile Mounting Bracket (RI N6469)
- Standard Power Cable (HKNA137)
- 2 Vaar Marranty + 1 Vaar Sarvice from the Start LITE

Product Features

- 6 25e / 12 5 kHz Channel Snacing
- 16 Channels
- 2 Programmable Ruttons
- LFD Indicators
- Radio Management (Ontional)

Analog Features

- Auto/Priority/Dual Priority Scan
- Ouik Call II™ Call Alart/Salactive Call (Decode)
- MDC1200 PTT ID (Numeric ID Fncode)
- Audio Indicator Tones
- Time-Out Timer
- \/∩X
- Rusy Channel Lockout

Digital Features

- Digital Conventional
- Ontional for Analog models
- Standard for Digital models
- Racic Privacy
- Radio Check (Decode)
- Remote Monitor (Decode)
- Radio Inhihit (Decode)
- Dual Priority Scan
- Transmit Interrunt (Decode)
- Dual Canacity Direct Mode



Francies Not Allowed:

153 600 MHz +/1 10 kHz 173 800 MHz +/1 10 kHz 433 400 MHz +/1 10 kHz

Programmable Features

- Fscalert
- Local/Distance Mode
- Reneater / Talkaround
- Silent Monitor
- Valuma Sat
- Voice Announcement
- High / Low Power
- Nuisance Channel Delete
- Scan On / Off
- Tight / Normal Squelch
- V/OX On / Off

Analog Models

Model #	Band Split	Band	Power	Chan	Display	MSRP
AAM01JNC9JC1_N	136-174 MHz	VHF	25W	16	N/A	\$501.67
AAM01JQC9JC1_N	136-174 MHz	VHF	45W	16	N/A	\$560.00
AAM01QNC9JC1_N	403-470 MHz	UHF	25W	16	N/A	\$551.67
AAM01QPC9JC1_N	403-470 MHz	UHF	40W	16	N/A	\$610.00

Digital Models

Model #	Band Split	Band	Power	Chan	Display	MSRP
AAM01JNC9JA1_N	136-174 MHz	VHF	25W	16	N/A	\$585.00
AAM01JQC9JA1_N	136-174 MHz	VHF	45W	16	N/A	\$643.33

AAM01QNC9JA1_N	403-470 MHz	UHF	25W	16	N/A	\$635.00
AAM01QPC9JA1_N	403-470 MHz	UHF	40W	16	N/A	\$693.33

CM200d™ Mobile

Options: TO COMPLETE AN ORDER YOU MUST SELECT ONE (1) CHOICE FOR EACH OPTION

Microphone Options

Options	Description	MSRP
STDMIC0751	Standard	\$0.00
QA03848	Enhanced	\$51.00
QA03850	Heavy Duty	\$31.00
B71	Omit	-\$10.00

Bracket Options

Options	Description		MSRP
STDBKT0751	Standard		\$0.00
B65	Omit Standard		-\$4.00

Cable Options

Options	Description	MSRP
STDCBL0751	Standard Power	\$0.00
B161	Omit Standard	-\$8.00

Shipping Options

Options	Description	MSRP
STDBOX0751	Standard Model	\$0.00
B842	Bulk Packaging	\$0.00

Warranty Options

Options	Description	MSRP
STDRSA0751	Standard 2 Year	\$0.00
GA00164	Omit 1Year SFS	-\$18.33

CM200d™ Mobile

General Options

Ceneral Options		
Options	Description	MSRP
HKVN4223	CM200d Analog	\$83.00
G400	1 Year Service	\$34.00
G24	2 Year Service	\$65.00

Quantity Discount Program

You may "mix and match" any combination of SL300/CP185/CP200d portable models and/or CM200d/CM300d mobile models ("Radio Units") on a single order and receive the appropriate quantity discount for each model. Quantity discounts are calculated and granted at the time a new order is placed ("Qualifying Order"). Additional Radio Units added to the Qualifying Order will be charged at the single Radio Unit price without discount. Deleting or cancelling Radio Units from a Qualifying Order will be viewed as a new Qualifying Order and reseller will receive the discount offered (if any) for the number of Radio Units actually shipped. All Radio Units must be shipped at the same time in order to qualify for the corresponding product models quantity discount. Change order requests or Radio Units returns that extend, stagger or otherwise change the number of Radio Units actually purchased in a single shipment, will result in a charge to the reseller's account for the difference in price between the number of units purchased and the quantity discount reseller qualified under a Qualifying Order.

Service from the Start LITE

MOTOTRBO portable and mobiles radios ship with a standard 2-year parts and labor warranty. Additionally, they ship standard with a 1-year Service from the Start -LITE (SFS) option. If you desire additional years of SFS, you may choose one of the above general options. Please note that these plans are in addition to the 2-year standard warranty and 1 year SFS that ships standard with the unit. Repairs will be made only at the designated Motorola repair depot. Local services are not included. Motorola will pay the inbound shipping charges only with use of the Motorola designated delivery service. Motorola will pay for outbound

FCC/IC Information:

VHF (1.25W)· AR7QQFT2NQN / 1NQAR_QQFT2NQN VHF (25_45W)· AR7QQFT2NQ1 / 1NQAR_QQFT2NQ1 IHF (1.25W)· AR7QQFT4NQ2 / 1NQAR_QQFT4NQ2

Environmental Specifications

Onerating Temperature: -20° to +60° C Sealing: IP5/1*

* With microphone sealing hoot and rear accessory connector cover

Technology Bid-ESCNJ 18/19-03 Educational Services Commission of New Jersey
NJ State Approved Co-op #65MCESCCPS

Bid Term - 7/1/18 - 6/30/20; Extended to 6/30/22

I IHF (25-ΔΩ\Λ)\ ΔR799FTΔΩ93 / 1Ω9ΔR-99FTΔΩ93

nronerly installed

CM300d™ Mobile

Standard Package Includes

- Standard Micronhone (PMMN/A090)
- Standard Low Profile Mounting Bracket (RI N6469)
- Standard Power Cable (HKNA127)
- 2 Vear Marranty ± 1 Vear Service from the Start LITE

Product Features:

- 6 25a / 12 5 kHz Channel Snacing
- Alnha-Numeric Disnlay
- White-lit Backlight
- 99 Channole
- 1 Programmable Ruttons
- IFD Indicators
- Radio Management (Ontional)

Analog Features

- Auto/Priority/Dual Priority Scan
- Muik Call II™ Call Alart/Calactive Call (Decode)
- MDC1200 PTT ID (Numeric ID Encode)
- Audio Indicator Tones
- Time-Out Timer
- \/∩X
- Rusy Channel Lockout

Digital Features

- Digital Conventional
- Ontional for Analog models
- Standard for Digital models
- Racic Privacy
- Radio Check (Decode)
- Remote Monitor (Decode)
- Radio Inhihit (Decode)
- Dual Priority Scan
- Transmit Interrunt (Decode)
- Dual Canacity Direct Mode



Franciac Not Allowed:

153 600 MHz +/1 10 kHz 173 800 MHz +/1 10 kHz 422 400 MHz

Programmable Features

- Fscalert
- Local/Distance Mode
- Reneater / Talkaround
- Silent Monitor
- Valuma Sat
- Voice Announcement

- High / Low Power
- Nuisance Channel Delete - Scan On / Off
- Tight / Normal Squelch
- VOX On / Off

Analog Models

Model #	Band Split	Band	Power	Chan	Display	MSRP
AAM01JNH9JC1_N	136-174 MHz	VHF	25W	99	Yes	\$560.00
AAM01JQH9JC1 N	136-174 MHz	VHF	45W	99	Yes	\$618.33
AAM01QNH9JC1 N	403-470 MHz	UHF	25W	99	Yes	\$610.00
AAM010PH9JC1 N	403-470 MHz	UHF	40W	99	Yes	\$668.33

Digital Models

Model #	Band Split	Band	Power	Conv	Display	MSRP
AAM01JNH9JA1 N	136-174 MHz	VHF	25W	99	Yes	\$643.33
AAM01IOH9IA1 N	136-174 MHz	VHF	45W	99	Yes	\$701.67

AAM01QNH9JA1_N	403-470 MHz	UHF	25W	99	Yes	\$693.33
AAM01QPH9JA1 N	403-470 MHz	UHF	40W	99	Yes	\$751.67

CM300d™ Mobile

Options: TO COMPLETE AN ORDER YOU MUST SELECT ONE (1) CHOICE FOR EACH OPTION

Microphone Options

Options	Description	MSRP
STDMIC0866	Standard	\$0.00
QA03848	Enhanced	\$51.00
QA03850	Heavy Duty	\$31.00
B71	Omit	-\$10.00

Bracket Options

Options	Description	MSRP
STDBKT0866	Standard	\$0.00
B65	Omit Standard	-\$4.00

Cable Options

Options	Description	MSRP
STDCBL0866	Standard	\$0.00
B161	Omit Standard	-\$8.00

Shipping Options

Options	Description	M	SRP
STDBOX0866	Standard		\$0.00
B842	Bulk Packaging		\$0.00

Warranty Options

Options	Description	MSRP
STDRSA0866	Standard 2	\$0.00
GA00164	Omit 1Year SFS	-\$18.33

CM300d™ Mobile

General Options

deficial options		
Options	Description	MSRP
HKVN4223	CM200d	\$83.00
	Analog to	
	Digital Upgrade	
G400	1 Year Service	\$34.00
	from the Start -	
	LITE (US Only)	
G24	2 Year Service	\$65.00
	from the Start -	
	LITE (US Only)	
	` ''	

Quantity Discount Program

You may "mix and match" any combination of SL300/CP185/CP200d portable models and/or CM200d/CM300d mobile models ("Radio Units") on a single order and receive the appropriate quantity discount for each model. Quantity discounts are calculated and granted at the time a new order is placed ("Qualifying Order"). Additional Radio Units added to the Qualifying Order will be charged at the single Radio Unit price without discount. Deleting or cancelling Radio Units from a Qualifying Order will be viewed as a new Qualifying Order and reseller will receive the discount offered (if any) for the number of Radio Units actually shipped. All Radio Units must be shipped at the same time in order to qualify for the corresponding product models quantity discount. Change order requests or Radio Units returns that extend, stagger or otherwise change the number of Radio Units actually purchased in a single shipment, will result in a charge to the reseller's account for the difference in price between the number of units purchased and the quantity discount reseller qualified under a Qualifying Order.

Service from the Start LITE

MOTOTRBO portable and mobiles radios ship with a standard 2-year parts and labor warranty. Additionally, they ship standard with a 1-year Service from the Start -LITE (SFS) option. If you desire additional years of SFS, you may choose one of the above general options. Please note that these plans are in addition to the 2-year standard warranty and 1 year SFS that ships standard with the unit. Repairs will be made only at the designated Motorola repair depot. Local services are not included. Motorola will pay the inbound shipping charges only with use of the Motorola designated delivery service. Motorola will pay for outbound

FCC/IC Information:

\\HE \(\frac{1}{2} \sum \lambda \rangle \) \\Delta \(\frac{1}{2} \sum \lambda \rangle \rangle \rangle \) \\Delta \(\frac{1}{2} \sum \lambda \rangle \rangle \rangle \) \\Delta \(\frac{1}{2} \sum \lambda \rangle \rangle \rangle \) \\Delta \(\frac{1}{2} \sum \lambda \rangle \rangle \rangle \rangle \) \\Delta \(\frac{1}{2} \sum \lambda \rangle \rangle

Environmental Specifications

Onerating Temperature -20° to +60° C Sealing: IP54

BPR™ 40 Portable

Standard Package Includes:

- 8 Channel Model (Mag One Rattery NiMH 1200 mΔh PMNN4071 R
- 16 Channel Model (Mag One Rattery Li-ion 1500 mΔh PMNNΔ075 R
- Mag One Tri Chemistry Ranid Charger Kit (includes PMI N5041 R Rase/
- Mag One Antenna (VHF PMΔD4051 R / LIHF PMΔF4020 R)
- Mag One Spring Relt Clin (PMI NA743)
- Operating Instruction Manual
- Warranty
- Portable: One Vear
- Mag One Accessories (excent hatteries). Six Months
- All Other Accessories (includes Mag One Rattery and Motorola accessories). One Year

Product Features:

- 2 or 16 Channels
- 12 5 kHz only Channel Spacing
- 2 Programmable Ruttons
- Adjustable Power Levels (chine with 1M/)
- Priority Scan
- Small Size and Light Weight

Programmable Features:

- Nuisance Channel Delete
- PI /DPI Fnahle
- High/I ow Power
- Volume Set
- Scan
- Talkaround

Frequencies N	ot Allowed:	Default Frequencies
VHF	IIHF	VHF IIHF
152 91000	453 46500	151 625 464 500
172 27500	<i>4</i> 57 15000	Additional frequencies can be added using the Customer
172 26275	<i>4</i> 60 ጻ <i>4</i> 375	All frequencies must be divisible by 5 A or 6 25 kHz
	464.52500	Caution: Frequencies on the VHF band in the US have been assigned by the FCC with
	469.11500	channel centers every 7.5 kHz, which means some of these frequencies are not
		evenly divisible by 6.25 kHz or 5 kHz. In order for a radio to be able to synthesize





Technology Bid-ESCNJ 18/19-03

Educational Services Commission of New Jersey Bid Term - 7/1/18 - 6/30/20; Extended to 6/30/22 NJ State Approved Co-op #65MCESCCPS

Model #	Band Split	Band	Power	Conv	Display	Keypad	MSRP
NI N	150-174 MHz	VHF	5W	8	No	No	\$233.00
AAH84KDJ8AA1_N	150-174 MHz	VHF	5W	16	No	No	\$258.00
MAHO4NCJOAAI_	450-470 MHz	UHF	4W	8	No	No	\$250.00
AAH84RCJ8AA1_N	450-470 MHz	UHF	4W	16	No	No	\$275.00

General Options

Options	Description	MSRP
Q884	1 Year Service from	\$34.00
H885	2 Tear Service (IUC	\$65.00
H886	3 Year Service from	\$97.00

Service from the Start LITE

SfS LITE 1, 2 or 3 years of extended hardware repair coverage beginning at date of shipment. Repairs will be made

FCC/IC Information:

VHF: AZ489FT3810 / 109U-89FT3810 UHF: AZ489FT4873 / 109U-89FT4873

Environmental Specifications:

Operating Temperature: -30° C to +60° C (Radio Only)

Sealing: IPX4

SL300™ Portable

Standard Package Includes:

- Standard Rattery (Lision 2200 mAh DMMINIA/AS)
- Standard Micro-LISR Wall Charger (25009298001)
- VHE Stubby / LIHE Stubby Antonna (Must Salact Ontion)
- Standard Carry Holster (PMI N7190)
- Rattery Door Cover (DMI NI7074)
- 2 Vaar Marranty ± 1 Vaar Carvice from the Start LITE

Droduct Features

- Digital (3W) and Analog (2W) Mode
- 2 Zanes (Display Model)
- Dual Canacity Direct Mode
- 6 75a / 17 5 kHz Channel Spacing
- 1 Programmable Side Rutton Display Model Includes Menu List
- Racic Drivacy
- Rusy Channal Lackaut
- Fmergency
- IFD Rattery Indicator
- Inne Worker
- MDC1200
- Onik Call II
- Radio Chack (Dacoda)
- Radio Inhihit (Decode)
- Remote Monitor (Decode)
- Scan Priority / Dual Priority
- Time-Out-Timer
- Voice Announcement
- LISAS MOTOTRRO CPS
- Radio Management Canable

Programmable Features

- All Alart Tones On/Off
- Rrightness (Display Model)
- Fmergency On/Off
- High / Low Power
- Monitor
- Nuisance Channel Delete
- One Touch Rutton
- Permanent Monitor
- Privacy On/Off
- Ranastar / Talkarnund - Scan On/Off
- Scrambling On/Off
- Site Lack On/Off
- Tight / Mormal Squalch
- Voice Announcement On/Off
- Valuma Sat
- VOX On / Off
- Zone Toggle (Display Model)

Digital Models

Model #	Band Split	Band	Power	Conv Chan	Display	Keypad	MSRP	
AAH88JCC9JA2_N	136-174 MHz	VHF	3W (D)	2	No	No	\$	356.33
AAH88JCP9JA2_N	136-174 MHz	VHF	3₩ (Δ)	99	Yes	No	\$	396.33
AAH88QCC9JA2_N	403-470 MHz	UHF	3W (D)	2	No	No	\$	382.07
AAH88QCP9JA2_N	403-470 MHz	UHF	3₩ (Δ)	99	Yes	No	\$	432.07

FCC INFORMATION VHF: AZ489FT3835, UHF: AZ489FT4922



SL300™ Portable

Options: TO COMPLETE AN

Battery Options

Options	Description	MSRP
STDBAT0546	Standard	\$0.00

Antenna Options

Options	Description	MSRP
QA04760	VHF Stubby	\$0.00
QA04761	VHF Stubby	\$0.00
QA04762	VHF Stubby	\$0.00
QA04763	UHF Stubby	\$0.00
QA04764	UHF Stubby	\$0.00
QA04765	UHF Stubby	\$0.00
H112	Omit Antenna	-\$3.50

Carry Options

Options	Description	MSRP
STDBLT0546	Standard	\$0.00
QA04882	ALT: Flexible	\$7.50
QA04883	ALT: Nylon	\$5.00
H301	Omit Swivel	-\$3.50

Charger Options

Options	Description	MSRP
STDCHG0546	Standard	\$0.00
QA04770	ALT: Drop-In	\$25.00
H951	Omit Standard	-\$5.00

Shipping Options

Options	Description	MSRP
STDBOX0546	Standard	\$0.00
H415	Bulk Packaging	\$0.00

Warranty Options

Options	Description	MSRP
STDRSA0546	Standard 2	\$0.00
QA00510	Omit 1Year SFS	-\$18.33

SL300 Portable

General Options

Options	Description	MSRP	
QA04755	Swivel Earpiece	\$	29.00
QA04757	Earbud with	\$	20.00
Q884	1 Year Service	\$	34.00
H885	2 Year Service	\$	65.00

Quantity Discount Program

You may "mix and match" any combination of SL300/CP185/CP200d portable models and/or CM200d/CM300d mobile models ("Radio Units") on a single order and receive the appropriate quantity discount for each model. Quantity discounts are calculated and granted at the time a new order is placed ("Qualifying Order"). Additional Radio Units added to the Qualifying Order will be charged at the single Radio Unit price without discount. Deleting or cancelling Radio Units from a Qualifying Order will be viewed as a new Qualifying Order and reseller will receive the discount offered (if any) for the number of Radio Units actually shipped. All Radio Units must be shipped at the same time in order to qualify for the corresponding product models quantity discount. Change order requests or Radio Units returns that extend, stagger or otherwise change the number of Radio Units actually purchased in a single shipment, will result in a charge to the reseller's account for the difference in price between the number of units purchased and the quantity discount reseller qualified under a Qualifying Order.

Service from the Start LITE

MOTOTRBO portable and mobiles radios ship with a standard 2-year parts and labor warranty. Additionally, they ship standard with a 1-year Service from the Start -LITE (SFS) option. If you desire additional years of SFS, you may choose one of the above general options. Please note that these plans are in addition to the 2-year standard warranty and 1 year SFS that ships standard with the unit. Repairs will be made only at the designated Motorola repair depot. Local services are not included. Motorola will pay the inbound shipping charges only with use of the Motorola designated delivery service. Motorola will hav for outhound shinning via Motorola's normal shinning methods. No discounts are allowed on these ontions

FCC/IC Information: (136-174 MHz) AZ489FT3835 / 109U-89FT3835 (403-470 MHz) AZ489FT4922 / 109U-89FT4922

Environmental Specifications: Operating Temperature: -30° to +60° C (Radio Only) Sealing: IP54

VL50™ Portable

Standard Package Includes:

- Standard Battery (1100 mAh Li-ion, 3.6V 56557)
- Standard Charger (120V Double Unit Charger 56553)
- Swivel Belt Holster (HCLN4013)
- User Guide (6881096C37)
- One Year Warranty

Product Features:

- Up to 8 Channels
- 12.5 kHz Channel Spacing
- Scan
- 83 DPL, 38 PL Codes
- VibraCall Alert
- Battery Meter
- Radio Signal Strength Indicator
- Enhanced VOX (No accessory needed)
- 7 Selectable Call Tones

Default Frequencies:

UHF

464.5000	467.8500
464.5500	467.8750
467.7625	467.9000
467.8125	467.9250



Models

TOGCIS							
Model #	Band Split	Band	Power	Conv Chan	Display	Keypad	MSRP
P24VPC03D2_A	464.5-467.9 MHz	UHF	1W	8	Yes	No	\$255.00

Technology Bid-ESCNJ 18/19-03 Educational Services Commission of New Jersey
NJ State Approved Co-op #65MCESCCPS

Bid Term - 7/1/18 - 6/30/20; Extended to 6/30/22

FCC Information: AZ489FT4926