

CATERPILLAR MACHINE PRICE LIST

938M

938M WHEEL LOADER
 CLAYTON, NC, USA

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

- Auto idle shut down feature
- Cat C7.1ACERT engine
- Power modes (standard and performance)
- Power by range (high power in range 4)
- Tier 4 Final/Stage V compliant
- Turbocharged and aftercooled
- Filtered crankcase breather
- Diesel particulate filter
- Selective Catalyst Reduction
- Coolant protection to -34C (-29F)
- Differential lock in front axle
- Dry type air cleaner
- Enclosed wet disc full hydraulic brakes
- Fuel priming pump, automatic
- Fuel water separator
- Hydraulically driven demand cooling fan
- Hydrostatic transmission with electronic control
- Operator modes (default, TC, hystat and ice)
- Directional shift aggressiveness (fast, medium, slow)
- Rimpull control, adjust wheel torque
- Creeper control, adjust ground speed
- Lubed for life driveshafts
- Parking brake, electric
- Single plane cooling package wide 6 fins per inch density
- S-O-S port,engine,coolant,transmission oil

HYDRAULICS

- Automatic lift and bucket kickouts, adjustable in-cab
- Bucket and fork modes, adjustable in-cab
- Cylinder damping at kickout and mechanical end stops
- Fine mode control (fast, medium, slow) in fork mode
- Hydraulic response setting (fast, medium, slow)
- Hydraulic diagnostic connectors and S-O-S ports
- Hydraulic sight gauge, visible
- Load sensing hydraulics and steering
- Seat mounted hydraulic joystick controls

ELECTRICAL

- Alternator, 115-amp, heavy duty
- 12V power supply in cab (2)
- Batteries, 1,000 CCA (2) 24 volt system, disconnect switch
- Back up alarm
- Emergency shutdown switch

- LED rear stop and turn lights
- Heavy duty gear reduction starter
- Product Link
- Remote jump start post
- Resettable main and critical function breakers
- Roading lights front and rear

OPERATOR ENVIRONMENT

- 75 mm (3 in) retractable seatbelt
- Automatic temperature control
- Cab, enclosed ROPS/FOPS pressurized and sound suppressed
- Cup holders
- External heated mirrors with lower parabolic
- Ground level cab door release
- Gauges
- Digital hour meter, odometer and tachometer
- Digital ground speedometer and direction indicator
- Engine coolant temperature gauge
- Fuel and diesel exhaust fluid level indicator
- Hydraulic oil temperature gauge
- Hydraulic control lockout
- Interior cab lighting, door and dome
- Interior rearview mirrors (2)
- Lunch box storage
- Operator warning system indicators
- Radio ready speakers
- Rear window defrost, electric
- Seat mounted electronic implement controls, adjustable
- Sliding glass on the side windows
- Column mounted multi function control -lights, wipers, turn signal
- Suspension seat, fabric
- Tilt and telescope steering wheel
- Tinted front glass
- Wet arm wiper/washer, 2-speed and intermittent, front
- Wet arm wiper washer, rear

OTHER STANDARD EQUIPMENT

- Large-access enclosure doors with adjustable close/open force
- Parallel lift loader linkage
- Recovery hitch with pin
- Remote mounted lubrication points
- Vandalism protection-lockable compartments

CATERPILLAR MACHINE PRICE LIST

938M

| 938M WHEEL LOADER CLAYTON, NC, USA | Ship Weight lbs | LIST PRICE AT DEALER |
|---------------------------------------|--------------------|-------------------------|
|---------------------------------------|--------------------|-------------------------|

**Lane 2 is reserved for the Base Order Management Program
Please use Lane 2 when placing orders that are part of the Base Order
Management program.**

| | | |
|-----------------|---|------------------|
| 628-9484 | 938M SWL DCA1E 0 LANE 1 - AVAILABLE FROM CLAYTON PDC. LANE 2 - AVAILABLE FROM CLAYTON FACTORY USING PRIORITY CODE L2. LANE 3 - AVAILABLE FROM CLAYTON FACTORY USING PRIORITY CODE L2. | \$296,700 |
|-----------------|---|------------------|

- INCLUDES:
- 536-5303 938M WHEEL LOADER
 - 430-2945 PREP PACK, NORTH AMERICA
 - 536-5343 HYDRAULICS, 3V, CPLR READY, SL
 - 536-5284 HYDRAULICS, STANDARD
 - 530-1628 LINES, AUX 3RD, STD LIFT
 - 536-5339 JUMPER LINES, NONE
 - 333-6858 STEERING, STANDARD
 - 349-8014 DIFFERENTIAL, OPEN REAR
 - 536-5320 ENVIRONMENT, STANDARD
 - 454-0612 WEATHER, STANDARD
 - 549-0451 CAB, DELUXE
 - 563-5967 SEAT, DELUXE
 - 372-1868 STANDARD RADIO (12V)
 - 366-8150 FENDERS, STANDARD
 - 467-7990 COUNTERWEIGHT,3770LBS(1710KG),HEAVY,7PC
 - 430-2860 RIDE CONTROL
 - 536-5314 QUICK COUPLER, FUSION
 - 559-0841 LIGHTS, AUX, HALOGEN
 - 541-3066 LIGHTS, ROADING, HALOGEN, RH
 - 519-8081 TOOLBOX AUX, NONE

NOTE: Please refer to the Lane 1 section to complete your order.

CATERPILLAR MACHINE PRICE LIST

938M

| 938M WHEEL LOADER CLAYTON, NC, USA | Ship Weight lbs | LIST PRICE AT DEALER |
|---------------------------------------|--------------------|-------------------------|
|---------------------------------------|--------------------|-------------------------|

| | | |
|-----------------|--|------------------|
| 628-9485 | 938M SWL DCA2E 0 | \$303,300 |
| | LANE 1 - AVAILABLE FROM CLAYTON PDC | |
| | LANE 2 - AVAILABLE FROM CLAYTON FACTORY USING PRIORITY CODE L2 | |
| | LANE 3 - AVAILABLE FROM CLAYTON FACTORY USING PRIORITY CODE L2 | |

- INCLUDES:
- 536-5303 938M WHEEL LOADER
 - 430-2945 PREP PACK, NORTH AMERICA
 - 536-5343 HYDRAULICS, 3V, CPLR READY, SL
 - 536-5284 HYDRAULICS, STANDARD
 - 530-1628 LINES, AUX 3RD, STD LIFT
 - 536-5339 JUMPER LINES, NONE
 - 333-6858 STEERING, STANDARD
 - 349-8013 DIFFERENTIAL,LIMITED SLIP REAR
 - 536-5320 ENVIRONMENT, STANDARD
 - 454-0613 WEATHER, COLD START 120V
 - 549-0451 CAB, DELUXE
 - 563-5967 SEAT, DELUXE
 - 372-1868 STANDARD RADIO (12V)
 - 366-8150 FENDERS, STANDARD
 - 467-7990 COUNTERWEIGHT,3770LBS(1710KG),HEAVY,7PC
 - 430-2860 RIDE CONTROL
 - 536-5314 QUICK COUPLER, FUSION
 - 559-0841 LIGHTS, AUX, HALOGEN
 - 541-3066 LIGHTS, ROADING, HALOGEN, RH
 - 491-7922TOOLBOX AUX

NOTE: Please refer to the Lane 1 section to complete your order.

| | | |
|-----------------|--|------------------|
| 628-9486 | 938M SWL DCA3E 0 | \$314,720 |
| | LANE 1 - AVAILABLE FROM CLAYTON PDC | |
| | LANE 2 - AVAILABLE FROM CLAYTON FACTORY USING PRIORITY CODE L2 | |
| | LANE 3 - AVAILABLE FROM CLAYTON FACTORY USING PRIORITY CODE L2 | |

- INCLUDES:
- 536-5303 938M WHEEL LOADER
 - 430-2945 PREP PACK, NORTH AMERICA
 - 549-0443 HYDRAULICS, 3V, CPLR READY, HL
 - 536-5284 HYDRAULICS, STANDARD
 - 527-8880 LINES, AUX 3RD, HIGH LIFT
 - 536-5339 JUMPER LINES, NONE
 - 333-6858 STEERING, STANDARD
 - 349-8013 DIFFERENTIAL,LIMITED SLIP REAR
 - 536-5350 ENVIRONMENT, HIGH DEBRIS
 - 454-0613 WEATHER, COLD START 120V
 - 549-0451 CAB, DELUXE
 - 563-5967 SEAT, DELUXE
 - 372-1868 STANDARD RADIO (12V)
 - 366-8150 FENDERS, STANDARD
 - 467-7990 COUNTERWEIGHT,3770LBS(1710KG),HEAVY,7PC
 - 430-2860 RIDE CONTROL
 - 536-5314 QUICK COUPLER, FUSION
 - 559-0841 LIGHTS, AUX, HALOGEN
 - 541-3066 LIGHTS, ROADING, HALOGEN, RH
 - 519-8081 TOOLBOX AUX, NONE

NOTE: Please refer to the Lane 1 section to complete your order.

CATERPILLAR MACHINE PRICE LIST

938M

| 938M WHEEL LOADER CLAYTON, NC, USA | Ship Weight lbs | LIST PRICE AT DEALER |
|---------------------------------------|--------------------|-------------------------|
|---------------------------------------|--------------------|-------------------------|

| | | |
|--|--|------------------|
| 536-5303 938M WHEEL LOADER 0 | | \$273,510 |
| LANE 2 - AVAILABLE FROM CLAYTON FACTORY. | | |
| LANE 3 - AVAILABLE FROM CLAYTON FACTORY. | | |

Serial Number Prefix J3R.

| | | |
|--|--|------------------|
| 628-9483 938M SWL AGRICULTURE CFG4 0 | | \$273,510 |
|--|--|------------------|

LANE 3 - AVAILABLE FROM CLAYTON FACTORY
 Serial Number Prefix J3R
 938M Ag Handler includes Ag Handler decal along with boosted payload
 in combination with larger tires with enhanced stability and
 flotation to meet the needs of agriculture environments.

INCLUDES:
 536-5303 938M WHEEL LOADER
 FILM GP, AG HANDLER

REQUIRES:
 467-7991 COUNTERWEIGHT,4431LBS(2010KG),AGG,8PCS
 461-2924 TIRES, 23.5R25 MX XHA2 * L3 or
 618-0430 TIRES, 23.5R25 MA MS302 * L3 or
 373-7314 TIRES,750/65R26 MXMEGAXBIB* AG
 536-5340 ENVIRONMENT, MEDIUM DEBRIS or
 536-5350 ENVIRONMENT, HIGH DEBRIS
 536-5349 AUTOLUBE
 549-0451 CAB, DELUXE

RECOMMEND:
 566-4597 CONTROL GP,PAYLOAD,DEMO 250 HR
 333-1425 WARNING, BEACON, LED STROBE
 559-0843 LIGHTS, STD, LED
 430-2860 RIDE CONTROL
 349-8013 DIFFERENTIAL,LIMITED SLIP REAR

CATERPILLAR MACHINE PRICE LIST

938M

| 938M WHEEL LOADER CLAYTON, NC, USA | Ship Weight lbs | LIST PRICE AT DEALER |
|---------------------------------------|--------------------|-------------------------|
|---------------------------------------|--------------------|-------------------------|

| | |
|---|-------------------------|
| <p>559-6228</p> <p>938M SWL AG HANDLER CFG2 0</p> <p>LANE 2 - AVAILABLE FROM CLAYTON FACTORY</p> <p>LANE 3 - AVAILABLE FROM CLAYTON FACTORY</p> | <p>\$273,510</p> |
|---|-------------------------|

Serial Number Prefix J3R
 938M Aggregate Handler: Includes Aggregate Handler branding and limits selections to drive performance and comfort enhancing features, an expectation of the Cat Aggregate Handler range.

NOT COMPATIBLE with High Lift Linkage Arrangements.

INCLUDES:
 536-5303 938M WHEEL LOADER
 387-4097 FILM GP, AGGREGATE

REQUIRES:
 467-7991 COUNTERWEIGHT,4431LBS(2010KG),AGG,8PCS or
 467-7990 COUNTERWEIGHT,3770LBS(1710KG),HEAVY,7PC
 in combination with 23.5 tires.

One of the following buckets in North America:
 469-0194 BUCKET-S&G, 3.8 YD3, PO, BOCE
 625-4745 BUCKET-S&G, 3.8 YD3, PO, BOTS
 466-2256 BUCKET-S&G, 4.2 YD3, PO, BOCE (Lane 3 only)
 625-4739 BUCKET-S&G, 4.2 YD3, PO, BOTS (Lane 3 only)
 469-0192 BUCKET-S&G, 3.8 YD3, FUS, BOCE
 625-4744 BUCKET-S&G, 3.8 YD3, FUS, BOTS
 451-1411 BUCKET-S&G, 4.2 YD3, FUS, BOCE
 625-4743 BUCKET-S&G, 4.2 YD3, FUS, BOTS

RECOMMEND:
 566-4597 CONTROL GP,PAYLOAD,DEMO 250 HR
 469-0502 BREATHER GROUP
 559-0843 LIGHTS, STD, LED
 333-1425 WARNING, BEACON, LED STROBE
 430-2860 RIDE CONTROL
 349-8164 GUARD, DRIVESHAFT
 349-8163 GUARD, CRANKCASE
 349-8165 GUARD, POWERTRAIN, LOWER
 536-5349 AUTOLUBE
 536-5340 ENVIRONMENT, MEDIUM DEBRIS
 349-8013 DIFFERENTIAL,LIMITED SLIP REAR
 366-6882 TIRES,20.5R25 MX XHA2 * L3 or
 461-2924 TIRES, 23.5R25 MX XHA2 * L3

CATERPILLAR MACHINE PRICE LIST

938M

| 938M WHEEL LOADER CLAYTON, NC, USA | Ship Weight lbs | LIST PRICE AT DEALER |
|---------------------------------------|--------------------|-------------------------|
|---------------------------------------|--------------------|-------------------------|

| | | |
|--|--|------------------|
| <p>559-6225 938M SWL WASTE HANDLER CFG1 0</p> <p>LANE 3 - AVAILABLE FROM CLAYTON FACTORY Serial Number Prefix J3R 938M Waste Handler: Includes Waste Handler branding and limits selections to drive performance and comfort enhancing features, an expectation of the Cat Waste Handler range.</p> | | \$273,510 |
|--|--|------------------|

INCLUDES:
 536-5303 938M WHEEL LOADER
 387-4096 FILM GP, WASTE HANDLER

REQUIRES:
 349-8164 GUARD, DRIVESHAFT
 349-8163 GUARD, CRANKCASE
 349-8165 GUARD, POWERTRAIN, LOWER
 425-1425 GUARD, POWERTRAIN, SIDE
 391-1990 GUARD, HITCH
 536-5340 ENVIRONMENT, MEDIUM DEBRIS or
 536-5350 ENVIRONMENT, HIGH DEBRIS
 Recommend:
 342-0250 GUARD, WINDSHIELD or 562-5684 KIT, POLY FRONT WINDSHIELD
 377-1530 GUARD, FRONT LIGHTS
 377-1560 GUARD, REAR LIGHTS or 430-2926 GUARD, REAR RADIATOR
 430-2917 GUARD, STEERING CYLINDER
 433-9751 GUARD, TILT CYLINDER, STD LIFT or
 418-8602 GUARD, TILT CYLINDER,HIGH LIFT
 423-7157 PRECLEANER, CAB, RESPA
 430-2860 RIDE CONTROL
 419-8851 FENDERS, DEFLECTORS
 536-5349 AUTOLUBE
 349-8013 DIFFERENTIAL,LIMITED SLIP REAR
 One of the following puncture proof or puncture resistant tires.
 Puncture Proof:
 604-7274 TIRES,20.5R25 TL BRAWLER, SM or
 604-7280 TIRES,20.5R25 TL BRAWLER, TR
 Puncture Resistant:
 376-0819 TIRES,20.5R25TR TL538S+ *** L5 or
 376-0877 TIRES,20.5R25 MX XMINE D2** L5

Below kits are recommended when working in the presence of
 Siloxane gas:
 595-8650 KIT,POWERED PRECLEANER,ENGINE
 622-4217 KIT, SILOXANE FILTER, ENGINE

| | | |
|--|--|-----------|
| <p>0P-3538 938M MISC MATERIAL 0</p> <p>ONLY AVAILABLE FROM WACO PARTS SERVICE Use this top level reference when ordering miscellaneous kits located in the Alternate Sourced Attachments section.</p> | | NC |
|--|--|-----------|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 1 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|------------------|-----------------|----------------------|
|-----|---------|------------------|-----------------|----------------------|

LANE 1 AM-NORTH MANDATORY ATTACHMENTS

LANE SELECTION.

| | | | |
|---------|------------------------|---|----|
| 0P-9001 | LANE 1 ORDER | 0 | NC |
|---------|------------------------|---|----|

ENGINE

| | | | | |
|---|----------|--|---|----|
| L | 536-5268 | ENGINE, 938 Meets U.S. EPA Tier 4 Final and EU Stage IV emission standards. ONLY FOR USE WITH: 628-9484 938M SWL DCA1E 628-9485 938M SWL DCA2E 628-9486 938M SWL DCA3E | 0 | NC |
|---|----------|--|---|----|

PRODUCT LINK

| | | | | |
|---|----------|--|---|----|
| L | 565-0908 | PRODUCT LINK, CELLULAR PL641 Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data. | 0 | NC |
|---|----------|--|---|----|

TIRES

Due to industry-wide tire availability, tires may change based on availability. Tire changes are available on a limited basis through Lane 1 using 0P-4218 and may extend delivery time of a DCA arrangement based on target tire arrangement availability. For any Lane 1 tire offering with a use type of C, please check with factory before placing order to confirm tire availability.

| | | | | |
|---|----------|---|---|----------|
| L | 366-6882 | TIRES,20.5R25 MX XHA2 * L3 Michelin;Radial;XHA2;L3;3 pc rim Non directional tread;Includes axle oscillation stops | 0 | \$18,150 |
|---|----------|---|---|----------|

OPERATION AND MAINTENANCE MANUAL

| | | | |
|----------|--|---|----|
| 421-8926 | SERIALIZED TECHNICAL MEDIA KIT The technical media kit will include the Operations & Maintenance Manual (OMM) and other media specified on the Factory Notification List required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary. Any additional media or translations not included in the kit, should be ordered through https://publications.cat.com | 0 | NC |
|----------|--|---|----|

DECAL PACKAGES

| | | | | |
|---|----------|---|---|----|
| P | 430-2963 | INSTRUCTIONS, ANSI, US This package includes picto decals as required for North America except for Canada. | 0 | NC |
| P | 430-2964 | INSTRUCTIONS, ISO, CANADA This package includes picto decals as required for Canada. | 0 | NC |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 1 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|-------------------------|--------------------|-------------------------|
|-----|---------|-------------------------|--------------------|-------------------------|

LANE 1 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

PROTECTION

| | | |
|---------|---|------------------|
| 0P-2266 | SHIPPING/STORAGE PROTECTION 0 Provides protective application of Fluid Film TM for protection while shipping and for extended storage periods. This product will need to be power washed with soapy water prior to shipment to the customer. | \$239 NET |
|---------|---|------------------|

PACKING

| | | |
|---------|---|-----------|
| 0P-0210 | PACK, DOMESTIC TRUCK 0 | NC |
|---------|---|-----------|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 1 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|-----------------|-----------------|----------------------|
|-----|---------|-----------------|-----------------|----------------------|

LANE 1 AM-NORTH OPTIONAL ATTACHMENTS

SPECIAL ARRANGEMENTS.

Additional attachments that can be added to PDC machines to allow quick ship and configuration flexibility.
 NO RETURNS accepted for kit components not used or for parts removed from machine during kit installation.
 FOR USE WITH ALL DCA'S UNLESS OTHERWISE STATED.

OPTIONS

| | | | | |
|---|----------|--|--|---------|
| L | 452-0857 | KIT, GUARD, POWERTRAIN, SIDE 0 Kit provides two (2) side transmission guards that mount to both sides of the rear frame. | | \$624 |
| L | 374-5843 | KIT, GUARD, DRIVESHAFT 0 Kit provides drive shaft guard that mounts underneath the front frame. | | \$708 |
| L | 374-5844 | KIT, GUARD, POWERTRAIN, LOWER 0 Kit provides lower transmission guard that mounts underneath the rear frame. | | \$1,632 |
| L | 374-5845 | KIT, GUARD, CRANKCASE 0 Kit provides engine crankcase guard that mounts underneath the rear frame. | | \$1,118 |
| P | 467-7992 | KIT, COUNTERWEIGHT, AGGREGATE 0 Kit converts a heavy counterweight machine to a Aggregate Handler machine by adding an additional frame mounted counterweight for use in applications such as Log and Lumber, Aggregate Handling, Auto Re-Handling and heavy material handling. NOT compatible with High Lift machines. CANNOT BE USED WITH: Brawler Tires | | \$4,097 |
| L | 370-7008 | KIT, WARNING,BEACON,LED STROBE 0 Kit provides hard mounted strobe beacon on hinged (breakaway) bracket mounted to the rear of the cab structure. | | \$325 |
| P | 576-9758 | KIT, JUMPER LINES,3RD FUNCTION 0 Kit provides 3rd function jumper lines and threaded flat face connect under pressure quick disconnects mounted to the coupler. Recommended for use with 3rd function work tools. Provides a kit to add 3rd function jumper line. For use with machine serial numbers after J3R07425 and P5K00120 | | \$415 |

TIRES

| | | | | |
|--|---------|--|--|-----------|
| | 0P-4218 | TIRE ARR, CHANGE 0 Charge to cover the costs of completing a tire arrangement change including hardware, oscillation stops, fender adjustments and time to complete the work. Tire changes are available on a limited basis and may extend delivery time of a DCA arrangement based on target tire arrangement availability. For any Lane 1 tire offering with a use type of C, please check with factory before placing order to confirm tire availability. | | \$620 NET |
|--|---------|--|--|-----------|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 1 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|-----------------|-----------------|----------------------|
|-----|---------|-----------------|-----------------|----------------------|

LANE 1 AM-NORTH OPTIONAL ATTACHMENTS (CONT.)

SPECIAL ARRANGEMENTS. (Cont.)

| | | | | |
|---|----------|--|---|----------|
| C | 461-2924 | TIRES, 23.5R25 MX XHA2 * L3 0 Michelin;Radial;XHA2;L3;Non directional tread Includes axle oscillation stops and fender extension brackets Compatible with 470-6570 COUNTERWEIGHT,3064LBS(1390KG),STD,5PCS on Standard Lift machines for use in general construction applications REQUIRES: 348-4657 CTWT, STD, LIGHT, 2412LBS(1094KG),4PCS when used in combination with High Lift machines. REQUIRES: 387-4097 FILM GP, AGGREGATE or 387-4098 FILM GP, FOREST HANDLER when used in combination with 467-7990 COUNTERWEIGHT, HEAVY on Standard Lift machines for use in heavy material handling applications REQUIRES: 0P-4218 TIRE ARR, CHANGE 387-4097 FILM GP, AGGREGATE or 387-4098 FILM GP, FOREST HANDLER ONLY FOR USE WITH: 593-8977 938M SWL DCA1D CANNOT BE USED WITH: 467-7991 COUNTERWEIGHT,4431LBS(2010KGS),AGG,8PCS | 0 | \$25,120 |
| P | 376-0788 | TIRES, 20.5R25 YK RB31 * L3 0 Yokohama;Radial;RB31;L3;3 pcs Includes axle oscillation stops. REQUIRES: 0P-4218 TIRE ARR, CHANGE | 0 | \$17,680 |

DECALS

Must select one when ordering 461-2924 23.5 tire

| | | | | |
|---|----------|---------------------------------|---|------|
| L | 387-4097 | FILM GP, AGGREGATE 0 | 0 | NC |
| L | 387-4098 | FILM GP, FOREST HANDLER 0 | 0 | \$70 |

WORK TOOLS

GENERAL PURPOSE BUCKETS

| | | | | |
|---|----------|---|-------|----------|
| P | 345-2427 | BUCKET-GP, 3.5 YD3, FUS, BOCE 2,519 Includes: BUCKET-GP, HO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width General Purpose Bucket | 2,519 | \$11,306 |
| P | 417-4925 | BUCKET-GP, 3.2 YD3, FUS, BOCE 2,403 Includes: BUCKET-GP, HO Cutting Edge, Bolt On (4 Piece) 2540mm (100") width General Purpose Bucket | 2,403 | \$10,528 |
| P | 417-4355 | BUCKET-GP, 3.2 YD3, FUS, BOCE 2,430 Includes: BUCKET-GP, HO Cutting Edge, Bolt On (4 Piece) 2743mm (108") width General Purpose Bucket | 2,430 | \$10,764 |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 1 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|-----------------|-----------------|----------------------|
|-----|---------|-----------------|-----------------|----------------------|

LANE 1 AM-NORTH OPTIONAL ATTACHMENTS (CONT.)

WORK TOOLS (Cont.)

| | | | | |
|---|----------|--|-------|----------|
| P | 417-4929 | BUCKET-GP, 3.8 YD3, FUS, BOCE | 2,601 | \$11,833 |
| | | Includes: BUCKET-GP, HO Cutting Edge, Bolt On (4 Piece) 2743mm (108") width General Purpose Bucket | | |

LIGHT MATERIAL BUCKETS

| | | | | |
|---|----------|---|-------|----------|
| P | 417-4935 | BUCKET-LM, 4.5 YD3, FUS, BOCE | 2,873 | \$11,333 |
| | | Light Material Bucket, Width 2750 mm (108"). Includes 1pc BOCE Capacity: 3.5 m3 (4.5 yd3) fill factor 100% FOR USE WITH: FUSION Quick Coupler | | |
| P | 417-4342 | BUCKET-LM, 5.5 YD3, FUS, BOCE | 3,172 | \$13,111 |
| | | Light Material Bucket, Width 2750 mm (108"). Includes 1pc BOCE Capacity: 4.2 m3 (5.5 yd3) fill factor 100% FOR USE WITH: FUSION Quick Coupler | | |

CARRIAGE & FORKS

| | | | | |
|---|----------|---|-------|----------|
| P | 572-5671 | CARRIAGE,FUS, FORK 60", PALLET | 640 | \$4,954 |
| | | 60" wide carriage with 54" Pallet tines | | |
| P | 572-5672 | CARRIAGE, FUS, FORK, 60", CON | 961 | \$9,594 |
| | | 96" wide carriage with 60" Construction tines | | |
| P | 572-5673 | CARRIAGE, FUS, FORK, 72", CON | 1,004 | \$10,640 |
| | | 96" wide carriage with 72" Construction tines | | |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|----------------------|-----------------|----------------------|
|-----|---------|----------------------|-----------------|----------------------|

LANE SELECTION

| | | | |
|---------|--|---|----|
| OP-9002 | LANE 2 ORDER | 0 | NC |
| | Only for dealers enrolled in the Base Orders Management (BOM) program. | | |
| OP-9003 | LANE 3 ORDER | 0 | NC |

REGIONAL PACKAGES

| | | | | |
|---|----------|------------------------------------|---|----|
| L | 430-2943 | PREP PACK, UNITED STATES | 0 | NC |
| | | Includes ANSI Decals | | |

FEATURE PACKAGES

CONTROLS

| | | | | |
|---|----------|--|---|---------|
| L | 333-6858 | STEERING, STANDARD | 0 | NC |
| L | 333-6859 | STEERING, STANDARD, DUAL MODE | 0 | \$1,380 |
| | | Adds the ability to enable Dual Mode Steering (Quick Steer) to minimize operator efforts in repetitive cycles. REQUIRES: 536-5318 AUX ECM | | |
| L | 347-8296 | STEERING, SECONDARY | 0 | \$3,565 |
| | | Provides limited steering control in the event of a loss of power or a loss of hydraulic flow. Includes operator warning system indicator and operator alarm | | |
| L | 366-8009 | STEERING, SECONDARY, DUAL MODE | 0 | \$4,935 |
| | | Adds the ability to enable Dual Mode Steering (Quick Steer) and provides a secondary back-up steering system. REQUIRES: 536-5318 AUX ECM | | |

REAR AXLE

| | | | | |
|---|----------|---|---|---------|
| L | 349-8014 | DIFFERENTIAL, OPEN REAR | 0 | NC |
| | | Open rear differential (without a traction aid) in addition to the standard front axle diff-lock. | | |
| L | 349-8013 | DIFFERENTIAL,LIMITED SLIP REAR | 0 | \$3,555 |
| | | Adds a rear limited slip traction aid in addition to the standard front axle diff-lock. | | |

SPECIAL ARRANGEMENTS

ENVIRONMENT PACKAGES

| | | | | |
|---|----------|--|---|---------|
| L | 536-5320 | ENVIRONMENT, STANDARD | 0 | NC |
| | | Contains dustbowl precleaner, standard fan and standard 115 amp alternator. | | |
| L | 536-5340 | ENVIRONMENT, MEDIUM DEBRIS | 0 | \$2,935 |
| | | Adds Sy-Klone engine pre-cleaner and reversing fan but maintains 115 amp alternator. | | |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|----------------------|-----------------|----------------------|
|-----|---------|----------------------|-----------------|----------------------|

SPECIAL ARRANGEMENTS (CONT.)

ENVIRONMENT PACKAGES (Cont.)

| | | | | |
|---|----------|--|--|---------|
| L | 536-5350 | ENVIRONMENT, HIGH DEBRIS 0 FOR USE IN LANE 3 ONLY Adds Sy-Klone engine pre-cleaner and reversing fan and upgrades to a brushless, filtered 150 amp alternator. | | \$4,520 |
|---|----------|--|--|---------|

COLD WEATHER PACKAGES

| | | | | |
|---|----------|---|--|----|
| L | 454-0612 | WEATHER, STANDARD 0 Appropriate at temperatures above -10 Celsius (15 Fahrenheit) and altitude below 1500 meters (5000 feet) | | NC |
|---|----------|---|--|----|

| | | | | |
|---|----------|--|--|---------|
| L | 454-0613 | WEATHER, COLD START 120V 0 Adds ether starting aid, 120V block heater and two additional batteries on the machine right (in place of standard toolbox) for better cold starting. Recommend the following Heated Breather components to be dealer installed when working in environments colder than -25C (-13F) 359-2842 pipe breather 359-2843 pipe breather 359-2844 pipe breather 372-5865 filter as breather ONLY FOR USE WITH: 536-5303 938M WHEEL LOADER 628-9483 938M SWL AGRICULTURE CFG4 559-6225 938M SWL WASTE HANDLER CFG1 559-6228 938M SWL AG HANDLER CFG2 | | \$2,460 |
|---|----------|--|--|---------|

| | | | | |
|---|----------|---|--|---------|
| L | 452-0888 | WEATHER, THERMAL BYPASS 120V 0 FOR USE IN LANE 3 ONLY Adds the cold start package of ether starting aid, 120V block heater and two additional batteries on the machine right (in place of standard toolbox) along with a thermal bypass valve that allows hydraulic oil to bypass the cooler and quickly warm up. Recommended for use in extreme cold climates for better cold starting and hydraulic performance. Recommend the following Heated Breather components to be dealer installed when working in environments colder than -25C (-13F) 359-2842 pipe breather 359-2843 pipe breather 359-2844 pipe breather 372-5865 filter as breather ONLY FOR USE WITH: 536-5303 938M WHEEL LOADER 628-9483 938M SWL AGRICULTURE CFG4 559-6225 938M SWL WASTE HANDLER CFG1 559-6228 938M SWL AG HANDLER CFG2 | | \$2,935 |
|---|----------|---|--|---------|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|----------------------|-----------------|----------------------|
|-----|---------|----------------------|-----------------|----------------------|

SPECIAL ARRANGEMENTS (CONT.)

ENGINE

| | | | | |
|---|----------|--|--|----|
| L | 536-5268 | ENGINE, 938 0 | | NC |
| | | Meets U.S. EPA Tier 4 Final and EU Stage IV emission standards. ONLY FOR USE WITH: 536-5303 938M WHEEL LOADER 628-9483 938M SWL AGRICULTURE CFG4 559-6225 938M SWL WASTE HANDLER CFG1 559-6228 938M SWL AG HANDLER CFG2 628-9484 938M SWL DCA1E 628-9485 938M SWL DCA2E 628-9486 938M SWL DCA3E | | |

HYDRAULICS

LINKAGE/HYRAULICS/VALVES

| | | | | |
|---|----------|--|--|----------|
| L | 536-5341 | HYDRAULICS, 2V, PIN-ON, SL 0 | | NC |
| | | Standard Lift, 2 function hydraulics, For use with pin-on attachments DOES NOT ALLOW INSTALLATION OF QUICK COUPLER. | | |
| L | 536-5342 | HYDRAULICS, 2V, CPLR READY, SL 0 | | \$635 |
| | | Standard Lift, 2 function hydraulics, coupler ready. Coupler not included. | | |
| L | 536-5343 | HYDRAULICS, 3V, CPLR READY, SL 0 | | \$2,760 |
| | | Standard Lift, 3 function hydraulics, coupler ready. Coupler not included. Does NOT include auxiliary 3rd function hydraulic lines down the lift arm or jumper lines to coupler with quick disconnects. | | |
| L | 536-5344 | HYDRAULICS, 4V, CPLR READY, SL 0 | | \$5,260 |
| | | FOR USE IN LANE 3 ONLY Standard Lift, 4 function hydraulics, coupler ready. Coupler not included. Auxiliary 4th function lines terminate mid way down the lift arm. Finland Only - Can order 4V linkage option via Lane 2. REQUIRES: Auxiliary 3rd function hydraulic lines for standard lift Auxiliary ECM for control of 4th function hydraulics | | |
| L | 549-0441 | HYDRAULICS, 2V, PIN-ON, HL 0 | | \$7,490 |
| | | High Lift, 2 function hydraulics, for use with pin-on attachments DOES NOT ALLOW INSTALLATION OF QUICK COUPLER. | | |
| L | 549-0442 | HYDRAULICS, 2V, CPLR READY, HL 0 | | \$8,110 |
| | | High Lift, 2 function hydraulics, coupler ready. Coupler not included. | | |
| L | 549-0443 | HYDRAULICS, 3V, CPLR READY, HL 0 | | \$10,240 |
| | | High Lift, 3 function hydraulics, coupler ready. Coupler not included. Does NOT include auxiliary 3rd function hydraulic lines down the lift arm or jumper lines to coupler with quick disconnects. | | |
| L | 549-0444 | HYDRAULICS, 4V, CPLR READY, HL 0 | | \$12,770 |
| | | FOR USE IN LANE 3 ONLY High Lift, 4 function hydraulics, coupler ready. Coupler not included. Auxiliary 4th function lines terminate mid way down the lift arm. Finland Only - Can order 4V linkage option via Lane 2. REQUIRES: Auxiliary 3rd function hydraulic lines for high lift Auxiliary ECM for control of 4th function hydraulics | | |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|----------------------|-----------------|----------------------|
|-----|---------|----------------------|-----------------|----------------------|

HYDRAULICS (CONT.)

LOAD CHECK VALVES

| | | | | |
|---|----------|---|--|---------|
| L | 536-5284 | HYDRAULICS, STANDARD 0 Hydraulic lines to lift and tilt cylinders that do NOT include load check valves. | | NC |
| L | 536-5288 | HYDRAULICS, LOAD CHECK VALVES 0 Hydraulic lines to lift and tilt cylinders that include load check valves. REQUIRES: Ride Control CANNOT BE USED WITH: Tilt Cylinder Guard 566-4597 CONTROL GP,PAYLOAD,DEMO 250 HR 492-6471 CONTROL GP, PAYLOAD | | \$8,780 |

AUX 3RD HYDRAULIC LINES

| | | | | |
|---|----------|--|--|-------|
| L | 536-5329 | LINES, AUX 3RD, NONE 0 Caps hydraulic 3rd function lines at a bulkhead at the top of the front frame. Does NOT include auxiliary 3rd function hydraulic lines down the lift arm. | | NC |
| L | 530-1628 | LINES, AUX 3RD, STD LIFT 0 Includes Auxiliary 3rd function hydraulic lines down the lift arm for a standard lift linkage. REQUIRES: Standard lift linkage | | \$355 |
| L | 527-8880 | LINES, AUX 3RD, HIGH LIFT 0 Includes Auxiliary 3rd function hydraulic lines down the lift arm for a high lift linkage. REQUIRES: High lift linkage | | \$355 |

JUMPER LINES 3RD

| | | | | |
|---|----------|---|--|-------|
| L | 536-5339 | JUMPER LINES, NONE 0 Caps hydraulic 3rd function lines. Does NOT include hydraulic lines from the lift arm across to the coupler or Quick Disconnects. | | NC |
| L | 445-4725 | JUMPER LINES, AUX 3RD, FUSION 0 Provides jumper lines and flat face connect under pressure quick disconnect coupling from 3rd function auxiliary lines on the front linkage to the coupler. REQUIRES: Fusion Coupler and Auxiliary Lines 3rd | | \$675 |
| L | 561-6216 | JUMPER LINES, AUX 3RD, ISO 0 Provides jumper lines and flat face connect under pressure quick disconnect coupling from 3rd function auxiliary lines on the front linkage to the coupler. REQUIRES: ISO Coupler and Auxiliary Lines 3rd | | \$675 |

ELECTRICAL

WORK LIGHTS

| | | | | |
|---|----------|---|--|----|
| L | 488-1112 | LIGHTS, STD HALOGEN 0 Standard machine light package consisting of two (2) forward facing, cab mounted halogen (70W) wide flood work lights, and two (2) rear door mounted halogen (70W) work/reversing lights. | | NC |
|---|----------|---|--|----|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|----------------------|-----------------|----------------------|
|-----|---------|----------------------|-----------------|----------------------|

ELECTRICAL (CONT.)

WORK LIGHTS (Cont.)

| | | | | |
|---|----------|---|--|---------|
| L | 559-0843 | LIGHTS, STD, LED 0 Standard machine LED light package consisting of two (2) forward facing, cab mounted LED (850 lm) wide flood work lights, and two (2) rear door mounted LED (850 lm) work/reversing lights. Plus three (3) additional LED engine enclosure lights and (1) LED Diesel Exhaust Fluid fill light to aid in service. LED lighting provides brighter lighting and longer life. | | \$339 |
| L | 559-0841 | LIGHTS, AUX, HALOGEN 0 Auxiliary light package consisting of four (4) forward facing, cab mounted halogen (70W) wide flood work lights, and two (2) rear facing cab mounted halogen (70W) wide flood work lights, and two (2) rear door mounted halogen (70W) work/reversing lights. Plus three (3) additional LED engine enclosure lights and (1) LED Diesel Exhaust Fluid fill light to aid in service. | | \$492 |
| L | 559-0842 | LIGHTS, AUX, LED 0 Auxiliary LED/Halogen light package consisting of two (2) forward facing, cab mounted halogen (70W) wide flood work lights, two (2) forward facing, cab mounted LED (2100 lm) low beam work lights, two (2) rear facing, cab mounted LED (850 lm) wide flood work lights, two (2) rear door mounted halogen (70W) work/reversing lights. Plus three (3) additional LED engine enclosure lights and (1) LED Diesel Exhaust Fluid fill light to aid in service. LED lighting provides brighter lighting and longer life. | | \$1,110 |
| L | 559-0844 | LIGHTS, AUX, LED, PREMIUM 0 Premium auxiliary LED light package consisting of two (2) forward facing, cab mounted LED (850 lm) wide flood work lights, two (2) forward facing, cab mounted LED (2100 lm) low beam work lights, two (2) rear facing, cab mounted LED (850 lm) wide flood work lights, two (2) rear door mounted LED (850 lm) work/reversing lights. Plus three (3) additional LED engine enclosure lights and (1) LED Diesel Exhaust Fluid fill light to aid in service. LED lighting provides brighter lighting and longer life. | | \$1,190 |

ROADING LIGHTS

| | | | | |
|---|----------|--|--|---------|
| L | 541-3066 | LIGHTS, ROADING, HALOGEN, RH 0 Includes (2) halogen roading lights for regions that drive on the right hand side of the road. | | NC |
| L | 541-3067 | LIGHTS, ROADING, LED, RH 0 Includes (2) LED roading lights for regions that drive on the right hand side of the road. LED lighting provides brighter lighting and longer life. | | \$1,020 |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|----------------------|-----------------|----------------------|
|-----|---------|----------------------|-----------------|----------------------|

OPERATOR ENVIRONMENT

CAB

| | | | | |
|---|----------|--|--|---------|
| L | 549-0450 | CAB, STANDARD 0 ROPS cab includes automatic blower control, seat mounted implement controls, two heated external mirrors, two internal mirrors, primary instrument display and storage. Tilt and telescoping steering wheel. Includes on/off functionality of soft touch panel functions, but does not allow real time adjustments. Rear view camera and separate WAVS display included CANNOT BE USED WITH: 593-8965 PREP PACK, EU 423-7157 PRECLEANER, CAB, RESPA | | \$1,890 |
| L | 549-0451 | CAB, DELUXE 0 ROPS cab includes automatic blower control, seat mounted implement controls, two heated electrically adjusted external mirrors, two internal mirrors, enhanced in cab LED lighting, front and rear sun visor, tilt, telescopic steering wheel, windshield washing access steps and storage. Also includes the secondary touch screen display which allows real time adjustments to: rimpull; creeper speed; 3rd & 4th maximum flow; throttle lock; fork fine mode; lift & tilt response; hystat modes; directional shift response; ride control activation speed; autolube intervals; bucket float; feather catch; rack snubbing; perfect parallelism, and duals as integrated rear view camera display, rear view camera included | | \$4,760 |

SEAT

| | | | | |
|---|----------|---|--|---------|
| L | 563-5966 | SEAT, STANDARD 0 Fully adjustable fabric covered mechanical suspension seat with mid backrest, headrest, armrests and 3 inch (75 mm) retractable high visibility orange seat belt. | | NC |
| L | 563-5967 | SEAT, DELUXE 0 Fully adjustable fabric covered AIR suspension seat with mid backrest, headrest, mechanical lumbar support, armrests, cushion tilt and extend along with 3 inch (75 mm) retractable high visibility orange seat belt | | \$1,240 |
| L | 563-5968 | SEAT, PREMIUM 0 Fully adjustable LEATHER & Fabric AIR suspension set with HIGH backrest, headrest, AIR LUMBAR support, armrests, cushion tilt and extend along with 3 inch (75 mm) retractable high visibility orange seat belt. Seat is HEATED and COOLED through bottom cushion and backrest. | | \$2,805 |

RADIO

Bluetooth radio technology enables the use of a hands free function such as listening to music and making phone calls.
 Authorization varies by country, please contact your Cat marketing representative with questions or click on the link below:
<https://dealer.cat.com/en/products/technology.html>

| | | | | |
|---|----------|--|--|----|
| L | 342-0130 | RADIO, READY 0 Provides installed speakers and wiring for easy radio installation. | | NC |
|---|----------|--|--|----|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|----------------------|-----------------|----------------------|
|-----|---------|----------------------|-----------------|----------------------|

OPERATOR ENVIRONMENT (CONT.)

RADIO (Cont.)

| | | | | |
|---|----------|--|--|-------|
| L | 378-0951 | RADIO READY, BLUETOOTH, MIC, AUX 0 Provides installed speakers and wiring for easy radio installation. Includes Bluetooth interface, a microphone and aux inputs for powering MP3 players, etc. | | \$635 |
| L | 372-1868 | STANDARD RADIO (12V) 0 Standard 12V AM/FM radio with Bluetooth technology, USB port, and 3.5 mm AUX input. Availability varies by country. Includes Microphones and Aux inputs for connecting MP3 players in Radio. | | \$860 |
| L | 333-1369 | STANDARD RADIO (12V), DUAL USB 0 Standard 12V AM/FM radio with Bluetooth technology, USB port, and 3.5 mm AUX input. Availability varies by country. Includes Microphones , Dual USB Charging ports on machine right hand side and Aux inputs for connecting MP3 players in Radio. | | \$945 |

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

| | | | | |
|---|----------|--|--|-------|
| L | 565-0908 | PRODUCT LINK, CELLULAR PL641 0 Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data. | | NC |
| L | 454-0590 | PRODUCT LINK, SATELLITE PL631 0 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage. | | \$500 |
| L | 565-0909 | PRODUCT LINK, CELLULAR PLE641 0 Product Link Elite series PLE641 (consisting of PL641 radio and PLE601 network manager) uses cellular networks to transmit location, utilization, health and productivity information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data. | | \$425 |
| L | 520-1721 | PRODUCT LINK, SATELLITE PLE631 0 Product Link Elite series PLE631 (consisting of PL631 radio and PLE601 network manager) uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage. | | \$924 |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|-----------------------------|-----------------|----------------------|
|-----|---------|-----------------------------|-----------------|----------------------|

TIRES, RIMS, AND WHEELS

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice. However, if the tire type cannot be supplied we will contact the dealer to propose alternatives. The dealer needs to choose between an alternative tire or a "rims only" option (where available) within 72 hours. If no response is provided by the deadline, the order will default to the alternative tire and will be changed at that point. As a consequence of a possible tire change, the total machine price will be decreased or increased depending on the price of the new tire.

For any tire with a Use type of C, please check with factory before placing order to confirm tire availability.

TIRES AVAILABLE FROM ALLIANCE

| | | | |
|---|----------|--|----------|
| C | 376-0796 | TIRES,28L/26 AN 26PR LS-2 1 PC 0 FOR USE IN LANE 3 ONLY Alliance;Forestry;28L-26;LS-2 High traction and robust lugs. Includes oscillation stops and fender extension brackets. | \$20,640 |
|---|----------|--|----------|

TIRES AVAILABLE FROM MICHELIN

| | | | |
|---|----------|--|----------|
| C | 376-0877 | TIRES,20.5R25 MX XMINE D2** L5 0 FOR USE IN LANE 3 ONLY Michelin;Radial;XMINE D2;L5 Non directional tread;Includes axle oscillation stops | \$35,770 |
| C | 461-2925 | TIRES, 23.5R25 MX XSNO + * L2 0 FOR USE IN LANE 3 ONLY Michelin;Radial;XSNO;L2;Non directional tread Includes axle oscillation stops and fender extension brackets Compatible with 470-6570 COUNTERWEIGHT,3064LBS(1390KG),STD,5PCS on Standard Lift machines for use in general construction applications & compatible with High Lift Machines. REQUIRES: 387-4097 FILM GP, AGGREGATE or 387-4098 FILM GP, FOREST HANDLER when used in combination with 467-7990 COUNTERWEIGHT, HEAVY on Standard Lift machines and 470-6570 COUNTERWEIGHT, STANDARD on High Lift machines for use in heavy material handling applications CANNOT BE USED WITH: 467-7991 COUNTERWEIGHT,4431LBS(2010KG),AGG,8PCS | \$28,250 |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|----------------------|-----------------|----------------------|
|-----|---------|----------------------|-----------------|----------------------|

TIRES, RIMS, AND WHEELS (CONT.)

TIRES AVAILABLE FROM MICHELIN (Cont.)

| | | | | |
|---|----------|--|---|----------|
| C | 461-2924 | TIRES, 23.5R25 MX XHA2 * L3 0 FOR USE IN LANE 3 ONLY Michelin;Radial;XHA2;L3;Non directional tread Includes axle oscillation stops and fender extension brackets Compatible with 470-6570 COUNTERWEIGHT,3064LBS(1390KG),STD,5PCS on Standard Lift machines for use in general construction applications & compatible with High Lift Machines. REQUIRES: 387-4097 FILM GP, AGGREGATE or 387-4098 FILM GP, FOREST HANDLER when used in combination with 467-7990 COUNTERWEIGHT, HEAVY on Standard Lift machines and 470-6570 COUNTERWEIGHT, STANDARD on High Lift machines for use in heavy material handling applications. CANNOT BE USED WITH: 467-7991 COUNTERWEIGHT,4431LBS(2010KG),AGG,8PCS | 0 | \$25,120 |
| C | 373-7314 | TIRES,750/65R26 MXMEGAXBIB* AG 0 FOR USE IN LANE 3 ONLY Michelin;Radial;MegaXbib;Ag Directional tread;Includes oscillation stops | 0 | \$24,000 |
| C | 373-7311 | TIRES,620/75R26 MXMEGAXBIB* AG 0 FOR USE IN LANE 3 ONLY Michelin;Radial;MegaXbib;Ag Directional tread;Includes axle oscillation stops | 0 | \$21,350 |
| C | 366-6894 | TIRES,20.5R25 MX XSNPLUS * L2 0 FOR USE IN LANE 3 ONLY Michelin;Radial;XSNPLUS;L2 Snow Non directional tread;Includes axle oscillation stops | 0 | \$17,350 |
| P | 366-6882 | TIRES,20.5R25 MX XHA2 * L3 0 Michelin;Radial;XHA2;L3;3 pc rim Non directional tread;Includes axle oscillation stops | 0 | \$18,150 |
| C | 366-6902 | TIRES, 550/65R25 MX XLD * L3 0 FOR USE IN LANE 3 ONLY Michelin;Radial;XLD;L3 Low profile;Includes axle oscillation stops | 0 | \$16,180 |
| L | 366-6898 | TIRES, 20.5R25 MX XTLA * L2 0 Michelin;Radial;XTLA;L2;3 pc rim Non directional tread;Includes axle oscillation stops | 0 | \$14,210 |

TIRES AVAILABLE FROM TITAN

| | | | | |
|---|----------|---|---|----------|
| L | 376-0830 | TIRES, 20.5R25 TI MXL * L3 0 Titan;Radial;MXL;L3;3 pc rim Aggressive non directional tread;Includes axle oscillation stops | 0 | \$11,320 |
|---|----------|---|---|----------|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|----------------------|-----------------|----------------------|
|-----|---------|----------------------|-----------------|----------------------|

TIRES, RIMS, AND WHEELS (CONT.)

TIRES AVAILABLE FROM TRELLEBORG

| | | | | |
|---|----------|--|---|----------|
| C | 604-7274 | TIRES,20.5R25 TL BRAWLER, SM 0 FOR USE IN LANE 3 ONLY Trelleborg;Brawler;20.5-25 Press on Soft Ride Smooth Solid Tires Machine speed with solid tires will be limited to 12 mph (20 kph) out of factory. REQUIRES: 348-4657 CTWT, STD, LIGHT, 2412LBS(1094KG),4PCS 565-0906 SPEED LIMITER, 12MPH(20KPH)(North America) or 472-6124 SPEED LIMITER, 12MPH(20KPH)(Europe) CANNOT BE USED WITH: 470-6570 COUNTERWEIGHT,3064LBS(1390KG),STD,5PCS 467-7990 COUNTERWEIGHT,3770LBS(1710KG),HEAV,7PC 467-7991 COUNTERWEIGHT,4431LBS(2010KG),AGG,8PCS 580-5851 MONITOR, TIRE PRESSURE The following EU arrangements: 430-2975 CONVERSION, TUV ROADING 430-2976 CONVERSION, TUV ROADING 20 KPH 472-6119 CONVERSION, IRH 472-6120 CONVERSION, IRH, ROADING, STD | 0 | \$41,840 |
| C | 604-7280 | TIRES,20.5R25 TL BRAWLER, TR 0 FOR USE IN LANE 3 ONLY Trelleborg;Brawler;20.5-25 Press On Soft Ride Traction Solid Tires Machine speed with solid tires will be limited to 12 mph (20 kph) out of factory. REQUIRES: 348-4657 CTWT, STD, LIGHT, 2412LBS(1094KG),4PCS 565-0906 SPEED LIMITER, 12MPH(20KPH)(North America) or 472-6124 SPEED LIMITER, 12MPH(20KPH)(Europe) CANNOT BE USED WITH: 470-6570 COUNTERWEIGHT,3064LBS(1390KG),STD,5PCS 467-7990 COUNTERWEIGHT,3770LBS(1710KG),HEAV,7PC 467-7991 COUNTERWEIGHT,4431LBS(2010KG),AGG,8PCS 580-5851 MONITOR, TIRE PRESSURE The following EU arrangements: 430-2975 CONVERSION, TUV ROADING 430-2976 CONVERSION, TUV ROADING 20 KPH 472-6119 CONVERSION, IRH 472-6120 CONVERSION, IRH, ROADING, STD | 0 | \$39,920 |

TIRES AVAILABLE FROM TRIANGLE

| | | | | |
|---|----------|---|---|---------|
| C | 376-0819 | TIRES,20.5R25TR TL538S+ *** L5 0 FOR USE IN LANE 3 ONLY Triangle;Radial;TL538S+;***,L5 | 0 | \$9,290 |
|---|----------|---|---|---------|

TIRES AVAILABLE FROM YOKOHAMA

| | | | | |
|---|----------|---|---|----------|
| C | 376-0788 | TIRES, 20.5R25 YK RB31 * L3 0 FOR USE IN LANE 3 ONLY Yokohama;Radial;RB31;L3;3 pcs Includes axle oscillation stops. | 0 | \$17,680 |
|---|----------|---|---|----------|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|----------------------|-----------------|----------------------|
|-----|---------|----------------------|-----------------|----------------------|

TIRES, RIMS, AND WHEELS (CONT.)

TIRES AVAILABLE FROM CAMSO

| | | | | |
|---|----------|--|--|---------|
| C | 607-8140 | TIRES, 20.5-25 CS PR20 0 FOR USE IN LANE 3 ONLY Camso LM L3 20.5-25 Bias Tire Non directional tread; Includes axle oscillation stops NOT compatible with TUV and IRH Rooding Package | | \$7,710 |
|---|----------|--|--|---------|

TIRES AVAILABLE FROM MAXAM

| | | | | |
|---|----------|---|--|----------|
| L | 613-2831 | TIRES, 20.5R25 MA MS301 * L3 0 Maxam MS301 L3 20.5R25 Radial Tire Non directional tread; Includes axle oscillation stops | | \$11,330 |
| C | 618-0430 | TIRES, 23.5R25 MA MS302 * L3 0 FOR USE IN LANE 3 ONLY Maxam MS302 L3 23.5R25 Radial Tire Non directional tread; Includes axle oscillation stops and fender extension brackets Compatible with 470-6570 COUNTERWEIGHT,3064LBS(1390KG),STD,5PCS on Standard Lift machines for use in general construction applications & compatible with High Lift Machines. REQUIRES: 387-4097 FILM GP, AGGREGATE or 387-4098 FILM GP, FOREST HANDLER when used in combination with 467-7990 COUNTERWEIGHT, HEAVY on Standard Lift machines and 470-6570 COUNTERWEIGHT, STANDARD on High Lift machines for use in heavy material handling applications. CANNOT BE USED WITH: 467-7991 COUNTERWEIGHT,4431LBS(2010KG),AGG,8PCS | | \$19,400 |
| C | 626-7871 | TIRES,20.5R25 MA MS202*L2 SNOW 0 FOR USE IN LANE 3 ONLY CONTACT CUSTOM PRODUCTS FOR AVAILABILITY. Maxam MS202 L2 20.5R25 Radial Snow Tire Non directional tread; Includes axle oscillation stops Recommended for Snow removal applications | | \$13,450 |

RIMS ONLY

US & Canada - Shipping on Beam Trailer requests will be accepted on a limited basis due to restricted availability and significant increase in shipping costs. Requesting dealers will be charged the difference between shipping on Beam Trailers and Traditional Trailers. Increased costs will vary with Beam Trailers availability.

EAME DEALERS WHEN ORDERING WILL USE MAFI TRANSPORT (0P2489)

| | | | | |
|---|----------|---|--|---------|
| L | 376-0836 | RIMS, 20.5, 3 PC, NO TIRES 0 FOR USE IN LANE 3 ONLY Machine speed will be limited to 12 mph (20 kph) out of factory when ordered in combination with 348-4657 CTWT, STD, LIGHT, 2412LBS,4PCS to be utilized with dealer installed solid tires. When ordering Rim Only groups in combination with Tire Pressure Monitoring, the valve stem sensor caps will be placed in the cab as a loose ship items. The valve stem sensor caps will need to be installed and calibrated by purchasing dealer. CANNOT BE USED WITH: The following EU arrangements: 430-2975 CONVERSION, TUV ROADING 430-2976 CONVERSION, TUV ROADING 20 KPH 472-6119 CONVERSION, IRH 472-6120 CONVERSION, IRH, ROADING, STD | | \$1,145 |
|---|----------|---|--|---------|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|----------------------|-----------------|----------------------|
|-----|---------|----------------------|-----------------|----------------------|

TIRES, RIMS, AND WHEELS (CONT.)

NO TIRES / NO RIMS

US & Canada - Shipping on Beam Trailer requests will be accepted on a limited basis due to restricted availability and significant increase in shipping costs. Requesting dealers will be charged the difference between shipping on Beam Trailers and Traditional Trailers. Increased costs will vary with Beam Trailers availability.

EAME DEALERS WHEN ORDERING WILL USE MAFI TRANSPORT (0P2489)

| | | | |
|---------|---|---|----------|
| 0P-2755 | NO TIRES / NO RIMS | 0 | \$-2,250 |
| | FOR USE IN LANE 3 ONLY | | |
| | CANNOT BE USED WITH: The following EU arrangements: | | |
| | 430-2975 CONVERSION, TUV ROADING | | |
| | 430-2976 CONVERSION, TUV ROADING 20 KPH | | |
| | 472-6119 CONVERSION, IRH | | |
| | 472-6120 CONVERSION, IRH, ROADING, STD | | |

OTHER ATTACHMENTS

FENDERS

| | | | |
|---|---|---|---------|
| L | 366-8150 FENDERS, STANDARD | 0 | NC |
| | Provides black, non-metallic front fenders and partial coverage rear fenders for use on machines configured with standard CENTERMOUNT rims. | | |
| | CANNOT BE USED WITH: The following EU arrangements: | | |
| | 430-2975 CONVERSION, TUV ROADING | | |
| | 430-2976 CONVERSION, TUV ROADING 20 KPH | | |
| | 472-6119 CONVERSION, IRH | | |
| | 472-6120 CONVERSION, IRH, ROADING, STD | | |
| | 430-2982 CONVERSION, UK ROADING | | |
| L | 366-8198 FENDERS, EXTENDED COVER | 0 | \$2,495 |
| | Provides yellow, non-metallic front fenders and extended coverage rear fenders for use on machines configured with standard CENTERMOUNT rims. Recommended for applications that include roading or long load and carry. | | |
| | CANNOT BE USED WITH: OFFSET TIRES | | |
| L | 430-2850 FENDERS, FULL COVER | 0 | \$3,120 |
| | Provides yellow, non-metallic front fenders and full coverage rear fenders along with mud flaps on the back side of both front and rear tires. For use on machines configured with standard CENTERMOUNT rims. Recommended for applications such as snow removal and extremely muddy conditions. | | |
| | CANNOT BE USED WITH: Offset Rims | | |
| L | 419-8851 FENDERS, DEFLECTORS | 0 | \$560 |
| | Provides yellow, metal front deflectors that provide protection to hitch, ladder, and cab from debris thrown up or stuck in the front tires. | | |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 MANDATORY | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|----------------------|-----------------|----------------------|
|-----|---------|----------------------|-----------------|----------------------|

OTHER ATTACHMENTS (CONT.)

COUNTERWEIGHTS

| | | | | |
|---|----------|---|--|---------|
| L | 470-6570 | COUNTERWEIGHT,3064LBS,STD,5PCS 0 Standard Counterweights are for use with Pin On work tools. Compatible with 23.5 R25 tire groups on Standard Lift machines working in general construction applications. Compatible with 23.5R25 tire groups on High Lift machines. NOT compatible with Brawler, Flexport and other solid tire groups. | | NC |
| L | 348-4657 | CTWT, STD, LIGHT, 2412LBS,4PCS 0 Standard Light Counterweights are for use with Flexport, Brawler and other solid tire groups. | | NC |
| L | 467-7990 | COUNTERWEIGHT,3770LBS,HEAV,7PC 0 Standard counterweight Plus additional frame mounted counterweights for use with Couplers and Hook On work tools. Compatible with 23.5R25 tire groups on Standard Lift machines configured with Aggregate Handler or Forest Handler segment modifier decals. Contact factory for compatibility with 23.5 tires when working in other heavy material handling applications. NOT compatible with Flexport and Brawler tire groups. Compatible with 938M High Lift on 20.5" tires. NOT compatible with 938M High Lift on 23.5" tires. | | \$3,120 |
| L | 467-7991 | COUNTERWEIGHT,4431LBS,AGG,8PCS 0 Heavy counterweight plus additional frame mounted counterweight for use in applications such as Log and Lumber, Aggregate Handling, Auto Re-Handling and heavy material handling. NOT compatible with 23.5 tire groups. NOT compatible with High Lift machines. NOT compatible with Brawler and other solid tire groups. | | \$7,210 |

TOOLBOX

| | | | | |
|---|----------|--|--|-------|
| L | 519-8081 | TOOLBOX AUX, NONE 0 Provides cosmetic cover over optional tool box location but does not include a tool box. | | NC |
| L | 491-7922 | TOOLBOX AUX 0 Provides lockable tool box that mounts under the left side of the cab. | | \$590 |

FLUIDS

| | | | | |
|--|----------|---|--|---------|
| | 619-8439 | HYDRAULIC OIL, STANDARD 0 | | NC |
| | 619-8441 | HYDRAULIC OIL, BIODEGRADABLE 0 | | \$2,720 |

INSTRUCTIONS

OPERATION AND MAINTENANCE MANUAL

| | | | | |
|--|----------|--|--|----|
| | 421-8926 | SERIALIZED TECHNICAL MEDIA KIT 0 The technical media kit, will include the Operation & Maintenance Manual (OMM) and other media specified on the Factory Notification required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary. Any additional media or translations not included in the kit, should be ordered through https://publications.cat.com | | NC |
|--|----------|--|--|----|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

HYDRAULICS

ELECTRONIC CONTROL MODULE

| | | | | |
|---|----------|---|--|----|
| L | 536-5318 | AUX ECM. 0 Additional Electronic Control Module (ECM) to control 4th function hydraulics and/or dual mode steering. REQUIRES: 4 function hydraulics and/or dual mode steering | | NC |
|---|----------|---|--|----|

OPERATOR ENVIRONMENT

RIDE CONTROL.

| | | | | |
|---|----------|--|--|---------|
| L | 430-2860 | RIDE CONTROL. 0 Improves ride quality when travelling. In "Automatic" mode, Ride Control is set to activate above 6 mph. System is programmable between 1.6 km/h (1 mph) and 14.5 km/h (9 mph). Includes system active indicator on dash. | | \$4,710 |
|---|----------|--|--|---------|

CAB FILTRATION

| | | | | |
|---|----------|--|--|---------|
| L | 423-7157 | PRECLEANER, CAB, RESPA 0 FOR USE IN LANE 3 ONLY Powered cab air precleaner improves operator air quality and cab pressurization. Includes cab pressure sensor. | | \$3,745 |
|---|----------|--|--|---------|

WASHING ACCESS STEPS

| | | | | |
|---|----------|---|--|-------|
| L | 469-0647 | WINDSHIELD ACCESS STEPS 0 Provides right hand side front frame mounted steps and hand rail to facilitate access for an operator to clean the front windshield. CANNOT BE USED WITH: CAB, DELUXE | | \$745 |
|---|----------|---|--|-------|

DECALS , STEP AND HANDRAIL

| | | | | |
|---|----------|--|--|-------|
| L | 615-9208 | DECAL,HI VIS STEP,HANDRAIL,LHS 0 This provides high visibility decals for the left-hand handrails and steps and additionally includes decals for the handrails on the inside of the cab door. CANNOT BE USED WITH: 549-0451 CAB, DELUXE | | \$147 |
| L | 615-9210 | DECAL,HI VIS STEP,HANDRAIL,DLX 0 This provides high visibility decals for the left-hand and right-hand side handrails and steps and additionally includes decals for the handrail on the inside of the cab door. FOR USE WITH: 549-0451 CAB, DELUXE or 469-0647 WINDSHIELD ACCESS STEPS | | \$189 |

CELL PHONE HOLDER

| | | | | |
|---|----------|---|--|------|
| L | 616-0037 | HOLDER,CELL PHONE 0 This upgrade provides a mount to place your cell phone. Clips are included to provide a way to route your charging cable cleanly. Holder is made of powder-coated, marine-grade aluminum, stainless steel components, and high-strength composite for durability. FOR USE WITH: 549-0450 CAB, STANDARD | | \$95 |
|---|----------|---|--|------|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

OPERATOR ENVIRONMENT (CONT.)

CELL PHONE HOLDER (Cont.)

| | | | | |
|---|----------|---|--|-------|
| L | 616-0034 | HOLDER,CELL PHONE,SEC DISPLAY 0 This upgrade provides a mount to place your cell phone. Clips are included to provide a way to route your charging cable cleanly. Holder is made of powder-coated, marine-grade aluminum, stainless steel components, and high-strength composite for durability. Requires Secondary Display FOR USE WITH: 549-0451 CAB, DELUXE | | \$116 |
|---|----------|---|--|-------|

INTEGRATED OBJECT DETECTION SYSTEM

For a list of countries that RF radar is approved for use in, visit <https://dealer.cat.com/detect>

| | | | | |
|---|----------|--|--|---------|
| L | 573-8473 | DETECTION, OBJECT (RADAR) 0 The Cat Integrated Object Detection System combines a camera, radar, and alarms to notify the operator when something is close to the rear of the machine. The system is configured with zones and objects in those zones trigger various levels of alarms. A display screen in the cab provides visual confirmation of the objects detected by the radar, so operators can make informed decisions. NOTE: Not available in all regions depending on radar approval. For a list of countries that the B7 radar is approved in please visit: https://dealer.cat.com/detect Object Detection - Approved Country Listing FOR USE WITH: 549-0451 CAB, DELUXE CANNOT BE USED WITH: 430-2926 GUARD, REAR RADIATOR | | \$4,100 |
|---|----------|--|--|---------|

LIGHTS

| | | | | |
|---|----------|--|--|-------|
| L | 333-1425 | WARNING, BEACON, LED STROBE 0 Provides hard mounted strobe beacon on hinged (breakaway) bracket mounted to the rear of the cab structure. | | \$310 |
| L | 616-0040 | LIGHTS,WARNING,REVERSE STROBE 0 Provides 2 reversing white strobes mounted to the rear grill. Reversing strobes flash white lights when machine is reversing. | | \$452 |

MIRROR

| | | | | |
|---|----------|---|--|-------|
| L | 482-5167 | SIDE MIRROR, RH 0 Provides a look down mirror mounted to the top right hand side of the cab. | | \$108 |
|---|----------|---|--|-------|

TECHNOLOGY PRODUCTS

CAT COMMAND - COMMAND FOR LOADING

In the USA, Cat M-series Small Wheel Loaders can be configured with Remote Control KITs for Non Line of Site operation. See COMMANDCI Price List for compatible Serial Numbers,KIT Part Numbers and Software Enabled Attachment Details.

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

TECHNOLOGY PRODUCTS (CONT.)

CAT PRODUCTION MEASUREMENT (CPM) PAYLOAD WEIGHING SYSTEM

Cat M-series Small Wheel Loaders are available with the Cat Production Measurement (CPM) that includes an integrated onboard payload weighing scale. This measures and/or records:

- Payload weight, material ID, truck ID, cycle (bucket dumps) count and fuel consumption
- Allows on-the-go weighing of the bucket payload during the lift cycle
- Daily payload total (tonnes/tons), productivity (tonnes/hour or tons/hour) and efficiency (tonnes/liter or tons/gal) data is reported wirelessly via Product Link to the VisionLink fleet management web portal (Cat Essentials Product Link subscription required).
- Detailed payload, productivity and efficiency data can be downloaded to a laptop computer for analysis in the optional VIMSpC software (VIMSpC and VIMS data cable are required, but VIMS is NOT required).
- Payload tickets can be printed with an optional printer. Refer to the Cat Connect Payload Technologies intranet page (<https://dealer.cat.com/payload>) for complete technical specifications; operation, sales, marketing and technical support publications.

CALIBRATION INSTRUCTIONS

This requires calibration and set-up by either the dealer or customer. Refer to the Systems Operation Test & Adjust manual for system calibration, material and truck ID lists set-up and operation instructions.

| | | | | |
|---|----------|--|--|----------------|
| L | 566-4597 | CONTROL GP,PAYLOAD,DEMO 250 HR 0 | | \$655 |
| | | Includes sensors and 250 hours of demonstration time for Cat Production Measurement (CPM). See note above for calibration instructions. The 250 hours of demonstration time can be activated via the secondary display and will remind the operator when time is close to expiring. A permanent software license for Cat Production Measurement (CPM) will be a separate charge. Purchase software license from https://fps.cat.com (Use Reason Code #149). Requires SEA 518-3210 CPM PAYLOAD SOFTWARE, SWL for permanent activation. REQUIRES: CAB, DELUXE 565-0909 PRODUCT LINK, CELLULAR PLE641 or 520-1721 PRODUCT LINK, SATELLITE PLE631 CANNOT BE USED WITH: Load Check Valves | | |
| L | 492-6471 | CONTROL GP, PAYLOAD 0 | | \$5,730 |
| | | Includes sensors, software license for Cat Production Measurement(CPM) Software is factory enabled, but the system must be calibrated prior to customer use. See note above for calibration instructions. REQUIRES: CAB, DELUXE 565-0909 PRODUCT LINK, CELLULAR PLE641 or 520-1721 PRODUCT LINK, SATELLITE PLE631 CANNOT BE USED WITH: Load Check Valves | | |
| L | 494-7948 | CONTROL GP, PRINTER 0 | | \$1,950 |
| | | Provides onboard ticket printing capability for Cat Production Measurement (CPM). Printer mounts in rear right corner of cab. REQUIRES: 492-6471 CONTROL GP, PAYLOAD or 566-4597 CONTROL GP,PAYLOAD,DEMO 250 HR | | |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

TECHNOLOGY PRODUCTS (CONT.)

TIRE PRESSURE MONITORING

| | | | | |
|---|----------|---|--|---------|
| L | 580-5851 | MONITOR, TIRE PRESSURE 0 Provides four sensors that mount to the valve stem of each tire along with a receiver module that monitors both pressure and temperature in each tire. Tire pressure and temperature information is shared with the operator via the secondary display. Warnings are provided via the secondary display and through Unified Fleet if pressure is outside of a configurable target range. REQUIRES: CAB, DELUXE CANNOT BE USED WITH: 604-7274 TIRES,20.5R25 TL BRAWLER, SM or 604-7280 TIRES,20.5R25 TL BRAWLER, TR | | \$1,895 |
|---|----------|---|--|---------|

GUARDS

UPPER GUARDS

| | | | | |
|---|----------|---|--|---------|
| L | 342-0250 | GUARD, WINDSHIELD 0 Provides protection to the front windshield from falling debris in waste, forestry, agriculture etc. while allowing excellent visibility to the ground and worktool. | | \$3,745 |
| L | 377-1530 | GUARD, FRONT LIGHTS 0 Provides two (2) front light guards that mount over the headlights. CANNOT BE USED WITH: The following EU arrangements: 430-2975 CONVERSION, TUV ROADING 430-2976 CONVERSION, TUV ROADING 20 KPH 472-6119 CONVERSION, IRH 472-6120 CONVERSION, IRH, ROADING, STD 430-2982 CONVERSION, UK ROADING | | \$439 |
| L | 377-1560 | GUARD, REAR LIGHTS 0 Provides two (2) rear light guards that mount over the tail lights. Not compatible with Heavy Duty Rear Guard. CANNOT BE USED WITH: 430-2926 GUARD, REAR RADIATOR The following EU arrangements: 430-2975 CONVERSION, TUV ROADING 430-2976 CONVERSION, TUV ROADING 20 KPH 472-6119 CONVERSION, IRH 472-6120 CONVERSION, IRH, ROADING, STD 430-2982 CONVERSION, UK ROADING | | \$499 |
| L | 433-9751 | GUARD, TILT CYLINDER, STD LIFT 0 Provides protection to the tilt cylinder, preventing damage to the rod, hoses and cylinder seal. Cannot be used with endorsed check valve option. | | \$895 |
| L | 418-8602 | GUARD, TILT CYLINDER,HIGH LIFT 0 Provides protection to the tilt cylinder, preventing damage to the rod, hoses and cylinder seal. Cannot be used with endorsed check valve option. | | \$1,015 |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

GUARDS (CONT.)

UPPER GUARDS (Cont.)

| | | | | |
|---|----------|---|--|---------|
| L | 430-2926 | GUARD, REAR RADIATOR 0 FOR USE IN LANE 3 ONLY Provides protection to rear of the machine and cooling package. Includes swing out guard for cooling access and mounting for rear camera. CANNOT BE USED WITH: 377-1560 GUARD, REAR LIGHTS 573-8473 DETECTION, OBJECT (RADAR) 370-6579 CONVERSION, LICENSE PLATE 467-7991 COUNTERWEIGHT,4431LBS(2010KG),AGG,8PCS | | \$5,790 |
|---|----------|---|--|---------|

LOWER GUARDS

| | | | | |
|---|----------|---|--|---------|
| L | 349-8165 | GUARD, POWERTRAIN, LOWER 0 Mounts underneath machine to provide protection for the transmission components | | \$1,630 |
| L | 425-1425 | GUARD, POWERTRAIN, SIDE 0 Mounts on side of machine to provide protection for the transmission components | | \$635 |
| L | 349-8163 | GUARD, CRANKCASE 0 Mounts underneath machine to provide protection to the engine components | | \$1,120 |
| L | 349-8164 | GUARD, DRIVESHAFT 0 Mounts underneath machine to provide front drive shaft protection. | | \$720 |
| L | 430-2917 | GUARD, STEERING CYLINDER 0 Provides protection to both steering cylinders, preventing damage to rods and cylinder seals. | | \$865 |
| L | 391-1990 | GUARD, HITCH 0 Provides protection to hitch area of the rear frame, preventing debris from entering the frame, while allowing visibility to service points. | | \$800 |

OTHER ATTACHMENTS

DECALS

| | | | | |
|---|----------|---|--|----|
| L | 387-4096 | FILM GP, WASTE HANDLER 0 REQUIRES: 349-8164 GUARD, DRIVESHAFT 349-8163 GUARD, CRANKCASE 349-8165 GUARD, POWERTRAIN, LOWER 425-1425 GUARD, POWERTRAIN, SIDE 391-1990 GUARD, HITCH 536-5340 ENVIRONMENT, MEDIUM DEBRIS or 536-5350 ENVIRONMENT, HIGH DEBRIS | | NC |
|---|----------|---|--|----|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

OTHER ATTACHMENTS (CONT.)

DECALS (Cont.)

| | | | | |
|---|----------|---|--|------|
| L | 387-4097 | FILM GP, AGGREGATE 0 REQUIRES: 467-7991 COUNTERWEIGHT,4431LBS(2010KG),AGG,8PCS or 467-7990 COUNTERWEIGHT,3770LBS(1710KG),HEAV,7PC in combination with 23.5 tires and One of the following buckets in North America 451-1410 BUCKET-S&G, 3.5 YD3, FUS, BOCE 625-4742 BUCKET-S&G, 3.5 YD3, FUS, BOTS 466-2256 BUCKET-S&G, 4.2 YD3, PO, BOCE 625-4739 BUCKET-S&G, 4.2 YD3, PO, BOTS 451-1411 BUCKET-S&G, 4.2 YD3, FUS, BOCE 625-4743 BUCKET-S&G, 4.2 YD3, FUS, BOTS | | NC |
| L | 387-4098 | FILM GP, FOREST HANDLER 0 REQUIRES: 467-7991 COUNTERWEIGHT,4431LBS(2010KG),AGG,8PCS or 467-7990 COUNTERWEIGHT,3770LBS(1710KG),HEAV,7PC in combination with 23.5 tires | | \$70 |

REMOTE AXLE AND GEARBOX BREATHER

| | | | | |
|---|----------|--|--|-------|
| L | 469-0502 | BREATHER GROUP. 0 Provides remote mounted breathers for both axles and hystat gearbox, used when machines enter deep water. | | \$312 |
|---|----------|--|--|-------|

AUTOLUBE ARRANGEMENT

| | | | | |
|---|----------|--|--|---------|
| L | 536-5349 | AUTOLUBE. 0 Provides Caterpillar Autolube System for automatic lubrication of machine pin joints requiring daily lubrication: Linkage pin joints, including bucket pins, articulation hitch, steering cylinders and axle trunnions. System is accessed through the Secondary Display to adjust lubrication frequency and provide low reservoir alert. REQUIRES: CAB, DELUXE | | \$7,680 |
|---|----------|--|--|---------|

SPEED LIMITER

| | | | | |
|---|----------|---|--|----|
| P | 565-0906 | SPEED LIMITER, 20KPH 0 This selection activates a electronic speed limit on the machine to reduce max ground speed down to 12mph (20kph).The Speed Limit is programed at the time of build and control with a factory password. This Speed Limiter is required with Solid Tire Offerings. NOT COMPATIBLE with 472-6124 SPEED LIMITER, 12MPH (20KPH) 430-2976 CONVERSION, TUV ROADING 12MPH (20KPH) | | NC |
|---|----------|---|--|----|

QUICK COUPLERS

COUPLERS

| | | | | |
|---|----------|--|--|---------|
| L | 536-5314 | QUICK COUPLER, FUSION 0 Includes a cast coupler frame, and electro-hydraulic coupler actuation system activated from the cab. Includes constant pressure coupler wedges. REQUIRES COUPLER READY MACHINE | | \$4,890 |
|---|----------|--|--|---------|

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

QUICK COUPLERS (CONT.)

COUPLERS (Cont.)

| | | | | |
|---|----------|---|--|---------|
| L | 536-5316 | QUICK COUPLER, ISO 23727 0 Includes an electro-hydraulic cast coupler actuation system, activated from the cab. Includes lock valve cylinder. Compatible with many competitive worktools, ISO Standard coupler interface is also used by Volvo. REQUIRES COUPLER READY MACHINE | | \$6,150 |
| L | 387-2859 | TRANSPORT GROUP 0 Required when a machine is ordered without a coupler or Pin-On Bucket | | \$635 |

WORK TOOLS

For European Dealers: For Lane 2 and Lane 3 orders no work tools can be ordered ex Factory (except for quick couplers). Please see WT-SWL price list for available work tools and order through Antares.

FORK CARRIAGE, FUSION COUPLER ONLY

| | | | | |
|---|----------|--|--|----------|
| P | 532-8222 | CARRIAGE, PAL C3/4, 62", FUS 324 1524mm width (60") Does not include tines. For Use With: Forks listed in the Fork Tines section below. REQUIRES: Fusion Coupler | | \$2,610 |
| P | 538-3866 | CARRIAGE, CON, FORK, 60", FUS 961 Construction forks, carriage, and tines 2435mm width (96") Includes 1524mm tines (60") REQUIRES: Fusion Coupler | | \$9,594 |
| P | 538-3867 | CARRIAGE, CON, FORK, 72", FUS 1,004 Construction forks, carriage, and tines 2435mm width (96") Includes 1829mm tines (72") REQUIRES: Fusion Coupler | | \$10,640 |

FORK TINES STRAIGHT

Price is for a quantity of one (1). Must order a quantity of two (2).

| | | | | |
|---|----------|---|--|---------|
| P | 371-2348 | FORK TINE, 2.25" X 6" X 48" 297 REQUIRES: 532-8222 CARRIAGE, PAL C3/4, 62"(1566MM), FUS | | \$965 |
| P | 371-2354 | FORK TINE, 2.25" X 6" X 54" 321 REQUIRES: 532-8222 CARRIAGE, PAL C3/4, 62"(1566MM), FUS | | \$1,035 |
| P | 371-2360 | FORK TINE, 2.25" X 6" X 60" 345 REQUIRES: 532-8222 CARRIAGE, PAL C3/4, 62"(1566MM), FUS | | \$1,069 |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

WORK TOOLS (CONT.)

FORK TINES HIGH VISIBILITY (OFFSET)

(MUST ORDER BOTH RIGHT AND LEFT FORKS)

| | | | | |
|---|----------|--|--|---------|
| P | 371-2374 | FORK TINE,2.25"X6"X48", RIGHT 301 High visibility forks recommended for enhanced line of site to fork tips REQUIRES: 532-8222 CARRIAGE, PAL C3/4, 62"(1566MM), FUS and 371-2375 FORK TINE,2.25"X6"X48", LEFT | | \$1,125 |
| P | 371-2375 | FORK TINE,2.25"X6"X48", LEFT 301 High visibility forks recommended for enhanced line of site to fork tips REQUIRES: 532-8222 CARRIAGE, PAL C3/4, 62"(1566MM), FUS and 371-2374 FORK TINE,2.25"X6"X48", RIGHT | | \$1,125 |
| P | 360-3354 | FORK TINE,2.25"X6"X54", LEFT 323 High visibility forks recommended for enhanced line of site to fork tips REQUIRES: 532-8222 CARRIAGE, PAL C3/4, 62"(1566MM), FUS and 360-3355 FORK TINE,2.25"X6"X54", RIGHT | | \$1,181 |
| P | 360-3355 | FORK TINE,2.25"X6"X54", RIGHT 323 High visibility forks recommended for enhanced line of site to fork tips REQUIRES: 532-8222 CARRIAGE, PAL C3/4, 62"(1566MM), FUS and 360-3354 FORK TINE,2.25"X6"X54", LEFT | | \$1,181 |
| P | 371-2377 | FORK TINE,2.25"X6"X60", RIGHT 348 High visibility forks recommended for enhanced line of site to fork tips REQUIRES: 532-8222 CARRIAGE, PAL C3/4, 62"(1566MM), FUS and 371-2376 FORK TINE,2.25"X6"x60"(60X150X1524MM), LEFT | | \$1,229 |
| P | 371-2376 | FORK TINE,2.25"X6"X60", LEFT 348 High visibility forks recommended for enhanced line of site to fork tips REQUIRES: 532-8222 CARRIAGE, PAL C3/4, 62"(1566MM), FUS and 371-2377 FORK TINE,2.25"X6"x60"(60X150X1524MM), RIGHT | | \$1,229 |

MATERIAL HANDLING ARM

| | | | | |
|---|----------|---|--|------------|
| P | 510-5071 | ARM, MATERIAL HANDLING, FUS 534 Four positions, one fixed, three manually adjustable. REQUIRES: Fusion Coupler | | \$8,097 NI |
|---|----------|---|--|------------|

BUCKETS

ALL BUCKETS LISTED HERE ARE "PERFORMANCE SERIES" BUCKETS OFFERING IMPROVED PENETRATION AND INCREASED FILL FACTOR

EAME DEALERS, PLEASE SEE WT-SWL PRICE LIST.

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

BUCKETS (CONT.)

BUCKETS, GENERAL PURPOSE (FUSION)

| | | | | |
|---|----------|--|-------|----------|
| P | 417-4919 | BUCKET-GP, 2.5 YD3, FUS, BOCE | 2,008 | \$7,875 |
| | | Includes: BUCKET-GP, HO Cutting Edge, Bolt On (4 Piece) 2550mm (100") width General Purpose Bucket | | |
| P | 625-4380 | BUCKET-GP, 2.5 YD3, FUS, A70 | 2,167 | \$9,819 |
| | | Includes: BUCKET-GP, HO Cat ADVANSYS 70 Bolt on Tips and Adaptors (set of 7) along with Segments (7 piece) 2550mm (100") width General Purpose Bucket | | |
| P | 417-4925 | BUCKET-GP, 3.2 YD3, FUS, BOCE | 2,403 | \$10,528 |
| | | Includes: BUCKET-GP, HO Cutting Edge, Bolt On (4 Piece) 2550mm (100") width General Purpose Bucket | | |
| P | 625-4397 | BUCKET-GP, 3.2 YD3, FUS, A70 | 2,579 | \$12,472 |
| | | Includes: BUCKET-GP, HO Cat ADVANSYS 70 Bolt on Tips and Adaptors (set of 7) along with Segments (7 piece) 2550mm (100") width General Purpose Bucket | | |
| P | 417-4355 | BUCKET-GP, 3.2 YD3, FUS, BOCE | 2,430 | \$10,764 |
| | | Includes: BUCKET-GP, HO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width General Purpose Bucket | | |
| P | 625-4734 | BUCKET-GP, 3.2 YD3, FUS, A70 | 2,599 | \$12,792 |
| | | Includes: BUCKET-GP, HO Cat ADVANSYS 70 Bolt on Tips and Adaptors (set of 7) along with Segments (7 piece) 2750mm (108") width General Purpose Bucket | | |
| P | 345-2427 | BUCKET-GP, 3.5 YD3, FUS, BOCE | 2,519 | \$11,306 |
| | | Includes: BUCKET-GP, HO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width General Purpose Bucket | | |
| P | 625-4732 | BUCKET-GP, 3.5 YD3, FUS, A70 | 2,694 | \$13,333 |
| | | Includes: BUCKET-GP, HO Cat ADVANSYS 70 Bolt on Tips and Adaptors (set of 7) along with Segments (7 piece) 2750mm (108") width General Purpose Bucket | | |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

BUCKETS (CONT.)

BUCKETS, GENERAL PURPOSE (FUSION) (Cont.)

| | | | | |
|---|----------|--|--|----------|
| P | 417-4929 | BUCKET-GP, 3.8 YD3, FUS, BOCE 2,601 Includes: BUCKET-GP, HO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width General Purpose Bucket | | \$11,833 |
| P | 625-4733 | BUCKET-GP, 3.8 YD3, FUS, A70 2,771 Includes: BUCKET-GP, HO Cat ADVANSYS 70 Bolt on Tips and Adaptors (set of 7) along with Segments (7 piece) 2750mm (108") width General Purpose Bucket | | \$13,847 |

BUCKETS, GENERAL PURPOSE (PIN-ON)

| | | | | |
|---|----------|---|--|----------|
| P | 417-4895 | BUCKET-GP, 3.2 YD3, PO, BOCE 2,455 FOR USE IN LANE 3 ONLY Includes: BUCKET-GP, PO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width General Purpose Bucket | | \$10,764 |
| P | 625-4735 | BUCKET-GP, 3.2 YD3, PO, A70 2,632 FOR USE IN LANE 3 ONLY Includes: BUCKET-GP, PO Cat ADVANSYS 70 Bolt on Tips and Adaptors (set of 7) along with Segments (7 piece) 2750mm (108") width General Purpose Bucket | | \$12,792 |
| P | 417-4927 | BUCKET-GP, 3.5 YD3, PO, BOCE 2,552 Includes: BUCKET-GP, PO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width General Purpose Bucket | | \$11,306 |
| P | 625-4736 | BUCKET-GP, 3.5 YD3, PO, A70 2,729 Includes: BUCKET-GP, PO Cat ADVANSYS 70 Bolt on Tips and Adaptors (set of 7) along with Segments (7 piece) 2750mm (108") width General Purpose Bucket | | \$13,333 |
| P | 417-4349 | BUCKET-GP, 3.8 YD3, PO, BOCE 2,649 Includes: BUCKET-GP, PO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width General Purpose Bucket | | \$11,833 |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

BUCKETS (CONT.)

BUCKETS, GENERAL PURPOSE (PIN-ON) (Cont.)

| | | | | |
|---|----------|--|-------|----------|
| P | 625-4737 | BUCKET-GP, 3.8 YD3, PO, A70 | 2,787 | \$13,847 |
| | | Includes: BUCKET-GP, PO Cat ADVANSYS 70 Bolt on Tips and Adaptors (set of 7) along with Segments (7 piece) 2750mm (108") width General Purpose Bucket | | |

BUCKETS, FLAT FLOOR (FUSION)

Recommended for fine grading and back drag applications. This bucket features a flat floor that helps operators create a finished grade.

| | | | | |
|---|----------|--|-------|----------|
| P | 491-0525 | BUCKET-FF, 3.2 YD3, FUS, BOCE | 2,621 | \$12,208 |
| | | FOR USE IN LANE 3 ONLY Width 2750 mm (108"). Includes BOCE. Flat Floor Bucket Capacity: 2.5 m3 (3.2 yd3) fill factor 100% | | |
| P | 491-0535 | BUCKET-FF, 3.8 YD3, FUS, BOCE | 2,811 | \$13,278 |
| | | FOR USE IN LANE 3 ONLY Width 2750 mm (108"). Includes BOCE. Flat Floor Bucket Capacity: 2.9 m3 (3.8 yd3) fill factor 100% | | |

BUCKETS, SAND & GRAVEL (FUSION)

Recommended for aggregate handling applications. This bucket includes additional wear plates for improved life when handling abrasive materials.

| | | | | |
|---|----------|--|-------|----------|
| P | 451-1410 | BUCKET-S&G, 3.5 YD3, FUS, BOCE | 2,638 | \$12,458 |
| | | Includes: BUCKET-GP, HO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width Sand & Gravel Bucket | | |
| P | 625-4742 | BUCKET-S&G, 3.5 YD3, FUS, A70 | 2,694 | \$14,472 |
| | | Includes: BUCKET-GP, HO Cat ADVANSYS 70 Bolt on Tips and Adaptors (set of 7) along with Segments (7 piece) 2750mm (108") width Sand & Gravel Bucket | | |
| P | 469-0192 | BUCKET-S&G, 3.8 YD3, FUS, BOCE | 2,723 | \$12,986 |
| | | FOR USE IN LANE 3 ONLY Includes: BUCKET-GP, HO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width Sand & Gravel Bucket | | |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

BUCKETS (CONT.)

BUCKETS, SAND & GRAVEL (FUSION) (Cont.)

| | | | | |
|---|----------|--|--|----------|
| P | 625-4744 | BUCKET-S&G, 3.8 YD3, FUS, A70 2,892 FOR USE IN LANE 3 ONLY Includes: BUCKET-GP, HO Cat ADVANSYS 70 Bolt on Tips and Adaptors (set of 7) along with Segments (7 piece) 2750mm (108") width Sand & Gravel Bucket | | \$15,000 |
| P | 451-1411 | BUCKET-S&G, 4.2 YD3, FUS, BOCE 2,788 Includes: BUCKET-GP, HO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width Sand & Gravel Bucket | | \$13,694 |
| P | 625-4743 | BUCKET-S&G, 4.2 YD3, FUS, A70 2,961 Includes: BUCKET-GP, HO Cat ADVANSYS 70 Bolt on Tips and Adaptors (set of 7) along with Segments (7 piece) 2750mm (108") width Sand & Gravel Bucket | | \$15,708 |

BUCKETS, SAND & GRAVEL (PIN-ON)

Recommended for aggregate handling applications. This bucket includes additional wear plates for improved life when handling abrasive materials.

| | | | | |
|---|----------|--|--|----------|
| P | 469-0194 | BUCKET-S&G, 3.8 YD3, PO, BOCE 2,757 FOR USE IN LANE 3 ONLY Includes: BUCKET-GP, PO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width Sand & Gravel Bucket | | \$12,986 |
| P | 625-4745 | BUCKET-S&G, 3.8 YD3, PO, A70 2,928 FOR USE IN LANE 3 ONLY Includes: BUCKET-GP, PO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width Sand & Gravel Bucket | | \$15,000 |
| P | 466-2256 | BUCKET-S&G, 4.2 YD3, PO, BOCE 2,840 FOR USE IN LANE 3 ONLY Includes: BUCKET-GP, PO Cutting Edge, Bolt On (4 Piece) 2750mm (108") width Sand & Gravel Bucket | | \$13,694 |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

BUCKETS (CONT.)

BUCKETS, SAND & GRAVEL (PIN-ON) (Cont.)

| | | | | |
|---|----------|---|-------|----------|
| P | 625-4739 | BUCKET-S&G, 4.2 YD3, PO, A70 | 3,000 | \$15,708 |
| | | FOR USE IN LANE 3 ONLY | | |
| | | Includes: | | |
| | | BUCKET-GP, PO | | |
| | | Cat ADVANSYS 70 Bolt on Tips and Adaptors (set of 7) along with | | |
| | | Segments (7 piece) | | |
| | | 2750mm (108") width | | |
| | | Sand & Gravel Bucket | | |

BUCKETS, LIGHT MATERIAL (FUSION)

| | | | | |
|---|----------|--|----------------|-------------------------|
| P | 452-7417 | BUCKET-LM, 4.0 YD3, FUS, BOCE | 2,689 2,689 | \$10,458 \$10,458 NI |
| | | FOR USE IN LANE 3 ONLY | | |
| | | Light Material Bucket, Width 2750 mm (108"). Includes 1pc BOCE | | |
| | | Capacity: 3 m3 (4 yd3) fill factor 100% | | |
| | | FOR USE WITH: FUSION Quick Coupler | | |
| P | 417-4935 | BUCKET-LM, 4.5 YD3, FUS, BOCE | 2,873 2,873 | \$11,333 \$11,333 NI |
| | | Light Material Bucket, Width 2750 mm (108"). Includes 1pc BOCE | | |
| | | Capacity: 3.5 m3 (4.5 yd3) fill factor 100% | | |
| | | FOR USE WITH: FUSION Quick Coupler | | |
| P | 450-0252 | BUCKET-LM, 5.0 YD3, FUS, BOCE | 3,015 3,015 | \$12,222 \$12,222 NI |
| | | FOR USE IN LANE 3 ONLY | | |
| | | Light Material Bucket, Width 2750 mm (108"). Includes 1pc BOCE | | |
| | | Capacity: 3.8 m3 (5 yd3) fill factor 100% | | |
| | | FOR USE WITH: FUSION Quick Coupler | | |
| P | 417-4342 | BUCKET-LM, 5.5 YD3, FUS, BOCE | 3,172 3,172 | \$13,111 \$13,111 NI |
| | | Light Material Bucket, Width 2750 mm (108"). Includes 1pc BOCE | | |
| | | Capacity: 4.2 m3 (5.5 yd3) fill factor 100% | | |
| | | FOR USE WITH: FUSION Quick Coupler | | |
| | | FOR USE WITH: FUSION Quick Coupler | | |
| P | 417-4950 | BUCKET-LM, 6.5 YD3, FUS, BOCE | 3,311 3,311 | \$14,875 \$14,875 NI |
| | | FOR USE IN LANE 3 ONLY | | |
| | | Light Material Bucket, Width 2750 mm (108"). Includes BOCE, | | |
| | | Capacity: 5 m3 (6.5 yd3) fill factor 100% | | |
| | | FOR USE WITH: FUSION Quick Coupler | | |

BUCKETS, LIGHT MATERIAL (PIN-ON)

| | | | | |
|---|----------|--|-------|----------|
| P | 360-3332 | BUCKET-LM, 4.5 YD3, PO, BOCE | 2,893 | \$11,333 |
| | | FOR USE IN LANE 3 ONLY | | |
| | | Light Material Bucket, Width 2750 mm (108"). Includes 1pc BOCE | | |
| | | Capacity: 3.5 m3 (4.5 yd3) fill factor 100% | | |
| P | 450-0251 | BUCKET-LM, 5.0 YD3, PO, BOCE | 3,023 | \$12,222 |
| | | FOR USE IN LANE 3 ONLY | | |
| | | Light Material Bucket, Width 2750 mm (108"). Includes 1pc BOCE | | |
| | | Capacity: 3.8 m3 (5 yd3) fill factor 100% | | |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

BUCKETS (CONT.)

BUCKETS, LIGHT MATERIAL (PIN-ON) (Cont.)

| | | | | |
|---|----------|---|--|----------|
| P | 360-3333 | BUCKET-LM, 5.5 YD3, PO, BOCE 3,170 FOR USE IN LANE 3 ONLY Light Material Bucket, Width 2750 mm (108"). Includes 1pc BOCE Capacity: 4.2 m3 (5.5 yd3) fill factor 100% | | \$13,111 |
| P | 360-3334 | BUCKET-LM, 6.5 YD3, PO, BOCE 3,298 FOR USE IN LANE 3 ONLY Light Material Bucket, Width 2750 mm (108"). Includes 1pc BOCE Capacity: 5 m3 (6.5 yd3) fill factor 100% | | \$14,875 |

FLUIDS

| | | | | |
|--|---------|--|--|-----------|
| | OP-2407 | ANTIFREEZE, -50C (-58F) 0 For use where there is a possibility ambient temperatures may fall below -37C (-34F) and down to a minimum of -52C (-62F) | | \$318 NET |
|--|---------|--|--|-----------|

ALTERNATE SOURCED ATTACHMENTS

Available through ANTARES Parts Ordering
NOTE: US & Canada ONLY may place orders in CMOPS to be transferred via the bridge to ANTARES Parts Ordering.
When ordering via CMOPS include top level reference numbers (OP3538) and OP number for packing.

NO RETURNS will be accepted for kit components not used or parts removed from machines during kit installation.

KIT ORDERS MUST BE ORDERED SEPARATELY FROM A MACHINE ORDER.

| | | | | |
|---|----------|--|--|----------|
| P | 370-7008 | KIT, WARNING, BEACON, LED STROBE 0 Kit provides hard mounted LED strobe beacon on hinged (breakaway) bracket mounted to the rear of the cab structure. Estimated time to install: 15 minutes | | \$279 NI |
| P | 614-0278 | KIT, LIGHTS, REVERSE STROBE 0 Kit provides 2 reversing white strobes mounted to the rear grill. Reversing strobes flash white lights when machine is reversing. Cannot be used with Japan MLIT Prep Pack Estimated time to install: 30 minutes | | \$386 NI |
| P | 374-5868 | KIT, LIGHTS, AUX, HALOGEN 0 Kit provides two (2) additional forward facing, cab mounted halogen (70W) wide flood work lights, and two (2) rear facing cab mounted halogen (70W) wide flood work lights. Estimated time to install: 60 minutes | | \$294 NI |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

ALTERNATE SOURCED ATTACHMENTS (CONT.)

| | | | | |
|---|----------|---|--|-------------------|
| P | 452-0853 | KIT, LIGHTS, AUX, LED 0 Kit provides two (2) additional forward facing, cab mounted LED (2100 lm) low beam work lights, two (2) rear facing, cab mounted LED (850 lm) wide flood work lights. LED lighting provides brighter lighting and longer life. | | \$972 NI |
| P | 463-3795 | KIT, LIGHTS, LED, ENGINE 0 Kit provides three (3) additional LED engine enclosure lights to illuminate the way for checking oil and coolant levels along with refueling the machine in dark conditions. | | \$299 NI |
| P | 376-5324 | KIT, PRECLEANER, CAB AIR-RESPA 0 Provides a powered cab air pre cleaner, mounting brackets, and interior cab pressure sensor. Improves operator air quality and cab pressurization in the K & M Series SWL. Recommended for high debris environments. | | \$2,576 NI |
| P | 376-4390 | KIT, PRECLEANER, TURBINE 0 Kit provides turbine precleaner for the engine that ejects particles before intake. Recommended for high debris environments. | | \$686 NI |
| P | 467-7992 | KIT, COUNTERWEIGHT, AGGREGATE 0 Kit converts a heavy counterweight machine to a Aggregate Handler machine by adding an additional frame mounted counterweight for use in applications such as Log and Lumber, Aggregate Handling, Auto Re-Handling and heavy material handling. NOT compatible with High Lift machines. CANNOT BE USED WITH: Brawler Tires | | \$4,979 NI |
| P | 447-4895 | KIT, COUPLER READY 0 Kit provides coupler valve and hydraulic lines to convert a 2V pin on STD lift machine into a 2V coupler ready machine For use with machine serial numbers before J3R07425 | | \$1,028 NI |
| P | 576-4833 | KIT, COUPLER READY 0 Kit provides coupler valve and hydraulic lines to convert a 2V pin on STD lift machine into a 2V coupler ready machine For use with machine serial numbers after J3R07425 and P5K00120 | | \$736 NI |
| P | 545-5499 | KIT, QUICK COUPLER, ISO 23727 0 Kit provides an electro-hydraulic Cast ISO Interface coupler actuation system activated from the cab. Includes lock valve cylinder. Compatible with many competitive work tools, ISO standard coupler interface is also used by Volvo. Requires Coupler Ready Machine. Recommend to also install Counterweight, Heavy For use with machine serial numbers before J3R07425 | | \$7,181 NI |
| P | 566-5500 | KIT,CAST QUICK CPLR, ISO 23727 0 Kit provides an electro-hydraulic Cast ISO Interface coupler actuation system activated from the cab. Includes lock valve cylinder. Compatible with many competitive work tools, ISO standard coupler interface is also used by Volvo. Requires Coupler Ready Machine. For use with machines after serial number J3R07425 and P5K00120 | | \$7,181 NI |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

ALTERNATE SOURCED ATTACHMENTS (CONT.)

| | | | | |
|---|----------|---|--|------------|
| P | 374-5791 | KIT, FAB QUICK COUPLER, FUSION 0 Kit provides an electro-hydraulic coupler actuation system activated from the cab. Includes constant pressure coupler wedges. Requires Coupler Ready Machine. Recommend to also install Counterweight, Heavy For use with machine serial numbers before J3R07425 | | \$5,708 NI |
| P | 566-5498 | KIT, CAST QUICK COUPLER, FUSION 0 Kit provides an electro-hydraulic Cast Fusion Interface coupler actuation system activated from the cab. Includes constant pressure coupler wedges. Requires Coupler Ready Machine. For use with machine serial numbers after J3R07425 and P5K00120 | | \$5,708 NI |
| P | 582-1425 | KIT, FORWARD FACING CAMERA 0 Includes a camera, display, harness, brackets and hardware to mount a forward facing camera system. The forward facing camera is mounted to an external breakaway bracket in the top left corner of cab. The display is mounted in the upper left corner of the cab and replaces an internal mirror. The forward camera may be required for local EU requirements. Consult Cat dealer for additional information. Refer to Product Bulletin, TEJB9977 at catpublications.com | | \$2,889 NI |
| P | 463-3793 | KIT, REAR VIEW CAMERA 0 Kit provides rear view camera that mounts to rear door and harness. Requires secondary display. | | \$1,465 NI |
| P | 463-3794 | KIT, MONITOR, SECONDARY DISPLAY 0 Kit provides a secondary display which allows real time adjustments to rimpull, creeper speed, 3rd function flow, throttle lock, and duals as a rear camera display (camera not included). For use with machines before serial number J3R03650 | | \$2,243 NI |
| P | 494-7956 | KIT, MONITOR, SECONDARY DISPLAY 0 Kit provides a secondary touch screen display which allows real time adjustments to rimpull, creeper speed, 3rd function flow, throttle lock, and duals as a rear camera display (camera not included) | | \$2,174 NI |
| P | 441-4005 | KIT, QUICK DISCONNECTS 0 Kit provides a set (male & female) of flat face connect under pressure quick disconnects. Recommended to adapt existing work tools to the new improved SWL quick disconnects. For use with machine serial numbers before J3R07425 Estimated time to install: 60 minutes | | \$428 NI |
| P | 441-3368 | KIT, JUMPER LINES, 3RD FUNCTION 0 Kit provides 3rd function jumper lines and threaded flat face connect under pressure quick disconnects mounted to the coupler. Recommended for use with 3rd function work tools. Provides a kit to add 3rd function jumper line. For use with machine serial numbers before J3R07425 Estimated time to install: 60 minutes | | \$785 NI |
| P | 576-9758 | KIT, JUMPER LINES, 3RD FUNCTION 0 Kit provides 3rd function jumper lines and threaded flat face connect under pressure quick disconnects mounted to the coupler. Recommended for use with 3rd function work tools. Provides a kit to add 3rd function jumper line. For use with machine serial numbers after J3R07425 and P5K00120 | | \$415 NI |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|--|----------|---|-----------------|----------------------|
| ALTERNATE SOURCED ATTACHMENTS (CONT.) | | | | |
| P | 374-5858 | KIT,COUNTERWEIGHT,HEAVY 705 LB 0 Kit provides additional frame mounted counterweights +320KG (705lbs). Kit converts standard counterweight group to heavy. | | \$3,646 NI |
| P | 589-6664 | ADAPTER INTERFACE, FUSION-IT 0 Provides adaptor bracket with fusion hooks on the back and manually engaged IT pins on the front allowing it to interface with IT coupler tools. Recommended for mixed fleet customers. Adaptor pushes attachment away from machine resulting in decreased lift and tilt capacity. | | \$3,083 NI |
| P | 457-0939 | KIT, 2V2L 0 Kit provides 2 valve single axis lift and tilt levers with console mounted FNR, diff lock and horn switches | | \$1,701 NI |
| P | 471-7009 | KIT, FNR, COLUMN 0 Kit provides a FNR shifter lever, wiring harness, mounting bracket and templates to modify the existing bracket and covers to install the shifter on the left hand (LH) side of the steering column. The multi-function stalk switch is relocated to the right hand (RH) side of the column. | | \$465 NI |
| P | 371-2400 | HOOK, FLAT BACK, FUSION 330 Provides brackets with Fusion hooks on the back and a flat interface on the front allowing it to be welded to existing SWL work tools. Recommended for customers who want to re-hinge existing non Fusion tools or competitive tools to a Fusion interface.Reference install procedures to Rework Loader Buckets for Use with Fusion Couplers (REHS3953). | | \$1,049 NI |
| P | 374-5855 | KIT, BLOCK HEATER, 120V 0 Kit provides 120V block heater to improve cold start performance. Estimated time to install: 2 Hours | | \$344 NI |
| P | 374-5856 | KIT, BLOCK HEATER, 240V 0 Kit provides 240V block heater to improve cold start performance. Estimated time to install: 2 Hours | | \$344 NI |
| P | 374-5854 | KIT, ETHER START 0 Kit provides ether starting aid to improve cold start performance. Estimated time to install: 2 Hours | | \$526 NI |
| P | 370-7010 | KIT, START, HEAVY DUTY 0 Kit provides battery box for installation of 2 additional batteries (in place of standard tool box), along with cables and battery tie-downs (batteries not included). Estimated time to install: 3 Hours | | \$1,576 NI |
| P | 387-4189 | KIT, ALTERNATOR HEAVY DUTY 0 Estimated time to install: 3 Hours | | \$1,854 NI |
| P | 452-0856 | KIT, RIDE CONTROL 0 Kit provides multi-accumulator system to absorb shock and reduce machine bounce when traveling. For use with machine serial numbers before J3R07425 | | \$5,500 NI |
| P | 577-0373 | KIT, RIDE CONTROL 0 Kit provides multi-accumulator system to absorb shock and reduce machine bounce when traveling. For use with machine serial numbers after J3R07425 and P5K00120 | | \$5,514 NI |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

ALTERNATE SOURCED ATTACHMENTS (CONT.)

| | | | | |
|---|----------|---|--|-------------------|
| P | 374-5859 | KIT, STEERING, SECONDARY 0 Kit provides a combined electric motor / hydraulic pump along with required lines to add a secondary back-up steering system for increased safety. Required in some countries and some locations by OSHA/MSHA. Provides limited steering control in the event of a loss of power or a loss of hydraulic flow. Includes operator warning system indicator and operator alarm. Estimated time to install: 4 Hours | | \$4,160 NI |
| P | 374-5847 | KIT, FENDERS, EXTENDED COVER 0 Kit provides yellow, non-metalic front fenders and extended coverage rear fenders. Kit converts standard fender group to extended cover. Recommended for applications that include long load and carry. Estimated time to install: 60 minutes | | \$2,917 NI |
| P | 562-5684 | KIT, POLY FRONT WINDSHIELD 0 Kit provides optical grade, fretted anti-glare tinted and anti-scratch coated polycarbonate front upper windshield, lower left and right window panels. Each panel is individually serviceable and will provide improved impact resistance from falling debris in various applications such as waste, recycling, forestry and agriculture while allowing unobstructed visibility to the ground and work tool. The polycarbonate kit is compatible with KIT, GUARD, WINDSHIELD for additional protection. | | \$2,354 NI |
| P | 387-4190 | KIT, GUARD, WINDSHIELD 0 Kit provides protection to the front windshield from falling debris in waste, forestry, agriculture, etc. while allowing excellent visibility to the ground and worktool. | | \$4,375 NI |
| P | 374-5861 | KIT, GUARD, FRONT LIGHTS 0 Kit provides two (2) front light guards that mount over the headlights. CANNOT BE USED WITH: 430-2975 CONVERSION, TUV ROADING 430-2976 CONVERSION, TUV ROADING 20 KPH 472-6120 CONVERSION, IRH, ROADING, STD 472-6119 CONVERSION, IRH 430-2982 CONVERSION, UK ROADING | | \$514 NI |
| P | 374-5864 | KIT, GUARD, REAR LIGHTS 0 Kit provides two (2) rear light guards that mount over the tail lights. Not compatible with Heavy Duty Rear Guard. | | \$582 NI |
| P | 437-1880 | KIT, GUARD, TILT CYL, STD LIFT 0 Provides protection to the tilt cylinder, preventing damage to the rod, hoses and cylinder seal. Cannot be used with endorsed check valve option. | | \$755 NI |
| P | 437-1881 | KIT, GUARD, TILT CYL,HIGH LIFT 0 Provides protection to the tilt cylinder, preventing damage to the rod, hoses and cylinder seal. Cannot be used with endorsed check valve option. | | \$1,174 NI |
| P | 452-0858 | KIT, REVERSING FAN 0 Kit provides a hydraulically operated demand fan with reversing option. Includes automatic and manual controls for fan reversal. Recommended for applications with a high content of airborne debris. | | \$2,708 NI |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|--|----------|---|-----------------|----------------------|
| ALTERNATE SOURCED ATTACHMENTS (CONT.) | | | | |
| P | 452-0860 | KIT, FULL COVER, MUD FLAPS 0 Kit provides mud flaps and extended coverage to front and rear tires. Kit converts extended cover fender group to full cover. Not for use with 366-8148 FENDERS, STANDARD. | | \$875 NI |
| P | 374-5843 | KIT, GUARD, DRIVESHAFT 0 Kit provides drive shaft guard that mounts underneath the front frame. | | \$847 NI |
| P | 374-5844 | KIT, GUARD, POWERTRAIN, LOWER 0 Kit provides lower transmission guard that mounts underneath the rear frame. | | \$1,924 NI |
| P | 452-0857 | KIT, GUARD, POWERTRAIN, SIDE 0 Kit provides two (2) side transmission guards that mount to both sides of the rear frame. | | \$736 NI |
| P | 374-5845 | KIT, GUARD, CRANKCASE 0 Kit provides engine crankcase guard that mounts underneath the rear frame. | | \$1,306 NI |
| P | 437-8603 | KIT, GUARD, FENDERS, WASTE 0 Provides yellow, metal front deflectors that provides protection to hitch, ladder, and cab from debris thrown up or stuck in the front tires. | | \$683 NI |
| P | 433-2002 | KIT, GUARD, HITCH 0 Provides protection to hitch area of the rear frame, preventing debris from entering the frame, while allowing visibility to service points. | | \$924 NI |
| P | 387-4194 | KIT, STEERING CYLINDER GUARD 0 Provides protection to both steering cylinders, preventing damage to rods and cylinder seals. | | \$1,021 NI |
| P | 377-1573 | KIT, GUARD, REAR RADIATOR 0 Kit provides protection to rear of the machine and cooling package. Includes swing out guard for cooling access and mounting for rear camera. CANNOT BE USED WITH: 374-5864 KIT, GUARD, REAR LIGHTS 430-2975 CONVERSION, TUV ROADING 430-2976 CONVERSION, TUV ROADING 20 KPH 472-6120 CONVERSION, IRH, ROADING, STD 472-6119 CONVERSION, IRH 430-2982 CONVERSION, UK ROADING 619-6725 KIT, OBJECT DETECTION, RADAR | | \$6,771 NI |
| P | 372-1949 | KIT, VISION MONITOR (WAVS) 0 Kit provides a dedicated rear vision monitor mounted high on the cab A post. Required in some EU countries where a rear view needs to be on permanent display. Can be used with any NTSC or PAL camera located elsewhere on the machine. | | \$1,972 NI |
| P | 370-7004 | KIT, SECURITY SYSTEM, CAT MSS 0 Kit provides a programmable system to manage access to machine. Includes 2 special MSS keys. | | \$1,361 NI |
| P | 416-1179 | KIT, RADIO, CD, DELUXE 0 Provides a AM/FM radio with weatherband and CD player, includes Bluetooth, Aux & USB capability | | \$1,313 NI |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|--|----------|---|-----------------|------------------------|
| ALTERNATE SOURCED ATTACHMENTS (CONT.) | | | | |
| P | 372-1871 | KIT, RADIO AM/FM 0 Provides a AM/FM radio with Bluetooth, Aux & USB capability | | \$722 NI |
| P | 472-6125 | KIT, CONV,20 KPH SPEED LIMITER 0 Kit provides 20 kph speed labels and electronically limits speed to 20 kph. CANNOT BE USED WITH: 472-6123 KIT, CONV, TUV ROADING 20 KPH | | \$23 NI NET |
| P | 374-5865 | KIT, LICENSE PLATE 0 Kit provides illuminated license plate holder that mounts to the rear door. | | \$294 NI |
| P | 363-4245 | KIT, DRAIN, ECO FUEL 0 Kit provides an ecology drain plug and tube for the fuel tank. | | \$560 NI |
| P | 416-1958 | KIT, FILM, WASTE HANDLER 0 | | \$32 NI |
| P | 416-1959 | KIT, FILM, AGGREGATE 0 | | \$32 NI |
| P | 416-1960 | KIT, FILM, FOREST HANDLER 0 | | \$32 NI |
| P | 452-0861 | KIT, STARTING, HIGH ALTITUDE 0 Kit provides a hydraulic fan bypass valve to improve cold starting in cold weather high altitude conditions. | | \$1,028 NI |
| P | 387-4186 | KIT, STEERING, DUAL MODE 0 Kit provides Dual Mode Hand Metering Unit (HMU) and required lines to convert a standard steering machine into Dual Mode. Adds the ability to enable Dual Mode Steering (Quick Steer) to minimize operator efforts in repetitive cycles. For machines with serial numbers after J3R07425 and P5K00120. The consist of 599-4061 KIT, AUX ECM is also required. | | \$1,806 NI |
| P | 419-7164 | KIT, BREATHER GROUP 0 Provides remote mounted breathers for both axles and hystat gearbox, used when machines enter deep water. | | \$369 NI |
| P | 595-8650 | KIT,POWERED PRECLEANER,ENGINE 0 Kit provides powered engine inlet air pre-cleaner system components needed as part of the siloxane gas solution that extends the Clean Emission Module and other aftertreatment component life in Industrial and Waste applications. This system allows Small Wheel Loader machines to operate in air containing siloxane and other volatile organic compounds. If the optional RESPA Cab HVAC Pre-Cleaner kit is desired, this kit contains instructions for additional rework that is required to use these two kits together. This kit is required for indoor job sites and highly recommended for outdoor job sites in Industrial and Waste applications where Siloxane Gas is present. NOT COMPATIBLE WITH TUV/IRH ROADING PACKAGES. REQUIRES: 622-4217 KIT, SILOXANE FILTER, ENGINE for a full siloxane gas solution. | | \$1,806 NI |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

ALTERNATE SOURCED ATTACHMENTS (CONT.)

| | | | | |
|---|----------|---|--|-------------------|
| P | 622-4217 | KIT, SILOXANE FILTER, ENGINE 0 Kit provides siloxane gas filter system components needed as part of the siloxane gas solution that extends the Clean Emission Module and other aftertreatment component life in Industrial and Waste applications. This system allows Small Wheel Loader machines to operate in air containing siloxane and other volatile organic compounds. If the optional RESPA Cab HVAC Pre-Cleaner kit is desired, this kit contains instructions for additional rework that is required to use these two kits together. This kit is required for indoor job sites and highly recommended for outdoor job sites in Industrial and Waste applications where Siloxane Gas is present. NOT COMPATIBLE WITH TUV/IRH ROADING PACKAGES. REQUIRES: 595-8650 KIT,POWERED PRE CLEANER ENGINE for a full siloxane gas solution. | | \$4,306 NI |
| P | 522-0264 | KIT, AUTOLUBE 0 Kit includes Caterpillar Autolube System for automatic lubrication of machine pin joints requiring daily lubrication: Linkage pin joints, including bucket pins, articulation hitch, steering cylinders and rear axle trunnions. System is accessed through the Secondary Display to adjust lubrication frequency and provide low reservoir alert. Kit is compatible with both standard lift & high lift machine configurations. For use with serial numbers after J3R03650 & P5K00100 | | \$6,410 NI |
| P | 460-2746 | KIT, RIM 25X26 1PC X4 0 Kit provides a set of 4 one piece rims for use with 750 Ag XBib tires. Enables easier switching between different types of tires in the field | | \$5,424 NI |
| P | 460-2747 | KIT, RIM 19X25 3PC X4 0 Kit provides a set of 4 three piece rims for use with 650 low profile and 23.5R25 tires. Enables easier switching between different types of tires in the field. | | \$7,472 NI |
| P | 460-2749 | KIT, RIM 17X25 3PC X4 0 Kit provides a set of 4 three piece rims for use with 20.5R25 Center Mount tires. Enables easier switching between different types of tires in the field. | | \$5,424 NI |
| P | 460-2750 | KIT, RIM 17X25 3PC X4 0 Kit provides a set of 4 three piece rims for use with 20.5R25 Offset tires. Enables easier switching between different types of tires in the field. | | \$5,424 NI |
| P | 450-0490 | KIT, THERMAL BYPASS 0 Kit provides a cold oil cooler bypass valve for machines that continuously operate in ambient temperatures lower than -5 Deg C and enables oil to quickly warm up to 50 Deg C | | \$694 NI |
| P | 445-2010 | KIT, WINDSHIELD ACCESS STEPS 0 Kit provides right hand side front frame mounted steps and hand rail to facilitate access for an operator to clean the front windshield. | | \$882 NI |
| P | 502-4860 | KIT, SERVICE TIE OFF 0 Kit provides a service tie off on left rear corner of cab that is a weld on dealer attachment. | | \$164 NI |
| P | 494-8000 | KIT, ELITE, NETWORK MANAGER 0 Kit includes Network Manager for conversion of Product Link Pro to Product Link Elite. Required to field install Cat Production Measurement kit 494-7950 KIT, CONTROL GP, PAYLOAD | | \$488 NI |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

ALTERNATE SOURCED ATTACHMENTS (CONT.)

| | | | | |
|---|----------|--|--|------------|
| P | 494-7950 | KIT, CONTROL GP, PAYLOAD 0 Kit includes sensors and hardware. Software license for Cat Production Measurement (CPM) will be a separate charge. Requires secondary display and Product Link Elite (Network Manager). 250 hours of demonstration time can be activated via the secondary display and will remind the operator when time is close to expiring. Requires purchase of software license from https://fps.cat.com (Use Reason Code #149). Requires SEA 518-3210 CPM PAYLOAD SOFTWARE, SWL for permanent activation. For use with serial numbers after J3R03650 & P5K00100 | | \$665 NI |
| P | 494-7947 | KIT, MONITOR, TIRE PRESSURE 0 Kit includes four sensors that mount to the valve stem of each tire along with a receiver module that monitors both pressure & temperature in each tire. Tire pressure & temperature information is shared with the operator via the secondary display. Warnings are provided via the secondary display and through Unified Fleet if pressure is outside of a configurable target range. Software license for Cat Tire Pressure Monitoring (TPM) will be a separate charge. Requires secondary touch screen display. Requires SEA 518-3231 for permanent activation. For use with serial numbers after J3R03650 & P5K00100 | | \$2,208 NI |
| P | 494-8001 | KIT, CONTROL GP, PRINTER 0 Kit includes printer for onboard ticket printing capability for Cat Production Measurement (CPM). Printer mounts in rear right corner of cab. REQUIRES: 492-6471 CONTROL GP, PAYLOAD 494-7950 KIT, CONTROL GP, PAYLOAD | | \$2,285 NI |
| P | 418-4190 | KIT, FUEL DOOR 0 Kit provides an elevated fuel fill location along with an access door for fueling the machine through the large right side service door without opening it. | | \$875 NI |
| P | 619-6725 | KIT, OBJECT DETECTION, RADAR 0 Kit provides a Cat Integrated Object Detection System that combines a radar and alarms to notify the operator when something is close to the rear of the machine. The system is configured with zones and objects in those zones trigger various levels of alarms. A display screen in the cab provides visual confirmation of the objects detected by the radar, so operators can make informed decisions. NOTE: Not available in all regions depending on radar approval. For a list of countries that the B7 radar is approved in please visit: https://dealer.cat.com/detect Object Detection - Approved Country Listing. Requires secondary display and rear camera. | | \$4,833 NI |
| P | 552-8380 | KIT, SEAT BELT, 4 POINT 0 This kit includes Harness and hardware for installation of four-point seat belts on premium seat. Estimated time to install: 2 hours | | \$635 NI |
| P | 615-1920 | KIT,DECAL HI VIS STEP,HANDRAIL 0 This kit provides high visibility decals for the left-hand and right-hand handrails and steps and additionally includes decals for the handrails on the inside of the cab door. | | \$168 NI |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|---------|---------------------|-----------------|----------------------|
|-----|---------|---------------------|-----------------|----------------------|

ALTERNATE SOURCED ATTACHMENTS (CONT.)

| | | | | |
|---|----------|---|--|-------------------|
| P | 599-4061 | KIT, AUX ECM 0 KIT includes Additional Electronic Control Module (ECM) to control 4th function hydraulics and/or dual mode steering. | | \$1,313 NI |
| P | 387-4023 | KIT, 3RD VALVE, STANDARD LIFT 0 Kit provides implement valve section, joystick and hydraulic lines to convert a 2 valve (2V) Standard Lift machine to 3 valve (3V) For machines with serial number before J3R03650 | | \$3,125 NI |
| P | 612-6230 | KIT, CELL PHONE HOLDER 0 The kit includes mount, hardware and cable management clips for installation onto the interior A-post of the cab. Holder is made of powder-coated, marine-grade aluminum, stainless steel components, and high-strength composite for durability. Estimated time to install: 30 minutes | | \$85 NI |
| P | 527-8437 | KIT, 3RD VALVE, STANDARD LIFT 0 Kit provides implement valve section, joystick and hydraulic lines to convert a 2 valve (2V) Standard Lift machine to 3 valve (3V) For machines with serial number after J3R03650 and before J3R07425 | | \$3,028 NI |
| P | 577-0375 | KIT, 3RD VALVE, STD OR HIGH LFT 0 Kit provides implement valve section, joystick and hydraulic lines to convert a 2 valve (2V) Standard Lift machine or High Lift machine to 3 valve (3V). For machines with serial number after J3R07425 and P5K00120 | | \$2,493 NI |
| P | 577-0371 | KIT, 4TH VALVE 0 Kit provides implement valve section, joystick, ECM and hydraulic lines to convert a 3 valve (3V) machine to 4 valve (4V) For machines with serial number after J3R07425 and P5K00120 599-4061 KIT, AUX ECM is also required. | | \$2,917 NI |
| P | 420-4335 | KIT, 3RD VALVE, HIGH LIFT 0 Kit provides implement valve section, joystick and hydraulic lines to convert a 2 valve (2V) High Lift machine to 3 valve (3V) For use with machine serial numbers before J3R07425 | | \$3,472 NI |
| P | 452-0863 | KIT, 4TH VALVE, STANDARD LIFT 0 Kit provides implement valve section, joystick, ECM and hydraulic lines to convert a 3 valve (3V) STD Lift machine to 4 valve (4V) | | \$2,917 NI |
| P | 567-0732 | KIT, AXLE COVER 0 KIT provides 4 piece non-metallic guard to prevent debris from getting between axle hub and housing for added protection to the seals. This kit is recommended for extreme debris environments like Industrial and Waste along with Basgasse handling (sugar cane pulp). | | \$317 NI |

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|------------|----------------------------|--------------------|-------------------------|
|-----|------------|----------------------------|--------------------|-------------------------|

ALTERNATE SOURCED ATTACHMENTS (CONT.)

ENDORSED FIELD INSTALLED ATTACHMENTS

Caterpillar does not warrant, service, or assume responsibility for these attachments.

All orders, pricing confirmation, and other communication for these attachments must be directed to the listed manufacturer.

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|-----|------------|----------------------------|--------------------|-------------------------|
|-----|------------|----------------------------|--------------------|-------------------------|

ALTERNATE SOURCED ATTACHMENTS (CONT.)**FIRE SUPPRESSION SYSTEM**

System to protect engine installation, hydraulic pumps, and transmission from a thermal incident. Fully integrated system which includes an in cab monitor of machine enclosure temperatures and focused foam based suppression system. Activates automatically as well as manually, from the cab or from the outside of the machine.

For use when machine is in application or environments with potentially flammable air borne debris or waste materials.

CONTACT YOUR DEALER OR AFEX FOR PRICING AND TERMS

Steve Payne
spayne@afexsystems.com
(919)-781-6610 Tel
(919)-787-3915 Fax
www.afexsystems.com

CATERPILLAR MACHINE PRICE LIST

938M

| USE | REF NO. | LANE 2 / 3 OPTIONAL | Ship Weight lbs | LIST PRICE AT DEALER |
|----------------|---------|---|-----------------|----------------------|
| PACKING | | | | |
| | OG-8010 | PACKING, PHYTO-SANITARY WOOD 0 All wood or wood derivative packaging material with this shipment requires Phytosanitary Certificate. If all packing material is wood-free (metal or plastic), this shipment requires a Declaration of No Wood Packing Material. | | NC |
| | OP-2266 | SHIPPING/STORAGE PROTECTION 0 Provides protective application of Fluid Film TM for protection while shipping and for extended storage periods. This product will need to be power washed with soapy water prior to shipment to the customer. | | \$239 NET |
| | OG-6022 | CERTIFICATE OF ORIGIN, ENGLISH 0 | | NC |
| | OP-0210 | PACK, DOMESTIC TRUCK 0 | | NC |
| | OP-2160 | PACK, MISCELLANEOUS MATERIAL 0 Exfactory Kits, Freight Collect | | NC |
| | OP-2161 | PACKING, KIT (RUSH) 0 Exfactory Kits, Freight Collect, Expedite Shipment | | \$161 NET |