

CATERPILLAR MACHINE PRICE LIST

950GC

950GC WHEEL LOADER
 QINGZHOU, CHINA

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

Engine Cat C7.1 and ATAAC
 Torque converter
 Transmission, automatic, power shift
 (4F/3R), kick-down function, overspeed
 protection
 Brakes, full hydraulic enclosed wet-disc
 EIMS (Engine Idle Management System)
 Fan, radiator, electronically
 controlled, hydraulically driven,
 temperature sensing, on demand
 Filter, fuel primary-water separator/
 secondary
 Radiator, unit core (9.5 fpi) with ATAAC
 Starting aid, glow plugs
 Switch, transmission neutralizer lockout

HYDRAULICS

Load sensing implement system pilot
 operated
 Dedicated load sensing steering pump
 Dedicated brake and fan gear pump

ELECTRICAL

Alarm, back-up/main disconnect switch
 Alternator (145-amp, brush type)
 Batteries (2), maintenance free
 Ignition key; start/stop switch
 Lighting system, halogen (6 total)
 -Four (4) halogen work lights
 -Two (2) halogen road lights
 Starting and charging system (24-volt)
 Starter, electric (heavy duty)
 Rear view camera

OPERATOR ENVIRONMENT

Air conditioning (HVAC) with 10 vents
 and filter unit located outside of cab
 Bucket/work tool function lockout
 Cab, pressurized and sound suppressed
 Hydroformed (ROPS/FOPS) structure
 12V power port (10A)
 Coat hook
 Pilot hydraulic controls, lift and
 tilt function
 Computerized monitoring system
 Gauges:
 -Engine coolant temperatures/fluid level
 -Hydraulic/transmission oil temperature
 -Tachometer
 Digital indicators
 -Gear indicator
 -Speedometer
 -Service meter units
 -Fault codes

Warning indicators:

-Air inlet heater
 -Electrical malfunction
 -Engine inlet manifold temperature
 -Engine oil pressure, fuel level
 -Fuel pressure high/low
 -Hydraulic oil level, parking brake
 -Primary steering oil pressure
 -Service brake oil pressure
 -Action light, engine malfunction
 -Transmission filter bypass
 Heater and defroster
 Horn
 Cup holders and personal tray on
 right console
 Storage tray behind seat
 Mirrors, rearview external
 Seat, Cat Comfort (cloth) suspension
 Seat belt
 Steering column, adjustable angle
 Wipers/washers (front and rear)
 Window, sliding (left and right side)

TIRES, RIMS, AND WHEELS

A tire must be selected from the
 mandatory attachments section
 Tire availability might vary by region
 Base machine price includes an allowance
 for base radial tires.

FLUIDS

Premixed 50% concentration of extended
 life coolant with freeze protection
 to -34C (-29F)

OTHER STANDARD EQUIPMENT

Lift and bucket return-to-dig kick outs
 (Electro-Magnetic), mechanical
 adjustment
 Couplings, Caterpillar O-ring face seal
 Doors, service access (locking)
 Front fender, steel
 Grill, airborne debris
 Hitch, drawbar with pin
 Hood, non-metallic on steel structure,
 wing doors
 Hoses, Caterpillar XT
 Counterweight
 Linkage, Z-Bar, fabricated crosstube/
 tilt lever
 SOS oil sampling valves
 Sight gages :
 -Engine coolant, hydraulic oil
 -Transmission oil level
 Diagnostic pressure taps

CATERPILLAR MACHINE PRICE LIST

950GC

950GC WHEEL LOADER
QINGZHOU, CHINA

Ship Weight
lbs

LIST PRICE
AT DEALER

OTHER STANDARD EQUIPMENT (CONT.)

- Transmission speed clutches
 - Transmission forward and reverse clutches
 - Steering pump load and discharge pressure
 - Brake system accumulator pressure
 - Front and rear brake pressure
- Product Link Ready

CATERPILLAR MACHINE PRICE LIST

950GC

950GC WHEEL LOADER
QINGZHOU, CHINA

Ship Weight
lbs

LIST PRICE
AT DEALER

**Lane 2 is reserved for the Base Order Management program.
Please use Lane 2 when placing orders that are part of the Base Order
Management program.**

CATERPILLAR MACHINE PRICE LIST

950GC

950GC WHEEL LOADER QINGZHOU, CHINA	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------------	--------------------	-------------------------

607-6475	950 GC WHEEL LOADER AM-N DCA7A 0	\$312,130
	LANE 1 - AVAILABLE FROM SAVANNAH & TACOMA DISTRIBUTION CENTER	
	INCLUDES:	
	554-0849 950 GC WHEEL LOADER	
	558-1787 COLD WEATHER PACKAGE, AM-N	
	1S-9937 AIR INLET STANDARD, RAIN CAP	
	390-6000 STEERING SYST, STANDARD	
	391-5315 SEAT BELT, 3", AUTO-ANTI-CINCH	
	392-3809 TOOL BOX	
	469-3139 COUNTERWEIGHT, 3016LBS	
	474-6209 CONVERTER (24V TO 12V/15A)	
	489-0438 SUSPENSION SEAT, AIR	
	489-2727 WARNING BEACON, LED	
	521-7456 HYDRAULICS,2V,W/RIDE CTRL ANSI	
	524-7645 FAN, STANDARD	
	552-4912 QUICK COUPLER CONTROL	
	552-8943 FRAME, MANUAL LUBE, STD OSC	
	553-1403 SINGLE AXIS LEVERS W/FNR	
	554-0884 LIGHTING, STANDARD	
	554-1500 LIGHTS, 9 CONNECTORS	
	557-3555 REGIONAL PKG, AM-N	
	559-4970 LINKAGE, STANDARD, 3V/QC	
	562-3218 ANTIFREEZE, -34C (-29F)	
	562-4197 LIGHTS, WORKING, 4 HALOGEN	
	573-5681 AXLE ARR, (OPEN, OPEN)	
	579-9102 PRODUCT LINK, CELLULAR PL641	
	603-0645 PREMIUM CORP RADIO (12V)	

CATERPILLAR MACHINE PRICE LIST

950GC

950GC WHEEL LOADER QINGZHOU, CHINA	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------------	--------------------	-------------------------

607-6477	950 GC WHEEL LOADER AM-N DCA8A 0	\$319, 940
	LANE 1 - AVAILABLE FROM SAVANNAH & TACOMA DISTRIBUTION CENTER	
	INCLUDES:	
	554-0849 950 GC WHEEL LOADER	
	558-1787 COLD WEATHER PACKAGE, AM-N	
	1S-9937 AIR INLET STANDARD, RAIN CAP	
	390-6000 STEERING SYST, STANDARD	
	391-5315 SEAT BELT, 3", AUTO-ANTI-CINCH	
	392-3809 TOOL BOX	
	469-3139 COUNTERWEIGHT, 3016LBS	
	474-6209 CONVERTER (24V TO 12V/15A)	
	489-0438 SUSPENSION SEAT, AIR	
	489-2727 WARNING BEACON, LED	
	521-7458 HYDRAULICS, 3V RC ANSI	
	524-7645 FAN, STANDARD	
	552-4912 QUICK COUPLER CONTROL	
	552-8943 FRAME, MANUAL LUBE, STD OSC	
	553-1405 SINGLE AXIS LEVER 3 W/FNR	
	554-0884 LIGHTING, STANDARD	
	554-1500 LIGHTS, 9 CONNECTORS	
	557-3555 REGIONAL PKG, AM-N	
	559-4970 LINKAGE, STANDARD, 3V/QC	
	562-3218 ANTIFREEZE, -34C (-29F)	
	562-4197 LIGHTS, WORKING, 4 HALOGEN	
	573-5683 AXLE ARR, (LSD, OPEN)	
	579-9102 PRODUCT LINK, CELLULAR PL641	
	603-0645 PREMIUM CORP RADIO (12V)	

607-6479	950 GC WHEEL LOADER AM-N DCA9A 0	\$322, 620
	LANE 1 - AVAILABLE FROM SAVANNAH & TACOMA DISTRIBUTION CENTER	
	INCLUDES:	
	554-0849 950 GC WHEEL LOADER	
	1S-9937 AIR INLET STANDARD, RAIN CAP	
	390-6000 STEERING SYST, STANDARD	
	391-5315 SEAT BELT, 3", AUTO-ANTI-CINCH	
	392-3809 TOOL BOX	
	469-3139 COUNTERWEIGHT, 3016LBS	
	474-6209 CONVERTER (24V TO 12V/15A)	
	489-0438 SUSPENSION SEAT, AIR	
	489-2727 WARNING BEACON, LED	
	521-7458 HYDRAULICS, 3V RC ANSI	
	524-7645 FAN, STANDARD	
	552-4912 QUICK COUPLER CONTROL	
	552-8943 FRAME, MANUAL LUBE, STD OSC	
	553-1405 SINGLE AXIS LEVER 3 W/FNR	
	554-0884 LIGHTING, STANDARD	
	554-1500 LIGHTS, 9 CONNECTORS	
	557-3555 REGIONAL PKG, AM-N	
	558-1787 COLD WEATHER PACKAGE, AM-N	
	559-4970 LINKAGE, STANDARD, 3V/QC	
	562-3218 ANTIFREEZE, -34C (-29F)	
	562-4197 LIGHTS, WORKING, 4 HALOGEN	
	573-5682 AXLE ARR, (LSD, LSD)	
	579-9102 PRODUCT LINK, CELLULAR PL641	
	603-0645 PREMIUM CORP RADIO (12V)	

CATERPILLAR MACHINE PRICE LIST

950GC

950GC WHEEL LOADER QINGZHOU, CHINA	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------------	--------------------	-------------------------

554-0849 950 GC WHEEL LOADER 0 LANE 2/LANE 3 - AVAILABLE FROM SELECT EPC LOCATIONS FOR AM-N LANE 2/LANE 3 - AVAILABLE FROM ZEEBRUGGE EPC FOR EU LANE 2/LANE 3 - AVAILABLE FROM QINGZHOU FACTORY FOR JAPAN & INDIA INCLUDES: -Engine,Cat C7.1, meets U.S. EPA Tier 4 Final, EU Stage V, and Japan 2014 emission standards. -Cat Clean Emissions Module (CEM) with Diesel Particulate Filter (DPF) remote Diesel Exhaust Fluid (DEF) tank & pump DEF Gauges available in Computerized monitoring system. -EIS Automatic Engine Idle Shutdown		\$300,040
--	--	------------------

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	MANDATORY ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------	-----------------	----------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS

LANE SELECTION

OP-9001	LANE 1 ORDER	0	NC
	Select this option when ordering from the PDC.		

TIRES

L	593-2886	TIRES, 23.5R25 MA MS302 ** L3	0	\$1,040
		Maxam Radial, MS302, tubeless. Self-cleaning tread design provides excellent traction and floatation.		
		ONLY FOR USE WITH: 607-6475 950 GC WHEEL LOADER AM-N DCA7A		
		607-6477 950 GC WHEEL LOADER AM-N DCA8A		
L	593-2900	TIRES, 23.5R25 MA MS202 ** L2	0	\$1,085
		For operation in soft underfoot conditions. Ideal for use in dirt, mud, snow, and ice. Tire features siped block pattern for maximum traction, wear and cut-resistant tread compound and self-cleaning thread with stone ejectors		
		ONLY FOR USE WITH: 607-6479 950 GC WHEEL LOADER AM-N DCA9A		

GENERAL PURPOSE BUCKET GP (PIN-ON)

P	559-9424	BKTA GP GC 115" 4.25YD3 PO	3,593	\$14,778
		Includes Bolt On Cutting Edge GP		

FUSION QUICK COUPLER

P	310-9391	QUICK COUPLER, FUSION	1,090	\$7,625
---	----------	---------------------------------	-------	---------

GENERAL PURPOSE BUCKET GP (FUSION)

P	559-9421	BKTA GP ST 115" 4.00YD3 FUS	3,810	\$17,306
		Includes Bolt On Cutting Edge GP		
		REQUIRES: 310-9391 QUICK COUPLER, FUSION		

CONSTRUCTION FORK TINE (FUSION)

P	520-7979	TINE GROUP, 72"	1,288	\$7,625 NI
		Lane 1 Work Tool - Ships loose from Caterpillar Work Tools & Services		
		INCLUDES: Right and Left offset tines.		
		TINE WIDTH: 7" (180mm)		
		TINE THICKNESS: 3.5" (90mm)		

CONSTRUCTION FORK CARRIAGE (FUSION)

P	520-7957	CARRIAGE GROUP, 96"	1,761	\$9,000 NI
		96"(2438mm) carriage		
		REQUIRES: 349-5246 QUICK COUPLER, FUSION and		
		520-7979 TINE GROUP, 72"		

OMISSION WORK TOOL

P	553-7758	OMISSION WORKTOOL	0	NC
		This is required when ordering a machine without an installed Bucket OR Quick Coupler to protect the links.		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	MANDATORY ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------	-----------------	----------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

PACKING

0P-4834	ROLL ON-ROLL OFF 0	\$97 NET
	Machine is in mobile condition and all attachments are installed unless specified.	

INSTRUCTIONS

421-8926	SERIALIZED TECHNICAL MEDIA KIT 0	NC
	Kit will include instructions and parts CD or parts book in the legally required language, based on shipping address. Any additional media such as a paper parts manual, not included in the kit, can be ordered through the media website.	

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 1 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

LANE 1 AM-NORTH OPTIONAL ATTACHMENTS

FLUIDS

0P-2407	ANTIFREEZE, -50C (-58F)	0		\$318 NET
	Extended life coolant			

PDC MACHINE PREP

618-9807	STANDARD DEALER PREP & PDI.	0		\$780 NET
	INCLUDES:			
	-Post-production quality inspection, pre-delivery inspection & testing			
	-Road test (heat cycle)			
	-All fluids topped off (including diesel, def & windshield fluid)			
	-Grease Unit			
	-Update/Flash software			
	-Removing shipment packing protection and wash unit			
	-Apply up to 4 "dealer" decals			
	-Documents scanned to dealer: Vision Link SN, Product Status Report, Cat Inspect PDI report			

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

0P-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
0P-9003	LANE 3 ORDER	0	NC

REGIONAL PACKAGES

To configure a machine, you must select a Regional Package that applies to your region.

L	557-3555	REGIONAL PKG, AM-N	0	NC
		INCLUDES: -Brake pedal, standard -ANSI decals -Ambient temperature capability up to 47C (117F)		

FEATURE PACKAGES

L	558-1785	STANDARD PACKAGE	0	NC
L	558-1787	COLD WEATHER PACKAGE, AM-N	0	\$1,185
		INCLUDES : -Ether starting aid -Jacket water heater 120V -Bypass Valve		

BOOMS, STICKS, AND LINKAGES

LINKAGE ARRANGEMENTS

L	387-5780	LINKAGE, STANDARD	0	NC
L	559-4970	LINKAGE, STANDARD, 3V/QC	0	\$600
		Linkage with hardware installed for the installation of Quick Coupler lines and/or third function front lines.		

NOTE: Does not include Quick Coupler lines/hydraulics or Third Function lines/hydraulics.

L	559-4973	LINKAGE, STANDARD, AL/3V/QC	0	\$835
		Linkage for the installation of Caterpillar Autolube system, 3V and/or QC.		

NOTE: Does not include Autolube system/lines, Quick Coupler lines/hydraulics or Third Function lines/hydraulics.

FRAME ARRANGEMENT

L	552-8943	FRAME, MANUAL LUBE, STD OSC	0	NC
		Includes manual greasing fittings of pin joints Includes standard oscillation for L3 Tire		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

BOOMS, STICKS, AND LINKAGES (CONT.)

FRAME ARRANGEMENT (Cont.)

L	540-7020	FRAME, AUTO LUBE, STD OSC 0 Includes manual greasing fittings of pin joints, and additional hardware for auto lubrication installation Includes Standard oscillation for L3 Tire NOTE: Does not include Autolube system/lines ONLY FOR USE WITH: 559-4973 LINKAGE, STANDARD, AL/3V/QC		NC
L	551-4658	FRAME, MAN LUBE, REDUCED OSC 0 Includes manual greasing fittings of pin joints Includes reduced oscillation for L5 Tire		NC
L	551-4659	FRAME, AUTO LUBE, REDUCED OSC 0 Includes manual greasing fittings of pin joints, and additional hardware for auto lubrication installation Includes reduced oscillation for L5 Tire NOTE: Does not include Autolube system/lines ONLY FOR USE WITH: 559-4973 LINKAGE, STANDARD, AL/3V/QC		NC

COUNTERWEIGHT

L	469-3139	COUNTERWEIGHT, 3016LBS 0 Includes DEF tank box.		NC
---	----------	---	--	----

POWERTRAIN

Axle packages include a combination of traction aids (open front and rear differentials or limited slip front and/or rear differentials).

NOTE: LSD - Limited Slip Differentials

Limited slip differentials should only be ordered if application and ground condition require them.
 Limited slip differentials will increase fuel consumption and tire wear/dragging if used on firm ground.
 Limited slip differentials will decrease machine maneuverability on good ground conditions.

L	573-5681	AXLE ARR, (OPEN, OPEN) 0 INCLUDES: -Open front differential -Open rear differential Recommended for mainly firm/dry ground condition like yard application truck loading and Load-and-Carry with good ground condition. Lowest fuel consumption.		NC
L	573-5682	AXLE ARR, (LSD, LSD) 0 INCLUDES: -Limited slip front differential -Limited slip rear differential Recommended for very adverse wet and loose ground condition and applications like snow removal and dozing (overburden removal). Will reduce operator comfort and increase fuel consumption.		\$5,010

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

POWERTRAIN (CONT.)

L	573-5683	AXLE ARR, (LSD, OPEN) 0 INCLUDES: -Limited slip front differential -Open rear differential Recommended for wet/loose ground condition like Load-and-Carry in wet conditions, uphill with empty bucket and stockpiling in material. Will reduce operator comfort and increase fuel consumption.		\$2,325
---	----------	--	--	---------

AIR INLETS, ENGINE

L	1S-9937	AIR INLET STANDARD, RAIN CAP 0 Engine air inlet to be used in moderate dust and airborne debris environments.		NC
L	481-1016	AIR INLET PRECLEANER, SNOW RMV 0 Provides a rubber baffle to reduce snow pack around the primary filter		\$431
L	130-3280	PRECLEANER. 0 Turbine engine air inlet precleaner, to be used in high dust and airborne debris environments.		\$840

HYDRAULICS

Must select either 2V or 3V Hydraulic arrangement. Selection will limit optional attachments compatible to your machine order.

NOTE: Ride control provides the operator with a smoother ride over rough terrain, enabling a more comfortable ride at higher speeds. The benefit is reduced cycle times, higher productivity and better fuel efficiency while performing Load-and-Carry applications. The system works by using an accumulator to dampen the linkage motion, acting as a shock absorber.

L	390-5913	HYDRAULICS, 2V, W/O RIDE CTRL 0 INCLUDES: -2 valve hydraulic system for implement lift and tilt -No ride control		NC
L	521-7456	HYDRAULICS, 2V, W/RIDE CTRL ANSI 0 INCLUDES: -2 valve hydraulic system for implement lift and tilt -Ride control ONLY FOR USE WITH: 557-3555 REGIONAL PKG, AM-N		\$3,945
L	397-9895	HYDRAULICS, 3V, W/O RIDE CTRL 0 INCLUDES: -3 valve hydraulic system -No ride control ONLY FOR USE WITH: 559-4970 LINKAGE, STANDARD, 3V/QC 559-4973 LINKAGE, STANDARD, AL/3V/QC		\$4,895
L	521-7458	HYDRAULICS, 3V RC ANSI 0 INCLUDES: -3 valve hydraulic system -Ride control ONLY FOR USE WITH: 387-5940 LINKAGE, STANDARD, 3V/QC 557-3555 REGIONAL PKG, AM-N 559-4973 LINKAGE, STANDARD, AL/3V/QC		\$8,830

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

ELECTRICAL

LIGHTS ROADING

L	554-0884	LIGHTING, STANDARD 0 Provides high beam/low beam lamps, front and rear turn signals, side marker lights, and reflective side markers for roading applications.		NC
---	----------	--	--	----

WORKING LIGHTS WIRING GP

L	554-1499	LIGHTS, 5 CONNECTORS 0 Includes 4 connectors for working lights and 1 connector for beacon		NC
L	554-1500	LIGHTS, 9 CONNECTORS 0 Includes 8 connectors for working lights and 1 connector for beacon		\$122

LIGHTS WORKING

L	562-4197	LIGHTS, WORKING, 4 HALOGEN 0 4 halogen working lights, cab mounted (2 facing forward / 2 facing rearward)		NC
L	562-4198	LIGHTS, WORKING, 4 LED 0 4 LED working lights, cab mounted (2 facing forward / 2 facing rearward)		\$640
L	559-1957	LIGHTS, WORKING, 8 LED 0 8 LED working lights, cab mounted (4 facing forward / 4 facing rearward) ONLY FOR USE WITH: 554-1500 LIGHTS, 9 CONNECTORS		\$1,365

OPERATOR ENVIRONMENT

IMPLEMENT CONTROLS

L	553-1403	SINGLE AXIS LEVERS W/FNR 0 Implement lift and tilt controls with two single axis levers, pilot controlled. ONLY FOR USE WITH: 390-5913 HYDRAULICS, 2V, W/O RIDE CTRL 521-7456 HYDRAULICS,2V,W/RIDE CTRL ANSI 521-7457 HYDRAULICS,2V,W/RIDE CTRL ISO		NC
L	553-1404	JOYSTICK W/FNR 0 Implement lift and tilt controls with one joystick, pilot controlled. Integrates a horn button and FNR switch. ONLY FOR USE WITH: 390-5913 HYDRAULICS, 2V, W/O RIDE CTRL 521-7456 HYDRAULICS,2V,W/RIDE CTRL ANSI 521-7457 HYDRAULICS,2V,W/RIDE CTRL ISO		NC
L	553-1405	SINGLE AXIS LEVER 3 W/FNR 0 Implement lift, tilt and third function controls with three single axis levers, pilot controlled. ONLY FOR USE WITH: 397-9895 HYDRAULICS, 3V, W/O RIDE CTRL 521-7458 HYDRAULICS, 3V RC ANSI 521-7459 HYDRAULICS,3V,W/RIDE CTRL ISO		\$600
L	553-1406	JOYSTICK W/FNR & ONE SAL 0 Implement lift and tilt controls with one joystick, third function with one single axis lever on the right hand side, all pilot controlled. ONLY FOR USE WITH: 397-9895 HYDRAULICS, 3V, W/O RIDE CTRL 521-7458 HYDRAULICS, 3V RC ANSI 521-7459 HYDRAULICS,3V,W/RIDE CTRL ISO		\$600

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

OPERATOR SEAT

L	489-0437	SUSPENSION SEAT, MECHANICAL 0 Seat with spring-mechanical suspension, height adjustable, fore-aft, armrest, back and head rest adjustments. Fabric cushions.		NC
L	489-0438	SUSPENSION SEAT, AIR 0 Seat with air suspension, height adjustable, fore-aft, armrest, back and head rest adjustments. Fabric cushions.		\$600

SEAT BELTS

L	391-5315	SEAT BELT, 3", AUTO-ANTI-CINCH 0 Auto tightening and anti-cinch 75 mm (3 inch) wide seat belt. It can provide max 5 cm(2 inch) free space to let operator reach.		NC
---	----------	--	--	----

RADIOS

L	603-0648	RADIO, AM/FM/BLUETOOTH READY 0 Includes AM/FM Antenna, Speakers, External Microphone for a future entertainment radio installation.		NC
L	603-0645	PREMIUM CORP RADIO (12V) 0 Premium 12V AM/FM radio with Bluetooth technology, USB port, and 3.5 mm AUX input. Availability varies by country.		\$585

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Cat marketing representative with questions.

L	579-9102	PRODUCT LINK, CELLULAR PL641 0 Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		NC
L	474-6206	PRODUCT LINK, SATELLITE PL631 0 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		NC

SAFETY AND SECURITY

STEERING

L	390-6000	STEERING SYST, STANDARD 0 Standard steering wheel (HMU).		NC
---	----------	--	--	----

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

SAFETY AND SECURITY (CONT.)

STEERING (Cont.)

L	390-5985	STEERING SYST, SECONDARY 0 Standard steering wheel (HMU) with electric secondary steering pump. Includes test switch and warning indicator in cab.		\$3,445
---	----------	--	--	---------

COOLING

FAN HYDRAULIC - COOLER

L	524-7645	FAN, STANDARD 0		NC
L	554-3399	FAN, REVERSING , ANSI 0 Provides reversing function to the standard hydraulically driven demand fan. This provides the ability to reverse the airflow direction to remove debris from the radiator and engine enclosures while the machine is still operating. Includes automatic and manual controls for airflow reversal. Recommended for applications with a high content of airborne debris. ONLY FOR USE WITH: 557-3555 REGIONAL PKG, AM-N		\$830

COOLANT

L	562-3218	ANTIFREEZE, -34C (-29F) 0 Suitable for most climates, prevents engine coolant from freezing to -34C (-29F).		NC
L	562-3219	ANTIFREEZE, -50C (-58F) 0 Suitable for extremely cold climates, prevents engine coolant from freezing to -50C (-58F).		\$318 NET

TIRES, RIMS, AND WHEELS

Includes rims, and come in a set of 4.

TIRES AVAILABLE FROM MAXAM

L	593-2886	TIRES, 23.5R25 MA MS302 ** L3 0 Maxam Radial, MS302, tubeless. Self-cleaning tread design provides excellent traction and floatation. ONLY FOR USE WITH: 552-8943 FRAME, MANUAL LUBE, STD OSC 540-7020 FRAME, AUTO LUBE, STD OSC		\$1,040
L	593-2900	TIRES, 23.5R25 MA MS202 ** L2 0 For operation in soft underfoot conditions. Ideal for use in dirt, mud, snow, and ice. Tire features siped block pattern for maximum traction, wear and cut-resistant tread compound and self-cleaning thread with stone ejectors ONLY FOR USE WITH: 552-8943 FRAME, MANUAL LUBE, STD OSC 540-7020 FRAME, AUTO LUBE, STD OSC		\$1,085

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS (CONT.)

TIRES AVAILABLE FROM MAXAM (Cont.)

L	593-2890	TIRES, 23.5R25 MA MS203 ** L2 0 MAXAM RADIAL; TREAD DEPTH=32.5mm; Rim=19.5"x25" 3 piece, Provides reduced vibration, damage resistance, and traction in soft to rocky underfoot conditions. ONLY FOR USE WITH: 552-8943 FRAME, MANUAL LUBE, STD OSC 540-7020 FRAME, AUTO LUBE, STD OSC		\$-177
L	593-2892	TIRES, MA 23.5R25 MS503 ** L5 0 Extra deep, open lug L5T traction pattern combines excellent traction and high resistance to wear and cutting, specifically designed to maximize service life in the harshest application. ONLY FOR USE WITH: 551-4658 FRAME, MAN LUBE, REDUCED OSC 551-4659 FRAME, AUTO LUBE, REDUCED OSC		\$12,680

TIRES AVAILABLE FROM BRIDGESTONE

L	608-5676	TIRES, 23.5R25 BS VUT * L2 0 Bridgestone radial, tubeless, Non-directional pattern VUT features superior traction and excellent self-cleaning, lighter weight provides superior maneuverability. ONLY FOR USE WITH: 552-8943 FRAME, MANUAL LUBE, STD OSC 540-7020 FRAME, AUTO LUBE, STD OSC		\$530
L	593-2884	TIRES, 23.5R25 BS VJT * L3 0 Bridgestone radial, tubeless, the V-STEEL J-TRACTION features advanced non-directional tread pattern, low-vibration characteristics enhance riding comfort and extra-tough for more lasting reliability. ONLY FOR USE WITH: 552-8943 FRAME, MANUAL LUBE, STD OSC 540-7020 FRAME, AUTO LUBE, STD OSC		\$7,230
L	593-2895	TIRE, 23.5R25 BS VSDT*L5 0 The V-STEEL DEEP TRACTION radial tire offers extra-heavy duty loader performance with excellent traction, cut resistance and long tread life. Equal load distribution, and even contact for rider comfort. ONLY FOR USE WITH: 551-4658 FRAME, MAN LUBE, REDUCED OSC 551-4659 FRAME, AUTO LUBE, REDUCED OSC		\$18,590

OTHER ATTACHMENTS

TOOL BOX

L	392-3725	NO TOOLBOX 0		NC
L	392-3809	TOOL BOX 0 Provides a lockable toolbox located under the battery box on the left hand side of the machine.		\$356

QUICK COUPLERS

CIRCUIT ACTUATION QC - NO COUPLER

P	471-0569	NO QUICK COUPLER READY 0		NC
---	----------	--------------------------------	--	----

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

QUICK COUPLERS (CONT.)

CIRCUIT ACTUATION QC - NO COUPLER (Cont.)

P	552-4912	QUICK COUPLER CONTROL. 0		\$3,165
		Includes all hydraulic lines, vertical wedge activation switch and dual level kick-out sensors (Bucket and Fork) with selection switch in the cab.		
		ONLY FOR USE WITH: 559-4970 LINKAGE, STANDARD, 3V/QC 559-4973 LINKAGE, STANDARD, AL/3V/QC		

WORK TOOLS

AVAILABILITY FOR BUCKETS

NOTE: "GET" is NOT automatically included on bucket orders. GET must be entered on the order with your bucket selection, unless text for bucket states otherwise. Please make the "GET" selection from "GET" listed immediately following the bucket listing.

NOTE: Recommend use of bolt-on adapter option, adapter and segment option, or bolt-on cutting edge option for General Purpose Buckets and Material Handling Buckets.

NOTE: Material density will determine the appropriate capacity bucket. Refer to the Specalog. Exceeding maximum payload may cause loader instability.

GC-TYPE GENERAL PURPOSE BUCKETS

P	559-9419	BKTA GP GC 115" 4.00YD3 PO 3,505		\$14,625
		PERFORMANCE SERIES BUCKET 950 GC dedicated bucket CAPACITIES: Rated: 2.9 M3 (3.75 YD3) bare or without bolt-on edges or segments Rated: 3.1 M3 (4.00 YD3) with bolt-on edges or adapters/teeth&segments 110%: 3.4 M3 (4.50 YD3) with bolt-on edges or adapters/teeth&segments		
P	559-9424	BKTA GP GC 115" 4.25YD3 PO 3,593		\$14,778
		PERFORMANCE SERIES BUCKET 950 GC dedicated bucket CAPACITIES: Rated: 3.1 M3 (4.00 YD3) bare or without bolt-on edges or segments Rated: 3.3 M3 (4.25 YD3) with bolt-on edges or adapters/teeth&segments 110%: 3.6 M3 (4.75 YD3) with bolt-on edges or adapters/teeth&segments		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

WORK TOOLS (CONT.)

OMISSION WORKTOOL

P	553-7758	OMISSION WORKTOOL 0		NC
		This is required when ordering a machine without an installed Bucket OR Quick Coupler to protect the links.		

Note: If using a worktool that is not listed on the machine pricelist please contact your local Product Application Specialist for approval before placing order
 CANNOT BE USED WITH: TURKEY DEALERS

FUSION QUICK COUPLER

P	310-9391	QUICK COUPLER, FUSION 1,090		\$7,625
		REQUIRES: 552-4912 QUICK COUPLER CONTROL		
P	617-6371	QUICK COUPLER, FUSION 1,090		\$7,625
		FOR USE IN LANE 3 ONLY REQUIRES: 552-4912 QUICK COUPLER CONTROL		

BUCKETS FOR FUSION QUICK COUPLER

P	559-9421	BKTA GP ST 115" 4.00YD3 FUS 3,810		\$17,306
		PERFORMANCE SERIES BUCKET CAPACITIES: Rated: 2.9 M3 (3.75 YD3) bare or without bolt-on edges or segments Rated: 3.1 M3 (4.00 YD3) with bolt-on edges or adapters/teeth&segments 110%: 3.4 M3 (4.50 YD3) with bolt-on edges or adapters/teeth&segments REQUIRES: 310-9391 QUICK COUPLER, FUSION 617-6367 QUICK COUPLER, FUSION 617-6371 QUICK COUPLER, FUSION		

INSTRUCTIONS

OPERATION AND MAINTENANCE MANUAL

	421-8926	SERIALIZED TECHNICAL MEDIA KIT 0		NC
		Kit will include instructions and parts CD or parts book in the legally required language, based on shipping address. Any additional media such as a paper parts manual, not included in the kit, can be ordered through the media website. https://oos.midlandcorp.com/CAT/Default.aspx		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

POWERTRAIN

SPEED LIMITER.

P	525-0144	SPEED LIMITER (20 KPH) 0 Controls the engine rpm to keep the ground speed at 20km/hour max.		\$665
---	----------	--	--	-------

ELECTRICAL

BEACON

P	489-2727	WARNING BEACON, LED 0 Provides a rotating warning beacon, flip down.		\$455
---	----------	---	--	-------

OPERATOR ENVIRONMENT

SUN VISOR

P	391-5330	SUN VISOR, REAR 0 Rear window pull down sun visor similar to the sun visor on front windshield.		\$122
---	----------	--	--	-------

CONVERTER-POWER

P	474-6209	CONVERTER (24V TO 12V/15A) 0 Provides a 24V to 12V converter (15A). No extra mounting provisions included, can be used to power a CB Radio.		\$1,075
---	----------	--	--	---------

TECHNOLOGY PRODUCTS

CAT PAYLOAD - WEIGHING SYSTEM

NOTE: Refer to KITS-MWL pricelist to order dealer installed kit for 950 GC for 950 GC CAT PAYLOAD.
 Installation and calibration instructions available on SIS with the machine serial number prefix or prefix C55.

GUARDS

FENDERS

P	415-7735	FENDER, EXTENSIONS, STEEL 0 Short rear fender extensions covering top of wheel. Attached to the swing up service door.		\$344
---	----------	---	--	-------

P	432-7325	FENDER, ROADING, NON-METALLIC 0 Roading fenders arrangement includes fender extensions on front fenders and full wrap non-metallic fenders for rear wheels. Rear fenders are attached to the swing up service door.		\$1,025
---	----------	--	--	---------

CAB GUARD

L	538-8879	GUARD, WINDSHIELD 0 Protects front of cab		\$3,320
---	----------	--	--	---------

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

GUARDS (CONT.)

TRANSMISSION GUARD

L	540-0571	GUARD, POWERTRAIN 0		\$1,475
		Protects bottom of transmission		

OTHER ATTACHMENTS

GREASING ARRANGEMENTS

L	555-4665	AUTOLUBE 0		\$6,630
		Provides Caterpillar Autolube system. Greases pin joints requiring daily lubrication: linkage pins joints including bucket pins, articulation hitch, steering cylinders and rear axle trunnions. ONLY FOR USE WITH: 559-4973 LINKAGE, STANDARD, AL/3V/QC AND 540-7020 FRAME, AUTO LUBE, STD OSC OR 551-4659 FRAME, AUTO LUBE, REDUCED OSC		

PACKING

PACKING FOR MACHINE

	OP-4834	ROLL ON-ROLL OFF 0		\$97 NET
		Machine is in mobile condition and all attachments are installed unless specified.		

PREPARATION ADDITIONAL

	OG-4129	STORAGE PROTECTION 0		\$461 NET
		Machines have been sprayed with Fluid Film TM, see your account rep for details. This product is added for corrosion protection while shipping and for extended storage periods. This product will need to be power washed with soapy water prior to shipment to the customer. Touch-up can not be done without removing it.		
	618-9807	STANDARD DEALER PREP & PDI 0		\$780 NET
		INCLUDES: -Post-production quality inspection, pre-delivery inspection & testing -Road test (heat cycle) -All fluids topped off (including diesel, def & windshield fluid) -Grease Unit -Update/Flash software -Removing shipment packing protection and wash unit -Apply up to 4 "dealer" decals -Documents scanned to dealer: Vision Link SN, Product Status Report, Cat Inspect PDI report		