

CATERPILLAR MACHINE PRICE LIST

962M-BR

962M WHEEL LOADER
 PIRACICABA, BRAZIL

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

Engine, Cat C7.1 ACERT
 Torque converter, with lock-up clutch
 free wheel stator
 Transmission countershaft, automatic,
 powershift (5F/3R)
 Pump transmission, split flow
 Productive Economy Mode (fuel
 consumption optimization)
 Brakes, full hydraulic enclosed wet-disc
 with Integrated Braking System (IBS)
 Brake wear indicators
 Fan drive hydraulic, electronically
 controlled, temperature sensing,
 on demand
 Fuel priming pump (electric)
 Fuel/Water separator
 Engine air intake with strata-tubes
 Parking Brake, disk & caliper

compartment for cell phone/MP3 player
 Coat hooks (2)
 Sliding Window
 Ergonomic Cab access
 Sun visor, front
 Computerized monitoring system
 Front dash information display with :
 -Speedometer/Tachometer
 -Digital gear indicator
 -Temperatures: engine coolant,
 hydraulic oil, transmission oil
 -Fuel level
 Warning Indicators:
 -Temperatures: axle oil, engine intake
 manifold
 -Pressures: engine oil, fuel pressure
 Hi/Low, primary steering oil,
 service brake oil
 -Battery voltage Hi/Low
 -Engine air filter restriction
 -Hydraulic oil filter restriction
 -Hydraulic oil level low
 -Parking brake
 -Transmission filter bypass
 Multi-function monitor:
 -180mm(7") color LCD touch-screen
 display
 -Rear-view camera image display
 (reverse travel activated)
 Machine utilization information :
 -Total fuel consumption
 -Average fuel burn rate
 -Engine fuel consumption
 -Total idle time
 -Total operating hours
 -Travel distance (odometer)
 -Total idle fuel
 -Total operating hours, neutral
 -Total operating hours with hydraulic
 filter in bypass

HYDRAULICS

Load sensing system with variable
 displacement piston pump.
 Hoses, Caterpillar XT
 Couplings, Caterpillar O-ring face seal
 Hydraulic oil cooler (swing out)
 Oil sampling valves
 Remote diagnostic pressure taps
 Hydraulic Service Center

ELECTRICAL

Batteries (2), maintenance free 1400CCA
 Starting and charging system (24V)
 Alarm, back-up
 Ignition key; start/stop switch
 Main disconnect switch
 Receptacle remote start w/o cables
 Starter, electric, heavy duty
 Emergency shut-off switch
 Rear camera
 Electrical Service Center

OPERATOR ENVIRONMENT

A-Post mounted membrane 16 switch keypad
 Climate Control
 Bucket/Work tool function lockout
 EH Parking Brake
 Intermittent front wiper control
 Horn, electric
 Lights, cab dome (2)
 Radio ready (entertainment) includes
 antenna, speaker & converters (12V-
 10amp)
 3 receptacles, 12V
 Beverage holders (2) with storage

OTHER STANDARD EQUIPMENT

Engine idle management system and auto
 idle shutdown
 Filters: fuel, engine air, engine oil,
 hydraulic oil, transmission
 Hitch, drawbar
 Kickout, lift & tilt, automatic
 (adjustable)
 Sight gauges: engine coolant, hydraulic
 oil, and transmission oil level
 Lift and tie down points
 Articulation locking bar
 Parallel Z-bar lifting

CATERPILLAR MACHINE PRICE LIST

962M-BR

962M WHEEL LOADER PIRACICABA, BRAZIL	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

**Lane 2 is reserved for the Base Order Management Program.
Please use Lane 2 when placing orders that are part of the Base Order
Management Program.**

464-2610	962M WHEEL LOADER 0	\$326,130
	LANE 2 - AVAILABLE FROM PIRACICABA FACTORY	
	LANE 3 - AVAILABLE FROM PIRACICABA FACTORY	

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER	0	NC

REGIONAL PACKAGES

L	543-3587	REGIONAL PACKAGE, AM-N	0	NC
		INCLUDES: -ANSI films Meets U.S. EPA Tier 4 Final emission standards		

SPECIAL ARRANGEMENTS

L	513-5389	STANDARD PKG W/AUTODIG & CPM	0	\$233
		Provides machine features required in standard and forestry applications. INCLUDES: -Platform -Cab air filter -CPM Payload Ready & Autodig Ready Includes hardware and 250 hour CPM demo mode only. Demo mode is dealer activated. System must be calibrated prior to use. Requires purchase of software for permanent feature activation. See the Optional Technology section for software options.		
L	513-5390	LOGGER PACKAGE	0	NC
		FOR USE IN LANE 3 ONLY Provides machine features required in forestry applications. INCLUDES: -Platform -Cab air filter REQUIRES: 538-2781 LINKAGE, LOGGER 393-0078 COUNTERWEIGHT, HL & LOGGER		

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------------	--------------------	-------------------------

SPECIAL ARRANGEMENTS (CONT.)

L	513-5391	<p>INDUSTRIAL PACKAGE 0</p> <p>FOR USE IN LANE 3 ONLY Provides machine features required in waste transfer stations, recycling stations, green waste and scrap applications. INCLUDES: -Reinforced platform -Carbon cab air filter -Guards: hitch, bottom cab (skirt), front frame, crankcase -Lift cylinder baffles -Heavy duty ladder RECOMMENDED: 505-1521 FILTRATION AR, STEEL, OR 505-1522 FILTRATION AR, STEEL CLNR AUX 493-9616 WINDOWS, FLAT, RUBBER MOUNTED, OR 493-9617 WINDOWS, FLAT, RUBBER MOUNTED GRD 485-4387 GUARDS, LIGHT REQUIRES: 366-9906 or 366-9910 AXLES 478-8371 FENDERS, NARROW or 488-1138 SOUND SUPPRESSION, INDUSTRIAL (EUR) or 465-6590 SOUND SUPPRESSION, LOW (NACD) and 399-4332 GUARD, HINGED, POWERTRAIN or 360-8835 GUARD, TILT CYLINDER</p>	0	\$10,330
---	----------	---	---	-----------------

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

SPECIAL ARRANGEMENTS (CONT.)

L	543-3606	<p>CORROSION RESISTANT PACKAGE 0</p> <p>FOR USE IN LANE 3 ONLY Minimizes the harmful effect in highly corrosive environments applications such as fertilizer handling, salt and its derivatives.</p> <p>INCLUDES: -Platform; -Electrical & Hydraulic installation; -Cab air filter; -Heavy duty alternator; -Heavy duty switch disconnect; -Silicon protection is applied on all the electric terminals, exposed connectors are treated with tube heat shrinkable; -Anticorrosion vapor capsules in closed compartments;</p> <p>REQUIRES: 365-0120 PRECLEANER, TURBINE 477-1660 WINDOW AR, CAB - CORROSION, OR 477-1659 WINDOW AR, RM - CORROSION</p> <p>RECOMMENDED: 524-1394 COOLING GP (6FPI) - CORROSION, OR 524-1393 COOLING GP (9FPI) - CORROSION - Cores protected - Grease points on the radiator hinges 477-1667 HOOD AR - CORROSION 521-9198 PAINTING GROUP, CORROSION (NACD) OR 522-5231 PAINTING GROUP, CORROSION (EU) - Differentiated Painting Process - Extra Varnish protection is applied on the engine compartment, chassis internal 506-0545 PROTECTION PACKAGE, LINES Hose couplings treated with tube heat shrinkable and sealant silicone. 513-5392 FAN, VPF, ISO, OR 513-5393 FAN, VPF, ANSI 538-2791 AUTOLUBE 505-1520 FILTRATION, STD, PRECLEANER</p>	0	\$6,500
---	----------	---	---	---------

BOOMS, STICKS, AND LINKAGES

LINKAGES

L	538-2779	LINKAGE, STANDARD LIFT 0	0	NC
L	538-2780	<p>LINKAGE, HIGH LIFT 0</p> <p>FOR USE IN LANE 3 ONLY Provides increased dump clearance of 11" (288mm) over standard lift arms.</p>	0	\$6,810
L	538-2781	<p>LINKAGE, LOGGER 0</p> <p>FOR USE IN LANE 3 ONLY ONLY FOR USE WITH: STANDARD PACKAGE LOGGER PACKAGE (AM-N)</p>	0	\$6,970

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

BOOMS, STICKS, AND LINKAGES (CONT.)

COUNTERWEIGHT

L	393-0075	COUNTERWEIGHT, STANDARD LIFT	0	NC
L	393-0078	COUNTERWEIGHT, HL & LOGGER FOR USE IN LANE 3 ONLY Provide 2381KG.	0	\$3,190
L	455-7847	COUNTERWEIGHT, AGGREGATE Provide 2381KG. Requires to conform to the CAT Wheel Loader Payload Policy. Provide 1600 Kg counterweight to use exclusively in aggregate rehandling applications.	0	\$3,190

NOTE: The Aggregate counterweight requires L3 and L4 tires, and buckets with Bolt on cutting edge only. It is recommended to use Caterpillar production measure application with aggregate counterweights to ensure compliance with Medium Wheel Loader Payload policy.

POWERTRAIN

ENGINE PRECLEANER

L	365-0121	AIR INLET PRECLEANER, TRASH FOR USE IN LANE 3 ONLY Turbine engine air inlet precleaner, to be used in extremely high dust and airborne debris environments with a grill protecting precleaner from large debris.	0	\$965
L	365-0112	AIR INLET STANDARD, RAIN CAP Includes standard strata tubes precleaner ejecting up to 96% of debris.	0	NC
L	365-0120	AIR INLET PRECLEANER, TURBINE Turbine engine air inlet precleaner, to be used in extremely high dust and airborne debris environments.	0	\$735

AXLE PACKAGES

Axle packages include a combination of traction aids, Ecology Drain (ED), Seal Guards (SG), and Axle Oil Cooler (AOC).

L	366-9903	AXLES, LOCK/OPEN, ED INCLUDES: -Manual front diff lock -Open rear differential -Ecology Drain CANNOT BE USED WITH: 505-1506 INDUSTRIAL PACKAGE	0	\$590
L	366-9905	AXLES, LOCK/OPEN, ED, ETS FOR USE IN LANE 3 ONLY Axles package includes : - Manual front diff lock - Open rear differential - Ecology drain - Extreme (Arctic) Temperature Seals CANNOT BE USED WITH: 505-1506 INDUSTRIAL PACKAGE	0	\$1,540

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

POWERTRAIN (CONT.)

AXLE PACKAGES (Cont.)

L	366-9906	AXLES, LOCK/OPEN, ED, SG 0 FOR USE IN LANE 3 ONLY INCLUDES: -Manual front diff lock -Open rear differential -Ecology Drain -Seal Guards		\$2,150
L	366-9910	AXLES, AUTO DIFF F/R, ED, SG 0 FOR USE IN LANE 3 ONLY INCLUDES : -Automatic front and rear diff lock -Ecology Drain -Seal Guards		\$8,000
L	366-9907	AXLES, LOCK/OPEN, ED, AOC 0 FOR USE IN LANE 3 ONLY INCLUDES: -Manual front diff lock -Open rear differential -Ecology Drain -Axle Oil Coolers Provides installed oil cooler system for front & rear axles Recommended for machines operating in high energy applications, such as extended load & carry. CANNOT BE USED WITH: 505-1506 INDUSTRIAL PACKAGE		\$7,240
L	366-9908	AXLES, AUTO DIFF F/R, ED 0 INCLUDES: -Automatic front and rear diff lock -Ecology Drain CANNOT BE USED WITH: 505-1506 INDUSTRIAL PACKAGE		\$6,440
L	366-9909	AXLES, AUTO DIFF F/R, ED, ETS 0 FOR USE IN LANE 3 ONLY INCLUDES : -Automatic front and rear diff lock -Ecology Drain -Extreme Temp Seals CANNOT BE USED WITH: 505-1506 INDUSTRIAL PACKAGE		\$7,390
L	366-9911	AXLES, AUTO DIFF F/R, ED, AOC 0 INCLUDES: -Automatic front and rear diff lock -Ecology Drain -Axle Oil Coolers Provides installed oil cooler system for front & rear axles Recommended for machines operating in high energy applications, such as extended load & carry. CANNOT BE USED WITH: 505-1506 INDUSTRIAL PACKAGE		\$13,090

HYDRAULICS

L	500-2565	HYDRAULICS, 2V RC (3V READY) 0 Provides 2 valve hydraulics (3V ready) and ride control.		\$4,945
L	501-0400	HYDRAULICS, 2V RC, STD/LOG/HL 0 Provides 2 valve hydraulics and ride control.		\$4,650

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

HYDRAULICS (CONT.)

. (Cont.)

L	500-2568	HYDRAULICS, 3V RC, STD/LOGGER 0 Provides 3 valve hydraulics and ride control. ONLY FOR USE WITH: 506-3486 LINKAGE, STANDARD LIFT 506-3488 LINKAGE, LOGGER		\$10,420
L	500-2570	HYDRAULICS, 3V RC, HIGH LIFT 0 FOR USE IN LANE 3 ONLY Provides 3 valve hydraulics and ride control.		\$10,420
L	500-2569	HYDRAULICS, 4V RC, STD/LOGGER 0 FOR USE IN LANE 3 ONLY Provides 4 valve hydraulics and ride control.		\$13,790
L	500-2571	HYDRAULICS, 4V RC, HIGH LIFT 0 FOR USE IN LANE 3 ONLY		\$13,790

HYDRAULIC OIL

L	366-9912	HYDRAULIC OIL, STANDARD 0 Cat HYDO Advanced 10 allows to extend oil change intervals up to 6000 hours with S-O-S services.		NC
---	----------	--	--	----

STARTERS, BATTERIES, & ALTERNATORS

ENGINE STARTING PACKAGE

L	373-3910	STARTING, STANDARD 0 Provides 145-amp brushed alternator.		NC
L	373-3911	STARTING, COLD (120V) 0 Provides 145-amp brushed alternator, 120V block heater, ether aid ready, transmission & fan bypass.		\$1,600

ELECTRICAL

LIGHTS

L	569-2124	LIGHTS, LED, PREMIUM 0 Includes: -2 LED forward roading lights (low/high beam) with LED turn signals -2 LED rear facing working lights in the hood -2 LED position/stop/turn lights -8 LED working lights on the cab		\$3,375
L	486-2308	LIGHTS, HALOGEN, PREMIUM 0 Includes: -2 halogen forward roading lights (low/high beam) with halogen turn signals -2 halogen rear facing working lights in the hood -2 LED position/stop/turn lights -8 halogen working lights on the cab		\$885

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

ELECTRICAL (CONT.)

LIGHTS (Cont.)

L	486-2311	LIGHTS, HALOGEN 0 Provides Rooding lights : - 2 forward rooding lights halogen(low/high beam) with Halogen turn signal. - 2 rear LED position stop turn lights Provides Halogen Work lights : - 2 forward facing standard lights on the top of the cab - 2 rear facing standard lights on the top of the cab - 2 rear facing standard lights on the Hood		NC
L	522-3605	LIGHTS, LED 0 FOR USE IN LANE 3 ONLY INCLUDES: -2 LED forward rooding lights (low/high beam) with LED turn signals -2 LED rear facing working lights in the hood -2 LED position/stop/turn lights -4 LED working lights on the cab		\$2,535

OPERATOR ENVIRONMENT

WINDOWS

L	477-1660	WINDOWS (CORROSION) 0 FOR USE IN LANE 3 ONLY Provides a paint thickness which is more than two times the thickness of the standard paint, giving the cab extra resistance against corrosion. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		NC
L	477-1659	WINDOWS RM (CORROSION) 0 FOR USE IN LANE 3 ONLY Provides front windows mounted in rubber seals for faster replacement, with a paint thickness which is more than two times the thickness of the standard paint, giving the cab extra resistance against corrosion. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		\$5,600
L	493-9616	WINDOWS, RUBBER MOUNTED 0 FOR USE IN LANE 3 ONLY Provides front windows mounted in rubber seals.		\$5,210
L	493-9617	WINDOWS, RUBBER MTD, FRONT GRD 0 FOR USE IN LANE 3 ONLY Provides front windows mounted in rubber seals and a front window guard.		\$8,840
L	493-9619	WINDOWS, STANDARD, FRONT GUARD 0 FOR USE IN LANE 3 ONLY Provides a front window guard.		\$3,630
L	493-9618	WINDOWS, STANDARD, FULL GUARD 0 FOR USE IN LANE 3 ONLY Provides a full window guard.		\$12,480
L	493-9615	WINDOWS, STANDARD 0		NC

STEERING

L	538-2795	STEERING, LHD JOYSTICK, SECOND 0 Provides an EH steering system & secondary steering.		\$14,440
---	----------	---	--	----------

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

STEERING (Cont.)

L	538-2794	STEERING, LHD JOYSTICK 0 Provides an EH steering system.		\$9,960
L	538-2796	STEERING, WHEEL HMU 0 Provides an HMU steering system.		NC
L	538-2797	STEERING, WHEEL HMU, SECOND 0 Provides an HMU steering system & secondary steering.		\$4,485

IMPLEMENT SINGLE AXIS LEVERS FOR STEERING

L	539-6051	SINGLE AXIS LEVERS, 4V, LHD 0 FOR USE IN LANE 3 ONLY INCLUDES: -3 single action levers for implement lift, tilt & 3rd function controls -1 roller switch controlling the 4th function on implement pod ONLY FOR USE WITH: 384-7008 STEERING, LHD JOYSTICK, SECOND 384-7007 STEERING, LHD JOYSTICK		NC
L	539-6028	SINGLE AXIS LEVERS W/FNR, 4V 0 FOR USE IN LANE 3 ONLY INCLUDES: -3 single action levers for implement lift, tilt and 3rd function controls -1 roller switch controlling the 4th function and FNR switch on implement pod ONLY FOR USE WITH: 384-7010 STEERING, WHEEL HMU, SECOND 384-7009 STEERING, WHEEL HMU		NC
L	539-6031	SINGLE AXIS LEVERS, 2V, LHD 0 INCLUDES: -2 single action levers for implement lift and tilt controls ONLY FOR USE WITH: 501-0400 HYDRAULICS, 2V RC, STD/LOG/HL or 500-2565 HYDRAULICS, 2V RC (3V READY) and 434-0710 STEERING, LHD, JOYSTICK or 434-0711 STEERING, LHD JOYSTICK, SECOND or 384-7008 STEERING, LHD JOYSTICK, SECOND or 384-7007 STEERING, LHD JOYSTICK		NC
L	539-6041	SINGLE AXIS LEVERS, 3V, LHD 0 INCLUDES: -3 single action levers for implement lift, tilt and 3rd function controls ONLY FOR USE WITH: 500-2566 HYDRAULICS, 3V RC, STD/LOGGER or 500-2570 HYDRAULICS, 3V RC, HIGH LIFT and 434-0710 STEERING, LHD JOYSTICK or 434-0711 STEERING, LHD JOYSTICK, SECOND or 384-7008 STEERING, LHD JOYSTICK, SECOND or 384-7007 STEERING, LHD JOYSTICK		NC

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

IMPLEMENT SINGLE AXIS LEVERS FOR STEERING (Cont.)

L	539-6020	LEVERS, SINGLE AXIS W/FNR, 2V 0		NC
		INCLUDES: -2 single action levers for implement lift and tilt controls -FNR switch on implement pod ONLY FOR USE WITH: 501-0400 HYDRAULICS, 2V RC, STD/LOG/HL or 500-2565 HYDRAULICS, 2V RC, (3V READY) and 434-0712 STEERING, WHEEL HMU or 434-0713 STEERING, WHEEL HMU, SECOND or 384-7010 STEERING, WHEEL HMU, SECOND or 384-7009 STEERING, WHEEL HMU		
L	539-6024	LEVERS, SINGLE AXIS W/FNR, 3V 0		NC
		INCLUDES: -3 single action levers for implement lift, tilt and 3rd function controls -FNR switch on implement pod ONLY FOR USE WITH: 500-2566 HYDRAULICS, 3V RC, STD/LOGGER or 500-2570 HYDRAULICS, 3V RC, HIGH LIFT and 434-0712 STEERING, WHEEL HMU or 434-0713 STEERING, WHEEL HMU, SECOND or 384-7010 STEERING, WHEEL HMU, SECOND or 384-7009 STEERING, WHEEL HMU		

IMPLEMENT JOYSTICK FOR STEERING

L	539-6029	JOYSTICK W/FNR, 4V 0		\$1,695
		FOR USE IN LANE 3 ONLY INCLUDES: -Implement joystick for lift & tilt controls -Horn, FNR & kickdown trigger switches integrated in implement joystick -2 rollers switch controlling the 3rd & 4th functions integrated in the joystick ONLY FOR USE WITH: 384-7010 STEERING, WHEEL HMU, SECOND 384-7009 STEERING, WHEEL HMU		
L	539-6054	JOYSTICK, 4V, LHD 0		\$1,565
		FOR USE IN LANE 3 ONLY INCLUDES: -Implement joystick for lift and tilt controls -Horn and kickdown trigger switches integrated in implement joystick -2 rollers switch controlling the 3rd and 4th functions integrated in the joystick ONLY FOR USE WITH: 384-7008 STEERING, LHD JOYSTICK SECOND 384-7007 STEERING, LHD JOYSTICK		
L	539-6036	JOYSTICK, 2V, LHD 0		\$1,095
		INCLUDES: -Implement joystick for lift and tilt controls -Horn and kickdown trigger switches integrated in implement joystick ONLY FOR USE WITH: 501-0400 HYDRAULICS, 2V RC, STD/LOG/HL 434-0710 STEERING, LHD, JOYSTICK 434-0711 STEERING, LHD JOYSTICK, SECOND 384-7008 STEERING, LHD JOYSTICK, SECOND 384-7007 STEERING, LHD JOYSTICK		

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

IMPLEMENT JOYSTICK FOR STEERING (Cont.)

L	539-6046	JOYSTICK, 3V, LHD 0		\$1,535
		INCLUDES: -Implement joystick for lift and tilt controls -Horn and kickdown trigger switches integrated in implement joystick -1 roller switch controlling the 3rd function integrated in the joystick ONLY FOR USE WITH: 500-2566 HYDRAULICS, 3V RC, STD/LOGGER 434-0710 STEERING, LHD JOYSTICK 434-0711 STEERING, LHD JOYSTICK, SECOND 384-7008 STEERING, LHD JOYSTICK, SECOND 384-7007 STEERING, LHD JOYSTICK		
L	539-6022	JOYSTICK, 2V, HMU/FNR 0		\$1,095
		INCLUDES: -Implement joystick for lift and tilt controls -Horn, FNR and kickdown trigger switches integrated in implement joystick ONLY FOR USE WITH: 501-0400 HYDRAULICS, 2V RC, STD/LOG/HL 434-0712 STEERING, WHEEL HMU 434-0713 STEERING, WHEEL HMU, SECOND 384-7010 STEERING, WHEEL HMU, SECOND 384-7009 STEERING, WHEEL HMU		
L	539-6026	JOYSTICK, 3V, HMU/FNR 0		\$1,535
		INCLUDES: -Implement joystick for lift and tilt controls -Horn, FNR and kickdown trigger switches integrated in implement joystick -1 roller switch controlling the 3rd function integrated in the joystick ONLY FOR USE WITH: 500-2566 HYDRAULICS, 3V RC, STD/LOGGER 434-0712 STEERING, WHEEL HMU 434-0713 STEERING, WHEEL HMU, SECOND 384-7010 STEERING, WHEEL HMU, SECOND 384-7009 STEERING, WHEEL HMU		

SEAT BELT

L	551-3397	SEAT BELT, 3" 0		\$104
		FOR USE IN LANE 3 ONLY		

DIFERENTIAL

L	384-7005	AUTO DIFF, HMU 0		NC
		ONLY FOR USE WITH: 366-9908 AXLES, AUTO DIFF F/R, ED or 366-9910 AXLES, AUTO DIFF F/R, ED, SG or 366-9911 AXLES, AUTO DIFF F/R, ED, AOC and 434-0712 STEERING, WHEEL HMU or 434-0713 STEERING, WHEEL HMU, SECOND or 384-7009 STEERING, WHEEL HMU or 384-7010 STEERING, WHEEL HMU, SECOND		

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

DIFERENTIAL (Cont.)

L	384-7006	MANUAL DIFF, HMU 0 ONLY FOR USE WITH: 366-9903 AXLES, LOCK/OPEN, ED or 366-9906 AXLES, LOCK/OPEN, SG or 366-9907 AXLES, LOCK/OPEN, AOC or 434-0712 STEERING, WHEEL HMU or 434-0713 STEERING, WHEEL HMU, SECOND or 384-7009 STEERING, WHEEL HMU or 384-7010 STEERING, WHEEL HMU, SECOND		NC
L	384-7003	AUTO DIFF, LHD JOYSTICK 0 ONLY FOR USE WITH: 366-9908 AXLES, AUTO DIFF F/R, ED or 366-9910 AXLES, AUTO DIFF F/R, ED, SG or 366-9911 AXLES, AUTO DIFF F/R, ED, AOC and 434-0710 STEERING, LHD JOYSTICK or 434-0711 STEERING, LHD JOYSTICK, SECOND or 384-7008 STEERING, LHD JOYSTICK, SECOND or 384-7007 STEERING, LHD JOYSTICK		NC
L	384-7004	MANUAL DIFF, LHD JOYSTICK 0 ONLY FOR USE WITH: 366-9903 AXLES, LOCK/OPEN, ED or 366-9906 AXLES, LOCK/OPEN, SG or 366-9907 AXLES, LOCK/OPEN, AOC and 434-0710 STEERING, LHD JOYSTICK or 434-0711 STEERING, LHD JOYSTICK, SECOND or 384-7008 STEERING, LHD JOYSTICK, SECOND or 384-7007 STEERING, LHD JOYSTICK		NC

CAB FILTERS

L	505-1521	FILTRATION, STEEL 0 FOR USE IN LANE 3 ONLY INCLUDES: -CAB ROOF, STEEL -COVER, HVAC, STEEL CANNOT BE USED WITH: 543-3606 CORROSION RESISTANT PACKAGE REQUIRED BY: STEEL MILL PACKAGE		\$2,155
L	505-1519	FILTRATION, STANDARD 0 INCLUDES: -CAB ROOF, NON-METALLIC -COVER, HVAC, NON-METALLIC		NC
L	505-1520	FILTRATION, STD, PRECLEANER 0 FOR USE IN LANE 3 ONLY INCLUDES: -CAB ROOF, NON-METALLIC -COVER, HVAC, NON-METALLIC -PRECLEANER, HVAC Provides a precleaner for dusty environments for cab air intake.		\$690
L	505-1522	FILTRATION, STEEL, ACF PRECLNR 0 FOR USE IN LANE 3 ONLY INCLUDES: -CAB ROOF, STEEL -COVER, HVAC, STEEL FOR ACF -ACF PRECLEANER, HVAC CANNOT BE USED WITH: 543-3606 CORROSION RESISTANT PACKAGE		\$3,515

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

CAB FILTERS (Cont.)

L	505-1523	FILTRATION, STD, ACF PRECLNR 0 FOR USE IN LANE 3 ONLY INCLUDES: -CAB ROOF, NON-METALLIC -COVER, HVAC, STEEL FOR ACF -ACF PRECLEANER, HVAC CANNOT BE USED WITH: 543-3606 CORROSION RESISTANT PACKAGE		\$1,870
---	----------	--	--	---------

TRIM ARRANGEMENT

L	538-2772	CAB TRIM, PREMIUM PLUS (HMU) 0 FOR USE IN LANE 3 ONLY INCLUDES: -SEAT, HEATED & VENTILATED-HMU Provides steering wheel and a heated and ventilated seat with leather trim. -MIRRORS, EXTERNAL, HEATED -DOOR, REMOTE OPENING SYSTEM Provides remote manual switch allowing to open the cab door from ground level. -SUN VISOR, REAR Provides pull down sun screen in rear windowHMU OR ONLY FOR USE WITH: 384-7009 STEERING, WHEEL HMU OR 384-7010 STEERING, WHEEL HMU, SECOND		\$3,905
L	538-2775	CAB TRIM, PREMIUM PLUS (LHD) 0 FOR USE IN LANE 3 ONLY INCLUDES: -SEAT, HEATED & VENTILATED, LHD Provides steering joystick on left hand armrest and a heated and ventilated seat with leather trim. -MIRRORS, EXTERNAL, HEATED -DOOR, REMOTE OPENING SYSTEM Provides remote manual switch allowing to open the cab door from ground level. -SUN VISOR, REAR Provides pull down sun screen in rear window. ONLY FOR USE WITH: 384-7007 STEERING, LHD JOYSTICK OR 384-7008 STEERING, LHD JOYSTICK, SECOND		\$3,905
L	538-2770	CAB TRIM, COMFORT (HMU) 0 INCLUDES: -SEAT, STANDARD-HMU Provides steering wheel and standard seat. -MIRRORS, EXTERNAL -SUN VISOR, REAR Provides pull down sun screen in rear window. ONLY FOR USE WITH: 384-7009 STEERING, WHEEL HMU or 384-7010 STEERING, WHEEL HMU, SECOND or 434-0712 STEERING, WHEEL HMU or 434-0713 STEERING, WHEEL HMU, SECOND		\$69

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

TRIM ARRANGEMENT (Cont.)

L	538-2771	CAB TRIM, DELUXE (HMU) 0 INCLUDES: -SEAT, HEATED-HMU Provides steering wheel and heated seat. -MIRRORS, EXTERNAL, HEATED -DOOR, REMOTE OPENING SYSTEM Provides remote manual switch allowing to open the cab door from ground level. -SUN VISOR, REAR Provides pull down sun screen in rear window. ONLY FOR USE WITH: 384-7009 STEERING, WHEEL HMU or 384-7010 STEERING, WHEEL HMU, SECOND or 434-0712 STEERING, WHEEL HMU or 434-0713 STEERING, WHEEL HMU, SECOND	0	\$1,030
L	538-2773	CAB TRIM, COMFORT (LHD) 0 FOR USE IN LANE 3 ONLY INCLUDES: -SEAT, STANDARD, LHD Provides steering joystick on left hand armrest and standard seat. -MIRRORS, EXTERNAL -SUN VISOR, REAR Provides pull down sun screen in rear window. ONLY FOR USE WITH: 384-7007 STEERING, LHD JOYSTICK or 384-7008 STEERING, LHD JOYSTICK, SECOND or 434-0710 STEERING, LHD JOYSTICK or 434-0711 STEERING, LHD JOYSTICK, SECOND	0	\$69
L	538-2774	CAB TRIM, DELUXE (LHD) 0 INCLUDES: -SEAT, HEATED, LHD Provides steering joystick on left hand armrest and heated seat. -MIRRORS, EXTERNAL, HEATED -DOOR, REMOTE OPENING SYSTEM Provides remote manual switch allowing to open the cab door from ground level. -SUN VISOR, REAR Provides pull down sun screen in rear window ONLY FOR USE WITH: 384-7007 STEERING, LHD JOYSTICK or 384-7008 STEERING, LHD JOYSTICK, SECOND or 434-0710 STEERING, LHD JOYSTICK or 434-0711 STEERING, LHD JOYSTICK, SECOND	0	\$1,185

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet.

Availability varies by country, please contact your Cat marketing representative with questions or click on the link below:
[HTTPS://DEALER.CAT.COM/en/bt/otd/machine-price-list.html](https://dealer.cat.com/en/bt/otd/machine-price-list.html)
 From there click on the "PRODUCT LINK Hardware Certification" link.

L	434-0691	PRODUCT LINK, CELLULAR PLE641 0 Product Link Elite series PLE641 (consisting of PL641 radio and PLE601 network manager) uses cellular networks to transmit location, utilization, health and productivity information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		NC
L	434-0693	PRODUCT LINK, SATELLITE PLE631 0 Product Link Elite series PLE631 (consisting of PL631 radio and PLE601 network manager) uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		\$439

COOLING

COOLING SYSTEM

L	524-1394	COOLING CORES 6 FPI, CORROSION 0 FOR USE IN LANE 3 ONLY Provides cooling capability up to 43C (109F) ambient. Radiator with 6 fins per inch. - Cores protected (painted); - Grease points on the radiator hinges. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		\$3,015
L	524-1393	COOLING CORES 9 FPI, CORROSION 0 FOR USE IN LANE 3 ONLY Provides cooling capability up to 47C (117F) ambient. Radiator with 9 fins per inch. - Cores protected (painted); - Grease points on the radiator hinges. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		\$2,665
L	521-9359	COOLING CORES, 6 FPI 0 Provides cooling capability up to 43C (109F) ambient. Radiator with 6 fins per inch.		\$342
L	521-9358	COOLING CORES, 9 FPI 0 Provides cooling capability up to 47C (117F) ambient. Radiator with 9 fins per inch.		NC

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

COOLING (CONT.)

COOLING FAN

L	513-5393	FAN, VPF, ANSI 0		\$5,250
		FOR USE IN LANE 3 ONLY Provides an attachment reversing function to the standard hydraulically driven demand fan. This provides the ability to rotate blades and to reverse the airflow direction to remove debris from the radiator and engine enclosures while the machine is still operating. Includes automatic and manual controls for airflow reversal. Recommended for applications with a high content of airborne debris.		
L	513-5394	FAN, STANDARD 0		NC
		Standard load sensing hydraulically driven fan.		

COOLANT

L	371-7064	ANTIFREEZE, -34C (-29F) 0		NC
		Premix Antifreeze, -34C or -29F		
L	423-2664	ANTIFREEZE, -50C (-58F) 0		\$275 NET
		Premix Antifreeze, -50C or -58F		

TIRES, RIMS, AND WHEELS

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice. However, if the tire type cannot be supplied we will contact the dealer to propose alternatives. The dealer needs to choose between an alternative tire or a "rims only" option (where available) within 72 hours. If no response is provided by the deadline, the order will default to the alternative tire and will be changed at that point. As a consequence of a possible tire change, the total machine price will be decreased or increased depending on the price of the new tire.

NOTE: All tires include rims & come in a set of 4. Tires are tubeless & non-directional unless otherwise stated.

NOTE: Other tires are available upon request.

TIRES AVAILABLE FROM MICHELIN

P	373-4052	TIRES, 23.5R25 MX XHA2 * L3 0		\$-2,845
---	----------	---	--	----------

TIRES AVAILABLE FROM BRIDGESTONE

P	509-1481	TIRES, 750/65R25 BS VTS * L3 0		\$12,680
---	----------	--	--	----------

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS (CONT.)

TIRES AVAILABLE FROM MAXAM

P	547-8401	TIRES, 23.5R25 MA MS302 **E3/L3 0 MAXAM RADIAL; TREAD DEPTH=36.5mm; Rim=19.5"x25" 3 piece Provides reduced vibration, damage resistance, and traction in soft to rocky underfoot conditions.		\$-10,670
---	----------	--	--	-----------

SOLID TIRES

P	540-4373	TIRES, 23.5X25 BR TRACTION 0 FOR USE IN LANE 3 ONLY Brawler HPS Solidflex Traction Off-the-Road (OTR) tread solid tires pressed on to standard CAT rims. Ideal for harsh/special applications on unimproved surfaces, such as as brick, glass, and scrap yards where debris is not an issue. Machine oscillation is reduced.		\$17,250
---	----------	--	--	----------

P	540-4374	TIRES, 23.5X25 BR SMOOTH 0 FOR USE IN LANE 3 ONLY Brawler HPS Solidflex Smooth tread solid tires pressed on to standard CAT rims. Ideal for harsh/special applications where debris is an issue, such as scrap yards, recycling centers and waste transfer stations. Machine oscillation is reduced.		\$20,550
---	----------	--	--	----------

TIRES/RIMS, ALLOWANCE FOR OMISSION

Dealers should contact their Application Specialist if they plan to use a tire not offered on the price list. Some tires may require axle oscillation stops or other machine modifications.

P	373-4064	RIMS ONLY, TIRES OMITTED 0 FOR USE IN LANE 3 ONLY		\$-16,240
P	0P-3647	OMISSION, TIRES AND RIMS 0 FOR USE IN LANE 3 ONLY		\$-19,590

BODY

FENDERS

L	464-6675	FENDERS, ROADING, LOW PROFILE 0 FOR USE IN LANE 3 ONLY Provide non-metallic front fenders with top extension, mud flaps and full wrap non-metallic rear fenders with removable mud flaps. ONLY FOR USE WITH: 509-1481 TIRES, 750/65R25 BS VTS*L3		\$3,070
---	----------	---	--	---------

L	464-6672	FENDERS, BASIC +. 0 Provide non-metallic front fenders with mud flaps and short rear fender extensions covering top of wheel. CANNOT BE USED WITH: 509-1481 TIRES, 750/65R25 BS VTS*L3		NC
---	----------	--	--	----

L	464-6673	FENDERS, ROADING 0 FOR USE IN LANE 3 ONLY Provide non-metallic front fenders with top extension, mud flaps and full wrap non-metallic rear fenders with removable mud flaps. CANNOT BE USED WITH: 509-1481 TIRES, 750/65R25 BS VTS*L3		\$2,775
---	----------	--	--	---------

L	464-6674	FENDERS, BASIC +, LOW PROFILE. 0 Provide non-metallic front fenders with mud flaps and short rear fender extensions covering top of wheel. ONLY FOR USE WITH: 509-1481 TIRES, 750/65R25 BS VTS*L3		\$153
---	----------	---	--	-------

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

BODY (CONT.)

FENDERS (Cont.)

L	478-8371	FENDERS, NARROW 0 FOR USE IN LANE 3 ONLY CONTACT CUSTOM PRODUCTS FOR AVAILABILITY. Provides narrow steel front fenders, steel rear fender extensions and heavy duty hanging steel steps. CANNOT BE USED WITH: 509-1481 TIRES, 750/65R25 BS VTS*L3		\$3,040
---	----------	---	--	---------

HOOD

L	477-1667	HOOD - CORROSION 0 FOR USE IN LANE 3 ONLY ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		NC
L	336-0000	HOOD, NON-METALLIC 0		NC

SOUND SUPPRESSION

L	465-6576	SOUND SUPPRESSION, STANDARD 0		NC
L	488-1138	SOUND SUPPRESSION, INDUSTRIAL 0 FOR USE IN LANE 3 ONLY Provides steering cylinder guards for high debris applications.		\$1,085

FLUIDS

LUBRICATION ARRANGEMENTS

L	538-2790	LUBRICATION, MANUAL, STD/LOG 0 ONLY FOR USE WITH: 506-3486 LINKAGE, STANDARD LIFT or 506-3488 LINKAGE, LOGGER		NC
L	538-2791	AUTOLUBE, STD/LOGGER 0 Provides Caterpillar autolube system. ONLY FOR USE WITH: 506-3486 LINKAGE, STANDARD LIFT or 506-3488 LINKAGE, LOGGER		\$6,440
L	538-2792	LUBRICATION, MANUAL, HIGH LIFT 0 FOR USE IN LANE 3 ONLY ONLY FOR USE WITH: 506-3487 LINKAGE, HIGH LIFT		NC
L	538-2793	AUTOLUBE, HIGH LIFT 0 FOR USE IN LANE 3 ONLY ONLY FOR USE WITH: 506-3487 LINKAGE, HIGH LIFT		\$6,650

FUEL ANTIFREEZE

	0P-3978	FUEL ANTIFREEZE, -25C (-13F) 0 Provides fuel (diesel) antifreeze protection down to -25C (-13F)		NC
--	---------	--	--	----

INSTRUCTIONS

OPERATION AND MAINTENANCE MANUAL

NOTE: Operation and maintenance Manual will be included in language requested below. REQUIRED BY: ALL LANE CONFIGURATION

	0P-3380	INSTRUCTIONS, ENGLISH 0		NC
--	---------	-----------------------------------	--	----

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OPERATOR ENVIRONMENT

RADIOS.

Bluetooth radio technology enables the use of a hands free function such as listening to music and making phone calls. Authorization varies by country, please contact your Cat marketing representative with questions or click on the link below: <https://dealer.cat.com/en/products/technology.html>

P	372-1603	RADIO, CB (READY) 0 Provides adjustable mounting brackets for two radios, a 20 amp 24V to 12V converter, a CB antenna, CB cable converter, and two separate four wire connectors that contain a ground, 12V and 24 V circuits		\$955
P	372-1600	RADIO, AM/FM/USB/MP3 BLUETOOTH 0 Provides AM/FM/MP3/WB/USB/AUX with integrated BlueTooth.		\$590

INTEGRATED OBJECT DETECTION SYSTEM

The Cat Integrated Object Detection adds radar and alarms to the standard on-board rear vision camera to notify the operator when something is close to the rear of the machine. This system is configured with zones, and objects in those zones trigger various levels of alarms. A display screen in the cab provides visual confirmation of the objects detected by the radar, so operators can make informed decisions.

L	486-9204	OBJECT DETECTION 0		\$2,785
L	486-9205	OBJECT DETN & CB RADIO READY 0 INCLUDES: 486-9204 OBJECT DETECTION 372-1603 RADIO, CB (READY)		\$3,720

VISIBILITY

P	380-5964	SECONDARY CAMERA DISPLAY 0 FOR USE IN LANE 3 ONLY Provides full-time display dedicated to rear-view camera.		\$1,755
---	----------	--	--	---------

SECURITY SYSTEM

P	372-1604	SECURITY SYSTEM, MACHINE 0 FOR USE IN LANE 3 ONLY Protects from vandalism and theft by preventing unauthorized personnel from starting a machine. Machines start only after a unique MSS key is inserted into the ignition. MSS keys can be programmed to start machines only certain days or hours.		\$700
---	----------	---	--	-------

LIGHTS

P	513-2458	LIGHTS, REVERSING STROBE 0 Provides 2 reversing blue strobes.		\$275
P	460-7450	LIGHT, SEAT BELT WARNING 0 Provides a seat belt warning light mounted to the rear of the cab structure.		\$230

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

LIGHTS (Cont.)

P	491-7467	LIGHT, WARNING BEACON 0 Provides hard mounted strobe beacon on hinged (breakaway) bracket mounted to the rear of the cab structure.		\$491
---	----------	--	--	--------------

TECHNOLOGY PRODUCTS

SOFTWARE ENABLED ATTACHMENTS (SEA) INSTRUCTIONS

Technology apps are activated by Software Enabled Attachments (SEA). SEAs are available factory installed or can be purchased for dealer installation.

Refer to Information Release Memo (IRM) EES03 -01 (media number PELJ0138) in the Caterpillar Media Information Center for further explanation of SEAs. Select the Product Support tab and search for number PELJ0138. Refer to REHS1238 & REHS8401 for how to obtain a Factory Level Password. Contact FPS: Internet with Corporate Web Security (CWS) ([https:// fps.cat.com/](https://fps.cat.com/)).

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

CAT PRODUCTION MEASUREMENT (CPM) PAYLOAD WEIGHING SYSTEM

Cat M-series Medium Wheel Loaders are available with the Cat Production Measurement (CPM) that includes an integrated onboard payload weighing scale. This measures and/or records:

- Payload weight, material ID, truck ID, cycle (bucket dumps) count and fuel consumption
- Allows on-the-go weighing of the bucket payload during the lift cycle
- Daily payload total (tonnes/tons), productivity (tonnes/hour or tons/hour) and efficiency (tonnes/liter or tons/gal) data is reported wirelessly via Product Link to the VisionLink fleet management web portal (Cat Essentials Product Link subscription required).
- Detailed payload, productivity and efficiency data can be downloaded to a laptop computer for analysis in the optional VIMSpC software (VIMSpC and VIMS data cable are required, but VIMS is NOT required).
- Payload tickets can be printed with an optional printer

Refer to the Cat Connect Payload Technologies intranet page (<https://dealer.cat.com/payload>) for complete technical specifications; operation, sales, marketing and technical support publications.

NOTES:

- 1) Permanent software is available from the factory below.
- 2) For field installation, permanent software can be purchased through the Caterpillar Feature Protection System and enabled by a dealer technician with Cat ET and an SEA password. SEA p/n 517-4683. Consult ANTARES parts distribution system for latest SEA price.
- 3) Both demo and permanent software require calibration prior to customer use.

CALIBRATION INSTRUCTIONS

This requires calibration and set-up by either the dealer or customer. Refer to the Systems Operation Test & Adjust manual UENR7119 for system calibration, material and truck ID lists set-up and operation instructions.

P	517-7123	CPM PAYLOAD SOFTWARE 0		\$5,010
		Includes permanent software, PDC activated. Includes 6 mo. of prepaid Cat Advanced Productivity VisionLink subscription, with PLE641 cellular Product Link ONLY. (Not available in all countries. Contact PL Admin for details.) REQUIRES: 478-1336 AUTODIG & CPM PAYLOAD, ARO ONLY FOR USE WITH: 370-3813 CPM PAYLOAD WEIGHING READY or 512-0858 STANDARD PACKAGE		
P	370-3813	CPM PAYLOAD WEIGHING READY 0		\$230
		FOR USE IN LANE 3 ONLY Includes hardware and demo software for CPM, dealer enabled for up to 250 hours. To activate demo software, it must be enabled by a dealer technician with Cat ET. No password is required. For permanent software activation in the field, purchase of software ONLY FOR USE WITH: Product Link Elite CANNOT BE USED WITH: 512-0858 STANDARD PACKAGE		

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

AUTODIG

Autodig is a software enabled attachment that controls the implement system during the bucket loading portion of a cycle to automatically load aggregate material.

NOT RECOMMENDED for hardbank or large rock loading.

P	453-3250	AUTODIG SOFTWARE 0		\$1,445
		Includes software for Aggregate Autodig. NOT RECOMMENDED for hardbank or large rock loading. REQUIRES: 478-1336 AUTODIG & CPM PAYLOAD, ARO		

GUARDS

P	485-4387	GUARDS, LIGHT 0		\$1,590
		FOR USE IN LANE 3 ONLY Provide protection guard for lights installed on the cab and counterweight. ONLY FOR USE WITH: 505-1509 INDUSTRIAL PACKAGE or 505-1506 INDUSTRIAL PACKAGE CANNOT BE USED WITH: 486-2311 LIGHTS, HALOGEN		
L	397-1606	GUARD, TILT CYLINDER 0		\$1,415
		FOR USE IN LANE 3 ONLY CANNOT BE USED WITH: 506-3488 LINKAGE, LOGGER REQUIRED BY: 505-1506 INDUSTRIAL PACKAGE		
P	367-9027	GUARD, POWERTRAIN 0		\$1,520
		Protects bottom of transmission.		
L	399-4332	GUARD, HINGED, POWERTRAIN 0		\$3,315
		FOR USE IN LANE 3 ONLY Provides heavy duty guard to protect the bottom of the transmission; hinged for service. ONLY FOR USE WITH: 505-1509 INDUSTRIAL PACKAGE REQUIRED BY: 505-1509 INDUSTRIAL PACKAGE		

OTHER ATTACHMENTS

P	503-4735	OIL CHANGE SYSTEM, HIGH SPEED 0		\$291
		Easy access drain line and Wiggins connector for remote engine oil drain. Provides quick, clean, and easy engine oil change without having to climb under the machine to access a gravity drain.		
L	506-4369	WHEEL CHOCKS 0		\$498
		Provides wheel chocks that mount to the frame.		

CORROSION RESISTANT OPTIONS

L	506-0545	PROTECTION PACKAGE, LINES 0		\$4,795
		FOR USE IN LANE 3 ONLY Hoses treated with tube heat shrinkable and sealant silicone. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

CORROSION RESISTANT OPTIONS (Cont.)

L	521-9198	PAINTING GROUP, CORROSION 0 FOR USE IN LANE 3 ONLY Provides a paint thickness which is more than two times the thickness of the standard paint, giving the machine extra resistance against corrosion. ONLY FOR USE WITH: CORROSION RESISTANT PACKAGE		\$4,965
---	----------	--	--	---------

QUICK COUPLERS

P	373-3904	QUICK COUPLER READY, HIGH LIFT 0 FOR USE IN LANE 3 ONLY REQUIRED BY: 506-3487 LINKAGE, HIGH LIFT AM-N Dealers		\$3,740
P	373-3902	QUICK COUPLER READY, STD LIFT 0 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed Caterpillar Work Tools & Services (CWTS) fusion style coupler. ONLY FOR USE WITH: 506-3486 LINKAGE, STANDARD LIFT 506-3488 LINKAGE, LOGGER REQUIRED BY: AM-N Dealers		\$3,740
L	349-5246	QUICK COUPLER, FUSION 1,248 ALSO AVAILABLE ON A MISCELLANEOUS ORDER Factory installed Caterpillar Work Tools & Services (CWTS) Fusion style coupler.		\$6,678
P	0P-4108	WORKTOOL'S LITERATURE 0 (SEBP5193) REQUIRED BY: 349-5246 QUICK COUPLER, FUSION		NC

LINES CONNECTING

L	378-8421	LINES GP-IMPLEMENT 3V (QC) 22 REQUIRES: 373-3893 or 373-3897 HYDRAULICS, 3V 349-5246 QUICK COUPLER, FUSION		\$551
L	378-8422	LINES GP-IMPLEMENT 3V&4V (QC) 44 REQUIRES: 373-3894 or 373-3898 HYDRAULICS, 4V 349-5246 QUICK COUPLER, FUSION		\$1,101

WORK TOOLS

OMISSION WORK TOOL

P	361-1437	OMISSION, WORKTOOL 0 Required in orders configured without a work tool or QC in order to prevent from damages on the linkage.		NC
---	----------	--	--	----

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

BUCKETS

Buckets must be ordered Installed on a Machine Order. For questions on buckets intended for Machine Orders please contact your Marketing Subsidiary Machine Coordinator.

Loose buckets should be ordered on a MISC Order through Caterpillar Work Tools - Wamego using source code OP-0672.

For availability of loose buckets please email worktools@cat.com If you are going to order a loose bucket from CWTS and a machine from Aurora and if you need them shipped at the same time then you need to cross-reference the MSO's with each other.

"GET" is NOT automatically included on bucket orders. "GET" must be entered on the order with your bucket selection, unless text for bucket states otherwise. Please make the "GET" selection from the "GET" listed immediately following the bucket listing.

Recommend use of bolt-on adapter option, adapter and segment option, or bolt-on cutting edge option for general purpose buckets and material handling buckets.

Material density will determine the appropriate capacity bucket. Refer to the Specalog. Exceeding maxium payload may cause loader instability.

ALL BUCKETS ARE ALSO AVAILABLE ON A MISCELLANEOUS ORDER

110% FILL FACTOR: This capacity is calculated considering GETs installed.

GENERAL PURPOSE PERFORMANCE SERIES BUCKETS (PIN-ON)

P	354-4855	BKT GP ST 114" 4.75 YD3 PO	3,803	\$14,653
			3,803	\$14,653 NI
		PERFORMANCE SERIES BUCKET		
		CAPACITIES:		
		4.5YD3 (3.4M3) w/bolt-on adaptaters, 117" (2972mm) wide		
		4.75YD3 (3.6M3) w/bolt-on adaptaters and segment, 117" (2972mm) wide		
		4.75YD3 (3.6M3) w/bolt-on cutting edges, 114"(2894mm) wide(Bucket Tag)		
		110% FILL FACTOR:		
		5.25YD3 (4M3) with GETs		
		RECOMMENDED WITH : COUNTERWEIGHT, 1460KG		

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

BUCKETS (CONT.)

GENERAL PURPOSE BUCKETS (FUSION)

P	354-4856	BKT GP ST 114" 4.75 YD3 FUS	3,503 3,503	\$14,653 \$14,653 NI
PERFORMANCE SERIES BUCKET CAPACITIES: 4.5YD3 (3.4M3) w/bolt-on adaptaters, 117" (2972mm) wide 4.75YD3 (3.6M3) w/bolt-on adaptaters and segment, 117" (2972mm) wide 4.75YD3 (3.6M3) w/bolt-on cutting edges, 114"(2894mm) wide(Bucket Tag) 110% FILL FACTOR: 5.25YD3 (4M3) with GETs RECOMMENDED WITH : COUNTERWEIGHT, 1460KG				

GROUND ENGAGING TOOLS

CUTTING EDGE

P	139-9229	CUTTING EDGE, BOLT-ON	600	\$1,447
ALSO AVAILABLE ON A MISCELLANEOUS ORDER Width: 2906MM				

INSTRUCTIONS

FILMS

P	468-0173	FILM, FOREST	0	NC
ONLY FOR USE WITH: 505-1554 LINKAGE, LOGGER				
P	468-0170	FILM, SCRAP	0	NC
ONLY FOR USE WITH: INDUSTRIAL PACKAGE				
P	468-0171	FILM, WASTE	0	NC
ONLY FOR USE WITH: INDUSTRIAL PACKAGE				

PACKING

EXPORT PACKING

OP-6619	ROLL ON-ROLL OFF	0	\$263 NET
Machine is in mobile condition and all attachments are installed unless spificied.			

ALLOWANCE FOR OMISSION

P	OP-4781	ALLOWANCE FOR OMISSION	0	\$476
REQUIRED BY: 373-4064 RIMS ONLY, TIRES OMITTED				

STORAGE PROTECTION

OP-2918	STORAGE PROTECTION	0	NC
This product is added for corrosion protection while shipping and for extended storage periods. This product will need to be power washed with soapy water prior the shipment to the customer. REQUIRED BY : ALL LANE CONFIGURATION			

CATERPILLAR MACHINE PRICE LIST

962M-BR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

PACKING (CONT.)

SPECIAL INSTRUCTIONS

0P-2949	EXPOSITION INSTRUCTION	0	NC
	This special instruction must be selected whenever dealer is placing an order for a unit intended for use at expositions and/or trade fairs		

CYLINDER PROTECTION

0P-3940	PROTECTION, CYLINDER ROD	0	NC
---------	------------------------------------	---	----