

CATERPILLAR MACHINE PRICE LIST

**988K**

988K WHEEL LOADER DECATUR, IL, USA	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------------	--------------------	-------------------------

Standard Equipment:

**POWERTRAIN**

- Advanced Productivity Electronic Control Shifting (APECS)
- Air to air aftercooler
- Brakes, full hydraulic, enclosed, wet multiple disc service brakes
- Electro hydraulic parking brake
- Engine, Cat C18 w/ACERT technology
- Fuel priming pump (electric)
- Fuel to air cooler
- Ground level engine shutoff
- Guard, transmission
- Hydraulically driven demand fan
- Integrated braking
- Radiator, Aluminum Modular (AMR)
- Separated cooling system
- Starting aid (ether) automatic
- Throttle lock
- Torque converter, impeller clutch with lock-up clutch & rimpull control system
- Turbine precleaner, engine air intake
- Transmission, planetary powershift, 4F/3R electronic control

- Fuel level
- Hydraulic oil temperature
- Speedometer/Tachometer
- Torque convertor temperature
- Instrumentation, warning indicators:
  - Action alert system, three category
  - Axle/Brake oil temperature (front/rear)
  - Brake oil pressure
  - Electrical system, low voltage
  - Engine failure malfunction alert and action lamp
- Mirrors, rearview (externally mounted)
- Parking brake status
- Rimpull select switch
- Seat, Cat Comfort (cloth) air suspension
- STIC control system with steering lock
- Tinted glass
- Transmission gear (indicator)
- Product Link Elite:
  - VIMS
  - Graphical information display
  - External data port
  - Customizable operator profiles
- Wet-arm wipers/washers (front and rear), intermittent wipers (front and rear)

**ELECTRICAL**

- Alarm, back-up
- Alternator, 150-amp
- Batteries, maintenance-free, 4-1000 CCA
- Converter, 10/15-amp, 24V to 12V
- Lights, front & rear, access stairway, turn signals
- Starter, electric (heavy duty)
- Starter lockout in bumper
- Starting receptacle for emergency start
- Transmission lockout in bumper

**OTHER STANDARD EQUIPMENT**

- Automatic bucket tilt/lift kickouts electronically adjustable from cab
- Counterweight
- Doors, service access (locking)
- Ecology drains for engine, radiator, hydraulic tank
- Economy mode with on demand throttle
- Emergency platform egress
- Engine, crankcase, 250 hour interval with CJ-4 oil
- Engine idle management features:
  - Auto idle kickdown
  - Delayed engine shutdown
  - Engine idle shutdown
- Fuel tank, 731 L (188 gal)
- Ground level fuel fill
- Ground level transmission electronic clutch pressure control access
- Hitch, drawbar with pin
- Hoses, Cat XT(TM)
- Hydraulic oil cooler
- Hydraulic, steering and brake filtration/screening system
- Oil sampling valves
- Stairway, left and right rear access
- Steering, load sensing
- Toe kicks
- Vandalism protection caplocks

**OPERATOR ENVIRONMENT**

- Air conditioner
- Cab, sound-suppressed, pressurized, internal four-post rollover protective structure (ROPS/FOPS), radio ready for entertainment includes antenna, speakers, converter (12-volt 10/15-amp) and power port
- Coat and hard hat hooks
- E/H tilt & lift controls (seat mounted)
- Flip-up armrest
- Heater and defroster
- Horn, electric
- Implement hydraulic lockout
- Laminated glass
- Light, dome (cab)
- Lunchbox and beverage holders
- Instrumentation, gauges:
  - Engine coolant temperature

CATERPILLAR MACHINE PRICE LIST

**988K**

---

988K WHEEL LOADER  
DECATUR, IL, USA

Ship Weight  
lbs

LIST PRICE  
AT DEALER

---

**OTHER STANDARD EQUIPMENT (CONT.)**

Venturi stack

CATERPILLAR MACHINE PRICE LIST

**988K**

---

988K WHEEL LOADER DECATUR, IL, USA	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------------	--------------------	-------------------------

---

<b>347-5000</b> <b>988K WHEEL LOADER HRC</b> ..... 101,021 LANE 2 - AVAILABLE FROM DECATUR FACTORY LANE 3 - AVAILABLE FROM DECATUR FACTORY	101,021	<b>\$922,960</b>
--	---------	------------------

AVAILABLE FOR: AM-N, EU, ISRAEL, JAPAN, & SOUTH KOREA

<b>0P-4742</b> <b>988K MISCELLANEOUS MATERIAL</b> ..... 0 AVAILABLE FROM DECATUR FACTORY	0	<b>NC</b>
---	---	-----------

Only reference numbers under the Factory Sourced Kits section can be used on a MISC order.

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**LANE SELECTION**

OP-9002	LANE 2 ORDER . . . . .	0	NC
OP-9003	LANE 3 ORDER . . . . .	0	NC

**SPECIAL ARRANGEMENTS**

**LOADER ARRANGEMENTS**

L	367-2710	<b>LOADER, STANDARD . . . . .</b> REQUIRES: 347-5000 988K WHEEL LOADER HRC 467-5822 or 467-5833 CPM PAYLOAD WEIGHING	0	NC
L	367-2730	<b>LOADER, BLOCK HANDLER . . . . .</b> FOR USE WITH LANE 3 ONLY Specialized machine for block handling applications. Includes larger lift and tilt cylinders, and extra counterweight. Other attachments that can complement this offering are ride control and axle oil cooler. REQUIRES: 347-5000 988K WHEEL LOADER HRC 367-2726 LIFT, STANDARD 3V, BLOCK HANDLER 424-6490 LUBRICATION or 424-6495 AUTOLUBE 347-4940 ENGINE, BRAKE 42PR or ** Tires with HLA Rims 467-5822 or 467-5833 CPM PAYLOAD WEIGHING	17,879	\$31,480

NOTE: In this application CPM accuracy is not guaranteed.

L	589-2744	<b>LOADER, MILLYARD . . . . .</b> FOR USE WITH LANE 3 ONLY Specialized machine for log loading millyard applications. Includes larger lift and tilt cylinders, extra counterweight, swing out radiator system with wider fin spacing and auto-reversing fan. Other attachments that can complement this offering are ride control and axle oil cooler. REQUIRES: 347-5000 988K WHEEL LOADER HRC 532-8992 LIFT, STANDARD 3V, MILLYARD 424-6490 LUBRICATION or 518-7215 AUTOLUBE 550-0284 LIGHTS, LED (MY, SM) 360-8193 CAMERA, REAR VISION 42PR or ** Tires with HLA Rims	0	\$42,790
---	----------	--	---	----------

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**SPECIAL ARRANGEMENTS (CONT.)**

**LOADER ARRANGEMENTS (Cont.)**

L	552-0032	<b>LOADER, STEEL MILL</b> ..... 0 FOR USE WITH LANE 3 ONLY Specialized machine for steel mill slag handling applications. Includes transmission and parking brake override systems, steel roof, stainless steel braided hose guarding (refer to TEKQ1464), reinforced platform to accommodate fire suppression systems, brake accumulator guard, solid metal access ladders, swing out radiator system with wide fin spacing and auto-reversing fan. Ecosafe oil is recommended. REQUIRES: 347-5000 988K WHEEL LOADER HRC 367-2715 LIFT, STANDARD or 367-2725 LIFT, HIGH 548-2125 LUBRICATION or 548-2130 or 548-2135 AUTOLUBE 550-0284 LIGHTS, LED (MY, SM) 561-6899 CAB, STEEL MILL 441-5220 MIRRORS, STANDARD (SM) 360-8193 CAMERA, REAR VISION 519-9951 FUEL TANK, STANDARD (SM) 435-1155 GUARDS, HEAVY DUTY 541-7900 COOLER, AXLE OIL (MY, SM) or 435-1223 GUARD 467-5822 or 467-5833 CPM PAYLOAD WEIGHING 557-9861 KIT, AXLE OSCILLATION STOP		\$35,470
L	367-2750	<b>LOADER, EZ CLEAN</b> ..... 0 FOR USE WITH LANE 3 ONLY Provides reversing fan feature, lower cooling fin density, and easy core cleaning access. REQUIRES: 347-5000 988K WHEEL LOADER HRC 472-7125 or 516-3924 LIFT, EZ CLEAN 467-5822 or 467-5833 CPM PAYLOAD WEIGHING		\$21,670

**BOOMS, STICKS, AND LINKAGES**

**LIFT ARRANGEMENTS**

Please pay attention to compatibility, it is dependent on Loader selection.

L	347-4900	<b>LIFT, STANDARD 2V</b> ..... 0 Provides standard lift with 2-valve function. Recommended for use with Load and Carry applications, loading 30/40 ton off highway trucks. ONLY FOR USE WITH: 367-2710 or 367-2719 LOADER, STANDARD		NC
L	347-4910	<b>LIFT, STANDARD 3V</b> ..... 442 FOR USE WITH LANE 3 ONLY Provides standard lift with 3-valve function. Recommended for use with Load and Carry applications, loading 30/40 ton off highway trucks. ONLY FOR USE WITH: 367-2710 or 367-2719 LOADER, STANDARD		\$9,170
L	347-4920	<b>LIFT, HIGH 2V</b> ..... 950 Provides high lift with 2-valve function. Recommended for loading 50/70 ton trucks or any application where maximum dump clearance is desired. ONLY FOR USE WITH: 367-2710 or 367-2719 LOADER, STANDARD		\$8,080

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**BOOMS, STICKS, AND LINKAGES (CONT.)**

**LIFT ARRANGEMENTS (Cont.)**

L	347-4930	<b>LIFT, HIGH 3V</b> ..... 1,393 FOR USE WITH LANE 3 ONLY Provides high lift with 3-valve function. Recommended for loading 50/70 ton trucks or any application where maximum dump clearance is desired. ONLY FOR USE WITH: 367-2710 or 367-2719 LOADER, STANDARD	1,393	\$17,260
L	367-2726	<b>LIFT, STANDARD 3V, BLOCK HANDLER</b> ..... 7,811 FOR USE WITH LANE 3 ONLY Provides standard lift height linkage with application specific design, tilt lever guard, and 3V hydraulics. ONLY FOR USE WITH: 367-2730 or 367-2739 LOADER, BLOCK HANDLER	7,811	\$9,170
L	532-8992	<b>LIFT, STANDARD 3V, MILLYARD</b> ..... 0 FOR USE WITH LANE 3 ONLY Provides standard lift height linkage with application specific design and 3V hydraulics. ONLY FOR USE WITH: 589-2744 or 589-2745 LOADER, MILLYARD	0	\$9,170
L	367-2715	<b>LIFT, STANDARD 2V, STEEL MILL</b> ..... 5,016 FOR USE WITH LANE 3 ONLY Provides standard lift linkage with 2V hydraulics and rear bumper with side guards. ONLY FOR USE WITH: 552-0032 or 552-0034 LOADER, STEEL MILL	5,016	\$1,465
L	367-2725	<b>LIFT, HIGH 2V, STEEL MILL</b> ..... 7,813 FOR USE WITH LANE 3 ONLY Provides high lift linkage with 2V hydraulics and rear bumper with side guards. ONLY FOR USE WITH: 552-0032 or 552-0034 LOADER, STEEL MILL	7,813	\$9,540
L	472-7125	<b>LIFT, STANDARD 2V, EZ CLEAN</b> ..... 0 FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 367-2750 LOADER, EZ CLEAN	0	\$3,500
L	516-3924	<b>LIFT, HIGH 2V, EZ CLEAN</b> ..... 0 FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 367-2750 LOADER, EZ CLEAN	0	\$11,570

**LUBRICATION ARRANGEMENTS**

The autolube option provides a LINCOLN INDUSTRIAL CORP. "CENTROMATIC" automatic greasing system for 18 lube locations requiring lubrication on the Lift Ar. This arrangement is powered using hydraulic oil for trouble free performance and includes a 60 lb. reservoir. Special guarding is added when needed to protect lines or valve components. Tank or reservoir can be filled from a remote location at ground level or at the tank port.

Please pay attention to compatibility, it is dependent on Lift selection.

L	367-5610	<b>LUBRICATION, STANDARD</b> ..... 0 ONLY FOR USE WITH: LIFT, STANDARD or LIFT, HIGH	0	NC
L	367-5580	<b>AUTOLUBE, CENTROMATIC</b> ..... 393 ONLY FOR USE WITH: LIFT, STANDARD	393	\$16,200
L	367-5585	<b>AUTOLUBE, CENTROMATIC</b> ..... 409 ONLY FOR USE WITH: LIFT, HIGH	409	\$16,200

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**BOOMS, STICKS, AND LINKAGES (CONT.)**

**LUBRICATION ARRANGEMENTS (Cont.)**

L	424-6490	LUBRICATION, STANDARD (BH, MY) . . . . . 21 FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 367-2726 LIFT, STANDARD 3V, BLOCK HANDLER 532-8992 LIFT, STANDARD 3V, MILLYARD		NC
L	424-6495	AUTOLUBE, CENTROMATIC (BH) . . . . . 459 FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 367-2726 LIFT, STANDARD 3V, BLOCK HANDLER		\$16,200
L	518-7215	AUTOLUBE, CENTROMATIC (MY) . . . . . 0 FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 532-8992 LIFT, STANDARD 3V, MILLYARD		\$16,200
L	548-2125	LUBRICATION, STANDARD (SM) . . . . . 0 FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 367-2715 LIFT, STANDARD 2V, STEEL MILL 367-2725 LIFT, HIGH 2V, STEEL MILL		NC
L	548-2130	AUTOLUBE, CENTROMATIC (SM) . . . . . 0 FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 367-2715 LIFT, STANDARD 2V, STEEL MILL		\$16,200
L	548-2135	AUTOLUBE, CENTROMATIC (SM) . . . . . 0 FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 367-2725 LIFT, HIGH 2V, STEEL MILL		\$16,200

**POWERTRAIN**

**ENGINES**

L	366-1928	ENGINE, STANDARD . . . . . 0 US EPA T4F/EU Stage V Technology ONLY FOR USE WITH: 347-5000 988K WHEEL LOADER HRC CANNOT BE USED WITH: 367-2730 LOADER, BLOCK HANDLER		NC
L	347-4940	ENGINE, BRAKE . . . . . 78 US EPA T4F/EU Stage V Technology Provides engine braking for steep grades or speed reduction. ONLY FOR USE WITH: 347-5000 988K WHEEL LOADER HRC		\$2,945

**ENGINE PRECLEANERS**

L	377-9320	PRECLEANER, STANDARD . . . . . 0 ONLY FOR USE WITH: 347-5000 988K WHEEL LOADER HRC		NC
L	377-0851	PRECLEANER, DUAL . . . . . 37 ONLY FOR USE WITH: 347-5000 988K WHEEL LOADER HRC		\$2,835

**AXLES**

L	347-5246	AXLES, STANDARD . . . . . 0 Provides standard front and rear axles.		NC
L	347-5256	AXLES, NO-SPIN REAR . . . . . -15 FOR USE WITH LANE 3 ONLY Provides standard front axle and no-spin rear axle. With normal hard packed floor conditions this can cause significant tire wear. No-spin recommended in applications which require improved traction. CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		\$4,850

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**SUSPENSION SYSTEMS**

**RIDE CONTROL**

The ride control option provides a suspension system by placing two accumulators in the lift circuit. Manual off and automatic mode selection. In auto mode the suspension system engages when reaching preset value. It reduces bounce caused by bucket-induced loads when traveling loaded or unloaded. For use in high speed roading, load and carry, and any other application in which load retention, bucket spillage, or operator ride may be a problem. This option is ideal for government bid specifications.

L	347-4973	NO RIDE CONTROL . . . . .	0	NC
L	478-3882	RIDE CONTROL . . . . . Axle oil cooler is recommended with ride control attachment and any high braking applications. CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL AVAILABLE FOR: ALL REGIONS EXCEPT EU	252	\$10,130
L	478-3884	RIDE CONTROL (EU) . . . . . Axle oil cooler is recommended with ride control attachment and any high braking applications. CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL AVAILABLE FOR: ALL REGIONS EXCEPT CANADA	252	\$10,130
L	541-7880	RIDE CONTROL (SM) . . . . . Axle oil cooler is recommended with ride control attachment and any high braking applications. ONLY FOR USE WITH: 552-0032 or 552-0034 LOADER, STEEL MILL AVAILABLE FOR: ALL REGIONS EXCEPT EU	0	\$13,090
L	541-7890	RIDE CONTROL (SM) (EU) . . . . . Axle oil cooler is recommended with ride control attachment and any high braking applications. ONLY FOR USE WITH: 552-0032 or 552-0034 LOADER, STEEL MILL AVAILABLE FOR: ALL REGIONS EXCEPT CANADA	0	\$13,090

**HYDRAULICS**

L	470-5053	ACCUMULATORS . . . . . AVAILABLE FOR: ALL REGIONS EXCEPT EU	0	NC
L	470-5043	ACCUMULATORS (EU) . . . . . AVAILABLE FOR: ALL REGIONS EXCEPT CANADA	0	NC

**LINE GROUPS**

**STEERING**

L	376-6936	STEERING, STANDARD . . . . . AVAILABLE FOR: ALL REGIONS EXCEPT EU	0	NC
L	376-6937	STEERING, SECONDARY . . . . . Provides a ground speed driven supplemental steering pump.	135	\$8,590



CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**ELECTRICAL**

**LIGHTS**

L	345-0538	<b>LIGHTS, STANDARD</b> ..... 0 Provides the following: Front flood/running lights (4 Halogen/all facing forward) Rear flood lights (4 Halogen/all facing rear) and 2 taillights Upper ROPS lights (6 Halogen/2 facing rear and 4 facing forward) CANNOT BE USED WITH: 589-2744 or 589-2745 LOADER, MILLYARD 552-0032 or 552-0034 LOADER, STEEL MILL		NC
L	360-8184	<b>LIGHTS, HID</b> ..... 28 Provides the following: Standard front flood/running lights (4 Halogen/all facing forward) Rear flood lights (2 HID/4 Halogen/all facing rear) and 2 taillights Upper ROPS lights (4 HID/facing forward and 4 Halogen/2 facing rear and 2 facing forward) CANNOT BE USED WITH: 589-2744 or 589-2745 LOADER, MILLYARD 552-0032 or 552-0034 LOADER, STEEL MILL		\$3,100
L	550-0283	<b>LIGHTS, LED</b> ..... 0 Provides the following: Front flood/running lights (4 LED/all facing forward) Rear flood lights (4 LED/all facing rear) and 2 taillights Upper ROPS lights (8 LED/2 facing rear and 6 facing forward) CANNOT BE USED WITH: 589-2744 or 589-2745 LOADER, MILLYARD 552-0032 or 552-0034 LOADER, STEEL MILL		\$4,100
L	550-0284	<b>LIGHTS, LED (MY, SM)</b> ..... 0 FOR USE WITH LANE 3 ONLY Provides the following: Front flood/running lights (4 LED/all facing forward) Rear flood lights (4 LED/all facing rear) and 2 taillights Upper ROPS lights (8 LED/2 facing rear and 6 facing forward) ONLY FOR USE WITH: 589-2744 or 589-2745 LOADER, MILLYARD 552-0032 or 552-0034 LOADER, STEEL MILL		\$4,100

**OPERATOR ENVIRONMENT**

**CAB PACKAGES**

NOTE: 2-point seat belts are standard. 4-point seat belts are available through parts distribution if needed.

L	561-6844	<b>CAB, BASIC</b> ..... 0 INCLUDES: -Cab door, standard window (LH) -Cab glass, standard -Cab precleaner, non-powered -Seat, heated and actively cooled -Seat belt, 3", 2-point, minder -Radio, CB (ready) CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		NC
---	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**OPERATOR ENVIRONMENT (CONT.)**

**CAB PACKAGES (Cont.)**

L	561-6875	<b>CAB, BASIC PLUS</b> . . . . . 0 INCLUDES: -Cab door, sliding window (LH) -Cab glass, standard -Cab precleaner, non-powered -Seat, heated and actively cooled -Seat belt, 3", 2-point, minder -Radio, CB (ready) CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		\$1,140
L	561-6905	<b>CAB, DELUXE</b> . . . . . 0 INCLUDES: -Cab door, standard window (LH) -Cab glass, rubber mounted -Cab precleaner, powered -Seat, heated and actively cooled -Seat belt, 3", 2-point, minder -Radio, CB (ready) CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		\$11,030
L	523-6588	<b>CAB, STEEL MILL</b> . . . . . 0 INCLUDES: -Cab door, standard window (LH) (SM) -Cab glass, rubber mounted -Cab precleaner, powered -Seat, standard -Seat belt, 3", 2-point, minder -Radio, CB (ready) ONLY FOR USE WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		\$11,950

**MIRRORS**

L	346-3864	<b>MIRRORS, STANDARD</b> . . . . . 0 CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		NC
L	376-7034	<b>MIRRORS, HEATED</b> . . . . . 6 CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		\$121
L	441-5220	<b>MIRRORS, STANDARD (SM)</b> . . . . . 14 FOR USE WITH LANE 3 ONLY Provides mirrors with metal back for steel mill applications. ONLY FOR USE WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		NC

**INTEGRATED OBJECT DETECTION SYSTEM**

L	360-8191	<b>CAMERA, REAR VISION</b> . . . . . 0 Provides an object detection system (camera only) to enhance operator awareness of surroundings. This system uses visual information only in order to provide the operator with additional information about the work area to the rear of the wheel loader. ONLY FOR USE WITH: 367-2710 or 367-2719 LOADER, STANDARD 367-2730 or 367-2739 LOADER, BLOCK HANDLER		NC
---	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**OPERATOR ENVIRONMENT (CONT.)**

**INTEGRATED OBJECT DETECTION SYSTEM (Cont.)**

L	360-8193	<b>CAMERA, REAR VISION</b> . . . . . 0 FOR USE WITH LANE 3 ONLY Provides an object detection system (camera only) to enhance operator awareness of surroundings. This system uses visual information only in order to provide the operator with additional information about the work area to the rear of the wheel loader. ONLY FOR USE WITH: 589-2744 or 589-2745 LOADER, MILLYARD 552-0032 or 552-0034 LOADER, STEEL MILL 367-2750 LOADER, EZ CLEAN		NC
L	372-3042	<b>DETECTION, OBJECT (RADAR) (C5)</b> . . . . . 19 Not available for EU. Provides an object detection system (camera & radar) to enhance operator awareness of surroundings. This system uses visual and radar information in order to provide the operator with additional information about the work area to the rear of the wheel loader. For a list of countries that RF radar is approved for use in, visit <a href="https://dealer.cat.com/detect">https://dealer.cat.com/detect</a> ONLY FOR USE WITH: 367-2710 or 367-2719 LOADER, STANDARD 367-2730 or 367-2739 LOADER, BLOCK HANDLER		\$2,835

**TECHNOLOGY PRODUCTS**

**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet.

Authorization varies by country, please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	578-9006	<b>PRODUCT LINK, CELLULAR PLE641</b> . . . . . 0 Product Link Elite series PLE641 (consisting of PL641 radio and PLE601 network manager) uses cellular networks to transmit location, utilization, health and productivity information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		NC
L	509-4150	<b>PRODUCT LINK, SATELLITE PLE631</b> . . . . . 0 Product Link Elite series PLE631 (consisting of PL631 radio and PLE601 network manager) uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		\$439

**FUEL SYSTEMS**

**FUEL TANKS**

L	519-9949	<b>FUEL TANK, NON-FAST FILL</b> . . . . . 0 CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		NC
---	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**FUEL SYSTEMS (CONT.)**

***FUEL TANKS (Cont.)***

L	519-9950	FUEL TANK, FAST FILL . . . . . 0 Provides fast fill adaption with automatic shutoff. CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		\$1,960
L	519-9951	FUEL TANK, STEEL MILL . . . . . 0 FOR USE WITH LANE 3 ONLY Provides thicker wall fuel tank without fast fill receiver port for steel mill applications. ONLY FOR USE WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		\$2,270

***FUEL LINES***

L	433-3842	FUEL LINES, NON-HEATED . . . . . 0		NC
L	433-3843	FUEL LINES, HEATED . . . . . 16		\$1,045

**TIRES, RIMS, AND WHEELS**

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice. However, if the tire type cannot be supplied we will contact the dealer to propose alternatives. The dealer needs to choose between an alternative tire or a "rims only" option (where available) within 72 hours. If no response is provided by the deadline, the order will default to the alternative tire and will be changed at that point. As a consequence of a possible tire change, the total machine price will be decreased or increased depending on the price of the new tire.

NOTE: All tires are tubeless, include heavy duty rims and come in a set of 4.

NOTE: 42PR tires may be used to improve lateral stability. Recommended for use with uneven floors and/or high truck loading heights with dense materials.

NOTE: Tires with HLA rims have tires mounted on rims for Heavy Load Applications. These are required for machines in block handler and millyard applications and any other application where higher loads may be encountered.

NOTE: Block Handler and Millyard orders require 42PR or \*\* tires with HLA rims.

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**TIRES, RIMS, AND WHEELS (CONT.)**

**TIRES AVAILABLE FROM BRIDGESTONE**

P	490-7503	<b>TIRES, 35/65-33 BS 42PR L5</b> ..... 0 Bridgestone Bias DL; Tread Depth=97mm (122/32"); Rim=28"x33" 4 piece Suitable for severe rock environments where maximum damage protection is needed. CANNOT BE USED WITH: Block Handler or Millyard orders		\$9,630
P	452-4111	<b>TIRES, 35/65-33 BS 42PR L5 HLA</b> ..... 6,210 Same tire as above, but with Heavy Load Application rims. HLA rims are required for block handler and millyard applications and any other application where higher loads may be encountered.		\$15,730
P	490-7504	<b>TIRES, 35/65R33 BS VSNT ** L4</b> ..... 0 Bridgestone Radial; Tread Depth=62.5mm (79/32"); Rim=28"x33" 4 piece Provides damage resistance, mobility, and traction in moderate rock environments. CANNOT BE USED WITH: Block Handler or Millyard orders		\$-200
P	493-6840	<b>TIRES, 35/65R33 BS ** L4 HLA</b> ..... 0 Same tire as above, but with Heavy Load Application rims. HLA rims are required for block handler and millyard applications and any other application where higher loads may be encountered.		\$5,900
P	499-5790	<b>TIRES, 35/65R33 BS VSDL ** L5</b> ..... 2,772 Bridgestone Radial; Tread Depth=95mm (120/32"); Rim=28"x33" Suitable for severe rock environments where maximum damage protection is needed. CANNOT BE USED WITH: Block Handler or Millyard orders		\$14,580
P	452-4118	<b>TIRES, 35/65R33 BS ** L5 HLA</b> ..... 1,610 Bridgestone Radial VSDL IDU with Heavy Load Application rims. HLA rims are required for block handler and millyard applications and any other application where higher loads may be encountered.		\$26,900

**TIRES AVAILABLE FROM MICHELIN**

P	478-4157	<b>TIRES, 35/65R33 MX *** L4</b> ..... 0 Michelin Radial XTXL; Tread Depth=60mm (76/32"); Rim=28"x33" Directional tire that provides damage resistance, mobility, and traction in moderate rock environments. CANNOT BE USED WITH: Block Handler or Millyard orders		\$13,650
P	396-4287	<b>TIRES, 35/65R33 MX ** L5</b> ..... 0 Michelin Radial XLDD2; Tread Depth=97mm (122/32"); Rim=28"x33" Directional tire suitable for severe rock environments where maximum damage protection is needed. CANNOT BE USED WITH: Block Handler or Millyard orders		\$16,880

**TIRES, ALLOWANCE FOR OMISSION**

P	396-4156	<b>RIMS ONLY, TIRES OMITTED</b> ..... -7,964 CANNOT BE USED WITH: Block Handler or Millyard orders		\$-37,860
P	442-6345	<b>RIMS ONLY (HLA), TIRES OMITTED</b> ..... -9,152 Provides Heavy Load Application rims. HLA rims are required for machines in block handler and millyard applications and any other application where higher loads may be encountered.		\$-32,060

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**OTHER ATTACHMENTS**

**SOUND SUPPRESSION**

L	347-5105	<b>NO SOUND SUPPRESSION</b> . . . . . 0		NC
		Operator sound pressure level: 72 dB(A) per ISO 6396 Machine sound power level: 111 dB(A) per ISO 6395 ONLY FOR USE WITH: 347-5000 988K WHEEL LOADER HRC CANNOT BE USED WITH: 141-5066 EU CERTIFICATION		
L	347-5125	<b>SOUND SUPPRESSION</b> . . . . . 298		\$4,955
		Operator sound pressure level: 72 dB(A) per ISO 6396 Machine sound power level: 109 dB(A) per ISO 6395 REQUIRES: 435-1165 GUARD, BOTTOM 372-9038 GUARD, CRANKCASE ONLY FOR USE WITH: 347-5000 988K WHEEL LOADER HRC		

**WHEEL CHOCKS**

L	541-8669	<b>NO WHEEL CHOCKS</b> . . . . . 0		NC
		ONLY FOR USE WITH: 367-2710 or 367-2719 LOADER, STANDARD or 367-2730 or 367-2739 LOADER, BLOCK HANDLER		
L	541-8671	<b>NO WHEEL CHOCKS (EZ CLEAN)</b> . . . . . 0		NC
		ONLY FOR USE WITH: 589-2744 or 589-2745 LOADER, MILLYARD or 367-2750 LOADER, EZ CLEAN		
L	0P-4780	<b>NO WHEEL CHOCKS (SM)</b> . . . . . 0		NC
		ONLY FOR USE WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		
L	541-8670	<b>WHEEL CHOCKS</b> . . . . . 0		\$1,725
		Includes wheel chocks and an integrated storage system. REQUIRES: 143-3604 MIRRORS, HANDRAIL MOUNTED CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		

**FLUIDS**

**HYDRAULIC OIL**

L	435-1144	<b>HYDRAULIC OIL, STANDARD</b> . . . . . 0		NC
L	435-1164	<b>HYDRAULIC OIL, ARCTIC</b> . . . . . 89		\$6,329
		Installs 0W-20 CAT TDTO Cold Weather Oil in place of standard 10W HYDO-10 hydraulic oil. For use in cold climates for ambient temperature down to -40C (-40F).		
L	435-1154	<b>HYDRAULIC OIL, ECOSAFE</b> . . . . . 89		\$3,806
		Installs EcoSafe FR46 hydraulic fluid.		

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**SPECIAL ARRANGEMENTS**

L	367-5432	<b>COOLER, AXLE OIL</b> . . . . . 405 Axle oil cooler attachment is recommended with ride control for long downhill grades or any high braking applications. ONLY FOR USE WITH: 367-2710 or 367-2719 LOADER, STANDARD 367-2730 or 367-2739 LOADER, BLOCK HANDLER		\$11,370
L	541-7900	<b>COOLER, AXLE OIL</b> . . . . . 0 FOR USE WITH LANE 3 ONLY Axle oil cooler attachment for use with the swing out fan system included in the steel mill and millyard loaders. ONLY FOR USE WITH: 589-2744 or 589-2745 LOADER, MILLYARD 552-0032 or 552-0034 LOADER, STEEL MILL 367-2750 LOADER, EZ CLEAN		\$10,470
L	435-1223	<b>GUARD, HYDRAULIC TANK</b> . . . . . 19 FOR USE WITH LANE 3 ONLY Required for and only for steel mill orders when not ordering axle oil cooler.		\$148

**STARTERS, BATTERIES, & ALTERNATORS**

**STARTING ARRANGEMENT**

L	374-6450	<b>STARTING, COLD WEATHER</b> . . . . . 94 Includes 1 additional starter and 2 additional batteries.		\$1,755
---	----------	---	--	---------

**STARTING AIDS**

L	374-7404	<b>HEATER, ENGINE COOLANT, 120V</b> . . . . . 1 110/120-volt external power source required.		\$358
---	----------	---	--	-------

**ELECTRICAL**

L	376-7128	<b>LIGHT, WARNING (LED STROBE)</b> . . . . . 17 ***DEALER INSTALLED ATTACHMENT***		\$710
---	----------	--	--	-------

**OPERATOR ENVIRONMENT**

L	504-5735	<b>RADIO, AM/FM/AUX</b> . . . . . 0		\$745
L	376-7135	<b>RADIO, AM/FM/AUX/USB/BT/CD/SAT</b> . . . . . 6 BlueTooth radio technology enables the use of a hands free function such as listening to music and making phone calls. Authorization varies by country, please contact your Cat marketing representative with questions or click on the link below: <a href="https://dealer.cat.com/en/products/technology.html">https://dealer.cat.com/en/products/technology.html</a> Requires service contract with satellite radio provider.		\$1,655
L	346-3863	<b>VISOR, CAB</b> . . . . . 2		\$174
L	143-3604	<b>MIRRORS, HANDRAIL MOUNTED</b> . . . . . 26 Provides rear view outboard handrail mounted mirrors. REQUIRED BY: 541-8670 WHEEL CHOCKS		\$605

CATERPILLAR MACHINE PRICE LIST

988K

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS

**SOFTWARE ENABLED ATTACHMENTS (SEA) INSTRUCTIONS**  
 Technology apps are activated by Software Enabled Attachments (SEA). SEAs are available factory installed or can be purchased for dealer installation.

Refer to Information Release Memo (IRM) EES03 -01 (media number PELJ0138) in the Caterpillar Media Information Center for further explanation of SEAs. Select the Product Support tab and search for number PELJ0138. Refer to REHS1238 & REHS8401 for how to obtain a Factory Level Password. Contact FPS: Internet with Corporate Web Security (CWS) ([https:// fps.cat.com/](https://fps.cat.com/)).

**CAT PRODUCTION MEASUREMENT (CPM) PAYLOAD WEIGHING SYSTEM**  
 CPM includes an integrated onboard payload weighing scale with material management, cycle count & time recording and wireless production detail reporting capability.  
 -Payload & cycle totals are sent wirelessly to VisionLink. (Cat Essentials subscription required.)  
 -Detailed payload reports and KPI metrics can be visualized on-line and downloaded for further analysis, with a subscription to Cat Advanced Productivity. (First 6 months included with purchase of CPM; subscription fee applies thereafter. Requires PLE641 cellular Product Link.) Payload detail may also be downloaded via a wired connection between the loader and a laptop computer for analysis in VIMSpC software (requires purchase of VIMSpC software and VIMS data cable).

Refer to <https://dealer.cat.com> for complete technical specifications; operation, sales, marketing and technical support publications.

NOTES:

- 1) Demo and permanent software are available from the factory.
- 2) For field installation, permanent software can be purchased through the Caterpillar Feature Protection System and enabled by a dealer technician with Cat ET and an SEA password. SEA p/n 539-6076. Consult ANTARES parts distribution system for latest SEA price.
- 3) Both demo and permanent software require calibration prior to customer use.

CALIBRATION INSTRUCTIONS

This app requires calibration and set-up by either the dealer or customer. Refer to the Systems Operation Test & Adjust manual UENR7119 for system calibration, material and truck ID lists set-up and operation instructions.

L	467-5822	CPM PAYLOAD WEIGHING READY . . . . . 0		NC
		Includes hardware and demo software for CPM, dealer enabled for up to 250 hours. To activate demo software, it must be enabled by a dealer technician with Cat ET. No password is required. For permanent software activation in the field, purchase of software is required. See note 2 above for details.		
		CANNOT BE USED WITH: 589-2744 or 589-2745 LOADER, MILLYARD		



CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**TECHNOLOGY PRODUCTS (CONT.)**

L	467-5833	CPM PAYLOAD WEIGHING . . . . . 0 Includes hardware and permanent software for CPM. Software is factory enabled, but the system must be calibrated prior to customer use. See note above for calibration instructions. CANNOT BE USED WITH: 589-2744 or 589-2745 LOADER, MILLYARD		\$6,270
L	378-8634	PRINTER, PAYLOAD . . . . . 5 Provides onboard ticket printing capability for Cat Production Measurement (CPM).		\$2,495

**COOLING**

L	347-5185	COOLING, HIGH AMBIENT . . . . . 0 Provides increased air flow through software. Recommended for ambient temperatures up to 50C (122F).		NC
---	----------	--	--	----

**TIRES, RIMS, AND WHEELS**

***TIRE PRESSURE MONITORING SYSTEM***

L	543-7141	MONITORING, TIRE PRESSURE . . . . . 0 Provides four sensors that mount to the valve stem of each tire along with a receiver module that monitors both pressure and temperature in each tire. Tire pressure and temperature information is shared with the operator via the info display. Warnings are provided through Unified Fleet if pressure is outside of a configurable target range. The system is not recommended for use on tires with liquid additives or sealants. CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		\$3,045
---	----------	--	--	---------

**GUARDS**

L	435-1165	GUARD, BOTTOM . . . . . 104 INCLUDED IN: 435-1155 GUARDS, HEAVY DUTY REQUIRED BY: 347-5125 SOUND SUPPRESSION 347-4919 SOUND SUPPRESSION		\$3,065
L	372-9038	GUARD, CRANKCASE . . . . . 107 INCLUDED IN: 435-1155 GUARDS, HEAVY DUTY REQUIRED BY: 347-5125 SOUND SUPPRESSION 347-4919 SOUND SUPPRESSION		\$725
L	347-5138	GUARD, STEERING CYLINDER . . . . . 103 INCLUDED IN: 435-1155 GUARDS, HEAVY DUTY REQUIRED BY: 141-5066 EU CERTIFICATION		\$1,315

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**GUARDS (CONT.)**

L	435-1155	<b>GUARDS, HEAVY DUTY</b> . . . . . 589 FOR USE WITH LANE 3 ONLY Includes a front guard and tilt cylinder rod guard, in addition to the guards below: 435-1165 GUARD, BOTTOM 372-9038 GUARD, CRANKCASE 347-5138 GUARD, STEERING CYLINDER CANNOT BE USED WITH: 367-2730 or 367-2739 LOADER, BLOCK HANDLER 589-2744 or 589-2745 LOADER, MILLYARD REQUIRED BY: 552-0032 or 552-0034 LOADER, STEEL MILL		<b>\$4,860</b>
---	----------	---	--	----------------

**OTHER ATTACHMENTS**

**MISCELLANEOUS ATTACHMENTS**

L	459-6446	<b>COVER, INLET GRILL (CW)</b> . . . . . 0 Provides inlet grill covers for extended idling in cold weather. Recommended for ambient temperatures of -10C (14F) and below. ONLY FOR USE WITH: 347-5000 988K WHEEL LOADER HRC and 367-2710 LOADER, STD or 367-2730 LOADER, BH		<b>\$3,640</b>
L	347-5028	<b>FENDERS, ROADING</b> . . . . . 315 Provides full coverage front and rear fenders.		<b>\$5,170</b>
L	376-1572	<b>OIL CHANGE SYSTEM, HIGH SPEED</b> . . . . . 5 Provides remote port and components for high speed oil change.		<b>\$595</b>

**AGGREGATE HANDLER**

L	481-3972	<b>AGGREGATE HANDLER, STD LIFT</b> . . . . . 0 Provides additional counterweight for the Aggregate Handler, which allows customers to maximize machine payload in re-handling applications. Reference salesgram TEKQ1233-01. REQUIRES: 347-4900 LIFT, STANDARD 2V or 347-4910 LIFT, STANDARD 3V or 472-7125 LIFT, STANDARD 2V, EZ CLEAN and GENERAL PURPOSE or COAL BUCKET		<b>\$13,980</b>
L	481-3973	<b>AGGREGATE HANDLER, HIGH LIFT</b> . . . . . 0 Provides additional counterweight for the Aggregate Handler, which allows customers to maximize machine payload in re-handling applications. Reference salesgram TEKQ1233-01. REQUIRES: 347-4920 LIFT, HIGH 2V or 347-4930 LIFT, HIGH 3V or 516-3924 LIFT, HIGH 2V, EZ CLEAN and GENERAL PURPOSE or COAL BUCKET		<b>\$21,530</b>

**QUICK COUPLERS**

L	445-2500	<b>QUICK COUPLER.</b> . . . . . 3,803 FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 347-4910 LIFT, STANDARD 3V		<b>\$28,126</b>
L	471-3510	<b>QUICK COUPLER.</b> . . . . . 3,829 FOR USE WITH LANE 3 ONLY ONLY FOR USE WITH: 347-4930 LIFT, HIGH 3V		<b>\$30,569</b>

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**QUICK COUPLERS (CONT.)**

L	420-7700	<b>QUICK COUPLER, BLOCK HANDLING</b> . . . . .	3,523	<b>\$28,126</b>
		FOR USE WITH LANE 3 ONLY		
		ONLY FOR USE WITH: 367-2726 LIFT, STANDARD 3V, BLOCK HANDLER		

**WORK TOOLS**

***FORKS***

Loose forks should be ordered on a MISC Order through Caterpillar Work Tools - Wamego using source code OP-4740. For availability of loose forks please email [worktools@cat.com](mailto:worktools@cat.com).

If you are going to order a loose fork from CWTS and a machine from Decatur and if you need them shipped at the same time then you need to cross-reference the MSO's with each other.

L	460-5270	<b>FORK, BLOCK HANDLING, QC</b> . . . . .	8,163	<b>\$41,183 NI</b>
		FOR USE WITH LANE 3 ONLY		
		82" (2100mm) Carriage and 71" (1810mm) non-swinging tines		
		Maximum width over tines: 63.39" (1610mm)		
		TINE WIDTH: 15.57" (400mm)		
		TINE THICKNESS: 5.9" (150mm)		
		ONLY FOR USE WITH: 420-7700 QUICK COUPLER, BLOCK HANDLING		
L	431-6176	<b>FORK, LOGGING</b> . . . . .	16,570	<b>\$106,383 NI</b>
		FOR USE WITH LANE 3 ONLY		
		109" (2769mm) Carriage, 94" (2388mm) Tines		
		INCLUDES: Double top clamp, fixed tines, solid tips		
		INSIDE HEIGHT: 115" (2921mm)		
		ONLY FOR USE WITH: 589-2744 or 589-2745 LOADER, MILLYARD		

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**BUCKETS**

For questions on buckets intended for Machine Orders please contact your Marketing Subsidiary Machine Coordinator.

Loose buckets should be ordered on a MISC Order through Caterpillar Work Tools - Wamego using source code OP-4740. For availability of loose buckets please email [worktools@cat.com](mailto:worktools@cat.com).

If you are going to order a loose bucket from CWTS and a machine from Decatur and if you need them shipped at the same time then you need to cross-reference the MSO's with each other.

"GET" is NOT automatically included on bucket orders. "GET" must be entered on the order with your bucket selection, unless text for bucket states otherwise. Please make the "GET" selection from the "GET" listed immediately following the bucket listing. Rock bucket selections list "GET" for spade or straight edge.

Material density will determine the appropriate capacity bucket. Refer to the Specalog. Exceeding maximum payload may cause loader instability.

All listed Maximum Recommended Material Densities are based on the maximum gross weight that the 988K is rated for minus the weight of the bucket and all required G.E.T. at 100% fill factor.

EXPORT ORDERS - If you are ordering a LOADER, STANDARD & BUCKET, then you must order your BUCKET as Not Installed (NI).

QUEBEC ORDERS - If ordering a Bucket, then you must order it as Not Installed (NI).

**GENERAL PURPOSE BUCKETS**

Use for excavating and bank loading material requiring breakout force as well as stockpile / rehandling applications. Includes casted corner in sidebar for Corner Guard System GET.

P	<b>347-4980</b>	<b>BUCKET-GP, 152" 9.00 YD3</b> . . . . .	10,007 10,007	<b>\$48,368</b> <b>\$48,368 NI</b>
		Maximum Recommended Material Density: 1660 kg/m3 (2800 lb/yd3)		
		6.7M3(8.7YD3) w/bolt-on adapters, K110, 3988mm (157") wide		
		6.9M3(9.0YD3) w/bolt-on adapters & segments, K110, 3988mm (157") wide		
		6.9M3(9.0YD3) w/bolt-on cutting edge system, 3962mm (156") wide		
P	<b>347-4990</b>	<b>BUCKET-GP, 152" 10.00YD3</b> . . . . .	10,536 10,536	<b>\$50,954</b> <b>\$50,954 NI</b>
		Maximum Recommended Material Density: 1510 kg/m3 (2550 lb/yd3)		
		7.4M3(9.7YD3) w/bolt-on adapters, K110, 3988mm (157") wide		
		7.6M3(10.0YD3) w/bolt-on adapters & segments, K110, 3988mm (157") wide		
		7.6M3(10.0YD3) w/bolt-on cutting edge system, 3962mm (156") wide		

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**BUCKETS (CONT.)**

**GENERAL PURPOSE BUCKETS (Cont.)**

P	435-4029	BUCKET-GP, 152" 11.00 YD3 . . . . .	11,005 11,005	\$52,424 \$52,424 NI
		Maximum Recommended Material Density: 1450 kg/m3 (2440 lb/yd3)		
		8.2M3(10.7YD3) w/bolt-on adapters, K110, 3988mm (157") wide		
		8.4M3(11.0YD3) w/bolt-on adapters & segments, K110, 3988mm (157") wide		
		8.4M3(11.0YD3) w/bolt-on cutting edge system, 3962mm (156") wide		
P	472-0120	BUCKET-GP, 152" 12.50YD3 . . . . .	11,828 11,828	\$56,597 \$56,597 NI
		Maximum Recommended Material Density: 1590 kg/m3 (2680 lb/yd3)		
		9.3M3(12.2YD3) w/bolt-on adapters, K110, 3988mm (157") wide		
		9.6M3(12.5YD3) w/bolt-on adapters & segments, K110, 3988mm (157") wide		
		9.6M3(12.5YD3) w/bolt-on cutting edge system, 3962mm (156") wide		
		REQUIRES: 481-3972 AGGREGATE HANDLER, STD LIFT or		
		481-3973 AGGREGATE HANDLER, HIGH LIFT		

**GET for GENERAL PURPOSE BUCKETS**

(includes mounting hardware)

P	208-5262	CUTTING EDGE, BOLT-ON . . . . .	1,119	\$2,924
		40mm thick w/40mm end bits		
P	174-7950	GUARD, CORNER . . . . .	139	\$1,065
		REQUIRES: 208-5262 CUTTING EDGE, BOLT-ON		
P	232-0167	ADAPTERS, BOLT ON, SET OF 8 . . . . .	1,281	\$3,479
		45mm thick		
		ONLY FOR USE WITH: K110 tips		
P	217-4652	SEGMENTS, BOLT-ON, SET OF 7 . . . . .	702	\$2,650
		45mm thick. Use with STRAIGHT buckets.		
		ONLY FOR USE WITH: K110 adapters and tips		
P	309-1123	TIP, PENETRATION . . . . .	24	\$158
		Recommended for harder-to-penetrate, moderate impact, low-to-moderate abrasive materials. Very good penetration, less wear material.		
		ONLY FOR USE WITH: K110 adapters		
P	309-1127	TIP, GENERAL DUTY . . . . .	27	\$271
		Recommended for general application in moderate impact and abrasive conditions. Good penetration, (2) self-sharpening cavities.		
		ONLY FOR USE WITH: K110 adapters		
P	309-1122	TIP, EXTRA DUTY . . . . .	38	\$183
		Recommended for general applications requiring more wear material in moderate-to-high impact conditions. Good wear material, good penetration.		
		ONLY FOR USE WITH: K110 adapters		

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**BUCKETS (CONT.)**

**ROCK BUCKETS**

Use for bank or face loading in most tough digging conditions.

For GCN1 dealers only:

Buckets in this section need to be ordered through a separate CMOPS order to CWTS, even if required for a new machine order. Please include the machine MSO on your bucket order. Please communicate with your local Sales Rep to confirm bucket price before placing your order into the system.

P	498-9988	<b>BUCKET-ROCK, 158" 8.30YD3</b> . . . . .	10,781 10,781	<b>\$66,286</b> <b>\$66,286 NI</b>
		SPADE EDGE Maximum Recommended Material Density: 1771 kg/m3 (2985 lb/yd3) INCLUDES: (8) weld-on double strap Advansys adapters, outer side wear plates, and 35mm bolt-on heel plates. OPTIONAL: sidebar protectors and base edge wear plates REQUIRES: (8) Advansys 130 tips and (1) segment group		
P	498-9990	<b>BUCKET-ROCK, 158" 9.00YD3</b> . . . . .	11,120 11,120	<b>\$68,401</b> <b>\$68,401 NI</b>
		SPADE EDGE Maximum Recommended Material Density: 1643 kg/m3 (2769 lb/yd3) INCLUDES: (8) weld-on double strap Advansys adapters, outer side wear plates, and 35mm bolt-on heel plates. OPTIONAL: sidebar protectors and base edge wear plates REQUIRES: (8) Advansys 130 tips and (1) segment group		
P	498-9992	<b>BUCKET-ROCK, 158" 10.00YD3</b> . . . . .	11,627 11,627	<b>\$71,789</b> <b>\$71,789 NI</b>
		SPADE EDGE Maximum Recommended Material Density: 1491 kg/m3 (2514 lb/yd3) INCLUDES: (8) double strap Advansys adapters, outer side wear plates, and 35mm bolt-on heel plates. OPTIONAL: sidebar protectors and base edge wear plates REQUIRES: (8) Advansys 130 tips and (1) segment group		

**GET for ROCK BUCKETS**

(includes mounting hardware)

P	109-9051	<b>SEGMENT, BOLT-ON, SET OF 7</b> . . . . .	580	<b>\$2,650</b>
		40mm thick. Use with SPADE buckets.		
P	107-3533	<b>SEGMENTS, HD, BOLT-ON, SET OF 7</b> . . . . .	400	<b>\$2,204</b>
		45mm thick. Use with SPADE buckets.		
P	124-6346	<b>SEGMENTS, H.A., BOLT-ON, SET OF 7</b> . . . . .	805	<b>\$2,792</b>
		45mm thick, Half Arrow. Use with SPADE buckets.		
P	232-0161	<b>SEGMENTS, H.A., BOLT-ON, SET OF 7</b> . . . . .	1,011	<b>\$3,892</b>
		50mm thick base edges, Half Arrow. Use with SPADE buckets. Includes 45mm thick half-arrow protectors and top-mounted wear plates.		
P	381-4095	<b>TIP, HEAVY PENETRATION</b> . . . . .	65	<b>\$354</b>
		ONLY FOR USE WITH: Advansys 130 adapters		
P	381-4096	<b>TIP, HEAVY ABRASION</b> . . . . .	68	<b>\$383</b>
		ONLY FOR USE WITH: Advansys 130 adapters		
P	368-3791	<b>TIP, HEAVY DUTY</b> . . . . .	57	<b>\$293</b>
		ONLY FOR USE WITH: Advansys 130 adapters		
P	368-3857	<b>TIP, HVY DUTY LONG LIFE (ARM)</b> . . . . .	60	<b>\$568</b>
		ONLY FOR USE WITH: Advansys 130 adapters		

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**BUCKETS (CONT.)**

**GET for ROCK BUCKETS (Cont.)**

P	486-6524	TIP HEAVY ABR LONG LIFE (ARM) . . . . .	70	\$643
		ONLY FOR USE WITH: Advansys 130 adapters		
P	368-3859	TIP, SHORT . . . . .	45	\$200
		ONLY FOR USE WITH: Advansys 130 adapters		
P	381-4094	TIP, GENERAL DUTY . . . . .	51	\$232
		ONLY FOR USE WITH: Advansys 130 adapters		
P	368-3860	TIP, COAL . . . . .	45	\$200
		ONLY FOR USE WITH: Advansys 130 adapters		
P	356-6437	PROTECTORS, SIDEBAR, SET OF 2 . . . . .	104	\$1,143
		Set of two, one for RH and one for LH side of the bucket.		
		ONLY FOR USE WITH: ROCK BUCKETS ONLY		
P	494-8224	PROTECTORS, SIDEBAR, SET OF 4 . . . . .	207	\$2,285
		Set of four, two for RH and two for LH side of the bucket.		
		ONLY FOR USE WITH: ROCK BUCKETS ONLY		
P	364-6636	PLATE GP-WEAR . . . . .	195	\$564
		Bolt-On Bottom, Rear Base Edge Wear Plates		
		25mm Thick Wear Plate		

**HEAVY DUTY ROCK BUCKETS**

Use for bank or face loading in high abrasion and moderate impact conditions.

P	498-9994	BUCKET-ROCK, 160" 8.30YD3 . . . . .	14,072	\$79,553
			14,072	\$79,553 NI
		SPADE EDGE		
		Maximum Recommended Material Density: 1771 kg/m3 (2985 lb/yd3)		
		INCLUDES: (8) weld-on double strap Advansys adapters, cutting edge with weld-on base edge end protection, floor liner, radius liner, inside and outside wear plates, (1) 45mm bolt-on half arrow segment group, 25mm bolt-on base edge bottom wear plates, (2) sets of sidebar protectors and wings (rock deflectors).		
		REQUIRES: (8) Advansys 130 tips		

**HEAVY DUTY GRANITE BUCKETS**

P	498-9996	BUCKET-ROCK, 157" 8.30YD3 . . . . .	16,455	\$92,138
			16,455	\$92,138 NI
		SPADE EDGE		
		Maximum Recommended Material Density: 1658 kg/m3 (2795 lb/yd3)		
		INCLUDES: (7) weld-on Advansys 130 flushmount adapters on a 64mm thick cutting edge with weld-on base edge end protection adapter covers, full shell liner, inside and outside wear plates, bolt-on top cutting edge protection, (1) 45mm bolt-on half arrow segment group with top covers, 25mm bolt-on base edge bottom wear plates, heel shrouds, (2) sets of sidebar protectors, 30-Series MAWPs for bottom wear protection and a stronger rock guard design.		
		REQUIRES: (7) Advansys 130 tips		

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**BUCKETS (CONT.)**

**IRON ORE BUCKETS**

P	498-9998	BUCKET-ROCK, 154" 6.20YD3 . . . . .	12,767 12,767	\$71,019 \$71,019 NI
		Iron ore design w/ lower capacity SPADE EDGE Maximum Recommended Material Density: 2412 kg/m3 (4065 lb/yd3) INCLUDES: (7) weld-on Advansys 130 double strap adapters on a 64mm thick cutting edge with weld-on base edge end protection floor liner, radius liner, inside and outside wear plates, (1) 75mm bolt-on half arrow segment group, 22mm bolt-on base edge bottom wear plates, 35mm weld-on heel plates, (2) sets of sidebar protectors REQUIRES: (7) Advansys 130 tips		

**GET for HD ROCK / HD GRANITE / IRON ORE BUCKETS**

(includes mounting hardware)

P	381-4095	TIP, HEAVY PENETRATION . . . . .	65	\$354
		Recommended for high abrasive and impact conditions, especially shot rock. Excellent penetration and wear material. ONLY FOR USE WITH: Advansys 130 adapters		
P	381-4096	TIP, HEAVY ABRASION . . . . .	68	\$383
		Recommended for high abrasive, moderate impact, easier-to-penetrate materials. Excellent wear material, less penetration. ONLY FOR USE WITH: Advansys 130 Adapters		

**SERRATED EDGE BUCKETS**

P	416-5162	BUCKET-ROCK, 156" 9.0 YD3 . . . . .	12,421 12,421	\$63,039 \$63,039 NI
		SERRATED V-SPADE EDGE Maximum Recommended Material Density: 1660 kg/m3 (2800 lb/yd3)		
P	428-9115	BUCKET-ROCK, 156" 8.30 YD3 . . . . .	12,026 12,026	\$60,907 \$60,907 NI
		SERRATED V-SPADE EDGE Maximum Recommended Material Density: 1810 kg/m3 (3050 lb/yd3)		

**COAL BUCKETS**

P	433-4750	BUCKET-COAL, 162" 15.0 YD3 . . . . .	13,278 13,278	\$50,779 \$50,779 NI
		STRAIGHT EDGE Maximum Recommended Material Density: 1130 kg/m3 (1910 lb/yd3) INCLUDES: Bolt-On Cutting Edge (BOCE)		
P	433-4740	BUCKET-COAL, 162" 17.0 YD3 . . . . .	14,186 14,186	\$57,407 \$57,407 NI
		STRAIGHT EDGE Maximum Recommended Material Density: 900 kg/m3 (1520 lb/yd3) INCLUDES: Bolt-On Cutting Edge (BOCE)		



CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**BUCKETS (CONT.)**

**SPECIAL APPLICATION BUCKETS**

P	421-6100	BUCKET-SLAG, 159" 8.30 YD3 . . . . .	18,638 18,638	\$77,561 \$77,561 NI
		SPADE EDGE Maximum Recommended Material Density: 1735 kg/m3 (2925 lb/yd3) INCLUDES: Weld-on serrated spade edge segments and half arrow sidebar protection		
P	435-1810	BUCKET-SLAG, 154" 7.00 YD3 . . . . .	16,828 16,828	\$72,614 \$72,614 NI
		Straight edge with J600 double strap adapters Maximum Recommended Material Density: 1900 kg/m3 (3210 lb/yd3) INCLUDES: (8) J600 double strap adapters, weld-on half arrow segments, weld-on sidebar protection and full paddleplate design REQUIRES: (8) J600 tips		

**GET for SPECIAL APPLICATION BUCKETS**

P	6I-6420	TIP, ABRASION, HEAVY DUTY . . . . .	74	\$571
		ONLY FOR USE WITH: J600 adapters and 335-7160 SLAG BUCKET ONLY		

**BLOCK HANDLING BUCKETS**

L	478-6135	BUCKET-ROCK, 158" 9.00YD3 . . . . .	12,635 12,635	\$61,804 \$61,804 NI
		FOR USE WITH LANE 3 ONLY SPADE EDGE Maximum Recommended Material Density 2800 lb/yd3 (1660 kg/m3) INCLUDES: (8) Weld-On K130 Double Strap Adapters REQUIRES: (8) K130 tips and (1) segment group ONLY FOR USE WITH: 420-7700 QUICK COUPLER, BLOCK HANDLING		

**GET for BLOCK HANDLING BUCKETS**

P	109-9051	SEGMENT, BOLT-ON, SET OF 7 . . . . .	580	\$2,650
		40mm thick. Use with SPADE buckets.		
P	107-3533	SEGMENTS, HD, BOLT-ON, SET OF 7 . . . . .	400	\$2,204
		45mm thick. Use with SPADE buckets.		
P	124-6346	SEGMENTS, H.A., BOLT-ON, SET OF 7 . . . . .	805	\$2,792
		45mm thick, Half Arrow. Use with SPADE buckets.		
P	232-0161	SEGMENTS, H.A., BOLT-ON, SET OF 7 . . . . .	1,011	\$3,892
		50mm thick base edges, Half Arrow. Use with SPADE buckets. Includes 45mm thick half-arrow protectors and top-mounted wear plates.		
P	229-7129	TIP, GENERAL DUTY . . . . .	42	\$221
		Recommended for general applications in moderate impact and abrasive conditions. Good penetration, (2) self-sharpening cavities. ONLY FOR USE WITH: K130 adapters		
P	229-7121	TIP, EXTRA DUTY . . . . .	55	\$278
		Recommended for general applications requiring more wear material in moderate-to-high impact conditions. Good wear material, good penetration. ONLY FOR USE WITH: K130 adapters		
P	229-7122	TIP, PENETRATION . . . . .	37	\$226
		Recommended for harder-to-penetrate, moderate impact, low-to-moderate abrasive materials. Very good penetration, less wear material. ONLY FOR USE WITH: K130 Adapters		

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**BUCKETS (CONT.)**

**GET for BLOCK HANDLING BUCKETS (Cont.)**

P	229-7125	TIP, HEAVY PENETRATION . . . . .	69	\$335
		Recommended for high abrasive and impact conditions, especially shot rock. Excellent penetration and wear material. ONLY FOR USE WITH: K130 adapters		

**FLUIDS**

**ANTIFREEZE**

Standard machine includes antifreeze protection to -34C (-29F).  
Different lubricants are also required for extreme temperatures.  
Please refer to operation and maintenance manual.

P	0P-2411	COOLANT, -50C (-58F) . . . . .	0	\$520 NET
---	---------	--------------------------------	---	-----------

**FACTORY SOURCED KITS**

**OBJECT DETECTION KITS**

Please consult the DETECTCAT retrofit price list for dealer installed Object Detection kits on Large Wheel Loaders.

**RETRO-FIT KITS for CURRENT 988K**

If ordering on a MISC MSO, you need to use 0P-4742 for TOP LEVEL and 0P-0812 for PACKING.

Kits must be ordered as NOT-INSTALLED.

No returns on Kit components or for parts removed.

C	557-9861	KIT, AXLE OSCILLATION STOP . . . . .	0	\$373 NI
		988K Ser# TWX00001 & up, T8E00001 & up, LWX00001 & up, L8X00001 & up Provides clearance to accommodate L5 slick tires or machines equipped with tire chains. Limits rear axle oscillation to +/- 6 degrees. Reference special instruction M0094697-00. REQUIRED BY: 552-0032 or 552-0034 LOADER, STEEL MILL		
C	560-2915	KIT, TIRE PRESSURE MONITORING . . . . .	0	\$3,170 NI
		988K Ser# TWX01247 & up, T8E00001 & up, LWX00756 & up, L8X00001 & up Provides four sensors that mount to the valve stem of each tire along with a receiver module that monitors both pressure and temperature in each tire. Tire pressure and temperature information is shared with the operator via the primary display. Warnings are provided through Unified Fleet if pressure is outside of a configurable target range. Software license for Cat Tire Pressure Monitoring (TPM) will be a separate charge. Requires SEA for permanent activation.		

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FACTORY SOURCED KITS (CONT.)**

**RETRO-FIT KITS for CURRENT 988K (Cont.)**

C	563-3197	<b>KIT, WHEEL CHOCKS</b> . . . . . 0 988K Ser# TWX00001 & up, T8E00001 & up, LWX00001 & up, L8X00001 & up Provides all parts for field installation of wheel chocks and an integrated storage system. CANNOT BE USED WITH: 552-0032 or 552-0034 LOADER, STEEL MILL		\$2,010 NI
C	516-3925	<b>KIT, TIRE HANDLER (SL)</b> . . . . . 0 988K Ser# TWX00001 & up, T8E00001 & up, LWX00001 & up, L8X00001 & up Provides additional counterweight for tire handler applications. CANNOT BE USED WITH: BUCKETS		\$33,383 NI
C	513-5313	<b>KIT, AGGREGATE HANDLER (SL)</b> . . . . . 0 988K Ser# TWX00001 & up, T8E00001 & up, LWX00001 & up, L8X00001 & up Provides additional counterweight for the Aggregate Handler, which allows customers to maximize machine payload in re-handling applications. Reference salesgram TEKQ1223-01. ONLY FOR USE WITH: Standard Lift, 2 Star or 42PR Tires, & GP Bucket		\$13,979 NI
C	513-5314	<b>KIT, AGGREGATE HANDLER (HL)</b> . . . . . 0 988K Ser# TWX00001 & up, T8E00001 & up, LWX00001 & up, L8X00001 & up Provides additional counterweight for the Aggregate Handler, which allows customers to maximize machine payload in re-handling applications. Reference salesgram TEKQ1223-01. ONLY FOR USE WITH: High Lift, 2 Star or 42PR Tires, & GP Bucket		\$21,524 NI
C	498-9814	<b>KIT, RIDE CONTROL (STANDARD)</b> . . . . . 0 988K Ser# TWX00001 & up, T8E00001 & up, LWX00001 & up, L8X00001 & up Provides all parts for field installation of the ride control system. Accumulators meet Canadian pressure vessel requirements.		\$10,760 NI
C	471-9675	<b>KIT, COVER, INLET GRILL (CW)</b> . . . . . 0 988K Ser# TWX00001 & up, T8E00001 & up Provides all parts for field installation of the inlet grill covers for extended idling in cold weather. Recommended for ambient temperatures of -10C (14F) and below. Requires standard or block handler configs, not compatible with the millyard or steel mill configs.		\$4,000 NI
C	450-9894	<b>KIT, AUTOLUBE</b> . . . . . 95 988K Ser# TWX00001-1171, LWX00001-737 Provides all parts, including hardware and guarding, for field installation of the Lincoln autolube centromatic system. This kit is universal for all boom lengths.		\$17,220 NI
C	521-5061	<b>KIT, AUTOLUBE</b> . . . . . 0 988K Ser# TWX01172 & up, T8E00001 & up, LWX00738 & up, L8X00001 & up Provides all parts, including hardware and guarding, for field installation of the Lincoln autolube centromatic system. This kit is universal for all boom lengths.		\$17,220 NI

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FACTORY SOURCED KITS (CONT.)**

***RETRO-FIT KITS for CURRENT 988K (Cont.)***

C	450-9895	<b>KIT, CPM PAYLOAD</b> . . . . . 5 988K Ser# TWX00001-738, LWX0001 & up Provides all parts for field installation of the CPM system. For latest software info, see SEPD1989 for more details.		<b>\$1,415 NI</b>
NOTE: This kit will require a one time password charge of LP \$4,148.30 Instructions for obtaining this password will be provided with the special instructions included with this kit.				
C	450-9896	<b>KIT, THIRD VALVE</b> . . . . . 435 988K Ser# TWX00001 & up, T8E00001 & up, LWX00001 & up, L8X00001 & up Provides all parts for field installation of the third valve system.		<b>\$9,740 NI</b>
C	476-9627	<b>KIT, SECONDARY STEERING</b> . . . . . 0 988K Ser# TWX00001 & up, T8E00001 & up, LWX00001 & up, L8X00001 & up Provides all parts for field installation of secondary steering.		<b>\$9,120 NI</b>
C	476-9606	<b>KIT, AXLE OIL COOLER</b> . . . . . 0 988K Ser# TWX00001 & up, T8E00001 & up, LWX00001 & up, L8X00001 & up Provides all parts for field installation of the axle oil cooler system.		<b>\$10,850 NI</b>
C	458-3099	<b>KIT, ROADING FENDERS</b> . . . . . 0 988K Ser# TWX00001 & up, T8E00001 & up, LWX00001 & up, L8X00001 & up Provides all parts for field installation of roading fenders.		<b>\$5,680 NI</b>
C	476-9647	<b>KIT, ENGINE PRECLEANER (DUAL)</b> . . . . . 0 988K Ser# TWX00001 & up, T8E00001 & up Provides all parts for field installation of dual engine precleaner.		<b>\$3,125 NI</b>
C	458-3103	<b>KIT, CAB PRECLEANER (POWERED)</b> . . . . . 0 988K Ser# TWX00001 & up, T8E00001 & up, LWX00001 & up, L8X00001 & up Provides all parts for field installation of powered cab precleaner.		<b>\$7,230 NI</b>

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	<b>LANE 2 / 3 OPTIONAL</b>	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------------	-----------------	----------------------

**FACTORY SOURCED KITS (CONT.)**

**COMMAND FOR LOADING KIT**

Command for loading enables remote operation of the Cat 988K. In order to promote safety with minimal impact to productivity, Command for loading removes the operator from the cab of a machine. The Command for loading Operator Console utilizes seamless integration of new on-board hardware with familiar controls to allow the operator to have full functionality of the machine from a safe distance. Command for loading is currently compatible with 988K. The Operator Console is extremely portable and is carried using a shoulder harness.

**SOFTWARE ENABLED ATTACHMENT (SEA)**

When quoting always include the price of the Software Enabled Attachment (SEA) even though it is not ordered at the same time as the installation kits. The on-board systems will not function until the SEA is activated. Once the system is installed, activation requires dealer support through Caterpillar Electronic Technician (Dealer Version), communication adapter, and authority to request factory passwords form the Caterpillar Factory Password System (FPS).

When the factory password is generated at the request of the service technician, a purchase order will automatically be generated in the ANTARES system by FPS.

Refer to Information Release Memo (IRM) EES03-01 (PELJ0138) in the Global Sales Library (GSL) for further explanation of SEA's. Refer to RESH1238 for how to obtain a Factory Level Password from <https://fps.cat.com/>.

SEA's cannot be ordered directly in ANTARES. They can only be ordered using the Factory Password System (see instructions above).

WARNING: If you order directly in ANTARES, you may get invoiced twice.

P	<b>SEA, COMMAND LOADING LP</b> . . . . . 0	<b>\$43,400 NET</b>
	Required to enable the remote operation Command for Loading on-board system. One is required per machine installation.	

**BASE ON BOARD INSTALLATION KIT**

The following field retrofit kit includes: on-cab lighting, electronics bay, wiring harness, bumper lockout service panel, and mounting hardware.

P	<b>516-3920 KIT, ON-BOARD INSTALLTION</b> . . . . . 0	<b>\$10,430 NI NET</b>
	988K Ser# TWX00001 & up, T8E00001 & up Includes REHSXXXX Special Instruction (English only). REQUIRES: 1 OF 2 BELOW FROM PARTS DEPARTMENT: 545-8018 KIT, CONSOLE INSTALL (2.4GHZ) or 545-8019 KIT, CONSOLE INSTALL (900MHZ)	

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FACTORY SOURCED KITS (CONT.)**

**OPERATOR CONTROL KITS**

The new Gen 3 console is designed to easily transfer control between machines that are equipped with Command for loading. In addition, the Gen 3 console has improved ergonomics, battery life, and serviceability. Gen 3 consoles are available in two frequency ranges: 900 MHz (902-928 MHz) or 2.4 GHz (2403.1-2478.6 MHz) to provide site and/or country specific requirement.

Approved countries:

900 MHz: United States and Canada.  
 2.4 GHz: United States Canada, Australia, New Zealand, Peru, Chile, Columbia, Mongolia, Brazil, Mexico, Indonesia, Russia, European Union, Japan, China, Ukraine, South Africa, Democratic Republic of the Congo, and Saudi Arabia.

For the latest approved country listing, please visit:  
<https://dealer.cat.com/cda/layout?m=423015&x=7&id=2678888>

The following Generation 3 Console kits contain one operator console, two rechargeable Lithium Ion console batteries, one DC battery charger, one AC battery charger, shoulder harness, 3 smart cards with pouch, system carrying case, Operations and Maintenance Manual, Quick Reference Guide, Trouble Shooting Guide, and Special Instructions.

NOTE:  
 The ON-BOARD INSTALLTION KIT is available from the factory only.  
 The CONSOLE INSTALL KITS are available from parts department only.

P	545-8018	KIT, CONSOLE INSTALL (2.4 GHZ)	0	\$17,650	NI NET
P	545-8019	KIT, CONSOLE INSTALL (900 GHZ)	0	\$17,650	NI NET

**INSTRUCTIONS**

P	504-1365	FILM, AM-NORTH REQUIRED BY: AM-NORTH	0		NC
P	347-5045	FILMS, ANSI ONLY FOR USE WITH: 347-5000 988K WHEEL LOADER REQUIRED BY: AM-NORTH EXCEPT QUEBEC (N050)	0		NC

CATERPILLAR MACHINE PRICE LIST

**988K**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**PACKING**

MUST SELECT ONE

0P-0294	<b>PACK, DOMESTIC TRUCK</b> . . . . .	0		<b>NC</b>
	Complete machine loaded on truck. CANNOT BE USED WITH: Tire Omission			
0P-0201	<b>DOMESTIC TRUCK, TIRE REMOVAL</b> . . . . .	0		<b>\$620 NET</b>
	Removes tires/rims. CANNOT BE USED WITH: Tire Omission			
0P-2829	<b>PACK, DOMESTIC TRUCK</b> . . . . .	0		<b>\$266 NET</b>
	Complete machine loaded on truck. ONLY FOR USE WITH: Tire Omission			
0P-0812	<b>PACK, MISC SHIPMENTS</b> . . . . .	0		<b>NC</b>
	Use this as the packing reference number on a MISC MSO.			

**TRANSPORT GROUP**

P	451-7913	<b>TRANSPORT, BUCKET (NI) / OMIT</b> . . . . .	0	<b>NC</b>
		Required when ordering a Not Installed (NI) Bucket on your machine order or when omitting a Bucket from your machine order.		