

CATERPILLAR MACHINE PRICE LIST

PM620-LR

PM620 COLD PLANER
 LITTLE ROCK, AR, USA (SAP)

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

CAT C18, inline 6-cylinder, twin turbo-charged, aftercooled 630 HP (470 kW) diesel engine
 Power and torque curve optimized for fuel efficiency
 Engine diagnostic connector (for CAT ET)
 Air cleaner, dry type dual element with integral precleaner
 Belt, automatic tensioner
 Fuel filter/water separator
 Hydrostatic transmission
 Computerized load control
 Four tracks each with polyurethane track pads
 Dual pump propel system with opposite track traction control
 Alignment controlled steering system with four steering mode
 -front, rear and crab steer
 -coordinated steer
 Alignment is optimized for selected mode
 Auto tensioning track

and operating instructions
 LED wake-up model with floor light
 Integrated grade control
 Silver-class touch screen display
 Ramp-in, ramp-out function
 Digital moldboard control
 3 rotor speeds selectable on control panels
 Two level warning system with action light and horn (warning, critical warning)
 Quick detach fuse/relay/controller
 Automatic throttle control
 Camera ready display

ELECTRICAL

Backup alarm
 Alternator, 100-amp
 Batteries, two maintenance free 1400 CCA each
 Horn, forward warning
 Ground located horn, operator warning
 Electrical system, 24-volt
 Remote jump start receptacle
 Work lights (4 fixed, 10 pole mount)
 Machine diagnostic connector (for CAT ET)
 Self diagnostic system
 Product Link ready

APPLICATION SPECIFIC COMPONENTS

ROTOR AND CHAMBER SYSTEM
 Caterpillar patented tool holder with easy extraction feature
 External floating side plates
 Dry clutch, belt transmission and automatic tensioner
 Dedicated water spray for tool cooling and dust control
 Curb clearance right side plate
 Moldboard with floating, locked or service height levels and adjustable down pressure
 Hydraulic raiseable and floating anti-slab
CONVEYORS
 Front loading
 850 mm (33.5") belt width collecting conveyor
 850 mm (33.5") belt width discharge conveyor
 Dual stage, infinitely variable speed, with independent reversing
 60-degree swing either side of center for discharging conveyor
 Conveyor boost function

OPERATOR ENVIRONMENT

Dual operator positions, on the left and right of the operators platform
 Operator platform with visibility to both crawlers of the machine
 Machine monitoring system
 Lockable vandalism guards for all control panels
 Platform handrails/guardrails
 Control and propel console with LED backlit panels and joystick propel and steering
 Electronic machine management system
 Digital graphic display for diagnostics

FLUIDS

Extended life coolant with protection to -37C (-34F)

OTHER STANDARD EQUIPMENT

Doors, service access, hinged, locking
 Fuel tank 1200 L (317 gal)
 Pressure test ports with quick connect
 Water tank 3400 L (898 gal)
 Sound suppression insulation kit
 Sight gauges
 -water
 -hydraulic oil

CATERPILLAR MACHINE PRICE LIST

PM620-LR

PM620 COLD PLANER
LITTLE ROCK, AR, USA (SAP)

Ship Weight
lbs

LIST PRICE
AT DEALER

OTHER STANDARD EQUIPMENT (CONT.)

-filter restriction
Mirrors
Rear water fill
12-volt ports at operator station
Air system
Pressure test ports with quick connect
S.O.S. sampling ports
Auxiliary electro-hydraulic power
package for operational and emergency
functions
Operational functions:
-electro-hydraulic powered canopy and
engine hood lift
Emergency functions:
-spring applied brakes releasing
-auxiliary services
Air filter restriction electric
indicator
Compressed air lubricator and pressure
regulator unit
On board winterization system

CATERPILLAR MACHINE PRICE LIST

PM620-LR

PM620 COLD PLANER
LITTLE ROCK, AR, USA (SAP)

Ship Weight
lbs

LIST PRICE
AT DEALER

**Lane 2 is reserved for the Base Order Management Program.
Please use Lane 2 when placing orders that are part of the Base
Orders Management Program.**

CATERPILLAR MACHINE PRICE LIST

PM620-LR

PM620 COLD PLANER LITTLE ROCK, AR, USA (SAP)	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

565-8009	PM620 02A COLD PLANER 0 LANE 2 - AVAILABLE FROM NORTH LITTLE ROCK FACTORY LANE 3 - AVAILABLE FROM NORTH LITTLE ROCK FACTORY	\$602,070
----------	--	------------------

CATERPILLAR MACHINE PRICE LIST

PM620-LR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-----------------------------	--------------------	-------------------------

NOTE

To place MISCELLANEOUS MATERIAL orders, please use 0G-4198 PM620 MISC MATL and reference the Minerbio source PM620 COLD PLANER price list for material selection. Please note, ONLY miscellaneous material orders may be placed through the Mineribo facility.

CATERPILLAR MACHINE PRICE LIST

PM620-LR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER	0	NC

SPECIAL ARRANGEMENTS

CHASSIS

L	558-4169	MACHINE, PM6 COMMON	0	NC
---	----------	-------------------------------	---	----

POWERTRAIN

ENGINE

L	558-4145	ENGINE, CAT C18	0	NC
		Meets U.S. EPA Tier 4 Final and EU Stage V emission standards.		

HYDRAULICS

WATER FILL PUMP

L	396-4803	PLUG, NO WATER FILL PUMP	0	NC
L	374-6812	PUMP,WATER FILL, HIGH CAPACITY	0	\$2,730
		Line connected to the water tank allowing pressurized water filling from certain water systems.		

DUST EXTRACTION

L	377-2969	VENTILATION SYSTEM	0	\$10,030
		Dust and particles from operations are collected in multiple areas by hydraulically driven fan and discharged into secondary conveyor.		

HIGH PRESSURE WASHDOWN

L	396-4801	NO HIGH PRESSURE CLEANER	0	NC
L	374-6811	PUMP, WASHING, HIGH PRESSURE	0	\$5,420
		High pressure washdown water pump, including (1) wand with 15 m (50 ft) of hose on reel.		

ELECTRICAL

LIGHTING

L	374-1436	LIGHTS, HALOGEN	0	\$2,365
		Includes 14 halogen lights: 1 light facing each of the 4 tracks, 2 lights facing the rear of the cutter box, 2 lights mounted on the top front end of the discharge conveyor, 2 lights on the top rear face of the machine and 4 lights on the rear face of the machine.		

CATERPILLAR MACHINE PRICE LIST

PM620-LR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

ELECTRICAL (CONT.)

LIGHTING (Cont.)

L	477-9167	LIGHTS, LED 0		\$7,800
		Includes 14 LED lights: 1 light facing each of the 4 tracks, 2 lights facing the rear of the cutter box, 2 lights mounted on the top front end of the discharge conveyor, 2 lights on the top rear face of the machine and 4 lights on the rear face of the machine.		

OPERATOR ENVIRONMENT

OPERATOR STATION

L	378-8243	NO CANOPY 0		NC
L	374-1443	CANOPY, FOLDING, HYDRAULIC 0		\$10,290
		Hydraulically folding canopy with extendible side wings.		

SEATS

L	376-4122	PLATFORM, NO SEATS 0		NC
L	376-4111	SEAT FULL SIZE SUSPENSION 0		\$4,300
		Includes suspension seats with adjustable operator position.		

OPERATOR FIXED DISPLAY

L	393-6393	SINGLE CENTER DISPLAY 0		NC
		Includes one (1) center mounted display for machine operation, system diagnostic and grade and slope control. Also includes brackets.		
L	393-6394	DOUBLE CENTER DISPLAY 0		\$4,310
		Includes two (2) center mounted displays for machine operation, system diagnostic and grade and slope control. Also includes brackets.		

GRADE AND SLOPE

P	380-3870	CONTROL, CAT G&S SYSTEM 0		\$7,580
		Measures grade from the position of side plates, using position sensing cylinders. Provides information to machine displays for operation of grade control.		

GRADE AND SLOPE CONTROLS

L	501-3599	PLUG, NO INBOARD SKI 0		NC
P	380-3868	INBOARD SKI 0		\$3,050
		Inboard ski bracket assembly for both left and right side of machine, reading position from position sensing cylinder. Includes bracket, ski and sensor.		

CATERPILLAR MACHINE PRICE LIST

PM620-LR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	472-2959	PRODUCT LINK, SATELLITE PL631 0 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		\$439
L	472-2960	PRODUCT LINK, SATELLITE PLE631 0 Product Link Elite series PLE631 (consisting of PL631 radio and PLE601 network manager) uses a satellite network to transmit location, utilization and health information for viewing in Product Link user applications. For use in areas with poor or no cellular coverage.		\$811
L	468-9668	PRODUCT LINK, CELLULAR PL641 0 Product Link Basic series PL641 uses cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		NC
L	468-9504	PRODUCT LINK, CELLULAR PLE641 0 Product Link Elite series PLE641 (consisting of PL641 radio and PLE601 network manager) uses cellular networks to transmit location, utilization, health and productivity information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		\$372

FUEL SYSTEMS

FUEL TANK

L	374-1279	TANK, FUEL STANDARD 0		NC
L	374-1280	TANK, FUEL FAST FILL 0 Allows for transfer of fuel from pressurized fill systems.		\$3, 620

OTHER ATTACHMENTS

MILL ROTORS

L	517-0847	ROTOR, K STD - 15 MM 0 Latest Design tool holder system with 2010 mm (79.1") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 15 mm. Includes: 170 Bits		\$40, 490
---	----------	--	--	------------------

CATERPILLAR MACHINE PRICE LIST

PM620-LR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

MILL ROTORS (Cont.)

C	578-0189	ROTOR, K MICRO - 6 MM 0 FOR USE WITH LANE 3 ONLY CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest design tool holder system for Micro Milling with 2010 mm (79.1") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, and tooth spacing of 6 mm to provide micro finish. Includes: 350 Bits		\$72,880
C	567-0933	ROTOR, K FINE - 8 MM 0 FOR USE WITH LANE 3 ONLY CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest design tool holder system with 2010 mm (79.1") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 8 mm. Includes: 276 Bits		\$58,710
C	559-1544	ROTOR, K COARSE - 18 MM 0 FOR USE WITH LANE 3 ONLY CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY. Latest design tool holder system with 2010 mm (79.1") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 18 mm. Includes: 150 Bits		\$38,470
C	582-7725	ROTOR, K COARSE - 25 MM 0 FOR USE WITH LANE 3 ONLY CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Latest design tool holder system with 2010 mm (79.1") cut width. Allows for quick change of tool holder without the need for welding, replaceable bolt on kicker paddles, tooth spacing 25 mm. Includes: 122 Bits		\$35,760
C	505-2908	ROTOR, H MICRO - 6X2MM 0 FOR USE WITH LANE 3 ONLY CUSTOM ATTACHMENT - PLEASE CONTACT THE FACTORY FOR AVAILABILITY Weld on tool holders for micro milling with 2010 mm (79.1") cut width. Advanced design of weld on bit blocks to allow micro finish with a tooth spacing 6x2 mm. Includes: 672 Bits		\$89,210
L	0F-5136	OMISSION, ROTOR 0 FOR USE IN LANE 3 ONLY		NC

DISCHARGE CONVEYOR

L	374-1367	DISCHARGE CONVEYOR, FOLDING 0 Hydraulically downward folding discharge conveyor.		\$48,350
---	----------	--	--	----------

CONVEYOR SWING RELEASE

L	418-2294	NO CONVEYOR SWING VALVE 0		NC
L	377-9877	CONVEYOR SWING VALVE 0 Valve actuation allows conveyor to swing free when connected to certain transport fixtures for turning.		\$1,035

CATERPILLAR MACHINE PRICE LIST

PM620-LR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

ADDITIONAL WATER SPRAYING SYSTEM

NOTE: Local regulations or job specifications may require use of a ventilation system and/or additional dust reduction options. Please check your local requirements and job specs for conformance.

L	519-7351	COVER, NO ADDITIONAL SPRAY	0	NC
L	376-4133	DUST REDUCTION ADDIT. (2M/79") Additional water spraying system for dust reduction, including additional spraying bars located inside the rotor housing and the conveyors.	0	\$2,475

WATER TANK GROUND LEVEL FILLING PORT

L	387-4320	PORT, FILLING, WATER TANK Water tank ground level Filling Port. U.S. standard only.	0	NC
---	----------	---	---	----

WATER SIDE FILL

L	396-4805	PLUG, NO SIDE FILL	0	NC
L	374-1439	SIDE FILL VALVE & PORT Line connected to the water tank, providing addition location for water fill.	0	\$454

STEERING GUIDE

P	397-8284	GUIDE, TELESCOPING STEERING Provides two telescoping steering guides with multi point adjustment for advanced steering marker placement.	0	NC
P	501-0412	GUIDE, STANDARD STEERING Provides two standard steering guides with lateral adjustment of pendulum markers.	0	NC

COMMISSIONING

NOTE: It is recommended that startup and commissioning of machines be included as part of the machine sale. The net charge covers a three day commissioning event. Trained personnel cover proper machine setup, basic maintenance, operation and application on a customer's jobsite. To request and schedule a machine commissioning event, dealers will need to contact the Caterpillar Paving Technical Training group by filling out the online request form.

URL: https://www.catpaving.com/registration/class_request_form

L	0P-2586	COMMISSIONING, NEEDED Commissioning Needed, trained personnel are required to properly commission the machine.	0	\$6,420 NET
L	0P-2587	COMMISSIONING, NOT NEEDED Commissioning, Not Needed, necessary dealer resource are available to properly commission the machine.	0	NC

CATERPILLAR MACHINE PRICE LIST

PM620-LR

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------------	--------------------	-------------------------

FLUIDS

HYDRAULIC OIL

L	374-1432	HYDR. OIL HYDO ADVANCED 10W 0 CAT standard hydraulic oil		NC
---	----------	---	--	----

INSTRUCTIONS

DECAL PACKAGES

L	374-1366	FILM, NACD 0 ANSI picto warning decals using symbols plus the word "WARNING" as required for the USA.		NC
---	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

PM620-LR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

ELECTRICAL

P	363-7444	LIGHT, HAZARD, CANOPY 0 Includes two LED amber strobe lights, magnetically mounted.		\$344 NI
P	394-0410	LIGHT, HAZARD 0 Includes two LED amber strobe lights mounted to the conveyor and rear of the machine.		\$715
P	374-1437	LAMP, LED (FIXED) 0 Provides a single LED lamp with integrated bracket for fixed mounting. To serve as a replacement lamp or reserve stock.		\$505 NI
P	398-7378	LAMP, LED (POLE MOUNT) 0 Provides a single LED lamp with integrated bracket for pole mounting. To serve as a replacement lamp or reserve stock.		\$660 NI
P	394-9642	LAMP, HALOGEN (MAGNETIC) 0 Provides a single halogen lamp with magnetic mounting.		\$316 NI
P	376-4129	LIGHT, TRUCK SIGNAL 0 Red / Green light to communicate with truck driver		\$555

OPERATOR ENVIRONMENT

P	374-1445	UMBRELLA 0 Includes two umbrellas to provide operator or ground crew protection from sun and rain. Single umbrella measures 54"x54" and is collapsible. Includes support shafts and mounting hardware to be installed on machine at customer direction.		\$700 NI
P	532-7658	WINDSCREEN 0 FOR USE IN LANE 3 ONLY Collapsible windscreens mount to and move with the canopy. Rear windscreen can fold up into canopy cavity when not in use. ONLY FOR USE WITH: 374-1443 CANOPY, FOLDING, HYDRAULIC		\$7,080

OTHER ATTACHMENTS

GRADE AND SLOPE CONTROLS

P	376-4136	SENSOR, SONIC, AVERAGING 0 Sonic averaging ski for mounting on the LH or RH side, consisting of two sonic sensors (in addition to the machine grade control base system or the optional inboard consisting of two sonic sensors (in addition to the base system) with adjustable mounting arms. ONLY FOR USE WITH: 380-3870 CONTROL, CAT G&S SYSTEM		\$10,230 NI
P	416-2036	SENSOR, SONIC, FOR STRING LINE 0 Include bracket, (1) ultrasonic sensor and cables for mounting at the center of the machine. ONLY FOR USE WITH: 380-3870 CONTROL, CAT G&S SYSTEM		\$4,110 NI

CATERPILLAR MACHINE PRICE LIST

PM620-LR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

GRADE AND SLOPE CONTROLS (Cont.)

P	387-9468	DISPLAY, OPTIONAL 0 Additional display (1) with mounting bracket for ground/operator station. Order QTY 3 maximum		\$2,850 NI
---	----------	---	--	------------

VISIBILITY ENHANCEMENTS

P	387-9552	REAR CAMERA. 0 This camera system is used to enhance the operator's rear visibility while operating. The LCD color display is designed to have a sharp, clear picture with camera mounted on the top rear end of the machine		\$895
P	387-9467	CONVEYOR CAMERA. 0 This camera system is used to enhance the operator's forward visibility while operating. The LCD color display is designed to have a sharp, clear picture with camera mounted on the top front end of the discharge conveyor		\$1,100
P	376-4123	CAMERA, AUX. 0 Camera with cable and magnetic mount. The single camera system is compact, rugged, reliable, and the camera can be placed anywhere within cable length.		\$750 NI

ROTOR SERVICING TOOLS

P	376-4134	PNEUMATIC BIT REMOVAL TOOL 0 Includes pneumatic hammer, punch tools, coil hose and fittings.		\$630 NI
P	388-1047	ROTOR TURNING DEVICE. 0 Includes control device and electrical motor for powered rotational assist when servicing the rotor.		\$3,050
P	577-4176	EXTRACTOR, TOOL HOLDER 0 Hand tool for extracting cutter bit tool holders which have broken at the shank inside the weld on block. Tool is engaged to broken shank via a threaded pulling bolt. Extraction tool can be configured to be used on G,J, or K rotor systems.		\$278 NI

MISC ATTACHMENTS

P	376-4130	CUTTING BIT TRAY 0 Two additional trays between rear crawlers for bit storage.		\$434
P	376-4126	PUMP, FUEL TRANSFER 0 Allows for transfer of fuel from non-pump container.		\$1,645
P	376-4132	LOW PRESSURE WASH DOWN 0 Low pressure washdown system, including (1) wand with 1 m (50 ft) of hose on reel.		\$1,465

DOCUMENTATION

L	354-8706	YEAR OF MANUFACTURE PLATE 0 Plate attached to PIN plate showing year of Final Plant Shipping Date.		NC
---	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

PM620-LR

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------------	--------------------	-------------------------

DOCUMENTATION (CONT.)

0P-1870	CERTIFICATE OF ORIGIN		0	NC
---------	---------------------------------	--	---	-----------

PACKING

0P-0210	PACK, DOMESTIC TRUCK		0	NC
---------	--------------------------------	--	---	-----------