

CATERPILLAR MACHINE PRICE LIST

WT-BHL**BACKHOE LOADER WORK TOOLS
BCP ATTACHMENTS (SAP)**Ship Weight
lbsLIST PRICE
AT DEALER

Standard Equipment:

This Price List consists of Work Tools
for BHL - B, C, D, E, F/F2 Series and
Next Generation 415 - 450

This price list is divided into the
following sections

LOADER CURRENT PIN-ON
LOADER CURRENT IT
LOADER INDUSTRIAL CURRENT
LOADER NON CURRENT PIN-ON
BACKHOE CURRENT: 415-444
BACKHOE CURRENT: 450
BACKHOE NON CURRENT

FOR NORTH AND SOUTH AMERICA
Orders will automatically transfer
from CMOPS to Antares Parts Ordering.

FOR THE REST OF THE WORLD
This price list is for REFERENCE ONLY.
Work Tool orders must be placed using
Antares Parts Ordering.

FOR JAPAN
Please access the usual regional
resources to obtain pricing information.

For BCP Attachment Product and
Application Support
1-866-963-3531, Option #1, Option #2
E-mail: BCP_Work_Tools@Cat.com

For Order Management/Availability
Support
1-866-963-3531, Option #1, Option #1
E-mail:
Cat_Parts_BCP_Work_Tools_Support@Cat.com

IMPORTANT for EAC or EAEU Dealers:
(country codes: AM, BY, KY, KZ, RU)
Work tools that DO require certifica-
tion for the EAEU market access and
WILL NOT be certified by Caterpillar:
Augers, Box Blades, Backhoe Attachm.,
Bale Grabs, Brush cutters, Compact-
ors, Cold planners, Grapple buckets
Hydr.Couplers, Material handlng arm,
Mixing Bucket, Mulchers, Rakes, Power
Box Rakes, Tillers, Silage Defacers,
Snow Blowers, Stump Grinders,
Trenchers, V-Plow Blades, Wheel Saws
Above statement is NOT related to the
compatibility of those tools to machines

CATERPILLAR MACHINE PRICE LIST

WT-BHL

BACKHOE LOADER WORK TOOLS
BCP ATTACHMENTS (SAP)

Ship Weight
lbs

LIST PRICE
AT DEALER

0P-0070

BACKHOE LOADER WORK TOOLS 0
Please use this reference number when ordering.

NC

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT PIN-ON

PIN-ON HINGE CHANGE

From the loader side the pin-on hinges have changed going to F series. F2 is equal to F series. Next generation BHL after F2 (with no series letter) are equal to F/F2.

The attachments are grouped into following sections:

SINGLE TILT PIN-ON (FRONT):

415F2, 416F/F2, 420F/F2 ST, 422F/F2, 430F/F2 ST, 450F
 Next Generation 415-450

PARALLEL LIFT PIN-ON NON EST (FRONT):

Fit on following machines (Non Equal size Tyres):
 426F2, 427F2, 428F/F2 ST, 432F/F2
 Next Generation 428, 432

PARALLEL LIFT PIN-ON EST (FRONT):

Fit on following machines (Equal Size Tyres):
 434F/F2 ST, 444F/F2
 Next Generation 434, 444

From F2 the quick disconnects have changed into "Twist to Connect" F1 and earlier have "Push to Connect". If you have Aux on the front these are the correct Quick Disconnects:

W	455-7380	KIT, LOADER, COUPLING QD 0 'Twist to Connect' hydr.QDs, incl 1x 439-1588 Fem.+ 1x 439-1589 Male FOR USE WITH: F2 series and Next Generation For pre F2 series, order: 1x 195-6525 Female QD + 1x 421-6170 Male QD.	\$419 NI
----------	-----------------	--	-----------------

SINGLE TILT PIN-ON (FRONT): - General Purpose Buckets

These buckets fit onto the following machines
 415F2, 416F/F2, 420F/F2 ST, 422F/F2, 430F/F2 ST
 Next Generation 415-430

W	337-7382	BUCKET-GP, 1.0 YD3, PO 776 Cap 0.76m3 (1.0yd3), width 2262mm (89"), base edge. FOR USE WITH: 415F2, 416F/F2, Next Gen 415, 416	\$2,764 NI
W	337-7383	BUCKET-GP, 1.0 YD3, PO, BOCE 0 Cap 0.76m3 (1.0yd3), width 2262mm (89"), incl. Bolt on edge (9R-5321) FOR USE WITH: 415F2, 416F/F2, Next Gen 415, 416	\$3,236 NI
W	337-7385	BUCKET-GP, 1.3 YD3, PO 965 Cap 1.0 m3 (1.3 yd3), width 2262mm (89"), base edge FOR USE WITH: 420F/F2, 430F/F2 ST, Next Gen 420, 420XE, 430	\$3,500 NI
W	337-7387	BUCKET-GP, 1.3 YD3, PO, BOT 966 Cap 1.0 m3 (1.3 yd3), width 2262mm (89"), incl Bolt-on Teeth (9R-5866) FOR USE WITH: 420F/F2, 430F/F2 ST, Next Gen 420, 420XE, 430	\$3,896 NI
W	337-7386	BUCKET-GP, 1.3 YD3, PO, BOCE 1,021 Cap 1.0 m3 (1.3 yd3), width 2262mm (89"), incl Bolt-on edge (9R-5321) FOR USE WITH: 420F/F2, 430F/F2 ST, Next Gen 420, 420XE, 430	\$3,972 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT PIN-ON (CONT.)

SINGLE TILT PIN-ON (FRONT): - General Purpose Buckets (Cont.)

W	337-7396	BUCKET-GP, 1.3 YD3, PO 988 Cap 1.0m3 (1.3yd3), width 2406mm (95"), base edge FOR USE WITH: 420F/F2, 430F/F2 ST, Next Gen 420, 420XE, 430		\$3,521 NI
W	337-7397	BUCKET-GP, 1.3 YD3, PO, BOCE 1,179 Cap 1.0m3 (1.3yd3), width 2406mm (95"), incl Bolt-on edge (9R-5320) FOR USE WITH: 420F/F2, 430F/F2 ST, Next Gen 420, 420XE, 430		\$3,993 NI
W	337-7388	BUCKET-GP, 1.4 YD3, PO 1,012 Cap 1.07m3 (1.4yd3), width 2262mm (89"), base edge FOR USE WITH: 420F/F2, 430F/F2 ST, Next Gen 420, 420XE, 430		\$3,743 NI
W	337-7389	BUCKET-GP, 1.4 YD3, PO, BOCE 1,162 Cap 1.07m3 (1.4yd3), width 2262mm (89"), incl Bolt-on edge (9R-5321) FOR USE WITH: 420F/F2, 430F/F2 ST, Next Gen 420, 420XE, 430		\$4,215 NI
W	337-7390	BUCKET-GP, 1.4 YD3, PO, BOT 1,063 Cap 1.07m3 (1.4yd3), width 2262mm (89"), incl Bolt-on Teeth (9R-5866) FOR USE WITH: 420F/F2, 430F/F2 ST, Next Gen 420, 420XE, 430		\$4,139 NI
W	337-7401	BUCKET-GP, 1.5 YD3, PO 1,056 Cap 1.15m3 (1.5yd3), width 2406mm (95"), base edge FOR USE WITH: 420F/F2, 430F/F2 ST, Next Gen 420, 420XE, 430		\$4,014 NI
W	337-7402	BUCKET-GP, 1.5 YD3, PO, BOCE 1,241 Cap 1.15m3 (1.5yd3), width 2406mm (95"), incl Bolt-on edge (9R-5320) FOR USE WITH: 420F/F2, 430F/F2 ST, Next Gen 420, 420XE, 430		\$4,486 NI
W	337-7403	BUCKET-GP, 1.5 YD3, PO, BOT 1,107 Cap 1.15m3 (1.5yd3), width 2406mm (95"), incl Bolt-on Teeth (9R-5866) FOR USE WITH: 420F/F2, 430F/F2 ST, Next Gen 420, 420XE, 430		\$4,410 NI
W	270-9163	BUCKET-GP, 1.75 YD3, PO, BOCE 1,473 Cap.1.34m3 (1.75yd3), width 2434mm (96") INCLUDES: 2 piece bolt-on cutting edge (2x 9U-9665) FOR USE WITH: 450E/F If ordering these as replacement buckets for 446D/446B, please order updated service brace 324-0720.		\$5,931 NI
W	521-6207	BUCKET-GP, 1.75 YD3, PO, BOCE 2,226 Cap.1.34m3 (1.75yd3), width 2438mm (96") INCLUDES: 2 piece bolt-on cutting edge (2x 9U-9665) FOR USE WITH: Next Generation 440, 450		\$5,931 NI
W	521-6208	BUCKET-GP, 2.0 YD3, PO, BOCE 2,403 Cap.1.53m3 (2.0yd3), width 2438mm (96") INCLUDES: 2 piece bolt-on cutting edge (2x 9U-9665) FOR USE WITH: Next Generation 440, 450		\$6,549 NI

SINGLE TILT PIN-ON (FRONT) - Multi Purpose Buckets

W	337-7436	BUCKET-MP, 1.3 YD3, PO 1,593 Cap 1.03m3 (1.3yd3), width 2279mm (90"), base edge FOR USE WITH: 415F/F2, 415F/F2 IL, 416F/F2, 420F/F2, 430F/F2 ST, Next Gen 415, 415 IL, 416, 420, 430 REQUIRES: Hydraulics, Loader 3rd Valve		\$7,222 NI
---	----------	---	--	------------

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT PIN-ON (CONT.)

SINGLE TILT PIN-ON (FRONT) - Multi Purpose Buckets (Cont.)

W	337-7437	BUCKET-MP, 1.3 YD3, PO, BOT 1,642 Cap 1.03m3 (1.3yd3), width 2279mm (90"), incl Bolt-on Teeth (9R-5866) FOR USE WITH: 415F/F2, 415F/F2 IL, 416F/F2, 420F/F2, 430F/F2 ST, Next Gen 415, 415 IL, 416, 420, 430 REQUIRES: Hydraulics, Loader 3rd Valve		\$7,472 NI
W	337-7438	BUCKET-MP, 1.3 YD3, PO, BOCE 1,742 Cap 1.03m3 (1.3yd3), width 2279mm (90"), incl Bolt-on edge (9R-5321) FOR USE WITH: 415F/F2, 415F/F2 IL, 416F/F2, 420F/F2, 430F/F2 ST, Next Gen 415, 415 IL, 416, 420, 430 REQUIRES: Hydraulics, Loader 3rd Valve		\$7,569 NI
W	337-7439	BUCKET-MP, 1.3 YD3, PO, FORKS 1,819 Cap 1.03m3 (1.3yd3), width 2279mm (90"), base edge INCLUDES: fold over forks FOR USE WITH: 415F/F2, 415F/F2 IL, 416F/F2, 420F/F2, 430F/F2 ST, Next Gen 415, 415 IL, 416, 420, 430 REQUIRES: Hydraulics, Loader 3rd Valve		\$9,181 NI
W	337-7440	BUCKET-MP, 1.3YD3, PO, FORKS, BOT 1,874 Cap 1.03m3 (1.3yd3), width 2279mm (90") INCLUDES: fold over forks and bolt-on teeth (9R-5866) FOR USE WITH: 415F/F2, 415F/F2 IL, 416F/F2, 420F/F2, 430F/F2 ST, Next Gen 415, 415 IL, 416, 420, 430 REQUIRES: Hydraulics, Loader 3rd Valve		\$9,417 NI
W	337-7441	BUCKET-MP, 1.3YD3, PO, FORKS, BOCE 1,973 Cap 1.03m3 (1.3yd3), width 2279mm (90") INCLUDES: fold over forks and bolt-on cutting edge (9R-5321) FOR USE WITH: 415F/F2, 415F/F2 IL, 416F/F2, 420F/F2, 430F/F2 ST, Next Gen 415, 415 IL, 416, 420, 430 REQUIRES: Hydraulics, Loader 3rd Valve		\$9,528 NI
W	337-7442	BUCKET-MP, 1.4 YD3, PO 1,655 Cap 1.1m3 1.4yd3, width 2425mm (95"), base edge FOR USE WITH: 420F/F2, 430F/F2 ST REQUIRES: Hydraulics, Loader 3rd Valve		\$7,486 NI
W	337-7443	BUCKET-MP, 1.4 YD3, PO, BOT 1,722 Cap 1.1m3 1.4yd3, width 2425mm (95"), incl Bolt-on Teeth (9R-5866) FOR USE WITH: 420F/F2, 430F/F2 ST REQUIRES: Hydraulics, Loader 3rd Valve		\$7,736 NI
W	337-7444	BUCKET-MP, 1.4 YD3, PO, BOCE 1,856 Cap 1.1m3 1.4yd3, width 2425mm (95"), incl Bolt-on edge (9R-5321) FOR USE WITH: 420F/F2, 430F/F2 ST REQUIRES: Hydraulics, Loader 3rd Valve		\$7,833 NI
W	337-7445	BUCKET-MP, 1.4 YD3, PO, FORKS 2,003 Cap 1.1m3 1.4yd3, width 2425mm (95"), base edge INCLUDES: fold over forks FOR USE WITH: 420F/F2, 430F/F2 ST REQUIRES: Hydraulics, Loader 3rd Valve		\$9,444 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT PIN-ON (CONT.)

SINGLE TILT PIN-ON (FRONT) - Multi Purpose Buckets (Cont.)

W	337-7446	BUCKET-MP,1.4YD3,PO, FORKS,BOT 1,944 Cap 1.1m3 1.4yd3, width 2425mm (95") INCLUDES: fold over forks and bolt-on teeth (9R-5866) FOR USE WITH: 420F/F2, 430F/F2 ST REQUIRES: Hydraulics, Loader 3rd Valve		\$9,681 NI
W	337-7447	BUCKET-MP,1.4YD3,PO,FORKS,BOCE 2,099 Cap 1.1m3 1.4yd3, width 2425mm (95") INCLUDES: fold over forks and bolt-on cutting edge (9R-5321) FOR USE WITH: 420F/F2, 430F/F2 ST REQUIRES: Hydraulics, Loader 3rd Valve If ordering these as replacement buckets for 446D/446B, please order updated service brace 324-0720.		\$9,792 NI
W	272-1701	BUCKET-MP,1.5YD3,PO,BRKTS,BOCE 2,105 Cap 1.15m3 (1.5yd3), width 2425mm (95") INCLUDES: fork mounting brackets & bolt-on cutting edge (2x 118-7110) REQUIRES: Hydraulics, Loader 3rd Valve FOR USE WITH: 450E/F If ordering these as replacement buckets for 446D/446B, please order updated service brace 324-0720.		\$9,681 NI
W	272-1700	BUCKET-MP,1.5YD3,PO,FORKS,BOCE 2,456 Cap 1.15m3 (1.5yd3), width 2425mm (95") INCLUDES: Fold over forks & bolt-on cutting edge (2x 118-7110) REQUIRES: Hydraulics, Loader 3rd Valve FOR USE WITH: 450E/F		\$10,035 NI
W	521-6205	BUCKET-MP HD,1.75YD3 PO BOCE 2,698 Heavy Duty MP, Cap.1.34m3 (1.75yd3), width 2438mm (96") INCLUDES: 2 piece bolt-on cutting edge (2x 9U-9665) on front of the clam, 1 piece bolt-on cutting edge on dozer front REQUIRES: Hydraulics, Loader 3rd Valve FOR USE WITH: Next Generation 440, 450		\$12,292 NI
W	521-6206	BUCKET-MP, XD, 1.75YD3,PO,BOCE 2,866 Extreme Duty MP, Cap.1.34m3 (1.75yd3), width 2438mm (96") INCLUDES: 2 piece bolt-on cutting edge (2x 9U-9665) on front of the clam, 1 piece bolt-on cutting edge on back of the clam & dozer front REQUIRES: Hydraulics, Loader 3rd Valve FOR USE WITH: Next Generation 440, 450		\$13,736 NI

SINGLE TILT PIN-ON (FRONT) - Forks

W	461-0763	FORK, PALLET, 48", BHL ST, F 0 60" pallet fork with tines 1219mm (48") long, 51mm (2") thick and 127mm (5") wide FOR USE WITH: 416F/F2, 420F/F2, 430F/F2 ST, Next Gen 416, 420, 430 440		\$7,313 NI
---	----------	--	--	-------------------

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT PIN-ON (CONT.)

SNOW PUSHES

To use the straight pushes, you need to have a pin-on bucket with no GETs. The straight push will hook onto the base edge of the bucket and will kept in place with chains.
 Availability can be restricted due to North American snow season.
 Please contact your BCP Attachments contact.

W	479-8088	SNOW PUSH, 10', BKT REC	1,990	\$8,806 NI
		3219mm (126") overall width, 3067mm (120") working width 906mm (36") moldboard height 2 trip edges 137 mm (5.4") height each with a 1 piece STEEL bolt-on cutting edge and each with 4 adjustable trip springs 2 heavy duty adjustable skid shoes FOR USE WITH: any bucket with base edge with NO GETs		
W	479-8092	SNOW PUSH, 12', BKT REC	2,180	\$9,681 NI
		3829mm (150") overall width, 3677mm (144") working width 906mm (36") moldboard height 2 trip edges 137 mm (5.4") height each with a 1 piece STEEL bolt-on cutting edge and each with 4 adjustable trip springs 2 heavy duty adjustable skid shoes FOR USE WITH: any bucket with base edge with NO GETs		
W	508-8300	SNOW PUSH, 10', REC, R.TRIP	1,865	\$8,347 NI
		Incl. 2 section trip edge each with 4 adjustable springs, each with a bolt-on rubber edge 38mmx203mm (1.5"x 8") approx 50mm(2") adjust. Width 3.05m (10'), with bolt side skids, Overall Height 966mm (38") FOR USE WITH: any loader bucket with NO GETs.		
W	508-8305	SNOW PUSH, 12', REC, R.TRIP	2,055	\$9,125 NI
		Incl. 2 section trip edge each with 4 adjustable springs, each with a bolt-on rubber edge 38mmx203mm (1.5"x 8") approx 50mm(2") adjust. Width 3.66m (12'), with bolt side skids, Overall Height 966mm (38") FOR USE WITH: any loader bucket with NO GETs.		

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT IT

QUICK DISCONNECTS COMPATIBILITY

From F2 the quick disconnects have changed into "Twist to Connect" F1 and earlier have "Push to Connect". If you have Aux on the front these are the correct Quick Disconnects:

W	455-7380	KIT, LOADER, COUPLING QD 0 Twist to Connect hydr. QDs, incl 1x 439-1588 Fem.+ 1x 439-1589 Male FOR USE WITH: F2 series, Next Generation 415 - 450 For pre F2 series, order: 1x 195-6525 Female QD + 1x 195-6527 Male QD		\$419 NI
---	----------	---	--	-----------------

QUICK COUPLER IT for Next Generation machines:

W	596-8446	KIT, LOADER COUPLER 0 Kit to installed hydr IT coupler on Single Tilt machines FOR USE WITH: Next Gen 415, 416, 420, 420XE, 430		\$5,215 NI
W	539-6387	KIT, LOADER COUPLER 0 Kit to installed hydr IT coupler on Single Tilt machines FOR USE WITH: Next Gen 440 and 450		\$5,215 NI

QUICK COUPLER IT for 415F2, 416F/F2, 420F/F2, 430F/F2 STL

W	417-6878	QUICK COUPLER, IT, BHL F 452 FOR USE WITH: 415F2, 416F, 416F2, 420F, 420F2, 430F, 430F2 STL BHL FOR USE WITH: IT Attachments REQUIRES: Supply group		\$8,375 NI
W	519-9196	KIT, COUPLER HYDRAULIC SUPPLY 29 FOR USE WITH: 416F2, 420F2, 430F2 417-6878 QUICK COUPLER, IT, BHL F FOR USE WITH: 416F2 Serial Number prefix HWB 420F2 Serial Number prefix HWC 430F2 Serial Number prefix HWE		\$1,958 NI
W	418-9071	KIT, COUPLER HYDRAULIC SUPPLY 33 FOR USE WITH: 416F, 420F and 430F 417-6878 QUICK COUPLER, IT, BHL F FOR USE WITH: 415F2, 416F, 416F2, 420F, 420F2, 422F, 422F2, 430F, 430F, 430F2 FOR USE WITH: 416F2 Serial Number prefix LBF and LYA 420F2 Serial number prefix LBS and LYB 430F2 Serial number prefix LYD 415F2 Serial Number prefix HWA, PF4 416F Serial Number prefix KSF, LWT 420F Serial Number SKR, LTG 422F Serial Number LRH 422F2 Serial Number LYF 430F Serial Number RDF, LDY		\$2,076 NI
W	418-9078	LINES, CONNECTOR 12 REQUIRES: 3rd valve FOR USE WITH: 415F2, 416F, 416F2, 420F, 420F2, 430F, 430F2 417-6878 QUICK COUPLER, IT, BHL F		\$1,243 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT IT (CONT.)

QUICK COUPLER IT for 450F

W	465-7298	QUICK COUPLER, IT, 450E/F 523 FOR USE WITH: 450E and 450F STL BHL FOR USE WITH: IT Attachments REQUIRES: Supply Group		\$9,972 NI
W	465-3300	KIT, COUPLER HYDRAULIC SUPPLY 29 FOR USE WITH: 450F and BHL 465-7298 QUICK COUPLER, IT, 450E/F		\$1,972 NI
W	465-9168	LINES, CONNECTOR 18 REQUIRES: 3rd valve FOR USE WITH: 450E/F and BHL 465-7298 QUICK COUPLER, IT, 450E/F		\$1,563 NI

COUPLER IT HOOKS

W	109-6712	HOOK, BLANK, IT 356		\$1,403 NI
W	113-2677	HOOK, FLAT BACK, IT 155		\$826 NI

BUCKETS for IT COUPLER - General Purpose - ALL 420 & 430 Models

W	251-1797	BUCKET-GP, 1.25 YD3, IT 957 Width 2262mm (89"), Capacity 0.96m3 (1.25yd3) Drilled to accept bolt-on teeth or cutting edge FOR USE WITH: All 420 & 430 Models		\$3,375 NI
W	251-1796	BUCKET-GP, 1.25 YD3, IT, BOT 1,018 Width 2262mm (89"), Capacity 0.96m3 (1.25yd3) INCLUDES: bolt-on teeth (9R-5866) FOR USE WITH: All 420 & 430 Models		\$3,771 NI
W	251-1795	BUCKET-GP, 1.25 YD3, IT, BOCE 1,111 Width 2262mm (89"), Capacity 0.96m3 (1.25yd3) INCLUDES: bolt-on cutting edge (9R-5321) FOR USE WITH: All 420 & 430 Models		\$3,847 NI
W	251-1800	BUCKET-GP, 1.31 YD3, IT 979 Width 2406mm (95"), Capacity 1.0m3 (1.31yd3) Drilled to accept bolt-on teeth or cutting edge FOR USE WITH: All 420 & 430 Models		\$3,549 NI
W	251-1799	BUCKET-GP, 1.31 YD3, IT, BOT 1,042 Width 2406mm (95"), Capacity 1.0m3 (1.31yd3) INCLUDES: bolt-on teeth (9R-5866) FOR USE WITH: All 420 & 430 Models WIDE BUCKET - RECOMMENDED WITH ALL-WHEEL-STEER		\$3,944 NI
W	251-1798	BUCKET-GP, 1.31 YD3, IT, BOCE 1,169 Width 2406mm (95"), Capacity 1.0m3 (1.31yd3) INCLUDES: bolt-on cutting edge (9R-5320) FOR USE WITH: All 420 & 430 Models WIDE BUCKET - RECOMMENDED WITH ALL-WHEEL-STEER		\$4,021 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT IT (CONT.)

BUCKETS for IT COUPLER - General Purpose - ALL 420 & 430 Models (Cont.)

W	251-1794	BUCKET-GP, 1.5 YD3, IT 1,030 Width 2406mm (95"), Capacity 1.15m3 (1.5yd3) Drilled to accept bolt-on teeth or cutting edge FOR USE WITH: All 420 & 430 Models WIDE BUCKET - RECOMMENDED WITH ALL-WHEEL-STEER		\$4,014 NI
W	251-1792	BUCKET-GP, 1.5 YD3, IT, BOCE 1,184 Width 2406mm (95"), Capacity 1.15m3 (1.5yd3) INCLUDES: bolt-on cutting edge (9R-5320) FOR USE WITH: All 420 & 430 Models WIDE BUCKET - RECOMMENDED WITH ALL-WHEEL-STEER		\$4,486 NI

BUCKETS for IT COUPLER - General Purpose - 446 & 450 Models

W	242-1654	BUCKET-GP, 1.5 YD3, IT, BOCE 1,500 INCLUDES: bolt-on cutting edge FOR USE WITH: All 446 & 450 Models		\$5,319 NI
W	242-1653	BUCKET-GP, 2.0 YD3, IT, BOCE 1,645 INCLUDES: bolt-on cutting edge FOR USE WITH: All 446 & 450 Models		\$6,549 NI
W	502-1117	BUCKET-GP, 1.75 YD3, IT, BOCE 18,970 Cap.1.34m3 (1.75yd3), width 2438mm (96") INCLUDES: 2 piece bolt-on cutting edge (2x 9U-9665) FOR USE WITH: Next Generation 440, 450		\$5,931 NI
W	506-0984	BUCKET-GP, 2.0 YD3, IT, BOCE 2,065 Cap.1.53m3 (2.0yd3), width 2438mm (96") INCLUDES: 2 piece bolt-on cutting edge (2x 9U-9665) FOR USE WITH: Next Generation 440, 450		\$6,549 NI

BUCKETS for IT COUPLER - Multi Purpose - All 420 & 430 Models

W	216-8810	BUCKET-MP, 1.3 YD3, IT 1,549 Width 2262mm (89"), Capacity 1.0m3 (1.3yd3) Drilled to accept bolt-on teeth or cutting edge FOR USE WITH: All Models Except 446 & 450 REQUIRES: 3rd valve		\$7,222 NI
W	232-2697	BUCKET-MP, 1.3 YD3, IT, BOT 1,654 Width 2262mm (89"), Capacity 1.0m3 (1.3yd3) INCLUDES: bolt-on teeth (9R-5866) FOR USE WITH: All Models Except 446 & 450 REQUIRES: 3rd valve		\$7,472 NI
W	232-2696	BUCKET-MP 1.3 YD3, IT, BOCE 1,677 Width 2262mm (89"), Capacity 1.0m3 (1.3yd3) INCLUDES: bolt-on cutting edge (9R-5321) FOR USE WITH: All Models Except 446 & 450 REQUIRES: 3rd valve		\$7,569 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT IT (CONT.)

BUCKETS for IT COUPLER - Multi Purpose - All 420 & 430 Models (Cont.)

W	216-8840	BUCKET-MP, 1.4 YD3, IT 1,612 Width 95" (2425mm), Capacity 1.07m3 (1.4yd3) Drilled to accept bolt-on teeth or cutting edge FOR USE WITH: All 420 & 430 Models WIDE BUCKET - RECOMMENDED WITH ALL-WHEEL-STEER REQUIRES: 3rd valve		\$7,486 NI
W	232-2699	BUCKET-MP, 1.4 YD3, IT, BOT 1,716 Width 95" (2425mm), Capacity 1.07m3 (1.4yd3) INCLUDES: bolt-on teeth (9R-5866) FOR USE WITH: All 420 & 430 Models WIDE BUCKET - RECOMMENDED WITH ALL-WHEEL-STEER REQUIRES: 3rd valve		\$7,736 NI
W	232-2698	BUCKET-MP 1.4 YD3, IT, BOCE 1,748 Width 95" (2425mm), Capacity 1.07m3 (1.4yd3) Includes bolt-on cutting edge (9R-5320) FOR USE WITH: All 420 & 430 Models WIDE BUCKET - RECOMMENDED WITH ALL-WHEEL-STEER REQUIRES: 3rd valve		\$7,840 NI

BUCKETS for IT COUPLER - Multi Purpose - 440, 450

W	506-1010	BUCKET-MP HD 1.75YD3 IT BOCE 2,414 Heavy Duty MP, Cap.1.34m3 (1.75yd3), width 2438mm (96") INCLUDES: 2 piece bolt-on cutting edge (2x 9U-9665) on front of the clam, 1 piece bolt-on cutting edge on dozer front. REQUIRES: Hydraulics, Loader 3rd Valve FOR USE WITH: Next Generation 440, 450		\$12,292 NI
W	506-1011	BUCKET-MP, XD, 1.75YD3,IT,BOCE 2,579 Extreme Duty MP, Cap.1.34m3 (1.75yd3), width 2438mm (96") INCLUDES: 2 piece bolt-on cutting edge (2x 9U-9665) on front of the clam, 1 piece bolt-on cutting edge on back of the clam & dozer front REQUIRES: Hydraulics, Loader 3rd Valve FOR USE WITH: Next Generation 440, 450		\$13,736 NI

BUCKETS for IT COUPLER - Side Dump

W	571-8458	BUCKET-SD, 1.25 YD3, IT, BOCE 2,178 Side Dump Bucket, left side dumping. Width 2770 mm (109"). Capacity: 0.95 m3 (1.25 yd3) fill factor 100%, Height: 995mm (39.2") INCLUDES: hydr.lines with Turn QDs and a 3 piece BOCE FOR USE WITH: IT Coupler REQUIRES: 3rd Valve on the machine and Turn QDs on machine		\$17,028 NI
---	----------	---	--	--------------------

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT IT (CONT.)

BROOMS, BA25 - Angle

W	600-8979	BROOM, MANUAL ANGLE, BA25 0 Excluding hook group, 700mm (27.5") brush diameter Manual angling - 0, 15 and 30 degrees left or right of center Sweeping width straight -- max angled: 2500mm (98")-- 2200mm(87") Brush material - 50% Polypropylene / 50% Steel Wire INCLUDES: Turn/Twist to connect QDs REQUIRES: Machine side: IT Quick Coupler REQUIRES: Broom side: hook group (see "BROOM KITS" below)		\$12,938 NI
W	600-8980	BROOM, HYD. ANGLE, BA25, 12V 0 Excluding hook group, 700mm (27.5") brush diameter Hydraulic angling 30 degr. left/right of center using 12V Divert Valve Sweeping width straight -- max angled: 2500mm (98")-- 2200mm(87") Brush material - 50% Polypropylene / 50% Steel Wire INCLUDES: Turn/Twist to connect QDs REQUIRES: Machine side: IT Quick Coupler REQUIRES: Broom side: hook group (see "BROOM KITS" below)		\$16,667 NI
W	497-9461	KIT, BROOM TANK,BA22-25,105GAL 325 FOR USE WITH: BA25 REQUIRES: 609-9555 KIT, BROOM, SPRAY, BA22/BA25		\$4,194 NI
W	497-9458	KIT, BROOM, SPRAY, BA25, 12V 51 Spray kit, INCLUDES: Water pump, filter, hoses, fixing materials, spray nozzles. NOT INCLUDED: Water tank FOR USE WITH: BA25 REQUIRES: 497-9461 KIT, BROOM TANK,BA22-25,105GAL		\$1,278 NI
W	609-9555	KIT, BROOM, SPRAY, BA22/BA25 36 Spray kit, INCLUDES: Water pump, filter, hoses, fixing materials, spray nozzles. NOT INCLUDED: Water tank FOR USE WITH: BA25 REQUIRES: 497-9461 KIT, BROOM TANK,BA22-25,105GAL		\$1,472 NI

BROOMS, BP25 - Pick-up

W	600-8976	BROOM, PICKUP, BP25, 12V-24V 1,433 Excluding hook group, Sweeping width: 2500mm (98.4") Brushes: diameter 700mm (27.5") & 100% Polypropylene INCLUDES: Water sprinklers, 0.4m3 (100 Gal) water tank, 12V-24V water pump, Turn/Twist to connect QDs, elect. Harness REQUIRES: Machine side: IT Quick Coupler REQUIRES: Broom side: hook group (see "BROOM KITS" below) REQUIRES: 588-4294: KIT, ROADING, BP when roading		\$22,889 NI
---	----------	--	--	-------------

BROOMS - hooks groups and kits

W	487-8490	HOOK, BROOM, IT 64 INCLUDES: 2 hooks for IT 14/28 QC and fixing materials FOR USE WITH: standard quick coupler IT14/28		\$764 NI
---	----------	---	--	----------

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT IT (CONT.)

BROOMS - hooks groups and kits (Cont.)

W	588-4294	KIT, ROADING, BP 22 Locking device to prevent the broom from dropping during roading. FOR USE WITH: BP22 and BP25 NOTE: Required for roading in certain parts of the EU. Consult dealer for clarification.		\$972 NI
---	----------	--	--	-----------------

BROOM QUICK DISCONNECT KITS

W	196-4191	KIT, QDS, PUSH, SIZE 12 3 FOR USE WITH: machines with Push to Connect Quick Disc. Coupl. Size 12		\$208 NI
W	177-0893	KIT, BROOM, ELEC, BHL 7		\$292 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT IT (CONT.)

CARRIAGES and FORK TINES for IT QUICK COUPLER

W	6W-8832	CARRIAGE, PALLET, 61", IT 699 Standard carriage. Does NOT include tines FOR USE WITH: standard/IT quick coupler REQUIRES: 2 tines, please order seperately Please order quantity of 2:		\$2,511 NI
W	292-4571	CARRIAGE, PALLET 60", IT 589 Standard carriage. Does NOT include tines FOR USE WITH: standard/IT quick coupler FOR USE WITH THE FOLLOWING FORK TINES: 195-6935, 195-6937 OR 195-6939 Please order quantity of 2:		\$2,556 NI
W	195-6935	FORK TINE, 2" X 5" X 48" 216		\$806 NI
W	195-6937	FORK TINE, 2" X 5" X 42" 198		\$764 NI
W	195-6939	FORK TINE, 2" X 5" X 54" 232		\$833 NI

CARRIAGE WITH HYDRAULIC ADJUSTABLE FORKS for IT QUICK COUPLER

W	573-4593	CARRIAGE, HYD, IT, FORKS 48" 1,193 Carriage with hydraulic adjustable forks/tines Overall Width-Height: 1900mm (75") - 1010mm (40"), incl. lines + QDs FOR USE WITH: standard/IT quick coupler		\$11,111 NI
---	----------	--	--	--------------------

MATERIAL HANDLING ARM for IT QUICK COUPLER

W	229-9714	ARM, MATERIAL HANDLING, IT 990 For safe handling of bulky objects. Mechanically adjustable to 3 positions, length from 2.01m (79") to 2.97m (117") to 3.93 (155") Rated Capacity 2095 kg (4619 lbs). FOR USE WITH: standard/IT quick coupler		\$7,333 NI
W	169-3945	TRUSS BOOM 402 Length 4.00m (157.5") Rated Capacity 5000 kg (11023 lbs) FOR USE WITH: standard/IT quick coupler		\$5,667 NI
W	169-6460	HOOK, LIFTING 461 Distance between coupler cylinder and hook center 500mm (19.7") Rated Capacity 5000 kg (11023 lbs) FOR USE WITH: standard/IT quick coupler		\$4,868 NI

RAKE for IT QUICK COUPLER

W	230-5865	RAKE, LOADER, IT, 92" 1,200 Raking width: 2108mm (83"), Height:1270mm (50") Number of teeth: 7, Tooth spacing 330mm (13") FOR USE WITH: standard/IT quick coupler		\$7,104 NI
---	----------	---	--	-------------------

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER CURRENT IT (CONT.)

SNOW PLOWS for IT QUICK COUPLER

Availability can be restricted due to snow season.
 Please contact your BCP Work Tools contact.

W	481-3671	SNOW PLOW, 9', IT 1,900 Hydraulic Angling - 30 degrees left or right of center Overall width: 2740 mm (108"), Blade height: 800 mm (31") 2 trip edges 203 mm (8") height each with a 1 piece bolt-on cutting edge and each with 4 adjust. trip springs 2 heavy duty adjustable skid feet Hydraulic lines with "Twist to Connect" quick disconnects FOR USE WITH: standard/IT quick coupler REQUIRES: 3rd Valve on the machine		\$10,833 NI
W	481-3672	SNOW PLOW, 10', IT 1,990 Hydraulic Angling - 30 degrees left or right of center Overall width: 3045 mm (120"), Blade height: 800 mm (31") 2 trip edges 203 mm (8") height each with a 1 piece bolt-on cutting edge and each with 4 adjust. trip springs 2 heavy duty adjustable skid feet Hydraulic lines with "Twist to Connect" quick disconnects FOR USE WITH: standard/IT quick coupler REQUIRES: 3rd Valve on the machine		\$11,306 NI
W	481-3673	SNOW PLOW, 12', IT 2,185 Hydraulic Angling - 30 degrees left or right of center Overall width: 3658 mm (144"), Blade height: 800 mm (31") 2 trip edges 203 mm (8") height each with a 1 piece bolt-on cutting edge and each with 4 adjust. trip springs 2 heavy duty adjustable skid feet Hydraulic lines with "Twist to Connect" quick disconnects FOR USE WITH: standard/IT quick coupler REQUIRES: 3rd Valve on the machine		\$12,111 NI

SNOW STRAIGHT PUSHES

Availability can be restricted due to snow season.
 Please contact your BCP Work Tools contact.

W	479-8087	SNOW PUSH, 10', IT 1,800 3219 mm (126") overall width, 3067 mm (120") working width 906mm (36") moldboard height, 2 heavy duty adjustable skid shoes 2 trip edges 137mm (5.4") height each with a 1 piece STEEL Bolt-on-Cutting edge and each with 4 adjustable trip springs FOR USE WITH: standard/IT quick coupler		\$8,806 NI
W	479-8091	SNOW PUSH, 12', IT 1,990 3829 mm (150") overall width, 3677 mm (144") working width 906mm (36") moldboard height, 2 heavy duty adjustable skid shoes 2 trip edges 137mm (5.4") height each with a 1 piece STEEL Bolt-on-Cutting edge and each with 4 adjustable trip springs FOR USE WITH: standard/IT quick coupler		\$9,681 NI
W	508-8290	SNOW PUSH, 10', IT, R.TRIP 1,678 Incl. 2 section trip edge each with 4 adjustable springs, each with a bolt-on rubber edge 38mmx203mm (1.5"x 8") approx 50mm(2") adjust. Width 3.05m (10'), with bolt side skids, Overall Height 966mm (38") FOR USE WITH: standard/IT quick coupler		\$8,347 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-------------------------------	--------------------	-------------------------

LOADER CURRENT IT (CONT.)

SNOW STRAIGHT PUSHES (Cont.)

W	508-8295	SNOW PUSH, 12', IT, R.TRIP 1,865 Incl. 2 section trip edge each with 4 adjustable springs, each with a bolt-on rubber edge 38mmx203mm (1.5"x 8") approx 50mm(2") adjust. Width 3.66m (12'), with bolt side skids, Overall Height 966mm (38") FOR USE WITH: standard/IT quick coupler	1,865	\$9,125 NI
---	----------	---	-------	-------------------

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER INDUSTRIAL CURRENT

INDUSTRIAL LOADER ATTACHMENTS for 414E IL & 415F2 IL:

W	461-9717	BOX, BLADE/SCARIFIER 0 Weight = 1440 lbs (652kgs) 89" (2260mm) overall width, 88" (2235mm) working width, 24.5" (622mm) moldboard height 2 Reversible Bolt-on cutting edges, 1 piece front and 1 piece rear 8 scarifier shanks, 2 heavy duty reversible side routers REQUIRES: Category II 3-point hitch INCLUDES: 3 attachment pins		\$8,444 NI
W	470-5247	KIT, DUAL TILT CYLINDER 0 Converts single tilt 3-point hitch to dual tilt system to allow both left and right vertical articulation of the hitch. Refer to Cat Service Information System (SIS) Refer to Special Instructions M0066044 for installation instructions. INCLUDES: Hydraulic Lines FOR USE WITH: 415F2IL		\$2,333 NI
W	572-3103	KIT, POWER TAKE OFF 0 Retrofit kit hydraulic PTO 35HP at 540 RPM, compatible Class 2 PTO FOR USE WITH: 415F2 IL RECOMMENDED: 560-0641 KIT-HAND THROTTLE Installation time 24 hours see M0119215 and OMM SEBU9310-08		\$3,979 NI

Buckets for 414E IL see section "LOADER Non-Current Pin-on (pre F)":
 GENERAL PURPOSE BUCKETS SINGLE TILT PIN-ON
 MULTI PURPOSE BUCKETS SINGLE TILT PIN-ON
 Buckets for 415F2 IL see section "LOADER Current Pin-on (F, F2)":
 GENERAL PURPOSE BUCKETS SINGLE TILT PIN-ON
 MULTI PURPOSE BUCKETS SINGLE TILT PIN-ON

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER NON CURRENT PIN-ON

SINGLE TILT PIN-ON (FRONT) - General Purpose Buckets 414-436 Pre F

W	251-1780	BUCKET-GP, 1.0 YD3, PO 776 Cap 0.75m3 (1.0yd3), width 2262mm (89"), base edge FOR USE WITH: 414E, 416E/E2 or earlier		\$2,861 NI
W	251-1789	BUCKET-GP, 1.25 YD3, PO 965 Cap 0.96m3 (1.25yd3), width 2262mm (89"), base edge Drilled to accept bolt-on teeth or cutting edge FOR US WITH: ALL Models E series or earlier excl 446 & 450		\$3,368 NI
W	251-1786	BUCKET-GP, 1.4 YD3, PO 1,012 Cap 1.07m3 (1.4yd3), width 2262mm (89"), base edge Drilled to accept bolt-on teeth or cutting edge FOR US WITH: ALL Models E series or earlier excl 446 & 450		\$3,556 NI
W	251-1777	BUCKET-GP, 1.5 YD3, PO 1,056 Cap 1.15m3 (1.5yd3), width 2406mm (95"), base edge FOR USE WITH: 430E & 436E or earlier		\$4,306 NI

SINGLE TILT PIN-ON (FRONT) - General Purpose Buckets 446, 450 Pre F

W	270-9163	BUCKET-GP, 1.75 YD3, PO, BOCE 1,473 Cap 1.35m3 (1.75yd3), width 2434mm (96") INCLUDES: 2 piece bolt-on cutting edge (2x 9U-9665) FOR USE WITH: 450E/F If ordering these as replacement buckets for 446D/446B, please order updated service brace 324-0720.		\$5,931 NI
---	----------	---	--	------------

SINGLE TILT PIN-ON (FRONT) - Multi Purpose Buckets 414-436 Pre F

W	216-8800	BUCKET-MP, 1.3 YD3, PO 1,593 Cap 1.0m3 (1.3yd3), width 2279mm (90"), base edge, no brackets REQUIRES: Hydraulics, Loader 3rd Valve		\$7,222 NI
W	232-2681	BUCKET-MP, 1.3 YD3, PO, BOCE 1,719 Cap 1.0m3 (1.3yd3), width 2279mm (90"), no brackets INCLUDES: bolt-on cutting edge (9R-5321) REQUIRES: Hydraulics, Loader 3rd Valve		\$7,572 NI
W	232-2685	BUCKET-MP, 1.3 YD3, PO, FORKS 1,958 Cap 1.0m3 (1.3yd3), width 2279mm (90"), base edge INCLUDES: fold over forks REQUIRES: Hydraulics, Loader 3rd Valve		\$9,181 NI
W	216-8820	BUCKET-MP, 1.4 YD3, PO 1,655 Cap 1.07m3 (1.3yd3), width 2425mm (95"), base edge, no brackets REQUIRES: Hydraulics, Loader 3rd Valve		\$7,486 NI
W	232-2690	BUCKET-MP, 1.4 YD3, PO, FORKS 2,003 Cap 1.07m3 (1.3yd3), width 2425mm (95"), base edge INCLUDES: fold over forks REQUIRES: Hydraulics, Loader 3rd Valve		\$9,444 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

LOADER NON CURRENT PIN-ON (CONT.)

SINGLE TILT PIN-ON (FRONT) - Multi Purpose Buckets 446 B, D Series

W	272-1701	BUCKET-MP,1.5YD3,PO,BRKTS,BOCE 2,105 Cap 1.15m3 (1.5yd3), width 2425mm (95") INCLUDES: fork mounting brackets & bolt-on cutting edge (2x 118-7110) REQUIRES: Hydraulics, Loader 3rd Valve When ordering these as replacement buckets for 446D/446B, please order updated service brace 324-0720.		\$9,681 NI
---	----------	---	--	------------

SINGLE TILT PIN-ON (FRONT) - Forks 414-436 Pre F Series

W	231-5197	FORK, PALLET, 48", BHL ST, C-E 1,050 INCLUDES: 1524mm (60") wide carriage and 1219mm (48") tines non-floating tines FOR USE WITH: pre F Series Machines		\$6,556 NI
---	----------	--	--	------------

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444

COMPATIBILITY

The work tools in this section will fit on following sales models (pin sizes and pin spread are the same for all these models)

Centre Pivot Machines:

415F/F2 - 416D/E/F/F2 - 420D/E/F/F2 - 430D/E/F/F2

Next Generation: 415 - 440

Side Shift Machines:

416D/E/F/F2 - 420D - 422D/E/E2/F/F2 - 426F2 - 427F2 - 428D/E/E2/F/F2

430D - 432D/E/E2/F/F2 - 434E/E2/F/F2 - 438D - 444E/E2/F/F2 - 442D

Next Generation: 415 - 440

Following sub-sections are in this section:

COMPATIBILITY QUICK DISCONNECTS

QUICK COUPLERS: DUAL LOCK PIN GRABBER

HYDRAULIC KITS FOR DUAL LOCK PIN GRABBER COUPLERS

QUICK COUPLERS: PIN PULLER

BUCKETS:

QUICK DISCONNECTS

From F2 the quick disconnects have changed into "Twist to Connect" F1 and earlier have "Push to Connect". If you have Aux on the stick, these are the correct Quick Disconnects:

P	442-9566	KIT, HOE, COUPLING Q-DISCON 0	\$414 NI
		'Twist to Connect' hydr.QDs, incl 1x 439-1590 Fem.+ 1x 439-1591 Male FOR USE WITH: F2 series For pre F2 series, order: 1x 106-0401 Female QD + 1x 106-0406 Male QD	

QUICK COUPLERS - Dual Lock Pin-Grabber

All quick couplers need to be fitted to the machine stick using the original bucket pins which come with a new machine. Otherwise order an extra set.

W	444-7500	COUPLER, PG, MAN.D.LOCK, BHL 192	\$2,194 NI
		Mechanical quick coupler with dual lock for backhoe buckets (Base machine includes 1 set of buckets pins) INCLUDES: 1 set of pins and hardware to attach 1 bucket REQUIRES: 178-3593 Bucket Pins for EACH ADDITIONAL Bucket. FOR USE WITH: E, F/F2 Series and Next Generation 415 - 444	
W	485-5303	COUPLER, PG, HYD.D.LOCK,BHL 192	\$4,285 NI
		Hydraulic quick coupler with dual lock for backhoe buckets. (Base machine includes 1 set of buckets pins) INCLUDES: 1 set of pins and hardware to attach 1 bucket REQUIRES: 178-3593 Bucket Pins for EACH ADDITIONAL Bucket. REQUIRES: Hydraulics to operate the quick coupler. See hydraulic kits for quick coupler for field installed retrofit kits. FOR USE WITH: E, F/F2 Series and Next Generation 415 - 444	

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

QUICK COUPLERS - Dual Lock Pin-Grabber (Cont.)

W	178-3593	PINS, BUCKET, BHL-F, 45MM-50MM 6 Includes bucket pins and hardware FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444		\$125 NI
---	----------	--	--	----------

HYDRAULIC KITS FOR DUAL LOCK PIN GRABBER COUPLERS

W	585-0341	KIT, LINES, HYD CPLR 14FT S-STK 0 Kit Quick Coupler Hoe lines to operate hydraulic PG Dual Lock QC. FOR USE WITH: Next Generation: 415 - 440 with Standard Stick see installation instructions M0105743		\$1,972 NI
W	585-0342	KIT, LINES, HYD CPLR 14FT E-STK 0 Kit Quick Coupler Hoe lines to operate hydraulic PG Dual Lock QC. FOR USE WITH: Next Generation: 415 - 440 with E-Stick see installation instructions M0105743		\$1,972 NI
W	468-7970	KIT, LINES, HYD CPLR 14FT S-STK 0 FOR USE WITH: 415F2, 416F2, or 420F2 machines FOR FITTING REFER SPECIAL INSTRUCTIONS #REHS6634		\$1,972 NI
W	468-7971	KIT, LINES, HYD CPLR 14FT E-STK 0 FOR USE WITH: 415F2, 416F2, or 420F2 machines FOR FITTING REFER SPECIAL INSTRUCTIONS #REHS6635		\$1,972 NI
W	468-7972	KIT, LINES, HYD CPLR 16FT S-STK 0 FOR USE WITH: 430F2 machines FOR FITTING REFER SPECIAL INSTRUCTIONS #REHS6636		\$1,972 NI
W	468-7973	KIT, LINES, HYD CPLR 16FT E-STK 0 FOR USE WITH: 430F2 machines FOR FITTING REFER SPECIAL INSTRUCTIONS #REHS6637		\$1,972 NI

QUICK COUPLERS - Pin Puller

W	494-1938	QUICK COUPLER, PIN PULLER, CASE 214 Manual Pin-Puller for backhoe work tools includes one set of pins and hardware for attaching a Caterpillar bucket or work tool and one additional bucket link pin to connect a Case bucket. REQUIRES: 178-3593 bucket pins for EACH ADDITIONAL bucket or work tool. FOR USE WITH: Cat D, E, & F Series buckets, Case Super L/M Series buckets or work tools.		\$2,701 NI
W	487-6056	QUICK COUPLER, PIN PULLER, DEERE 210 Manual Pin-Puller for backhoe work tools includes one set of pins and hardware for attaching a Caterpillar bucket or work tool and one additional bucket link pin to connect a Deere bucket. FOR USE WITH: Cat D, E, & F Series buckets, Deere 310SE/SG buckets or work tools. REQUIRES: 178-3593 bucket pins for EACH ADDITIONAL bucket or work tool.		\$2,701 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

QUICK COUPLERS - 1/4 YD Pin Lock

P	544-1901	COUPLER, PIN LOCK, BL F 0 Manual coupler for dedicated 1/4 YD pin-lock backhoe work tools. Includes one set of mounting pins and hardware for attaching one work tool		\$1,528 NI
W	226-1126	COUPLER, TILTING PIN LOCK 240 Manual coupler with hydraulic tilting for dedicated 1/4 YD pin-lock backhoe work tools. FOR USE WITH: D Series standard and E-stick configuration For use with E Series standard stick configuration only.: Includes connector lines COMPATIBLE WITH: Wain-Roy products		\$6,840 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

BUCKETS for PIN-ON - Standard Duty Pin-on Teeth

For light duty excavation in soft soil or clay.
Includes weld on tooth adapters and tooth tips (DRS)
Replacement DRS tooth tips (order via parts/Antares, no Bridge)
208-5235 Penetration Tooth (installed ex factory) *
208-5232 Chisel Tooth *
208-5239 Sharp Tooth *
208-5237 Sharp Twin Tooth *
* = Per tooth required: 1 x 201-1239 Retainer and 1 x 500-0269 Pin

W	219-3410	BUCKET, 12", 2.8 FT3 214 Actual width range over outside G.E.T. tips 13.5"-14.2" Includes 3 tooth tips and pins for 12" buckets		\$1,146 NI
W	219-3380	BUCKET, 18", 4.2 FT3 254 Width: 458mm (18"), Cap: 0.12m3 (4.2ft3), Includes 4 tooth tips .		\$1,250 NI
W	219-3381	BUCKET, 24", 6.2 FT3 291 Width: 610mm (24"), Cap: 0.18m3 (6.2ft3), Includes 5 tooth tips		\$1,382 NI
W	219-3382	BUCKET, 30", 8.2 FT3 324 Width: 762mm (30"), Cap: 0.23m3 (8.2ft3), Includes 5 tooth tips		\$1,507 NI
W	219-3383	BUCKET, 36", 10.3 FT3 364 Width: 914mm (36"), Cap: 0.29m3 (10.3ft3), Includes 6 tooth tips.		\$1,653 NI

BUCKETS for PIN-ON - Heavy Duty Pin-on Teeth

For excavation in semi-rocky soil or hard bank material. Includes weld on tooth adapters and tooth tips (DRS) and back wear strips.
Replacement DRS tooth tips (order via parts/Antares, no Bridge)
208-5235 Penetration Tooth (installed ex factory) *
208-5232 Chisel Tooth *
208-5239 Sharp Tooth *
208-5237 Sharp Twin Tooth *
* = Per tooth required: 1 x 201-1239 Retainer and 1 x 500-0269 Pin

W	219-3411	BUCKET-HD, 12", 2.8 FT3 238 Width: 305mm (12"), Cap: 0.079m3 (2.8ft3) Actual width range over outside G.E.T. tips 13.5"-14.2" Includes 3 tooth tips and pins for 12" buckets		\$1,542 NI
W	219-3385	BUCKET-HD, 16", 3.7 FT3 280 Width: 406mm (16"), Cap: 0.11m3 (3.7ft3), Includes 3 tooth tips		\$1,611 NI
W	219-3386	BUCKET-HD, 18", 4.2 FT3 284 Width: 457mm (18"), Cap: 0.118m3 (4.2ft3), Includes 4 tooth tips		\$1,653 NI
W	219-3387	BUCKET-HD, 24", 6.2 FT3 333 Width: 610mm (24"), Cap: 0.175m3 (6.2ft3), Includes 5 tooth tips		\$1,778 NI
W	219-3388	BUCKET-HD, 30", 8.2 FT3 368 Width: 762mm (30"), Cap: 0.233m3 (8.2ft3), Includes 5 tooth tips		\$1,903 NI
W	219-3389	BUCKET-HD, 36", 10.3 FT3 417 Width: 914mm (36"), Cap: 0.292m3 (10.3ft3), Includes 6 tooth tips		\$2,049 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

BUCKETS for PIN-ON - Heavy Duty Rock Pin-on Teeth

For rocky conditions. Includes weld-on tooth adapters and tooth tips (DRS) and back wear strips.

Replacement DRS tooth tips (order via parts/Antares, no Bridge order):

- 208-5235 Penetration Tooth (installed ex factory) *
- 208-5232 Chisel Tooth *
- 208-5239 Sharp Tooth *
- 208-5237 Sharp Twin Tooth *

* = Per tooth required: 1 x 201-1239 Retainer and 1 x 500-0269 Pin

W	219-3412	BUCKET-ROCK, HD, 12", 2.5 FT3	250	\$1,701 NI
		Width: 305mm (12"), Cap: 0.07m3 (2.5ft3) Actual width range over outside G.E.T. tips 13.4"-13.9" Includes 3 tooth tips and pins for 12" bucket		
W	219-3395	BUCKET-ROCK, HD, 18", 4.6 FT3	304	\$1,833 NI
		Width: 457mm (18"), Cap: 0.13m3 (4.6ft3), Includes 4 tooth tips		
W	219-3396	BUCKET-ROCK, HD, 24", 7.0 FT3	381	\$1,979 NI
		Width: 610mm (24"), Cap: 0.2m3 (7ft3), Includes 5 tooth tips		
W	219-3397	BUCKET-ROCK, HD, 30", 9.5 FT3	396	\$2,132 NI
		Width: 762mm (30"), Cap: 0.27m3 (9.5ft3), Includes 5 tooth tips		
W	219-3398	BUCKET-ROCK, HD, 36", 11.5 FT3	451	\$2,257 NI
		Width: 914mm (36"), Cap: 0.33m3 (11.5ft3), Includes 6 tooth tips		

BUCKETS for PIN-ON - Cemetery

Special designed to trench graves, the shape allows vertical walls and and flat bottoms.

W	242-5039	BUCKET-CEMETERY, 36", 8.4 FT3	521	\$3,806 NI
		Width: 914mm (36"), Cap.: 0.238m3 (8.4 ft3), incl 5x J225 Long tip Tip Radius: 802mm (31.6") FOR USE WITH: Pin-on, requires bucket pins		
W	219-8655	BUCKET-CEMETERY, 36", 8.4 FT3	486	\$3,285 NI
		Width: 914mm (36"), Cap: 0.238m3 (8.4 ft3), incl 1 piece BOCE Tip Radius: 728mm (28.7") FOR USE WITH: Pin-on, requires bucket pins		

BUCKETS for PIN-ON - Cribbing

Super narrow, this bucket is specifically designed for railroad application working in conjunction with thumb. Your design allows small trench and maintenance between rails.

W	226-5743	BUCKET-CRIBBING, 8", 1.4 FT3	288	\$2,208 NI
		Width: 222mm (8"), Cap.: 0.040m3 (1.4 ft3), incl 2 x J200 Long tip Tip Radius: 1,284mm (50.6") FOR USE WITH: Pin-on, requires bucket pins		
W	216-3294	BUCKET-CRIBBING, 9", 2.1FT3	320	\$1,257 NI
		Trenching bucket width 230mm (9"), incl 2 bolt on teeth & side cutters FOR USE WITH: standard stick and E-sticks		

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

BUCKETS for PIN-ON - Coral Pin-on Teeth

Replacement DRS tooth tips (order via parts/Antares, no Bridge order):

208-5232 Chisel Tooth *

* = Per tooth required: 1 x 201-1239 Retainer and 1 x 500-0269 Pin

W	219-3413	BUCKET-CORAL, 12", 2.3 FT3	271	\$2,076 NI
		Width: 305mm (12"), Cap: 0.06m3 (2.3ft3)		
		Actual width range over outside G.E.T. tips 13.4"-13.9"		
		Includes 4 tooth tips		
W	219-3401	BUCKET-CORAL, 24", 5.0 FT3	384	\$2,826 NI
		Width: 610mm (24"), Cap: 0.14m3 (5ft3), Includes 8 tooth tips		
W	219-3402	BUCKET-CORAL, 30", 6.7 FT3	441	\$3,132 NI
		Width: 762mm (30"), Cap: 0.19m3 (6.7ft3), Includes 10 tooth tips		

BUCKETS for PIN-ON - Ditch Cleaning

For trenching, grading and finish work. Includes water holes.

W	212-8738	BUCKET-DC, 48", 13.0 FT3	453	\$2,875 NI
		Width: 1230mm (48"), Cap: 0.37m3 (13ft3)		
W	212-8740	BUCKET-DC, 54", 14.8 FT3	491	\$3,104 NI
		Width: 1380mm (54"), Cap: 0.42m3 (14.8ft3)		
W	212-8741	BUCKET-DC, 60", 16.7 FT3	530	\$3,333 NI
		Width: 1530mm (60"), Cap: 0.47m3 (16.7ft3)		

BUCKETS for PIN-ON - Grading (Mud)

Designed for grading with higher capacity and suited to carry buckets.

W	390-7473	BUCKET-GRADING, 47", 14.5 FT3	0	\$3,181 NI
		Width: 1200mm (47"), Cap: 0.41m3 (0.54yd3)		
		Base bucket without bolt-on cutting edge or pins		
W	388-9668	BUCKET-GRADING, 47", BOCE/PIN	633	\$3,493 NI
		Width: 1200mm (47"), Cap: 0.41m3 (0.54yd3)		
		Includes Pins & 1-piece bolt-on cutting edge		
W	390-7474	BUCKET-GRADING, 59", 18.4 FT3	0	\$3,667 NI
		Width: 1500mm (59"), Cap: 0.52m3 (0.68yd3)		
		Base bucket without bolt-on cutting edge or pins		
W	388-9669	BUCKET-GRADING, 59", BOCE/PIN	744	\$4,021 NI
		Width: 1500mm (59"), Cap: 0.52m3 (0.68yd3)		
		Includes Pins & 1-piece bolt-on cutting edge		

BUCKETS for PIN-ON - High Capacity Pin-on Teeth

Replacement DRS tooth tips (order via parts/Antares, no Bridge order):

208-5235 Penetration Tooth (installed ex factory) *

208-5232 Chisel Tooth *

208-5239 Sharp Tooth *

208-5237 Sharp Twin Tooth *

* = Per tooth required: 1 x 201-1239 Retainer and 1 x 500-0269 Pin

W	219-3390	BUCKET-HC, 18", 6.4 FT3	322	\$1,361 NI
		Width: 458mm (18"), Cap: 0.18m3 (6.4ft3), Includes 4 tooth tips		

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

BUCKETS for PIN-ON - High Capacity Pin-on Teeth (Cont.)

W	219-3391	BUCKET-HC, 24", 8.5 FT3 377 Width: 610mm (24"), Cap: 0.24m3 (8.5ft3), Includes 5 tooth tips		\$1,493 NI
W	219-3392	BUCKET-HC, 30", 11.3 FT3 430 Width: 762mm (30"), Cap: 0.32m3 (11.3ft3), Includes 5 tooth tips		\$1,660 NI
W	219-3393	BUCKET-HC, 36", 13.4 FT3 472 Width: 914mm (36"), Cap: 0.38m3 (13.4ft3), Includes 6 tooth tips		\$1,792 NI

BUCKETS for PIN-ON: - Soil Excavation Pin-on Teeth

Replacement DRS tooth tips (order via parts/Antares, no Bridge order):

- 208-5235 Penetration Tooth (installed ex factory) *
- 208-5232 Chisel Tooth *
- 208-5239 Sharp Tooth *
- 208-5237 Sharp Twin Tooth *

* = Per tooth required: 1 x 201-1239 Retainer and 1 x 500-0269 Pin

W	254-8940	BUCKET-SOIL, 18", 6.4 FT3 336 Includes 4 angle-down adapters and soil tooth tips.		\$1,799 NI
W	254-8941	BUCKET-SOIL, 24", 8.5 FT3 395 Includes 5 angle-down adapters and soil tooth tips.		\$1,931 NI
W	254-8942	BUCKET-SOIL, 30", 11.3 FT3 434 Includes 5 angle-down adapters and soil tooth tips.		\$2,097 NI
W	254-8943	BUCKET-SOIL, 36", 13.4 FT3 491 Includes 6 angle-down adapters and soil tooth tips.		\$2,229 NI

BUCKETS for 1/4 YD PIN LOCK - Ditch Cleaning

W	275-8776	BUCKET-DC,48",11.9 FT3,BOCE,PL 498 INCLUDES: bolt-on cutting edge FOR USE WITH: 1/4 YD Pin Lock Quick Coupler		\$2,903 NI
---	----------	--	--	------------

BUCKETS for 1/4 YD PIN LOCK - Heavy Duty Pin-on Teeth

Includes weld on DRS tooth adapters and tooth tips.

Replacement DRS tooth tips (order via parts/Antares, no Bridge order):

- 208-5235 Penetration Tooth (installed ex factory) *
- 208-5232 Chisel Tooth *
- 208-5239 Sharp Tooth *
- 208-5237 Sharp Twin Tooth *

* = Per tooth required: 1 x 201-1239 Retainer and 1 x 500-0269 Pin

W	247-1947	BUCKET-HD, 12", 3.4 FT3, PL 249 Width: 305mm (12"), Cap: 0.09m3 (3.4ft3), Includes 3 tooth tips FOR USE WITH: 1/4 YD Pin Lock Quick Coupler		\$1,632 NI
W	247-1948	BUCKET-HD, 16", 4.3 FT3, PL 288 Width: 406mm (16"), Cap: 0.12m3 (4.3ft3), Includes 3 tooth tips. FOR USE WITH: 1/4 YD Pin Lock Quick Coupler		\$1,701 NI
W	247-1949	BUCKET-HD, 18", 4.9 FT3, PL 304 Width: 457mm (18"), Cap: 0.14m3 (4.9ft3), Includes 4 tooth tips FOR USE WITH: 1/4 YD Pin Lock Quick Coupler		\$1,743 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

BUCKETS for 1/4 YD PIN LOCK - Heavy Duty Pin-on Teeth (Cont.)

W	247-1950	BUCKET-HD, 24", 7.3 FT3, PL 370 Width: 610mm (24"), Cap: 0.2m3 (7.3ft3), Includes 5 tooth tips FOR USE WITH: 1/4 YD Pin Lock Quick Coupler		\$1,889 NI
W	247-1951	BUCKET-HD, 30", 9.7 FT3, PL 428 Width: 762mm (30"), Cap: 0.28m3 (9.7ft3), Includes 5 tooth tips. FOR USE WITH: 1/4 YD Pin Lock Quick Coupler		\$2,049 NI
W	247-1952	BUCKET-HD, 36", 12.2 FT3, PL 494 Width: 914mm (36"), Cap: 0.34m3 (12.2ft3), Includes 6 tooth tips FOR USE WITH: 1/4 YD Pin Lock Quick Coupler		\$2,201 NI

BUCKETS for 1/4 YD PIN LOCK - High Capacity Pin-on Teeth

Includes weld on tooth adapters and tooth tips.

W	247-1954	BUCKET-HC, 16", 5.6 FT3, PL 327 Width: 406mm (16"), Cap: 0.16m3 (5.6ft3), Includes 3 tooth tips FOR USE WITH: 1/4 YD Pin Lock Quick Coupler		\$1,771 NI
W	247-1955	BUCKET-HC, 18", 6.5 FT3, PL 346 Width: 457mm (18"), Cap: 0.18m3 (6.5ft3), Includes 4 tooth tips FOR USE WITH: 1/4 YD Pin Lock Quick Coupler		\$1,826 NI
W	247-1956	BUCKET-HC, 24", 9.6 FT3, PL 414 Width: 610mm (24"), Cap: 0.26m3 (9.6ft3), Includes 5 tooth tips FOR USE WITH: 1/4 YD Pin Lock Quick Coupler		\$2,014 NI
W	247-1957	BUCKET-HC, 30", 12.9 FT3, PL 475 Width: 762mm (30"), Cap: 0.36m3 (12.9ft3), Includes 5 tooth tips FOR USE WITH: 1/4 YD Pin Lock Quick Coupler		\$2,847 NI
W	247-1958	BUCKET-HC, 36", 16.2 FT3, PL 543 Width: 914mm (36"), Cap: 0.46m3 (16.2ft3), Includes 6 tooth tips FOR USE WITH: 1/4 YD Pin Lock Quick Coupler		\$2,396 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

AUGERS

Nomenclature change: A68 is replacement for A26B, NO technical changes
 A68 stands for Auger with a Torque= 6826Nm (A68 = A26B)

W	227-4359	AUGER, A68, BHL, 45-50MM 404 A68 (old A26B) has a torque of 6826Nm Planetary drive unit with 2" hex output shaft. Includes 225-8809 Drive Group 227-4350 Mounting Group 227-4358 Lines Group Compatible with Pin Grabber Coupler RECOMMENDED: Add case drain for severe duty applications when working below minus 7 Degree C (20 Degree F). Installation time: 4 hrs, Instructions M0113305 (NO kit available).		\$4,743 NI
W	227-4360	AUGER, A68, BHL, 1/4YD PL 443 A68 (old A26B) has a torque of 6826Nm Planetary drive unit with 2" hex output shaft. INCLUDES: 225-8809 Drive Group 227-4362 Mounting Group 227-4358 Lines Group Compatible with 1/4 yard Pin Lock Coupler Special instructions for auxiliary two-way hydraulic lines via SIS Web: REHS1700- For use with E Stick on 416D, 420D, or 430D REHS1705- For use with Standard Stick on 416D REHS1707- For use with Standard Stick on 420D or 430D Field installed auxiliary combined function hydraulic kits for use with BOTH one-way and two-way flow work tools are available from the factory. Refer to Machine Price List to order. RECOMMENDED: Add case drain for severe duty applications when working below minus 7 Degree C (20 Degree F). Installation time: 4 hrs, Instructions M0113305 (NO kit available).		\$4,743 NI
W	225-8809	AUGER, DRIVE, A68 216 A68 (old A26B) has a torque of 6826Nm RECOMMENDED: Add case drain for severe duty applications when working below minus 7 Degree C (20 Degree F). Installation time: 4 hrs, Instructions M0113305 (NO kit available). REQUIRES: Bracket, connecting lines(dealer local supply) +auger flight		\$4,139 NI
W	227-4350	BRACKET, A68, BHL, 45-50MM, PO 101 FOR USE WITH: A68 (old A26B) for BHL D,E,F and Next Gen (excl 442/450) FOR USE WITH: Pin-on, 45-50mm		\$604 NI
W	227-4362	BRACKET, A68, BHL, 1/4YD PL 144 FOR USE WITH: A68 (old A26B) with a 1/4 YD Pin Lock coupler FOR USE WITH: 1/4 YD Pin Lock coupler		\$604 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

AUGER BITS - Standard Flights

Standard Duty, Approx. 50" (1270mm) Length, HEX Shaft, Double Flight
 Bit teeth are hardened, reversible and forged from medium carbon alloy steel. Teeth are held in place by bolt and nut.

Bit/Flight compatibility matrix vs Auger drive unit

Diam	mm	102	152	229	305	380	457	610	762	914
	inch	4	6	9	12	15	18	24	30	36
A68 Standard		++	++	++	++	++	++	++	++	++
Qty teeth #		0	2	4	4	5	6	8	10	12

++ = good performance, +- = acceptable performance, NA = Not Allowed
 # = 1 pilot point per flight, NOT included in teeth count

If no reference numbers appear below there are currently no items available in your region.

W	366-7751	BIT, AUGER 4"	40	\$456 NI
W	153-4083	BIT, AUGER 6"	50	\$456 NI
W	153-4084	BIT, AUGER 9"	75	\$599 NI
W	153-4085	BIT, AUGER 12"	100	\$743 NI
W	366-7752	BIT, AUGER 15"	109	\$903 NI
W	153-4086	BIT, AUGER 18"	144	\$1,056 NI
W	153-4089	BIT, AUGER 24"	200	\$1,125 NI
W	217-3194	BIT, AUGER 30"	212	\$1,653 NI
W	153-4091	BIT, AUGER 36"	380	\$1,938 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

AUGER BITS - Standard Flights (Cont.)

Optional replacement teeth available through Parts only:

- Pilot point/bit: 153-4093 Pilot Point
- Required pilot point hardware:
 - 1 x 7X-2549 Bolt
 - 1 x 6V-7687 Locknut

Replacement teeth & hardware for all auger bits:

- 153-4094 Standard Duty Tooth
- 174-9566 Hard Face Tooth optional
- 174-9567 Carbide Inserted Tooth optional
- Required teeth hardware:
 - 6V-8959 Bolt (1)
 - 6V-7687 Locknut (1)

AUGER BITS - Rock Head for Standard Flights

Transforms standard auger bit to rock drill bit by mounting bolt-on rock head to standard bit. Rotating bits (similar to cold planer bits) extend life and provide better penetration into rocky conditions. Bolt-on rock head can be quickly installed and removed depending on ground conditions for maximum versatility.

Bit/Flight compatibility matrix vs Auger drive unit											
Diam	mm	102	152	229	305	380	457	610	762	914	
	inch	4	6	9	12	15	18	24	30	36	
A68	Rock Head	NA	++	++	++	++	++	++	NA	NA	
	Qty teeth #		8	10	12	14	16	20			

++ = good performance, +- = acceptable performance, NA = Not Allowed
 # = 1 pilot point per flight, included in teeth count (4 pcs)

If no reference numbers appear below there are currently no items available in your region.

W	372-0230	ROCK HEAD, 6" BOLT-ON	23	\$335 NI
		FOR USE WITH: 153-4083 Auger flight		
W	372-0231	ROCK HEAD, 9" BOLT-ON	33	\$432 NI
		FOR USE WITH: 153-4084 Auger flight		
W	372-0232	ROCK HEAD, 12", BOLT-ON	41	\$526 NI
		FOR USE WITH: 153-4085 Auger flight		
W	372-0233	ROCK HEAD, 15" BOLT-ON	47	\$622 NI
		FOR USE WITH: 366-7752 Auger flight		
W	372-0234	ROCK HEAD, 18", BOLT-ON	55	\$708 NI
		FOR USE WITH: 153-4086 Auger flight		

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

AUGER BITS - Rock Head for Standard Flights (Cont.)

W	372-0235	ROCK HEAD, 24", BOLT-ON 79 FOR USE WITH: 153-4089 Auger flight		\$903 NI
---	----------	---	--	----------

Optional replacement teeth available through Parts only:
 372-0259 Standard Rock Drill Head Tooth

AUGER BITS - Industrial Flights

Industrial bits, approx. 48" (1219mm) length, HEX shaft, single flight. Bit teeth are hardened and forged from medium carbon alloy steel. Teeth held in place by press fit. Teeth are quickly changed by soft hammer to insert or remove tooth. Ideal for ground conditions where teeth need to be changed frequently. Multiple tooth options below for various ground conditions.

Bit/Flight compatibility matrix vs Auger drive unit											
Diam	mm	152	229	305	405	457	610	762	914	1067	1219
	inch	6	9	12	16	18	24	30	36	42	48

A68	Industrial	++	++	++	++	++	++	++	++	++	++
Qty	teeth #	2	4	4	6	6	8	10	12	16	18

++ = good performance, +- = acceptable performance, NA = Not Allowed
 # = 1 pilot point per flight, NOT included in teeth count

If no reference numbers appear below there are currently no items available in your region.

W	372-0260	BIT, AUGER 6" INDUSTRIAL 57		\$631 NI
W	372-0261	BIT, AUGER 9" INDUSTRIAL 72		\$778 NI
W	372-0262	BIT, AUGER 12" INDUSTRIAL 91		\$910 NI
W	372-0263	BIT, AUGER 16" INDUSTRIAL 114		\$1,111 NI
W	372-0264	BIT, AUGER 18" INDUSTRIAL 107		\$1,208 NI
W	372-0265	BIT, AUGER 24", INDUSTRIAL 151		\$1,493 NI
W	372-0266	BIT, AUGER 30" INDUSTRIAL 180		\$1,778 NI
W	372-0267	BIT, AUGER 36" INDUSTRIAL 223		\$2,063 NI
W	372-0268	BIT, AUGER 42" INDUSTRIAL 289		\$3,014 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

AUGER BITS - Industrial Flights (Cont.)

W	372-0269	BIT, AUGER 48" INDUSTRIAL	343	\$3,306 NI
---	----------	---------------------------------	-----	------------

Optional replacement teeth available through Parts only:

- 371-3694 Gage Tooth (Outer)
- 371-3690 Flat Tooth (Inner)
- 371-3695 HF Gage Tooth (Outer)
- 371-3691 Flat Carbide Tooth (Inner)
- 371-3696 Chisel Tooth (Inner)
- 371-3692 Flat Hard Face Tooth HF (Inner)
- 371-3697 Chisel Carbide Tooth (Inner)
- 371-3693 Flat HF Tooth (HF Both Sides, Inner)
- 371-3698 Chisel HF Tooth (Inner)

AUGER BITS - Industrial Rock Flights

Industrial Rock Flights, approx. 1220mm (48") length, HEX shaft, for heavy duty applications. The thickness of the flight is 19mm (3/4"). with a welded on Rock head including a bolt-on pilot bit.

Bit/Flight compatibility matrix vs Auger drive unit											
Diam	mm	152	229	305	405	457	610	762	914	1067	1219
	inch	6	9	12	16	18	24	30	36	42	48
A68	Ind Rock	++	++	++	++	++	++	++	++	NA	NA
Qty	teeth #	8	10	12	15	16	20	24	26		

++ = good performance, +- = acceptable performance, NA = Not Allowed

If no reference numbers appear below there are currently no items available in your region.

W	372-0270	BIT, ROCK AUGER 6"	78	\$1,431 NI
W	372-0271	BIT, ROCK AUGER 9"	107	\$1,597 NI
W	372-0272	BIT, ROCK AUGER 12"	134	\$1,764 NI
W	372-0273	BIT, ROCK AUGER 16"	167	\$3,104 NI
W	372-0274	BIT, ROCK AUGER 18"	191	\$3,444 NI
W	372-0275	BIT, ROCK AUGER 20"	217	\$3,778 NI
W	372-0276	BIT, ROCK AUGER 24"	281	\$4,451 NI
W	372-0277	BIT, ROCK AUGER 30"	310	\$5,451 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

AUGER BITS - Industrial Rock Flights (Cont.)

W	372-0278	BIT, ROCK AUGER 36"	409	\$6,458 NI
---	----------	-------------------------------	-----	------------

Optional replacement teeth available through Parts only:
 367-9767 Bit pilot (excluding 4 teeth)
 372-0289 Rock Drill Head Tooth

AUGER BITS - Tree Flight

Conical auber flights, for use in nurseries and landscaping to drill holes for trees and shrubs with root balls.

Bit/Flight compatibility matrix vs Auger drive unit

Diam	mm	610	914
	inch	24	36

A68	Tree Bit	++	++
-----	----------	----	----

++ = good performance

W	153-4092	TREE BIT, AUGER 24"	163	\$1,188 NI
		Tapered bit, INCLUDES: 5 teeth on 24" (610mm) width, 4 teeth on 12" (305mm) width and pilot point.		
W	153-4095	TREE BIT, AUGER 36"	310	\$1,868 NI
		Tapered bit, INCLUDES: 7 teeth on 36" (914mm) width, 6 teeth on 18" (457mm) width and pilot point.		

AUGER BITS - Adapters and Extensions

Following adapters and extensions can be used with all other auger bits and augers.

W	156-6329	ADAPTER, AUGER - HEX TO ROUND	15	\$256 NI
		HEX output shaft 2" (50mm) to round output shaft 2 9/16" (65mm)		
W	217-3191	ADAPTER, AUGER - ROUND TO HEX	15	\$256 NI
		Round output shaft 2.56" (65mm) to HEX output shaft 2" (50mm)		
W	372-0256	EXTENSION, TELESCOPING 3'	43	\$439 NI
		FOR USE WITH: All Auger Bits Three holes at 1'(0.3M) increments on extension to insert retention pin to vary depth; Insert extension inside auger bit Recommend retention pin 372-0258 for quick depth change		
W	372-0257	EXTENSION, TELESCOPING 6'	77	\$736 NI
		FOR USE WITH: All Auger Bitsements on extension to insert retention Six holes at 1'(0.3M) increments on extension to insert retention pin to vary depth; Insert extension inside auger bitnge Recommend retention pin 372-0258 for quick depth change		
W	156-6328	EXTENSION, AUGER 12"	20	\$256 NI
		12" (305mm) length HEX shaft		
W	217-3192	EXTENSION, AUGER 24"	33	\$296 NI
		24" (610mm) length HEX shaft		

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	------------------------	--------------------	-------------------------

BACKHOE CURRENT: 415-444 (CONT.)

AUGER BITS - Adapters and Extensions (Cont.)

Available through Parts only:

372-0258 Retention Pin Kit

Retention pin uses lynch (ring) pin to secure bit & drive unit instead of bolt & 2 nuts. Allows for quick change of flights, extensions, & drive kits.

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

COLD PLANERS

W	219-5470	COLD PLANER, PC404 1,499 450mm (18") Drum width, 46 conical concrete/asphalt bits Manual depth control, max 125mm (5") cutting depth. 130 degree supported rotation, Hardox side skid plates FOR USE WITH: D, E, F series standard stick and E-stick Includes DIRECT drive unit, hydraulic lines with quick disconnect and mounting bracket REQUIRES: One way aux (Hammer lines or Combo Lines) REQUIRES: 178-3593 PINS GROUP		\$18,792 NI
---	----------	---	--	--------------------

COMPACTING WHEELS for PIN-ON

W	517-6992	WHEEL, 12", BL 872 Trench width 290mm (11"), 2 wheels each with 9 pads Overall Length-Height-Width: 995mm(39.2")- 1138mm(44.8")- 398mm(15.7") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$4,910 NI
W	517-6993	WHEEL, 18", BL 1,110 Trench width 440mm (17"), 3 wheels each with 9 pads Overall Length-Height-Width: 991mm(39")- 1112mm(43.8")- 439mm(17.3") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$5,736 NI
W	517-6994	WHEEL, 24", BL 1,179 Trench width 560mm (22"), 3 wheels each with 9 pads Overall Length-Height-Width: 991mm(39")- 1110mm(43.7")- 559mm(22") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$6,153 NI

COMPACTING WHEELS for 1/4 YD PIN LOCK COUPLERS

W	517-6995	WHEEL, 12", 1/4 PL 836 Trench width 290mm (11"), 2 wheels each with 9 pads Overall Length-Height-Width: 995mm(39.2")- 1207mm(47.5")- 312mm(12.3") FOR USE WITH: Pin Lock coupler 1/4YD (Wain Roy)		\$4,910 NI
W	517-6996	WHEEL, 18", 1/4 PL 1,074 Trench width 440mm (17"), 3 wheels each with 9 pads Overall Length-Height-Width: 991mm(39")- 1181mm(46.5")- 439mm(17.3") FOR USE WITH: Pin Lock coupler 1/4YD (Wain Roy)		\$5,736 NI
W	517-6997	WHEEL, 24", 1/4 PL 1,142 Trench width 560mm (22"), 3 wheels each with 9 pads Overall Length-Height-Width: 991mm(39")- 1179mm(46.4")- 559mm(22") FOR USE WITH: Pin Lock coupler 1/4YD (Wain Roy)		\$6,153 NI

COMPACTOR PLATE CVP40

W	551-4957	COMPACTOR PLATE, CVP40 411 Has drill pattern XL REQUIRES: Mounting bracket and connecting lines.		\$8,222 NI
W	211-8200	BLADE, BACKFILL, CVP40 113 FOR USE WITH: CVP40 for back filling trenches		\$667 NI
W	264-5907	SWIVEL, CVP40, XL TO XL 269 FOR USE WITH: CVP40 and fitted between mounting bracket and CVP40		\$1,854 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
BACKHOE CURRENT: 415-444 (CONT.)				
COMPACTOR PLATE CVP40 (Cont.)				
W	311-2599	SWIVEL, CVP40, BHL TO XL 293 FOR USE WITH: CVP40 and D, E and F series BHL pin-on excl. 446D and 450E/F (Bracket and swivel integrated)		\$2,618 NI
W	311-2600	KIT, CVP40, BHL, THUMB STOP 34 FOR USE WITH: 415-440 D, E, F and Next Gen machines when fitted with pin grabber Q/C, a thumb arrangement and CVP 40 Compactor. Needed to protect hydraulic hoses from crushing. Hose clamps fit hoses with a maximum outside diameter of 30.9mm.		\$972 NI
W	416-8031	BRACKET, 1/4YD PL, XL 170 Mounting bracket, incl.bolts + nuts, excl. lines FOR USE WITH: 1/4 yard pin lock quick coupler		\$694 NI
W	564-9842	BRACKET, BL, 45-50MM, XL 177 Mounting bracket, drill pattern XL, incl. bucket pins, bolts + nuts FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444.		\$660 NI
W	178-3593	PINS, BUCKET, BHL-F, 45MM-50MM 6 Includes bucket pins and hardware. FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444		\$125 NI
W	491-7486	LINES, CVP40, BHL-F 22 Quick Disconnects not included FOR USE WITH: D, E and F series BHL.		\$319 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

HAMMERS - B6 and B6S Silenced, Flat Top

WARNING:

Demolition tools can create a hazard from flying objects.
Caterpillar recommends installing front guards on the cabs of the the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers	H hammers (incl. E)
Centre Pivot Machines:	B6 B8 B9	H65 H80 H95
415D/E/F/F2, 416D/E/F/F2	+ - ++ ++	++ ++ + -
420D/E/F/F2, 430D/E/F/F2	+ - ++ ++	++ ++ + -
Next Generation:		
415, 416, 420, 430, 440	+ - ++ ++	++ ++ + -
446D - 450E/F	- - - - ++	- - + - ++
Next Generation 450	- - - - ++	- - + - ++
Side Shift Machines:	B6 B8 B9	H65 H80 H95
All models from 422D up to incl 444F2	+ - ++ - -	++ + - - -
Next Generation:		
428, 432, 434, 444	+ - ++ - -	++ + - - -

++= Optimal +- = Acceptable -- = Not Allowed

W	532-9206	HAMMER, B6S 611 Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 500-900 , Energy Class 681 Joule (502 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 40-70 l/min (10.6-18.5 gal/min) Max Operation Pressure 13,707 kPa (1,988 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines.	\$9,306 NI
W	532-9106	HAMMER, B6 571 Non-Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 500-900 , Energy Class 681 Joule (502 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 40-70 l/min (10.6-18.5 gal/min) Max Operation Pressure 13,707 kPa (1,988 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines.	\$8,375 NI
W	567-9320	BRACKET, BHL 45-50MM, LG 209 Mounting bracket, drill pattern LG, incl. bucket pins, bolts+nuts Not suitable for tucking the hammer in the roading position. FOR USE WITH: Pin-On D, E, F series excl 446D and 450E/F.	\$451 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

HAMMERS - B6 and B6S Silenced, Flat Top (Cont.)

W	443-7285	BRACKET, 1/4YD PL, LG143 Mounting bracket, 1 pattern SM and LG, incl.bolts + nuts FOR USE WITH: 1/4 yard pin-lock quick coupler FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444		\$694 NI
W	551-1546	BRACKET, BHL-STD, PO, TUCK, LG 209 Mounting bracket, drill pattern LG, includes bucket pins, bolts & nuts FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444 allows for roading/tucking, for standard stick only.		\$660 NI
W	565-3682	BRACKET, BHL-EXT, PO, TUCK, LG209 Mounting bracket, drill pattern LG, includes bucket pins, bolts & nuts FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444 allows for roading/tucking, for E stick only.		\$660 NI
W	572-6066	BRACKET, BHL, QC, TUCK, LG 209 Mounting bracket, drill pattern LG, includes bucket pins, bolts & nuts FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444 allows for roading/tucking, for standard and E stick.		\$660 NI
W	178-3593	PINS, BUCKET, BHL-F, 45MM-50MM 6 Includes bucket pins and hardware. FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444		\$125 NI
W	570-6298	LINES, B6-B8 HAMMER, BHL21 Quick Disconnects not included FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444 CANNOT BE USED WITH: tuck brackets.		\$333 NI
W	565-6083	LINES, B6-B8 HAMMER, BHL-TUCK 19 Quick Disconnects not included To be used with tuck brackets only FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444		\$333 NI
W	523-3193	TOOL, MOIL, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	523-3195	TOOL, CONE, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	523-3196	TOOL, BLUNT, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	523-3197	TOOL, CHISEL, CROSS CUT, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	523-3191	TOOL, CHISEL, IN LINE, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	582-1493	TOOL, COMPACTING PLATE, B6 93 Diam: 68mm (2.7"), Length: 543mm (21.4"), Bottom width: 305mm (12") Working length: Non silenced / silenced: 268mm (10.6") / 218mm (8.6")		\$1,389 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

HAMMERS - B6 and B6S Silenced, Flat Top (Cont.)

W	582-1498	TOOL, SPADE PARALLEL, B6 42 Diam: 68mm (2.7"), Length: 709mm (27.9"), Spade width: 152mm (6") Working length: Non silenced / silenced: 434mm (17.1") / 384mm (15.1")		\$590 NI
W	582-1503	TOOL, SPADE TRANSVERSE, B6 42 Diam: 68mm (2.7"), Length: 709mm (27.9"), Spade width: 152mm (6") Working length: Non silenced / silenced: 434mm (17.1") / 384mm (15.1")		\$590 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

HAMMERS - B8 and B8S Silenced Flat Top, B8 Side Mount

WARNING:

Demolition tools can create a hazard from flying objects.
 Caterpillar recommends installing front guards on the cabs of the
 the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers	H hammers (incl. E)
Centre Pivot Machines:	B6 B8 B9	H65 H80 H95
415D/E/F/F2, 416D/E/F/F2	+ - ++ ++	++ ++ + -
420D/E/F/F2, 430D/E/F/F2	+ - ++ ++	++ ++ + -
Next Generation:		
415, 416, 420, 430, 440	+ - ++ ++	++ ++ + -
446D - 450E/F	- - - - ++	- - + - ++
Next Generation 450	- - - - ++	- - + - ++
Side Shift Machines:	B6 B8 B9	H65 H80 H95
All models from 422D		
up to incl 444F2	+ - ++ - -	++ + - - -
Next Generation:		
428, 432, 434, 444	+ - ++ - -	++ + - - -

++= Optimal +- = Acceptable -- = Not Allowed

W	532-9208	HAMMER, B8S 711	\$12,361 NI
		Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 400-800 , Energy Class 1,150 Joule (848 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 50-90 l/min (13.2-23.8 gal/min) Max Operation Pressure 14,686 kPa (2,130 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines.	
W	532-9108	HAMMER, B8 724	\$11,125 NI
		Non Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 400-800 , Energy Class 1,150 Joule (848 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 50-90 l/min (13.2-23.8 gal/min) Max Operation Pressure 14,686 kPa (2,130 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines.	

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

HAMMERS - B8 and B8S Silenced Flat Top, B8 Side Mount (Cont.)

W	582-1508	HAMMER, B8, BHL 45-50MM, PO SM 1,077 NON Silenced hydraulic hammer, Pin-On Side Mount incl. bucket pins BPM (blows/minute): 400-800 , Energy Class 1,150 Joule (848 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut), connecting lines FOR USE WITH: E, F/F2 Series and Next Generation 415 - 444 REQUIRED HYDRAULICS: Min - Max Flow: 50-90 l/min (13.2-23.8 gal/min) Max Operation Pressure 14,686 kPa (2,130 psi) REQUIRES: Machine side: hammer lines and front guards. REQUIRES: Tuck tools/chisels to be used.		\$9,750 NI
W	443-7285	BRACKET, 1/4YD PL, LG143 Mounting bracket, 1 pattern SM and LG, incl.bolts + nuts FOR USE WITH: 1/4 yard pin-lock quick coupler FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444		\$694 NI
W	567-9320	BRACKET, BHL 45-50MM, LG 209 Mounting bracket, drill pattern LG, incl. bucket pins, bolts+nuts Not suitable for tucking the hammer in the roading position. FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444.		\$451 NI
W	551-1546	BRACKET, BHL-STD, PO, TUCK, LG 209 Mounting bracket, drill pattern LG, includes bucket pins, bolts & nuts FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444 allows for roading/tucking, for standard stick only.		\$660 NI
W	565-3682	BRACKET, BHL-EXT, PO, TUCK, LG209 Mounting bracket, drill pattern LG, includes bucket pins, bolts & nuts FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444 allows for roading/tucking, for E stick only.		\$660 NI
W	572-6066	BRACKET, BHL, QC, TUCK, LG 209 Mounting bracket, drill pattern LG, includes bucket pins, bolts & nuts FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444 allows for roading/tucking, for standard and E stick.		\$660 NI
W	570-6298	LINES, B6-B8 HAMMER, BHL21 Quick Disconnects not included FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444 CANNOT BE USED WITH: tuck brackets.		\$333 NI
W	565-6083	LINES, B6-B8 HAMMER, BHL-TUCK 19 Quick Disconnects not included To be used with tuck brackets only FOR USE WITH: D, E, F series excl 446D, 450E/F and next generation 450		\$333 NI
W	532-9120	TOOL, MOIL, B8 50 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI
W	566-3424	TOOL, MOIL, B8, TUCK 19 Diam: 75mm (3"), Total Length: 695mm (27.4"), use for roading/tucking Working length: Non silenced / silenced: 408mm (16.1") / 358mm (14.1")		\$333 NI
W	532-9118	TOOL, CONE, B8 54 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

HAMMERS - B8 and B8S Silenced Flat Top, B8 Side Mount (Cont.)

W	566-3422	TOOL, CONE, B8, TUCK 19 Diam: 75mm (3"), Total Length: 695mm (27.4"), use for roading/tucking Working length: Non silenced / silenced: 408mm (16.1") / 358mm (14.1")		\$333 NI
W	532-9117	TOOL, BLUNT, B8 54 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI
W	566-3421	TOOL, BLUNT, B8, TUCK 21 Diam: 75mm (3"), Total Length: 695mm (27.4"), use for roading/tucking Working length: Non silenced / silenced: 408mm (16.1") / 358mm (14.1")		\$333 NI
W	532-9121	TOOL, CHISEL, IN LINE, B8 52 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI
W	566-3425	TOOL, CHISEL, INLINE, B8, TUCK 20 Diam: 75mm (3"), Total Length: 695mm (27.4"), use for roading/tucking Working length: Non silenced / silenced: 408mm (16.1") / 358mm (14.1")		\$333 NI
W	532-9119	TOOL, CHISEL, CROSS CUT, B8 52 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI
W	566-3423	TOOL, CHISEL, CROSS CUT, B8, TUCK 20 Diam: 75mm (3"), Total Length: 695mm (27.4"), use for roading/tucking Working length: Non silenced / silenced: 408mm (16.1") / 358mm (14.1")		\$333 NI
W	582-1494	TOOL, COMPACTING PLATE, B8 101 Diam: 75mm (2.9"), Length: 601mm (23.7"), Bottom width: 305mm (12") Working length: Non silenced / silenced: 314mm (12.4") / 264mm (10.4")		\$1,417 NI
W	582-1499	TOOL, SPADE PARALLEL, B8 46 Diam: 75mm (2.9"), Length: 718mm (28.3"), Spade width: 152mm (6") Working length: Non silenced / silenced: 431mm (17") / 381mm (15")		\$667 NI
W	582-1504	TOOL, SPADE TRANSVERSE, B8 46 Diam: 75mm (2.9"), Length: 718mm (28.3"), Spade width: 152mm (6") Working length: Non silenced / silenced: 431mm (17") / 381mm (15")		\$667 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

HAMMERS - B9 AND B9 SILENCED FLAT TOP

WARNING:

Demolition tools can create a hazard from flying objects.
 Caterpillar recommends installing front guards on the cabs of the
 the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers	H hammers (incl. E)
Centre Pivot Machines:	B6 B8 B9	H65 H80 H95
415D/E/F/F2, 416D/E/F/F2	+- ++ ++	++ ++ +-
420D/E/F/F2, 430D/E/F/F2	+- ++ ++	++ ++ +-
Next Generation:		
415, 416, 420, 430, 440	+- ++ ++	++ ++ +-
446D - 450E/F	-- -- ++	-- +- ++
Next Generation 450	-- -- ++	-- +- ++
Side Shift Machines:	B6 B8 B9	H65 H80 H95
All models from 422D up to incl 444F2	+- ++ --	++ +- --
Next Generation:		
428, 432, 434, 444	+- ++ --	++ +- --

++= Optimal +- = Acceptable -- = Not Allowed

W	532-9209	HAMMER, B9S 1,143	\$17,917 NI
		Silenced hydraulic hammer, flat top with drill pattern XL BPM (blows/minute): 400-800 , Energy Class 1,300 Joule (959 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 60-100 l/min (15.8-26.3 gal/min) Max Operation Pressure 15,665 kPa (2,272 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket XL, connecting lines.	
W	532-9109	HAMMER, B9 1,166	\$16,125 NI
		NON Silenced hydraulic hammer, flat top with drill pattern XL BPM (blows/minute): 400-800 , Energy Class 1,300 Joule (959 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 60-100 l/min (15.8-26.3 gal/min) Max Operation Pressure 15,665 kPa (2,272 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket XL, connecting lines.	
W	564-9842	BRACKET, BL, 45-50MM, XL 177	\$660 NI
		Mounting bracket, drill pattern XL, incl.bolts + nuts + bucket pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC on D, E, F/F2 Series and Next Generation 415 - 444.	
W	416-8031	BRACKET, 1/4YD PL, XL 170	\$694 NI
		Mounting bracket, drill pattern XL, incl.bolts + nuts FOR USE WITH: 1/4 Yard Pin Lock QCs & hammers with XL drill pattern	

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

HAMMERS - B9 AND B9 SILENCED FLAT TOP (Cont.)

W	564-2732	BRACKET, 1/2YD PL, XL 233 Mounting bracket, incl.bolts + nuts, excl. lines FOR USE WITH: 1/2Yard Pin Lock XLS QCs & Hammers with XL drill pattern		\$1,528 NI
W	532-9282	LINES, B9 HAMMER, BL 25 Quick Disconnects not included FOR USE WITH: Series D, E, F and Next Generation BHLs.		\$542 NI
W	532-9219	TOOL, MOIL, B9 64 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI
W	542-1762	TOOL, CONE, B9 62 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI
W	542-1763	TOOL, BLUNT, B9 68 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI
W	542-1764	TOOL, CHISEL, IN LINE, B9 66 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI
W	542-1765	TOOL, CHISEL, CROSS CUT, B9 66 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

HAMMERS - H65S Silenced flat top

WARNING:

Demolition tools can create a hazard from flying objects.
Caterpillar recommends installing front guards on the cabs of the the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers	H hammers (incl. E)
Centre Pivot Machines:	B6 B8 B9	H65 H80 H95
415D/E/F/F2, 416D/E/F/F2	+ - ++ ++	++ ++ + -
420D/E/F/F2, 430D/E/F/F2	+ - ++ ++	++ ++ + -
Next Generation:		
415, 416, 420, 430, 440	+ - ++ ++	++ ++ + -
446D - 450E/F	- - - - ++	- - + - ++
Next Generation 450	- - - - ++	- - + - ++
Side Shift Machines:	B6 B8 B9	H65 H80 H95
All models from 422D up to incl 444F2	+ - ++ - -	++ + - - -
Next Generation:		
428, 432, 434, 444	+ - ++ - -	++ + - - -

++= Optimal +- = Acceptable -- = Not Allowed

W	561-2552	HAMMER, H65S 534	\$11,167 NI
		Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 720-1,740 , Energy Class 1,085 Joule (800 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 40-115 l/min (10.6-30.4 gal/min) Max Operation Pressure 16,499 kPa (2,393 psi). REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines.	
W	567-9320	BRACKET, BHL 45-50MM, LG 209	\$451 NI
		Mounting bracket, drill pattern LG, incl. bucket pins, bolts+nuts Not suitable for tucking the hammer in the roading position. FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444.	
W	565-3682	BRACKET, BHL-EXT, PO, TUCK, LG 209	\$660 NI
		Mounting bracket, drill pattern LG, includes bucket pins, bolts & nuts FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444 for Pin-On E-Stick only & NO quick coupler, allows tucking/roading	
W	551-1546	BRACKET, BHL-STD, PO, TUCK, LG 209	\$660 NI
		Mounting bracket, drill pattern LG, includes bucket pins, bolts & nuts FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444 for Pin-On Stnd-Stick only & NO quick coupler, allows tucking/roading.	
W	572-6066	BRACKET, BHL, QC, TUCK, LG 209	\$660 NI
		Mounting bracket, drill pattern LG, includes bucket pins, bolts & nuts FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444 for Quick coupler only for Stnd- & E-Stick, allows tucking/roading	

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
BACKHOE CURRENT: 415-444 (CONT.)				
<i>HAMMERS - H65S Silenced flat top (Cont.)</i>				
W	178-3593	PINS, BUCKET, BHL-F, 45MM-50MM 6 Includes bucket pins and hardware. FOR USE WITH: Pin-On D, E, F series excl 446D and 450E/F		\$125 NI
W	313-4791	LINES, H65, BHL-F 26 Quick Disconnects not included.		\$500 NI
W	423-8307	TOOL, CHISEL, INLINE, H65 38 Diam.: 68mm (2.7"), Tot./Working Length: 650mm (25.6")/ 371mm (14.6") FOR USE WITH: new H65 and previous H65E		\$290 NI
W	428-8022	TOOL, CHISEL, CROSSCUT, H65 38 Diam.: 68mm (2.7"), Tot./Working Length: 650mm (25.6")/ 371mm (14.6") FOR USE WITH: new H65 and previous H65E		\$290 NI
W	423-8308	TOOL, CONE, H65 38 Diam.: 68mm (2.7"), Tot./Working Length: 650mm (25.6")/ 371mm (14.6") FOR USE WITH: new H65 and previous H65E		\$290 NI
W	423-8309	TOOL, BLUNT, H65 0 Diam.: 68mm (2.7"), Tot./Working Length: 650mm (25.6")/ 371mm (14.6") FOR USE WITH: new H65 and previous H65E		\$290 NI
W	433-9653	TOOL, SPADE PARALLEL, H65 33 Diam.: 68mm (2.7"), Length: 615mm (22.4"), Spade width: 152mm (6") FOR USE WITH: new H65 and previous H65E		\$465 NI
W	433-9652	TOOL, SPADE TRANSVERSE, H65 33 Diam.: 68mm (2.7"), Length: 615mm (22.5"), Spade width: 152mm (6") FOR USE WITH: new H65 and previous H65E		\$465 NI
W	433-9651	TOOL, COMPACTING PLATE, H65 90 Diam.: 68mm (2.7"), Length: 495mm (19.5"), Bottom width: 305mm (12") FOR USE WITH: new H65 and previous H65E		\$1,465 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

HAMMERS - H80S Silenced Flat Top

WARNING:

Demolition tools can create a hazard from flying objects.
 Caterpillar recommends installing front guards on the cabs of the
 the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers	H hammers (incl. E)
Centre Pivot Machines:	B6 B8 B9	H65 H80 H95
415D/E/F/F2, 416D/E/F/F2	+ - ++ ++	++ ++ + -
420D/E/F/F2, 430D/E/F/F2	+ - ++ ++	++ ++ + -
Next Generation:		
415, 416, 420, 430, 440	+ - ++ ++	++ ++ + -
446D - 450E/F	- - - - ++	- - + - ++
Next Generation 450	- - - - ++	- - + - ++
Side Shift Machines:	B6 B8 B9	H65 H80 H95
All models from 422D		
up to incl 444F2	+ - ++ - -	++ + - - -
Next Generation:		
428, 432, 434, 444	+ - ++ - -	++ + - - -

++= Optimal +- = Acceptable -- = Not Allowed

W	561-2553	HAMMER, H80S 725	\$16,667 NI
		Silenced hydraulic hammer, flat top with drill pattern XL BPM (blows/minute): 600-1,500 , Energy Class 1,365 Joule (1,000 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 60-130 l/min (16-34 gal/min) Max Operation Pressure 17,500 kPa (2,500 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket XL, connecting lines.	
W	564-9842	BRACKET, BL, 45-50MM, XL 177	\$660 NI
		Mounting bracket, drill pattern XL, incl. bucket pins, bolts + nuts FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444.	
W	416-8031	BRACKET, 1/4YD PL, XL 170	\$694 NI
		Mounting bracket, incl. bolts + nuts, excl. lines FOR USE WITH: 1/4 yard pin lock quick coupler	
W	178-3593	PINS, BUCKET, BHL-F, 45MM-50MM 6	\$125 NI
		Includes bucket pins and hardware. FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 444	
W	399-6962	LINES, H80-H95, BHL-F 18	\$500 NI
		Quick Disconnects not included. FOR USE WITH: D, E, F series excl 446D and 450E/F and NO Quick coupler new H80/H95 and previous H80E/H95E	

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
BACKHOE CURRENT: 415-444 (CONT.)				
<i>HAMMERS - H80S Silenced Flat Top (Cont.)</i>				
W	399-6964	LINES, H80-H95, BHL-F, QC 19 Quick Disconnects not included. FOR USE WITH: D, E, F series excl 446D and 450E/F AND a Quick coupler new H80/H95 and previous H80E/H95E.		\$500 NI
W	399-1711	TOOL, CHISEL, CROSSCUT, H80 55 Diam.: 74.5mm (2.9"), Tot./Working Length: 775mm (30.5")/ 356mm (14") FOR USE WITH: new H80 and previous H80E		\$428 NI
W	369-1549	TOOL, CHISEL, INLINE, H80 55 Diam.: 74.5mm (2.9"), Tot./Working Length: 775mm (30.5")/ 356mm (14") FOR USE WITH: new H80 and previous H80E		\$428 NI
W	369-1548	TOOL, CONE, H80 54 Diam.: 74.5mm (2.9"), Tot./Working Length: 775mm(30.5")/ 376mm(14.8") FOR USE WITH: new H80 and previous H80E		\$428 NI
W	376-7947	TOOL, BLUNT, H80 0 Diam.: 74.5mm (2.9"), Tot./Working Length: 775mm (30.5")/ 356mm (14") FOR USE WITH: new H80 and previous H80E		\$428 NI
W	381-6720	TOOL, SPADE PARALLEL, H80 44 Diam.: 74.5mm (2.9"), Length: 720mm (28.3"), Spade width: 152mm (6") FOR USE WITH: new H80 and previous H80E		\$556 NI
W	381-6719	TOOL, SPADE TRANSVERSE, H80 50 Diam.: 74.5mm (2.9"), Length: 720mm (28.3"), Spade width: 152mm (6") FOR USE WITH: new H80 and previous H80E		\$556 NI
W	381-6721	TOOL, COMPACTING PLATE, H80 104 Diam.: 74.5mm (2.9"), Length: 615mm (22"), Bottom width: 305mm (12") FOR USE WITH: new H80 and previous H80E / H75E		\$1,514 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

HAMMERS - H95S Silenced Flat Top

WARNING:

Demolition tools can create a hazard from flying objects.
Caterpillar recommends installing front guards on the cabs of the the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers	H hammers (incl. E)
Centre Pivot Machines:	B6 B8 B9	H65 H80 H95
415D/E/F/F2, 416D/E/F/F2	+- ++ ++	++ ++ +-
420D/E/F/F2, 430D/E/F/F2	+- ++ ++	++ ++ +-
Next Generation:		
415, 416, 420, 430, 440	+- ++ ++	++ ++ +-
446D - 450E/F	-- -- ++	-- +- ++
Next Generation 450	-- -- ++	-- +- ++
Side Shift Machines:	B6 B8 B9	H65 H80 H95
All models from 422D up to incl 444F2	+- ++ --	++ +- --
Next Generation:		
428, 432, 434, 444	+- ++ --	++ +- --

++= Optimal +- = Acceptable -- = Not Allowed

W	561-2555	HAMMER, H95S 1,109 Silenced hydraulic hammer, flat top with drill pattern XL BPM (blows/minute): 700-1,260 , Energy Class 2,034 Joule (1,500 ft lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 70-150 l/min (18.5-39.6 gal/min) Max Operation Pressure 17,237 kPa (2,500 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket XL, connecting lines	\$24,583 NI
W	564-9842	BRACKET, BL, 45-50MM, XL 177 Mounting bracket, drill pattern XL, incl. bucket pins, bolts + nuts FOR USE WITH: D, E, F/F2 Series and Next Generation 415 - 430.	\$660 NI
W	416-8031	BRACKET, 1/4YD PL, XL 170 Mounting bracket, incl. bolts + nuts, excl. lines FOR USE WITH: 1/4 yard pin lock quick coupler	\$694 NI
W	399-6962	LINES, H80-H95, BHL-F 18 Quick Disconnects not included. FOR USE WITH: D, E, F series excl 446D and 450E/F and NO Quick coupler new H80/H95 and previous H80E/H95E	\$500 NI
W	399-6964	LINES, H80-H95, BHL-F, QC 19 Quick Disconnects not included. FOR USE WITH: D, E, F series excl 446D and 450E/F AND a Quick coupler new H80/H95 and previous H80E/H95E.	\$500 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

HAMMERS - H95S Silenced Flat Top (Cont.)

W	399-1710	TOOL, CHISEL, CROSSCUT, H95 84 Diam.: 87.5mm (3.4"), Tot./Working Length: 875mm (34.5")/ 416mm (16.4") FOR USE WITH: new H95 and previous H95E		\$550 NI
W	369-0793	TOOL, CHISEL, INLINE, H95 84 Diam.: 87.5mm (3.4"), Tot./Working Length: 875mm (34.5")/ 416mm (16.4") FOR USE WITH: new H95 and previous H95E		\$550 NI
W	369-0792	TOOL, CONE, H95 84 Diam.: 87.5mm (3.4"), Tot./Working Length: 875mm (34.5")/ 416mm (16.4") FOR USE WITH: new H95 and previous H95E		\$550 NI
W	373-7159	TOOL, BLUNT, H95 0 Diam.: 87.5mm (3.4"), Tot./Working Length: 875mm (34.5")/ 416mm (16.4") FOR USE WITH: new H95 and previous H95E		\$550 NI

LINES FOR H70 + H90 HAMMERS

W	202-9130	LINES, H70/90, BHL, PO SM 19 Quick Disconnects not included FOR USE WITH: H70 and H90 hammers on BHL D, E, F and Next Gen		\$493 NI
---	----------	---	--	----------

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: 415-444 (CONT.)

RIPPERS for PIN-ON

W	491-4075	RIPPER, 25", BHL F	217	\$1,389 NI
		Shank length 635mm (25"), tip radius 778mm (31"), incl FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		

THUMBS and TINES

W	282-5409	THUMB, HYDRAULIC, NO TINE, BHL	221	\$5,778 NI
		Hydraulic Thumb Arrangement without tines FOR USE WITH: E, F/F2 Series and Next Generation 415 - 430 REQUIRES: Thumb tine (see below)		
W	579-8783	THUMB, HYDRAULIC, NO TINE, 440	0	\$5,778 NI
		Hydraulic Thumb Arrangement without tines FOR USE WITH: Next Generation 440 REQUIRES: Thumb tine (see below)		
W	282-5410	THUMB, STIFF LINK, NO TINE, BHL	198	\$2,826 NI
		Stiff Link Thumb Arrangement without tines FOR USE WITH: E, F/F2 Series and Next Generation 415 - 430 REQUIRES: Thumb tine (see below)		

Thumb tines table for Pin-on(NO QC) or Pin Grabber QC buckets

Size Bucket Type	12"+16"+18"+24"		30"		36"	
	Pin-on	PG QC	Pin-on	PG QC	Pin-on	PG QC
Standard Duty	A1	A3	B1	B3	C1	C3
Heavy Duty	A1	A3	B1	B3	C1	C3
Heavy Duty Rock	A2	A4	B2	B4	C2	C4
High Capacity	A3*	A5	B3	B4	C3	C5
Soil Excavation	A3*	A5	B3	B5	C3	C5

*= Thumb not recommended for 18" High Cap. or Soil Excav. bucket

Thumb tines table 1/4 YD Pin Lock QC buckets

Size Bucket Type	12"+16"+18"+36"		24"		30"	
	1/4 YD PL	QC	1/4 YD PL	QC	1/4 YD PL	QC
Heavy Duty	C2		A2		B2	
High Capacity	C4		C3		B4	

If no reference numbers appear below there are currently no items available in your region.

W	221-4282	THUMB, TINE, A 1	75	\$438 NI
W	221-4284	THUMB, TINE, A 2	99	\$438 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
BACKHOE CURRENT: 415-444 (CONT.)				
<i>THUMBS and TINES (Cont.)</i>				
W	221-4283	THUMB, TINE, A 3	107	\$438 NI
W	221-4285	THUMB, TINE, A 4	115	\$583 NI
W	281-6708	THUMB, TINE, A 5	122	\$583 NI
W	274-5819	THUMB, TINE, B 1	81	\$438 NI
W	274-5826	THUMB, TINE, B 2	108	\$438 NI
W	274-5823	THUMB, TINE, B 3	116	\$438 NI
W	274-5829	THUMB, TINE, B 4	124	\$583 NI
W	281-6711	THUMB, TINE, B 5	131	\$583 NI
W	274-5832	THUMB, TINE, C 1	51	\$438 NI
W	274-5837	THUMB, TINE, C 2	91	\$438 NI
W	274-5835	THUMB, TINE, C 3	99	\$438 NI
W	274-5839	THUMB, TINE, C 4	106	\$583 NI
W	281-6714	THUMB, TINE, C 5	114	\$583 NI

BACKHOE CURRENT: NEXT GENERATION 450

The work tools in this section will fit on following sales models
 (pin sizes and pin spread are the same for all these models)
 450E, 450F, next generation 450.

QUICK COUPLERS - Dual Lock Pin Grabber

W	485-5290	COUPLER, PG, HYDR.D.LOCK, 450	333	\$5,396 NI
Hydraulic pin grabber type quick coupler with a dual lock. FOR USE WITH: Next generation 450 INCLUDES: 1 set of bucket pins and hardware to attach 1 bucket and connecting lines. REQUIRES: 556-3635 Bucket Pins for EACH ADDITIONAL Bucket & hydraulic QC lines on machine. Avialable via Parts/Antares:				

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: NEXT GENERATION 450 (CONT.)

QUICK COUPLERS - Dual Lock Pin Grabber (Cont.)

W	556-3635	PINS, 60MM, MHE 10T-BHL 450 36 Includes 60mm diam bucket pins and hardware FOR USE WITH: Next generation 450 buckets		\$153 NI
W	527-6691	COUPLER, PL, MHE10T, BHL450 260 Manual coupler for dedicated 1/2 Yard pin-lock backhoe work tools. Includes one set of mounting pins FOR USE WITH: Next generation 450		\$3,271 NI

BUCKETS for PIN-ON - Heavy Duty

W	547-7030	BUCKET-HD, 18", 6.4 FT3, 60MM 447 Width 460mm (18"), Heaped Cap. 0.18m3 (0.24yd3), Incl 3 x J225 FOR USE WITH: Next generation 450 Pin-on, includes bucket pins		\$2,417 NI
W	547-7031	BUCKET-HD, 24", 9.5 FT3, 60MM 495 Width 610mm (24"), Heaped Cap. 0.27m3 (0.35yd3), Incl 4 x J225 FOR USE WITH: Next generation 450 Pin-on, requires bucket pins		\$2,528 NI
W	547-7032	BUCKET-HD, 30", 12.4 FT3, 60MM 567 Width 762mm (30"), Heaped Cap. 0.35m3 (0.46yd3), Incl 5 x J225 FOR USE WITH: Pin-on, requires bucket pins		\$2,806 NI
W	547-7033	BUCKET-HD, 36", 15.9 FT3, 60MM 663 Width 914mm (36"), Heaped Cap. 0.45m3 (0.59yd3), Incl 5 x J225 FOR USE WITH: Pin-on, requires bucket pins		\$3,076 NI
W	547-7034	BUCKET-HD, 42", 19.2 FT3, 60MM 745 Width 1067mm (42"), Heaped Cap. 0.54m3 (0.71yd3), Incl 6 x J225 FOR USE WITH: Pin-on, requires bucket pins		\$3,354 NI

BUCKETS FOR 1/2 YARD PIN LOCK

W	527-7302	BUCKET-HD, 18", 7.0 FT3, PL 551 Width 460mm (18"), Heaped Cap. 0.20m3 (0.26yd3), Incl 3 x J250 FOR USE WITH: Next generation 450 & 1/2 Yard Pin Lock QC		\$3,563 NI
W	528-8034	BUCKET-HD, 24", 10.8 FT3, PL 664 Width 610mm (24"), Heaped Cap. 0.31m3 (0.40yd3), Incl 4 x J250 FOR USE WITH: Next generation 450 & 1/2 Yard Pin Lock QC		\$4,361 NI
W	528-8784	BUCKET-HD, 36", 17.6 FT3, PL 860 Width 914mm (36"), Heaped Cap. 0.50m3 (0.65yd3), Incl 6 x J250 FOR USE WITH: Next generation 450 & 1/2 Yard Pin Lock QC		\$5,611 NI
W	528-8786	BUCKET-HD, 48", 27.0 FT3, PL 1,057 Width 1067mm (42"), Heaped Cap. 0.76m3 (1.0yd3), Incl 8 x J250 FOR USE WITH: Next generation 450 & 1/2 Yard Pin Lock QC		\$6,875 NI

BUCKETS FOR PIN-ON - Ditch Cleaning

W	547-7081	BUCKET-DC, 47", 9.5 FT3, 60MM 358 Width 1200mm (47"), Heaped Cap. 0.27m3 (0.35yd3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: Water holes		\$3,340 NI
---	----------	---	--	------------

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: NEXT GENERATION 450 (CONT.)

BUCKETS FOR PIN-ON - Ditch Cleaning (Cont.)

W	547-7082	BUCKET-DC 59" 12.4FT3 417 Width 1500mm (59"), Heaped Cap. 0.35m3 (0.46yd3) FOR USE WITH: Pin-on, requires bucket pins. INCLUDES: Water holes		\$3,840 NI
W	547-7083	BUCKET-DC, 71", 14.9 FT3, 60MM 476 Width 1800mm (71"), Heaped Cap. 0.42m3 (0.55yd3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: Water holes		\$4,340 NI

BUCKETS FOR PIN-ON - Grading/Mud

Designed for grading with higher capacity and suited to carry buckets

W	547-7084	BUCKET-GRADING, 47", 15.1 FT3 705 Width 1200mm (47"), Heaped Cap. 0.43m3 (0.56yd3) FOR USE WITH: Pin-on, includes bucket pins and BOCE		\$3,597 NI
W	547-7085	BUCKET-GRADING, 59", 19.8 FT3 822 Width 1500mm (59"), Heaped Cap. 0.56m3 (0.73yd3) FOR USE WITH: Pin-on, includes bucket pins and BOCE		\$4,139 NI
W	547-7086	BUCKET-GRADING, 71", 24 FT3 938 Width 1800mm (71"), Heaped Cap. 0.68m3 (0.89yd3) FOR USE WITH: Pin-on, includes bucket pins and BOCE		\$4,688 NI

COMPACTING WHEELS for PIN-ON for 450

W	517-6998	WHEEL, 12", MHE 10T-BL 450 959 Trench width 310mm (12"), 2 wheels each with 9 pads Overall Length-Height-Width: 1014mm(39.9")- 1155mm(45.5")-323mm(12.7") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$5,326 NI
W	517-6999	WHEEL, 18", MHE 10T-BL 450 1,266 Trench width 450mm (18"), 3 wheels each with 9 pads Overall Length-Height-Width: 1014mm(39.9")- 1168mm(46")- 449mm(17.7") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$6,694 NI
W	517-7000	WHEEL, 24", MHE 10T-BL 450 1,307 Trench width 560mm (22"), 3 wheels each with 9 pads Overall Length-Height-Width: 1014mm(39.9")- 1168mm(46")- 556mm(21.9") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$6,972 NI
W	517-7001	WHEEL, 36", MHE 10T-BL 450 1,982 Trench width 880mm (35"), 5 wheels each with 9 pads Overall Length-Height-Width: 1091mm(43")- 1168mm(46")- 884mm(34.8") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$8,069 NI

COMPACTOR PLATE CVP40

W	551-4957	COMPACTOR PLATE, CVP40 411 Has drill pattern XL REQUIRES: Mounting bracket and connecting lines.		\$8,222 NI
W	211-8200	BLADE, BACKFILL, CVP40 113 FOR USE WITH: CVP40 for back filling trenches		\$667 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: NEXT GENERATION 450 (CONT.)

COMPACTOR PLATE CVP40 (Cont.)

W	264-5907	SWIVEL, CVP40, XL TO XL	269	\$1,854 NI
		FOR USE WITH: CVP40 and fitted between mounting bracket and CVP40		
W	564-9843	BRACKET, 10T-BL450, 60-60MM,XL	224	\$833 NI
		Includes bucket pins		
		FOR USE WITH: 446D and 450E/F and next generation 450		
W	564-2732	BRACKET, 1/2YD PL, XL	233	\$1,528 NI
		Mounting bracket, incl.bolts + nuts, excl. lines		
		FOR USE WITH: 1/2 yard pin lock quick coupler.		
W	491-7486	LINES, CVP40, BHL-F	22	\$319 NI
		Quick Disconnects not included		
		FOR USE WITH: Series D, E, F and Next Generation BHLs.		

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: NEXT GENERATION 450 (CONT.)

HAMMERS - B9 AND B9 SILENCED FLAT TOP

WARNING:

Demolition tools can create a hazard from flying objects.
 Caterpillar recommends installing front guards on the cabs of the
 the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers			H hammers (incl. E)		
Centre Pivot Machines:	B6	B8	B9	H65	H80	H95
446D - 450E/F	--	--	++	--	+-	++
Next Generation 450	--	--	++	--	+-	++

++= Optimal +- = Acceptable -- = Not Allowed

W	532-9209	HAMMER, B9S 1,143 Silenced hydraulic hammer, flat top with drill pattern XL BPM (blows/minute): 400-800 , Energy Class 1,300 Joule (959 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 60-100 l/min (15.8-26.3 gal/min) Max Operation Pressure 15,665 kPa (2,272 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket XL, connecting lines.		\$17,917 NI
W	532-9109	HAMMER, B9 1,166 NON Silenced hydraulic hammer, flat top with drill pattern XL BPM (blows/minute): 400-800 , Energy Class 1,300 Joule (959 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 60-100 l/min (15.8-26.3 gal/min) Max Operation Pressure 15,665 kPa (2,272 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket XL, connecting lines.		\$16,125 NI
W	564-9843	BRACKET, 10T-BL450, 60-60MM,XL 224 Mounting bracket, drill pattern XL, incl.bolts + nuts + bucket pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC on Next Generation 450		\$833 NI
W	564-2732	BRACKET, 1/2YD PL, XL 233 Mounting bracket, incl.bolts + nuts, excl. lines FOR USE WITH: 1/2 yard pin lock quick coupler.		\$1,528 NI
W	532-9282	LINES, B9 HAMMER, BL 25 Quick Disconnects not included FOR USE WITH: Series D, E, F and Next Generation BHLs.		\$542 NI
W	532-9219	TOOL, MOIL, B9 64 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI
W	542-1762	TOOL, CONE, B9 62 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: NEXT GENERATION 450 (CONT.)

HAMMERS - B9 AND B9 SILENCED FLAT TOP (Cont.)

W	542-1763	TOOL, BLUNT, B9 68 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI
W	542-1764	TOOL, CHISEL, IN LINE, B9 66 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI
W	542-1765	TOOL, CHISEL, CROSS CUT, B9 66 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: NEXT GENERATION 450 (CONT.)

HAMMERS - H80S Silenced Flat Top

WARNING:

Demolition tools can create a hazard from flying objects.
 Caterpillar recommends installing front guards on the cabs of the
 the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers			H hammers (incl. E)		
Centre Pivot Machines:	B6	B8	B9	H65	H80	H95
446D - 450E/F	--	--	++	--	+-	++
Next Generation 450	--	--	++	--	+-	++

++= Optimal +- = Acceptable -- = Not Allowed

W	561-2553	HAMMER, H80S 725	\$16,667 NI
		Silenced hydraulic hammer, flat top with drill pattern XL BPM (blows/minute): 600-1,500 , Energy Class 1,365 Joule (1,000 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 60-130 l/min (16-34 gal/min) Max Operation Pressure 17,500 kPa (2,500 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket XL, connecting lines.	
W	564-9843	BRACKET, 10T-BL450, 60-60MM,XL 224	\$833 NI
		Mounting bracket, incl.bolts + nuts, excl. lines, excl pins Services FOR USE WITH: Pin-On 450E/F, next generation 450 REQUIRES: PINS, SPARE if a pin-grabber QC is used	
W	564-2732	BRACKET, 1/2YD PL, XL 233	\$1,528 NI
		Mounting bracket, incl.bolts + nuts, excl. lines FOR USE WITH: 1/2 yard pin lock quick coupler.	
W	399-6964	LINES, H80-H95, BHL-F, QC 19	\$500 NI
		Quick Disconnects not included FOR USE WITH: Series D, E, F and Next Generation BHLs.	
W	399-1711	TOOL, CHISEL, CROSSCUT, H80 55	\$428 NI
		Diam.: 74.5mm (2.9"), Tot./Working Length: 775mm (30.5")/ 356mm (14") FOR USE WITH: new H80 and previous H80E	
W	369-1549	TOOL, CHISEL, INLINE, H80 55	\$428 NI
		Diam.: 74.5mm (2.9"), Tot./Working Length: 775mm (30.5")/ 356mm (14") FOR USE WITH: new H80 and previous H80E	
W	369-1548	TOOL, CONE, H80 54	\$428 NI
		Diam.: 74.5mm (2.9"), Tot./Working Length: 775mm(30.5")/ 376mm(14.8") FOR USE WITH: new H80 and previous H80E	
W	376-7947	TOOL, BLUNT, H80 0	\$428 NI
		Diam.: 74.5mm (2.9"), Tot./Working Length: 775mm (30.5")/ 356mm (14") FOR USE WITH: new H80 and previous H80E	
W	381-6720	TOOL, SPADE PARALLEL, H80 44	\$556 NI
		Diam.: 74.5mm (2.9"), Length: 720mm (28.3"), Spade width: 152mm (6") FOR USE WITH: new H80 and previous H80E	

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-------------------------------	--------------------	-------------------------

BACKHOE CURRENT: NEXT GENERATION 450 (CONT.)

HAMMERS - H80S Silenced Flat Top (Cont.)

W	381-6719	TOOL, SPADE TRANSVERSE, H80 50 Diam.: 74.5mm (2.9"), Length: 720mm (28.3"), Spade width: 152mm (6") FOR USE WITH: new H80 and previous H80E		\$556 NI
W	381-6721	TOOL, COMPACTING PLATE, H80 104 Diam.: 74.5mm (2.9"), Length: 615mm (22"), Bottom width: 305mm (12") FOR USE WITH: new H80 and previous H80E / H75E		\$1,514 NI

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: NEXT GENERATION 450 (CONT.)

HAMMERS - H95S Silenced Flat Top

WARNING:

Demolition tools can create a hazard from flying objects.
 Caterpillar recommends installing front guards on the cabs of the the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers			H hammers (incl. E)		
Centre Pivot Machines:	B6	B8	B9	H65	H80	H95
446D - 450E/F	--	--	++	--	+-	++
Next Generation 450	--	--	++	--	+-	++

++= Optimal +- = Acceptable -- = Not Allowed

W	561-2555	HAMMER, H95S	1,109	\$24,583 NI
		Silenced hydraulic hammer, flat top with drill pattern XL BPM (blows/minute): 700-1,260 , Energy Class 2,034 Joule (1,500 ft lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 70-150 l/min (18.5-39.6 gal/min) Max Operation Pressure 17,237 kPa (2,500 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket XL, connecting lines		
W	564-9843	BRACKET, 10T-BL450, 60-60MM,XL	224	\$833 NI
		Mounting bracket, incl.bolts + nuts, excl. lines, excl pins Services FOR USE WITH: Pin-On 450E/F, next generation 450 REQUIRES: PINS, SPARE if a pin-grabber QC is used		
W	564-2732	BRACKET, 1/2YD PL, XL	233	\$1,528 NI
		Mounting bracket, incl.bolts + nuts, excl. lines FOR USE WITH: 1/2 yard pin lock quick coupler.		
W	399-6964	LINES, H80-H95, BHL-F, QC	19	\$500 NI
		Quick Disconnects not included FOR USE WITH: Series D, E, F and Next Generation BHLs.		
W	399-1710	TOOL, CHISEL, CROSSCUT, H95	84	\$550 NI
		Diam.: 87.5mm (3.4"), Tot./Working Length: 875mm (34.5")/416mm(16.4") FOR USE WITH: new H95 and previous H95E		
W	369-0793	TOOL, CHISEL, INLINE, H95	84	\$550 NI
		Diam.: 87.5mm (3.4"), Tot./Working Length: 875mm (34.5")/416mm(16.4") FOR USE WITH: new H95 and previous H95E		
W	369-0792	TOOL, CONE, H95	84	\$550 NI
		Diam.: 87.5mm (3.4"), Tot./Working Length: 875mm (34.5")/416mm(16.4") FOR USE WITH: new H95 and previous H95E		
W	373-7159	TOOL, BLUNT, H95	0	\$550 NI
		Diam.: 87.5mm (3.4"), Tot./Working Length: 875mm (34.5")/416mm(16.4") FOR USE WITH: new H95 and previous H95E		

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE CURRENT: NEXT GENERATION 450 (CONT.)

THUMB, HYDRAULIC for Next Generation 450

If no reference numbers appear below there are currently no items available in your region.

W	556-3630	THUMB, HYDRAULIC, 450	240	\$5,778 NI
		Hydraulic thumb. Including connecting lines.		
		FOR USE WITH: Next generation 450 Pin-on or Dual Lock Pingrab coupler		
		REQUIRES: Thumb tine per table below.		

Thumb tines table for Pin-on(NO QC) or Pin Grabber QC buckets

Size	18"		24"		30"		36"	
Bucket	Pin-on	PG QC	Pin-on	PG QC	Pin-on	PG QC	Pin-on	PG QC
Heavy Duty	NA	NA	A3	A5	B3	B5	C3	C5

NA = Not Allowed

W	221-4283	THUMB, TINE, A 3	107	\$438 NI
W	274-5823	THUMB, TINE, B 3	116	\$438 NI
W	274-5835	THUMB, TINE, C 3	99	\$438 NI
W	281-6708	THUMB, TINE, A 5	122	\$583 NI
W	281-6711	THUMB, TINE, B 5	131	\$583 NI
W	281-6714	THUMB, TINE, C 5	114	\$583 NI

RIPPER, FOR Next Generation 450

W	546-4141	RIPPER, 37", MHE 10T-BHL 450	375	\$2,014 NI
		Tip Radius 1119m (44"), includes bucket pins, 1 x J225 long tooth tip		
		FOR USE WITH: Next generation 450 Pin-on or Dual Lock Pingrab coupler		

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE NON CURRENT

QUICK COUPLERS - Pin Puller

W	303-9515	COUPLER, PIN PULLER, 450	260	\$5,090 NI
		FOR USE WITH: Pin on buckets compatible with 450F machines CANNOT BE USED WITH: New buckets compatible with 450/310 machines		
W	322-0190	PINS, PIN PULLER COUPLER, 450	42	\$347 NI
		INCLUDES: One set of pins and hardware with handle.		

BRACKETS

W	305-4984	BRACKET, BHL E-D, MD-LG	165	\$1,319 NI
		Incl bolts and nuts, excl. connecting lines, excl. bucket pins FOR USE WITH: H65D-H70, H90C and BHL D&E		
W	415-2224	BRACKET, BHL A-C, XL	155	\$2,264 NI
		Incl bolts and nuts, excl. connecting lines, excl. bucket pins FOR USE WITH: H75E, H80E, H95E and 416--436C		

BUCKETS for PIN-ON - Ditch Cleaning for 450

W	306-9325	BUCKET-DC, DH, 48", 16.2 FT3	578	\$4,736 NI
W	306-9327	BUCKET-DC, DH, 60", 20.3 FT3	668	\$5,153 NI

BUCKETS for PIN-ON - Heavy Duty Pin-on Teeth for 416, 426, 436 B & C

W	134-5888	BUCKET-HD, 12", 2.5 FT3	270	\$1,597 NI
		Width 305mm (12"), Cap 0.07m3 (0.09yd3), Includes 3 tooth tips Bucket pins Included		
W	134-5866	BUCKET-HD, 16", 3.5 FT3	322	\$1,639 NI
		Width 405mm (16"), Cap 0.10m3 (0.13yd3), Includes 3 tooth tips		
W	134-5867	BUCKET-HD, 18", 4.5 FT3	334	\$1,667 NI
		Width 458mm (18"), Cap 0.13m3 (0.17yd3), Includes 4 tooth tips		
W	134-5868	BUCKET-HD, 24", 7.0 FT3	389	\$1,868 NI
		Width 610mm (24"), Cap 0.20m3 (0.26yd3), Includes 5 tooth tips		
W	134-5869	BUCKET-HD, 30", 9.5 FT3	427	\$2,049 NI
		Width 762mm (30"), Cap 0.27m3 (0.35yd3), Includes 5 tooth tips		
W	134-5870	BUCKET-HD, 36", 11.5 FT3	480	\$2,194 NI
		Width 914mm (36"), Cap 0.33m3 (0.43yd3), Includes 6 tooth tips		

BUCKETS for PIN-ON - Heavy Duty Pin-on Teeth for 446 B & D

W	9R-3218	BUCKET-HD, 18", 6.3 FT3	381	\$1,694 NI
		Width 458mm (18"), Cap 0.18m3 (0.23yd3), Includes 3 tooth tips		
W	9R-3224	BUCKET-HD, 24", 9.5 FT3	459	\$2,042 NI
		Width 610mm (24"), Cap 0.27m3 (0.35yd3), Includes 4 tooth tips		
W	9R-3230	BUCKET-HD, 30", 12.4 FT3	501	\$2,229 NI
		Width 762mm (30"), Cap 0.35m3 (0.46yd3), Includes 5 tooth tips		

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE NON CURRENT (CONT.)

BUCKETS for PIN-ON - Heavy Duty Pin-on Teeth for 446 B & D (Cont.)

W	9R-3236	BUCKET-HD, 36", 15.5 FT3	561	\$2,486 NI
		Width 914mm (36"), Cap 0.44m3 (0.57yd3), Includes 6 tooth tips		

BUCKETS for PIN-ON - Heavy Duty Pin-On Teeth for 450:

W	278-4499	BUCKET-HD, 18", 6.3 FT3	456	\$1,861 NI
		INCLUDES: 3x J225 Long tips		
W	278-4487	BUCKET-HD, 24", 9.5 FT3	542	\$2,132 NI
		INCLUDES: 4x J225 Long tips		
W	278-4493	BUCKET-HD, 30", 12.4 FT3	611	\$2,396 NI
		INCLUDES: 4x J225 Long tips		
W	275-4026	BUCKET-HD, 36", 15.5 FT3	703	\$2,667 NI
		INCLUDES: 6x J225 Long tips		

BUCKETS for PIN-ON - High Capacity Heavy Duty tooth tips for C2

W	136-6911	BUCKET-HC, 18", 6.5 FT3	360	\$1,368 NI
		Width 458mm (18"), Cap 0.18m3 (0.24yd3), Includes 4 tooth tips		
W	136-6912	BUCKET-HC, 24", 9.0 FT3	422	\$1,514 NI
		Width 610mm (24"), Cap 0.24m3 (0.31yd3), Includes 5 tooth tips		
W	136-6913	BUCKET-HC, 30", 11.0 FT3	464	\$1,653 NI
		Width 762mm (30"), Cap 0.32m3 (0.42yd3), Includes 5 tooth tips		
W	136-6914	BUCKET-HC, 36", 14.0 FT3	515	\$1,813 NI
		Width 914mm (36"), Cap 0.38m3 (0.50yd3), Includes 6 tooth tips		

COMPACTING WHEELS for PIN LOCK COUPLERS for 450

W	517-7002	WHEEL, 12", 1/2 PL	946	\$5,326 NI
		Trench width 310mm (12"), 2 wheels each with 9 pads Overall Length-Height-Width: 998mm(39.3")- 1276mm(50.2")- 356mm(14") FOR USE WITH: Pin Lock coupler 1/2YD (Wain Roy)		
W	517-7003	WHEEL, 18", 1/2 PL	1,240	\$6,694 NI
		Trench width 450mm (18"), 3 wheels each with 9 pads Overall Length-Height-Width: 997mm(39.3")- 1284mm(50.6")- 449mm(17.7") FOR USE WITH: Pin Lock coupler 1/2YD (Wain Roy)		
W	517-7004	WHEEL, 24", 1/2 PL	1,281	\$6,972 NI
		Trench width 560mm (22"), 3 wheels each with 9 pads Overall Length-Height-Width: 997mm(39.3")- 1284mm(50.6")- 556mm(21.9") FOR USE WITH: Pin Lock coupler 1/2YD (Wain Roy)		
W	517-7005	WHEEL, 36", 1/2 PL	1,970	\$8,069 NI
		Trench width 880mm (35"), 5 wheels each with 9 pads Overall Length-Height-Width: 1073mm(42.2")- 1284mm(50.6")-884mm(34.8") FOR USE WITH: Pin Lock coupler 1/2YD (Wain Roy)		

CATERPILLAR MACHINE PRICE LIST

WT-BHL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

BACKHOE NON CURRENT (CONT.)

THUMBS for 416 / 420 / 430 D Series Only

Stiff link Thumbs

W	224-6232	THUMB, FIXED, TINE A1,BHL-D PO 297 Includes 221-4282 THUMB, TINE, A 1 FOR USE WITH: 24" heavy duty or standard duty buckets Thumb installation instructions, REHS1770, available via SIS Web		\$2,833 NI
W	224-6233	THUMB, FIXED, TINE A3,BHL-D PO 330 Includes 221-4283 THUMB, TINE, A 3 FOR USE WITH: 24" heavy duty or standard duty buckets with a pin pin grabber coupler or a 24" high capacity without coupler or a 24" heavy duty 1/4 YD pin lock bucket. Thumb installation instructions, REHS1770, available via SIS Web		\$2,833 NI

THUMBS for PIN-ON for 450E/F only

Following tines are for 282-5411 Thumb, Hydr for 450 only.
 The A3 tine is for 24" and 30" pin-on buckets.
 The C3 tine is for 36" pin-on buckets.

W	274-5835	THUMB, TINE, C 3 99		\$438 NI
W	221-4283	THUMB, TINE, A 3 107		\$438 NI