

**1.82m (72 in.) Winch Operated Straight Blade**

Code	Description	List price(USD)
	<p><b>1.82m (72 in.) Winch Operated Straight Blade</b>  1.8m (72 in.) wide winch operated straight blade  Made from thick heavy gauge steel with heavy-duty ribbing for rigidity  Low friction black powdercoat finish  Five-position manual angling  Two adjustable skid shoes  Trip protection  Replaceable steel cutting edge with optional poly and rubber wear bars</p>	
	<p><b>BASE MACHINE</b>  <i>For XUV835, XUV865 only. A winch is needed for blade lift operations if not already installed. Roof/OPS mounted auxiliary lights are recommended if used at night or in conditions where good artificial light does not exist.</i>  Includes blade, blade frame, push tubes, large roller fairlead for winch, and shift lever mounted winch controls. Requires blade undercarriage (Option Code 3154) if not already installed on the vehicle  Heavy duty front suspension recommended, heavy duty rear suspension also recommended when installing a full cab, sprayer or spreader on all E and M-spec open station vehicles. M-spec cab and R-spec vehicles come from the factory with heavy duty suspension already standard.</p>	
801BM	1.82m (72 in.) Winch Operated Straight Blade	\$1,777.00
	<p><b>DESTINATION AND LANGUAGE</b>  <b>Basic Factory Options</b>  <b>DESTINATION</b></p>	
001A	US/Canada	In Base Price
	<p><b>LIFT COMPONENTS</b>  <b>Basic Factory Options</b>  <b>LIFT FRAME KITS</b></p>	
3154	<p>Undercarriage mount  <i>For use on XUV835, XUV865 only</i>  <i>Required with initial blade install on XUV835 and XUV865. Option not needed if undercarriage mount was previously installed on vehicle.</i></p>	In Base Price
	<b>MISCELLANEOUS</b>	

**1.82m (72 in.) Winch Operated Straight Blade**

Code	Description	List price(USD)
<b>ATTACHMENTS FOR FIELD CONVERSION</b>		
<b>MISCELLANEOUS</b>		
BM26185	Beacon Light <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec cab vehicles require Rear Cab Harness</i> <i>R-spec vehicles come pre-wired for Beacon Light</i>	\$277.13
BM26268	Front Attachment Harness (dash port)	\$144.46
BM26739	Rear Cab Attachment Harness	\$78.11
BM26266	E-spec Attachment Harness	\$295.31
BM26215	LED Driving Lights (2 Lights) <i>To mount lights to front of OPS:</i> <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness</i> <i>M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights</i>	\$398.04
BM26267	Roof Attachment Harness	\$95.23
BM26216	LED Work Lights (2 Lights) <i>To mount lights to front of OPS:</i> <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Front Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Front Cab Harness</i> <i>M-spec cab and R-spec vehicles come pre-wired for OPS mounted lights</i> <i>To mount lights to rear of OPS:</i> <i>E-spec vehicles require E-spec Attachments Harness, Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec open station vehicles require Roof Attachments Harness, Rear Cab Harness</i> <i>M-spec cab vehicles require Rear Cab Harness</i> <i>R-spec vehicles come pre-wired for OPS mounted lights</i>	\$398.04



## 1.82m (72 in.) Winch Operated Straight Blade

Code	Description	List price(USD)
BM26740	Front Cab Attachment Harness	\$78.11
BM26756	RUBBER WEAR BAR - WINCH BLADE	\$386.27
BM26401	POLY WEAR BAR - WINCH BLADE	\$386.27
	<b>SUSPENSION ATTACHMENTS FOR FIELD CONVERSION SUSPENSION</b>	
BM26395	Heavy Duty Front Shocks <i>Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station</i>	\$302.81
BM26308	Heavy Duty Rear Shocks <i>Recommended on XUV835E, XUV865E, XUV835M open station, XUV865M open station</i>	\$345.61
	<b>BLADE ATTACHMENTS FOR FIELD CONVERSION PLOW MARKERS</b>	
BM26397	Plow Markers	\$51.36