

CATERPILLAR MACHINE PRICE LIST

WT-MHE

MINI HYDRAULIC EXCAVATOR WORK TOOLS

Ship Weight
lbsLIST PRICE
AT DEALER

Standard Equipment:

This Price List consists of Work Tools
for models 300.9 through 310 (Next Gen)
Mini Hydraulic Excavators

This price list is split into the
following sections:

MHE - BELOW 1 TON

Model: 300.9D

MHE - FROM ONE TON AND INCLUDING 2 TONS

Models: 301.4C/301.5/301.6C/301.7D/
301.7DCR/301.8/301.8C

Next generation 301.5 / 301.6 / 301.7CR

Next generation 301.8

Next generation 302CR

MHE - ABOVE 2 TONS AND BELOW 3 TONS

Models:302.2D/302.4D/302.5C/302.5/302.7D

MHE - FROM 3 TONS AND BELOW 5 TONS

Models: 303C CR/303E CR/303.5C CR/
303.5D CR/303.5E CR/303.5E2/304D CR/
304E CR/ 304E2/304.5E2

MHE - FROM 5 TONS AND BELOW 7 TONS

Models: 304C CR/305C CR/305D CR/305E CR/
305E2/305.5D CR/305.5E CR/305.5E2/306E2

Next Generation 306/306.5/306.6CR SB

MHE - FROM 7 TONS AND BELOW 10 TONS

Models: 307D / 307E / 307E2

Next generation 307.5

308D / 308E CR/ 308E2

Next generation 308 / 309CR

MHE 10 TONS

Models: Next generation 310

MHE - HAMMERS

All applicable models

MHE - SSL ATTACHMENTS FOR XTC MACHINES

Model: 304.5E2 fitted with SSL coupler

MHE - SSL TO MHE ADAPTER/QUICK COUPLER

Available on all models 3 tons and above

MHE - NON CURRENT MODELS

Covers worktools with different sized

pins or spreads to the above.

Please see specific items for usage.

MHE - AUGER BITS

MHE - AUGER BITS

SECTION ORDER

Each section divided by machine weight
is arranged in the following order:

- 1: Couplers
- 2: Buckets
- 3: All remaining attachments in
alphabetical order

FOR NORTH AND SOUTH AMERICA

CATERPILLAR MACHINE PRICE LIST

WT-MHE**MINI HYDRAULIC EXCAVATOR WORK TOOLS**Ship Weight
lbsLIST PRICE
AT DEALER

Orders will automatically transfer
from CMOPS to Antares Parts Ordering.

FOR THE REST OF THE WORLD
This price list is for REFERENCE ONLY.
Work Tool orders must be placed using
Antares Parts Ordering.

FOR JAPAN
Please access the usual regional
resources for pricing information

For BCP Attachment Product and
Application Support
1-866-963-3531, Option #1, Option #2
E-mail: BCP_Work_Tools@Cat.com

For Order Management/Availability
Support
1-866-963-3531, Option #1, Option #1
E-mail:
Cat_Parts_BCP_Work_Tools_Support@Cat.com

CATERPILLAR MACHINE PRICE LIST

WT-MHE

MINI HYDRAULIC EXCAVATOR WORK TOOLS

Ship Weight
lbs

LIST PRICE
AT DEALER

CATERPILLAR MACHINE PRICE LIST

WT-MHE

MINI HYDRAULIC EXCAVATOR WORK TOOLS

Ship Weight
lbs

LIST PRICE
AT DEALER

0P-0227

MINI HYD EXCAVATOR WORK TOOLS 0
Please use this reference number when ordering.

NC

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

MHE - BELOW 1 TON

BUCKETS FOR PIN-ON - Digging/General Purpose

Bucket pins are 25mm in diameter.
 Following MHE have the same linkage: 300.9D

W	373-4456	BUCKET-DG, 10", 0.49 FT3, U1T 33 Width 250mm (10"), Heaped Capacity 0.014m3 (0.49 ft3) Pin-on, Includes 3 weld-on teeth		\$569 NI
W	432-5173	BUCKET-DG, 15", 0.62 FT3, U1T 17 Width 370mm (15"), Heaped Capacity 0.018m3 (0.62 ft3) Pin-on, Includes 3 weld-on teeth and weld-on side cutters		\$594 NI

BUCKETS FOR PIN-ON - Ditch Cleaning

W	373-4458	BUCKET-DC, 28", 0.95 FT3, U1T 55 Width 700mm (28"), Heaped Capacity 0.027m3 (0.95 ft3)		\$840 NI
---	----------	---	--	----------

BUCKETS FOR PIN-ON - Pins

Must be ordered directly in ANTARES, not available through CMOPS

373-5697 PIN, BUCKET, 25MM
 Consists of 1x 25mm diam bucket pin exl retention pin. For a pin set please order 2x 373-5697 and 2x 373-5664 pin retention (NB 373-5697 must be ordered directly in ANTARES not through CMOPS)

HAMMERS - H25D FLAT TOP - for details see Hammer Section

Please note: This option is not available in all regions.

WARNING:

Demolition tools can create a hazard from flying objects. Caterpillar recommends installing front guards on the cabs of the excavators. Failure to do so can lead to injury or death.

NOTEF
 Compatibility table for hammers:

Machines	B hammers	H hammers
300.9D	B1 Pin-On ++	H25D ++

++= Optimal +-= Acceptable ---= Not Allowed

For the correct part numbers, please see Hammer Section.

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

MHE - FROM ONE TON AND INCLUDING 2 TONS

QUICK COUPLERS

All quick couplers need to be fitted to the machine stick using the original bucket pins which come with a new machine. Otherwise order an extra set.

Bucket pins are 30mm in diameter.

Following MHE have the same linkage: 301.4C / 301.5 / 301.6C / 301.7D

301.7DCR / 301.8 / 301.8C

Next generation 301.5 / 301.6 / 301.7CR / 301.8

Next generation 302CR

W	361-1092	COUPLER, PG, MAN.D.LOCK, 1T 26 INCLUDES: 1 set of Bucket Pins and hard ware to attach 1 bucket REQUIRES: 154-2672 Bucket Pins for EACH ADDITIONAL Bucket Includes 1 set of bucket pins 154-2672.		\$781 NI
W	154-2672	PINS, BUCKET, 30MM 4 INCLUDES: 2 bucket pins and hardware To be used with pin-on bucket and PG coupler. Every tool needs 1 set.		\$76 NI

BUCKETS FOR PIN-ON - Digging/General Purpose

Bucket pins are 30mm in diameter. Following MHE have the same linkage:

301.4C / 301.5 / 301.6C / 301.7D / 301.7DCR/ 301.8/ 301.8C

Next generation 301.5 / 301.7 / 301.8

Next generation 302

Designed for general purpose. All buckets come with weld-on sidecutter and double strap bolt-on Uniteeth.

W	147-1014	BUCKET-DG, 9", 0.65 FT3, 1T 65 Width 230mm (9"), Heaped Cap. 0.018m3 (0.65 ft3), Incl 3 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$451 NI
W	147-1018	BUCKET-DG, 12", 0.78 FT3, 1T 69 Width 300mm (12"), Heaped Cap. 0.022M3 (0.78 ft3), Incl 3 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$486 NI
W	147-1020	BUCKET-DG, 16", 1.16 FT3, 1T 78 Width 400mm (16"), Heaped Cap. 0.033M3 (1.16 ft3), Incl 3 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$556 NI
W	190-7387	BUCKET-DG, 18", 1.40 FT3, 1T 84 Width 460mm (18"), Heaped Cap. 0.04M3 (1.40 ft3), Incl 3 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$597 NI
W	147-1023	BUCKET-DG, 20", 1.59 FT3, 1T 91 Width 500mm (20"), Heaped Cap. 0.045M3 (1.59 ft3), Incl 4 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$625 NI
W	147-1026	BUCKET-DG, 24", 1.97 FT3, 1T 100 Width 600mm (24"), Heaped Cap. 0.056m3 (1.97 ft3), Incl 4 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$694 NI

BUCKETS FOR PIN-ON - Ditch Cleaning

W	147-1029	BUCKET-DC, 32", 1.54 FT3, 1T 89 Width 800mm (32"), Heaped Cap. 0.044m3 (1.54 ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: back grading edge & water holes		\$618 NI
---	----------	--	--	----------

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

MHE - FROM ONE TON AND INCLUDING 2 TONS (CONT.)

BUCKETS FOR PIN-ON - Ditch Cleaning (Cont.)

W	147-1031	BUCKET-DC, 40", 1.97 FT3, 1T 94 Width 1000mm (40"), Heaped Cap. 0.056M3 (1.97 ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: water holes		\$618 NI
W	244-3073	BUCKET-DCT, 39", 2.0 FT3, 1T 168 Width 1000mm (39"), Heaped Cap. 0.056M3 (2.00 ft3) Tilt: 45 degrees each way from horizontal FOR USE WITH: Pin-on, requires bucket pins INCLUDES: back grading edge, connecting lines & water holes		\$2,799 NI

BUCKETS FOR PIN-ON - Grading/Mud

Designed for grading with higher capacity and suited to carry buckets.

W	388-9661	BUCKET-GRADING, 39",3.1FT3, 1T 132 Width 1000mm (39"), Heaped Cap. 0.09m3 (3.1 ft3) FOR USE WITH: Pin-on, includes bucket pins.		\$639 NI
---	----------	--	--	-----------------

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM ONE TON AND INCLUDING 2 TONS (CONT.)

AUGERS

Nomenclature change: A11 is replacement for A7B, NO technical changes
 A11 stands for Auger with a Torque= 1105Nm (A11 = A7B)
 For auger bits, please see section "AUGER BITS"

W	218-3206	AUGER, A11, MHE 1T, 30MM 174 A11 (old A7B) has a torque of 1105Nm INCLUDES: DIRECT drive unit, hydraulic lines with quick disconnects, mounting bracket, hardware and 2" (50mm) HEX output shaft. REQUIRES: 1 set of bucket pins		\$1,896 NI
W	225-3893	AUGER, DRIVE, A11 151 FOR USE WITH: A11 and A7B REQUIRES: 2 way proportional aux lines on carrier machine		\$1,653 NI
W	213-9238	BRACKET, A11, MHE 1T, 30MM 36 FOR USE WITH: A11 and A7B		\$243 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM ONE TON AND INCLUDING 2 TONS (CONT.)

COMPACTION WHEELS FOR PIN-ON

To compact soil in trenches by rolling the wheels over the soil and pushing it down using the boom and stock of the machine.

W	517-6970	WHEEL, 12", 1T 342 Trench width 270mm (11"), 2 wheels each with 8 pads Overall Length-Height-Width: 726mm(28.6")- 752mm(29.6")- 292mm(11.5") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$3,208 NI
W	517-6971	WHEEL, 16", 1T 476 Trench width 400mm (16"), 3 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 792mm(31.2")- 399mm(15.7") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$3,701 NI
W	517-6972	WHEEL, 22", 1T 569 Trench width 550mm (22"), 4 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 792mm(31.2")- 553mm(21.8") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$4,069 NI

COMPACTION WHEELS for PIN LOCK COUPLERS

W	517-6982	WHEEL, 12", 1/8 PL 395 Trench width 270mm (11"), 2 wheels each with 8 pads Overall Length-Height-Width: 726mm(28.6")- 921mm(36.3")- 292mm(11.5") FOR USE WITH: Pin Lock coupler 1/8YD (Wain Roy)		\$3,208 NI
W	517-6983	WHEEL, 16", 1/8 PL 528 Trench width 400mm (16"), 3 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 961mm(37.8")- 399mm(15.7") FOR USE WITH: Pin Lock coupler 1/8YD (Wain Roy)		\$3,701 NI
W	517-6984	WHEEL, 22", 1/8 PL 622 Trench width 550mm (22"), 4 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 961mm(37.8")- 553mm(21.8") FOR USE WITH: Pin Lock coupler 1/8YD (Wain Roy)		\$4,069 NI
W	517-6985	WHEEL, 12", 1/8 PL 389 Trench width 270mm (11"), 2 wheels each with 8 pads Overall Length-Height-Width: 726mm(28.6")- 901mm(35.5")- 292mm(11.5") FOR USE WITH: Pin Lock coupler 1/8YD (TAG)		\$3,208 NI
W	517-6986	WHEEL, 16", 1/8 PL 523 Trench width 400mm (16"), 3 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 941mm(37")- 399mm(15.7") FOR USE WITH: Pin Lock coupler 1/8YD (TAG)		\$3,701 NI
W	517-6987	WHEEL, 22", 1/8 PL 617 Trench width 550mm (22"), 4 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 941mm(37")- 553mm(21.8") FOR USE WITH: Pin Lock coupler 1/8YD (TAG)		\$4,069 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM ONE TON AND INCLUDING 2 TONS (CONT.)

HAMMERS - B and H series - for details see Hammer Section

WARNING:

Demolition tools can create a hazard from flying objects. Caterpillar recommends installing front guards on the cabs of the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers			H hammers	
	B1	B2	B4	H35	H45
301.4C,	++	--	--	++	--
301.6C, 301.7D, 301.8C	++	+-	--	++	+-
Next Generation					
301.5, 301.6	++	+-	--	++	+-
301.7CR, 301.8	++	+-	--	++	+-
302CR	+-	++	--	+-	++

++= Optimal +-= Acceptable ---= Not Allowed

For the correct part numbers, please see Hammer Section.

THUMBS

W	555-8424	THUMB, HYDRAULIC, 1T 93	\$1,944 NI
		No-link style hydraulic thumb. Please note: this Thumb meshes with buckets 18" and larger INCLUDES: Thumb with 2 teeth, mounting group and hydr. cylinder FOR USE WITH: Pin-on or the pin-grabber dual lock coupler (not CW05) NOT FOR USE WITH: 301.4C REQUIRES: Auxiliary lines group with two-way flow functionality REQUIRES: Machine with thumb ready stick. No bracket available for field installed retrofit in Next Generation machines. For old generation machines, you can use 209-9171 bracket (only available directly through Antares).	

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - ABOVE 2 TONS AND BELOW 3 TONS

QUICK COUPLERS

All quick couplers need to be fitted to the machine stick using the original bucket pins which come with a new machine. Otherwise order an extra set.

Bucket pins are 35mm in diameter.

Following MHE have the same linkage: 302.2D/302.4D/302.5C/302.5/302.7D

W	361-1093	COUPLER, PG, MAN.D.LOCK, 2T 44 Mechanical Quick Coupler INCLUDES: 1 set of Bucket Pins and hard ware to attach 1 bucket REQUIRES: 154-2683 Bucket Pins for EACH ADDITIONAL Bucket		\$1,142 NI
W	154-2683	PINS, BUCKET, 35MM 13 INCLUDES: 2 bucket pins and hardware FOR USE WITH: Quick Coupler 361-1093 and Pin-On Buckets		\$90 NI

BUCKETS FOR PIN-ON - Digging/General Purpose - 302.2D & 302.4D

Bucket pins are 35mm in diameter. Following MHE have the same linkage:
 302.2D / 302.4D / 302.5C / 302.5 / 302.7D

These buckets have a reduced tip radius to fit on 302.2D & 302.4D.

Designed for general purpose. All buckets come with weld-on sidecutter and double strap bolt-on Uniteeth.

W	396-9302	BUCKET-DG, 10", 0.97 FT3, 2T 104 Width 260mm (10"), Heaped Cap. 0.027m3 (0.97 ft3), Incl 3 Unitooth FOR USE WITH: Pin-on, includes bucket pins		\$590 NI
W	396-9303	BUCKET-DG, 12", 1.2 FT3, 2T 101 Width 300mm (12"), Heaped Cap. 0.034m3 (1.2 ft3), Incl 3 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$604 NI
W	396-9304	BUCKET-DG, 16" 1.6 FT3, 2T 110 Width 400mm (16"), Heaped Cap. 0.045m3 (1.6 ft3), Incl 3 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$674 NI
W	396-9305	BUCKET-DG, 18", 1.9 FT3, 2T 119 Width 460mm (18"), Heaped Cap. 0.054m3 (1.9 ft3), Incl 3 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$715 NI
W	396-9306	BUCKET-DG, 20", 2.0 FT3, 2T 130 Width 500mm (20"), Heaped Cap. 0.06m3 (2.0 ft3), Incl 4 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$750 NI
W	396-9307	BUCKET-DG, 24", 2.7 FT3, 2T 143 Width 600mm (24"), Heaped Cap. 0.076m3 (2.7 ft3), Incl 4 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$840 NI
W	396-9308	BUCKET-DG, 28", 3.2 FT3, 2T 157 Width 700mm (28"), Heaped Cap. 0.092m3 (3.2 ft3), Incl 4 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$924 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - ABOVE 2 TONS AND BELOW 3 TONS (CONT.)

BUCKETS FOR PIN-ON - Digging/General Purpose - NOT 302.2D OR 302.4D

CAN NOT BE USED on 302.2D & 302.4D as buckets will damage stick.
Designed for general purpose. All buckets come with weld-on sidecutter and double strap bolt-on Uniteeth.

W	176-7283	BUCKET-DG, 10", 1.2 FT3, 2T 112 Width 260mm (10"), Heaped Cap. 0.035m3 (1.2 ft3), Incl 3 Unitooth FOR USE WITH: Pin-on, includes bucket pins		\$625 NI
W	153-7851	BUCKET-DG, 12", 1.4 FT3, 2T 111 Width 300mm (12"), Heaped Cap. 0.041m3 (1.4 ft3), Incl 3 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$667 NI
W	153-7854	BUCKET-DG, 16", 1.9 FT3, 2T 121 Width 400mm (16"), Heaped Cap. 0.054m3 (1.9 ft3), Incl 3 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$736 NI
W	190-7390	BUCKET-DG, 18", 2.3 FT3, 2T 130 Width 460mm (18"), Heaped Cap. 0.065m3 (2.3 ft3), Incl 3 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$792 NI
W	153-7857	BUCKET-DG, 20", 2.6 FT3, 2T 140 Width 500mm (20"), Heaped Cap. 0.073M3 (2.6 ft3), Incl 4 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$833 NI
W	153-7860	BUCKET-DG, 24", 3.2 FT3, 2T 155 Width 600mm (24"), Heaped Cap. 0.092m3 (3.2 ft3), Incl 4 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$931 NI
W	190-7391	BUCKET-DG, 27", 3.9 FT3, 2T 170 Width 700mm (27"), Heaped Cap. 0.111m3 (3.9 ft3), Incl 4 Unitooth FOR USE WITH: Pin-on, requires bucket pins		\$1,021 NI

BUCKETS FOR PIN-ON - Ditch Cleaning

W	153-7863	BUCKET-DC, 32", 2.8 FT3, 2T 179 Width 800mm (32"), Heaped Cap. 0.08m3 (2.8 ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: back grading edge & water holes		\$757 NI
W	153-7865	BUCKET-DC, 40", 3.6 FT3, 2T 172 Width 1000mm (40"), Heaped Cap. 0.102m3 (3.6ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: water holes		\$806 NI
W	153-7867	BUCKET-DC, 47", 4.1 FT3, 2T 193 Width 1200mm (47"), Heaped Cap. 0.116M3 (4.1 ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: water holes		\$910 NI
W	246-0094	BUCKET-DCT, 43", 4.4 FT3, 2T 293 Width 1100mm (43"), Heaped Cap. 0.125M3 (4.4 ft3) Tilt: 45 degrees each way from horizontal FOR USE WITH: Pin-on, requires bucket pins INCLUDES: back grading edge, connecting lines & water holes		\$3,104 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-------------------------------	--------------------	-------------------------

MHE - ABOVE 2 TONS AND BELOW 3 TONS (CONT.)

BUCKETS FOR PIN-ON - Grading/Mud

W	388-9662	BUCKET-GRADING,39", 6.2 FT3,2T 188 Width 1000mm (39"), Heaped Cap. 0.17M3 (6.2ft3) FOR USE WITH: Pin-on, includes bucket pins	188	\$986 NI
---	----------	--	-----	-----------------

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - ABOVE 2 TONS AND BELOW 3 TONS (CONT.)

AUGERS

Nomenclature change: A11 is replacement for A7B, NO technical changes
 A11 stands for Auger with a Torque= 1105Nm (A11 = A7B)
 Nomenclature change: A23 is replacement for A14B, NO technical changes
 A23 stands for Auger with a Torque= 2300Nm (A23 = A14B)
 For auger bits, please see section "AUGER BITS"

W	218-3207	AUGER, A11, MHE 2T, 35MM	179	\$1,896 NI
		A11 (old A7B) has a torque of 1105Nm INCLUDES: DIRECT drive unit, hydraulic lines with quick disconnects, mounting bracket, hardware and 2" (50mm) HEX output shaft. FOR USE WITH: pin-on REQUIRES: 1 set of bucket pins		
W	225-3893	AUGER, DRIVE, A11	151	\$1,653 NI
		A11 (old A7B) has a torque of 1105Nm REQUIRES: Bracket, connecting lines and auger flight		
W	218-3197	AUGER, A23, MHE 2T, 35MM	257	\$2,486 NI
		A23 (old A14B) has torque of 2300Nm INCLUDES: DIRECT drive unit, hydraulic lines with quick disconnects, mounting bracket, hardware and 2" (50mm) HEX output shaft. FOR USE WITH: pin-on REQUIRES: 1 set of bucket pins		
W	225-3895	AUGER, DRIVE, A23	242	\$2,243 NI
		A23 (old A14B) has torque of 2300Nm REQUIRES: Bracket, connecting lines and auger flight		
W	213-8570	BRACKET, A11/A23, MHE 2T, 35MM	41	\$243 NI
		FOR USE WITH: A11 + A23 and old A7B + A14B		

COMPACTION WHEELS FOR PIN-ON

To compact soil in trenches by rolling the wheels over the soil and pushing it down using the boom and stock of the machine.

W	517-6973	WHEEL, 12", 2T	354	\$3,208 NI
		Trench width 270mm (11"), 2 wheels each with 8 pads Overall Length-Height-Width: 725mm(28.5")- 787mm(31")- 313mm(12.3") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		
W	517-6974	WHEEL, 16", 2T	489	\$3,701 NI
		Trench width 400mm (16"), 3 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 827mm(32.6")- 399mm(15.7") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		
W	517-6975	WHEEL, 22", 2T	583	\$4,069 NI
		Trench width 550mm (22"), 4 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 827mm(32.6")- 553mm(21.8") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - ABOVE 2 TONS AND BELOW 3 TONS (CONT.)

COMPACTION WHEELS for PIN LOCK COUPLERS

W	517-6982	WHEEL, 12", 1/8 PL 395 Trench width 270mm (11"), 2 wheels each with 8 pads Overall Length-Height-Width: 726mm(28.6")- 921mm(36.3")- 292mm(11.5") FOR USE WITH: Pin Lock coupler 1/8YD (Wain Roy)		\$3,208 NI
W	517-6983	WHEEL, 16", 1/8 PL 528 Trench width 400mm (16"), 3 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 961mm(37.8")- 399mm(15.7") FOR USE WITH: Pin Lock coupler 1/8YD (Wain Roy)		\$3,701 NI
W	517-6984	WHEEL, 22", 1/8 PL 622 Trench width 550mm (22"), 4 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 961mm(37.8")- 553mm(21.8") FOR USE WITH: Pin Lock coupler 1/8YD (Wain Roy)		\$4,069 NI
W	517-6985	WHEEL, 12", 1/8 PL 389 Trench width 270mm (11"), 2 wheels each with 8 pads Overall Length-Height-Width: 726mm(28.6")- 901mm(35.5")- 292mm(11.5") FOR USE WITH: Pin Lock coupler 1/8YD (TAG)		\$3,208 NI
W	517-6986	WHEEL, 16", 1/8 PL 523 Trench width 400mm (16"), 3 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 941mm(37")- 399mm(15.7") FOR USE WITH: Pin Lock coupler 1/8YD (TAG)		\$3,701 NI
W	517-6987	WHEEL, 22", 1/8 PL 617 Trench width 550mm (22"), 4 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 941mm(37")- 553mm(21.8") FOR USE WITH: Pin Lock coupler 1/8YD (TAG)		\$4,069 NI

COMPACTOR PLATE CVP16

FOR USE WITH: 302.5, 302.5C, 302.7D

W	551-4956	COMPACTOR PLATE, CVP16 191 Has drill pattern SM and LG REQUIRES: Mounting bracket and connecting lines		\$5,826 NI
W	222-6443	BLADE, BACKFILL, CVP16 34 FOR USE WITH: CVP16 for back filling trenches		\$313 NI
W	265-7461	SWIVEL, CVP16, LG TO LG 132 FOR USE WITH: CVP16 and fitted between mounting bracket and CVP16.		\$1,339 NI
W	532-9053	BRACKET, MHE 2T 35MM, SM-LG 94 Mounting bracket, drill pattern SM + LG, incl.bolts + nuts, incl. pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC		\$382 NI
W	154-2683	PINS, BUCKET, 35MM 13 Full set of bucket pins 35mm diameter		\$90 NI
W	203-0998	LINES, CVP16, MHE 2T 4		\$319 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - ABOVE 2 TONS AND BELOW 3 TONS (CONT.)

HAMMERS - B and H series - for details see Hammer Section

WARNING:

Demolition tools can create a hazard from flying objects. Caterpillar recommends installing front guards on the cabs of the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers	H hammers
302.2D, 302.4D	B1 B2 B4	H35 H45 H55
302.5C, 302.7D CR	+- ++ --	+- ++ --
	-- ++ +-	-- ++ +-

++= Optimal += Acceptable --= Not Allowed

For the correct part numbers, please see Hammer Section.

THUMB, HYDRAULIC FOR PIN-ON

W	451-6380	THUMB, HYDRAULIC, 2T 140	\$2,403 NI
		No-link style INCLUDES: Thumb group with 2 teeth FOR USE WITH: 302.4D and 302.7D REQUIRES: Auxiliary lines group with two-way flow functionality REQUIRES: Machine with thumb ready stick or separate mounting bracket	
W	204-4972	BRACKET, MOUNTING 7	\$347 NI
		FOR USE WITH: Thumbs and non-thumb-ready sticks.	

MHE - FROM 3 TONS AND BELOW 5 TONS

QUICK COUPLERS

All quick couplers need to be fitted to the machine stick using the original bucket pins which come with a new machine. Otherwise order an extra set.

Bucket pins are 40mm in diameter.

Following MHE have the same linkage: 303C CR / 303E CR / 303.5C CR

303.5D CR / 303.5E CR/ 303.5E2 / 304D CR/ 304E CR/ 304E2 / 304.5E2

For 304C CR please see section 5T-7T

W	444-7494	COUPLER, PG, MAN.D.LOCK, 3-4T 76	\$1,410 NI
		Mechanical Quick Coupler INCLUDES: 1 set of Bucket Pins and hard ware to attach 1 bucket REQUIRES: 154-2638 Bucket Pins for EACH ADDITIONAL Bucket	
W	485-5300	COUPLER, PG, HYDR.D.LOCK, 3-4T 91	\$2,479
		Hydraulic Quick Coupler INCLUDES: 1 set of pins and hardware to attach 1 bucket REQUIRES: 154-2638 bucket pins for EACH ADDITIONAL bucket and hydraulic QC lines on machine.	

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
MHE - FROM 3 TONS AND BELOW 5 TONS (CONT.)				
QUICK COUPLERS (Cont.)				
W	373-2370	KIT, HYDRAULIC QC LINES, 3 TON 18 FOR USE WITH: Hyd dual lock PG coupler and hyd CW05/CW10 coupler and for machines 303C, 303.5C, 303.5D and 304D		\$1,417 NI
W	384-5013	KIT, HYDRAULIC QC LINES, 3 TON 18 FOR USE WITH: Hyd dual lock PG coupler and hyd CW05/CW10 coupler and for machines 303.5E, 303.5E2, 304E, 304E2 and 304.5E2		\$1,460 NI
W	154-2638	PINS, BUCKET, 40MM 11 INCLUDES: 2 bucket pins and hardware FOR USE WITH: 444-7494 and 485-5300 and Pin-On Buckets		\$97 NI

SSL to MHE ADAPTER / QUICK COUPLER

For the SSL to MHE Adapter / quick coupler please see section "SSL to MHE ADAPTER / QUICK COUPLER".
 This section also shows the allowed SSL attachments available.

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 3 TONS AND BELOW 5 TONS (CONT.)

BUCKETS FOR PIN-ON

Bucket pins are 40mm in diameter. Following MHE have the same linkage:
 303C CR/ 303E CR
 303.5C CR/ 303.5D CR/ 303.5E CR/ 303.5E2
 304D CR/ 304E CR/ 304E2
 304.5E2
 For 304C CR please see section 5T-7T

BUCKETS FOR PIN-ON - Heavy Duty with pin-on tips

NOTE: Optional side cutters are available. Part numbers are:
 LH Side Cutter 252-2611 / RH Side Cutter 252-2612
 Bolts 4F-3653 (3 per side cutter, total 6 per bucket)
 Nuts 4K-0367 (3 per side cutter, total 6 per bucket)
 (IRM): GET06-03 for further information and selection criteria.

W	464-9900	BUCKET-HD, 12", 1.7 FT3, 3T	142	\$958 NI
		Width 305mm (12"), Heaped Cap. 0.05M3 (1.7ft3), Incl 3 x J200 FOR USE WITH: Pin-on, requires bucket pins		
W	464-9901	BUCKET-HD, 16", 2.5 FT3, 3T	162	\$1,042 NI
		Width 406mm (16"), Heaped Cap. 0.07M3 (2.5ft3), Incl 3 x J200 FOR USE WITH: Pin-on, requires bucket pins		
W	464-9902	BUCKET-HD, 18", 2.9 FT3, 3T	180	\$1,083 NI
		Width 457mm (18"), Heaped Cap. 0.08M3 (2.9ft3), Incl 4 x J200 FOR USE WITH: Pin-on, requires bucket pins		
W	464-9903	BUCKET-HD, 20", 3.3 FT3, 3T	192	\$1,118 NI
		Width 508mm (20"), Heaped Cap. 0.09M3 (3.3ft3), Incl 4 x J200 FOR USE WITH: Pin-on, requires bucket pins		
W	464-9904	BUCKET-HD, 24", 4.2 FT3, 3T	216	\$1,208 NI
		Width 619mm (24"), Heaped Cap. 0.12M3 (4.2ft3), Incl 4 x J200 FOR USE WITH: Pin-on, requires bucket pins		
W	535-8403	BUCKET-HD, 24", 4.2 FT3, 3T	216	\$1,201 NI
		Width 610mm (24"), Heaped Cap. 0.12M3 (4.2ft3), Incl 5 x J200 DOES NOT MESH WITH THUMB FOR USE WITH: Pin-on, requires bucket pins		
W	464-9905	BUCKET-HD, 30", 5.6 FT3, 3T	258	\$1,347 NI
		Width 762mm (30"), Heaped Cap. 0.16M3 (5.6ft3), Incl 5 x J200 FOR USE WITH: Pin-on, requires bucket pins		
W	464-9906	BUCKET-HD, 36", 7.0 FT3, 3T	293	\$1,479 NI
		Width 914mm (36"), Heaped Cap. 0.2M3 (7.0ft3), Incl 5 x J200 FOR USE WITH: Pin-on, requires bucket pins		

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 3 TONS AND BELOW 5 TONS (CONT.)

BUCKETS FOR PIN-ON - Cemetery / Cemetary

Special designed to trench graves, the shape allows vertical walls and and flat bottoms.

W	415-6725	BUCKET-CEMETERY, 32", 4.2 FT3 273 Width: 813mm (32"), Cap.: 0.119m3 (4.2 ft3), base edge Tip Radius: 546mm (21.5") FOR USE WITH: Pin-on, requires bucket pins		\$3,868 NI
---	----------	---	--	-------------------

BUCKETS FOR PIN-ON - Ditch Cleaning

W	279-4322	BUCKET-DC, 40", 4.8 FT3, 3T 234 Width 1000mm (39"), Heaped Cap. 0.137M3 (4.8ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: back grading edge and water holes		\$1,042 NI
W	279-4323	BUCKET-DC, 47", 5.9 FT3, 3T 234 Width 1200mm (47"), Heaped Cap. 0.167M3 (5.9ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: water holes		\$1,118 NI
W	282-9315	BUCKET-DC, 55", 6.9 FT3, 3T 234 Width 1400mm (55"), Heaped Cap. 0.197M3 (6.9ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: water holes		\$1,285 NI
W	279-4325	BUCKET-DCT, 47", 5.9 FT3, 3T 357 Width 1200mm (47"), Heaped Cap. 0.167M3 (5.9ft3) Tilt: 45 degrees each way from horizontal FOR USE WITH: Pin-on, requires bucket pins INCLUDES: back grading edge, connecting lines & water holes		\$3,722 NI

BUCKETS FOR PIN-ON - Grading/Cleaning

Designed for cleaning and grading.

W	423-2737	BUCKET-GRADING, 32", 6.7 FT3 311 Width: 813mm (32"), Cap.: 0.119m3 (6.7 ft3), base edge Tip Radius: 711mm (28") FOR USE WITH: Pin-on, requires bucket pins		\$2,854 NI
W	415-5304	BUCKET-GRADING, 42", 7.3 CFT 313 Width: 1067mm (42"), Cap.: 0.207m3 (7.3 ft3), includes BOCE Tip Radius: 660mm (26") FOR USE WITH: Pin-on, requires bucket pins		\$3,931 NI

BUCKETS FOR PIN-ON - Grading/Mud

Designed for grading with higher capacity and suited to carry buckets.

W	388-9663	BUCKET-GRADING, 47", 8.1 FT3, 3T 381 Width 1200mm (47"), Heaped Cap. 0.23M3 (8.1ft3) FOR USE WITH: Pin-on, includes bucket pins and BOCE		\$1,285 NI
---	----------	---	--	-------------------

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 3 TONS AND BELOW 5 TONS (CONT.)

AUGERS

Nomenclature change: A23 is replacement for A14B, NO technical changes
 A23 stands for Auger with a Torque= 2300Nm (A23 = A14B)
 Nomenclature change: A41 is replacement for A19B, NO technical changes
 A41 stands for Auger with a Torque= 4100Nm (A41 = A19B)
 For auger bits, please see section "AUGER BITS"

W	218-3198	AUGER, A23, MHE 3T, 40MM	264	\$2,486 NI
		A23 (old A14B) has a torque of 2300Nm INCLUDES: DIRECT drive unit, hydraulic lines with quick disconnects, mounting bracket, hardware and 2" (50mm) HEX output shaft. FOR USE WITH: pin-on REQUIRES: 1 set of bucket pins REQUIRES: 2 way proportional aux lines on carrier machine		
W	225-3895	AUGER, DRIVE, A23	242	\$2,243 NI
		A23 (old A14B) has a torque of 2300Nm REQUIRES: Bracket, connecting lines and auger flight		
W	220-7137	AUGER, A41, MHE 3T, 40MM	205	\$2,951 NI
		A41 (old A19B) has a torque of 4100Nm Includes single reduction planetary drive unit, hydraulic lines with quick disconnects, mounting bracket, hardware and 2" (50mm) HEX output shaft. FOR USE WITH: pin-on REQUIRES: 1 set of bucket pins REQUIRES: 2 way proportional aux lines on carrier machine		
W	230-5578	AUGER, DRIVE, A41	187	\$2,708 NI
		A41 (old A19B) has a torque of 4100Nm REQUIRES: Bracket, connecting lines and auger flight		
W	213-8568	BRACKET, A11-A41, MHE 3T, 40MM	46	\$243 NI
		FOR USE WITH: A23 + A41 and old A14B + A19B		

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 3 TONS AND BELOW 5 TONS (CONT.)

COMPACTION WHEELS FOR PIN-ON

To compact soil in trenches by rolling the wheels over the soil and pushing it down using the boom and stock of the machine.

W	517-6976	WHEEL, 12", 3/4T 357 Trench width 270mm (11"), 2 wheels each with 8 pads Overall Length-Height-Width: 726mm(28.6")- 806mm(31.7")- 309mm(12.2") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$3,208 NI
W	517-6977	WHEEL, 16", 3/4T 493 Trench width 400mm (16"), 3 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 846mm(33.3")- 399mm(15.7") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$3,701 NI
W	517-6978	WHEEL, 22", 3/4T 586 Trench width 550mm (22"), 4 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 846mm(33.3")- 553mm(21.8") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$4,069 NI

COMPACTION WHEELS for PIN LOCK COUPLERS

W	517-6982	WHEEL, 12", 1/8 PL 395 Trench width 270mm (11"), 2 wheels each with 8 pads Overall Length-Height-Width: 726mm(28.6")- 921mm(36.3")- 292mm(11.5") FOR USE WITH: Pin Lock coupler 1/8YD (Wain Roy)		\$3,208 NI
W	517-6983	WHEEL, 16", 1/8 PL 528 Trench width 400mm (16"), 3 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 961mm(37.8")- 399mm(15.7") FOR USE WITH: Pin Lock coupler 1/8YD (Wain Roy)		\$3,701 NI
W	517-6984	WHEEL, 22", 1/8 PL 622 Trench width 550mm (22"), 4 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 961mm(37.8")- 553mm(21.8") FOR USE WITH: Pin Lock coupler 1/8YD (Wain Roy)		\$4,069 NI
W	517-6985	WHEEL, 12", 1/8 PL 389 Trench width 270mm (11"), 2 wheels each with 8 pads Overall Length-Height-Width: 726mm(28.6")- 901mm(35.5")- 292mm(11.5") FOR USE WITH: Pin Lock coupler 1/8YD (TAG)		\$3,208 NI
W	517-6986	WHEEL, 16", 1/8 PL 523 Trench width 400mm (16"), 3 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 941mm(37")- 399mm(15.7") FOR USE WITH: Pin Lock coupler 1/8YD (TAG)		\$3,701 NI
W	517-6987	WHEEL, 22", 1/8 PL 617 Trench width 550mm (22"), 4 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 941mm(37")- 553mm(21.8") FOR USE WITH: Pin Lock coupler 1/8YD (TAG)		\$4,069 NI

COMPACTOR PLATE CVP16

W	551-4956	COMPACTOR PLATE, CVP16 191 Has drill pattern SM and LG REQUIRES: Mounting bracket and connecting lines		\$5,826 NI
W	222-6443	BLADE, BACKFILL, CVP16 34 FOR USE WITH: CVP16 for back filling trenches		\$313 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 3 TONS AND BELOW 5 TONS (CONT.)

COMPACTOR PLATE CVP16 (Cont.)

W	265-7461	SWIVEL, CVP16, LG TO LG	132	\$1,339 NI
		FOR USE WITH: CVP16 and fitted between mounting bracket and CVP16		
W	532-9063	BRACKET, MHE 3T, 40MM, SM-LG	134	\$451 NI
		Mounting bracket, drill pattern SM + LG, incl.bolts + nuts + buck.pins		
		FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC		
W	154-2638	PINS, BUCKET, 40MM	11	\$97 NI
		Full set of bucket pins 40mm diameter		
W	203-0977	LINES, CVP16, MHE 3T, PO	15	\$319 NI
		FOR USE WITH: CVP16 and pin-on (No quick coupler)		
W	203-0981	LINES, CVP16, MHE 3T, QC	15	\$319 NI
		FOR USE WITH: CVP16 and machine with a quick coupler		

HAMMERS - B and H Series - for details see Hammer Section

WARNING:

Demolition tools can create a hazard from flying objects. Caterpillar recommends installing front guards on the cabs of the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers			H hammers		
	B2	B4	B6	H45	H55	H65
303C CR, 303E CR	+-	++	+-	+-	++	--
303.5D CR, 303.5E CR, 303.5E2	+-	++	+-	+-	++	--
304D CR, 304E CR, 304E2	--	++	+-	--	++	--
304.5E2	--	++	+-	--	++	--

++= Optimal +- = Acceptable -- = Not Allowed

For the correct part numbers, please see Hammer Section.

RIPPERS FOR PIN-ON

W	453-8570	RIPPER, 19", MHE 3T	99	\$861 NI
		26" (650mm) Tip Radius		
		FOR USE WITH: Pin-on or Pin grabber coupler		
		INCLUDES: one J200 long tooth tip		

THUMBS, HYDRAULIC FOR PIN-ON

W	452-2740	THUMB, HYDRAULIC, 3T	145	\$2,403 NI
		Teeth will mesh with buckets 18" to 36" wide		
		REQUIRES: Auxiliary lines group with two-way flow functionality		
		REQUIRES: Machine with thumb ready stick or separate mounting bracket		

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 5 TONS AND BELOW 7 TONS

QUICK COUPLERS

All quick couplers need to be fitted to the machine stick using the original bucket pins which come with a new machine. Otherwise order an extra set.

Bucket pins are 45mm in diameter.

Following MHE have the same linkage: 304C CR

305C CR/ 305D CR/ 305E CR/ 305E2

305.5D CR/ 305.5E CR/ 305.5E2/ 306E2

Next generation 306/ 306.5/ 306.6CR SB

W	444-7496	COUPLER, PG, MAN.D.LOCK, 5T 113 Mechanical Quick Coupler INCLUDES: 1 set of pins and hardware to attach 1 bucket REQUIRES: 282-2785 bucket pins for EACH ADDITIONAL bucket		\$2,028 NI
W	485-5301	COUPLER, PG, HYDR.D.LOCK, 5T 91 Hydraulic Quick Coupler INCLUDES: 1 set of bucket pins and hardware to attach one bucket REQUIRES: 282-2785 bucket pins for EACH ADDITIONAL bucket and hydraulic QC lines on machine.		\$3,576 NI
W	485-5304	COUPLER, PG, HYDR. TILT, 5T 247 Hydraulic Pin grabber type quick coupler with a dual lock and hydraulic tilt function 180 degrees left or right from center. INCLUDES: 1 set of pins and hardware to attach 1 bucket REQUIRES: Hydraulic QC Lines to operate the quick coupler and Primary 2 Way Aux or 2nd Aux Hydraulics for tilting. REQUIRES: 282-2785 Bucket Pins for EACH ADDITIONAL bucket NOTE: Not compatible with thumbs		\$8,646 NI
W	373-2375	KIT, HYDRAULIC QC LINES, 5 TON 25 FOR USE WITH: Hyd dual lock PG coupler and hyd CW05/CW10 coupler and for machines 304C, 305C, 305D and 305.5D		\$1,558 NI
W	384-5015	KIT, HYDRAULIC QC LINES, 5 TON 0 FOR USE WITH: Hyd dual lock PG coupler and hyd CW05/CW10 coupler and for machines 305E, 305E2, 305.5E, and 305.5E2		\$1,606 NI
W	282-2785	PINS, BUCKET, 45MM 11 INCLUDES: 2 bucket pins and hardware FOR USE WITH: 444-7496 and 485-5301 Quick Couplers		\$111 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 5 TONS AND BELOW 7 TONS (CONT.)

QUICK COUPLER: TILT ROTATOR SYSTEM TRS6

The TRS6 significantly reduces the time and need to constantly reposition the machine by providing a rotary and tilt connection between the base machine and the attachment. This revolutionary enhancement features 360 degrees of continuous rotation and 40 degrees of angular tilt. In addition to coupling attachments like buckets and forks, the TRS6 is also equipped to handle hydro-mechanical attachments like compactors, grapples, brooms and more. For installation instructions see media reference M0104954 Only available for Next Generation sales models. No backward compatibility to previous sales models

W	585-0421	TILT ROTATOR, TRS6, S40-S40 0 TRS6 with S40 interface machine side and S40 hydr. QC attachment side INCLUDES: Vibration function. 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 306 CR REQUIRES: Machine side: Quick Coupler lines, S40 quick Coupler and 1st AUX REQUIRES: 570-7210 KIT JOYSTICK TRS6, MHE 6T-10T and 585-0431 KIT, HARNESS, TRS6 and 585-0454 LINES, TRS6, MHE 5T-6T REQUIRES: Dedicated attachments with S40 hinges.		\$20,743 NI
W	585-0422	TILT ROTATOR, TRS6, S40-S40, G 0 TRS6 with S40 interface machine side and S40 hydr. QC attachment side INCLUDES: Grapple Attachment, vibration function. 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 306 CR REQUIRES: Machine side: Quick Coupler lines, S40 quick Coupler and 1st AUX REQUIRES: 570-7210 KIT JOYSTICK TRS6, MHE 6T-10T and 585-0431 KIT, HARNESS, TRS6 and 585-0454 LINES, TRS6, MHE 5T-6T REQUIRES: Dedicated attachments with S40 hinges.		\$25,681 NI
W	585-0423	TILT ROTATOR, TRS6,5T PO-S40,G 0 TRS6 with 5-6T Pin-on machine side & with S40 hydr QC attachment side INCLUDES: Grapple Attachment, vibration function. 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 306 CR REQUIRES: Machine side: 1st AUX REQUIRES: 570-7210 KIT JOYSTICK TRS6, MHE 6T-10T and 585-0431 KIT, HARNESS, TRS6 and 585-0454 LINES, TRS6, MHE 5T-6T REQUIRES: Dedicated attachments with S40 hinges.		\$26,549 NI
W	585-0424	TILT ROTATOR, TRS6, 5T, PO-S40 0 TRS6 with 5-6T Pin-on machine side & with S40 hydr QC attachment side INCLUDES: Vibration function. 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 306 CR REQUIRES: Machine side: 1st AUX REQUIRES: 570-7210 KIT JOYSTICK TRS6, MHE 6T-10T and 585-0431 KIT, HARNESS, TRS6 and 585-0454 LINES, TRS6, MHE 5T-6T REQUIRES: Dedicated attachments with S40 hinges.		\$21,611 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 5 TONS AND BELOW 7 TONS (CONT.)

QUICK COUPLER: TILT ROTATOR SYSTEM TRS6 (Cont.)

W	585-0425	TILT ROTATOR, TRS6, 5T, PO-PG 463 TRS6 with 5-6T Pin-on machine side and with a hydraulic Pin Grabber for 5-6T on attachment side. INCLUDES: Vibration function, 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 306 CR REQUIRES: Machine side: 1st AUX REQUIRES: 570-7210 KIT JOYSTICK TRS6, MHE 6T-10T and 585-0431 KIT, HARNESS, TRS6 and 585-0454 LINES, TRS6, MHE 5T-6T REQUIRES: Pin-on 5-6T linkage attachments		\$22,757 NI
W	585-0431	KIT, HARNESS, TRS6 9 1 piece harness, bracket & harness connector cap (stick QC operation) The harness connects the TRS6 ECM with the machine ECM.		\$632 NI
W	585-0454	LINES, TRS6, MHE 5-6T 19 Jumper lines connect TRS6 to auxilliary quick disconnect and includes pressure and return		\$257 NI
W	570-7210	KIT, TRS JOYSTICK, MHE 6T-10T 4 LH and RH joystick installed on existing joystick bases. The TRS will NOT work without these special joysticks.		\$2,354 NI

SSL to MHE ADAPTER / QUICK COUPLER

For the SSL to MHE Adapter / quick coupler please see section "SSL to MHE ADAPTER / QUICK COUPLER".
 This section also shows the allowed SSL attachments available.

BUCKETS FOR PIN-ON - Heavy Duty with pin-on teeth

NOTE: Optional side cutters are available. Part numbers are:
 LH Side Cutter 252-2611 / RH Side Cutter 252-2612
 Bolts 4F-3653 (3 per side cutter, total 6 per bucket)
 Nuts 4K-0367 (3 per side cutter, total 6 per bucket)
 (IRM): GET05-13 for further information and selection criteria.

W	464-9907	BUCKET-HD, 12", 2.1 FT3, 5T 156 Width 305mm (12"), Heaped Cap. 0.06M3 (2.1ft3), Incl 3 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,125 NI
W	464-9908	BUCKET-HD, 16", 2.7 FT3, 5T 174 Width 406mm (16"), Heaped Cap. 0.08M3 (2.7ft3), Incl 3 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,188 NI
W	464-9909	BUCKET-HD, 18", 3.1 FT3, 5T 194 Width 457mm (18"), Heaped Cap. 0.09M3 (3.1ft3), Incl 4 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,236 NI
W	464-9910	BUCKET-HD, 20", 3.6 FT3, 5T 207 Width 508mm (20"), Heaped Cap. 0.1M3 (3.6ft3), Incl 4 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,278 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 5 TONS AND BELOW 7 TONS (CONT.)

BUCKETS FOR PIN-ON - Heavy Duty with pin-on teeth (Cont.)

W	464-9911	BUCKET-HD, 24", 4.6 FT3, 5T 234 Width 610mm (24"), Heaped Cap. 0.13M3 (4.6ft3), Incl 4 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,375 NI
W	535-8405	BUCKET-HD, 24", 4.6 FT3, 5T 234 Width 610mm (24"), Heaped Cap. 0.13M3 (4.6ft3), Incl 5 x J200 DOES NOT MESH WITH THUMB FOR USE WITH: Pin-on, requires bucket pins		\$1,375 NI
W	464-9912	BUCKET-HD, 30", 6.1 FT3, 5T 280 Width 762mm (30"), Heaped Cap. 0.17M3 (6.1ft3), Incl 5 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,521 NI
W	464-9913	BUCKET-HD, 36", 7.8 FT3, 5T 320 Width 914mm (36"), Heaped Cap. 0.22M3 (7.8ft3), Incl 5 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,674 NI
W	537-7604	BUCKET-HD, 36", 7.8 FT3, 5T 320 Width 914mm (36"), Heaped Cap. 0.22M3 (7.8ft3), Incl 6 x J200 DOES NOT MESH WITH THUMB FOR USE WITH: Pin-on, requires bucket pins		\$1,674 NI

BUCKETS FOR PIN-ON - Heavy Duty/Large Capacity with pin-on teeth

W	464-9914	BUCKET-HDC, 12", 2.9 FT3, 5T 185 Width 305mm (12"), Heaped Cap. 0.08M3 (2.9ft3), Incl 3 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,208 NI
W	464-9915	BUCKET-HDC, 16", 3.7 FT3, 5T 204 Width 406mm (16"), Heaped Cap. 0.11M3 (3.7ft3), Incl 3 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,292 NI
W	464-9916	BUCKET-HDC, 18", 4.4 FT3, 5T 226 Width 457mm (18"), Heaped Cap. 0.12M3 (4.4ft3), Incl 4 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,354 NI
W	464-9917	BUCKET-HDC, 20", 5.1 FT3, 5T 241 Width 508mm (20"), Heaped Cap. 0.14M3 (5.1ft3), Incl 4 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,417 NI
W	464-9918	BUCKET-HDC, 24", 6.4 FT3, 5T 271 Width 619mm (24"), Heaped Cap. 0.18M3 (6.4ft3), Incl 4 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,528 NI
W	535-8407	BUCKET-HDC, 24", 6.4 FT3, 5T 271 Width 610mm (24"), Heaped Cap. 0.18M3 (6.4ft3), Incl 5 x J200 DOES NOT MESH WITH THUMB FOR USE WITH: Pin-on, requires bucket pins		\$1,535 NI
W	464-9919	BUCKET-HDC, 30", 8.5 FT3, 5T 322 Width 762mm (30"), Heaped Cap. 0.24M3 (8.5ft3), Incl 5 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,715 NI
W	464-9920	BUCKET-HDC, 36", 10.6 FT3, 5T 367 Width 914mm (36"), Heaped Cap. 0.3M3 (10.6ft3), Incl 5 x J200 FOR USE WITH: Pin-on, requires bucket pins		\$1,896 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 5 TONS AND BELOW 7 TONS (CONT.)

BUCKETS FOR PIN-ON - Heavy Duty/Large Capacity with pin-on teeth (Cont.)

W	537-7606	BUCKET-HDC, 36", 10.6 FT3, 5T 367 Width 914mm (36"), Heaped Cap. 0.30M3 (10.6ft3), Incl 6 x J200 DOES NOT MESH WITH THUMB FOR USE WITH: Pin-on, requires bucket pins		\$1,896 NI
---	----------	--	--	-------------------

BUCKETS FOR PIN-ON - Ditch Cleaning

W	279-4326	BUCKET-DC, 39", 5.9 FT3, 5T 258 Width 1000mm (39"), Heaped Cap. 0.166M3 (5.9ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: back grading edge and water holes		\$1,167 NI
W	279-4327	BUCKET-DC, 51", 7.8 FT3, 5T 260 Width 1300mm (51"), Heaped Cap. 0.221M3 (7.8ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: water holes		\$1,361 NI
W	279-4328	BUCKET-DC, 63", 10.1 FT3, 5T 306 Width 1600mm (63"), Heaped Cap. 0.287M3 (10.1ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: water holes		\$1,708 NI
W	274-9022	BUCKET-DCT, 63", 9.9 FT3, 5T 551 Width 1600mm (63"), Heaped Cap. 0.279M3 (9.9ft3) Tilt: 45 degrees each way from horizontal FOR USE WITH: Pin-on, requires bucket pins INCLUDES: back grading edge, connecting lines & water holes		\$4,292 NI

BUCKETS FOR PIN-ON - Grading/Cleaning

Designed for cleaning and grading.

W	415-5306	BUCKET-GRADING, 48", 15.2 FT3 389 Width: 1220mm (48"), Cap.: 0.430m3 (15.2 ft3), includes BOCE Tip Radius: 773mm (30.4") FOR USE WITH: Pin-on, requires bucket pins		\$4,306 NI
---	----------	---	--	-------------------

BUCKETS FOR PIN-ON - Grading/Mud

W	388-9664	BUCKET-GRADING, 47", 9.2FT3,5T 410 Width 1200mm (47"), Heaped Cap. 0.26M3 (9.2ft3) FOR USE WITH: Pin-on, includes bucket pins and BOCE		\$1,424 NI
W	388-9665	BKT GRADING 59" 0.34YD3 5T 490 Width 1500mm (59"), Heaped Cap. 0.33M3 (11.6ft3) FOR USE WITH: Pin-on, includes bucket pins and BOCE		\$1,778 NI

BUCKETS FOR TRS6

These NORDIC style buckets are special designed to be used with the TRS6.

BUCKETS FOR TRS6: Digging buckets for S40

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-------------------------------	--------------------	-------------------------

MHE - FROM 5 TONS AND BELOW 7 TONS (CONT.)***BUCKETS FOR TRS6 (Cont.)*****BUCKETS FOR TRS6: Grading buckets for S40****BUCKETS FOR TRS6: Grading buckets for Dual Lock Quick Coupler****BUCKETS FOR TRS6: Trenching buckets for S40**

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 5 TONS AND BELOW 7 TONS (CONT.)

AUGERS

Nomenclature change: A41 is replacement for A19B, NO technical changes
 A41 stands for Auger with a Torque= 4100Nm (A41 = A19B)
 Nomenclature change: A68 is replacement for A26B, NO technical changes
 A68 stands for Auger with a Torque= 6826Nm (A68 = A26B)
 For auger bits, please see section "AUGER BITS"

W	275-1000	AUGER, A41, MHE 5T, 45MM	207	\$2,951 NI
		A41 (old A19B) has a torque of 4100Nm Includes single reduction planetary drive unit, hydraulic lines with quick disconnects, mounting bracket, hardware and 2" (50mm) HEX output shaft. FOR USE WITH: pin-on REQUIRES: 1 set of bucket pins REQUIRES: 2 way proportional aux lines on carrier machine		
W	230-5578	AUGER, DRIVE, A41	187	\$2,708 NI
		A41 (old A19B) has a torque of 4100Nm REQUIRES: Bracket, connecting lines and auger flight		
W	275-1001	AUGER, A68, MHE 5T, 45MM	234	\$4,743 NI
		A68 (old A26B) has a torque of 6826Nm INCLUDES: Double Planetary reduction (34:1) drive unit, hydraulic lines with QDS, mounting bracket, hardware and 50mm HEX output shaft. FOR USE WITH: pin-on RECOMMENDED: Add case drain for severe duty applications when working below minus 7 Degree C (20 Degree F). Installation time: 4 hrs, Instructions M0113305 (NO kit available). REQUIRES: 1 set of bucket pins REQUIRES: 2 way proportional aux lines on carrier machine		
W	225-8809	AUGER, DRIVE, A68	216	\$4,139 NI
		A68 (old A26B) has a torque of 6826Nm RECOMMENDED: Add case drain for severe duty applications when working below minus 7 Degree C (20 Degree F). Installation time: 4 hrs, Instructions M0113305 (NO kit available). REQUIRES: Bracket, connecting lines and auger flight		
W	275-0999	BRACKET, A41-A68, MHE 5T, 45MM	47	\$368 NI
		FOR USE WITH: A41 + A68 and old A19B + A26B		

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 5 TONS AND BELOW 7 TONS (CONT.)

COMPACTION WHEELS FOR PIN-ON

To compact soil in trenches by rolling the wheels over the soil and pushing it down using the boom and stock of the machine.

W	517-6979	WHEEL, 12", 5/6T 374 Trench width 270mm (11"), 2 wheels each with 8 pads Overall Length-Height-Width: 726mm(28.6")- 829mm(32.6")- 343mm(13.5") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$3,208 NI
W	517-6980	WHEEL, 16", 5/6T 508 Trench width 400mm (16"), 3 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 868mm(34.2")- 399mm(15.7") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$3,701 NI
W	517-6981	WHEEL, 22", 5/6T 601 Trench width 550mm (22"), 4 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 868mm(34.2")- 553mm(21.8") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$4,069 NI

COMPACTION WHEELS for PIN LOCK COUPLERS

W	517-6982	WHEEL, 12", 1/8 PL 395 Trench width 270mm (11"), 2 wheels each with 8 pads Overall Length-Height-Width: 726mm(28.6")- 921mm(36.3")- 292mm(11.5") FOR USE WITH: Pin Lock coupler 1/8YD (Wain Roy)		\$3,208 NI
W	517-6983	WHEEL, 16", 1/8 PL 528 Trench width 400mm (16"), 3 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 961mm(37.8")- 399mm(15.7") FOR USE WITH: Pin Lock coupler 1/8YD (Wain Roy)		\$3,701 NI
W	517-6984	WHEEL, 22", 1/8 PL 622 Trench width 550mm (22"), 4 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 961mm(37.8")- 553mm(21.8") FOR USE WITH: Pin Lock coupler 1/8YD (Wain Roy)		\$4,069 NI
W	517-6985	WHEEL, 12", 1/8 PL 389 Trench width 270mm (11"), 2 wheels each with 8 pads Overall Length-Height-Width: 726mm(28.6")- 901mm(35.5")- 292mm(11.5") FOR USE WITH: Pin Lock coupler 1/8YD (TAG)		\$3,208 NI
W	517-6986	WHEEL, 16", 1/8 PL 523 Trench width 400mm (16"), 3 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 941mm(37")- 399mm(15.7") FOR USE WITH: Pin Lock coupler 1/8YD (TAG)		\$3,701 NI
W	517-6987	WHEEL, 22", 1/8 PL 617 Trench width 550mm (22"), 4 wheels each with 8 pads Overall Length-Height-Width: 693mm(27.3")- 941mm(37")- 553mm(21.8") FOR USE WITH: Pin Lock coupler 1/8YD (TAG)		\$4,069 NI

COMPACTOR PLATE CVP16

W	551-4956	COMPACTOR PLATE, CVP16 191 Has drill pattern SM and LG REQUIRES: Mounting bracket and connecting lines		\$5,826 NI
W	222-6443	BLADE, BACKFILL, CVP16 34 FOR USE WITH: CVP16 for back filling trenches		\$313 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 5 TONS AND BELOW 7 TONS (CONT.)

COMPACTOR PLATE CVP16 (Cont.)

W	265-7461	SWIVEL, CVP16, LG TO LG	132	\$1,339 NI
		FOR USE WITH: CVP16 and fitted between mounting bracket and CVP16		
W	569-5414	BRACKET, MHE 5T 45MM, SM-LG	127	\$451 NI
		Mounting bracket, drill pattern SM + LG, incl.bolts + nuts + buck.pins		
		FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC		
W	282-2785	PINS, BUCKET, 45MM	11	\$111 NI
		Full set of bucket pins 45mm diameter		
W	203-0983	LINES, CVP16, MHE 5T	18	\$319 NI

FLAIL MOWER

Hydraulic mower with swinging teeth to cut and break down material for use in agriculture, landmanagement and landscaping to control overgrowth, maintain hedgdes. Caterpillar recommends a machine configuration with appropriate guarding for maximum protection.

W	504-6010	FLAIL MOWER, HMF110	830	\$13,264 NI
		Overall / Working width: 1187mm (47") / 1000mm (40")		
		Overall Height: 738mm (29"), Length: 853mm (34")		
		Maximum Cutting diameter: 50-75mm (2"-3")		
		Hydraulic Flow range: 50-80 lpm (13-21 gpm)		
		Hydraulic Pressure range: 150-250 bar (2175-3626 psi)		
		INCLUDES: V-Belt Drive drum with 16 hammer teeth, axial piston motor, mounting bracket and pins, connecting lines and quick disconnects		
		FOR USE WITH: only 305E2 and 305.5E2		
		REQUIRES: Case drain kit 504-6159		
W	504-6159	KIT, CASE DRAIN, 305E2 + 6T NG	10	\$215 NI

Available via parts/Antares:
 504-6062 Hammer tooth
 504-6163 Y Blade Tooth

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 5 TONS AND BELOW 7 TONS (CONT.)

HAMMERS - B and H series - for details see Hammer Section

WARNING:

Demolition tools can create a hazard from flying objects. Caterpillar recommends installing front guards on the cabs of the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers	H hammers
305C CR, 305D CR,	B4 +- B6 ++	H55E ++ H65E ++
305E CR, 305E2	B4 +- B6 ++	H55E ++ H65E ++
305.5D CR, 305.5E CR, 305.5E2	B4 +- B6 ++	H55E ++ H65E ++
306E, 306E2	B4 +- B6 ++	H55E ++ H65E ++

++= Optimal += Acceptable --= Not Allowed

For the correct part numbers, please see Hammer Section.

RIPPERS FOR PIN-ON

W	453-8571	RIPPER, 27", MHE 5T 134	\$1,021 NI
		32" (810mm) Tip Radius	
		FOR USE WITH: Pin-on or Pin grabber coupler	
		INCLUDES: one J200 long tooth tip	

SCRAP SHEAR: BOOM MOUNTED

360 degrees rotatable tool. Speed valve for faster jaw closing. Removable and reversible cutters. Easy cutting-tolerance adjustment To have an operational demolition tool you need:

- 1) Double or Combined function (Open/Close)
- 2) Low flow Double Function circuit (rotate)
- 3) High Pressure boom and stick auxiliary lines (Open/Close)
- 4) Medium pressure boom and stick lines (Rotate)
- 5) Hand control or foot valve to operate open/close, rotate functions

WARNING:

This product can create a hazard from flying objects. Caterpillar recommends installing front guarding on the cabs of the excavators. Failure to do so can lead to injury or death.

W	583-8100	SHEAR, HYDRAULIC, S308 1,213	\$27,764 NI
		REQUIRES: Mounting bracket and connecting lines	
W	283-4187	BRACKET, S308, 305D/E BOOM 95	\$3,326 NI
		FOR USE WITH: 305D, 305E CR boom mounted	
W	449-9083	BRACKET, S308, 305.5E BOOM 92	\$3,326 NI
		FOR USE WITH: 305.5E CR boom mounted	
W	231-7108	LINES, S308, MHE 5-6T 50	\$347 NI
		FOR USE WITH: 304D CR, 304E CR, 305D, 305E CR, 305.5E CR	

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-------------------------------	--------------------	-------------------------

MHE - FROM 5 TONS AND BELOW 7 TONS (CONT.)

THUMBS, HYDRAULIC FOR PIN-ON

W	575-0496	THUMB, HYDRAULIC, 5-6T 206 Teeth will mesh with buckets 450mm (18") to 915mm (36") wide REQUIRES: Auxiliary lines group with two-way flow functionality REQUIRES: Machine with thumb ready stick or separate mounting bracket		\$2,403 NI
---	----------	---	--	-------------------

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 7 TONS AND BELOW 10 TONS

QUICK COUPLERS

All quick couplers need to be fitted to the machine stick using the original bucket pins which come with a new machine. Otherwise order an extra set.

Bucket pins are 50mm in diameter.

Following MHE have the same linkage: 307D / 307E / 307E2

Next generation 307.5

308D / 308E CR/ 308E2

Next generation 308 / 309CR

W	444-7498	COUPLER, PG, MAN.D.LOCK, 8T 196 Mechanical pin grabber type quick coupler with a dual lock. INCLUDES: 1 set of bucket pins and hardware to attach 1 bucket REQUIRES: 308-0324 Bucket Pins for EACH ADDITIONAL bucket		\$2,354 NI
W	485-5302	COUPLER, PG, HYDR.D.LOCK, 8T 206 Hydraulic pin grabber type quick coupler with a dual lock. FOR USE WITH: 308E INCLUDES: 1 set of bucket pins and hardware to attach 1 bucket and connecting lines. REQUIRES: 308-0324 bucket pins for EACH ADDITIONAL bucket and hydraulic QC lines on machine.		\$5,674
W	485-5305	COUPLER, PG, HYDR. TILT, 8T 399 Hydraulic Pin grabber type quick coupler with a dual lock and hydraulic tilt function 180 degrees left or right from center. INCLUDES: 1 set of pins and hardware to attach 1 bucket REQUIRES: Hydraulic QC Lines to operate the quick coupler and Primary 2 Way Aux or 2nd Aux Hydraulics for tilting. REQUIRES: for 308E with 2nd Aux 2x 383-8492 Adjust. Relief Valve REQUIRES: for 308E2 with 2nd Aux 2x 423-4559 Fixed Relief Valve REQUIRES: for 308E2 with serial number below FJX02625,458-6610 REQUIRES: 308-0324 Bucket Pins for EACH ADDITIONAL bucket NOTE: Not compatible with thumbs		\$12,250 NI
W	373-4405	KIT, HYDRAULIC QC LINES 40 FOR USE WITH: Hyd dual lock PG coupler and hyd CW10 coupler and for machines 308E, 308E2		\$1,897 NI
W	561-8200	KIT, CTRL, QUICK CPLR, STD STK 0 Quick Coupler control kit for hydraulic QCs Dual lock PG, CW10 or S50 FOR USE WITH: Next Generation 308 and 309		\$2,196 NI
W	561-8201	KIT, CTRL, QUICK CPLR, LNG STK 0 Quick Coupler control kit for hydraulic QCs Dual lock PG, CW10 or S50 FOR USE WITH: Next Generation 308 and 309		\$2,196 NI
W	308-0324	PINS, BUCKET, 50MM 25 INCLUDES: 2 bucket pins and hardware FOR USE WITH: 444-7498 & 485-5302 Couplers		\$125 NI
W	485-0314	COUPLER, PIN LOCK, 8T 176 Manual dedicated quick coupler for 1/4 yard pin lock attachments. REQUIRES: Buckets with dedicated hinges for Pin Lock.		\$1,528 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 7 TONS AND BELOW 10 TONS (CONT.)

COUPLER: Cat Symmetrical hydraulic quick coupler S50

W	576-1200	COUPLER, S50, HYD, 8T, HOOK 197 Dedicated hydraulic quick coupler S50. Requires dedicated attachments with S50 hinges. FOR USE WITH: Next Gen 307.5, 308CR and 309CR REQUIRES: Quick Coupler lines on the machine + 576-1164 Lines, S50, 8T		\$4,215 NI
W	576-1164	LINES, S50, 8T 6 FOR USE WITH: S50 Quick Coupler on Next Gen 307.5, 308CR and 309CR REQUIRES: Quick coupler lines on the machine		\$389 NI
W	576-1201	COUPLER, S50, HYD, 8T,LCS,HOOK 209 Dedicated hydraulic quick coupler S50. Requires dedicated attachments with S50 hinges. INCLUDES: Hydraulic Locking Control System which indicates if the quick coupler is safely locked/coupled or not. FOR USE WITH: Next Gen. 307.5, 308CR and 309CR REQUIRES: quick coupler lines on the machine. You might need to flash parts of the machine software, depending on the version. REQUIRES: 577-1565 KIT, HARNESS, TRS8 to provide an electrical harness on the machine to operate the HLCS. REQUIRES: 576-1164 LINES, S50, 8T		\$5,007 NI
W	577-1565	KIT, HARNESS, TRS8 18 3 piece harness, bracket & harness connector cap (stick QC operation) The harness connects the TRS8 ECM or S50 with the machine ECM.		\$778 NI

COUPLER: TILT ROTATOR SYSTEM TRS8

The TRS8 significantly reduces the time and need to constantly reposition the machine by providing a rotary and tilt connection between the base machine and the attachment. This revolutionary enhancement features 360 degrees of continuous rotation and 40 degrees of angular tilt. In addition to coupling attachments like buckets and forks, the TRS8 is also equipped to handle hydro-mechanical attachments like compactors, grapples, brooms and more.

For installation instructions see media reference M0104954

Only available for Next Generation sales models. No backward compatibility to previous sales models

W	570-7120	TILT ROTATOR, TRS8, S50-S50, G 683 TRS8 with S50 interface machine side and S50 hydr. QC attachment side INCLUDES: Grapple Attachment, vibration function. 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 307.5, 308CR, 309CR and 310 REQUIRES: Machine side: Quick Coupler lines and S50 quick Coupler, Case drain: either 2nd AUX (this comes with case drain) or 1st AUX & Case Drain Kit 504-6156 (Not possible for 310) REQUIRES: 570-7210 KIT JOYSTICK TRS8 and 577-1565 KIT, HARNESS, TRS8 and 577-1587 LINES, TRS8, MHE, 8T-10T REQUIRES: Dedicated attachments with S50 hinges.		\$31,083 NI
---	----------	--	--	--------------------

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 7 TONS AND BELOW 10 TONS (CONT.)

COUPLER: TILT ROTATOR SYSTEM TRS8 (Cont.)

W	570-7121	TILT ROTATOR, TRS8, S50-S50 827 TRS8 with S50 interface machine side and S50 hydr. QC attachment side INCLUDES: Vibration function. 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 307.5, 308CR, 309CR and 310 REQUIRES: Machine side: Quick Coupler lines and S50 quick Coupler, Case drain: either 2nd AUX (this comes with case drain) or 1st AUX & Case Drain Kit 504-6156 (Not possible for 310) REQUIRES: 570-7210 KIT JOYSTICK TRS8 and 577-1565 KIT, HARNESS, TRS8 and 577-1587 LINES, TRS8, MHE, 8T-10T REQUIRES: Dedicated attachments with S50 hinges.		\$25,813 NI
W	570-7124	TILT ROTATOR, TRS8, 8T, PO-S50 683 TRS8 with 8T Pin-on machine side and S50 hydr. QC attachment side INCLUDES: Vibration function. 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 307.5, 308CR, 309CR and 310 REQUIRES: Machine side: Case drain: either 2nd AUX (this comes with case drain) or 1st AUX & Case Drain Kit 504-6156 (Not possible for 310) REQUIRES: 570-7210 KIT JOYSTICK TRS8 and 577-1565 KIT, HARNESS, TRS8 and 577-1587 LINES, TRS8, MHE, 8T-10T REQUIRES: Dedicated attachments with S50 hinges.		\$27,313 NI
W	570-7122	TILT ROTATOR, TRS8, 8T, PO-PG 683 TRS8 with 8T Pin-on machine side and with a hydraulic Pin Grabber for 8T on attachment side. INCLUDES: Vibration function. 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 307.5, 308CR, 309CR REQUIRES: Machine side: 1st AUX & Case Drain Kit 504-6156, or 2nd AUX REQUIRES: 570-7210 KIT JOYSTICK TRS8 and 577-1565 KIT, HARNESS, TRS8 and 577-1587 LINES, TRS8, MHE, 8T-10T REQUIRES: Pin-on 7T / 8T linkage attachments		\$30,938 NI
W	570-7210	KIT, TRS JOYSTICK, MHE 6T-10T 4 LH and RH joystick installed on existing joystick bases. The TRS8 will NOT work without these special joysticks.		\$2,354 NI
W	577-1565	KIT, HARNESS, TRS8 18 3 piece harness, bracket & harness connector cap (stick QC operation) The harness connects the TRS8 ECM or S50 with the machine ECM.		\$778 NI
W	577-1587	LINES, TRS8, MHE 8T-10T 24 Jumper lines connect TRS8 to auxilliary quick disconnect and includes pressure, return and case drain hoses.		\$389 NI

SSL to MHE ADAPTER / QUICK COUPLER

For the SSL to MHE Adapter / quick coupler please see section "SSL to MHE ADAPTER / QUICK COUPLER".
 This section also shows the allowed SSL attachments available.

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 7 TONS AND BELOW 10 TONS (CONT.)

BUCKETS FOR PIN-ON - Heavy Duty/Heavy Duty Rock with pin-on teeth

Bucket pins are 50mm in diameter. Following MHE have the same linkage:

307D / 307E / 307E2

Next generation 307.5

308D / 308E CR/ 308E2

Next generation 308 / 309

ACCEPTS: Sidecutters

Available through Parts only:

153-1646 RH Sidecutter (Qty 1)

153-1647 LH Sidecutter (Qty 1)

8T-4131 Nut (Qty 6)

8T-6430 Bolt (Qty 6)

W	305-6813	BUCKET-HD, 13", 3.5 FT3, 7T	299	\$1,847 NI
		Width 330mm (13"), Heaped Cap. 0.1M3 (3.5ft3), Incl 3 x J225		
		FOR USE WITH: Pin-on, includes bucket pins		
W	295-5951	BUCKET-HD, 18", 5.4 FT3, 7T	333	\$2,007 NI
		Width 457mm (18"), Heaped Cap. 0.15M3 (5.4ft3), Incl 4 x J225		
		FOR USE WITH: Pin-on, requires bucket pins		
W	295-5952	BUCKET-HD, 24", 8.1 FT3, 7T	392	\$2,229 NI
		Width 610mm (24"), Heaped Cap. 0.23M3 (8.1ft3), Incl 4 x J225		
		FOR USE WITH: Pin-on, requires bucket pins		
W	295-5953	BUCKET-HD, 30", 10.9 FT3, 7T	455	\$2,451 NI
		Width 762mm (30"), Heaped Cap. 0.31M3 (10.9ft3), Incl 5 x J225		
		FOR USE WITH: Pin-on, requires bucket pins		
W	295-5954	BUCKET-HD, 36", 13.8 FT3, 7T	507	\$2,694 NI
		Width 914mm (36"), Heaped Cap. 0.39M3 (13.8ft3), Incl 5 x J225		
		FOR USE WITH: Pin-on, requires bucket pins		
W	295-5970	BUCKET-HDR, 24", 8.1 FT3, 7T	427	\$2,590 NI
		Width 610mm (24"), Heaped Cap. 0.23M3 (8.1ft3), Incl 4 x J225		
		FOR USE WITH: Pin-on, requires bucket pins		
W	295-5971	BUCKET-HDR, 30", 10.9 FT3, 7T	490	\$2,813 NI
		Width 762mm (30"), Heaped Cap. 0.31M3 (10.9ft3), Incl 5 x J225		
		FOR USE WITH: Pin-on, requires bucket pins		

BUCKETS FOR PIN-ON - Ditch Cleaning

W	306-5664	BUCKET-DC, 48", 11.6 FT3, 7T	476	\$2,910 NI
		Width 1219mm (48"), Heaped Cap. 0.33M3 (11.6ft3)		
		FOR USE WITH: Pin-on, requires bucket pins		
		INCLUDES: Water holes		
		NOT INCLUDED: BOCE 311-6221 + 4x 8T4778 NUT + 4x 159-2953 SCREW		
W	306-5662	BUCKET-DC, 54", 13.2 FT3, 7T	516	\$3,139 NI
		Width 1372mm (54"), Heaped Cap. 0.37M3 (13.2ft3)		
		FOR USE WITH: Pin-on, requires bucket pins		
		INCLUDES: Water holes		
		NOT INCLUDED: BOCE 311-9238 + 5x 8T4778 NUT + 5x 159-2953 SCREW		

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 7 TONS AND BELOW 10 TONS (CONT.)

BUCKETS FOR PIN-ON - Ditch Cleaning (Cont.)

W	306-5660	BUCKET-DC, 60", 14.9 FT3, 7T	556	\$3,375 NI
		Width 1524mm (60"), Heaped Cap. 0.42M3 (14.9ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: Water holes NOT INCLUDED: BOCE 311-9239 + 6x 8T4778 NUT + 6x 159-2953 SCREW		

BUCKETS FOR PIN-ON - Grading/Mud

Designed for grading with higher capacity and suited to carry buckets

W	388-9666	BUCKET-GRADING, 47", 14.6FT3, 7T	651	\$3,354 NI
		Width 1200mm (47"), Heaped Cap. 0.41M3 (14.6ft3) FOR USE WITH: Pin-on, includes bucket pins and BOCE		
W	388-9667	BUCKET-GRADING, 59", 18.4FT3, 7T	761	\$3,868 NI
		Width 1500mm (59"), Heaped Cap. 0.52M3 (18.4ft3) FOR USE WITH: Pin-on, includes bucket pins and BOCE		

BUCKETS FOR TRS8

These NORDIC style buckets are special designed to be used with the TRS8. They meet the Nordic soil conditions.

- BUCKETS FOR TRS8: Digging buckets for S45 or S50**
- BUCKETS FOR TRS8: Grading buckets for S45 or S50**
- BUCKETS FOR TRS8: Grading buckets for Dual Lock Quick Coupler**
- BUCKETS FOR TRS8: Trenching buckets for S40 or S50**

BUCKETS FOR PIN LOCK QUICK COUPLER

These buckets come with pin-on teeth, but do not take side cutters.

W	247-1947	BUCKET-HD, 12", 3.4 FT3, PL	249	\$1,563 NI
		Width 305mm (12"), Heaped Cap. 0.096M3 (3.4ft3), Incl 3 x tooth tips FOR USE WITH: Pin Lock Quick Coupler		
W	247-1948	BUCKET-HD, 16", 4.3 FT3, PL	288	\$1,632 NI
		Width 406mm (16"), Heaped Cap. 0.122M3 (4.3ft3), Incl 3 x tooth tips FOR USE WITH: Pin Lock Quick Coupler		
W	247-1949	BUCKET-HD, 18", 4.9 FT3, PL	304	\$1,674 NI
		Width 457mm (18"), Heaped Cap. 0.139M3 (4.9ft3), Incl 4 x tooth tips FOR USE WITH: Pin Lock Quick Coupler		
W	247-1950	BUCKET-HD, 24", 7.3 FT3, PL	370	\$1,819 NI
		Width 610mm (24"), Heaped Cap. 0.207M3 (7.3ft3), Incl 5 x tooth tips FOR USE WITH: Pin Lock Quick Coupler		

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 7 TONS AND BELOW 10 TONS (CONT.)

BUCKETS FOR PIN LOCK QUICK COUPLER (Cont.)

W	247-1951	BUCKET-HD, 30", 9.7 FT3, PL 428 Width 762mm (30"), Heaped Cap. 0.275M3 (9.7ft3), Incl 5 x tooth tips FOR USE WITH: Pin Lock Quick Coupler		\$1,965 NI
W	247-1952	BUCKET-HD, 36", 12.2 FT3, PL 494 Width 914mm (36"), Heaped Cap. 0.345M3 (12.2ft3), Incl 6 x tooth tips FOR USE WITH: Pin Lock Quick Coupler		\$2,118 NI
W	247-1954	BUCKET-HC, 16", 5.6 FT3, PL 327 Width 406mm (16"), Heaped Cap. 0.159M3 (5.6ft3), Incl 3 x tooth tips FOR USE WITH: Pin Lock Quick Coupler		\$1,701 NI
W	247-1955	BUCKET-HC, 18", 6.5 FT3, PL 346 Width 457mm (18"), Heaped Cap. 0.184M3 (6.5ft3), Incl 4 x tooth tips FOR USE WITH: Pin Lock Quick Coupler		\$1,757 NI
W	247-1956	BUCKET-HC, 24", 9.6 FT3, PL 414 Width 610mm (24"), Heaped Cap. 0.272M3 (9.6ft3), Incl 5 x tooth tips FOR USE WITH: Pin Lock Quick Coupler		\$1,931 NI
W	247-1957	BUCKET-HC, 30", 12.9 FT3, PL 475 Width 762mm (30"), Heaped Cap. 0.365M3 (12.9ft3), Incl 5 x tooth tips FOR USE WITH: Pin Lock Quick Coupler		\$2,738 NI
W	247-1958	BUCKET-HC, 36", 16.2 FT3, PL 543 Width 914mm (36"), Heaped Cap. 0.459M3 (16.2ft3), Incl 6 x tooth tips FOR USE WITH: Pin Lock Quick Coupler		\$2,299 NI

AUGERS

Nomenclature change: A68 is replacement for A26B, NO technical changes
 A68 stands for Auger with a Torque= 6826Nm (A68 = A26B)
 For auger bits, please see section "AUGER BITS"

W	313-1460	AUGER, A68, MHE 8T, 50MM 324 A68 (old A26B) has a torque of 6826Nm INCLUDES: Double Planetary reduction (34:1) drive unit, hydraulic lines with QDS, mounting bracket, hardware and 50mm HEX output shaft. FOR USE WITH: pin-on RECOMMENDED: Add case drain for severe duty applications when working below minus 7 Degree C (20 Degree F). Installation time: 4 hrs, Instructions M0113305 (NO kit available). REQUIRES: 1 set of bucket pins REQUIRES: 2 way proportional aux lines on carrier machine		\$4,743 NI
W	225-8809	AUGER, DRIVE, A68 216 A68 (old A26B) has a torque of 6826Nm RECOMMENDED: Add case drain for severe duty applications when working below minus 7 Degree C (20 Degree F). Installation time: 4 hrs, Instructions M0113305 (NO kit available). REQUIRES: Bracket, connecting lines and auger flight		\$4,139 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 7 TONS AND BELOW 10 TONS (CONT.)

COMPACTION WHEELS FOR PIN-ON

To compact soil in trenches by rolling the wheels over the soil and pushing it down using the boom and stock of the machine.

W	517-6988	WHEEL, 12", 7/8T 915 Trench width 310mm (12"), 2 wheels each with 9 pads Overall Length-Height-Width: 998mm(39.3")- 1152mm(45.4")- 338mm(13.3") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$4,632 NI
W	517-6989	WHEEL, 18", 7/8T 1,227 Trench width 450mm (18"), 3 wheels each with 9 pads Overall Length-Height-Width: 997mm(39.3")- 1165mm(45.9")- 449mm(17.7") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$5,819 NI
W	517-6990	WHEEL, 24", 7/8T 1,268 Trench width 560mm (22"), 3 wheels each with 9 pads Overall Length-Height-Width: 997mm(39.3")- 1165mm(45.9")- 556mm(21.9") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$6,056 NI
W	517-6991	WHEEL, 36", 7/8T 1,945 Trench width 880mm (35"), 5 wheels each with 9 pads Overall Length-Height-Width: 1073mm(42.2")- 1164mm(45.8")- 884mm(34.8") FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		\$7,014 NI

COMPACTION WHEELS FOR PIN LOCK COUPLERS

W	517-6995	WHEEL, 12", 1/4 PL 836 Trench width 290mm (11"), 2 wheels each with 9 pads Overall Length-Height-Width: 995mm(39.2")- 1207mm(47.5")- 312mm(12.3") FOR USE WITH: Pin Lock coupler 1/4YD (Wain Roy)		\$4,271 NI
W	517-6996	WHEEL, 18", 1/4 PL 1,074 Trench width 440mm (17"), 3 wheels each with 9 pads Overall Length-Height-Width: 991mm(39")- 1181mm(46.5")- 439mm(17.3") FOR USE WITH: Pin Lock coupler 1/4YD (Wain Roy)		\$4,986 NI
W	517-6997	WHEEL, 24", 1/4 PL 1,142 Trench width 560mm (22"), 3 wheels each with 9 pads Overall Length-Height-Width: 991mm(39")- 1179mm(46.4")- 559mm(22") FOR USE WITH: Pin Lock coupler 1/4YD (Wain Roy)		\$5,347 NI

COMPACTOR PLATE CVP40

W	551-4957	COMPACTOR PLATE, CVP40 411 Has drill pattern XL REQUIRES: Mounting bracket and connecting lines		\$8,222 NI
W	211-8200	BLADE, BACKFILL, CVP40 113 FOR USE WITH: CVP40 for back filling trenches.		\$660 NI
W	264-5907	SWIVEL, CVP40, XL TO XL 269 FOR USE WITH: CVP40 for back filling trenches.		\$1,768 NI
W	564-9840	BRACKET, MHE 8T, 50MM, XL 186 Mounting bracket, drill pattern XL, incl. nuts+bolts & bucket pin FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC		\$660 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 7 TONS AND BELOW 10 TONS (CONT.)

COMPACTOR PLATE CVP40 (Cont.)

W	416-8031	BRACKET, 1/4YD PL, XL 170 Mounting bracket, incl.bolts + nuts, excl. lines FOR USE WITH: 1/4 yard pin lock quick coupler		\$694 NI
W	564-2732	BRACKET, 1/2YD PL, XL 233 Mounting bracket, incl.bolts + nuts, excl. lines FOR USE WITH: 1/2 yard pin lock quick coupler.		\$1,528 NI
W	308-0324	PINS, BUCKET, 50MM 25 Full set of bucket pins 50mm diameter		\$125 NI
W	490-0015	LINES, CVP40, MHE 8T/10T 29 FOR USE WITH: Pin-On/QC and NO bucket thumb		\$417 NI
W	325-3832	LINES,CVP40, MHE 8T/10T, THUMB 57 FOR USE WITH: Pin-On/QC and WITH bucket thumb		\$972 NI

FLAIL MOWERS FOR PIN-ON

Hydraulic mower with swinging teeth to cut and break down material for use in agriculture, landmanagement and landscaping to control overgrowth, maintain hedgdes. Caterpillar recommends a machine configuration with appropriate guarding for maximum protection.

W	504-6011	FLAIL MOWER, HMF210 843 Overall / Working width: 1187mm (47") / 1000mm (40") Overall Height: 762mm (30"), Length: 853mm (34") Maximum Cutting diameter: 50-75mm (2"-3") Hydraulic Flow range: 70-130 lpm (18-34 gpm) Hydraulic Pressure range: 150-250 bar (2175-3626 psi) INCLUDES: V-Belt Drive drum with 16 hammer teeth, axial piston motor, mounting bracket and pins, connecting lines and quick disconnects FOR USE WITH: 308E2, Next generation 307.5, 308CR, 309CR, 310 REQUIRES: Case drain kit 504-6156 REQUIRES: For 310 ONLY 581-7634 BRACKET, FLAIL, MHE 10T NOTE: the set-up is for a 308E2. When used with Next Gen 307.5, 308CR, 309CR and 310 the QDs need to be converted per instruction M0107554		\$13,264 NI
W	504-6156	KIT, CASE DRAIN, 308E2 + 8T NG 14 FOR USE WITH: 308E2, Next Gen. 307.5, 308CR, 310 with 1st Aux only. Next Gen 307.5, 308CR, 310 with 2nd Aux has case drain included. Next Gen 309 always includes 1st Aux + 2nd Aux + case drain.		\$215 NI

GRAPPLE, CONTRACTOR FOR PIN-ON

W	583-5312	GRAPPLE, MECHANICAL, G108 820 Mechanical (Power / Contractors) grapple with adjustable link. FOR USE WITH: Pin-On or with Pin Grabber Dual Lock QC. REQUIRES: Thumb ready stick		\$6,250 NI
---	----------	---	--	------------

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 7 TONS AND BELOW 10 TONS (CONT.)

HAMMERS - B and H series - for details see Hammer Section

WARNING:

Demolition tools can create a hazard from flying objects. Caterpillar recommends installing front guards on the cabs of the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers			H hammers (incl. E)		
	B6	B8	B9	H65	H80	H95
307D, 307E, 307E2	+-	++	++	+-	++	++
308D, 308E, 308E2 CR	+-	++	++	+-	++	++
Next Generation						
307.5, 308, 309CR	+-	++	++	+-	++	++

++= Optimal += Acceptable --= Not Allowed

For the correct part numbers, please see Hammer Section.

MULCHERS FOR PIN-ON

Hydraulic mulcher to mulch trees and undergrowth up to 120mm (5") in diameter, for use in landscaping, agriculture and landmanagement. Caterpillar recommends a machine configuration with appropriate guarding for maximum protection.

<p>W 504-6012 MULCHER, HM208</p> <p>Overall / Working width: 1026mm (40") / 818mm (32") Overall Height: 1065mm (42"), Length: 714mm (28") Maximum Cutting diameter: 120mm (5") Hydraulic Flow range: 70-130 lpm (18-34 gpm) Hydraulic Pressure range: 150-250 bar (2175-3626 psi) INCLUDES: V-Belt Drive drum with 15 reversible chisel teeth, dual speed axial piston motor, mounting bracket and pins, connecting lines with quick disconnects. FOR USE WITH: 308E2, Next generation 307.5, 308CR, 309CR, 310 REQUIRES: Case drain kit 504-6156 REQUIRES: For 310 ONLY 581-7636 BRACKET, MULCHER, MHE 10T NOTE: the set-up is for a 308E2. When used with Next Gen 307.5, 308CR, 309CR and 310 the QDs need to be converted per instruction M0107554</p>	<p>1,078</p>	<p>\$24,583 NI</p>
---	--------------	---------------------------

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 7 TONS AND BELOW 10 TONS (CONT.)

MULCHERS FOR PIN-ON (Cont.)

W	504-6013	MULCHER, HM210 1,188 Overall / Working width: 1226mm (48") / 1012mm (40") Overall Height: 1065mm (42"), Length: 714mm (28") Maximum Cutting diameter: 120mm (5") Hydraulic Flow range: 70-130 lpm (18-34 gpm) Hydraulic Pressure range: 150-250 bar (2175-3626 psi) INCLUDES: V-Belt Drive drum with 24 reversible chisel teeth, dual speed axial piston motor, mounting bracket and pins, connecting lines with quick disconnects. FOR USE WITH: 308E2, Next generation 307.5, 308CR, 309CR, 310 REQUIRES: Case drain kit 504-6156 REQUIRES: For 310 ONLY 581-7636 BRACKET, MULCHER, MHE 10T NOTE: the set-up is for a 308E2. When used with Next Gen 307.5, 308CR, 309CR and 310 the QDs need to be converted per instruction M0107554		\$25,139 NI
W	504-6156	KIT, CASE DRAIN, 308E2 + 8T NG 14 FOR USE WITH: 308E2, Next Gen. 307.5 and 308CR with 1st Aux only. Next Gen 307.5 and 308CR with 2nd Aux has case drain included. Next Gen 309 always includes 1st Aux + 2nd Aux + case drain.		\$215 NI
W	523-5933	KIT, SWITCH, MULCHER, 8T E 10 FOR USE WITH: 308E2 ONLY		\$576 NI
W	557-5072	KIT, SWITCH, MULCHER, 7-10T NG 11 FOR USE WITH: Next Generation 307.5, 308CR, 309CR, 310		\$299 NI

Available via parts/Antares:
 475-2746 Chisel Tooth, reversible
 504-6100 Carbide Tooth

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - FROM 7 TONS AND BELOW 10 TONS (CONT.)

RAKES FOR PIN-ON

Designed to land cleaning, sort material and a small soil superficial preparation.

W	456-5071	RAKE, 48", MHE 8T, 5 TINE 671 Designed to land cleaning, sort material and a small soil superficial preparation.		\$4,660 NI
---	----------	--	--	-------------------

RIPPERS FOR PIN-ON

W	453-8572	RIPPER, 34", MHE 8T 235 41" (1039mm) Tip Radius FOR USE WITH: Pin-on or Pin grabber coupler INCLUDES: one J225 long tooth tip		\$1,444 NI
---	----------	---	--	-------------------

SCRAP SHEAR: STICK MOUNTED

360 degrees rotatable tool. Speed valve for faster jaw closing.
 Removable and reversible cutters. Easy cutting-tolerance adjustment
 To have an operational demolition tool you need:

- 1) Double or Combined function (Open/Close)
- 2) Low flow Double Function circuit (rotate)
- 3) High Pressure boom and stick auxiliary lines (Open/Close)
- 4) Medium pressure boom and stick lines (Rotate)
- 5) Hand control or foot valve to operate open/close, rotate functions

WARNING:

This product can create a hazard from flying objects.
 Caterpillar recommends installing front guarding on the cabs of the excavators. Failure to do so can lead to injury or death.

W	583-8100	SHEAR, HYDRAULIC, S308 1,213 REQUIRES: Mounting bracket and connecting lines		\$27,764 NI
W	318-4863	BRACKET, S308, MHE 8T PO 77 FOR USE WITH: Pin on mounting 307D, 308D CR, 308E CR, 308E2 CR		\$2,250 NI
W	359-9831	LINES, S308, MHE 7-9T 33 FOR USE WITH: 307D, 308D CR, 308E CR, 308E2 CR		\$417 NI

THUMBS, HYDRAULIC FOR PIN-ON

W	305-6740	THUMB, HYDRAULIC, 8T, PO 264 No-link style FOR USE WITH: Pin on HD&HDR Bkts (except 330mm/13" and 457mm/18" HD) REQUIRES: Auxiliary lines group with two-way flow functionality		\$4,111 NI
W	305-6741	THUMB, HYDRAULIC, 8T, PG 307 No-link style FOR USE WITH: Pin grabber coupler HD&HDR Buckets (except 330mm/13" HD) REQUIRES: Auxiliary lines group with two-way flow functionality		\$4,111 NI
W	305-6742	THUMB, STIFF LINK, 8T, PO 234 FOR USE WITH: Pin on HD&HDR Bkts (except 330mm/13" and 457mm/18" HD)		\$2,000 NI
W	305-6743	THUMB, STIFF LINK, 8T, PG 277 FOR USE WITH: Pin grabber coupler HD&HDR Buckets (except 330mm/13" HD)		\$2,000 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-------------------------------	--------------------	-------------------------

MHE - FROM 7 TONS AND BELOW 10 TONS (CONT.)

THUMBS, HYDRAULIC FOR PIN-ON (Cont.)

W	305-6744	THUMB, HYDRAULIC, 8T, LINK, PO 342 Link style with full rotation FOR USE WITH: Pin on HD&HDR Bkts (except 330mm/13" and 457mm/18" HD) REQUIRES: Auxiliary lines group with two-way flow functionality	342	\$5,819 NI
W	305-6745	THUMB, HYDRAULIC, 8T, LINK, PG 401 Link style with full rotation FOR USE WITH: Pin grabber coupler HD&HDR Buckets (except 330mm/13" HD) REQUIRES: Auxiliary lines group with two-way flow functionality	401	\$5,819 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
MHE - 10 TONS				
QUICK COUPLERS				
W	485-5306	COUPLER, PG, HYDR.D.LOCK, 10T 0 Hydraulic pin grabber type quick coupler with a dual lock. FOR USE WITH: 310 INCLUDES: 1 set of bucket pins and hardware to attach 1 bucket and connecting lines. REQUIRES: 556-3635 Bucket Pins for EACH ADDITIONAL Bucket & hydraulic QC lines on machine. Avialable via Parts/Antares:		\$6,722 NI
W	556-3635	PINS, 60MM, MHE 10T-BHL 450 36 Includes 60mm diam bucket pins and hardware FOR USE WITH: Next generation 310		\$153 NI
W	527-6691	COUPLER, PL, MHE10T, BHL450 260 Manual coupler for dedicated 1/2 Yard pin-lock backhoe work tools. Includes one set of mounting pins FOR USE WITH: Next generation 310		\$2,444 NI
COUPLER: Cat Symmetrical hydraulic quick coupler S50				
W	576-1202	COUPLER, S50, HYD, 10T, HOOK 215 Dedicated hydraulic quick coupler S50. Requires dedicated attachments with S50 hinges. FOR USE WITH: Next Generation 310 REQUIRES: Quick Coupler lines on machine + 576-1165 Lines, S50, 10T		\$4,299 NI
W	576-1165	LINES, S50, 10T 7 FOR USE WITH: S50 Quick Coupler on Next Gen 310 REQUIRES: Quick coupler lines on the machine		\$389 NI
W	576-1203	COUPLER, S50, HYD,10T,LCS,HOOK 225 Dedicated hydraulic quick coupler S50. Requires dedicated attachments with S50 hinges. INCLUDES: Hydraulic Locking Control System which indicates if the quick coupler is safely locked/coupled or not. FOR USE WITH: Next Gen. 310 REQUIRES: quick coupler lines on the machine. You might need to flash parts of the machine software, depending on the version. REQUIRES: 577-1565 KIT, HARNESS, TRS8 to provide an electrical harness on the machine to operate the HLCS. REQUIRES: 576-1165 LINES, S50, 10T		\$5,090 NI
W	577-1565	KIT, HARNESS, TRS8 18 3 piece harness, bracket & harness connector cap (stick QC operation) The harness connects the TRS8 ECM or S50 with the machine ECM.		\$778 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - 10 TONS (CONT.)

COUPLER: TILT ROTATOR SYSTEM TRS8

The TRS8 significantly reduces the time and need to constantly reposition the machine by providing a rotary and tilt connection between the base machine and the attachment. This revolutionary enhancement features 360 degrees of continuous rotation and 40 degrees of angular tilt. In addition to coupling attachments like buckets and forks, the TRS8 is also equipped to handle hydro-mechanical attachments like compactors, grapples, brooms and more.

For installation instructions see media reference M0104954

Only available for Next Generation sales models. No backward compatibility to previous sales models

W	570-7120	TILT ROTATOR, TRS8, S50-S50, G 683 TRS8 with S50 interface machine side and S50 hydr. QC attachment side INCLUDES: Grapple Attachment, vibration function. 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 307.5, 308CR, 309CR and 310 REQUIRES: Machine side: Quick Coupler lines and S50 quick Coupler, Case drain: either 2nd AUX (this comes with case drain) or 1st AUX & Case Drain Kit 504-6156 (Not possible for 310) REQUIRES: 570-7210 KIT JOYSTICK TRS8 and 577-1565 KIT, HARNESS, TRS8 and 577-1587 LINES, TRS8, MHE, 8T-10T REQUIRES: Dedicated attachments with S50 hinges.	827	\$31,083 NI
W	570-7121	TILT ROTATOR, TRS8, S50-S50 827 TRS8 with S50 interface machine side and S50 hydr. QC attachment side INCLUDES: Vibration function. 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 307.5, 308CR, 309CR and 310 REQUIRES: Machine side: Quick Coupler lines and S50 quick Coupler, Case drain: either 2nd AUX (this comes with case drain) or 1st AUX & Case Drain Kit 504-6156 (Not possible for 310) REQUIRES: 570-7210 KIT JOYSTICK TRS8 and 577-1565 KIT, HARNESS, TRS8 and 577-1587 LINES, TRS8, MHE, 8T-10T REQUIRES: Dedicated attachments with S50 hinges.	683	\$25,813 NI
W	570-7125	TILT ROTATOR, TRS8, 10T,PO-S50 683 TRS8 with 10T Pin-on machine side and S50 hydr. QC attachment side INCLUDES: Vibration function. 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 307.5, 308CR, 309CR and 310 REQUIRES: Machine side: Case drain: either 2nd AUX (this comes with case drain) or 1st AUX & Case Drain Kit 504-6156 (Not possible for 310) REQUIRES: 570-7210 KIT JOYSTICK TRS8 and 577-1565 KIT, HARNESS, TRS8 and 577-1587 LINES, TRS8, MHE, 8T-10T REQUIRES: Dedicated attachments with S50 hinges.		\$27,528 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - 10 TONS (CONT.)

COUPLER: TILT ROTATOR SYSTEM TRS8 (Cont.)

W	570-7123	TILT ROTATOR, TRS8, 10T, PO-PG 683 TRS8 with 10T Pin-on machine side and with a hydraulic Pin Grabber for 10T on attachment side. INCLUDES: Vibration function, 40 degrees tilt left and right, 360 degrees rotation left/right, locking control system FOR USE WITH: Next Generation 310 REQUIRES: Machine side: 1st AUX & Case Drain Kit 504-6156, or 2nd AUX REQUIRES: 570-7210 KIT JOYSTICK TRS8 and 577-1565 KIT, HARNESS, TRS8 and 577-1587 LINES, TRS8, MHE, 8T-10T REQUIRES: Pin-on 10T linkage attachments		\$31,160 NI
W	570-7210	KIT, TRS JOYSTICK, MHE 6T-10T 4 LH and RH joystick installed on existing joystick bases. The TRS8 will NOT work without these special joysticks.		\$2,354 NI
W	577-1565	KIT, HARNESS, TRS8 18 3 piece harness, bracket & harness connector cap (stick QC operation) The harness connects the TRS8 ECM or S50 with the machine ECM.		\$778 NI
W	577-1587	LINES, TRS8, MHE 8T-10T 24 Jumper lines connect TRS8 to auxilliary quick disconnect and includes pressure, return and case drain hoses.		\$389 NI

BUCKETS FOR PIN-ON - Heavy Duty with pin-on teeth

W	547-7030	BUCKET-HD, 18", 6.4 FT3, 60MM 447 Width 460mm (18"), Heaped Cap. 0.18m3 (6.4ft3), Incl 3 x J225 FOR USE WITH: Pin-on, includes bucket pins		\$2,253 NI
W	547-7031	BUCKET-HD, 24", 9.5 FT3, 60MM 495 Width 610mm (24"), Heaped Cap. 0.27m3 (9.5ft3), Incl 4 x J225 FOR USE WITH: Pin-on, requires bucket pins		\$2,365 NI
W	547-7032	BUCKET-HD, 30", 12.4 FT3, 60MM 567 Width 762mm (30"), Heaped Cap. 0.35m3 (12.4ft3), Incl 5 x J225 FOR USE WITH: Pin-on, requires bucket pins		\$2,621 NI
W	547-7033	BUCKET-HD, 36", 15.9 FT3, 60MM 663 Width 914mm (36"), Heaped Cap. 0.45m3 (15.9ft3), Incl 5 x J225 FOR USE WITH: Pin-on, requires bucket pins		\$2,876 NI
W	547-7034	BUCKET-HD, 42", 19.2 FT3, 60MM 745 Width 1067mm (42"), Heaped Cap. 0.54m3 (19.2ft3), Incl 6 x J225 FOR USE WITH: Pin-on, requires bucket pins		\$3,131 NI

BUCKETS FOR PIN 1/2 Yard Pin Lock

W	527-7302	BUCKET-HD, 18", 7.0 FT3, PL 551 Width 460mm (18"), Heaped Cap. 0.20m3 (7.0ft3), Incl 3 x J250 FOR USE WITH: Next generation 310 & 1/2 Yard Pin Lock QC		\$2,607 NI
W	528-8034	BUCKET-HD, 24", 10.8 FT3, PL 664 Width 610mm (24"), Heaped Cap. 0.31m3 (10.8ft3), Incl 4 x J250 FOR USE WITH: Next generation 310 & 1/2 Yard Pin Lock QC		\$3,194 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - 10 TONS (CONT.)

BUCKETS FOR PIN 1/2 Yard Pin Lock (Cont.)

W	528-8784	BUCKET-HD, 36", 17.6 FT3, PL 860 Width 914mm (36"), Heaped Cap. 0.50m3 (17.6ft3), Incl 6 x J250 FOR USE WITH: Next generation 310 & 1/2 Yard Pin Lock QC		\$4,115 NI
W	528-8786	BUCKET-HD, 48", 27.0 FT3, PL 1,057 Width 1067mm (48"), Heaped Cap. 0.76m3 (27.0ft3), Incl 8 x J250 FOR USE WITH: Next generation 310 & 1/2 Yard Pin Lock QC		\$5,036 NI

BUCKETS FOR PIN-ON - Ditch Cleaning

W	547-7081	BUCKET-DC, 47", 9.5 FT3, 60MM 358 Width 1200mm (47"), Heaped Cap. 0.27m3 (9.5ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: Water holes		\$3,121 NI
W	547-7082	BUCKET-DC, 59", 12.4FT3, 60MM 417 Width 1500mm (59"), Heaped Cap. 0.35m3 (12.4ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: Water holes		\$3,586 NI
W	547-7083	BUCKET-DC, 71", 14.9 FT3, 60MM 476 Width 1800mm (71"), Heaped Cap. 0.42m3 (14.9ft3) FOR USE WITH: Pin-on, requires bucket pins INCLUDES: Water holes		\$4,051 NI

BUCKETS FOR PIN-ON - Grading/Mud

Designed for grading with higher capacity and suited to carry buckets

W	547-7084	BUCKET-GRADING, 47", 15.1 FT3 705 Width 1200mm (47"), Heaped Cap. 0.43m3 (15.1ft3) FOR USE WITH: Pin-on, includes bucket pins and BOCE		\$3,357 NI
W	547-7085	BUCKET-GRADING, 59", 19.8 FT3 822 Width 1500mm (59"), Heaped Cap. 0.56m3 (19.8ft3) FOR USE WITH: Pin-on, includes bucket pins and BOCE		\$3,867 NI
W	547-7086	BUCKET-GRADING, 71", 24 FT3 938 Width 1800mm (71"), Heaped Cap. 0.68m3 (24.0ft3) FOR USE WITH: Pin-on, includes bucket pins and BOCE		\$4,376 NI

BUCKETS FOR TRS8

These NORDIC style buckets are special designed to be used with the TRS8. They meet the Nordic soil conditions.

BUCKETS FOR TRS8: Digging buckets for S45 or S50

BUCKETS FOR TRS8: Grading buckets for S45 or S50

BUCKETS FOR TRS8: Grading buckets for Dual Lock Quick Coupler

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-------------------------------	--------------------	-------------------------

MHE - 10 TONS (CONT.)

BUCKETS FOR TRS8 (Cont.)

BUCKETS FOR TRS8: Trenching buckets for S40 or S50

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
MHE - 10 TONS (CONT.)				
COMPACTOR PLATE CVP40				
W	551-4957	COMPACTOR PLATE, CVP40 411 Has drill pattern XL REQUIRES: Mounting bracket and connecting lines		\$8,222 NI
W	211-8200	BLADE, BACKFILL, CVP40 113 FOR USE WITH: CVP40 for back filling trenches.		\$660 NI
W	264-5907	SWIVEL, CVP40, XL TO XL 269 FOR USE WITH: CVP40 for back filling trenches.		\$1,768 NI
W	564-9843	BRACKET, 10T-BL450, 60-60MM,XL 224 Mounting bracket with drill pattern XL, incl. nuts,bolts & bucket pins FOR USE WITH: Next Generation 310		\$833 NI
W	564-2732	BRACKET, 1/2YD PL, XL 233 Mounting bracket, incl.bolts + nuts, excl. lines FOR USE WITH: 1/2 yard pin lock quick coupler.		\$1,528 NI
W	556-3635	PINS, 60MM, MHE 10T-BHL 450 36		\$153 NI
W	490-0015	LINES, CVP40, MHE 8T/10T 29 FOR USE WITH: Pin-On/QC and NO bucket thumb.		\$417 NI
W	325-3832	LINES,CVP40, MHE 8T/10T, THUMB 57 FOR USE WITH: Pin-On/QC and WITH bucket thumb.		\$972 NI

FLAIL MOWERS FOR PIN-ON

Hydraulic mower with swinging teeth to cut and break down material for use in agriculture, land management and landscaping to control overgrowth maintain hedges. Caterpillar recommends a machine configuration with appropriate guarding for maximum protection.

W	504-6011	FLAIL MOWER, HMF210 843 Overall / Working width: 1187mm (47") / 1000mm (40") Overall Height: 762mm (30"), Length: 853mm (34") Maximum Cutting diameter: 50-75mm (2"-3") Hydraulic Flow range: 70-130 lpm (18-34 gpm) Hydraulic Pressure range: 150-250 bar (2175-3626 psi) INCLUDES: V-Belt Drive drum with 16 hammer teeth, axial piston motor, mounting bracket and pins, connecting lines and quick disconnects FOR USE WITH: 308E2, Next generation 307.5, 308CR, 309CR, 310 REQUIRES: Case drain kit 504-6156 REQUIRES: For 310 ONLY 581-7634 BRACKET, FLAIL, MHE 10T NOTE: the set-up is for a 308E2. When used with Next Gen 307.5, 308CR, 309CR and 310 the QDs need to be converted per instruction M0107554		\$13,264 NI
W	504-6156	KIT, CASE DRAIN, 308E2 + 8T NG 14 FOR USE WITH: 308E2, Next Gen. 307.5, 308CR, 310 with 1st Aux only. Next Gen 307.5, 308CR, 310 with 2nd Aux has case drain included. Next Gen 309 always includes 1st Aux + 2nd Aux + case drain.		\$215 NI
W	581-7634	BRACKET, FLAIL, MHE 10T 103 FOR USE WITH: Next Gen. 310 only		\$1,042 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - 10 TONS (CONT.)

HAMMERS - B and H series - for details see Hammer Section

WARNING:

Demolition tools can create a hazard from flying objects. Caterpillar recommends installing front guards on the cabs of the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Compatibility table for hammers:

Machines	B hammers	H hammers (incl. E)
Next Generation	B8 B9	H80 H95
310	-- ++	++ ++

++= Optimal += Acceptable --= Not Allowed

MULCHERS FOR PIN-ON

Hydraulic mulcher to mulch trees and undergrowth up to 120mm (5") in diameter, for use in landscaping, agriculture and land management. Caterpillar recommends a machine configuration with appropriate guarding for maximum protection.

W	504-6012	MULCHER, HM208 1,078	\$24,583 NI
		Overall / Working width: 1026mm (40") / 818mm (32") Overall Height: 1065mm (42"), Length: 714mm (28") Maximum Cutting diameter: 120mm (5") Hydraulic Flow range: 70-130 lpm (18-34 gpm) Hydraulic Pressure range: 150-250 bar (2175-3626 psi) INCLUDES: V-Belt Drive drum with 15 reversible chisel teeth, dual speed axial piston motor, mounting bracket and pins, connecting lines with quick disconnects. FOR USE WITH: 308E2, Next generation 307.5, 308CR, 309CR, 310 REQUIRES: Case drain kit 504-6156 REQUIRES: For 310 ONLY 581-7636 BRACKET, MULCHER, MHE 10T NOTE: the set-up is for a 308E2. When used with Next Gen 307.5, 308CR, 309CR and 310 the QDs need to be converted per instruction M0107554	
W	504-6013	MULCHER, HM210 1,188	\$25,139 NI
		Overall / Working width: 1226mm (48") / 1012mm (40") Overall Height: 1065mm (42"), Length: 714mm (28") Maximum Cutting diameter: 120mm (5") Hydraulic Flow range: 70-130 lpm (18-34 gpm) Hydraulic Pressure range: 150-250 bar (2175-3626 psi) INCLUDES: V-Belt Drive drum with 24 reversible chisel teeth, dual speed axial piston motor, mounting bracket and pins, connecting lines with quick disconnects. FOR USE WITH: 308E2, Next generation 307.5, 308CR, 309CR, 310 REQUIRES: Case drain kit 504-6156 REQUIRES: For 310 ONLY 581-7636 BRACKET, MULCHER, MHE 10T NOTE: the set-up is for a 308E2. When used with Next Gen 307.5, 308CR, 309CR and 310 the QDs need to be converted per instruction M0107554	
W	504-6156	KIT, CASE DRAIN, 308E2 + 8T NG 14	\$215 NI
		FOR USE WITH: 308E2, Next Gen. 307.5 and 308CR with 1st Aux only. Next Gen 307.5 and 308CR with 2nd Aux has case drain included. Next Gen 309 always includes 1st Aux + 2nd Aux + case drain.	

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - 10 TONS (CONT.)

MULCHERS FOR PIN-ON (Cont.)

W	581-7636	BRACKET, MULCHER, MHE 10T	117	\$1,250 NI
		FOR USE WITH: Next Gen. 310 only		
W	557-5072	KIT, SWITCH, MULCHER, 7-10T NG	11	\$299 NI
		FOR USE WITH: Next Generation 307.5, 308CR, 309CR, 310		

Available via parts/Antares:
 475-2746 Chisel Tooth, reversible
 504-6100 Carbide Tooth

RIPPERS FOR PIN-ON

W	546-4141	RIPPER, 37", MHE 10T-BHL 450	375	\$2,014 NI
		FOR USE WITH: Pin-on or Pin grabber coupler		
		INCLUDES: one J225 long tooth tip		

THUMBS, HYDRAULIC FOR PIN-ON

W	540-6735	THUMB, HYDRAULIC, 10T	324	\$4,806 NI
		FOR USE WITH: Pin-on or Pin grabber coupler		
		REQUIRES: Auxiliary lines group with two-way flow functionality		

COMPACTING WHEELS for PIN-ON for 450

W	517-6998	WHEEL, 12", BL 450	959	\$4,632 NI
		Trench width 310mm (12"), 2 wheels each with 9 pads		
		Overall Length-Height-Width: 1014mm(39.9")- 1155mm(45.5")-323mm(12.7")		
		FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		
W	517-6999	WHEEL, 18", BL 450	1,266	\$5,819 NI
		Trench width 450mm (18"), 3 wheels each with 9 pads		
		Overall Length-Height-Width: 1014mm(39.9")- 1168mm(46")- 449mm(17.7")		
		FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		
W	517-7000	WHEEL, 24", BL 450	1,307	\$6,056 NI
		Trench width 560mm (22"), 3 wheels each with 9 pads		
		Overall Length-Height-Width: 1014mm(39.9")- 1168mm(46")- 556mm(21.9")		
		FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		
W	517-7001	WHEEL, 36", BL 450	1,982	\$7,014 NI
		Trench width 880mm (35"), 5 wheels each with 9 pads		
		Overall Length-Height-Width: 1091mm(43")- 1168mm(46")- 884mm(34.8")		
		FOR USE WITH: Pin-on or Pin Grabber coupler (bucket pins included)		

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - 10 TONS (CONT.)

COMPACTING WHEELS for PIN LOCK COUPLERS for 450

W	517-7002	WHEEL, 12", 1/2 PL 946 Trench width 310mm (12"), 2 wheels each with 9 pads Overall Length-Height-Width: 998mm(39.3")- 1276mm(50.2")- 356mm(14") FOR USE WITH: Pin Lock coupler 1/2YD (Wain Roy)		\$4,632 NI
W	517-7003	WHEEL, 18", 1/2 PL 1,240 Trench width 450mm (18"), 3 wheels each with 9 pads Overall Length-Height-Width: 997mm(39.3")- 1284mm(50.6")- 449mm(17.7") FOR USE WITH: Pin Lock coupler 1/2YD (Wain Roy)		\$5,819 NI
W	517-7004	WHEEL, 24", 1/2 PL 1,281 Trench width 560mm (22"), 3 wheels each with 9 pads Overall Length-Height-Width: 997mm(39.3")- 1284mm(50.6")- 556mm(21.9") FOR USE WITH: Pin Lock coupler 1/2YD (Wain Roy)		\$6,056 NI
W	517-7005	WHEEL, 36", 1/2 PL 1,970 Trench width 880mm (35"), 5 wheels each with 9 pads Overall Length-Height-Width: 1073mm(42.2")- 1284mm(50.6")- 884mm(34.8") FOR USE WITH: Pin Lock coupler 1/2YD (Wain Roy)		\$7,014 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS

WARNING:
 Demolition tools can create a hazard from flying objects. Caterpillar recommends installing front guards on the cabs of the excavators. Failure to do so can lead to injury or death.

Compatibility table for hammers:

Machines	B hammers	H hammers
300.9D	B1 Pin-On ++	H25D ++
301.4C, 301.6C, 301.7D, 301.8C Next Generation 301.5, 301.6 301.7CR, 301.8 302CR	B1 B2 B4 ++ -- -- ++ +- -- ++ +- -- +- ++ --	H35 H45 ++ -- ++ +- ++ +- +- ++
302.2D, 302.4D 302.5C, 302.7D CR	B1 B2 B4 +- ++ -- -- ++ +-	H35 H45 H55 +- ++ -- -- ++ +-
303C CR, 303E CR 303.5D CR, 303.5E CR, 303.5E2 304D CR, 304E CR, 304E2 304.5E2	B2 B4 B6 +- ++ -- +- ++ -- -- ++ +- -- ++ +-	H45 H55 H65 +- ++ -- +- ++ -- -- ++ -- -- ++ --
305C CR, 305D CR, 305E CR, 305E2 305.5D CR, 305.5E CR, 305.5E2 306E, 306E2	B4 B6 B8 +- ++ -- +- ++ -- +- ++ -- +- ++ +-	H55 H65 H80 ++ ++ -- ++ ++ -- ++ ++ -- ++ ++ --
307D, 307E, 307E2 308D, 308E, 308E2 CR Next Generation 307.5, 308, 309CR	B6 B8 B9 +- ++ ++ +- ++ ++ +- ++ ++	H65 H80 H95 +- ++ ++ +- ++ ++ +- ++ ++
Next Generation 310	B8 B9 -- ++	H80 H95 ++ ++

++= Optimal +- = Acceptable -- = Not Allowed

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs		LIST PRICE AT DEALER
------------	----------------	-------------------------------	----------------------------	--	---------------------------------

MHE - HAMMERS (CONT.)

Bracket & drill pattern table for brackets and hammers.

Hammer	Drill pattern					
	XS	SM	MD	LG	XL	
B1 Pin-On		NA				
B1		x	x			
B2		x	x			
B4		x	x			
B6				x		
B8				x		
B9						x
H25D	x					
H35			x			
H45			x			
H55				x		
H65				x		
H80						x
H95						x

H series includes H-E series

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - B1 PIN-ON 300.9D ONLY

If no hammer reference numbers appear below there are currently no items available in your region.

W	573-4711	HAMMER, B1, 0.9T, 25MM, PO,TM 162 NON Silenced hydraulic hammer, Pin-On for 300.9D BPM (blows/minute): 800-1,400 , Energy Class 201 Joule (148 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut), connecting lines & quick disconnects, 1 set of bucket pins FOR USE WITH: 300.9D Pin-on only REQUIRED HYDRAULICS: Min - Max Flow: 15-25 l/min (4.0-6.6 gal/min) Max Operation Pressure 11,749 kPa (1,704 psi) REQUIRES: Machine side: hammer lines and front guards		\$4,035 NI
W	565-6082	TOOL, CONE, B1, 300.9D 0 Diam: 40mm (1.6"), Total Length: 360mm (14.2") Working length: Non silenced / silenced: 210mm (8.3") / 180mm (7.1")		\$160 NI
W	576-5523	TOOL, CHISEL, INLINE,B1,300.9D 0 Diam: 40mm (1.6"), Total Length: 360mm (14.2") Working length: Non silenced / silenced: 210mm (8.3") / 180mm (7.1")		\$160 NI
W	576-5524	TOOL, CHISEL, XCUT, B1, 300.9D 0 Diam: 40mm (1.6"), Total Length: 360mm (14.2") Working length: Non silenced / silenced: 210mm (8.3") / 180mm (7.1")		\$160 NI
W	532-9151	TOOL, MOIL, B1 8 Diam: 40mm (1.6"), Total Length: 430mm (16.9") Working length: Non silenced / silenced: 280mm (11") / 250mm (9.8")		\$160 NI
W	542-1750	TOOL, CONE, B1 8 Diam: 40mm (1.6"), Total Length: 430mm (16.9") Working length: Non silenced / silenced: 280mm (11") / 250mm (9.8")		\$160 NI
W	542-1751	TOOL, BLUNT, B1 9 Diam: 40mm (1.6"), Total Length: 430mm (16.9") Working length: Non silenced / silenced: 280mm (11") / 250mm (9.8")		\$160 NI
W	542-1752	TOOL, CHISEL, IN LINE, B1 9 Diam: 40mm (1.6"), Total Length: 430mm (16.9") Working length: Non silenced / silenced: 280mm (11") / 250mm (9.8")		\$160 NI
W	542-1753	TOOL, CHISEL, CROSS CUT, B1 9 Diam: 40mm (1.6"), Total Length: 430mm (16.9") Working length: Non silenced / silenced: 280mm (11") / 250mm (9.8")		\$160 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - B1 AND B1 SILENCED FLAT TOP

Compatibility table B1 and B1S Flat top:

300.9D	--	<1 ton	25mm pins
301.4C, 301.6C, 301.7D, 301.8C Next Generation	++	>=1Ton - <=2Tons	30mm pins
301.5, 301.6, 301.7CR, 301.8 302CR	++ +-		
302.2D, 302.4D 302.5C, 302.7D CR	+- --	>2Tons - <3Tons	35mm pins

++= Optimal +- = Acceptable -- = Not Allowed

NOTE: If lines+brackets fit a machine+hammer, still CHECK compatitibily

If no reference numbers appear below there are currently no items available in your region.

W	532-9101	HAMMER, B1 183 NON Silenced hydraulic hammer, flat top with drill pattern SM & MD BPM (blows/minute): 800-1,400 , Energy Class 201 Joule (148 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) FOR USE WITH: CHECK compatibility table above for allowed sales models REQUIRED HYDRAULICS: Min - Max Flow: 15-25 l/min (4.0-6.6 gal/min) Max Operation Pressure 11,749 kPa (1,704 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket SM, connecting lines	\$4,375 NI
W	532-9201	HAMMER, B1S 190 Silenced hydraulic hammer, flat top with drill pattern SM BPM (blows/minute): 800-1,400 , Energy Class 201 Joule (148 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) FOR USE WITH: CHECK compatibility table above for allowed sales models REQUIRED HYDRAULICS: Min - Max Flow: 15-25 l/min (4.0-6.6 gal/min) Max Operation Pressure 11,749 kPa (1,704 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket SM, connecting lines	\$4,861 NI
W	532-9055	BRACKET, MHE 1T, 30MM, SM-MD 55 Mounting bracket, drill pattern SM + MD, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC + Hammers with SM/MD drill pattern on 1 Ton platform (30mm pins)	\$382 NI
W	532-9086	LINES, B1-B2 HAMMER, 1T 0 FOR USE WITH: B1 + B2 on 1 Ton platform (30mm pins) incl Next Gen.	\$174 NI
W	532-9057	BRACKET, MHE 2T, 35MM, SM-MD 74 Mounting bracket, drill pattern SM + MD, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC + Hammers with SM/MD drill pattern on 2 Ton platform (35mm pins)	\$382 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - B1 AND B1 SILENCED FLAT TOP (Cont.)

W	532-9087	LINES, B1-B2-B4 HAMMER, 2T 0 FOR USE WITH: B1, B2 Hammer on 2 Ton platform (35mm pins) FOR USE WITH: B4 on 302.5C, 302.7D CR		\$181 NI
W	532-9151	TOOL, MOIL, B1 8 Diam: 40mm (1.6"), Total Length: 430mm (16.9") Working length: Non silenced / silenced: 280mm (11") / 250mm (9.8")		\$160 NI
W	542-1750	TOOL, CONE, B1 8 Diam: 40mm (1.6"), Total Length: 430mm (16.9") Working length: Non silenced / silenced: 280mm (11") / 250mm (9.8")		\$160 NI
W	542-1751	TOOL, BLUNT, B1 9 Diam: 40mm (1.6"), Total Length: 430mm (16.9") Working length: Non silenced / silenced: 280mm (11") / 250mm (9.8")		\$160 NI
W	542-1752	TOOL, CHISEL, IN LINE, B1 9 Diam: 40mm (1.6"), Total Length: 430mm (16.9") Working length: Non silenced / silenced: 280mm (11") / 250mm (9.8")		\$160 NI
W	542-1753	TOOL, CHISEL, CROSS CUT, B1 9 Diam: 40mm (1.6"), Total Length: 430mm (16.9") Working length: Non silenced / silenced: 280mm (11") / 250mm (9.8")		\$160 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - B2 AND B2 SILENCED FLAT TOP and SIDE MOUNT

Compatibility table B2 and B2S:

301.4C, 301.6C, 301.7D, 301.8C Next Generation 301.5, 301.6, 301.7CR, 301.8 302CR	-- +- +- ++	>=1Ton - <=2Tons	30mm pins
302.2D, 302.4D, 302.5C, 302.7D CR	++	>2Tons - <3Tons	35mm pins
303C CR, 303E CR 303.5D CR, 303.5E CR, 303.5E2 304D CR, 304E CR, 304E2, 304.5E2	+- +- --	>=3Tons - <5Tons	40mm pins

++= Optimal += Acceptable --= Not Allowed

NOTE: If lines+brackets fit a machine+hammer, still CHECK compatitibility

If no reference numbers appear below there are currently no items available in your region.

W	532-9102	HAMMER, B2 250 NON Silenced hydraulic hammer, flat top with drill pattern SM BPM (blows/minute): 700-1,200 , Energy Class 290 Joule (214 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) FOR USE WITH: CHECK compatibility table above for allowed sales models REQUIRED HYDRAULICS: Min - Max Flow: 20-30 l/min (5.3-7.9 gal/min) Max Operation Pressure 11,749 kPa (1,704 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket SM, connecting lines	\$5,000 NI
W	532-9202	HAMMER, B2S 259 Silenced hydraulic hammer, flat top with drill pattern SM BPM (blows/minute): 700-1,200, Energy Class 290 Joule (214 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) FOR USE WITH: CHECK compatibility table above for allowed sales models REQUIRED HYDRAULICS: Min - Max Flow: 20-30 l/min (5.3-7.9 gal/min) Max Operation Pressure 11,749 kPa (1,704 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket SM, connecting lines	\$5,556 NI
W	576-5540	HAMMER, B2, MHE 1T,30MM, PO,SM 272 NON Silenced hydraulic hammer, Pin-On Side Mount incl. bucket pins BPM (blows/minute): 700-1,200 , Energy Class 290 Joule (214 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut), connecting lines FOR USE WITH: CHECK compatibility table above for allowed sales models Pin-On, 1Ton 30mm pins platform REQUIRED HYDRAULICS: Min - Max Flow: 20-30 l/min (5.3-7.9 gal/min) Max Operation Pressure 11,749 kPa (1,704 psi) REQUIRES: Machine side: hammer lines and front guards	\$4,569 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - B2 AND B2 SILENCED FLAT TOP and SIDE MOUNT (Cont.)

W	532-9055	BRACKET, MHE 1T, 30MM, SM-MD 55 Mounting bracket, drill pattern SM + MD, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC + Hammers with SM/MD drill pattern on 1 Ton platform (30mm pins)		\$382 NI
W	532-9086	LINES, B1-B2 HAMMER, 1T 0 FOR USE WITH: B1 + B2 on 1 Ton platform (30mm pins) incl Next Gen.		\$174 NI
W	532-9057	BRACKET, MHE 2T, 35MM, SM-MD 74 Mounting bracket, drill pattern SM + MD, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC + Hammers with SM/MD drill pattern on 2 Ton platform (35mm pins)		\$382 NI
W	532-9087	LINES, B1-B2-B4 HAMMER, 2T 0 FOR USE WITH: B1, B2 Hammer on 2 Ton platform (35mm pins) FOR USE WITH: B4 on 302.5C, 302.7D CR		\$181 NI
W	532-9059	BRACKET, MHE 3T, 40MM, SM-MD 114 Mounting bracket, drill pattern SM + MD, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC + Hammers with SM/MD drill pattern on 3-4 Ton platform (40mm pins)		\$382 NI
W	532-9088	LINES, B4-B6 HAMMER, 3T 0 FOR USE WITH: B2, B4 + B6 Hammer on 3-4 Ton platform (40mm pins)		\$208 NI
W	532-9175	TOOL, MOIL, B2 12 Diam: 45mm (1.8"), Total Length: 500mm (19.7") Working length: Non silenced / silenced: 326mm (12.8") / 296mm (11.7")		\$174 NI
W	542-1754	TOOL, CONE, B2 12 Diam: 45mm (1.8"), Total Length: 500mm (19.7") Working length: Non silenced / silenced: 326mm (12.8") / 296mm (11.7")		\$174 NI
W	542-1755	TOOL, BLUNT, B2 13 Diam: 45mm (1.8"), Total Length: 500mm (19.7") Working length: Non silenced / silenced: 326mm (12.8") / 296mm (11.7")		\$174 NI
W	542-1756	TOOL, CHISEL, IN LINE, B2 12 Diam: 45mm (1.8"), Total Length: 500mm (19.7") Working length: Non silenced / silenced: 326mm (12.8") / 296mm (11.7")		\$174 NI
W	542-1757	TOOL, CHISEL, CROSS CUT, B2 12 Diam: 45mm (1.8"), Total Length: 500mm (19.7") Working length: Non silenced / silenced: 326mm (12.8") / 296mm (11.7")		\$174 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - B4 AND B4 SILENCED FLAT TOP and SIDE MOUNT

Compatibility table B4 and B4s:

302.2D, 302.4D 302.5C, 302.7D CR	--	>2Tons - <3Tons	35mm pins
303C CR, 303E CR 303.5C CR, 303.5D CR 303.5E CR, 303.5E2	++	>=3Tons - <5Tons	40mm pins
304D CR, 304E CR, 304E2, 304.5E2	++		
305C CR, 305D CR, 305E CR, 305E2 305.5D CR, 305.5E CR, 305.5E2 306E, 306E2	+-	>=5Tons - <7Tons	45mm pins

++= Optimal += Acceptable --= Not Allowed

If no hammer references appear below there are none currently available in your region.

W	532-9104	HAMMER, B4 351 NON Silenced hydraulic hammer, flat top with drill pattern SM and MD BPM (blows/minute): 600-1,100 , Energy Class 370 Joule (273 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 25-50 l/min (6.6-13.2 gal/min) Max Operation Pressure 11,749 kPa (1,704 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket SM or MD, connecting lines	\$5,750 NI
W	532-9204	HAMMER, B4S 357 Silenced hydraulic hammer, flat top with drill pattern SM and MD BPM (blows/minute): 600-1,100 , Energy Class 370 Joule (273 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 25-50 l/min (6.6-13.2 gal/min) Max Operation Pressure 11,749 kPa (1,704 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket SM or MD, connecting lines	\$6,389 NI
W	532-9304	HAMMER, B4, MHE 3T 40MM, PO SM 337 NON Silenced hydraulic hammer, Pin-On Side Mount incl. bucket pins BPM (blows/minute): 600-1,100 , Energy Class 370 Joule (273 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 25-50 l/min (6.6-13.2 gal/min) Max Operation Pressure 11,749 kPa (1,704 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: connecting lines	\$5,264 NI
W	532-9057	BRACKET, MHE 2T, 35MM, SM-MD 74 Mounting bracket, drill pattern SM + MD, incl. bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC 302.2D, 302.4D, 302.5C, 302.7D CR	\$382 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - B4 AND B4 SILENCED FLAT TOP and SIDE MOUNT (Cont.)

W	532-9087	LINES, B1-B2-B4 HAMMER, 2T 0 FOR USE WITH: B1, B2 Hammer on 2 Ton platform (35mm pins) FOR USE WITH: B4 on 302.5C, 302.7D CR		\$181 NI
W	569-5414	BRACKET, MHE 5T 45MM, SM-LG 127 Mounting bracket, drill pattern SM + LG, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC		\$451 NI
W	532-9275	BRACKET, MHE 3-5T, MD-LG 99 FOR USE WITH: 3T or 5T MHE REQUIRES: 316-0412 KIT, MOUNTING GROUP SSL 5T for 5T MHE REQUIRES: 249-1145 KIT, MOUNTING GROUP SSL 3T for 3T MHE		\$486 NI
W	532-9088	LINES, B4-B6 HAMMER, 3T 0 FOR USE WITH: B4 or B6 on 303C CR, 303E CR, 303.5D CR, 303.5E CR, 303.5E2, 304D CR, 304E CR, 304E2, 304.5E2		\$208 NI
W	532-9089	LINES, B6-B8 HAMMER, 5T-8T 0 FOR USE WITH: 305C CR up to and including 309 CR with pin-on brackets or dedicated quick coupler brackets. FOR USE WITH: B4 on 5T-6T machines		\$208 NI
W	532-9190	TOOL, MOIL, B4 19 Diam: 53mm (2.1"), Total Length: 580mm (22.8") Working length: Non silenced / silenced: 360mm (14.2") / 330mm (13")		\$201 NI
W	542-1758	TOOL, CONE, B4 21 Diam: 53mm (2.1"), Total Length: 580mm (22.8") Working length: Non silenced / silenced: 360mm (14.2") / 330mm (13")		\$201 NI
W	542-1759	TOOL, BLUNT, B4 20 Diam: 53mm (2.1"), Total Length: 580mm (22.8") Working length: Non silenced / silenced: 360mm (14.2") / 330mm (13")		\$201 NI
W	542-1760	TOOL, CHISEL, IN LINE, B4 20 Diam: 53mm (2.1"), Total Length: 580mm (22.8") Working length: Non silenced / silenced: 360mm (14.2") / 330mm (13")		\$201 NI
W	542-1761	TOOL, CHISEL, CROSS CUT, B4 20 Diam: 53mm (2.1"), Total Length: 580mm (22.8") Working length: Non silenced / silenced: 360mm (14.2") / 330mm (13")		\$201 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - B6 AND B6 SILENCED FLAT TOP and SIDE MOUNT

Compatibility table B6 and B6s:

303C CR, 303E CR	--	>=3Tons - <5Tons	40mm pins
303.5C CR, 303.5D CR	--		
303.5E CR, 303.5E2	--		
304D CR, 304E CR, 304E2, 304.5E2	+-		
305C CR, 305D CR, 305E CR, 305E2	++	>=5Tons - <7Tons	45mm pins
305.5D CR, 305.5E CR, 305.5E2	++		
306E, 306E2	++		
307D, 307E, 307E2	+-	>=7Tons - <10Tons	50mm pins
308D, 308E CR, 308E2 CR	+-		
Next Generation			
307.5, 308, 309CR	+-		

++= Optimal +- = Acceptable -- = Not Allowed

If no hammer references appear below there are none currently available in your region.

W	532-9206	HAMMER, B6S 611	\$9,306 NI
		Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 500-900 , Energy Class 681 Joule (502 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 40-70 l/min (10.6-18.5 gal/min) Max Operation Pressure 13,707 kPa (1,988 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines	
W	532-9106	HAMMER, B6 571	\$8,375 NI
		Non-Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 500-900 , Energy Class 681 Joule (502 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 40-70 l/min (10.6-18.5 gal/min) Max Operation Pressure 13,707 kPa (1,988 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines.	
W	532-9306	HAMMER, B6, MHE 5T,45MM, PO,SM 562	\$7,458 NI
		NON Silenced hydraulic hammer, Pin-On Side Mount incl. bucket pins BPM (blows/minute): 500-900 , Energy Class 681 Joule (502 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut), connecting lines FOR USE WITH: CHECK compatibility table above for allowed sales models Pin-On, 5Ton 45mm pins platform REQUIRED HYDRAULICS: Min - Max Flow: 40-70 l/min (10.6-18.5 gal/min) Max Operation Pressure 13,707 kPa (1,988 psi) REQUIRES: Machine side: hammer lines and front guards	

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - B6 AND B6 SILENCED FLAT TOP and SIDE MOUNT (Cont.)

W	532-9063	BRACKET, MHE 3T, 40MM, SM-LG 134 Mounting bracket, drill pattern SM + LG, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber $\text{\textcircled{C}}$		\$451 NI
W	532-9088	LINES, B4-B6 HAMMER, 3T 0 FOR USE WITH: B4 or B6 on 303C CR, 303E CR, 303.5D CR, 303.5E CR, 303.5E2, 304D CR, 304E CR, 304E2, 304.5E2		\$208 NI
W	569-5414	BRACKET, MHE 5T 45MM, SM-LG 127 Mounting bracket, drill pattern SM + LG, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber $\text{\textcircled{C}}$		\$451 NI
W	532-9275	BRACKET, MHE 3-5T, MD-LG 99 FOR USE WITH: 3T or 5T MHE REQUIRES: 316-0412 KIT, MOUNTING GROUP SSL 5T for 5T MHE REQUIRES: 249-1145 KIT, MOUNTING GROUP SSL 3T for 3T MHE		\$486 NI
W	532-9067	BRACKET, MHE 8T, 50MM, LG 153 Mounting bracket, drill pattern LG, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber $\text{\textcircled{C}}$		\$451 NI
W	443-7285	BRACKET, 1/4YD PL, LG 143 Mounting bracket, l pattern SM and LG, incl. bolts + nuts FOR USE WITH: 1/4 yard pin-lock quick coupler		\$694 NI
W	532-9089	LINES, B6-B8 HAMMER, 5T-8T 0 FOR USE WITH: 305C CR up to and including 309 CR with pin-on brackets or dedicated quick coupler brackets. FOR USE WITH: B4 on 5T-6T machines		\$208 NI
W	523-3193	TOOL, MOIL, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	523-3195	TOOL, CONE, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	523-3196	TOOL, BLUNT, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	523-3197	TOOL, CHISEL, CROSS CUT, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	523-3191	TOOL, CHISEL, IN LINE, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - B8 AND B8 SILENCED FLAT TOP and SIDE MOUNT

Compatibility table B8 and B8s:

306E, 306E2	+-	>=5Tons - <7Tons	45mm pins
307D, 307E, 307E2	++	>=7Tons - <10Tons	50mm pins
308D, 308E CR, 308E2 CR	++		
Next Generation			
307.5, 308, 309CR	++		
Next Generation			
310	--	10Tons	60mm pins

++= Optimal += Acceptable --= Not Allowed

If no hammer references appear below there are none currently available in your region.

W	532-9208	HAMMER, B8S 711 Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 400-800 , Energy Class 1,150 Joule (848 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 50-90 l/min (13.2-23.8 gal/min) Max Operation Pressure 14,686 kPa (2,130 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines	\$12,361 NI
W	532-9108	HAMMER, B8 724 Non Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 400-800 , Energy Class 1,150 Joule (848 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 50-90 l/min (13.2-23.8 gal/min) Max Operation Pressure 14,686 kPa (2,130 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines	\$11,125 NI
W	532-9308	HAMMER, B8, MHE 8T, 50MM, PO, SM 774 NON Silenced hydraulic hammer, Pin-On Side Mount incl. bucket pins BPM (blows/minute): 400-800 , Energy Class 1,150 Joule (848 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut), connecting lines FOR USE WITH: CHECK compatibility table above for allowed sales models Pin-On, 8Ton 50mm pins platform REQUIRED HYDRAULICS: Min - Max Flow: 50-90 l/min (13.2-23.8 gal/min) Max Operation Pressure 14,686 kPa (2,130 psi) REQUIRES: Machine side: hammer lines and front guards	\$9,750 NI
W	532-9067	BRACKET, MHE 8T, 50MM, LG 153 Mounting bracket, drill pattern LG, incl. bolts + nuts + buck. pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC	\$451 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - B8 AND B8 SILENCED FLAT TOP and SIDE MOUNT (Cont.)

W	532-9089	LINES, B6-B8 HAMMER, 5T-8T 0 FOR USE WITH: 305C CR up to and including 309 CR with pin-on brackets or dedicated quick coupler brackets. FOR USE WITH: B4 on 5T-6T machines		\$208 NI
W	532-9120	TOOL, MOIL, B8 50 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI
W	532-9118	TOOL, CONE, B8 54 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI
W	532-9117	TOOL, BLUNT, B8 54 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI
W	532-9121	TOOL, CHISEL, IN LINE, B8 52 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI
W	532-9119	TOOL, CHISEL, CROSS CUT, B8 52 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI

HAMMERS - B9 AND B9 SILENCED FLAT TOP

Compatibility table B9 and B9s:

307D, 307E, 307E2	++	>=7Tons - <10Tons	50mm pins
308D, 308E CR, 308E2 CR	++		
Next Generation			
307.5, 308, 309CR	++		
Next Generation			
310	++	10Tons	60mm pins

++= Optimal += Acceptable --= Not Allowed

W	532-9209	HAMMER, B9S 1,143 Silenced hydraulic hammer, flat top with drill pattern XL BPM (blows/minute): 400-800 , Energy Class 1,300 Joule (959 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 60-100 l/min (15.8-26.3 gal/min) Max Operation Pressure 15,665 kPa (2,272 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket XL, connecting lines		\$17,917 NI
---	----------	--	--	-------------

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - B9 AND B9 SILENCED FLAT TOP (Cont.)

W	532-9109	HAMMER, B9 1,166 NON Silenced hydraulic hammer, flat top with drill pattern XL BPM (blows/minute): 400-800 , Energy Class 1,300 Joule (959 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 60-100 l/min (15.8-26.3 gal/min) Max Operation Pressure 15,665 kPa (2,272 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket XL, connecting lines		\$16,125 NI
W	564-9840	BRACKET, MHE 8T, 50MM, XL 186 Mounting bracket, drill pattern XL, incl.bolts + nuts + bucket pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC on machines >=7 - <10Tons + 50mm pins: Next Gen, D and E series		\$660 NI
W	564-2732	BRACKET, 1/2YD PL, XL 233 Mounting bracket, incl.bolts + nuts, excl. lines FOR USE WITH: 1/2 yard pin lock quick coupler.		\$1,528 NI
W	564-9843	BRACKET, 10T-BL450, 60-60MM,XL 224 Mounting bracket, drill pattern XL, incl.bolts + nuts + bucket pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC on Next Gen. 310		\$833 NI
W	416-8031	BRACKET, 1/4YD PL, XL 170 Mounting bracket, drill pattern XL, incl.bolts + nuts FOR USE WITH: 1/4 Yard Pin Lock QCs & hammers with XL drill pattern		\$694 NI
W	580-9885	LINES, B9 HAMMER, 7T-10T 24 FOR USE WITH: B9 for 7, 8, 9 and 10 Tons machines pin-on brackets or dedicated quick coupler brackets.		\$451 NI
W	532-9219	TOOL, MOIL, B9 64 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI
W	542-1762	TOOL, CONE, B9 62 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI
W	542-1763	TOOL, BLUNT, B9 68 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI
W	542-1764	TOOL, CHISEL, IN LINE, B9 66 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI
W	542-1765	TOOL, CHISEL, CROSS CUT, B9 66 Diam: 85mm (3.4"), Total Length: 745mm (29.3") Working length: Non silenced / silenced: 409mm (16.1") / 391m (15.4")		\$431 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - H35S SILENCED FLAT TOP

Compatibility table H35s:

301.4C, 301.6C, 301.7D, 301.8C Next Generation	+-	>=1Ton - <=2Tons	30mm pins
301.5, 301.6, 301.7CR, 301.8 302CR	++		
302.2D, 302.4D 302.5C, 302.7D CR	+-	>2Tons - <3Tons	35mm pins
	--		

++= Optimal += Acceptable --= Not Allowed

If no hammer references appear below there are none currently available in your region.

W	561-2548	HAMMER, H35S	214	\$5,833 NI
		Silenced hydraulic hammer, flat top with drill pattern MD BPM (blows/minute): 600-1,800 , Energy Class 407 Joule (300 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 12-35 l/min (3.2-9.2 gal/min) Max Operation Pressure 16,499 kPa (2,393 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket MD, connecting lines		
W	532-9055	BRACKET, MHE 1T, 30MM, SM-MD	55	\$382 NI
		Mounting bracket, drill pattern SM + MD, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC		
W	290-3181	LINES, H35, MHE 1T	24	\$319 NI
		INCLUDES: hose assemblies and required connectors		
W	423-8333	TOOL, CHISEL, INLINE, H35	8	\$160 NI
		Diam.: 40mm (1.6"), Tot./Working Length: 400mm (15.7")/ 240mm (9.5") FOR USE WITH: new H35 and previous H35E		
W	428-8033	TOOL, CHISEL, CROSSCUT, H35	8	\$160 NI
		Diam.: 40mm (1.6"), Tot./Working Length: 400mm (15.7")/ 240mm (9.5") FOR USE WITH: new H35 and previous H35E		
W	423-8334	TOOL, CONE, H35	8	\$160 NI
		Diam.: 40mm (1.6"), Tot./Working Length: 400mm (15.7")/ 240mm (9.5") FOR USE WITH: new H35 and previous H35E		
W	423-8336	TOOL, BLUNT, H35	0	\$160 NI
		Diam.: 40mm (1.6"), Tot./Working Length: 400mm (15.7")/ 240mm (9.5") FOR USE WITH: new H35 and previous H35E		
W	433-9659	TOOL, SPADE PARALLEL, H35	9	\$313 NI
		Diam.: 40mm (1.6"), Length: 400mm (15.7"), Spade width: 108mm (4.3") FOR USE WITH: new H35 and previous H35E		
W	433-9658	TOOL, SPADE TRANSVERSE, H35	9	\$313 NI
		Diam.: 40mm (1.6"), Length: 400mm (15.7"), Spade width: 108mm (4.3") FOR USE WITH: new H35 and previous H35E		

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-------------------------------	--------------------	-------------------------

MHE - HAMMERS (CONT.)

HAMMERS - H35S SILENCED FLAT TOP (Cont.)

W	433-9645	TOOL, COMPACTING PLATE, H35 39 Diam.: 40mm (1.6"), Length: 370mm (14.6"), Bottom width: 203mm (8") FOR USE WITH: new H35 and previous H35E		\$847 NI
---	----------	---	--	-----------------

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - H45S SILENCED FLAT TOP

Compatibility table H45S:

301.4C, 301.6C, 301.7D, 301.8C Next Generation	--	>=1Ton - <=2Tons	30mm pins
301.5, 301.6, 301.7CR, 301.8 302CR	+-		
302.2D, 302.4D 302.5C, 302.7D CR	++	>2Tons - <3Tons	35mm pins
303C CR, 303E CR 303.5D CR, 303.5E CR, 303.5E2 304D CR, 304E CR, 304E2	+- +- --	>=3Tons - <5Tons	40mm pins

++= Optimal +- = Acceptable -- = Not Allowed

If no hammer references appear below there are none currently available in your region.

W	561-2549	HAMMER, H45S 265 Silenced hydraulic hammer, flat top with drill pattern MD BPM (blows/minute): 780-1,800 , Energy Class 542 Joule (400 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 25-62 l/min (6.6-16.4 gal/min) Max Operation Pressure 16,996 kPa (2,465 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket MD, connecting lines		\$7,333 NI
W	532-9057	BRACKET, MHE 2T, 35MM, SM-MD 74 Mounting bracket, drill pattern SM + MD, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC		\$382 NI
W	292-0231	LINES, H45, MHE 2T 24		\$319 NI
W	423-8327	TOOL, CHISEL, INLINE, H45 15 Diam.: 50mm (2"), Tot./Working Length: 475mm (18.7")/ 270mm (10.6") FOR USE WITH: new H45 and previous H45E		\$194 NI
W	428-8025	TOOL, CHISEL, CROSSCUT, H45 15 Diam.: 50mm (2"), Tot./Working Length: 475mm (18.7")/ 270mm (10.6") FOR USE WITH: new H45 and previous H45E		\$194 NI
W	423-8329	TOOL, CONE, H45 15 Diam.: 50mm (2"), Tot./Working Length: 475mm (18.7")/ 270mm (10.6") FOR USE WITH: new H45 and previous H45E		\$194 NI
W	423-8331	TOOL, BLUNT, H45 0 Diam.: 50mm (2"), Tot./Working Length: 475mm (18.7")/ 270mm (10.6") FOR USE WITH: new H45 and previous H45E		\$194 NI
W	433-9657	TOOL, SPADE PARALLEL, H45 15 Diam.: 50mm (2"), Length: 450mm (17.7"), Spade width: 108mm (4.3") FOR USE WITH: new H45 and previous H45E		\$319 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - H45S SILENCED FLAT TOP (Cont.)

W	433-9656	TOOL, SPADE TRANSVERSE, H4515 Diam.: 50mm (2"), Length: 450mm (17.7"), Spade width: 108mm (4.3") FOR USE WITH: new H45 and previous H45E		\$319 NI
W	433-9646	TOOL, COMPACTING PLATE, H4543 Diam.: 50mm (2"), Length: 405mm (16"), Bottom width: 203mm (8") FOR USE WITH: new H45 and previous H45E		\$861 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - H55S SILENCED FLAT TOP

Compatibility table H55S:

303C CR, 303E CR	+-	>=3Tons - <5Tons	40mm pins
303.5C CR, 303.5D CR	++		
303.5E CR, 303.5E2	++		
304D CR, 304E CR, 304E2, 304.5E2	++		
305C CR, 305D CR, 305E CR, 305E2	++	>=5Tons - <7Tons	45mm pins
305.5D CR, 305.5E CR, 305.5E2	++		
306E, 306E2	++		

++= Optimal += Acceptable --= Not Allowed

If no hammer references appear below there are none currently available in your region.

W	561-2551	HAMMER, H55S 459	\$9,493 NI
		Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 600-1,680 , Energy Class 813 Joule (600 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 30-85 l/min (7.9-22.5 gal/min) Max Operation Pressure 16,499 kPa (2,393 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines	
W	532-9063	BRACKET, MHE 3T, 40MM, SM-LG 134	\$451 NI
		Mounting bracket, drill pattern SM or LG, incl.bolts + nuts + buck.pin FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC	
W	569-5414	BRACKET, MHE 5T 45MM, SM-LG 127	\$451 NI
		Mounting bracket, drill pattern SM + LG, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC	
W	532-9275	BRACKET, MHE 3-5T, MD-LG 99	\$486 NI
		FOR USE WITH: 3T or 5T MHE REQUIRES: 316-0412 KIT, MOUNTING GROUP SSL 5T for 5T MHE REQUIRES: 249-1145 KIT, MOUNTING GROUP SSL 3T for 3T MHE	
W	330-5359	LINES, H55, MHE 3-5T 22	\$417 NI
W	423-8310	TOOL, CHISEL, INLINE, H55 24	\$236 NI
		Diam.: 58mm (2.3"), Tot./Working Length: 550mm (21.7")/ 324mm (12.8") FOR USE WITH: new H55 and previous H55E	
W	428-8024	TOOL, CHISEL, CROSSCUT, H55 24	\$236 NI
		Diam.: 58mm (2.3"), Tot./Working Length: 550mm (21.7")/ 324mm (12.8") FOR USE WITH: new H55 and previous H55E	
W	423-8312	TOOL, CONE, H55 23	\$236 NI
		Diam.: 58mm (2.3"), Tot./Working Length: 550mm (21.7")/ 324mm (12.8") FOR USE WITH: new H55 and previous H55E	
W	423-8314	TOOL, BLUNT, H55 0	\$236 NI
		Diam.: 58mm (2.3"), Tot./Working Length: 550mm (21.7")/ 324mm (12.8") FOR USE WITH: new H55 and previous H55E	

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
MHE - HAMMERS (CONT.)				
<i>HAMMERS - H55S SILENCED FLAT TOP (Cont.)</i>				
W	433-9655	TOOL, SPADE PARALLEL, H55 635 Diam.: 58mm (2.3"), Length: 590mm (20.5"), Spade width: 152mm (6") FOR USE WITH: new H55 and previous H55E		\$458 NI
W	433-9654	TOOL, SPADE TRANSVERSE, H55 22 Diam.: 58mm (2.3"), Length: 590mm (20.5"), Spade width: 152mm (6") FOR USE WITH: new H55 and previous H55E		\$458 NI
W	433-9648	TOOL, COMPACTING PLATE, H55 82 Diam.: 58mm (2.3"), Length: 430mm (16.9"), Bottom width: 305mm (12") FOR USE WITH: new H55 and previous H55E		\$1,465 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - H65S SILENCED FLAT TOP

Compatibility table H65S:

303C CR, 303E CR	--	>=3Tons - <5Tons	40mm pins
303.5C CR, 303.5D CR	--		
303.5E CR, 303.5E2	--		
304D CR, 304E CR, 304E2, 304.5E2	--		
305C CR, 305D CR, 305E CR, 305E2	++	>=5Tons - <7Tons	45mm pins
305.5D CR, 305.5E CR, 305.5E2	++		
306E, 306E2	++		
307D, 307E, 307E2	+-	>=7Tons - <10Tons	50mm pins
308D, 308E CR, 308E2 CR	+-		
Next Generation			
307.5, 308, 309CR	+-		

++= Optimal +- = Acceptable -- = Not Allowed

If no hammer references appear below there are none currently available in your region.

W	561-2552	HAMMER, H65S 534	\$11,167 NI
		Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 720-1,740 , Energy Class 1,085 Joule (800 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 40-115 l/min (10.6-30.4 gal/min) Max Operation Pressure 16,499 kPa (2,393 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines	
W	569-5414	BRACKET, MHE 5T 45MM, SM-LG 127	\$451 NI
		Mounting bracket, drill pattern SM + LG, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC	
W	532-9275	BRACKET, MHE 3-5T, MD-LG 99	\$486 NI
		FOR USE WITH: 3T or 5T MHE REQUIRES: 316-0412 KIT, MOUNTING GROUP SSL 5T for 5T MHE REQUIRES: 249-1145 KIT, MOUNTING GROUP SSL 3T for 3T MHE	
W	443-7285	BRACKET, 1/4YD PL, LG143	\$694 NI
		Mounting bracket, 1 pattern SM and LG, incl. bolts + nuts FOR USE WITH: 1/4 yard pin-lock quick coupler	
W	270-8682	LINES, H55-H65, MHE 5T15	\$319 NI
		FOR USE WITH: 305D CR, 305E CR, 305.5D CR, 305.5E CR, 306E, 306E2	
W	532-9067	BRACKET, MHE 8T, 50MM, LG153	\$451 NI
		Mounting bracket, drill pattern LG, incl.bolts + nuts + buck.pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC	
W	353-8830	LINES, H65, MHE 8T 22	\$417 NI
		FOR USE WITH: 307D, 307E, 307E2, 308D CR, 308E CR, 308E2 CR	

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - H65S SILENCED FLAT TOP (Cont.)

W	423-8307	TOOL, CHISEL, INLINE, H65 38 Diam.: 68mm (2.7"), Tot./Working Length: 650mm (25.6")/ 371mm (14.6") FOR USE WITH: new H65 and previous H65E		\$264 NI
W	428-8022	TOOL, CHISEL, CROSSCUT, H65 38 Diam.: 68mm (2.7"), Tot./Working Length: 650mm (25.6")/ 371mm (14.6") FOR USE WITH: new H65 and previous H65E		\$264 NI
W	423-8308	TOOL, CONE, H65 38 Diam.: 68mm (2.7"), Tot./Working Length: 650mm (25.6")/ 371mm (14.6") FOR USE WITH: new H65 and previous H65E		\$264 NI
W	423-8309	TOOL, BLUNT, H65 0 Diam.: 68mm (2.7"), Tot./Working Length: 650mm (25.6")/ 371mm (14.6") FOR USE WITH: new H65 and previous H65E		\$264 NI
W	433-9653	TOOL, SPADE PARALLEL, H65 33 Diam.: 68mm (2.7"), Length: 615mm (22.4"), Spade width: 152mm (6") FOR USE WITH: new H65 and previous H65E		\$465 NI
W	433-9652	TOOL, SPADE TRANSVERSE, H65 33 Diam.: 68mm (2.7"), Length: 615mm (22.5"), Spade width: 152mm (6") FOR USE WITH: new H65 and previous H65E		\$465 NI
W	433-9651	TOOL, COMPACTING PLATE, H65 90 Diam.: 68mm (2.7"), Length: 495mm (19.5"), Bottom width: 305mm (12") FOR USE WITH: new H65 and previous H65E		\$1,465 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - H80S SILENCED FLAT TOP

Compatibility table H80S:

307D, 307E, 307E2	++	>=7Tons - <10Tons 50mm pins
308D, 308E CR, 308E2 CR	++	
Next Generation		
307.5, 308, 309CR	++	

++= Optimal += Acceptable --= Not Allowed

If no hammer references appear below there are none currently available in your region.

W	561-2553	HAMMER, H80S 725 Silenced hydraulic hammer, flat top with drill pattern XL BPM (blows/minute): 600-1,500 , Energy Class 1,365 Joule (1,000 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 60-130 l/min (16-34 gal/min) Max Operation Pressure 17,500 kPa (2,500 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket XL, connecting lines		\$16,667 NI
W	564-9840	BRACKET, MHE 8T, 50MM, XL 186 Mounting bracket, drill pattern XL, incl. nuts+bolts & bucket pin FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC		\$660 NI
W	564-2732	BRACKET, 1/2YD PL, XL 233 Mounting bracket, incl.bolts + nuts, excl. lines FOR USE WITH: 1/2 yard pin lock quick coupler.		\$1,528 NI
W	308-0324	PINS, BUCKET, 50MM 25 Full set of bucket pins 50mm diameter		\$125 NI
W	564-9843	BRACKET, 10T-BL450, 60-60MM,XL 224 Mounting bracket with drill pattern XL, incl. nuts,bolts & bucket pins FOR USE WITH: Next Generation 310		\$833 NI
W	416-8031	BRACKET, 1/4YD PL, XL 170 Mounting bracket, incl. bolts + nuts, excl. lines FOR USE WITH: 1/4 yard pin lock quick coupler		\$694 NI
W	397-2420	LINES, H80-H95, MHE 8T-10T 15 FOR USE WITH: H80/H80E and H95/H95E.		\$417 NI
W	376-7947	TOOL, BLUNT, H80 0 Diam.: 74.5mm (2.9"), Tot./Working Length: 775mm (30.5")/ 356mm (14") FOR USE WITH: new H80 and previous H80E		\$389 NI
W	399-1711	TOOL, CHISEL, CROSSCUT, H80 55 Diam.: 74.5mm (2.9"), Tot./Working Length: 775mm (30.5")/ 356mm (14") FOR USE WITH: new H80 and previous H80E		\$389 NI
W	369-1549	TOOL, CHISEL, INLINE, H80 55 Diam.: 74.5mm (2.9"), Tot./Working Length: 775mm (30.5")/ 356mm (14") FOR USE WITH: new H80 and previous H80E		\$389 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - H80S SILENCED FLAT TOP (Cont.)

W	369-1548	TOOL, CONE, H80 54 Diam.: 74.5mm (2.9"), Tot./Working Length: 775mm(30.5")/ 376mm(14.8") FOR USE WITH: new H80 and previous H80E		\$389 NI
W	381-6720	TOOL, SPADE PARALLEL, H80 44 Diam.: 74.5mm (2.9"), Length: 720mm (28.3"), Spade width: 152mm (6") FOR USE WITH: new H80 and previous H80E		\$556 NI
W	381-6719	TOOL, SPADE TRANSVERSE, H80 50 Diam.: 74.5mm (2.9"), Length: 720mm (28.3"), Spade width: 152mm (6") FOR USE WITH: new H80 and previous H80E		\$556 NI
W	381-6721	TOOL, COMPACTING PLATE, H80 104 Diam.: 74.5mm (2.9"), Length: 615mm (22"), Bottom width: 305mm (12") FOR USE WITH: new H80 and previous H80E / H75E		\$1,743 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - H95S SILENCED FLAT TOP

Compatibility table H95S:

307D, 307E, 307E2	++	>=7Tons - <10Tons	50mm pins
308D, 308E CR, 308E2 CR	++		
Next Generation			
307.5, 308, 309CR	++		
Next Generation			
310	++	10Tons	60mm pins

++= Optimal +-= Acceptable ---= Not Allowed

If no hammer references appear below there are none currently available in your region.

W	561-2555	HAMMER, H95S 1,109	\$24,583 NI
		Silenced hydraulic hammer, flat top with drill pattern XL BPM (blows/minute): 700-1,260 , Energy Class 2,034 Joule (1,500 ft lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 70-150 l/min (18.5-39.6 gal/min) Max Operation Pressure 17,237 kPa (2,500 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket XL, connecting lines	
W	564-9840	BRACKET, MHE 8T, 50MM, XL 186	\$660 NI
		Mounting bracket, drill pattern XL, incl. nuts+bolts & bucket pins FOR USE WITH: Pin-On stick mounted or with dual lock Pin grabber QC	
W	564-2732	BRACKET, 1/2YD PL, XL 233	\$1,528 NI
		Mounting bracket, incl.bolts + nuts, excl. lines FOR USE WITH: 1/2 yard pin lock quick coupler.	
W	564-9843	BRACKET, 10T-BL450, 60-60MM,XL 224	\$833 NI
		Mounting bracket with drill pattern XL, incl. nuts+bolts & bucket pins FOR USE WITH: Next Generation 310 REQUIRES: 1 x 556-3635 PINS, 60mm SPARE if a pin-grabber QC is used	
W	556-3635	PINS, 60MM, MHE 10T-BHL 450 36	\$153 NI
		Includes 60mm diam bucket pins and hardware FOR USE WITH: New generation 310	
W	416-8031	BRACKET, 1/4YD PL, XL 170	\$694 NI
		Mounting bracket, incl. bolts + nuts, excl. lines FOR USE WITH: 1/4 yard pin lock quick coupler	
W	393-7732	BRACKET, STEX 65MM, XL 231	\$1,458 NI
		Mounting bracket, drill pattern XL, incl.bolts + nuts, excl buck.pins FOR USE WITH: 311D RR, 311F RR, 312D, 312D L, 312D2, 312D2 L, 312E, 312E L, 312F L, 312FL GC, 313FL GC 313D2. REQUIRES: 2x 086-0523 Bucket pins, 2x 099-0724 Bolt + 4x 096-4876 Nut	
W	397-2420	LINES, H80-H95, MHE 8T-10T 15	\$417 NI
		FOR USE WITH: H80/H80E and H95/H95E	

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - HAMMERS (CONT.)

HAMMERS - H95S SILENCED FLAT TOP (Cont.)

W	399-1710	TOOL, CHISEL, CROSSCUT, H95 84 Diam.: 87.5mm (3.4"), Tot./Working Length: 875mm(34.5")/416mm(16.4") FOR USE WITH: new H95 and previous H95E		\$500 NI
W	369-0793	TOOL, CHISEL, INLINE, H95 84 Diam.: 87.5mm (3.4"), Tot./Working Length: 875mm(34.5")/416mm(16.4") FOR USE WITH: new H95 and previous H95E		\$500 NI
W	369-0792	TOOL, CONE, H95 84 Diam.: 87.5mm (3.4"), Tot./Working Length: 875mm(34.5")/416mm(16.4") FOR USE WITH: new H95 and previous H95E		\$500 NI
W	373-7159	TOOL, BLUNT, H95 0 Diam.: 87.5mm (3.4"), Tot./Working Length: 875mm(34.5")/416mm(16.4") FOR USE WITH: new H95 and previous H95E		\$500 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - SSL ATTACHMENTS FOR XTC MACHINES

APPROVED ATTACHMENTS WITH SSL INTERFACE for XTC:

These work tools are to be used on machines equipped with the XTC quick coupler which takes attachments with SSL interface.

W	487-2025	BLADE, 78", WELD-ON 0 Overall width 2030mm (80"), Weld-on Edge width 1980mm (78") Overall height 610mm (24") FOR USE WITH: Skid Steer Coupler		\$1,333 NI
W	426-6536	BUCKET-MP, 74", BOCE 962 Width over base edge 1883mm (74"), 0.37 m3 (13.0ft3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge, spillguard to prevent material spillage over back of bucket. FOR USE WITH: Skid Steer Coupler		\$4,639 NI
W	426-6548	BUCKET-MP, 80", BOCE 1,016 Width over base edge 2036mm (80"), 0.40 m3 (14.1ft3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge, spillguard to prevent material spillage over back of bucket. FOR USE WITH: Skid Steer Coupler		\$4,972 NI
W	279-5377	BUCKET-GP, 80", BOCE 631 Width 1980mm (78"), 0.48 m3 (17.0ft3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge FOR USE WITH: Skid Steer Coupler		\$1,881 NI
W	261-1350	CARRIAGE, PAL CL2, 51", SSL 249 Standard Class II carriage, 55" (1400mm) wide FOR USE WITH: Skid Steer Coupler REQUIRES: 2 Tines (Forks) Class II, NOT INCLUDED		\$1,447 NI
W	351-9371	CARRIAGE, PAL C2, 46", SSL 207 Standard Hook Carriage, Overall Carriage width step, 1270mm (50") REQUIRES: 2 Forks/Tines NOT included		\$611 NI
W	195-6942	FORK, PAL C2, 42" X 4" X 1.5" 104 40 x 100 x 1070mm (1.5" x 4" x 42") Pull Type Order quantity of 2 for a pair. FOR USE WITH: 261-1350 or 351-9371		\$208 NI
W	177-1990	BLADE, ANGLE, 84" 730 2134mm (84") overall width, 610mm (24") blade height 4 Trip Springs, 2 Heavy Duty Adjustable Skid Feet INCLUDES: Hydraulic lines with quick disconnects, mounting bracket and hardware, 1 piece Bolt-On Cutting Edge FOR USE WITH: Skid Steer Coupler REQUIRES: Standard Flow Hydraulics		\$3,722 NI
W	233-2346	TRENCHER, T112, MAN. 6" STANDARD 1,076 48" (1219mm) Boom, MANUAL side sift, Trench depth: 48" (1219mm) with boom angle of 60 degrees Standard chain included, 6" (152mm) cutting width FOR USE WITH: Skid Steer Coupler REQUIRES: Standard Flow Hydraulics		\$5,833 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - SSL ATTACHMENTS FOR XTC MACHINES (CONT.)

APPROVED ATTACHMENTS WITH SSL INTERFACE for XTC: (Cont.)

W	277-8210	POWER BOX RAKE-MANUAL, PR172 900 Width overall - working: 2057mm (81") - 1829mm (72") MANUAL angling: +/- 20 degrees over center FOR USE WITH: Skid Steer Coupler REQUIRES: Standard Flow hydraulics, 49-86 l/min (13-23 gpm) at 230 bar (3,340 psi)		\$10,368 NI
W	448-5660	BROOM, MANUAL ANGLE, BA118C 905 MANUAL Angling - 30 degrees left or right of center Sweeping width straight / angled : 2119mm (83") / 1849mm (73") Brush: material - 50% polypropylene / 50% steel wire Brush diameter: 815mm (32") INCLUDES: hydraulic lines with 1/2" quick disconnects, mounting bracket and hardware FOR USE WITH: Skid Steer Coupler REQUIRES: Standard Flow Hydraulics		\$7,819 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - SSL TO MHE ADAPTER / QUICK COUPLER

SSL to MHE ADAPTER / QUICK COUPLER

Compatibility table for which sales model MHE are allowed to use the SSL to MHE adapter:

Machines	>=3T - <5T 525-5854	>=5T - <7T 542-7262	>=7T - <10T 542-7263
303C CR, 303E CR	--	NA	NA
303.5D CR, 303.5E CR, 303.5E2	--	NA	NA
304D CR, 304E CR, 304E2	--	NA	NA
304.5E2	++	NA	NA
305C CR, 305D CR,	NA	++	NA
305E CR, 305E2	NA	++	NA
305.5D CR, 305.5E CR, 305.5E2	NA	++	NA
306E, 306E2	NA	++	NA
Next Generation			
306, 306.5, 306.6CR SB	NA	++	NA
307D, 307E, 307E2	NA	NA	++
308D, 308E, 308E2 CR	NA	NA	++
Next Generation			
307.5, 308, 309CR	NA	NA	++

++= Approved ---= Not Approved NA = Not Applicable

If no references appear below there are no items currently available in your region.

W	525-5854	COUPLER, SSL, MHE 3-4T247 Adapter to connect approved SSL attachments to MHE machines. FOR USE WITH: 304.5E2 only and approved attachments only	\$1,597 NI
W	542-7262	COUPLER, SSL, MHE 5-6T262 Adapter to connect approved SSL attachments to MHE machines. FOR USE WITH: Approved attachments only	\$1,667 NI
W	542-7263	COUPLER, SSL, MHE 7-9T311 Adapter to connect approved SSL attachments to MHE machines. FOR USE WITH: Approved attachments only	\$1,736 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - SSL TO MHE ADAPTER / QUICK COUPLER (CONT.)

SSL GP BUCKETS for SSL to MHE ADAPTER / QUICK COUPLER

Compatibility table for SSL GP buckets to be used on MHE
 >=3T - <5T | >=5T - <7T | >=7T - <10T
 SSL to MHE adapter 525-5854 | 542-7262 | 542-7263

1576mm (62", old 60")	++	++	++
1730mm (68", old 66")	--	++	++
1883mm (74", old 72")	--	++	++
2036mm (80", old 78")	--	--	++
2188mm (86", old 84")	--	--	++

++ = Approved / -- = NOT Approved

If no references appear below there are no items currently available in your region.

W	279-5364	BUCKET-GP, 62", BASE EDGE 448 Width over base edge 1576mm (62"), 0.36 m3 (12.7ft3) Heaped Capacity INCLUDES: Base Edge with drilled mounting holes	\$1,267 NI
W	279-5365	BUCKET-GP, 62", BOCE 448 Width over base edge 1576mm (62"), 0.36 m3 (12.7ft3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge	\$1,474 NI
W	279-5366	BUCKET-GP, 62", BOT 448 Width over base edge 1576mm (62"), 0.36 m3 (12.7ft3) Heaped Capacity INCLUDES: 8 Single Strap Bolt-on Uniteeth	\$1,544 NI
W	279-5368	BUCKET-GP, 68", BASE EDGE 561 Width over base edge 1730mm (68"), 0.40 m3 (14.1ft3) Heaped Capacity INCLUDES: Base Edge with drilled mounting holes	\$1,382 NI
W	279-5369	BUCKET-GP, 68", BOCE 561 Width over base edge 1730mm (68"), 0.40 m3 (14.1ft3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge	\$1,608 NI
W	279-5370	BUCKET-GP, 68", BOT 561 Width over base edge 1730mm (68"), 0.40 m3 (14.1ft3) Heaped Capacity INCLUDES: 8 Single Strap Bolt-on Uniteeth	\$1,660 NI
W	279-5372	BUCKET-GP, 74", BASE EDGE 597 Width over base edge 1883mm (74"), 0.44 m3 (15.5ft3) Heaped Capacity INCLUDES: Base Edge with drilled mounting holes	\$1,499 NI
W	279-5373	BUCKET-GP, 74", BOCE 597 Width over base edge 1883mm (74"), 0.44 m3 (15.5ft3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge	\$1,744 NI
W	279-5374	BUCKET-GP, 74", BOT 597 Width over base edge 1883mm (74"), 0.44 m3 (15.5ft3) Heaped Capacity INCLUDES: 8 Single Strap Bolt-on Uniteeth	\$1,776 NI
W	279-5376	BUCKET-GP, 80", BASE EDGE 631 Width over base edge 2036mm (80"), 0.48 m3 (17.0ft3) Heaped Capacity INCLUDES: Base Edge with drilled mounting holes	\$1,614 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - SSL TO MHE ADAPTER / QUICK COUPLER (CONT.)

SSL GP BUCKETS for SSL to MHE ADAPTER / QUICK COUPLER (Cont.)

W	279-5377	BUCKET-GP, 80", BOCE 631 Width 1980mm (78"), 0.48 m3 (17.0ft3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge		\$1,881 NI
W	279-5378	BUCKET-GP, 80", BOT 631 Width over base edge 2036mm (80"), 0.48 m3 (17.0ft3) Heaped Capacity INCLUDES: 9 Single Strap Bolt-on Uniteeth		\$1,926 NI
W	292-9270	BUCKET-GP, 86", BASE EDGE 635 Width over base edge 2188mm (86"), 0.63 m3 (22.2ft3) Heaped Capacity INCLUDES: Base Edge with drilled mounting holes		\$1,729 NI
W	296-8192	BUCKET-GP, 86", BOCE 723 Width over base edge 2188mm (86"), 0.63 m3 (22.2ft3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge		\$2,017 NI
W	296-8191	BUCKET-GP, 86", BOT 669 Width over base edge 2188mm (86"), 0.63 m3 (22.2ft3) Heaped Capacity INCLUDES: 9 Single Strap Bolt-on Uniteeth		\$2,042 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - NON CURRENT MODELS

This section contains a very limited selection of work tools for non-current MHE with different pins sizes and or spread compared to current MHE Sales Models.

BRACKETS, MOUNTING GROUPS and LINES

W	249-1144	KIT, MOUNTING GROUP SSL 2T 8 Mounting group including 2 bucket pins, 4 renten.pins and 4 bushings FOR USE WITH: H55E Pin-On to fit 302.5C or 302.7D pin-on REQUIRES: 270-8680 LINES, CONNECTING		\$208 NI
W	211-8189	LINES, CVP40, 7-8T, A-C 31 INCLUDES: hose assemblies, quick disconnects and required connectors FOR USE WITH: CVP40 on 307/308 A,B and C series		\$771 NI
W	313-6573	LINES, H65DS, 7-8T, A-C 22 INCLUDES: hose assemblies, quick disconnects and required connectors FOR USE WITH: H65Ds on 307/308 A,B and C series		\$493 NI
W	249-1145	KIT, MOUNTING GROUP SSL 3T 9 Mounting group including 2 bucket pins, 4 renten.pins and 4 bushings FOR USE WITH: H55E Pin-On to fit Models: 303C CR, 303E CR, 303.5C CR, 303.5D CR, 303.5E CR, 303.5E2, 304D CR, 304E CR, 304E2, 304.5E2 FOR USE WITH: H65E Pin-On to fit Models: 303.5C CR, 303.5D CR, 303.5E CR, 303.5E2, 304D CR, 304E CR, 304E2, 304.5E2 REQUIRES: 270-8681 LINES, CONNECTING		\$208 NI
W	316-0412	KIT, MOUNTING GROUP SSL 5T 22 Mounting group including 2 bucket pins, 4 renten.pins and 4 bushings FOR USE WITH: H55E/H65E Pin-On to fit Models: 305E CR, 305.5D CR, 305.5E CR, 306E, 306E2 REQUIRES: 270-8682 LINES, CONNECTING		\$208 NI
W	374-2080	LINES, H25, MHE 300.9D 22 INCLUDES: hose assemblies, quick disconnects and required connectors FOR USE WITH: 300.9D with any stick.		\$319 NI
W	270-8680	LINES, H55D, PO, 2T, STD STICK 13 INCLUDES: hose assemblies, quick disconnects and required connectors FOR USE WITH: H55E Pin-On on 302.5C or 302.7D pin-on		\$319 NI
W	270-8681	LINES, H55D, PO, 2T, LONG STICK 15 INCLUDES: hose assemblies, quick disconnects and required connectors FOR USE WITH: H55E/H65E pin-on		\$319 NI
W	330-5361	LINES, H55, MHE 4-5T, LONG 22 FOR USE WITH: 304CR and 305CR with long stick		\$1,007 NI
W	270-8682	LINES, H55-H65, MHE 5T 15 INCLUDES: hose assemblies, quick disconnects and required connectors FOR USE WITH: H55E/H65E pin-on		\$319 NI
W	252-1211	KIT, MOUNTING GRP, H65D 40MM 22 Kit with pins and bushings to convert H65D Pin-on. FOR USE WITH: H65D Pin-On and 303C CR-303.5E2 & 304D CR-304.5E2		\$389 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - NON CURRENT MODELS (CONT.)

BRACKETS, MOUNTING GROUPS and LINES (Cont.)

W	283-1502	KIT, MOUNTING GRP, H65D 45MM 22 Kit with pins and bushings to convert H65D Pin-on. FOR USE WITH: H65D Pin-On and 304C CR, 305C CR--306E2 CR		\$486 NI
W	371-6751	BRACKET, MHE <1T 25MM, XS 62 FOR USE WITH: Hammers Flat Top with drill pattern XS and Pin-On mounted to 300.9D REQUIRES: buckets pins		\$417 NI
W	318-2265	BRACKET, MHE 8T 50MM, H63-H90 176 Incl bolts and nuts, excl. connecting lines, excl. bucket pins FOR USE WITH: H63, H70, H90C and 307D--307E2, 308D--308E2		\$2,146 NI
W	219-0667	BRACKET, STEX 65MM, H90C 231 FOR USE WITH: H90C and 311F		\$2,486 NI
W	316-0411	KIT, MOUNTING GRP, H55D 40MM 22 Kit with pins and bushings to convert H55D Pin-on FOR USE WITH: H55D Pin-On and 304 CR and 305 CR		\$486 NI
W	441-0350	BRACKET, MHE 304 CR, SM-LG 110 Incl bolts and nuts, excl. connecting lines, excl. bucket pins FOR USE WITH: B6, H35E--H65E and 304 CR and 305 CR		\$1,972 NI
W	398-9920	BRACKET, MHE 8T 45MM, XL 157 Incl bolts and nuts, excl. connecting lines, excl. bucket pins FOR USE WITH: H75E, H80E, H95E and 307--307C, 308--308C		\$2,097 NI
W	308-7541	BRACKET, MHE 5T 45MM, XL 132 Incl bolts and nuts, excl. connecting lines, excl. bucket pins FOR USE WITH: H80E, H95E, H65D and 304C CR, 305C CR--306E2 CR		\$2,097 NI
W	168-8703	BRACKET, MHE 3T 40MM, 380-340 101 Incl bolts and nuts, excl. connecting lines, excl. bucket pins FOR USE WITH: H63 and 304C CR, 305C CR--306E2 CR		\$1,139 NI
W	277-8941	BRACKET, MHE 5T 45MM, 380-340 104 Incl bolts and nuts, excl. connecting lines, excl. bucket pins FOR USE WITH: H63 and 304C CR, 305C CR--306E2 CR		\$1,417 NI

302.5C - THUMB, HYDRAULIC

W	291-1429	THUMB, HYDRAULIC, 302.5C 148 No-link style INCLUDES: Thumb group with 2 teeth. REQUIRES: Auxiliary lines group with two-way flow functionality REQUIRES: Machine with thumb ready stick or separate mounting bracket FOR USE WITH: Machine with serial numbers GBB00806 and up.		\$2,403 NI
W	204-4972	BRACKET, MOUNTING 7 INCLUDES: Bracket and spacers Required if machine is not equipped with 270-6364 or 270-6366 stick.		\$347 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - NON CURRENT MODELS (CONT.)

303CR AND 303.5 - BUCKETS, DITCH CLEANING

W	174-2460	BUCKET-DC, 40", 3.9 FT3, 40MM 236 0.11m3 (3.9ft3) Heaped Capacity, includes rear edge FOR USE WITH: Pin-on, requires bucket pins		\$944 NI
W	174-2461	BUCKET-DC, 47", 4.8 FT3, 40MM 222 0.14m3 (4.8ft3) Heaped Capacity, includes rear edge FOR USE WITH: Pin-on, requires bucket pins		\$1,097 NI
W	174-1811	BUCKET-DC, 55", 5.6 FT3, 40MM 249 0.16m3 (5.6 ft3) Heaped Capacity, includes rear edge FOR USE WITH: Pin-on, requires bucket pins		\$1,243 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	------------------------	--------------------	-------------------------

MHE - NON CURRENT MODELS (CONT.)**304CR, 304.5 AND 305CR - BUCKETS, HEAVY DUTY**

W	303-1317	BUCKET, HD, 12"	155	\$1,067 NI
		INCLUDES: 3 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		
W	303-1318	BUCKET, HD, 16"	175	\$1,113 NI
		INCLUDES: 3 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		
W	303-1319	BUCKET, HD, 18"	194	\$1,146 NI
		INCLUDES: 4 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		
W	303-1320	BUCKET, HD, 20"	213	\$1,276 NI
		INCLUDES: 5 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		
W	303-1321	BUCKET, HD, 24"	238	\$1,376 NI
		INCLUDES: 5 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		
W	303-1322	BUCKET, HD, 30"	280	\$1,490 NI
		INCLUDES: 5 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		
W	303-1323	BUCKET, HD, 36"	324	\$1,607 NI
		INCLUDES: 6 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		

304CR, 304.5 AND 305CR - BUCKETS, HEAVY DUTY LARGE CAPACITY

W	303-1337	BUCKET-HDC, 12", 2.9 FT ³ , 40MM	185	\$1,175 NI
		INCLUDES: 3 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		
W	303-1338	BUCKET-HDC, 16", 3.7 FT ³ , 40MM	205	\$1,222 NI
		INCLUDES: 3 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		
W	303-1339	BUCKET-HDC, 18", 4.4 FT ³ , 40MM	226	\$1,258 NI
		INCLUDES: 4 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		
W	303-1340	BUCKET-HDC, 20", 5.1 FT ³ , 40MM	246	\$1,404 NI
		INCLUDES: 5 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		
W	303-1341	BUCKET-HDC, 24", 6.4 FT ³ , 40MM	275	\$1,514 NI
		INCLUDES: 5 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		
W	303-1342	BUCKET-HDC, 30", 8.5 FT ³ , 40MM	322	\$1,639 NI
		INCLUDES: 5 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		
W	303-1343	BUCKET-HDC, 36", 10.6FT ³ , 40MM	370	\$1,699 NI
		INCLUDES: 6 J200 long tooth tips		
		FOR USE WITH: Pin-on, requires bucket pins		

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-------------------------------	--------------------	-------------------------

MHE - NON CURRENT MODELS (CONT.)

304CR, 304.5 AND 305CR - BUCKETS, DITCH CLEANING

W	180-1356	BUCKET-DC, 51", 6.5 FT3, 40MM 0.18m3 (6.5 ft3) Heaped Capacity FOR USE WITH: Pin-on, requires bucket pins	253	\$1,215 NI
---	----------	--	-----	-------------------

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - NON CURRENT MODELS (CONT.)

307C AND 308C - COUPLER, PIN LOCK

W	226-1127	COUPLER, PIN LOCK, MHE 7-8T C	166	\$4,938 NI
		REQUIRES: Buckets with dedicated hinges for Pin Lock		
W	226-1128	COUPLER, TILTING PIN LOCK	260	\$10,986 NI
		REQUIRES: Buckets with dedicated hinges for Pin Lock		

TOOLS FOR NON-CURRENT HAMMERS

W	373-9233	TOOL, CONE, H25D	7	\$139 NI
		Diam.: 36mm (1.4"), Tot./Working Length: 360mm (14.2")/ 207mm (8.2")		
W	373-1609	TOOL, CHISEL, INLINE, H25D	0	\$139 NI
		Diam.: 36mm (1.4"), Tot./Working Length: 360mm (14.2")/ 207mm (8.2")		

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - AUGER BITS

MHE - AUGER BITS

STANDARD FLIGHTS

Standard Duty, Approx. 50" (1270mm) Length, HEX Shaft, Double Flight
 Bit teeth are hardened, reversible and forged from medium carbon alloy steel. Teeth are held in place by bolt and nut.

Bit/Flight compatibility matrix vs Auger drive unit

Diam	mm	102	152	229	305	380	457	610	762	914
	inch	4	6	9	12	15	18	24	30	36

A11	Standard	++	++	++	++	++	++	NA	NA	NA
A23	Standard	++	++	++	++	++	++	++	+-	NA
A41	Standard	++	++	++	++	++	++	++	++	+-
A68	Standard	++	++	++	++	++	++	++	++	++

Qty	teeth #	0	2	4	4	5	6	8	10	12
-----	---------	---	---	---	---	---	---	---	----	----

++ = good performance, +- = acceptable performance, NA = Not Allowed
 # = 1 pilot point per flight, not included in teeth count

If no reference numbers appear below there are currently no items available in your region.

W	366-7751	BIT, AUGER 4"	40	\$375 NI
W	153-4083	BIT, AUGER 6"	50	\$375 NI
W	153-4084	BIT, AUGER 9"	75	\$493 NI
W	153-4085	BIT, AUGER 12"	100	\$618 NI
W	366-7752	BIT, AUGER 15"	109	\$750 NI
W	153-4086	BIT, AUGER 18"	144	\$875 NI
W	153-4089	BIT, AUGER 24"	200	\$1,125 NI
W	217-3194	BIT, AUGER 30"	212	\$1,368 NI
W	153-4091	BIT, AUGER 36"	380	\$1,604 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - AUGER BITS (CONT.)

MHE - AUGER BITS (Cont.)

ROCK HEAD FOR STANDARD FLIGHTS

Transforms standard auger bit to rock drill bit by mounting bolt-on rock head to standard bit. Rotating bits (similar to cold planer bits) extend life and provide better penetration into rocky conditions. Bolt-on rock head can be quickly installed and removed depending on ground conditions for maximum versatility.

Bit/Flight compatibility matrix vs Auger drive unit

Diam	mm	152	229	305	380	457	610
	inch	6	9	12	15	18	24

A11	Rock Head	NA	NA	NA	NA	NA	NA
A23	Rock Head	++	++	++	+-	+-	+-
A68	Rock Head	++	++	++	++	++	++

Qty	teeth #	8	10	12	14	16	20
-----	---------	---	----	----	----	----	----

++ = good performance, +- = acceptable performance, NA = Not Allowed
 # = 1 pilot point per flight, included in teeth count (4 pcs)

If no reference numbers appear below there are currently no items available in your region.

W	372-0230	ROCK HEAD, 6" BOLT-ON	23	\$278 NI
		FOR USE WITH: 153-4083 Auger flight		
W	372-0231	ROCK HEAD, 9" BOLT-ON	33	\$354 NI
		FOR USE WITH: 153-4084 Auger flight		
W	372-0232	ROCK HEAD, 12", BOLT-ON	41	\$438 NI
		FOR USE WITH: 153-4085 Auger flight		
W	372-0233	ROCK HEAD, 15" BOLT-ON	47	\$514 NI
		FOR USE WITH: 366-7752 Auger flight		
W	372-0234	ROCK HEAD, 18", BOLT-ON	55	\$590 NI
		FOR USE WITH: 153-4086 Auger flight		
W	372-0235	ROCK HEAD, 24", BOLT-ON	79	\$750 NI
		FOR USE WITH: 153-4089 Auger flight		

Optional replacement teeth available through Parts only:
 372-0259 Standard Rock Drill Head Tooth

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-------------------------------	-----------------	----------------------

MHE - AUGER BITS (CONT.)

MHE - AUGER BITS (Cont.)

INDUSTRIAL FLIGHTS

Bit/Flight compatibility matrix vs Auger drive unit

Diam	mm	152	229	305	405	457	610	762	914	1067	1219
	inch	6	9	12	16	18	24	30	36	42	48

A11	Industrial	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
A23	Industrial	++	++	++	+-	+-	+-	+-	NA	NA	NA
A41	Industrial	++	++	++	+-	+-	+-	+-	+-	+-	+-
A68	Industrial	++	++	++	++	++	++	++	++	++	++

Qty	teeth #	2	4	4	6	6	8	10	12	16	18
-----	---------	---	---	---	---	---	---	----	----	----	----

++ = good performance, +- = acceptable performance, NA = Not Allowed
 # = 1 pilot point per flight, NOT included in teeth count

If no reference numbers appear below there are currently no items available in your region.

W	372-0260	BIT, AUGER 6" INDUSTRIAL	57	\$521 NI
W	372-0261	BIT, AUGER 9" INDUSTRIAL	72	\$639 NI
W	372-0262	BIT, AUGER 12" INDUSTRIAL	91	\$757 NI
W	372-0263	BIT, AUGER 16" INDUSTRIAL	114	\$917 NI
W	372-0264	BIT, AUGER 18" INDUSTRIAL	107	\$1,000 NI
W	372-0265	BIT, AUGER 24", INDUSTRIAL	151	\$1,236 NI
W	372-0266	BIT, AUGER 30" INDUSTRIAL	180	\$1,472 NI
W	372-0267	BIT, AUGER 36" INDUSTRIAL	223	\$1,708 NI
W	372-0268	BIT, AUGER 42" INDUSTRIAL	289	\$2,493 NI
W	372-0269	BIT, AUGER 48" INDUSTRIAL	343	\$2,736 NI

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - AUGER BITS (CONT.)

MHE - AUGER BITS (Cont.)

INDUSTRIAL ROCK FLIGHT

Industrial Rock Flights, approx. 1220mm (48") length, HEX shaft, for heavy duty applications. The thickness of the flight is 19mm (3/4"). with a welded on Rock head including a bolt-on pilot bit. Bit/Flight compatibility matrix vs Auger drive unit

Diam	mm	152	229	305	405	457	610	762	914
	inch	6	9	12	16	18	24	30	36
A11	Ind.Rock	NA	NA	NA	NA	NA	NA	NA	NA
A23	Ind.Rock	++	++	++	+-	+-	+-	+-	NA
A41	Ind.Rock	++	++	++	+-	+-	+-	+-	+-
A68	Ind.Rock	++	++	++	++	++	++	++	++
Qty	teeth #	8	10	12	15	16	20	24	26

++ = good performance, +- = acceptable performance, NA = Not Allowed
 # = 1 pilot bit per flight, included in teeth count (4 pcs)

If no reference numbers appear below there are currently no items available in your region.

W	372-0270	BIT, ROCK AUGER 6"	78	\$1,181 NI
W	372-0271	BIT, ROCK AUGER 9"	107	\$1,319 NI
W	372-0272	BIT, ROCK AUGER 12"	134	\$1,458 NI
W	372-0273	BIT, ROCK AUGER 16"	167	\$2,569 NI
W	372-0274	BIT, ROCK AUGER 18"	191	\$2,847 NI
W	372-0275	BIT, ROCK AUGER 20"	217	\$3,125 NI
W	372-0276	BIT, ROCK AUGER 24"	281	\$3,681 NI
W	372-0277	BIT, ROCK AUGER 30"	310	\$4,514 NI
W	372-0278	BIT, ROCK AUGER 36"	409	\$5,347 NI

Optional replacement teeth available through Parts only:
 367-9767 Bit pilot (excluding 4 teeth)
 372-0289 Rock Drill Head Tooth

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

MHE - AUGER BITS (CONT.)

MHE - AUGER BITS (Cont.)

AUGER BITS: TREE FLIGHT

Conical auger flights, for use in nurseries and landscaping to drill holes for trees and shrubs with root balls.

Bit/Flight compatibility matrix vs Auger drive unit

Diam	mm	610	914
	inch	24	36

A11	Tree Bit	NA	NA
A23	Tree Bit	++	NA
A41	Tree Bit	++	+-
A68	Tree Bit	++	++

++ = good performance

+- = acceptable performance

NA = Not applicable / Not Allowed

If no reference numbers appear below there are currently no items available in your region.

W	153-4092	TREE BIT, AUGER 24"	163	\$986 NI
		Tapered bit, INCLUDES: 5 teeth on 24" (610mm) width, 4 teeth on 12" (305mm) width and pilot point.		
W	153-4095	TREE BIT, AUGER 36"	310	\$1,549 NI
		Tapered bit, INCLUDES: 7 teeth on 36" (914mm) width, 6 teeth on 18" (457mm) width and pilot point.		

CATERPILLAR MACHINE PRICE LIST

WT-MHE

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
MHE - AUGER BITS (CONT.)				
<i>MHE - AUGER BITS (Cont.)</i>				
AUGER BITS: ADAPTERS and EXTENTIONS				
If no reference numbers appear below there are currently no items available in your region.				
W	156-6329	ADAPTER, AUGER - HEX TO ROUND 15 HEX output shaft 2" (50mm) to round output shaft 2 9/16" (65mm)		\$208 NI
W	217-3191	ADAPTER, AUGER - ROUND TO HEX 15 Round output shaft 2.56" (65mm) to HEX output shaft 2" (50mm)		\$208 NI
W	372-0256	EXTENSION, TELESCOPING 3' 43 Three holes at 1'(0.3M) increments on extension to insert retention pin to vary depth; Insert extension inside auger bit Recommend retention pin 372-0258 for quick depth change FOR USE WITH: All Auger Bits		\$361 NI
W	372-0257	EXTENSION, TELESCOPING 6' 77 Six holes at 1'(0.3M) increments on extension to insert retention pin to vary depth; Insert extension inside auger bit Recommend retention pin 372-0258 for quick depth change FOR USE WITH: All Auger Bits		\$611 NI
W	156-6328	EXTENSION, AUGER 12" 20 12" (305mm) length HEX shaft		\$208 NI
W	217-3192	EXTENSION, AUGER 24" 33 24" (610mm) length HEX shaft		\$243 NI

Available through Parts only:
 372-0258 Retention Pin Kit
 Retention pin uses lynch (ring) pin to secure bit & drive unit instead of bolt & 2 nuts. Allows for quick change of flights, extensions, & drive kits.