

CATERPILLAR MACHINE PRICE LIST

WT-SSL

SKID STEER LOADER WORK TOOLS

Ship Weight
lbsLIST PRICE
AT DEALER

Standard Equipment:

for all models of Skid Steer Loader,
Multi-Terrain Loader and Compact Track
Loader

216, 226, 228, 232, 236, 239, 242,
246, 247, 248, 249, 252, 256, 257,
259, 262, 267, 268, 272, 277, 279,
287, 289, 297 and 299.

This Price List is split into the
headings below:

AUGERS
AUGER BITS
AUGER BITS: TREE FLIGHT
AUGER BITS: ADAPTERS and EXTENSIONS
BACKHOES: BH130, BH150 - BH160
BALE GRABS
BALE SPEARS
BLADES, ANGLE
BLADES, DOZER 6 WAY
BROOMS: ANGLE
BROOMS: PICKUP
BROOMS: UTILITY
BRUSH CUTTERS
BUCKETS: GENERAL PURPOSE
BUCKETS: LOW PROFILE (DIRT)
BUCKETS: LIGHT MATERIAL
BUCKETS: MATERIAL HANDLING
BUCKETS: MIXING
BUCKETS: MULTI PURPOSE
BUCKETS: SKELETON
BUCKETS: UTILITY
BUCKET OPTIONS: TOOTH BARS
COLD PLANERS
COMPACTORS, VIBRATORY
CONVERSION KITS
CARRIAGES - FORKS / TINES
FORKS, UTILITY
INDUSTRIAL GRAPPLE FORKS
UTILITY GRAPPLE FORKS
INDUSTRIAL GRAPPLE BUCKETS
INDUSTRIAL GRAPPLE RAKES
UTILITY GRAPPLE BUCKETS
UTILITY GRAPPLE GROUP
HAMMERS
LANDSCAPE RAKES
LANDSCAPE TILLERS
MACHINE ATTACHMENTS
MATERIAL HANDLING ARM
MULCHERS
POWER BOX RAKES
WHEEL SAWS
SHEAR
SILAGE DEFACER
SNOW BLOWERS

SNOW PLOW
SNOW PUSHES, STRAIGHT
SNOW WINGS
SECTIONAL SNOW PUSHES
STUMP GRINDERS
TRENCHERS
DEMO CONTROL KIT

FOR NORTH AND SOUTH AMERICA
Orders will automatically transfer
from CMOPS to Antares Parts Ordering.

FOR THE REST OF THE WORLD
This price list is for REFERENCE ONLY.
Work Tool orders must be placed using
Antares Parts Ordering.

FOR JAPAN
Please access the usual regional
resources to obtain pricing information.

For BCP Attachment Product and
Application Support
1-866-963-3531, Option #1, Option #2
E-mail: BCP_Work_Tools@Cat.com

CATERPILLAR MACHINE PRICE LIST

WT-SSL

SKID STEER LOADER WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-------------------------------------	--------------------	-------------------------

0P-0096	SKID STEER LOADER WORK TOOLS 0 CMOPS orders for machines and work tools MUST be ordered separately.	NC
0P-0188	MULTI TERRAIN WORK TOOLS 0 CMOPS orders for machines and work tools MUST be ordered separately.	NC
0P-6322	COMPACT TRACK LOADER WORK TOOL 0 CMOPS orders for machines and work tools MUST be ordered separately.	NC

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS												Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	--	--	--	--	--	--	--	--	--	--	--	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS

AUGERS

Nomenclature change: A23 is replacement for A14B, NO technical changes
 A23 stands for Auger with a Torque= 2300Nm (A23 = A14B)
 Nomenclature change: A41 is replacement for A19B, NO technical changes
 A41 stands for Auger with a Torque= 4100Nm (A41 = A19B)
 Nomenclature change: A68 is replacement for A26B, NO technical changes
 A68 stands for Auger with a Torque= 6826Nm (A68 = A26B)

					236										287
		226			239			248			257	262		277	289
	216	242	228	232	249	246	247	268	252	256	259	272	267	279	299
A23	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
A41	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
A68	XPS	C	C	C	C	C	C	C	C	C	C	C	C	C	C

C = Compatible

Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region

W	218-3178	AUGER, A23, SSL	377	\$2,486 NI
		A23 (old A14B) has a torque of 2300Nm Direct drive unit with 2" hex output shaft Hydraulic flow range: 42-83 l/min (11-22 gpm) Hydraulic pressure range: 145-235 bar (2,100 - 3,400 psi) INCLUDES: 225-3895 Drive Grp, 211-5044 Mounting Grp, 225-0896 Line Grp REQUIRES: Standard Flow Hydraulics		
W	225-3895	AUGER, DRIVE, A23	242	\$2,243 NI
		A23 (old A14B) has a torque of 2300Nm REQUIRES: Bracket, connecting lines and auger flight		
W	219-7706	AUGER, A41, SSL	417	\$2,951 NI
		A41 (old A19B) has a torque of 4100Nm Single reduction planetary drive unit with 2" hex output shaft. Hydraulic flow range: 42-83 l/min (11-22 gpm) Hydraulic pressure range: 145-235 bar (2,100 - 3,400 psi) INCLUDES: 230-5578 Drive Grp, 211-5044 Mounting Grp, 161-5858 Line Grp REQUIRES: Standard Flow Hydraulics		
W	230-5578	AUGER, DRIVE, A41	187	\$2,708 NI
		A41 (old A19B) has a torque of 4100Nm REQUIRES: Bracket, connecting lines and auger flight		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

AUGERS (Cont.)

W	424-0440	AUGER, A68, SSL HF 391 A68 (old A26B) has a torque of 6826Nm Double reduction planetary drive unit with 2" hex output shaft Hydraulic flow range: 95-130 l/min (25-34 gpm) Hydraulic pressure range: 207-290 bar (3,000 - 4,200 psi) INCLUDES: 225-8809 Drive Grp, 211-5044 Mounting Grp, 424-0441 Line Grp RECOMMENDED: Add case drain for severe duty applications when working below minus 7 Degree C (20 Degree F). Installation time: 4 hrs, Instructions M0113305 (NO kit available). REQUIRES: High Flow/ High Flow XPS Hydraulics 8-pin electrical high flow jumper 241-3763 for B/B2 series machines or 226B3		\$4,743 NI
W	225-8809	AUGER, DRIVE, A68 216 A68 (old A26B) has a torque of 6826Nm RECOMMENDED: Add case drain for severe duty applications when working below minus 7 Degree C (20 Degree F). Installation time: 4 hrs, Instructions M0113305 (NO kit available). REQUIRES: Bracket, connecting lines and auger flight		\$4,139 NI
W	211-5044	BRACKET, AUGER, SSL 205 FOR USE WITH: A21, A41, A68 (old A14B, A19B, A26B)		\$563 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

AUGER BITS - STANDARD FLIGHTS

Standard Duty, Approx. 50" (1270mm) Length, HEX Shaft, Double Flight
 Bit teeth are hardened, reversible and forged from medium carbon alloy steel. Teeth are held in place by bolt and nut.

Bit/Flight compatibility matrix vs Auger drive unit

Diam	mm	102	152	229	305	380	457	610	762	914
	inch	4	6	9	12	15	18	24	30	36

A23	Standard	++	++	++	++	++	++	++	+-	NA
A41	Standard	++	++	++	++	++	++	++	++	+-
A68	Standard	++	++	++	++	++	++	++	++	++
Qty	teeth #	0	2	4	4	5	6	8	10	12

++ = good performance, +- = acceptable performance, NA = Not Allowed
 # = 1 pilot point per flight, NOT included in teeth count

If no reference numbers appear below there are currently no items available in your region.

W	366-7751	BIT, AUGER 4"	40	\$375 NI
W	153-4083	BIT, AUGER 6"	50	\$375 NI
W	153-4084	BIT, AUGER 9"	75	\$493 NI
W	153-4085	BIT, AUGER 12"	100	\$618 NI
W	366-7752	BIT, AUGER 15"	109	\$750 NI
W	153-4086	BIT, AUGER 18"	144	\$875 NI
W	153-4089	BIT, AUGER 24"	200	\$1,125 NI
W	217-3194	BIT, AUGER 30"	212	\$1,368 NI
W	153-4091	BIT, AUGER 36"	380	\$1,604 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	------------------------	--------------------	-------------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)***AUGER BITS - STANDARD FLIGHTS (Cont.)***

Optional replacement teeth available through Parts only:

Pilot point/bit: 153-4093 Pilot Point

Required pilot point hardware:

1 x 7X-2549 Bolt

1 x 6V-7687 Locknut

Replacement teeth & hardware for all auger bits:

153-4094 Standard Duty Tooth

174-9566 Hard Face Tooth optional

174-9567 Carbide Inserted Tooth optional

Required teeth hardware:

6V-8959 Bolt (1)

6V-7687 Locknut (1)

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

AUGER BITS - ROCK HEAD FOR STANDARD FLIGHTS

Transforms standard auger bit to rock drill bit by mounting bolt-on rock head to standard bit. Rotating bits (similar to cold planer bits) extend life and provide better penetration into rocky conditions. Bolt-on rock head can be quickly installed and removed depending on ground conditions for maximum versatility.

Bit/Flight compatibility matrix vs Auger drive unit

Diam	mm	152	229	305	380	457	610
	inch	6	9	12	15	18	24

A23	Rock Head	++	++	++	+-	+-	+-
A41	Rock Head	++	++	++	+-	+-	+-
A68	Rock Head	++	++	++	++	++	++

Qty	teeth #	8	10	12	14	16	20
-----	---------	---	----	----	----	----	----

++ = good performance, +- = acceptable performance, NA = Not Allowed
 # = 1 pilot bit per flight, included in teeth count (4 pcs per bit)

If no reference numbers appear below there are currently no items available in your region.

W	372-0230	ROCK HEAD, 6" BOLT-ON	23	\$278 NI
		FOR USE WITH: 153-4083 Auger flight		
W	372-0231	ROCK HEAD, 9" BOLT-ON	33	\$354 NI
		FOR USE WITH: 153-4084 Auger flight		
W	372-0232	ROCK HEAD, 12", BOLT-ON	41	\$438 NI
		FOR USE WITH: 153-4085 Auger flight		
W	372-0233	ROCK HEAD, 15" BOLT-ON	47	\$514 NI
		FOR USE WITH: 366-7752 Auger flight		
W	372-0234	ROCK HEAD, 18", BOLT-ON	55	\$590 NI
		FOR USE WITH: 153-4086 Auger flight		
W	372-0235	ROCK HEAD, 24", BOLT-ON	79	\$750 NI
		FOR USE WITH: 153-4089 Auger flight		

Optional replacement teeth available through Parts only:
 372-0259 Standard Rock Drill Head Tooth

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

AUGER BITS - INDUSTRIAL FLIGHTS

Industrial bits, approx. 48" (1219mm) length, HEX shaft, single flight. Bit teeth are hardened and forged from medium carbon alloy steel. Teeth held in place by press fit. Teeth are quickly changed by soft hammer to insert or remove tooth. Ideal for ground conditions where teeth need to be changed frequently. Multiple tooth options below for various ground conditions

Bit/Flight compatibility matrix vs Auger drive unit

Diam	mm	152	229	305	405	457	610	762	914	1067	1219
	inch	6	9	12	16	18	24	30	36	42	48

A23	Industrial	++	++	++	+-	+-	+-	+-	NA	NA	NA
A41	Industrial	++	++	++	+-	+-	+-	+-	+-	+-	+-
A68	Industrial	++	++	++	++	++	++	++	++	++	++

Qty teeth #	2	4	4	6	6	8	10	12	16	18
-------------	---	---	---	---	---	---	----	----	----	----

++ = good performance, +- = acceptable performance, NA = Not Allowed
 # = 1 pilot point per flight, NOT included in teeth count

If no reference numbers appear below there are currently no items available in your region.

W	372-0260	BIT, AUGER 6" INDUSTRIAL	57	\$521 NI
W	372-0261	BIT, AUGER 9" INDUSTRIAL	72	\$639 NI
W	372-0262	BIT, AUGER 12" INDUSTRIAL	91	\$757 NI
W	372-0263	BIT, AUGER 16" INDUSTRIAL	114	\$917 NI
W	372-0264	BIT, AUGER 18" INDUSTRIAL	107	\$1,000 NI
W	372-0265	BIT, AUGER 24", INDUSTRIAL	151	\$1,236 NI
W	372-0266	BIT, AUGER 30" INDUSTRIAL	180	\$1,472 NI
W	372-0267	BIT, AUGER 36" INDUSTRIAL	223	\$1,708 NI
W	372-0268	BIT, AUGER 42" INDUSTRIAL	289	\$2,493 NI
W	372-0269	BIT, AUGER 48" INDUSTRIAL	343	\$2,736 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	------------------------	--------------------	-------------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)***AUGER BITS - INDUSTRIAL FLIGHTS (Cont.)***

Optional replacement teeth available through Parts only:

- 371-3694 Gage Tooth (Outer)
- 371-3690 Flat Tooth (Inner)
- 371-3695 HF Gage Tooth (Outer)
- 371-3691 Flat Carbide Tooth (Inner)
- 371-3696 Chisel Tooth (Inner)
- 371-3692 Flat Hard Face Tooth HF (Inner)
- 371-3697 Chisel Carbide Tooth (Inner)
- 371-3693 Flat HF Tooth (HF Both Sides, Inner)
- 371-3698 Chisel HF Tooth (Inner)

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

AUGER BITS - INDUSTRIAL ROCK FLIGHT

Industrial Rock Flights, approx. 1220mm (48") length, HEX shaft, for heavy duty applications. The thickness of the flight is 19mm (3/4"). with a welded on Rock head including a bolt-on pilot bit.

Bit/Flight compatibility matrix vs Auger drive unit

Diam	mm	152	229	305	405	457	610	762	914
inch		6	9	12	16	18	24	30	36

A23	Ind.Rock	++	++	++	+-	+-	+-	+-	NA
A41	Ind.Rock	++	++	++	+-	+-	+-	+-	+-
A68	Ind.Rock	++	++	++	++	++	++	++	++
Qty	teeth #	8	10	12	15	16	20	24	26

++ = good performance, +- = acceptable performance, NA = Not Allowed
 # = 1 pilot bit per flight, included in teeth count (4 pcs)

If no reference numbers appear below there are currently no items available in your region.

W	372-0270	BIT, ROCK AUGER 6"	78	\$1,181 NI
W	372-0271	BIT, ROCK AUGER 9"	107	\$1,319 NI
W	372-0272	BIT, ROCK AUGER 12"	134	\$1,458 NI
W	372-0273	BIT, ROCK AUGER 16"	167	\$2,569 NI
W	372-0274	BIT, ROCK AUGER 18"	191	\$2,847 NI
W	372-0275	BIT, ROCK AUGER 20"	217	\$3,125 NI
W	372-0276	BIT, ROCK AUGER 24"	281	\$3,681 NI
W	372-0277	BIT, ROCK AUGER 30"	310	\$4,514 NI
W	372-0278	BIT, ROCK AUGER 36"	409	\$5,347 NI

Optional replacement teeth available through Parts only:
 367-9767 Bit pilot (excluding 4 teeth)
 372-0289 Rock Drill Head Tooth

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

AUGER BITS - TREE FLIGHT

Conical auger flights, for use in nurseries and landscaping to drill holes for trees and shrubs with root balls.

Bit/Flight compatibility matrix vs Auger drive unit

Diam	mm	610	914
	inch	24	36

A23	Tree Bit	++	NA
A41	Tree Bit	++	+-
A68	Tree Bit	++	++

++ = good performance, +- = acceptable performance, NA = Not Allowed

If no reference numbers appear below there are currently no items available in your region.

W	153-4092	TREE BIT, AUGER 24"	163	\$986 NI
		Tapered bit, INCLUDES: 5 teeth on 24" (610mm) width, 4 teeth on 12" (305mm) width and pilot point.		
W	153-4095	TREE BIT, AUGER 36"	310	\$1,549 NI
		Tapered bit, INCLUDES: 7 teeth on 36" (914mm) width, 6 teeth on 18" (457mm) width and pilot point.		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

AUGER BITS - ADAPTERS and EXTENTIONS

Following adapters and extensions can be used with all other auger bits and augers.

W	156-6329	ADAPTER, AUGER - HEX TO ROUND 15 HEX output shaft 2" (50mm) to round output shaft 2 9/16" (65mm)		\$208 NI
W	217-3191	ADAPTER, AUGER - ROUND TO HEX 15 Round output shaft 2.56" (65mm) to HEX output shaft 2" (50mm)		\$208 NI
W	372-0256	EXTENSION, TELESCOPING 3' 43 FOR USE WITH: All Auger Bits Three holes at 1'(0.3M) increments on extension to insert retention pin to vary depth; Insert extension inside auger bit Recommend retention pin 372-0258 for quick depth change		\$361 NI
W	372-0257	EXTENSION, TELESCOPING 6' 77 FOR USE WITH: All Auger Bits Six holes at 1'(0.3M) increments on extension to insert retention pin to vary depth; Insert extension inside auger bit Recommend retention pin 372-0258 for quick depth change		\$611 NI
W	156-6328	EXTENSION, AUGER 12" 20 12" (305mm) length HEX shaft		\$208 NI
W	217-3192	EXTENSION, AUGER 24" 33 24" (610mm) length HEX shaft		\$243 NI

Available through Parts only:
 372-0258 Retention Pin Kit
 Retention pin uses lynch (ring) pin to secure bit & drive unit instead of bolt & 2 nuts. Allows for quick change of flights, extensions, & drive kits.

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SMART BACKHOE ATTACHMENT BH130 - D3 series ONLY

New design backhoe attachment with full EH joystick control, which allows you to operate it from within the machine. No need to remove the front door. Operate it while enjoying the cab environment as if using a bucket. The BH130 is a SMART Attachment. When the harness is connected to the machine, the machine recognizes the BH130. Choose between Machine mode or Attachment mode. In Attachment mode, choose between Backhoe or Excavator Joystick pattern.

BH130 backhoe attachment compatibility for D3 Series only:

D & D2							D3 only						
		246	279	272									279
226	239	236	257	262	287	297	226	239	236		246		289
232	249	242	259	277	289	299	232	249	242	259	262	272	299
BH130	NC	NC	NC	NC	NC	NC	C*	C*	C*	C	C	C	C

C= Compatible / NC= Not Comp./ *= BH in transport mode while moving

If no reference numbers appear below there are currently no items available in your region.

W	551-6979	BACKHOE, BH130	2,381	\$22,222 NI
		Full EH joystick Backhoe attachment for closed door operation. Loading Height / Reach: 2470mm (97") / 1869mm (74") Max Digging Depth: 3189mm (126"), Side Shift : 838mm (33") Dig Depth at 610mm (2ft) / 2440mm (8ft): 3156mm (124") / 2705mm (106") Swing arc: 180 degrees, Bucket rotation 183 degrees Break out force Bucket / Stick : 3181kg (7013 lbs / 1605kg (3538 lbs) INCLUDES: 2 way Aux lines, hydraulic side shift, left/right hydraulic operated vertical stabilisers, 589-1929 Bracket Kit FOR USE WITH: all D3 machines ONLY REQUIRES: Standard Flow REQUIRES: Worktool harness on machine, 4 button Left Hand Joystick and 2 button Right Hand Joystick with thumb roller (see table below) REQUIRES: Software (or later version) installed on machine: 590-9633 Machine Software AND 598-5142 Machine Monitor Software REQUIRES: MHE attachments for 3T machines NOTE: ISO5006 visibility requirements apply for EU region. Consult Cat Dealer for additional information.		
W	589-1929	GROUP, MOUNTING, BH130	26	\$417 NI
		For retro-fit of additional D3 machines to use the BH130 on multiple machines. To be bolted to the machine and fitted to the BH130. See OMM for instructions. FOR USE WITH: BH130 on D3 machines (bracket stays on machine)		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SMART BACKHOE ATTACHMENT BH130 - D3 series ONLY (Cont.)

BH130 backhoe attachment Joysticks Requirements:
 Please check your machine configuration and table below indicates what extras you need to order:

Performance package & Controls	Joysticks	14 pins	You have to order
	Right Hand Left Hand	Electr. Harness	
	2 button+ 4 button	WT	
	thumb wheel		
226D3, 232D3, 239D3, 249D3:			
H1 Proportional	not incl	incl	not incl WTH2 + RH
H2 Prop+WT Harness	incl	incl	incl Nothing
H3 HF	incl	incl	incl Nothing
236D3, 242D3, 246D3, 259D3, 262D3, 272D3, 279D3, 289D3, 299D3:			
H1 Proportional	not incl	incl	not incl WTH4 + RH
H2 Prop+WT Harness	incl	incl	incl Nothing
H3 HF/ HF XPS	incl	incl	incl Nothing
272D3 XE, 299D3 XE:			
H3 XE	incl	incl	incl Nothing

RH = 2 buttons Right Hand Joystick + thumb roller	525-1499
WTH2 = Work Tool Harness	544-4108
WTH4 = Work Tool Harness	544-4110

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BACKHOES: BH150

NOTE: these backhoe attachments are restricted for sale in the European Union due to local regulations.

For work tools for the BH27, BH30 and BH30W, please go to WT-MHE price pages, section 2-3 Ton machines and all buckets will fit.

APPLIES TO ALL SERIES

	232								
	226	239	242	248		257	267		
BH150	216	228	249	247	252	256	259	268	

BH150	C	C	C	C	C	C			
-------	---	---	---	---	---	---	--	--	--

APPLIES TO SPECIFIED SERIES (C SERIES INCLUDES: C2)

236				262C		277C		287C	
236B				262D		277D		287D	297C
236B2		246	246C	262	272C	277	279C	287	289C 299C
236B3	236D	246B	246D	262B	272D	277B	279D	287B	289D 299D

BH150		C		C		C		C		C
-------	--	---	--	---	--	---	--	---	--	---

C = Compatible

Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

BACKHOES: BH150 - BACKHOE: MOUNTING GROUPS

W	367-9770	GROUP, BACKHOE MOUNTING	106	\$1,543 NI
		Kit allows BH160, BH150, & BH30W models to mount on C-Series machines Mandatory for use with 238-0330, 253-1480, 304-9900, 304-9901, 304-9902, 304-9903, and 204-4018 on C-Series machines NOTE: BH30W (204-4018) requires two 211-9558 link arms (parts only) Installation time: 4 hours, instructions see REHS3133		
W	304-9905	GROUP, MOUNTING, BH150	53	\$1,056 NI
		Mandatory for use with BH150 (304-9902 & 304-9903) on the following machines prior to C-Series: 216/B/B2/B3, 226/B/B2/B3, 228, 232/B/B2, 242/B/B2/B3, 247/B/B2/B3, 257/B/B2/B3, 259B3		
W	457-1210	GROUP, BACKHOE MOUNTING	0	\$1,543 NI
		FOR USE WITH: BH150 and 226D, 232D, 239D, 249D Installation time: 4 hours, Instructions see REHS9984		
W	444-9230	GROUP, BACKHOE MOUNTING	95	\$1,543 NI
		FOR USE WITH: BH150 and 236D, 242D, 257D, 259D Installation time: 4 hours, Instructions see REHS7842		
W	444-9240	GROUP, BACKHOE MOUNTING	106	\$1,543 NI
		FOR USE WITH: BH150 and 246D, 262D, 272D, 272D XHP, 277D, 279D, 287D, 289D, 297D, 297D XHP, 299D and 299D Note: The BH150 backhoe also requires two 443-4534 Hooks to replace the standard length 238-0336 Hooks Installation time: 4 hours, instructions see REHS7842		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-------------------------------	--------------------	-------------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)***BACKHOES: BH150 - BACKHOE: MOUNTING GROUPS (Cont.)***

Please order one 258-3639 Backhoe Mounting Group and two 211-9558 link arms (available through parts only) to mount a BH30W to a C-Series machine.

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BACKHOES: BH130/BH150/BH160 - BUCKETS (COUPLER & PINS)

W	444-7494	COUPLER, PG, MAN.D.LOCK, 3-4T	76	\$1,410 NI
		Base machine INCLUDES: one set of pins and hardware REQUIRES: 154-2638 bucket pins for EACH ADDITIONAL bucket		
W	154-2638	PINS, BUCKET, 40MM	11	\$97 NI
		INCLUDES: 2 bucket pins and hardware FOR USE WITH: 444-7494 and 361-1095 and Pin-On Buckets		

BACKHOES: BH130/BH150/BH160 - BUCKETS

The following MHE buckets can be used with the BH150 and BH160 Backhoe attachments. For additional work tools, please check WT-MHE price list, section 3-4 Tons machines. All work tools will fit.

If no reference numbers appear below there are currently no items available in your region.

BACKHOES: BH130/BH150/BH160 - HEAVY DUTY BUCKETS

NOTE: Optional side cutters are available. Part numbers are:
 LH Side Cutter 252-2611 / RH Side Cutter 252-2612
 Bolts 4F-3653 (3 per side cutter, total 6 per bucket)
 Nuts 4K-0367 (3 per side cutter, total 6 per bucket)
 (IRM): GET05-13 for further information and selection criteria.

W	464-9900	BUCKET-HD, 12", 1.7 FT3, 3T	142	\$958 NI
		Width 305mm (12"), Heaped Cap. 0.05M3 (0.06YD3), Incl 3 x J200 FOR USE WITH: Pin-on, requires bucket pins		
W	464-9901	BUCKET-HD, 16", 2.5 FT3, 3T	162	\$1,042 NI
		Width 406mm (16"), Heaped Cap. 0.07M3 (0.09YD3), Incl 3 x J200 FOR USE WITH: Pin-on, requires bucket pins		
W	464-9902	BUCKET-HD, 18", 2.9 FT3, 3T	180	\$1,083 NI
		Width 457mm (18"), Heaped Cap. 0.08M3 (0.11YD3), Incl 4 x J200 FOR USE WITH: Pin-on, requires bucket pins		
W	464-9903	BUCKET-HD, 20", 3.3 FT3, 3T	192	\$1,118 NI
		Width 508mm (20"), Heaped Cap. 0.09M3 (0.12YD3), Incl 4 x J200 FOR USE WITH: Pin-on, requires bucket pins		
W	464-9904	BUCKET-HD, 24", 4.2 FT3, 3T	216	\$1,208 NI
		Width 619mm (24"), Heaped Cap. 0.12M3 (0.15YD3), Incl 4 x J200 FOR USE WITH: Pin-on, requires bucket pins		
W	464-9905	BUCKET-HD, 30", 5.6 FT3, 3T	258	\$1,347 NI
		Width 762mm (30"), Heaped Cap. 0.16M3 (0.21YD3), Incl 5 x J200 FOR USE WITH: Pin-on, requires bucket pins		
W	464-9906	BUCKET-HD, 36", 7.0 FT3, 3T	293	\$1,479 NI
		Width 914mm (36"), Heaped Cap. 0.2M3 (0.26YD3), Incl 5 x J200 FOR USE WITH: Pin-on, requires bucket pins		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BACKHOES: BH130/BH150/BH160 - DITCH CLEANING BUCKETS

W	279-4322	BUCKET-DC, 40", 4.8 FT3, 3T 234 0.17 yd3 / 4.59 CFT Heaped Capacity INCLUDES: rear grading edge	234	\$1,042 NI
W	279-4323	BUCKET-DC, 47", 5.9 FT3, 3T 234 0.209 yd3 / 5.64 CFT Heaped Capacity	234	\$1,118 NI
W	282-9315	BUCKET-DC, 55", 6.9 FT3, 3T 234 0.249 yd3 / 6.72 CFT Heaped Capacity	234	\$1,285 NI
W	279-4325	BUCKET-DCT, 47", 5.9 FT3, 3T 357 0.209 yd3 / 5.6 CFT Heaped Capacity INCLUDES: rear grading edge FOR USE WITH: BH160 only	357	\$3,722 NI

BACKHOES: BH130/BH160 ONLY - AUGERS

W	218-3198	AUGER, A23, MHE 3T, 40MM 264 INCLUDES: DIRECT drive unit, hydraulic lines with quick disconnects, mounting bracket, hardware and 2" (50mm) HEX output shaft.	264	\$2,486 NI
W	220-7137	AUGER, A41, MHE 3T, 40MM 205 INCLUDES: PLANETARY drive unit, hydraulic lines with quick disconnects, mounting bracket, hardware and 2" (50mm) HEX output shaft.	205	\$2,951 NI

AUGER BITS

Please see Section AUGERS in this price list:
 paragraph AUGER BITS for auger flights, bits and extensions.

ADDITIONAL WORK TOOLS FOR BH160

These work tools require aux lines, which are only available on BH160.

CVP16 COMPACTOR PLATE:

Please check WT-MHE price list, section 3-4 Tons machines, Compactors.

HAMMMERS / BREAKERS

Hammer guard REQUIRED to guard against flying objects on backhoes.

W	211-2082	GUARD, MESH 13 Provides a half-door mesh guard mounted to front of cab. For use on A- and B-series machines with a backhoe attachment when operating a hydraulic hammer on the stick or other applications which might produce flying objects	13	\$417 NI
---	----------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	----	----------

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BALE GRABS

Cat Bale Grabs are designed for grasping and carrying baled material. Bales of wheat, hay and other materials are easily transported for livestock feed, bedding, to and from bale wrapper, and movement to storage. The Bale Grab firmly grasps baled materials but due to the rounded arm design no damage will take place to the bale. Offering the ability to pick up bales sitting flat or on their side the Bale Grab increases machine versatility.

																287
																289
	226			236				248			257	262			277	297
	216	242	228	232	249	246	247	268	252	256	259	272	267	279	299	
71"/1803mm	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
84"/2134mm	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C

C = Compatible
 Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	477-9896	BALE GRAB, 71"	575	\$3,000 NI
		1091 kg (2400 lb) Rated Capacity, 1803mm (71") working width		
		INCLUDES: Hydraulic lines with 1/2" quick disconnects		
		REQUIRES: Standard Flow Hydraulics		
W	489-0075	BALE GRAB, 84"	580	\$3,333 NI
		1091 kg (2400 lb) Rated Capacity, 2134mm (84") working width		
		INCLUDES: Hydraulic lines with 1/2" quick disconnects		
		REQUIRES: Standard Flow Hydraulics		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS												Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	--	--	--	--	--	--	--	--	--	--	--	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BALE SPEARS

																	287
																	289
	226				236				248			257	262			277	297
	216	242	228	232	249	246	247	268	252	256	259	272	267	279	299		
51"/1285mm	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
55"/1407mm	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
55"/1407mm	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	475-6074	BALE SPEAR, SINGLE 39"	154	\$660 NI
		1285mm (51") overall width, 1 x spear tine 990mm (39") long		
W	475-6079	BALE SPEAR, SINGLE 49"	159	\$681 NI
		1285mm (51") overall width, 1 x spear tine 1245mm (49") long		
W	475-6070	BALE SPEAR, DUAL 39"	260	\$1,111 NI
		1407mm (55") overall width, 2 x spear tines 990mm (39") long		
W	475-6080	BALE SPEAR, DUAL 49"	267	\$1,153 NI
		1407mm (55") overall width, 2 x spear tines 1245mm (49") long		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS												Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	--	--	--	--	--	--	--	--	--	--	--	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BLADES, ANGLE

Heavy duty, high capacity design for moving dirt, gravel, livestock waste and snow.

																287
																289
	226							248				257	262		277	297
216	242	228	232	249	246	247	268	252	256	259	272	267	279	299		
72"/1829mm	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
84"/2134mm	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C

C = Compatible

Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	177-1989	BLADE, ANGLE, 72"	690	\$3,493 NI
		1829mm (72") overall width, 610mm (24") blade height 4 Trip Springs, 2 Heavy Duty Adjustable Skid Feet INCLUDES: Hydraulic lines with quick disconnects, mounting bracket and hardware, 1 piece Bolt-On Cutting edge REQUIRES: Standard Flow Hydraulics		
W	177-1990	BLADE, ANGLE, 84"	730	\$3,722 NI
		2134mm (84") overall width, 610mm (24") blade height 4 Trip Springs, 2 Heavy Duty Adjustable Skid Feet INCLUDES: Hydraulic lines with quick disconnects, mounting bracket and hardware, 1 piece Bolt-On Cutting Edge REQUIRES: Standard Flow Hydraulics		

BLADES, ANGLE - OPTIONS

Snow kits include guard, markers, and mounting hardware.
Non-metallic edge not included in snow kits.

W	225-9522	KIT, SNOW AND IMPACT, 72"	50	\$619 NI
		FOR USE WITH: 177-1989		
W	225-9523	KIT, SNOW AND IMPACT, 84"	50	\$619 NI
		FOR USE WITH: 177-1990		
		Available through Antares / Parts system: 165-8477 Non-metallic 72" BOCE REQUIRES: 6x 8T-4140 Bolt + 6x 8T-4778 Locknut + 6x 165-7095 Washer 165-8478 Non-metallic 84" BOCE REQUIRES: 7x 8T-4140 Bolt + 7x 8T-4778 Locknut + 7x 165-7095 Washer		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BLADES, DOZER 6 WAY

Designed for rough and finish grading of dirt and gravel, as well as light dozing applications.

Compatibilty for B Series machines and up:

	B & B2 & B3					C & C2			D & D2 & D3						
	232		226			262	287		246		279	272			
	236	252	242	257		246	277	289	226	239	236	257	262	287	297
	216	247	262	268	259	256	279	299	232	249	242	259	277	289	299
2002mm	+-	++	++	++	++	++	+-	+-	++	++	++	++	+-	+-	+-
2342mm	+-	+-	+-	+-	++	++	++	++	+-	+-	+-	++	++	++	++

++ = Optimal attachment-machine combination
+- = Less optimal attachment-machine combination

Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	541-0940	BLADE, DOZER, 6-WAY, 79" 1,014	\$6,847 NI
		Overall width straight / full angled: 2002mm (79") / 1752mm (69") Hydr. Tilt +/- 10 degr, Angle/Rotation: 30 degr. left/right of center Overall height: 737mm (29") Comes with spill guard and 2 brackets for laser masts. INCLUDES: Hydraulic lines with quick disconnects, mounting bracket and hardware, 3 piece Bolt-On Cutting Edge REQUIRES: Standard Flow Hydraulics, 90 lpm (20 gpm) REQUIRES: Work Tool Harness and 4 button left hand joystick on machine mounting bracket, & 14-pin electrical harness. REQUIRES: Conversion harness 377-1579 for B/B2/B3/C/C2 machines	
W	541-0945	BLADE, DOZER, 6-WAY, 92" 1,085	\$7,521 NI
		Overall width straight / full angled: 2342mm (92") / 2049mm (81") Hydr. Tilt +/- 10 degr, Angle/Rotation: 30 degr. left/right of center Overall height: 737mm (29") Comes with spill guard and 2 brackets for laser masts. INCLUDES: Hydraulic lines with quick disconnects, mounting bracket and hardware, 3 piece Bolt-On Cutting Edge. REQUIRES: Standard Flow Hydraulics REQUIRES: Work Tool Harness and 4 button left hand joystick on machine mounting bracket, & 14-pin electrical harness REQUIRES: Conversion harness 377-1579 for B/B2/B3/C/C2 machines	

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BLADES, DOZER, SMART - D3 SERIES ONLY

Cat SMART Dozer Blades are for cutting, moving, and grading dirt, gravel, sand, and virtually any other material used as a base. They feature integrated joystick controls for more intuitive operation, grade indications of the machine and blade in the advanced machine display, and operator assist features to help create smooth grades faster and with less operator effort.

SMART Dozer blade compatibility for D3 Series only:

	D & D2							D3 only						
	226	239	236	257	262	287	297	226	239	236		246		289
	232	249	242	259	277	289	299	232	249	242	259	262	272	299
2.3m (92")	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	NC	C

C = Compatible / NC= Not Compatible

W	539-9210	BLADE, 6W DOZER, SMART, 92"	1,095	\$13,771 NI
		Overall width straight / full angled: 2342mm (92") / 2049mm (81")		
		Hydr. Tilt +/- 10 degr, Angle/Rotation: 30 degr. left/right of center		
		Overall height: 737mm (29")		
		INCLUDES: Spil guard, 2 brackets for lasers masts, hydraulic lines and Quick Disconnects, 3 piece Bolt-On-Cutting-Edge, ECM		
		FOR USE WITH: 279D3/ 289D3/ 299D3 with HF XPS or 299D3 XE only		
		REQUIRES: Software (or later version) installed on machine:		
		590-9633 Machine Software AND 598-5142 Machine Monitor Software		
W	585-5125	KIT, GRADING IMU, SMART, MACH	3	\$556 NI
		SMART Kit for dozer blade to be installed on the base machine.		
		INCLUDES: Box with Sensor, connecting harness, fixings		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SMART GRADER BLADES - D3 series ONLY

Cat? SMART Grader Blade attachments are for cutting, moving and grading dirt, gravel, sand and virtually any other material used as a base. There is an assist feature of the blade that takes the unit beyond SMART. The SMART grader blade brings cross slope to SSL/CTL platforms. The combination of these features along with the support of the Caterpillar Dealer Network makes this attachment Industry leading due to the industry first features.

SMART	Grader blade compatibility for D3 Series only:													
	D & D2				D3 only									
			246	279	272				279					
	226	239	236	257	262	287	297	226	239	236	246	289		
	232	249	242	259	277	289	299	232	249	242	259	262	272	299
GB120	---	---	---	---	---	---	---	++	++	++	++	+-#	+-#	+-#
GB124	---	---	---	---	---	---	---	+-	+-	+-	++	++	++	++

++= Optimal +- = Acceptable --- = Can Not be Operated
= +- excluding wings and ++ including wings

W	575-2080	GRADER BLADE, GB120, 78" 1,684	\$22,083 NI
		Blade width straight ex/ incl.extens.wings: 1992mm (78")/ 2592mm(103") Blade width angled ex/ incl.extens.wings: 1747mm (69")/ 2292mm (90") Grader blade angling / Tilt / Height: 30 Degr./ 15 Degr. / 431mm (17") "Earth Works GO!" ready for Laser, Cat Grade ready for GPS INCLUDES: 3 piece Bolt-On-Cutting-Edge, 2 mirrors, 2 wheels, ECM, harness, 2 brackets incl. Laser masts (excl Laser receivers) FOR USE WITH: all D3 machines ONLY, in standard flow REQUIRES: Work tool harness on machine, 4 button Left Hand Joystick and 2 button Right Hand Joystick with thumb roller (see table below). (is included for machines with HF, HF XPS or XE) REQUIRES: Software (or newer version) installed on machine: 602-0771 Machine Software AND 601-2728 Machine Monitor Software REQUIRES: For UTS, Dual Laser and Dual GNSS Grading extra parts need to be ordered (see BOMs below) OPTIONAL: 583-6638 KIT, WING, 600mm (24") extension OPTIONAL: 585-5125 KIT, GRADING IMU, SMART, MACH	
W	575-2082	GRADER BLADE, GB124, 96" 1,770	\$22,500 NI
		Blade width straight ex/ incl.extens.wings: 2449mm (96")/ 3049mm(121") Blade width angled ex/ incl.extens.wings: 2143mm (84")/ 2688mm (106") Grader blade angling / Tilt / Height: 30 Degr./ 15 Degr. / 431mm (17") "Earth Works GO!" ready for Laser, Cat Grade ready for GPS INCLUDES: 3 piece Bolt-On-Cutting-Edge, 2 mirrors, 2 wheels, ECM, harness, 2 brackets incl. Laser masts (excl Laser receivers) FOR USE WITH: all D3 machines ONLY, in standard flow REQUIRES: Work tool harness on machine, 4 button Left Hand Joystick and 2 button Right Hand Joystick with thumb roller (see table below). (is included for machines with HF, HF XPS or XE) REQUIRES: Software (or newer version) installed on machine: 602-0771 Machine Software AND 601-2728 Machine Monitor Software REQUIRES: For UTS, Dual Laser and Dual GNSS Grading extra parts need to be ordered (see BOMs below) OPTIONAL: 583-6638 KIT, WING, 600mm (24") extension OPTIONAL: 585-5125 KIT, GRADING IMU, SMART, MACH	

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SMART GRADER BLADES - D3 series ONLY (Cont.)

W 583-6638 KIT, GRADER, WINGS 194 \$4,306 NI

Left + Right wing, adds 600mm (24") to the width of the grader blade.
Rotation 205 Degrees between Forwards and Backwards.
INCLUDES: 2 wings, 2 hydraulic actuators, valve and various lines,
connectors, fixings- to fit it to the grader blade
Installation time : Approx 4 hours (see Media number: M0119515)

W 585-5125 KIT, GRADING IMU, SMART, MACH 3 \$556 NI

Provides information regarding the machine orientation to the machine display. To be installed on the machine (see Media number: M0117917)
INCLUDES: Box with Sensor, connecting harness, fixings

EXCLUDED (to be ordered from SITECH):
UTS BOM

- 1x 160667-501 Kit - Base, CAT, GB12X Grader Blade Attachment, V3.0
- 1x 200435-10 FRU - Electronic Controller, EC520-W w/IMU and Wi-Fi
- 1x 160065-005 Core Bundle - Compact Loader, Earthworks
- 1x 201500-00 FRU - 7" Touch Display, TD510-LW w/TPM, WiFi & BT
- 1x 160000-900 Module Bundle - Infield Designs, 3D Guidance
- 1x 160065-200 Module License - Compact Loader, Design Automatics
- 1x 81069-20 MAST-FIXED, STEEL CAT
- 1x 69601-62 Kit - Machine Target, MT900 w/ Shock Mount & Adaptor, AccuGrade
- 1x 0395-9450 CABLE, J1939, MS980, MS990, COILED
- 1x 97007-84 FRU - Radio, SNR934, On-Machine, 900MHZ + 2.4 GHZ, US/CAN/AUS/NZ, CAT

Dual Laser BOM

- 1x 160667-501 Kit - Base, CAT, GB12X Grader Blade Attachment, V3.0
- 1x 200435-10 FRU - Electronic Controller, EC520-W w/IMU and Wi-Fi
- 1x 160065-005 Core Bundle - Compact Loader, Earthworks
- 1x 201500-00 FRU- 7" Touch Display, TD510-LW w/TPM, WiFi+BT (Optional)
- 1x 86491-05 Kit - Sensor, Dual LR410 Laser Receivers, AccuGrade
- 2x 0794-2350 Cable, Coil, 10-6 Quick Disconnect

Dual GNSS BOM

- 1x 160667-501 Kit - Base, CAT, GB12X Grader Blade Attachment, V3.0
- 1x 200435-10 FRU - Electronic Controller, EC520-W w/IMU and Wi-Fi
- 1x 160065-005 Core Bundle - Compact Loader, Earthworks
- 1x 201500-00 FRU- 7" Touch Display, TD510-LW w/TPM, WiFi+BT (Optional)
- 1x 160000-900 Module Bundle - Infield Designs, 3D Guidance
- 1x 160065-200 Module License - Compact Loader, Design Automatics
- 2x 81069-20 MAST-FIXED, STEEL CAT
- 2x 95105-55 FRU - GNSS Receiver, Mast Mount Bracket, MS975 - Cat
- 1x 82167 Case - (2) MS97x, TD510/TD520/CB450/CB460/SNM940
- 1x 150413-013 Cable - GNSS
- 2x 0395-9450 CABLE, J1939, MS980, MS990, COILED
- 2x 96000-60 Option Combo - MS9xx, Full RTK/GLN/GAL/BeiDou
- 1x 97007-84 FRU - Radio, SNR934, On-Machine, 900MHZ + 2.4 GHZ, US/CAN/AUS/NZ, CAT

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SMART GRADER BLADES - D3 series ONLY (Cont.)

Please check your machine configuration and table below indicates what extras you need to order:

Performance package & Controls	Joysticks	14 pins	You have to order
	Right Hand 2 button+ thumb wheel	Left Hand 4 button	Electr. Harness WT
226D3, 232D3, 239D3, 249D3:			
H1 / H2 ON/OFF	not incl	not incl	not incl WTH1 + RH
H1 / H2 Prop.	not incl	incl	not incl WTH2 + RH
H1 / H2 Prop.WT	not incl	incl	incl RH
H3 Prop.WT	incl	incl	incl Nothing
236D3, 242D3, 246D3, 259D3, 262D3, 272D3, 279D3, 289D3, 299D3:			
H1 / H2 ON/OFF	not incl	not incl	not incl WTH3 + RH
H1 / H2 Prop.	not incl	incl	not incl WTH4 + RH
H1 / H2 Prop.WT	not incl	incl	incl RH
H3 Prop.WT	incl	incl	incl Nothing
272D3 XE, 299D3 XE:			
H3 Prop.WT	incl	incl	incl Nothing
WTH4 = Work Tool Harness 544-4110			
<hr/>			
RH = 2 buttons Right Hand Joystick + thumb roller			525-1499
WTH1 = WT Harness + 4 buttons Left Hand Joystick			544-4107
WTH2 = Work Tool Harness			544-4108
WTH3 = WT Harness + 4 buttons Left Hand Joystick			544-4109

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BOX BLADE, ACCUGRADE READY

Fits all current D series machines. Minimal machine requirement is 14 pin Work Tool Harness DeLuxe to have full work tool control.

The Box Blade is an AccuGrade Ready solution. It is the basic set-up to be used in 1D/2D Laser, GPS and UTS grading Technology.

INCLUDED:

- 1 Integrated proportional Electro Hydraulic valve for fine grading
- Harness to connect with AccuGrade components (not included)
- 14 pin Work Tool harness (provides power to ECM on Box Blade and allows for manual operation of the Box blade)
- 2 vertical laser masts (can not be used for GPS/UTS solution)
- 2 vertical placed independent controled tilting cylinders
- 2 Parabolic front mirrors for a good view on the front grading edge
- 2 front stabilisation wheels
- 2 reversible 1 piece BOCEs, with a CAT patented indication line to reverse/replace the BOCE.

Hydraulic flow range: 50-90 l/min (13.5 - 24 gpm)

FOR USE WITH: Standard Flow hydraulics

REQUIRES: Work Tool Harness Deluxe on machine (388-8273 4 button left hand joystick & 273-9104 2 button right hand joystick)

EXCLUDED (to be ordered from SITECH):

For 2 D Laser Grading:

- 86491-05 Kit - Sensor, Dual LR410 Laser Receivers, AccuGrade
- 0794-2350 2x Cable coil 10-6 quick disconnect.
- 90450-50 FRU - Control Box, CB450 w/ Software, AccuGrade
- 75560-40 Kit - Base, Cat, SSL Box Blade Tool BB121 & BB124
 Including: RAM Mount, Harness Mounting Provisions
- 92040-70 Option Key - GCS900, 2D, Automatics, Cat AccuGrade

For 3 D GNSS (GPS) Grading (excluding radio due to users preference):

- 69601-32 Kit-receiver, Dual Autonomous/SBAS/DGPS GPS-only, MS992, Carry case, AccuGrade
- 92040-80 Option Key - GCS900, CCS900, 3D, Automatics, Cat AccuGrade
- 96000-20 Option Key - MS9xx, Full RTK
- 90460-50 FRU - Control Box, CB460 w/ Software, AccuGrade
- 96000-30 Option Key - MS9xx, GLONASS
- 81069-20 Mast-Fixed, Steel CAT
- 0395-9450 Cable, J939, MS980, MS990, Coiled
- 75560-40 Kit - Base, Cat, SSL Box Blade Tool BB121 & BB124
 Including: RAM Mount, Harness Mounting Provisions

Reference your SITECH / Trimble dealer for other AccuGrade configurations.

W	489-2001	BOX BLADE, BB121, 84"	2,000	\$20,833 NI
		Overall / Grading width: 2.22m (87.5") / 2.1m (84")		
		Hight incl Laser masts: 2.70m (106"), Depth 2.1m (81")		
W	489-2002	BOX BLADE, BB124, 96"	2,150	\$21,250 NI
		Overall / Grading width: 2.53m (99.5") / 2.4m (96")		
		Hight incl Laser masts: 2.70m (106"), Depth 2.1m (81")		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BOX BLADE, ACCUGRADE READY (Cont.)

CONVERSION KITS FOR BOX BLADES

Please check your machine configuration, the table below indicates what extras you need to order:

Performance package & Controls	Joysticks	14 pins	You have to order
	Right Hand Left Hand	Electr. Harness	
	2 button+ 4 button	WT	
	thumb wheel		
226D, 232D, 239D, 249D (D1, D2 and D3):			
H1 / H2 ON/OFF	not incl	not incl	not incl WTH1 + RH
H1 / H2 Prop.	not incl	incl	not incl WTH2 + RH
H1 / H2 Prop.WT	not incl	incl	incl RH
H3 Prop.WT	incl	incl	incl Nothing
236D, 242D, 246D, 257D, 259D, 262D, 272D2, 277D, 279D, 287D, 289D, 297D2, 299D2 (D1, D2 and D3):			
H1 / H2 ON/OFF	not incl	not incl	not incl WTH3 + RH
H1 / H2 Prop.	not incl	incl	not incl WTH4 + RH
H1 / H2 Prop.WT	not incl	incl	incl RH
H3 Prop.WT	incl	incl	incl Nothing
272D(2)XHP, 272D3 XE, 297D(2)XHP, 299D(2)XHP, 299D3 XE:			
H3 Prop.WT	incl	incl	incl Nothing

Series Machine	D + D2	D3
RH = Right Hand Joystick with thumb roller and 2 buttons	273-9104	525-1499
WTH1 = Work Tool Harness + 4 buttons Left Hand Joystick	421-0265	544-4107
WTH2 = Work Tool Harness	421-0261	544-4108
WTH3 = Work Tool Harness + 4 buttons Left Hand Joystick	388-8273	544-4109
WTH4 = Work Tool Harness	388-8265	544-4110

For C series and B series:

W	532-5926	KIT, CONTROLLER, 8 PIN	2	\$625 NI
		Includes: strap-on 5 buttons aux joystick to operate box blade FOR USER WITH: 8 pins work tool harness on machine side		
W	532-5927	KIT, CONTROLLER, 14 PIN	2	\$625 NI
		Includes: strap-on 5 buttons aux joystick to operate box blade FOR USER WITH: 14 pins work tool harness on machine side		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS												Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-------------------------------	--	--	--	--	--	--	--	--	--	--	--	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BROOMS, ANGLE

																			287
																			289
		226																	297
	216	242	228	232	249	246	247	268	252	256	259	272	267	279	299				
BA18	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	
BA118C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	

C = Compatible

Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	448-5660	BROOM, MANUAL ANGLE, BA118C	905	\$7,819 NI
		MANUAL Angling - 30 degrees left or right of center Sweeping width straight / angled : 2119mm (83") / 1849mm (73") Brush: material - 50% polypropylene / 50% steel wire Brush diameter: 815mm (32") INCLUDES: hydraulic lines with 1/2" quick disconnects, mounting bracket and hardware REQUIRES: Standard Flow Hydraulics		
W	448-5670	BROOM, HYDRAULIC ANGLE, BA118C	955	\$9,333 NI
		HYDRAULIC Angling - 30 degrees left or right of center 2637mm (104") overall width 2119mm (82") sweeping width - straight 1849mm (73") sweeping width - angled 815mm (32") brush diameter Brush material - 50% polypropylene / 50% steel wire INCLUDES: Hydraulic lines with 1/2" quick disconnects, mounting bracket, & 14-pin electrical harness REQUIRES: Standard Flow Hydraulics REQUIRES: Work Tool Harness and 4 button left hand joystick on machine REQUIRES: Conversion harness 377-1579 for B/B2/B3/C/C2 series machines; not required for B3-Series high flow		

BROOMS, ANGLE - OPTIONS

W	248-5788	KIT, WATER SPRINKLER, BA18	20	\$886 NI
		Work tool water sprinkling kit complete with sprinkler heads (6), hoses, mounting hardware and quick disconnects for effective dust control. FOR USE WITH: BA18 angle brooms only (not BA118C) REQUIRES: Control, Work Tool, Electrical (order with machine) REQUIRES: Water Tank, Machine (reference machine attachments section of this price list to order) NOTE: Not compatible with 242-7199 KIT, DEFLECTOR		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BROOMS, ANGLE - OPTIONS (Cont.)

W	452-4175	KIT, WATER SPRINKLER, BA118C Work tool water sprinkling kit complete with sprinkler heads (6), hoses, mounting hardware, and quick disconnects for effective dust control FOR USE WITH: BA118C Angle brooms only (not BA18) REQUIRES: Control, Work Tool, Electrical (order with machine) REQUIRES: Water Tank, Machine (reference machine attachments section of this price list to order) NOTE: Not compatible with 452-4200 KIT, DEFLECTOR, BA118C Installation time: 1.0 hour, instructions see REHS8314	16	\$886 NI
W	242-7199	KIT, DEFLECTOR, BA18 Angle Broom Deflector Kit INCLUDES: steel cowl extension, and rubber debris deflector flap, and mounting hardware kit to Angle Broom. FOR USE WITH: BA18 angle brooms only (not BA118C) NOTE: Not compatible with 248-5788 KIT, WATER SPRINKLER	47	\$729 NI
W	452-4200	KIT, DEFLECTOR, BA118C Angle Broom Deflector Kit INCLUDES: steel cowl extension, rubber debris deflector flap, and mounting hardware FOR USE WITH: BA118C Angle brooms only (not BA18) NOTE: Not compatible with 452-4175 KIT, WATER SPRINKLER, BA118C Installation time: 1.0 hour, instructions see REHS8317	40	\$729 NI
W	452-4195	KIT, HYDR. ANGLE CONV., BA118C Converts manual angle broom BA118C into a hydraulic angle broom INCLUDES: valve, cylinder, assembled hoses, and hardware FOR USE WITH: 448-5660 BROOM, MANUAL ANGLE, BA118C REQUIRES: Control, Work Tool, Electrical (order with machine) REQUIRES: Conversion harness 377-1579 for B/B2/B3/C/C2 series machines; not required for B3-Series high flow Installation time: 3.0 hours, instructions see REHS8316	22	\$1,563 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BROOMS, PICKUP

																				287
																				289
		226	228		239			248			257	262			277	297				
	216	242	232	236	249	246	247	268	252	256	259	272	267	279	299					
BP115C	C*#	C*	C*	C*	C	C	C	C	C	C	C	C	C	C	C	C				
BP118C				C*	C*	C	C	C	C	C	C	C	C	C	C	C				

C = Compatible/ *= lift restricted/ # = Extra counter weight required
Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	448-5680	BROOM, PICKUP, BP115C	1,160	\$7,243 NI
		1990mm (78") overall width, 1524mm (60") working width 26" (660mm) brush diameter Adjustable brush height. Volumizer increases material retention. Brush material - 50% polypropylene / 50% steel wire INCLUDES: Hydraulic lines with 1/2" quick disconnects and brush frame chains REQUIRES: Pickup broom bracket for A/B Series; Not needed for C/D Series REQUIRES: Standard Flow Hydraulics		
W	448-5690	BROOM, PICKUP, BP118C	1,258	\$7,785 NI
		2295mm (90") overall width, 1829mm (72") working width 26" (660mm) brush diameter Adjustable brush height. Volumizer increases material retention. Brush material - 50% polypropylene / 50% steel wire INCLUDES: Hydraulic lines with 1/2" quick disconnects and brush frame chains REQUIRES: Pickup broom bracket for A/B Series machines; Not needed for C/D Series REQUIRES: Standard Flow Hydraulics		

BROOMS, PICKUP - OPTIONS

W	452-4185	KIT, WATER SPRINK, BP115C-118C	6	\$194 NI
		INCLUDES 2 sprinkler heads, hoses, hardware and quick disconnects FOR USE WITH: BP115C and BP118C pick-up brooms only REQUIRES: Control, Work Tool, Electrical (order with machine) REQUIRES: Water Tank, Machine (reference machine attachments section)		
W	452-4150	KIT, GUTTER BRUSH, C-SERIES	90	\$1,785 NI
		100% Steel wire bristles (Poly available via parts only) Left or right side mount INCLUDES: motor, brackets, assembled hoses, and fittings FOR USE WITH: BP115C and BP118C pick-up brooms only Installation time: 3.0 hours, instructions see REHS8313		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BROOMS, PICKUP - BRACKETS

Pick Up Broom Brackets are required for use with A & B Series machines
 They are not needed for C or D Series machines.

W	296-3649	BRACKET, BROOM, RADIAL A-B 51 Supports brush frame while dumping INCLUDES: right and left side bracket assemblies to attach to machine lift arms REQUIRED FOR: 216, 226, 228, 236, 246, 247, 248, 267 or 277 A & B Series machines		\$431 NI
W	296-3647	BRACKET, BROOM, BETA A-B 20 Supports brush frame while dumping INCLUDES: right and left side bracket assemblies and chains to attach to machine lift arms REQUIRED FOR: 252, 262, 268 or 287 A & B Series machines		\$229 NI
W	296-3648	BRACKET, BROOM, ALPHA A-B 34 Supports brush frame while dumping INCLUDES: right and left side bracket assemblies to attach to machine lift arms REQUIRED FOR: 232, 242, 257 or 259 A & B Series machines		\$285 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS												Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	--	--	--	--	--	--	--	--	--	--	--	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BROOMS, UTILITY

																	287
																	289
		228		239			248			257	262			277	297		
	216	226	232	249	242	246	247	268	252	256	259	272	267	279	299		
BU115	C*	C*	C*	C*	C	C	C	C	C	C	C	C	C	C	C	C	
BU118				C*	C*	C	C	C	C	C	C*	C	C	C	C	C	

C = Compatible/ *= lift restricted
 Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	493-2258	BROOM, UTILITY, BU115, BOCE	967	\$4,944 NI
		1810mm (71") overall width, 1510mm (59") sweeping width 660mm (26") brush diameter - brush material: 100% polypropylene INCLUDES: bolt-on cutting edge Requires: Standard Flow Hydraulics		
W	493-2259	BROOM, UTILITY, BU118, BOCE	1,067	\$5,375 NI
		2115mm (83") overall width, 1865mm (73") sweeping width 660mm (26") brush diameter - brush material 100% polypropylene INCLUDES: bolt on cutting edge Requires: Standard Flow Hydraulics		

BROOMS, UTILITY - OPTIONS

W	242-7200	BRUSH, GUTTER, B-SERIES	119	\$2,826 NI
		100% Steel wire bristles (Poly available via parts only) Left or right side mount All hydraulic lines included FOR USE WITH: BP15B/BP18B pick-up broom and BU115/BU118 utility brooms only REQUIRES: 257-5229 Mounting kit if used on BU115/BU118 utility brooms only		
W	257-5229	KIT, GUTTER BRUSH MOUNTING	0	\$250 NI
		FOR USE WITH: 242-7200 BRUSH, GUTTER, B-SERIES and BU115 or BU118		
W	257-3140	MOUNTING BRACKET, NOZZLE	2	\$28 NI
		Additional mounting brackets for sprinkler heads on Utility Brooms only. FOUR REQUIRED PER BROOM.		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BROOMS, UTILITY - OPTIONS (Cont.)

W	256-9335	KIT, WATER SPRINKLER 10 Work tool water sprinkling kit complete with sprinkler heads (4) hoses, mounting hardware and quick disconnects for effective dust control. FOR USE WITH: BP15B/BP18B pick-up broom and BU115/BU118 utility brooms only REQUIRES: Control, Work Tool, Electrical (order with machine) REQUIRES: Water Tank (choose either machine cab mounted or utility broom mounted); Reference Machine Attachments section or Broom Options section of this price list to order REQUIRES: Mounting Brackets, qty 4 257-3140, if installing sprinkler kit on utility broom and installing machine cab mounted water tank		\$235 NI
W	304-9870	KIT, WATER TANK, BROOM 31 Broom mounted water tank - 110 litres for BU115 & BU118 INCLUDES: Tank, pump, filter, harness+ 8 pin plug, hardware, 4 nozzle brackets but excl. the nozzles REQUIRES: Control, Work Tool, Electrical (order with machine) REQUIRES: 375-6445 HARNESS, CVSN 8WT to 14SSL for D series		\$850 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS				Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	--	--	--	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BROOMS, UTILITY - BRISTLES and BOLT-ON CUTTING EDGES

Please order direct from parts/Antares (no bridge orders)

Bolt-on-Cutting Edges:	BU115 BP15B	BU118 BP18B	BP115C	BP118C
489-6702 Edge *	1x			
489-6703 Edge *		1x		
452-4147 Edge *				1x
452-4148 Edge *			1x	
4F-3648 Bolt	6x	7x	6x	7x
6V-8188 Nut	6x	7x	6x	7x

* = Requires Nuts and bolts. Order qty as stated in table.

Bristles	BA18 BA118C	BU115	BU118	BP15B BP115C	BP18B BP118C
----------	----------------	-------	-------	-----------------	-----------------

Bristles kits: These kits are 1/2 of a full set. Order 2 for a full set. You can go 50/50% Poly/Wire or 100% Poly or 100% Wire.

562-7622 Poly Yellow (22)	C*				
562-7623 Poly Cold Blue #	C*				
562-7624 Wire Steel (21)	C*				
562-7602 Poly Yellow (18)		C**		C*	
562-7603 Poly Cold Blue #		C**		C*	
562-7604 Wire Steel (17)		C**		C*	
562-7612 Poly Yellow (21)			C**		C*
562-7613 Poly Cold Blue #)			C**		C*
562-7614 Wire Steel (20)			C**		C*

Gutter Brush Bristles, full set:

460-9777 Poly	C	C	C	C
172-4563 Wire	C	C	C	C

C = Compatible

= Special cold weather, blue, poly bristle kit, order 2 for full kit

* = BP15B, BP115C, BA18, BA118C come standard 50/50% Poly/Wire

** = BU115 and BU118 comes standard 100% Poly.

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BRUSHCUTTERS

The Turbo Guard Kit and the Debris Kit are required (when available) in applications with the potential for airborne debris. Example airborne debris laden environments are mulching, brushcutting, forestry applications, mowing, certain agricultural applications, paper recycling, etc..

Please refer to the machine price pages "Field Installed Attachments" section for the appropriate part numbers.

NOTE: Guarding the operator against flying objects RECOMMENDED. If not ordered with machine; Door, Cab, Polycarbonate should be ordered. Please see machine price list for availability.

Nomenclature change: BR115 is replacement for BR160, NO techn. changes
 BR115 stands for standard flow + working width ca. 1.5m
 Nomenclature change: BR117 is replacement for BR166, NO techn. changes
 BR117 stands for standard flow + working width ca. 1.7m
 Nomenclature change: BR118 is replacement for BR172, NO techn. changes
 BR118 stands for standard flow + working width ca. 1.8m
 Nomenclature change: BR218 is replacement for BR272, NO techn. changes
 BR218 stands for High flow + working width ca. 1.8m
 Nomenclature change: BR320 is replacement for BR378, NO techn. changes
 BR320 stands for High Flow XPS + working width ca. 2.0m

	ALL SERIES									SPECIFIC SERIES			
	216	226	239	252	248	268	279	297	242	257	242B3	242D	
BR115	++	++	++	++	--	--	--	--	++	++	--	--	
BR117	--	--	--	--	++	++	++	++	--	--	++	++	
BR118	--	--	--	--	++	++	++	++	--	--	++	++	
BR218 HF	--	++	--	++	--	--	--	--	++	++	--	--	
BR320 XPS	--	--	--	--	--	++	++	++	--	--	--	--	

++ = Optimal attachment-machine combination, -- = Not Allowed

W	264-9500	BRUSHCUTTER, BR115.	940	\$6,153 NI
		BR115 (old BR160) stands for standard flow + working width ca. 1.5m 1524mm (60") working width, 1575mm (62") overall width Hydraulic flow range: 57-65 l/min (15-17 gpm) Hydraulic pressure range: 150-230 bar (2,176-3,340 psi) REQUIRES: Standard Flow Hydraulics; Not compatible with 80 LPM REQUIRES: Turbo Guard Kit and Debris Kit on machine		
W	264-9600	BRUSHCUTTER, BR117.	1,020	\$6,439 NI
		BR117 (old BR166) stands for standard flow + working width ca. 1.7m Hydraulic flow range: 57-80 l/min (15-21 gpm) Hydraulic pressure range: 150-230 bar (2,176-3,340 psi) 1676mm (66") working width, 1727mm (68") overall width REQUIRES: Standard Flow Hydraulics REQUIRES: Turbo Guard Kit and Debris Kit on machine		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BRUSHCUTTERS (Cont.)

W	264-9400	BRUSHCUTTER, BR118. 1,094 BR118 (old BR172) stands for standard flow + working width ca. 1.8m 1829mm (72") working width, 1880mm (74") overall width Hydraulic flow range: 57-80 l/min (15-21 gpm) Hydraulic pressure range: 150-230 bar (2,176-3,340 psi) REQUIRES: Standard Flow Hydraulics REQUIRES: Turbo Guard Kit and Debris Kit on machine		\$6,725 NI
W	424-0435	BRUSHCUTTER, BR218, HF 1,096 BR218 (old BR272) stands for High flow + working width ca. 1.8m 1829mm (72") working width, 1880mm (74") overall width Hydraulic flow range: 76-100 l/min (20-26 gpm) Hydraulic pressure range: 150-230 bar (2,176-3,340 psi) INCLUDES: Hydraulic lines with 1/2" quick disconnects, mounting bracket, 14-pin electrical HF Jumper REQUIRES: 100-104 LPM High flow hydraulics FOR USE WITH: 226B/B2/B3, 242B/B2, 257B/B2 machines CAN NOT BE USED WITH: 242B3, 257B3, & 259B3 REQUIRES: 8-pin electrical high flow jumper 241-3763 for B/B2 series machines or 226B3 REQUIRES: Turbo Guard Kit and Debris Kit on machine		\$7,011 NI
W	424-0436	BRUSHCUTTER, BR320, HF XPS 1,175 BR320 (old BR378) stands for High Flow XPS + working width ca. 2.0m 1982mm (78") working width, 2032mm (80") overall width Hydraulic flow range: 76-130 l/min (20-34 gpm) Hydraulic pressure range: 150-280 bar (2,176-4,065 psi) REQUIRES: High Flow XPS or High Flow Hydraulics REQUIRES: 8-pin jumper plug 241-3763 for B/B2/C/C2 series machines REQUIRES: kit 382-6192 for D series with XHP and prefix NLC/SHY REQUIRES: Turbo Guard Kit and Debris Kit on machine		\$8,443 NI

BRUSHCUTTERS - INDUSTRIAL

The Turbo Guard Kit and the Debris Kit are required (when available) in applications with the potential for airborne debris. Example airborne debris laden environments are mulching, brushcutting, forestry applications, mowing, certain agricultural applications, paper recycling, etc.. Please refer to the machine price pages "Field Installed Attachments" section for the appropriate part numbers.

NOTE: Guarding the operator against flying objects RECOMMENDED. If not ordered with machine; Door, Cab, Polycarbonate should be ordered. Please see machine price list for availability.

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BRUSHCUTTERS - INDUSTRIAL (Cont.)

	226	232	242	247	252	257	277	287	297						
	216	228	236	239	246	248	249	256	259	262	267	272	279	289	299
BRX118							C#*	C#*		C	C	C	C	C	C
BRX318 HF XPS							C#*	C#*		C	C	C	C	C	C
BRX418 XE/XHP										C					C

C = Compatible/ *= lift restricted/ # = Extra counter weight required

If no reference numbers appear below there are currently no items available in your region.

W	523-5560	BRUSHCUTTER, BRX118. 2,380	\$15,542 NI
		1829mm (72") working width, 1911mm (75") overall width Max cutting diameter 200mm (8") Hydraulic flow range: 76-87 l/min (20-23 gpm) Hydraulic pressure range: 230 bar (3,330 psi) INCLUDES: Hydraulic lines with 1/2" quick disconnects and case drain to be connected with machine case drain REQUIRES: Standard Flow hydraulics and case drain REQUIRES: Turbo Guard Kit and Debris Kit on machine	
W	523-5570	BRUSHCUTTER, BRX318. 2,380	\$15,958 NI
		1829mm (72") working width, 1911mm (75") overall width Max cutting diameter 200mm (8") Hydraulic flow range: 120-125 l/min (31-33 gpm) Hydraulic pressure range: 280 bar (4,060 psi) INCLUDES: Hydraulic lines with 1/2" quick disconnects, mounting bracket, 14-pin electrical HF XPS Jumper plug REQUIRES: High flow or High Flow XPS hydraulics REQUIRES: 8-pin electrical high flow jumper 241-3763 for B/B2/C/C2 series machines REQUIRES: Turbo Guard Kit and Debris Kit on machine	
W	523-5580	BRUSHCUTTER, BRX418. 2,380	\$15,958 NI
		1829mm (72") working width, 1911mm (75") overall width Max cutting diameter 200mm (8") Hydraulic flow range: 150-155 l/min (40-41 gpm) Hydraulic pressure range: 280 bar (4,060 psi) INCLUDES: Hydraulic lines with 3/4" quick disconnects, mounting bracket, 14-pin electrical XE/XHP Jumper plug REQUIRES: XE or XHP hydraulics REQUIRES: Turbo Guard Kit and Debris Kit on machine REQUIRES: Conversion to screw-to-connect quick disconnects for: 299D2 XHP, serial prefix HLM (see M0097141) and 299D3 XE, serial prefix XES/LB3 (see M0110695)	

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS - GENERAL PURPOSE

All purpose buckets. For construction, landscaping, industrial and more aggressive job site requirements.

216	232	242				262	272			
226	236	246	248	256	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

1576mm (62")	C	C	C	C	C	C	C	C	C	C
1730mm (68")	C	C	C	C	C	C	C	C	C	C
1883mm (74")	C	C	C	C	C	C	C	C	C	C
2036mm (80")	C	C	C	C	C	C	C	C	C	C
2188mm (86")	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	279-5364	BUCKET-GP, 62", BASE EDGE	448	\$1,267 NI
		Width over base edge 1576mm (62"), 0.36 m3 (0.47 yd3) Heaped Capacity		
		INCLUDES: Base Edge with drilled mounting holes		
W	279-5365	BUCKET-GP, 62", BOCE	448	\$1,474 NI
		Width over base edge 1576mm (62"), 0.36 m3 (0.47 yd3) Heaped Capacity		
		INCLUDES: 1 piece Bolt-on cutting edge		
W	279-5366	BUCKET-GP, 62", BOT	448	\$1,544 NI
		Width over base edge 1576mm (62"), 0.36 m3 (0.47 yd3) Heaped Capacity		
		INCLUDES: 8 Single Strap Bolt-on Uniteeth		
		Recommended for use with C-Series machines		
W	279-5368	BUCKET-GP, 68", BASE EDGE	561	\$1,382 NI
		Width over base edge 1730mm (68"), 0.40 m3 (0.52 yd3) Heaped Capacity		
		INCLUDES: Base Edge with drilled mounting holes		
W	279-5369	BUCKET-GP, 68", BOCE	561	\$1,608 NI
		Width over base edge 1730mm (68"), 0.40 m3 (0.52 yd3) Heaped Capacity		
		INCLUDES: 1 piece Bolt-on cutting edge		
W	279-5370	BUCKET-GP, 68", BOT	561	\$1,660 NI
		Width over base edge 1730mm (68"), 0.40 m3 (0.52 yd3) Heaped Capacity		
		INCLUDES: 8 Single Strap Bolt-on Uniteeth		
W	279-5372	BUCKET-GP, 74", BASE EDGE	597	\$1,499 NI
		Width over base edge 1883mm (74"), 0.44 m3 (0.57 yd3) Heaped Capacity		
		INCLUDES: Base Edge with drilled mounting holes		
W	279-5373	BUCKET-GP, 74", BOCE	597	\$1,744 NI
		Width over base edge 1883mm (74"), 0.44 m3 (0.57 yd3) Heaped Capacity		
		INCLUDES: 1 piece Bolt-on cutting edge		
W	279-5374	BUCKET-GP, 74", BOT	597	\$1,776 NI
		Width over base edge 1883mm (74"), 0.44 m3 (0.57 yd3) Heaped Capacity		
		INCLUDES: 8 Single Strap Bolt-on Uniteeth		
W	279-5376	BUCKET-GP, 80", BASE EDGE	631	\$1,614 NI
		Width over base edge 2036mm (80"), 0.48 m3 (0.62 yd3) Heaped Capacity		
		INCLUDES: Base Edge with drilled mounting holes		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS - GENERAL PURPOSE (Cont.)

W	279-5377	BUCKET-GP, 80", BOCE 631 Width over base edge 2036mm (80"), 0.48 m3 (0.62 yd3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge		\$1,881 NI
W	279-5378	BUCKET-GP, 80", BOT 631 Width over base edge 2036mm (80"), 0.48 m3 (0.62 yd3) Heaped Capacity INCLUDES: 9 Single Strap Bolt-on Uniteeth		\$1,926 NI
W	292-9270	BUCKET-GP, 86", BASE EDGE 635 Width over base edge 2188mm (86"), 0.63 m3 (0.82 yd3) Heaped Capacity INCLUDES: Base Edge with drilled mounting holes		\$1,729 NI
W	296-8192	BUCKET-GP, 86", BOCE 723 Width over base edge 2188mm (86"), 0.63 m3 (0.82 yd3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge		\$2,017 NI
W	296-8191	BUCKET-GP, 86", BOT 669 Width over base edge 2188mm (86"), 0.63 m3 (0.82 yd3) Heaped Capacity INCLUDES: 9 Single Strap Bolt-on Uniteeth		\$2,042 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS - INDUSTRIAL PERFORMANCE

Heavy duty buckets. For construction, industrial and aggressive job site requirements.

	226	232	242	247	252	257	262	277	287	297				
	228	236	239	246	248	249	256	259	268	267	272	279	289	299
1676mm (68")	C	C	C	C	C	C	C	C	C	C	C	C	C	C
1830mm (74")	C	C	C	C	C	C	C	C	C	C	C	C	C	C
1980mm (80")	C	C	C	C	C	C	C	C	C	C	C	C	C	C
2134mm (86")	C	C	C	C	C	C	C	C	C	C	C	C	C	C
2286mm (92")	C	C	C	C	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	532-7738	BUCKET-IND, 68", BOCE 700 Width over base edge 1676mm (68"), 0.53m3 (0.69yd3) Heaped Capacity INCLUDES: Bolt-on cutting edge and bolt-on side cutters	\$2,507 NI
W	532-7739	BUCKET-IND, 68", BOT 662 Width over base edge 1676mm (68"), 0.51m3 (0.67yd3) Heaped Capacity INCLUDES: Bolt-on teeth and bolt-on side cutters	\$2,563 NI
W	532-7741	BUCKET-IND, 74", BOCE 739 Width over base edge 1830mm (74"), 0.58m3 (0.76yd3) Heaped Capacity INCLUDES: Bolt-on cutting edge and bolt-on side cutters	\$2,646 NI
W	532-7742	BUCKET-IND, 74", BOT 693 Width over base edge 1830mm (74"), 0.56m3 (0.73yd3) Heaped Capacity INCLUDES: Bolt-on teeth and bolt-on side cutters	\$2,681 NI
W	532-7744	BUCKET-IND, 80", BOCE 777 Width over base edge 1980mm (80"), 0.63m3 (0.82yd3) Heaped Capacity INCLUDES: Bolt-on cutting edge and bolt-on side cutters	\$2,785 NI
W	532-7745	BUCKET-IND, 80", BOT 729 Width over base edge 1980mm (80"), 0.61m3 (0.8yd3) Heaped Capacity INCLUDES: Bolt-on teeth and bolt-on side cutters	\$2,826 NI
W	532-7747	BUCKET-IND, 86", BOCE 814 Width over base edge 2134mm (86"), 0.68m3 (0.89yd3) Heaped Capacity INCLUDES: Bolt-on cutting edge and bolt-on side cutters	\$2,917 NI
W	532-7748	BUCKET-IND, 86", BOT 762 Width over base edge 2134mm (86"), 0.66m3 (0.86yd3) Heaped Capacity INCLUDES: Bolt-on teeth and bolt-on side cutters	\$2,944 NI
W	532-7750	BUCKET-IND, 92", BOCE 854 Width over base edge 2286mm (92"), 0.73m3 (0.95yd3) Heaped Capacity INCLUDES: Bolt-on cutting edge and bolt-on side cutters	\$3,056 NI
W	532-7751	BUCKET-IND, 92", BOT 794 Width over base edge 2286mm (92"), 0.71m3 (0.93yd3) Heaped Capacity INCLUDES: Bolt-on teeth and bolt-on side cutters	\$3,063 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS - LOW PROFILE (DIRT)

Low profile buckets with capacity similar to industry descriptions of low profile or dirt buckets; For use in construction or landscaping, agriculture, or applications that capacity is less important, price point very important, and highest breakout forces can be achieved with shortest flow of bucket offering. Previously described as Dirt (DT) Buckets.

Frequently used in rental, and cost sensitive customers.

216	232	242				262	272			
226	236	246	248	256	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

1421mm (56")	C	C	C	C	C	C	C	C	C	C
1576mm (62")	C	C	C	C	C	C	C	C	C	C
1730mm (68")	C	C	C	C	C	C	C	C	C	C
1883mm (74")	C	C	C	C	C	C	C	C	C	C
2036mm (80")	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	279-5434	BUCKET-LP, 56", BASE EDGE	392	\$782 NI
		Width over base edge 1421mm (56"), 0.30 m3 (0.39 yd3) Heaped Capacity		
		INCLUDES: Base Edge with drilled mounting holes		
W	279-5435	BUCKET-LP, 56", BOCE	392	\$969 NI
		Width over base edge 1421mm (56"), 0.30 m3 (0.39 yd3) Heaped Capacity		
		INCLUDES: 1 piece Bolt-on cutting edge		
W	279-5438	BUCKET-LP, 62", BOCE	451	\$1,106 NI
		Width over base edge 1576mm (62"), 0.34 m3 (0.44 yd3) Heaped Capacity		
		INCLUDES: 1 piece Bolt-on cutting edge		
W	279-5440	BUCKET-LP, 68", BASE EDGE	512	\$1,014 NI
		Width over base edge 1730mm (68"), 0.37 m3 (0.48 yd3) Heaped Capacity		
		INCLUDES: Base Edge with drilled mounting holes		
W	279-5441	BUCKET-LP, 68", BOCE	512	\$1,240 NI
		Width over base edge 1730mm (68"), 0.37 m3 (0.48 yd3) Heaped Capacity		
		INCLUDES: 1 piece Bolt-on cutting edge		
W	285-6089	BUCKET-LP, 74", BASE EDGE	546	\$1,131 NI
		Width over base edge 1883mm (74"), 0.41 m3 (0.53 yd3) Heaped Capacity		
		INCLUDES: Base Edge with drilled mounting holes		
W	285-6090	BUCKET-LP, 74", BOCE	546	\$1,376 NI
		Width over base edge 1883mm (74"), 0.41 m3 (0.53 yd3) Heaped Capacity		
		INCLUDES: 1 piece Bolt-on cutting edge		
W	268-4084	BUCKET-LP, 80", BASE EDGE	583	\$1,246 NI
		Width over base edge 2036mm (80"), 0.44 m3 (0.57 yd3) Heaped Capacity		
		INCLUDES: Base Edge with drilled mounting holes		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-------------------------------	--------------------	-------------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS - LOW PROFILE (DIRT) (Cont.)

W	268-4083	BUCKET-LP, 80", BOCE 583 Width over base edge 2036mm (80"), 0.44 m3 (0.57 yd3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge		\$1,513 NI
---	----------	----------------------------------------------------------------------------------------------------------------------------------------------------------	--	-------------------

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS - LIGHT MATERIAL

High capacity buckets. Ideal for handling light duty material, such as landscaping mulch, fertilizer, livestock feed and litter. Often used in landscaping and agricultural applications.

	216	232	242			262	272			
	226	236	246	248	256	257	267	277	287	297
	228	239	247	249	256	259	268	279	289	299
1830mm (72")	C	C	C	C	C	C	C	C	C	C
1980mm (78")	C	C	C	C	C	C	C	C	C	C
2138mm (86")	C	C	C	C	C	C	C	C	C	C
2490mm (98")	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	279-5420	BUCKET-LM, 74", BOCE 668 Width over base edge 1883mm (74"), 0.69 m3 (0.90 yd3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge	\$1,814 NI
W	279-5425	BUCKET-LM, 80", BOCE 706 Width over base edge 2036mm (80"), 0.75 m3 (0.98 yd3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge	\$1,950 NI
W	279-5430	BUCKET-LM, 86", BOCE 746 Width over base edge 2188mm (86"), 0.84 m3 (1.1 yd3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge	\$2,086 NI
W	296-7597	BUCKET-LM, 98", BOCE 806 Width over base edge 2490mm (98"), 0.93 m3 (1.22 yd3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge	\$2,357 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS - MATERIAL HANDLING

Designed for handling materials with a very low density and for which even Light Material buckets are too small.

216	232	242				262	272			
226	236	246	248	256	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

21388m (86")	C	C	C	C	C	C	C	C	C	C
2490mm (98")	C	C	C	C	C	C	C	C	C	C
2642mm (104")	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	472-2546	BUCKET-MH, 86", BOCE 804	\$2,326 NI
		Width over base edge 2185mm (86"), 1.07 m3 (1.43 yd3) Heaped Capacity	
		INCLUDES: 1 piece Bolt-on cutting edge	
W	472-2548	BUCKET-MH, 98", BOCE 881	\$2,403 NI
		Width over base edge 2490mm (98"), 1.25 m3 (1.63 yd3) Heaped Capacity	
		INCLUDES: 1 piece Bolt-on cutting edge	
W	469-0774	BUCKET-MH, 104", BOCE 920	\$2,444 NI
		Width over base edge 2642mm (104"), 1.33 m3 (1.74 yd3) Heaped Capacity	
		INCLUDES: 1 piece Bolt-on cutting edge	

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS - MIXING

Mixing Buckets are designed for material mixing in a variety of applications. Utilizing a chain driven auger equipped with replaceable paddles, the Cat Mixing Buckets ensure complete and repeatable mixing. Operated from the machine cab, mixing buckets are equipped with a hydraulically controlled dispensing chute. The Mixing Buckets allow work to be completed in difficult to access areas, improving productivity and savings on transportation costs.

	226	232	239	247	248	257	262	277	287	297					
	216	228	236	242	246	249	268	252	256	259	272	267	279	289	299
MB200	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
MB250				C#	C#	C	C	C	C	C	C	C	C	C	C

C = Compatible/ # = Extra counter weight required
 Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	489-2150	BUCKET, MIXING, MB200, 0.26YD3 639	\$7,222 NI
		Overall width 1605mm (63"), 0.20 m3 (0.26yd3) Capacity INCLUDES: Hydraulic lines with 1/2" quick disconnects, 14 pin electrical harness. Rigid Chute and Flexible Chute REQUIRES: Standard Flow Hydraulics REQUIRES: Work Tool Harness and 4 button left hand joystick on machine mounting bracket, & 14-pin electrical harness	
W	489-2200	BUCKET, MIXING, MB250, 0.33YD3 948	\$7,556 NI
		Overall width 1605mm (63"), 0.25 m3 (0.33yd3) Capacity INCLUDES: Hydraulic lines with 1/2" quick disconnects, 14 pin electrical harness, Rigid Chute and Flexible Chute REQUIRES: Standard Flow Hydraulics REQUIRES: Work Tool Harness and 4 button left hand joystick on machine mounting bracket, & 14-pin electrical harness	

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS - MULTI PURPOSE

Similar applications as GP Buckets but with clamping versatility.

216	232	242				262	272			
226	236	246	248	256	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

1576mm (62")	C	C	C	C	C	C	C	C	C	C
1730mm (68")	C	C	C	C	C	C	C	C	C	C
1883mm (74")	C	C	C	C	C	C	C	C	C	C
2036mm (80")	C	C	C	C	C	C	C	C	C	C
2188mm (86")	C	C	C	C	C	C	C	C	C	C

C = Compatible

Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	431-5570	BUCKET-MP, 62", BOCE 851 Width over base edge 1576mm (62"), 0.30 m3 (0.39 yd3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge, spillguard to prevent material spillage over back of bucket.	\$3,972 NI
W	423-4287	BUCKET-MP, 62", BOT 818 Width over base edge 1576mm (62"), 0.30 m3 (0.39 yd3) Heaped Capacity INCLUDES: 8 Single Strap Bolt On Uniteeth, spillguard to prevent material spillage over back of bucket.	\$3,972 NI
W	426-6490	BUCKET-MP, 68", BOCE 907 Width over base edge 1730mm (68"), 0.34 m3 (0.44 yd3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge, spillguard to prevent material spillage over back of bucket.	\$4,306 NI
W	426-6487	BUCKET-MP, 68", BOT 868 Width over base edge 1730mm (68"), 0.34 m3 (0.44 yd3) Heaped Capacity INCLUDES: 8 Single Strap Bolt On Uniteeth, spillguard to prevent material spillage over back of bucket.	\$4,306 NI
W	426-6536	BUCKET-MP, 74", BOCE 962 Width over base edge 1883mm (74"), 0.37 m3 (0.48 yd3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge, spillguard to prevent material spillage over back of bucket.	\$4,639 NI
W	426-6535	BUCKET-MP, 74", BOT 917 Width over base edge 1883mm (74"), 0.37 m3 (0.48 yd3) Heaped Capacity INCLUDES: 8 Single Strap Bolt On Uniteeth, spillguard to prevent material spillage over back of bucket.	\$4,639 NI
W	426-6548	BUCKET-MP, 80", BOCE 1,016 Width over base edge 2036mm (80"), 0.40 m3 (0.52 yd3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge, spillguard to prevent material spillage over back of bucket.	\$4,972 NI
W	426-6547	BUCKET-MP, 80", BOT 969 Width over base edge 2036mm (80"), 0.40 m3 (0.52 yd3) Heaped Capacity INCLUDES: 9 Single Strap Bolt On Uniteeth, spillguard to prevent material spillage over back of bucket.	\$4,972 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS - MULTI PURPOSE (Cont.)

W	426-6558	BUCKET-MP, 86", BOCE 1,072 Width over base edge 2188mm (86"), 0.43 m3 (0.56 yd3) Heaped Capacity INCLUDES: 1 piece Bolt-on cutting edge, spillguard to prevent material spillage over back of bucket.		\$5,306 NI
W	426-6557	BUCKET-MP, 86", BOT 1,018 Width over base edge 2188mm (86"), 0.43 m3 (0.56 yd3) Heaped Capacity INCLUDES: 9 Single Strap Bolt On Uniteeth, spillguard to prevent material spillage over back of bucket.		\$5,306 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKET: SIDE DISCHARGE

The side discharge buckets can discharge left or right hand side. The sawdust version is for light materials like sawdust, mulch, straw or silage. The sand version is for heavier materials like sand, soil or light aggregate.

	226	232	242	247	252	257	262	277	287	297				
	228	236	239	246	248	249	256	259	268	267	272	279	289	299
BD118	C	C	C	C	C	C	C	C	C	C	C	C	C	C
BD121	C	C	C	C	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	477-9895	BUCKET-SD, 72", BD118, SAWDUST	1,179	\$7,917 NI
		Capacity: 1.53m3 (2.0yd3), Belt width 305mm (12") Inside / Overall width: 1860mm (72") / 1854mm (73") 3 Direct Drive hydr.motors (2 for the belt and 1 for sawdust agitator) FOR USE WITH: Skid Steer Coupler REQUIRES: Standard Flow Hydraulics		
W	479-8085	BUCKET-SD, 84", BD121, SAWDUST	1,276	\$9,583 NI
		Capacity: 1.78m3 (2.33yd3), Belt width 305mm (12") Inside / Overall width: 2160mm (84") / 2159mm (85") 3 Direct Drive hydr.motors (2 for the belt and 1 for sawdust agitator) FOR USE WITH: Skid Steer Coupler REQUIRES: Standard Flow Hydraulics		
W	479-8095	BUCKET-SD, 72", BD118, SAND	1,060	\$7,917 NI
		Capacity: 0.76m3 (1.0yd3), Belt width 305mm (12") Inside / Overall width: 1860mm (72") / 1854mm (73") 3 Direct Drive hydr.motors (2 for the belt and 1 for sand agitator) FOR USE WITH: Skid Steer Coupler REQUIRES: Standard Flow Hydraulics		
W	479-8105	BUCKET-SD, 84", BD121, SAND	1,151	\$9,583 NI
		Capacity: 1.02m3 (1.33yd3), Belt width 305mm (12") Inside / Overall width: 2160mm (84") / 2159mm (85") 3 Direct Drive hydr.motors (2 for the belt and 1 for sand agitator) FOR USE WITH: Skid Steer Coupler REQUIRES: Standard Flow Hydraulics		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS: SKELETON, PLATE STYLE

The plate/rib style skeleton bucket is an addition to the rod style skeleton bucket. It allows to be used in more demanding applications in agricultural, land management and on construction sites for quickly sifting solid objects from loose materials. It has good visibility while handling materials.

Compatibility table

	216	232	242				262	272					
	226	236	246	248	252	257	267	277	287	297			
	228	239	247	249	256	259	268	279	289	299			
1880mm (74")	C	C	C	C	C	C	C	C	C	C	C	C	C
2032mm (80")	C	C	C	C	C	C	C	C	C	C	C	C	C
2184mm (86")	C	C	C	C	C	C	C	C	C	C	C	C	C
2349mm (92")	C	C	C	C	C	C	C	C	C	C	C	C	C

C = Compatible

W	553-2143	BUCKET-SK, PLATE, 74"	728	\$1,924 NI
		Overall Width-Height-Depth: 1869mm(74") - 529mm(21") - 1055mm(41.5")		
		Width over the plates: 1848mm (73"), Width between plates: 73mm (3")		
		Number of plates/ribs: 23, Plate/rib thickness: 10mm (0.4")		
W	563-1393	BUCKET-SK, PLATE, 80"	754	\$2,042 NI
		Overall Width-Height-Depth: 2036mm(80") - 529mm(21") - 1055mm(41.5")		
		Width over the plates: 2017mm (80"), Width between plates: 73mm (3")		
		Number of plates/ribs: 25, Plate/rib thickness: 10mm (0.4")		
W	563-1400	BUCKET-SK, PLATE, 86"	802	\$2,160 NI
		Overall Width-Height-Depth: 2202mm(74") - 529mm(21") - 1055mm(41.5")		
		Width over the plates: 2183mm (86"), Width between plates: 73mm (3")		
		Number of plates/ribs: 27, Plate/rib thickness: 10mm (0.4")		
W	564-3039	BUCKET-SK, PLATE, 92"	855	\$2,278 NI
		Overall Width-Height-Depth: 2368mm(93") - 529mm(21") - 1055mm(41.5")		
		Width over the plates: 2349mm (93"), Width between plates: 73mm (3")		
		Number of plates/ribs: 29, Plate/rib thickness: 10mm (0.4")		

BUCKETS - SKELETON, ROD STYLE

	226	232		242		247	252	257	262		277	287	297	
	228	236	239	246	248	249	256	259	268	267	272	279	289	299
2020mm (79")	C	C	C	C	C	C	C	C	C	C	C	C	C	C
2210mm (87")	C	C	C	C	C	C	C	C	C	C	C	C	C	C
2400mm (94")	C	C	C	C	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	549-6561	BUCKET-SK, ROD, 79"	741	\$2,326 NI
		Overall width: 2020mm (79"), Height: 644mm (25.4"), 21 welded teeth,		
		20 x 32mm (1.25") rods, spacing between rods 63.5mm (2.5")		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS - SKELETON, ROD STYLE (Cont.)

W	549-6563	BUCKET-SK, ROD, 87"	800	\$2,472 NI
		Overall width: 2210mm (87"), Height: 644mm (25.4"), 23 welded teeth, 22 x 32mm (1.25") rods, spacing between rods 63.5mm (2.5")		
W	549-6565	BUCKET-SK, ROD, 94"	860	\$2,618 NI
		Overall width: 2400mm (94"), Height: 644mm (25.4"), 25 welded teeth, 24 x 32mm (1.25") rods, spacing between rods 63.5mm (2.5").		

BUCKETS - CONCRETE SLAB

A simple way for handling concrete slabs with this slab bucket.

Compatibility for B Series machines and up:

	B & B2 & B3	C & C2	D & D2 & D3
232	226	262 287	246 279 272
236 252 242 257		246 277 289	226 239 236 257 262 287 297
247 262 268 259		256 279 299	232 249 242 259 277 289 299
Slab Bucket	++ ++ ++ ++	++ ++ ++	++ ++ ++ ++ ++ ++ ++

++ = Optimal attachment-machine combination

W	598-2232	BUCKET, CONCRETE SLAB, 24"	463	\$2,264 NI
		Working - overall width: 607mm (24") - 1150mm (45.3"), Overall height - length: 460mm (18.1") - 1332mm (52.4") Side plates: material thickness: 20mm (0.8"), Opening: 202mm (7.9") INCLUDES: 3 x J200 Long Tip Teeth (width over teeth 541mm (17.8"))		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

BUCKETS - UTILITY

Higher capacity buckets. For landscaping and agricultural work requiring grading, leveling, and stockpiling material.

	216	232	242			262	272			
	226	236	246	248	256	257	267	277	287	297
	228	239	247	249	256	259	268	279	289	299
1576mm (62")	C	C	C	C	C	C	C	C	C	C
1730mm (68")	C	C	C	C	C	C	C	C	C	C
1883mm (74")	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	285-6095	BUCKET-UT, 62", BOCE	531	\$1,340 NI
		Width over base edge 1576mm (62"), 0.43 m3 (0.56 yd3) Heaped Capacity		
		INCLUDES: 1 piece Bolt-on cutting edge		
W	285-6100	BUCKET-UT, 68", BOCE	569	\$1,475 NI
		Width over base edge 1730mm (68"), 0.48 m3 (0.62 yd3) Heaped Capacity		
		INCLUDES: 1 piece Bolt-on cutting edge		
W	285-6101	BUCKET-UT, 74", BOCE	607	\$1,611 NI
		Width over base edge 1883mm (74"), 0.52 m3 (0.67 yd3) Heaped Capacity		
		INCLUDES: 1 piece Bolt-on cutting edge		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	------------------------	--------------------	-------------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)***BUCKETS - TOOTH BARS***

Please order direct from parts/Antares (no bridge orders)

GP/MP bucket width	Toothbar part number		Qty	Uni	teeth
	Series I	Series II			
1576mm (62")		159-0330	7		
1760mm (68")		159-0340	8		
1883mm (74")	136-8736	159-0350	8		
2036mm (80")	217-4878	195-9160	8		
2188mm (86")	275-5427	264-2084	8		

Required Mounting Hardware for Series I / II Toothbars:

2 x 2J-3507 Nut
 2 x 3B-4516 Lockwasher
 2 x 5P-8250 Washer
 2 x 8S-9093 Bolt

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

COLD PLANERS

CAT Cold Planers are designed for small to medium size paving jobs in residential and commercial applications. Cold planers are used to economically restore asphalt and concrete paved surfaces to a specified grade or level. They are ideal for milling bumps or imperfections in expanded pavements, removing cracked or deteriorated pavement, removing traffic lane stripes and working on jobs where weight restrictions limit the use of dedicated planers. Please see dealer.cat.com for the latest cold planer mktg bulletins

Compatibilty for B Series machines and up:

		B & B2 & B3				C & C2			D & D2 & D3						
		232	247	226		262	287		226	239					
		236	252	242	257	246	277	289	236	257	246	277	287		297
		216	262	268	259	256	279	299	239	259	262	279	289	272	299
PC104	SF	C	C	C	C	C	C	C	C	C	C	C	C	C	C
PC105	SF	C	C	C	C	C	C	C	C	C	C	C	C	C	C
PC205B	SF					C	C	C				C	C	C	C
PC205B	HF	C	C	C	C				C	C					
PC305	HF/XPS	C	C	C	C	C	C	C	C	C	C	C	C	C	C
PC306	HF/XPS	C	C	C	C	C	C	C	C	C	C	C	C	C	C
	+water tank							C			C*	C	C	C	C
PC306XD	XPS							C				C	C	C*	CR
PC310	XPS					C	C				C*	C	C	C	C
PC310XD	XPS						C						C*R		C*R
XHP/XE machines only:															
PC406														C	C
	+water tank													C	C
PC408														C	C
PC412														C	C

C = Compatible/ *= Lift restricted/ R = Check max rated capacity mach.

Planers requiring HF/XPS can only be used on machines with HF/XPS or XHP/XE version. Using the harness plug sets the machines in the correct hydraulics setting. Not using the harness plug, the machine will always be in standard flow.
 PC205B: Only allowed for either SF or HF setting as per table above.
 SF always including case drain. HF, use harness plug.

If no reference numbers appear below there are currently no items available in your region.

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

COLD PLANERS (Cont.)

W	529-5760	COLD PLANER, PC104 1,504 350mm (14") drum width - 36 all purpose conical bits 1720mm (68") overall width, Manual tilt and depth Hydraulic Side Shift (manual selection on diverter valve on planer) Max Pro Pressure Gauge (for identifying optimal performance) Drum center and drum front indication gauges on both sides Optimal Flow / Pressure : 80 l/min (21 gpm) / 230 bar (3330 psi) INCLUDES: gear direct drive motor, 150mm (6") max. depth of cut, hydraulic lines with quick disconnects, mounting bracket and hardware. REQUIRES: Standard Flow Hydraulics		\$13,639 NI
W	529-5770	COLD PLANER, PC105 1,629 450mm (18") drum width - 42 all purpose conical bits 1860mm (73") overall width, Self-Levelling, replaceable side skids Max Pro Pressure Gauge (for identifying optimal performance) Drum center and drum front indication gauges on both sides Manually adjusted independent left/right depth control Optimal Flow / Pressure : 115 l/min (31gpm) / 230 bar (3330 psi) INCLUDES: piston direct drive motor, 150mm (6") max. depth of cut, hydraulic lines with quick disconnects, mounting bracket and hardware. REQUIRES: High Flow Hydraulics or Standard Flow with case drain connection and min flow of 80 l/min (21 gpm). For XPS machines run in Standard Flow with case drain. Do not use plug for XPS machines REQUIRES: 377-1579 Conversion Kit for B/B2/B3 SF/C/C2 Series		\$17,111 NI
W	529-5780	COLD PLANER, PC305 1,870 450mm (18") drum width - 42 all purpose conical bits 1860mm (73") overall width, Self-Levelling, replaceable side skids Max Pro Pressure Gauge (for identifying optimal performance) Drum center and drum front indication gauges on both sides Electro-Hydraulic: Independent left/right depth control, Sideshift, Tilt, Float-Tilt Switch to switch between float or tilt control INCLUDES: 1 piston direct drive motor, 170mm (6.7") max depth of cut, hydraulic lines with 1/2" quick disconnects, case drain line, 14-pin electrical harness, mounting brackets, and hardware Optimal Flow / Pressure: 125 l/min (33 gpm) / 280 bar (4000 psi) RECOMMENDED: Use with AMICS or advanced display REQUIRES: High Flow XPS Hydraulics REQUIRES: 371-3725 Conversion Kit for B/B2/C/C2 Series machines; not required for B3 or D Series machines		\$20,993 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

COLD PLANERS (Cont.)

W	529-5790	<p>COLD PLANER, PC306 1,530</p> <p>600mm (24") drum width, 54 all-purpose conical bits 1860mm (73") overall width, Self-Levelling, replaceable side skids Max Pro Pressure Gauge (for identifying optimal performance) Drum center and drum front indication gauges on both sides Electro-Hydraulic: Independent left/right depth control, Side shift, Tilt, Float-Tilt Switch to switch between float or tilt control INCLUDES: 1 piston direct drive motor, 170mm (6.7") max depth of cut, hydraulic lines with 1/2" quick disconnects, case drain line, 14-pin electrical harness, mounting brackets, and hardware Optimal Flow / Pressure: 125 l/min (33 gpm) / 280 bar (4000 psi) RECOMMENDED: Use with AMICS or advanced display REQUIRES: High Flow XPS Hydraulics REQUIRES: 371-3725 Conversion Kit for B/B2/C/C2 Series machines; not required for B3 or D Series machines</p>		\$22,521 NI
W	529-5791	<p>COLD PLANER, PC306, 42GAL TANK 2,108</p> <p>Includes integrated 160 ltr (42 Gal) water tank + water sprinklers. 600mm (24") drum width - 54 all purpose conical bits 1860mm (73") overall width, Self-Levelling, replaceable side skids Max Pro Pressure Gauge (for identifying optimal performance) Drum center and drum front indication gauges on both sides Electro-Hydraulic: Independent left/right depth control, Sideshift, Tilt, Float-Tilt Switch to switch between float or tilt control INCLUDES: 1 piston direct drive motor, 170mm (6.7") max depth of cut, hydraulic lines with 1/2" quick disconnects, case drain line, 14-pin electrical harness, mounting brackets, and hardware Optimal Flow / Pressure: 125 l/min (33 gpm) / 280 bar (4000 psi) RECOMMENDED: Use with AMICS or advanced display REQUIRES: High Flow XPS Hydraulics REQUIRES: 371-3725 Conversion Kit for B/B2/C/C2 Series machines; not required for B3 or D Series machines</p>		\$24,153 NI
W	529-5840	<p>COLD PLANER, PC306 XD 3,109</p> <p>600mm (24") drum width - 48 all purpose conical bits 1858mm (73") overall width, Self-Levelling, replaceable side skids Max Pro Pressure Gauge (for identifying optimal performance) Drum center and drum front indication gauges on both sides Electro-Hydraulic: Independent left/right depth control, Sideshift, Tilt, Float-Tilt Switch to switch between float or tilt control INCLUDES: 1 piston direct drive motor, 250mm (10") max depth of cut, hydraulic lines with 1/2" quick disconnects, case drain line, 14-pin electrical harness, mounting brackets, and hardware RECOMMENDED: Use with AMICS or advanced display REQUIRES: High Flow XPS Hydraulics REQUIRES: 371-3725 Conversion Kit for B/B2/C/C2 Series machines; not required for B3 or D Series machines NOTE: Some machines require limited installed options to avoid exceeding the maximum total machine rated capacity; Refer to the compatibility table.</p>		\$30,208 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

COLD PLANERS (Cont.)

W	529-5820	COLD PLANER, PC310 2,293 1000mm (39") drum width, 78 all-purpose conical bits 1860mm (73") overall width, Self-Levelling, replaceable side skids Max Pro Pressure Gauge (for identifying optimal performance) Drum center and drum front indication gauges on both sides Electro-Hydraulic: Independent left/right depth control, Side shift, Tilt, Float-Tilt Switch to switch between float or tilt control INCLUDES: 1 piston direct drive motor, 130mm (5.1") max depth of cut, hydraulic lines with 1/2" quick disconnects, case drain line, 14-pin electrical harness, mounting brackets, and hardware Optimal Flow / Pressure: 125 l/min (33 gpm) / 280 bar (4000 psi) RECOMMENDED: Use with AMICS or advanced display REQUIRES: High Flow XPS Hydraulics REQUIRES: 371-3725 Conversion Kit for B/B2/C/C2 Series machines; not required for B3 or D Series machines		\$31,389 NI
W	529-5850	COLD PLANER, PC310 XD 3,838 1000mm (39") drum width, 66 all-purpose conical bits 1860mm (73") overall width, Self-Levelling, replaceable side skids Max Pro Pressure Gauge (for identifying optimal performance) Drum center and drum front indication gauges on both sides Electro-Hydraulic: Independent left/right depth control, Side shift, Tilt, Float-Tilt Switch to switch between float or tilt control INCLUDES: 1 piston direct drive motor, 220mm (9") max depth of cut, hydraulic lines with 1/2" quick disconnects, case drain line, 14-pin electrical harness, mounting brackets, and hardware Optimal Flow / Pressure: 125 l/min (33 gpm) / 280 bar (4000 psi) RECOMMENDED: Use with AMICS or advanced display REQUIRES: High Flow XPS Hydraulics REQUIRES: 371-3725 Conversion Kit for B/B2/C/C2 Series machines; not required for B3 or D Series machines NOTE: Some machines require limited installed options to avoid exceeding the maximum total machine rated capacity; Refer to th compatibility table.		\$40,042 NI
W	529-5800	COLD PLANER, PC406 1,598 600mm (24") drum width - 54 all purpose conical bits 1860mm (73") overall width, Self-Levelling, replaceable side skids Max Pro Pressure Gauge (for identifying optimal performance) Drum center and drum front indication gauges on both sides Electro-Hydraulic: Independent left/right depth control, Sideshift, Tilt, Float-Tilt Switch to switch between float or tilt control INCLUDES: 1 piston direct drive motor, 170mm (6.7") max depth of cut, hydraulic lines with 1/2" and 3/4" quick disconnects, case drain line, 14 pin electrical harness, mounting brackets and hardware Optimal Flow / Pressure : 150 l/min (40 gpm) / 280 bar (4000 psi) REQUIRES: XE or XHP Hydraulics		\$23,674 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

COLD PLANERS (Cont.)

W	529-5801	COLD PLANER, PC406, 42GAL TANK 2,176 Includes integrated 160 ltr (42 Gal) water tank + water sprinklers. 600mm (24") drum width - 54 all purpose conical bits 1860mm (73") overall width, Self-Levelling, replaceable side skids Max Pro Pressure Gauge (for identifying optimal performance) Drum center and drum front indication gauges on both sides Electro-Hydraulic: Independent left/right depth control, Sideshift, Tilt, Float-Tilt Switch to switch between float or tilt control INCLUDES: 1 piston direct drive motor, 170mm (6.7") max depth of cut, hydraulic lines with 1/2" and 3/4" quick disconnects, case drain line, 14 pin electrical harness, mounting brackets and hardware Optimal Flow / Pressure : 150 l/min (40 gpm) / 280 bar (4000 psi) REQUIRES: XE or XHP Hydraulics		\$25,306 NI
W	529-5810	COLD PLANER, PC408 2,304 750mm (30") drum width - 60 all purpose duty conical bits 1860mm (73") overall width, Self-Levelling, replaceable side skids Max Pro Pressure Gauge (for identifying optimal performance) Drum center and drum front indication gauges on both sides Electro-Hydraulic: Independent left/right depth control, Sideshift, Tilt, Float-Tilt Switch to switch between float or tilt control INCLUDES: 1 piston direct drive motor, 170mm (6.7") max depth of cut, hydraulic lines with 1/2" and 3/4" quick disconnects, case drain line, 14 pin electrical harness, mounting brackets and hardware Optimal FLOW / Pressure : 150 l/min (40 gpm) / 280 bar (4000 psi) REQUIRES: XE or XHP Hydraulics		\$26,069 NI
W	529-5830	COLD PLANER, PC412 2,557 1200mm (47") drum width - 90 all purpose conical bits 1860mm (73") overall width, Self-Levelling, replaceable side skids Max Pro Pressure Gauge (for identifying optimal performance) Drum center and drum front indication gauges on both sides Electro-Hydraulic: Independent left/right depth control, Sideshift, Tilt, Float-Tilt Switch to switch between float or tilt control INCLUDES: 2 piston direct drive motors, 130mm (5") max. depth of cut, hydraulic lines with 3/4" quick disconnects, case drain line and electrical harness, mounting brackets, and hardware RECOMMENDED: Use with AMICS or advanced display REQUIRES: XE or XHP Hydraulics NOTE: Some machines require limited installed options to avoid exceeding the maximum total machine rated capacity; Refer to the compatibility table.		\$33,521 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

COLD PLANERS - WATER TANK KIT

If you require dust suppression, you can upgrade your cold planer with an integrated water tank kit.

Compatibility for Water Tank kit on which Cold Planer and machines:
 D & D2 & D3

	226	236	242	257	277	287	297			
	232	239	249	259	246	262	279	289	272	299
PC104	C	C	C	C	C	C	C	C	C	C
PC105	C	C	C	C	C	C	C	C	C	C
PC305				C	C	C	C	C	C	C
PC306XD						NC	NC	NC	NC	
PC310				C*	C	C	C	C	C	
PC310XD							NC		NC	
PC408								C	C	
PC412								C	C	

C = Compatible/ *= Lift restricted/ NC = No water tank kit allowed

W 591-0703 KIT, WATER TANK, PC, 42 GAL 522 \$3,889 NI
 Field installed kit for an integrated water tank solution for cold planers. The kit consists of a frame with the water tank inside with an SSL coupler interface on the outside. This replaces the existing SSL coupler interface on the cold planer.
 INCLUDES: Frame, water tank, water pump, water filter, tank harness, mounting ware and conversion harness for PC104 and PC105.
 FOR USE WITH: All planer models except XD but limited matching machines see compatibility table above
 REQUIRES: Water Spray kit, see section COLD PLANER - WATER SPRAY KITS
 REQUIRES: Work Tool harness, (no extra Joystick requirements)
 NOTE: Installation time: 4 hours, instructions see M0122969.

COLD PLANERS - WATER SPRAY KITS

W 206-2567 KIT, WATER SPRAY, PC3/PC4 10 \$500 NI
 Work tool water sprinkling kit complete with sprinkler heads (4), hoses, mounting hardware and quick disconnects for effective dust control.
 REQUIRES: Control, Work Tool, Electrical (order with machine)
 REQUIRES: Water Tank, Machine (reference machine attachments section of this price list to order)
 FOR USE WITH: PC3, PC4

W 231-2590 KIT, WATER SPRAY, PCX03/4/5 22 \$203 NI
 Work tool water sprinkling kit complete with sprinkler heads (2), hoses, mounting hardware and quick disconnects for dust control.
 REQUIRES: Control, Work Tool, Electrical (order with machine)
 REQUIRES: Water Tank, Machine (reference machine attachments section of this price list to order)
 FOR USE WITH: PC104B, PC104, PC105, PC203, PC204, PC205, PC205B, PC305B, PC305

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

COLD PLANERS - WATER SPRAY KITS (Cont.)

W	231-2591	KIT, WATER SPRAY, PCX06/8 24 Work tool water sprinkling kit complete with sprinkler heads (3), hoses, mounting hardware and quick disconnects for dust control. REQUIRES: Control, Work Tool, Electrical (order with machine) REQUIRES: Water Tank, Machine (reference machine attachments section of this price list to order) FOR USE WITH: PC206, PC306B, PC306, PC406, PC408B, PC408		\$250 NI
W	231-2592	KIT, WATER SPRAY, PC210/310B 26 Work tool water sprinkling kit complete with sprinkler heads (4), hoses, mounting hardware and quick disconnects for dust control. REQUIRES: Control, Work Tool, Electrical (order with machine) REQUIRES: Water Tank, Machine (reference machine attachments section of this price list to order) FOR USE WITH: PC210, PC310B		\$300 NI
W	381-8341	KIT, WATER SPRAY, PC412B 27 Work tool water sprinkling kit complete with sprinkler heads (5), hoses, mounting hardware and quick disconnects for dust control. REQUIRES: Control, Work Tool, Electrical (order with machine) REQUIRES: Water Tank, Machine (reference machine attachments section of this price list to order) FOR USE WITH: PC412B		\$347 NI
W	591-0710	KIT, WATER SPRAY, PC310 4 Work tool water sprinkling kit complete with sprinkler heads (4), hoses, mounting hardware and quick disconnects for dust control. REQUIRES: Control, Work Tool, Electrical (order with machine) REQUIRES: Water Tank, Machine (reference machine attachments section of this price list to order) FOR USE WITH: PC310		\$292 NI
W	591-0712	KIT, WATER SPRAY, PC412 6 Work tool water sprinkling kit complete with sprinkler heads (5), hoses, mounting hardware and quick disconnects for dust control. REQUIRES: Control, Work Tool, Electrical (order with machine) REQUIRES: Water Tank, Machine (reference machine attachments section of this price list to order) FOR USE WITH: PC412		\$340 NI

COLD PLANERS - DRUMS

W	231-2572	DRUM, ASPHALT, 3" 123 Width: 75mm(3"), Cut depth min-max: 50mm(2")- 200mm(8"), 24 GP bits FOR USE WITH: PC104, PC105, PC104B, PC203, PC204, PC205, PC205B		\$1,528 NI
W	231-2573	DRUM, ASPHALT, 6" 132 Width: 150mm(6"), Cut depth min-max: 50mm(2")- 200mm(8"), 24 GP bits FOR USE WITH: PC104, PC105, PC104B, PC203, PC204, PC205, PC205B		\$1,854 NI
W	231-2574	DRUM, ASPHALT, 8" 163 Width: 200mm(8"), Cut depth min-max: 50mm(2")- 200mm(8"), 36 GP bits FOR USE WITH: PC104, PC105, PC104B, PC203, PC204, PC205, PC205B		\$1,993 NI
W	231-2575	DRUM, ASPHALT, 12" 223 Width: 300mm(12"), Cut depth min-max: 50mm(2")- 200mm(8"), 42 GP bits FOR USE WITH: PC104, PC105, PC104B, PC203, PC204, PC205, PC205B		\$2,083 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)				
<i>COLD PLANERS - DRUMS (Cont.)</i>				
W	224-7360	DRUM, ASPHALT, 18" 304 Width: 450mm(18"), Cut depth min-max: 0mm(0")- 150mm(6"), 48 GP bits FOR USE WITH: PC105, PC204, PC205, PC205B		\$2,104 NI
W	231-2580	DRUM, ASPHALT, 3" 159 Width: 80mm(3.1"), Cut depth min-max: 50mm(2")-200mm(8"), 24 GP bits FOR USE WITH: PC206, PC305, PC306, PC305B, PC306B		\$1,667 NI
W	231-2581	DRUM, ASPHALT, 6" 159 Width: 150mm(6"), Cut depth min-max: 50mm(2")-200mm(8"), 28 GP bits FOR USE WITH: PC206, PC305, PC306, PC305B, PC306B		\$1,993 NI
W	606-2524	DRUM, ASPHALT, 12" 263 Width: 300mm(12"), Cut.depth min-max: 50mm(2")-215mm (8.5"), 42 GP bit FOR USE WITH: PC305, PC305B		\$2,896 NI
W	231-2583	DRUM, ASPHALT, 12" 278 Width: 300mm(12"), Cut depth min-max: 50mm(2")-200mm(8"), 42 GP bits FOR USE WITH: PC206, PC306, PC306B		\$2,896 NI
W	231-2586	DRUM, ASPHALT, 18" 362 Width: 450mm(18"), Cut depth min-max: 50mm(2")-200mm(8"), 48 GP bits FOR USE WITH: PC206, PC306, PC306B		\$2,431 NI
W	224-7384	DRUM, ASPHALT, 24" 368 Width: 600mm(24"), Cut depth min-max: 0mm(0")-170mm(7"), 60 GP bits FOR USE WITH: PC206, PC306, PC306B		\$2,549 NI
W	467-8067	KIT, DRUM, FINE TOOTH, 18" 331 Width: 450mm(18"), Cut.depth min-max: 0mm(0")- 30mm(1 1/6"), 208 fine FOR USE WITH: PC205, PC205B, PC105		\$9,243 NI
W	467-8068	KIT, DRUM, FINE TOOTH, 24" 478 Width: 600mm(24"), Cut.depth min-max: 0mm(0")- 30mm(1 1/6"), 308 fine FOR USE WITH: PC206, PC306B, PC306		\$11,750 NI
W	467-8069	KIT, DRUM, FINE TOOTH, 40" 657 Width: 1000mm(40"), Cut.depth min-max: 0mm(0")- 30mm(1 1/6"),508 fine FOR USE WITH: PC210, PC310B, PC310		\$18,924 NI

Available through Parts - NO BRIDGE ORDERS

Replacement conical carbide bits and holder for all cold planers:

- 561-8134 All Purpose bit (asphalt & concrete)
- 561-8132 Concrete bit
- 560-2306 Heavy Duty Asphalt bit
- 226-9308 Block Holder for bit
- 543-5470 Punch (Bit Remover)
- 539-6298 Puller Fork (Bit Remover)

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

COMPACTORS, VIBRATORY

**Nomenclature change: CV117 is replacement for CV16B, NO techn. changes
 CV117 stands for standard flow + working width ca. 1.7m
 Nomenclature change: CV119 is replacement for CV18B, NO techn. changes
 CV119 stands for standard flow + working width ca. 1.9m**

																	287
																	289
	226	232	239				248			257	262			277	297		
	216	242	228	236	249	246	247	268	252	256	259	272	267	279	299		
CV117	C*	C*	C*	C*	C*	C	C*	C	C	C	C*	C	C	C	C		
CV119						C		C	C	C		C	C	C	C		

C = Compatible/ *= lift restricted
 Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	231-8600	VIBRATORY COMPACTOR, CV117 2,174	\$12,021 NI
		CV117 (old CV16B) with working width of approx. 1.4m Width Overall - drum: 1855mm (73") - 1676mm (66") 610mm (24") Diameter SMOOTH drum design Drum Frequency - 2946 vpm @ max flow Dynamic (centrifugal) Force - 11,903 lb (5399 kg) Spring loaded dual-direction non-metallic scraper bar Hydraulic Flow range: 42-86 l/min (11-23 gpm) Hydraulic Pressure range: 145-235 bar (2,100-3,400 psi) INCLUDES: DIRECT drive unit, hydraulic lines with quick disconnects, mounting bracket and hardware REQUIRES: Standard Flow Hydraulics	
W	231-8601	VIBRATORY COMPACTOR, CV119 2,260	\$12,535 NI
		CV119 (old CV18B) with working width of approx. 1.9m Width overall - drum:: 2032mm (80") 1854mm (73") 610mm (24") Diameter SMOOTH drum design Drum Frequency - 2946 vpm @ max flow Dynamic (centrifugal) Force - 11,903 lb (5399 kg) Spring loaded dual-direction non-metallic scraper bar Hydraulic Flow range: 42-86 l/min (11-23 gpm) Hydraulic Pressure range: 145-235 bar (2,100-3,400 psi) INCLUDES: DIRECT drive unit, hydraulic lines with quick disconnects, mounting bracket and hardware REQUIRES: Standard Flow Hydraulics	

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	------------------------	--------------------	-------------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)**CONVERSION KITS**

Conversion kits are available to convert old work tools to function on the B3 High Flow and D Series machines (not for C2 machines).

The secondary auxiliary circuits have been moved from the machine to the work tool. Pre B3 and D series machines have a 8 pins harness and 5 l. The following kits provide the Bill of Material for the change.

Please consult the list below for the required work tool conversion kit. The work tool interface for B3 High Flow and D Series machines consists of two 1/2" Quick Disconnects (QD), case drain line and 14 pin electrical connector. These hydraulic lines provide flow for standard flow, high flow (HF) and High Flow XPS (HF XPS), based on the machine configuration.

The SSL/CTL D XHP work tool interface consists of two 3/4" Quick disconnects, case drain line and 14 pin electrical connector. These hydraulic lines provide standard flow, high flow XPS and XHP flow, based on the machine configuration. Please review the marketing bulletin explaining the conversion process. It is located at dealer.cat.com under the SSL/CTL machines section.

Compatibility Guide arranged by model

MODEL SERIES	B3 & D + SF/HF/XPS D + XHP prefix JST/ETL	D + XHP only NLC/SHY
A14B, A19B	Not Required	382-6184 #
A26B	382-6152#	382-6190#
BA18 (Manual Angle)	Not Required	382-6186#
BA18 (Hydraulic Angle)	375-6445	382-6187#
BH27/BH30/BH30W	Not Required	382-6184#
Angle Blade	Not Required	382-6181#
Dozer Blades	375-6445	382-6185#
BP15B, BP18B	Not Required	382-6184#
BR160, BR166, BR172	Not Required	382-6186#
BR272, BR378	382-6193#	382-6190#
BU115, BU118	Not Required	382-6184#
CV16B, CV18B	Not Required	382-6184#
Industrial Grapple Forks	Not Required	382-6181#
Industrial Grapple Rakes	Not Required	382-6181#
Hammers	Not Required	382-6183#
HM312, HM315	382-6180	382-6192#
HM315B	Not Required	382-6153#
Industrial Grapple Buckets	Not Required	382-6181#
LR15B, LR18B	Not Required	382-6184#
LT13B, LT18B	Not Required	382-6184#
MP Buckets	Not Required	382-6181#
PR172, PR184, PR190 (Hydraulic Angle)	375-6445	382-6185#
S305	375-6445	382-6188#
SG16B	375-6445	382-6185#
SG18B	382-6170	382-6192#
SR318, SR321	382-6151#	382-6189#

= kit is not stocked anymore. Please order consist parts.

Continued on next page

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

CONVERSION KITS (Cont.)

MODEL SERIES	B3 & D + SF/HF/XPS D + XHP prefix JST/ETL	D + XHP only NLC/SHY
PC104B, PC203, PC204	Not Required	382-6184#
PC205, PC206, PC210	379-0420	382-6192#
PC205, PC206, PC210	379-0420	382-6192#
PC205B, PC306B, PC310B	Not Required	382-6186#
SW45, SW60	379-0420	382-6192#
SW345B, SW360B	Not Required	382-6186#
SR117, SR118, SR121		
S/N WSG00274/SNB00246/ SNR00241 and below	375-6445	382-6189#
S/N WSG00275/SNB00247/ SNR00242 and above	375-6445	382-6185#
T6B, T9B	Not Required	382-6184#
T15B	382-6160	382-6192#
Utility Grapple Forks	Not Required	382-6181#
Utility Grapple Buckets	Not Required	382-6181#

= kit is not stocked anymore. Please order consist parts.

W	379-0420	KIT, W/T CONV, PLANER & SAW	85	\$1,558 NI
		INCLUDES: valve, couplings, harness and related hardware Installation time: 4.0 hours, instructions see REHS5689		
W	382-6180	KIT KX - WKTL CVRSN TO 3-LINES	37	\$1,914 NI
		Conversion kit for Mulcher HM312 & HM315 Installation time: 3.0 hours, instructions see REHS7083		
W	382-6170	KIT KY - WKTL CVRSN TO 3-LINES	53	\$1,894 NI
		Conversion kit for Stump Grinder SG18B Installation time: 4.0 hours, instructions see REHS7116		
W	382-6160	KIT KZ - WKTL CVRSN TO 3-LINES	51	\$2,125 NI
		Conversion kit for Trencher T15B Installation time: 3.0 hours, instructions see REHS4762		
W	375-6445	HARNES, CVRSN 8WT TO 14SSL	1	\$121 NI
		Conversion harness from 14 pin CAT SSL to 8 pin CAT Work Tool Note: 377-5466 14 pin HF XPS electrical jumper plug available through parts only		
W	377-1579	HARNES, CVRSN 14WT TO 8SSL	1	\$151 NI
		Conversion harness from 8 pin CAT SSL to 14 pin CAT Work Tool		

CONVERSION KITS - NEW WORK TOOLS

Conversion of new work tools with 3 lines and 14 pin harness to 5 lines and/or 8 pin harness for use with old machines

W	371-3725	KIT KS - WKTL CVRSN TO 5-LINES	3	\$356 NI
		Installation time: 0.5 hours, instructions see REHS7117 Conversion kit for SW345B, SW360B, SW380B, SW345, SW360, SW380, PC305B, PC306B, PC306B XD, PC310B, PC310B XD, PC305, PC306, PC310, PC306 XD, PC310 XD, HM315B, HM315C, T15B, SG18B		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

CONVERSION KITS - NON CAT ATTACHMENTS/ WORK TOOLS

With these conversions harnesses you can convert a non-CAT attachment to work on a D series CAT machine.

W	509-2817	HARNESS, CVRS 1-5FCT 14PIN SSL 1 FOR USE WITH: Non Caterpillar Attachments with a 14 pins Electrical harness/connector requiring 1 to 5 aux electrical outputs to the host CAT machine with a 14 pins Work Tools harness REQUIRES: 344-6145 Receptacle (14 pins male harness, not included) Installation time: 2.0 hours, instructions see M0075054		\$111 NI
W	520-3445	HARNESS, CVRS 2 PIN DELPHI 0 FOR USE WITH: Non Caterpillar Attachments with a 7 pins Electrical harness/connector or requiring 6 aux electrical outputs to the host machine with a 14 pins Work Tools harness Installation time: 2.0 hours, instructions see M0075056		\$28 NI

CONVERSION KITS - MACHINES WITH NO WORK TOOL HARNESS

In case your D series machine has no work tool harness, please check your machine configuration and table below indicates what to order:

Performance package & Controls	Joysticks	14 pins	You have to order
	Right Hand	Left Hand	Electr. Harness
	2 button+ thumb wheel	4 button	WT

226D, 232D, 239D, 249D					
H1 / H2	ON/OFF	not incl	not incl	not incl	421-0265+273-9104
H1 / H2	Prop.	not incl	incl	not incl	421-0261+273-9104
H1 / H2	Prop.WT	not incl	incl	incl	273-9104
H3	Prop.WT	incl	incl	incl	Nothing
236D, 242D, 246D, 257D, 259D, 262D, 272D2, 277D, 279D, 287D, 289D, 297D2, 299D2					
H1 / H2	ON/OFF	not incl	not incl	not incl	388-8273+273-9104
H1 / H2	Prop.	not incl	incl	not incl	388-8265+273-9104
H1 / H2	Prop.WT	not incl	incl	incl	273-9104
H3	Prop.WT	incl	incl	incl	Nothing
272D(2) XHP, 297D(2) XHP, 299D(2) XHP					
H3	Prop.WT	incl	incl	incl	Nothing

273-9104	Right Hand joystick with 2 buttons and thumb roller
388-8265	Kit, Work Tools Harness
388-8273	Kit, Work Tools Harness (incl. left hand 4 button joystick)
421-0261	Kit, Work Tools Harness
421-0265	Kit, Work Tools Harness (incl. left hand 4 button joystick)

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

CARRIAGES - FORKS/TINES

	216	232	242			262	272			
	226	236	246	248	256	257	267	277	287	297
	228	239	247	249	256	259	268	279	289	299
Carriage	C	C	C	C	C	C	C	C	C	C
Fork/Tines:										
1676mm (66")	C	C	C	C	C	C	C	C	C	C
1830mm (72")	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	351-9371	CARRIAGE, PAL C2, 46", SSL207	\$611 NI
		Standard Hook Carriage, Overall Carriage width step, 1270mm (50") REQUIRES: 2 Forks/Tines NOT included	
W	353-1693	CARRIAGE, PAL C2,46",SSL,QTY 6 1,242	\$3,486 NI
		6 pcs. of 351-9371 Carriage. Forks / Tines NOT included.	
W	195-6943	FORK, PAL C2, 36" X 4" X 1.5" 92	\$174 NI
		40 x 100 x 910mm (1.5" x 4" x 36") Pull Type Order quantity of 2 for a pair.	
W	195-6942	FORK, PAL C2, 42" X 4" X 1.5" 104	\$208 NI
		40 x 100 x 1070mm (1.5" x 4" x 42") Pull Type Order quantity of 2 for a pair.	
W	243-0002	FORK, PAL C2, 42", QTY 12 1,248	\$2,292 NI
		12 pcs. of 1956942 Forks	
W	195-8545	FORK, PAL C2, 48" X 4" X 1.5" 114	\$222 NI
		40 x 100 x 1220mm (1.5" x 4" x 48") Pull Type Order quantity of 2 for a pair.	
W	243-0003	FORK, PAL C2, 48", QTY 12 1,368	\$2,444 NI
		12 pcs. of 1958545 Forks	

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

CARRIAGE - FORKS/TINES - HEAVY DUTY/WALK THROUGH

Heavy Duty/Walk Through carriage and forks to handle pallets.
 Ideal for the larger SSLs.

	226	232	242	247	252	257	262	277	287	297				
	228	236	239	246	248	249	256	259	268	267	272	279	289	299
Carriage HD	C	C	C	C	C	C	C	C	C	C	C	C	C	C
Forks:														
1067mm (42")	C	C	C	C	C	C	C	C	C	C	C	C	C	C
1219mm (48")	C	C	C	C	C	C	C	C	C	C	C	C	C	C
1524mm (60")	C	C	C	C	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	532-7810	CARRIAGE, PAL HD C2, 57", SSL	320	\$1,042 NI
		Heavy duty carriage with walk through bracket (width 450mm (17.5-) Overall width: 1440mm (57"), Height: 910mm (36") REQUIRES: 2 x 540-1431 or 2 x 540-1432 or 2 x 540-1433, NOT included		
W	556-3173	KIT, HYD. POSITIONER, SSL, HD	44	\$1,500 NI
		Conversion kit to add hydraulic adjustability of the fork tines FOR USE WITH: Heavy duty Carriage 532-7810 NOT AVIALABLE FOR THE EU AS IT DOES NOT HAVE CE.		
W	540-1431	FORK, PAL HD C2, 42"X4.8"X1.8"	130	\$333 NI
		1067X122X45MM (42"X4.8"X1.8"), Please order 2 for a full set. FOR USE WITH: Heavy duty Carriage 532-7810.		
W	540-1432	FORK, PAL HD C2, 48"X4.8"X1.8"	146	\$347 NI
		1219X122X45MM (48"X4.8"X1.8") Please order 2 for a full set. FOR USE WITH: Heavy duty Carriage 532-7810.		
W	540-1433	FORK, PAL HD C2, 60"X4.8"X1.8"	174	\$417 NI
		1524X122X45MM (60"X4.8"X1.8") Please order 2 for a full set. FOR USE WITH: Heavy duty Carriage 532-7810.		

CARRIAGES WITH ASSEMBLED TINES

W	353-1696	CARRIAGE, 46", FORKS, 42", SSL	415	\$1,104 NI
		Includes 1 pc. of 2616681 carriage and 2 pcs. of 1956942 forks		
W	353-1697	CARRIAGE, 46", FORKS, 48", SSL	435	\$1,132 NI
		Includes 1 pc. of 3519371 carriage and 2 pcs. of 1958545 forks		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS								Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-------------------------------	--	--	--	--	--	--	--	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

FORKS, UTILITY

Light duty design, for agriculture and landscaping applications, for transporting small bales, removing dry compacted livestock waste, loosening of bedding materials and soil aeration.

216	232	242				262	272			
226	236	246	248	256	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

Industrial										
1676mm (66")	C	C	C	C	C	C	C	C	C	C
1829mm (72")	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	285-6105	FORKS, UTILITY, 66"	437	\$1,046 NI
		1676mm (66") wide, 7 round fork tines included		
W	285-6110	FORKS, UTILITY, 72"	484	\$1,201 NI
		1829mm (72") wide, 9 round forks included		

INDUSTRIAL GRAPPLE FORKS

Heavy duty design to handle a wide array of bulky, irregularly shaped objects encountered in demolition, industrial, construction, recycling and other aggressive applications. Independently controlled heavy duty grapple assemblies.

216	232	242				262	272			
226	236	246	248	256	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

Industrial										
1676mm (66")	C	C	C	C	C	C	C	C	C	C
1829mm (72")	C	C	C	C	C	C	C	C	C	C

C = Compatible

Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	279-5350	FORKS, INDUSTRIAL GRAPPLE, 66"	1,106	\$6,082 NI
		1676mm (66") Wide, 9 round fork tines incl., 965mm (38") jaw opening		
		INCLUDES: 2 cylinders, 2 heavy duty grapple assemblies		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

INDUSTRIAL GRAPPLE FORKS (Cont.)

W	279-5360	FORKS, INDUSTRIAL GRAPPLE, 72" 1,208 1829mm (72") Wide, 11 round fork tines incl., 965mm (38") jaw opening INCLUDES: 2 cylinders, 2 heavy duty grapple assemblies		\$7,258 NI
----------	-----------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	-------------------

UTILITY GRAPPLE FORKS

To handle hard to handle light materials on farms, nurseries and in landscaping. Not suited to handle large bales.

216	232	242				262	272			
226	236	246	248	256	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

Utility										
1676mm (66")	C	C	C	C	C	C	C	C	C	C
1829mm (72")	C	C	C	C	C	C	C	C	C	C

C = Compatible
 Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	285-6114	FORKS, UTILITY GRAPPLE, 66" 671 1676mm (66") Wide, 7 round fork tines incl., 876mm (34.5") jaw opening INCLUDES: 1 cylinder, 1 grapple assembly,		\$2,551 NI
W	285-6115	FORKS, UTILITY GRAPPLE, 72" 719 1829mm (72") Wide, 9 round fork tines incl., 876mm (34.5") jaw opening INCLUDES: 1 cylinder, 1 grapple assembly,		\$2,706 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

INDUSTRIAL GRAPPLE BUCKETS

Heavy duty design to handle a wide array of bulky, irregularly shaped objects encountered in demolition, industrial, construction, recycling and other aggressive applications. Independently controlled heavy duty grapple assemblies.

	216	232	242			262	272			
	226	236	246	248	256	257	267	277	287	297
	228	239	247	249	256	259	268	279	289	299
1576mm (62")	C	C	C	C	C	C	C	C	C	C
1730mm (68")	C	C	C	C	C	C	C	C	C	C
1883mm (74")	C	C	C	C	C	C	C	C	C	C
2036mm (80")	C	C	C	C	C	C	C	C	C	C

C = Compatible

Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	157-7226	BUCKET-IND. GR, 62", BOCE1,045 Width over base edge 1576mm (62"), 1016mm (40") jaw opening INCLUDES: 1 piece Bolt on cutting edge, 2 heavy duty grapple assemblies	\$4,700 NI
W	157-7227	BUCKET-IND. GR, 68", BOCE1,074 Width over base edge 1730mm (68"), 1016mm (40") jaw opening INCLUDES: 1 piece Bolt on cutting edge, 2 heavy duty grapple assemblies	\$4,932 NI
W	158-6095	BUCKET-IND. GR, 74", BOCE1,104 Width over base edge 1883mm (74"), 1016mm (40") jaw opening INCLUDES: 1 piece Bolt on cutting edge, 2 heavy duty grapple assemblies	\$5,522 NI
W	217-6230	BUCKET-IND. GR, 80", BOCE1,142 Width over base edge 2036mm (80"), 1016mm (40") jaw opening INCLUDES: 1 piece Bolt on cutting edge, 2 heavy duty grapple assemblies	\$6,074 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS								Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-------------------------------	--	--	--	--	--	--	--	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

INDUSTRIAL GRAPPLE RAKES

Heavy duty design with verticle tines to handle a wide array of irregularly shaped objects encountered in land clearing, industrial, construction, recycling and other aggressive applications. Independently controlled heavy duty grapple assemblies.

216	232	242				262	272			
226	236	246	248	256	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

1830mm (72")	C	C	C	C	C	C	C	C	C	C
2134mm (84")	C	C	C	C	C	C	C	C	C	C

C = Compatible
 Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	286-9300	RAKE, IND. GRAPPLE, 72"	1,070	\$4,107 NI
		1830mm (72") Wide, 9 tines included		
		INCLUDES: 2 cylinders, 2 heavy duty grapple assemblies		
W	286-9301	RAKE, IND. GRAPPLE, 84"	1,115	\$4,599 NI
		2134mm (84") Wide, 11 tines included		
		INCLUDES: 2 cylinders, 2 heavy duty grapple assemblies		

UTILITY GRAPPLE BUCKETS

To handle hard to handle light materials on farms, nurseries and in landscaping.

216	232	242				262	272			
226	236	246	248	256	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

Utility										
1730mm (68")	C	C	C	C	C	C	C	C	C	C
1883mm (74")	C	C	C	C	C	C	C	C	C	C

C = Compatible
 Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	285-6111	BUCKET-UTIL. GR, 68", BOCE	803	\$3,176 NI
		Width over base edge 1730mm (68"), 902mm (35.5") jaw opening		
		INCLUDES: 1 piece Bolt-on cutting edge, 1 cylinder 1 grapple assembly		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

UTILITY GRAPPLE BUCKETS (Cont.)

W	285-6112	BUCKET-UTIL. GR, 74", BOCE	841	\$3,313 NI
		Width over base edge 1883mm (74"), 902mm (35.5") jaw opening INCLUDES: 1 piece Bolt-on cutting edge, 1 cylinder 1 grapple assembly		

UTILITY GRAPPLE GROUP

Not installed; fits onto Utility Forks or Utility Bucket.

W	285-6116	UTILITY GRAPPLE	340	\$1,840 NI
		One Cylinder, one grapple assembly INCLUDES: hydraulic lines with quick disconnects and hardware		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

HAMMERS - B4/B6/B8 and B4S/B6S/B8S Silenced Flat Top

WARNING:

Demolition tools can create a hazard from flying objects. Caterpillar recommends installing front guards on the cabs of the excavators. Failure to do so can lead to injury or death.

Hammer Compatibilty:

	216	232	242						272		
	226	236	247	257	246	252		262	277	287	297
	228	239	249	259	248	267	256	268	279	289	299
B4	++	++	++	++	+-	+-	+-	+-	+-	+-	+-
B6	++	++	++	++	++	++	++	++	++	++	++
B8	+-	+-	+-	+-	++	++	++	++	++	++	++

++= Optimal +- = Acceptable --- = Not Allowed

If no hammer references appear below there are no B4/B6/B8 Hammers currently available in your region.

W	532-9104	HAMMER, B4 351	\$5,750 NI
		NON Silenced hydraulic hammer, flat top with drill pattern SM and MD BPM (blows/minute): 600-1,100 , Energy Class 370 Joule (273 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 25-50 l/min (6.6-13.2 gal/min) Max Operation Pressure 11,749 kPa (1,704 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket SM or MD, connecting lines	
W	532-9204	HAMMER, B4S 357	\$6,389 NI
		Silenced hydraulic hammer, flat top with drill pattern SM and MD BPM (blows/minute): 600-1,100 , Energy Class 370 Joule (273 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 25-50 l/min (6.6-13.2 gal/min) Max Operation Pressure 11,749 kPa (1,704 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket SM or MD, connecting lines	
W	532-9206	HAMMER, B6S 611	\$9,306 NI
		Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 500-900 , Energy Class 681 Joule (502 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 40-70 l/min (10.6-18.5 gal/min) Max Operation Pressure 13,707 kPa (1,988 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines	

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

HAMMERS - B4/B6/B8 and B4S/B6S/B8S Silenced Flat Top (Cont.)

W	532-9106	HAMMER, B6 571 Non-Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 500-900 , Energy Class 681 Joule (502 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 40-70 l/min (10.6-18.5 gal/min) Max Operation Pressure 13,707 kPa (1,988 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines		\$8,375 NI
W	532-9208	HAMMER, B8S 711 Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 400-800 , Energy Class 1,150 Joule (848 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 50-90 l/min (13.2-23.8 gal/min) Max Operation Pressure 14,686 kPa (2,130 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines		\$12,361 NI
W	532-9108	HAMMER, B8 724 Non Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 400-800 , Energy Class 1,150 Joule (848 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 50-90 l/min (13.2-23.8 gal/min) Max Operation Pressure 14,686 kPa (2,130 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines		\$11,125 NI
W	532-9240	BRACKET, LINES, SSL, MD-LG 324 Bracket with SSL interface and including lines and quick disconnects. FOR USE WITH: B Hammers with drill pattern MD or LG and SSL, CTL and SSL, CTLand MTL machines		\$1,597 NI
W	532-9250	BRACKET, SSL, MD-LG 300 Bracket with SSL interface, lines and quick disconnects NOT incl. FOR USE WITH: B and H Hammers with drill pattern MD or LG and SSL, CTL and SSL, CTLand MTL machines REQUIRES: connecting lines		\$1,181 NI
W	532-9264	LINES, B4-B6-B8 HAMMER, SSL 24 Connecting lines includes quick disconnects FOR USE WITH: B4/B6/B8 Hammers (NOT for H series hammers) CAN NOT BE USED WITH: H series hammers		\$417 NI
W	532-9063	BRACKET, MHE 3T, 40MM, SM-LG 134 FOR USE WITH: Hammers with drill pattern SM or LG and Pin-On stick mounted with 3T linkage.		\$451 NI
W	532-9088	LINES, B4-B6 HAMMER, 3T 0 FOR USE WITH: BH160		\$208 NI
W	532-9190	TOOL, MOIL, B4 19 Diam: 53mm (2.1"), Total Length: 580mm (22.8") Working length: Non silenced / silenced: 360mm (14.2") / 330mm (13")		\$201 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

HAMMERS - B4/B6/B8 and B4S/B6S/B8S Silenced Flat Top (Cont.)

W	542-1758	TOOL, CONE, B4 21 Diam: 53mm (2.1"), Total Length: 580mm (22.8") Working length: Non silenced / silenced: 360mm (14.2") / 330mm (13")		\$201 NI
W	542-1759	TOOL, BLUNT, B4 20 Diam: 53mm (2.1"), Total Length: 580mm (22.8") Working length: Non silenced / silenced: 360mm (14.2") / 330mm (13")		\$201 NI
W	542-1760	TOOL, CHISEL, IN LINE, B4 20 Diam: 53mm (2.1"), Total Length: 580mm (22.8") Working length: Non silenced / silenced: 360mm (14.2") / 330mm (13")		\$201 NI
W	542-1761	TOOL, CHISEL, CROSS CUT, B4 20 Diam: 53mm (2.1"), Total Length: 580mm (22.8") Working length: Non silenced / silenced: 360mm (14.2") / 330mm (13")		\$201 NI
W	523-3193	TOOL, MOIL, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	523-3195	TOOL, CONE, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	523-3196	TOOL, BLUNT, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	523-3197	TOOL, CHISEL, CROSS CUT, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	523-3191	TOOL, CHISEL, IN LINE, B6 40 Diam: 68mm (2.7"), Total Length: 702mm (27.6") Working length: Non silenced / silenced: 427mm (16.8") / 377mm (14.8")		\$229 NI
W	532-9120	TOOL, MOIL, B8 50 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI
W	532-9118	TOOL, CONE, B8 54 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI
W	532-9117	TOOL, BLUNT, B8 54 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI
W	532-9119	TOOL, CHISEL, CROSS CUT, B8 52 Diam: 75mm (3"), Total Length: 755mm (29.7") Working length: Non silenced / silenced: 468mm (18.4") / 418mm (16.5")		\$333 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

HAMMERS - H55 Silenced FLAT TOP

WARNING:

Demolition tools can create a hazard from flying objects. Caterpillar recommends installing front guards on the cabs of the loaders. Failure to do so can lead to injury or death.

Hammer Compatibilty:

	226	232		242		247	252	257	262		277	287	297		
	216	228	236	239	246	248	249	256	259	268	267	272	279	289	299

H55	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-----	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

C = Compatible/ *= lift restricted/ #= Extra counter weight required

If no hammer references appear below there are no H55 Hammers currently available in your region.

W	561-2551	HAMMER, H55S	459	\$9,493 NI
		Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 600-1,680 , Energy Class 813 Joule (600 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 30-85 l/min (7.9-22.5 gal/min) Max Operation Pressure 16,499 kPa (2,393 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines		
W	532-9250	BRACKET, SSL, MD-LG	300	\$1,181 NI
		Bracket with SSL interface, lines and quick disconnects NOT incl. FOR USE WITH: B and H Hammers with drill pattern MD or LG and SSL, CTL and SSL, CTLand MTL machines REQUIRES: connecting lines		
W	269-7807	BRACKET, SSL, PO	225	\$1,238 NI
		FOR USE WITH: H55s flat top, H65s flat top, H55Es PIN-ON, H65Es PIN-ON REQUIRES: Bracket 532-9275		
W	532-9275	BRACKET, MHE 3-5T, MD-LG	99	\$486 NI
		FOR USE WITH: H55s or H65s		
W	269-7271	LINES, H55-H65, SSL	22	\$417 NI
		FOR USE WITH: All SSL/MTL/CTL and H55/H65 (Pin-on/Flat top) and 532-9250 BRACKET, SSL, MD-GL CAN NOT BE USED: With B series Hammers		

HAMMERS - TOOLS for H55 Pin-On and H55 Silenced FLAT TOP

W	423-8310	TOOL, CHISEL, INLINE, H55	24	\$236 NI
W	428-8024	TOOL, CHISEL, CROSSCUT, H55	24	\$236 NI
W	423-8312	TOOL, CONE, H55	23	\$236 NI
W	423-8314	TOOL, BLUNT, H55	0	\$236 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

HAMMERS - TOOLS for H55 Pin-On and H55 Silenced FLAT TOP (Cont.)

W	433-9655	TOOL, SPADE PARALLEL, H55	635	\$458 NI
W	433-9654	TOOL, SPADE TRANSVERSE, H55	22	\$458 NI
W	433-9648	TOOL, COMPACTING PLATE, H55	82	\$1,465 NI

HAMMERS - H65 Flat top

Hammer Compatibility:

	226	232	242	247	252	257	262	277	287	297					
	216	228	236	239	246	248	249	256	259	268	267	272	279	289	299

H65	C	C	C	C	C	C	C	C	C	C	C	C	C	C
-----	---	---	---	---	---	---	---	---	---	---	---	---	---	---

C = Compatible/ *= lift restricted/ # = Extra counter weight required

If no hammer references appear below there are no H65 Hammers currently available in your region.

W	561-2552	HAMMER, H65S	534	\$11,167 NI
		Silenced hydraulic hammer, flat top with drill pattern LG BPM (blows/minute): 720-1,740 , Energy Class 1,085 Joule (800 ft-lb) INCLUDES: Housing and power cell, 1 tool box, nitrogen charge & 2 tools (1x cone and 1x chisel cross cut) REQUIRED HYDRAULICS: Min - Max Flow: 40-115 l/min (10.6-30.4 gal/min) Max Operation Pressure 16,499 kPa (2,393 psi) REQUIRES: Machine side: hammer lines and front guards / Hammer side: mounting bracket LG, connecting lines		
W	532-9250	BRACKET, SSL, MD-LG	300	\$1,181 NI
		Bracket with SSL interface, lines and quick disconnects NOT incl. FOR USE WITH: B and H Hammers with drill pattern MD or LG and SSL, CTL and SSL, CTLand MTL machines REQUIRES: connecting lines		
W	269-7807	BRACKET, SSL, PO	225	\$1,238 NI
		FOR USE WITH: H55s flat top, H65s flat top, H55Es PIN-ON, H65Es PIN-ON REQUIRES: Bracket 532-9275		
W	532-9275	BRACKET, MHE 3-5T, MD-LG	99	\$486 NI
		FOR USE WITH: H55s or H65s		
W	269-7271	LINES, H55-H65, SSL	22	\$417 NI
		FOR USE WITH: All SSL/MTL/CTL and H55/H65 (Pin-on/Flat top) and 532-9250 BRACKET, SSL, MD-GL CAN NOT BE USED: With B series Hammers		

HAMMERS - TOOLS for H65 Pin-On and H65 Silenced FLAT TOP

W	423-8307	TOOL, CHISEL, INLINE, H65	38	\$264 NI
---	----------	---------------------------	----	----------

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

HAMMERS - TOOLS for H65 Pin-On and H65 Silenced FLAT TOP (Cont.)

W	428-8022	TOOL, CHISEL, CROSSCUT, H65	38	\$264 NI
W	423-8308	TOOL, CONE, H65	38	\$264 NI
W	423-8309	TOOL, BLUNT, H65	0	\$264 NI
W	433-9653	TOOL, SPADE PARALLEL, H65	33	\$465 NI
W	433-9652	TOOL, SPADE TRANSVERSE, H65	33	\$465 NI
W	433-9651	TOOL, COMPACTING PLATE, H65	90	\$1,465 NI

HAMMERS - LEGACY BRACKETS & MOUNTING GROUPS H HAMMERS PIN-ON

W	356-3241	BRACKET, SSL, C-D	288	\$1,306 NI
W	249-1144	KIT, MOUNTING GROUP SSL 2T Mounting group including 2 bucket pins, 4 renten.pins and 4 bushings FOR USE WITH: SSL with BH30/BH30W and H55E Pin-On	8	\$208 NI
W	249-1145	KIT, MOUNTING GROUP SSL 3T Mounting group including 2 bucket pins, 4 renten.pins and 4 bushings FOR USE WITH: SSL with BH160 and H55E/H65E Pin-On	9	\$208 NI
W	269-7271	LINES, H55-H65, SSL FOR USE WITH: All SSL/MTL/CTL and H55E/H65E (Pin-on/Flat top)	22	\$417 NI
W	270-8680	LINES, H55D, PO, 2T, STD STICK INCLUDES: hose assemblies, quick disconnects and required connectors FOR USE WITH: SSL with BH30/BH30W and H55E Pin-On	13	\$319 NI
W	270-8681	LINES, H55D, PO, 2T, LONG STICK INCLUDES: hose assemblies, quick disconnects and required connectors FOR USE WITH: SSL with BH160 and H55E/H66E Pin-On	15	\$319 NI
W	316-0411	KIT, MOUNTING GRP, H55D 40MM Mounting group including 2 bucket pins, 4 renten.pins and 4 bushings FOR USE WITH: SSL with BH160 and H55D Pin-On	22	\$486 NI
W	252-1211	KIT, MOUNTING GRP, H65D 40MM Mounting group including 2 bucket pins, 4 renten.pins and 4 bushings FOR USE WITH: SSL with BH160 and H65D Pin-On	22	\$389 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

LANDSCAPE RAKES

Nomenclature change: LR116 is replacement for LR15B, NO tech. changes
LR116 stands for standard flow + working width ca. 1.6m
Nomenclature change: LR119 is replacement for LR18B, NO tech. changes
LR119 stands for standard flow + working width ca. 1.9m

Designed to pulverize, aerate, level and condition the soil, while collecting and depositing stones, rock and debris in the integrated hopper bucket for quick removal. To be operated in reverse drive.

	216	228	236	246	248	248	252	257	262		277	287	297
	226	232	242	247	249	268	256	259	267	272	279	289	299
LR116	C*	C*	C*	C*	C*	C*	C*	C*	C*	C*	C*	C*	C*
LR119				C*		C*	C*	C*	C*	C*	C*	C*	C*

C = Compatible/ *= lift restricted
Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	224-9220	LANDSCAPE RAKE, LR116.	1,309	\$7,750 NI
		LR116 (old LR15B) with working width of approx. 1.6m 1676mm (66") overall width, 1576mm (62") working width 1397mm (55") raking width, struck capacity 0.31m3 (0.4 yd3) Rake bars on conveyer chains, Poppet valve controlled circuitry Hydraulic Flow range: 42-86 l/min (11-23 gpm) Hydraulic Pressure range: 145-235 bar (2,100-3,400 psi) INCLUDES: CHAIN drive unit, hydraulic lines with quick disconnects, mounting bracket and hardware REQUIRES: Standard Flow Hydraulics		
W	224-9221	LANDSCAPE RAKE, LR119.	1,437	\$8,292 NI
		LR119 (old LR18B) with working width of approx. 1.9m 1930mm (76") overall width, 1880mm (74") working width 1702mm (67")raking width, struck capacity 0.34m3 (0.44 yd3) Rake bars on conveyer chains, Poppet valve controlled circuitry Hydraulic Flow range: 42-86 l/min (11-23 gpm) Hydraulic Pressure range: 145-235 bar (2,100-3,400 psi) INCLUDES: CHAIN drive unit, hydraulic lines with quick disconnects, mounting bracket and hardware REQUIRES: Standard Flow Hydraulics		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

LANDSCAPE TILLERS

Nomenclature change: LT114 is replacement for LT13B, NO technical changes. LT114 stands for standard flow + working width ca. 1.4m
 Nomenclature change: LT118 is replacement for LT18B, NO technical changes. LT118 stands for standard flow + working width ca. 1.8m

For breaking up and pulverizing soil, mixing material into the soil, stabilizing and leveling terrain in landscaping, agricultural and other ground maintenance applications.

Compatibility for B Series machines and up:

	B & B2 & B3					C & C2			D & D2 & D3					
	228	249	247			262	287		236	246	279	272		
	216	232	262	257		246	277	289	226	239	257	262	287	297
	226	236	242	268	259	256	279	299	232	242	249	259	277	289
LT114	++	++	++	++	++	++	+-	+-	++	++	++	++	+-	+-
LT118	--	--	--	++	++	++	++	++	--	--	++	++	++	++

++ = Optimal attachment-machine combination, -- = Not Allowed
 +- = Less optimal attachment-machine combination

Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"
 If no reference numbers appear below there are currently no items available in your region.

W	219-7165	LANDSCAPE TILLER, LT114	735	\$5,479 NI
		LT114 (old LT13B) with working width of approx. 1.4m Width overall / working: 1788mm (70.5") / 1354mm (52), 24 Bi-Rotational hardened tines, Working depth 25-152mm (1"- 6"), Bi-Directional Hydraulic Motor, offset to cover right side tire Hydraulic Flow range: 42-83 l/min (11-22 gpm) Hydraulic Pressure range: 145-235 bar (2,100-3,400 psi) INCLUDES: DIRECT drive unit, hydraulic lines with quick disconnects, mounting bracket and hardware. REQUIRES: Standard Flow Hydraulics		
W	219-0426	LANDSCAPE TILLER, LT118	907	\$6,215 NI
		LT118 (old LT18B) with working width of approx. 1.8m Width overall / working: 2271mm (89.5") / 1848mm (73), 36 Bi-Rotational hardened tines, Working depth 25-152mm (1"- 6"), Bi-Directional Hydraulic Motor, offset to cover right side tire Hydraulic Flow range: 83-114 l/min (22-30 gpm) Hydraulic Pressure range: 207-310 bar (3,000-4,500 psi) INCLUDES: DIRECT drive unit, hydraulic lines with quick disconnects, mounting bracket and hardware. REQUIRES: Standard Flow Hydraulics		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-------------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

MACHINE ATTACHMENTS - MACHINE WATER TANKS

Control, Work Tool, and Electrical also REQUIRED for operation of machine water tank and any work tool sprinkler kit. (Order with machine)

Ensure overall weight of tank plus work tool does not exceed the ROPS certification.

NOTE: For C-series machines no kit water tank is available. Please order direct on Antares the consist parts list mentioned in the installation instructions REHS8716.

W	346-1834	KIT, WATER TANK, 42 US GAL, AB 164 Cab mounted water tank, capacity 42 US gallons (160Ltr) FOR USE WITH: A & B Series machines INCLUDES: tank, pump, filter, lines, mounting brackets and quick disconnect INCLUDES: Harness for use with B3 high flow machines REQUIRES: Water Sprinkler Kit: Angle/Pick Up/Utility Broom, Cold planer	164	\$1,815 NI
W	482-5132	KIT, WATER TANK, 42 US GAL, D 0 Cab to mounted water tank, capacity 42 US gallons (160 Ltr) FOR USE WITH: D-series machines INCLUDES: tank, pump, filter, lines, mounting brackets and quick disconnect REQUIRES: Water Sprinkler Kit: Angle/Pick Up/Utility Broom, Cold planer For installation see media number SEHS0363 (approx 9.5 hours)	0	\$1,872 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

MATERIAL HANDLING ARM

The all purpose Material Handling Arm is a useful work tool for virtually all types of applications; including industrial, construction, and agriculture. The heavy duty design is also ideal for landscaping to load, carry, and set trees and large shrubs. Designed for two person operation.

	226	232	239		247	248			257	262		277	287	297	
	216	228	236	242	246	249	268	252	256	259	272	267	279	289	299
Arm	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C

C = Compatible

W	216-8756	ARM, MATERIAL HANDLING, SSL	280	\$1,724 NI
		Lift Capacity : Maximum 2000 lbs. (not to exceed rated load capacity of machine) Overall Width, with step, 52" (1319mm) Maximum horizontal reach 84" (2135mm) Maximum vertical reach 53" (1357mm) Single bent boom design with heavy duty clasped hook Two hook locations and easy access load tie down points Two compartments for chains and hooks One person operation REQUIRES center mounted step, available through Parts only below: 188-7176 Step Assembly (Qty 1) 8T-4121 Washer (Qty 6) 8T-4133 Nut (Qty 6) 8T-4195 Bolt (Qty 6)		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

MULCHERS

Mulchers are designed for high performance cutting and mulching vegetation, saplings and undergrowth from overgrown agricultural and forested terrain. The hydraulic mulcher reduces saplings, shrubs and trees into mulched material, making it ideal for environmental maintenance, such as brush clearing and creating fire lanes. Other applications include reclaiming untilled land, removing foliage from building construction sites, and shredding pruned material and waste for biomass production.

dealer.cat.com/cda/files/3386820/7/Marketing_Bulletin_Mulchers.pdf

The Turbo Guard Kit and the Debris Kit are required (when available) in applications with the potential for airborne debris. Example airborne debris laden environments are mulching, brushcutting, forestry applications, mowing, certain agricultural applications, paper recycling, etc.. Please refer to the machine price pages "Field Installed Attachments" section for the appropriate part numbers.

MULCHER COMPATIBILITY	216	226	228	232	239	249	236	242	246	247	248	268	252	256	257	262	272	267	277	297	287	289	299
HM112C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
HM115C																							
HM215C		C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
HM312 XPS									C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
HM315 XPS									C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
HM315B/C XPS									C	C	C	C	C	C	C	C	C	C	C	C	C	C	C

HM415B/C and HM418C for XE/XHP machines ONLY

C = Compatible

Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

MULCHERS (Cont.)

W	475-2750	<p>MULCHER, HM112C, SF 1,682</p> <p>49" (1240mm) drum width - 30 fixed reversible chisel teeth 60" (1518mm) overall width, 8" (200mm) Max cutting diameter For use in brush, vine, and softwood applications INCLUDES: Dual speed motor, V-belt drive, single bolt tooth retention, pressure gauge, adjustable push/guard frame, hydraulically operated front hood, diverter valve installed on work tool, hydraulic lines with 1/2" quick disconnects, case drain, 14-pin electrical harness, mounting brackets and hardware. REQUIRES: Standard flow hydraulics 16-18 GPM (60-69 LPM) AND Standard pressure 3300 PSI (230 BAR) REQUIRES: 377-1579 Conversion harness, Work Tool electrical control, and custom case drain lines on machine for B/B2/B3/C/C2 Series, standard flow only machines. REQUIRES: 377-1579 Conversion harness for B/B2/C/C2 Series high flow machines. REQUIRES: Turbo Guard Kit and Debris Kit on machine</p>		\$25,347 NI
W	475-2760	<p>MULCHER, HM115C, SF 1,803</p> <p>58" (1480mm) drum width - 36 fixed reversible chisel teeth 69" (1758mm) overall width, 8" (200mm) Max cutting diameter For use in brush, vine, and softwood applications INCLUDES: Dual speed motor, V-belt drive, single bolt tooth retention, pressure gauge, adjustable push/guard frame, hydraulically operated front hood, diverter valve installed on work tool, hydraulic lines with 1/2" quick disconnects, case drain, 14-pin electrical harness, mounting brackets and hardware. Hydraulic lines with 1/2" quick disconnects, case drain line, and 14-pin electrical harness, mounting brackets, and hardware. REQUIRES: Standard flow hydraulics 20-23 GPM (76-87 LPM) AND Standard pressure 3300 PSI (230 BAR) REQUIRES: 377-1579 Conversion harness, Work Tool electrical control, and custom case drain lines on machine for B/B2/B3/C/C2 Series, standard flow only machines. REQUIRES: 377-1579 Conversion harness for B/B2/C/C2 Series high flow machines. REQUIRES: Turbo Guard Kit and Debris Kit on machine</p>		\$26,667 NI
W	475-2770	<p>MULCHER, HM215C, HF 1,803</p> <p>58" (1480mm) drum width - 36 fixed reversible chisel teeth 69" (1758mm) overall width, 8" (200mm) Max cutting diameter For use in brush, vine, and softwood applications For use in brush, vine, and softwood applications INCLUDES: Dual speed motor, V-belt drive, single bolt tooth retention, pressure gauge, adjustable push/guard frame, hydraulically operated front hood, diverter valve installed on work tool, hydraulic lines with 1/2" quick disconnects, case drain, 14-pin electrical harness, mounting brackets and hardware. REQUIRES: High flow hydraulics 25-31 GPM (96-117 LPM) REQUIRES: 371-3725 Conversion Kit for B/B2/C/C2 series high flow machines. REQUIRES: Turbo Guard Kit and Debris Kit on machine</p>		\$27,639 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

MULCHERS (Cont.)

W	475-2780	<p>MULCHER, HM315C, HF XPS 2,959</p> <p>62" (1582mm) drum width - 34 Single bolt retention teeth 74" (1882mm) overall width, 8" (200mm) Max cutting diameter For use in hardwood applications INCLUDES: Dual speed motor, Pressure Gauge, Polychain belt drive, Adjustable push/guard frame, Diverter Valve, Hydraulically operated front hood, Hydraulic lines with 1/2" quick disconnects, case drain line, and 14-pin electrical harness, mounting brackets and hardware. REQUIRES: High Flow XPS hydraulics 31-33 GPM (120-125 LPM) AND Pressure 4061 PSI (280 BAR) REQUIRES: 371-3725 Conversion Kit for B/B2/C/C2 Series high flow machines REQUIRES: Turbo Guard Kit and Debris Kit on machine</p>		\$36,500 NI
W	475-2790	<p>MULCHER, HM415C, XE/XHP 2,959</p> <p>62" (1582mm) drum width - 34 Single bolt retention carbide teeth 74" (1882mm) overall width, 8" (200mm) Max cutting diameter For use in hardwood applications INCLUDES: Dual speed motor, Pressure Gauge, Poly chain belt drive, Adjustable push/guard frame, Diverter Valve, Hydraulically operated front hood, Hydraulic lines with 3/4" quick disconnects, case drain line, and 14-pin electrical harness, mounting brackets and hardware. REQUIRES: XE or XHP hydraulics 40-41 GPM (150-155 LPM) AND Pressure 4061 PSI (280 BAR) REQUIRES: Turbo Guard Kit and Debris Kit on machine REQUIRES: Conversion to screw-to-connect quick disconnects for: 299D2 XHP, serial prefix HLM (see M0097141) and 299D3 XE, serial prefix XES/LB3 (see M0110695)</p>		\$39,743 NI
W	475-2800	<p>MULCHER, HM418C, XE/XHP 3,197</p> <p>72" (1822mm) drum width - 38 Single bolt retention carbide teeth 84" (2122mm) overall width, 8" (200mm) Max cutting diameter For use in hardwood applications INCLUDES: Dual speed motor, Pressure Gauge, Poly chain belt drive, Adjustable push/guard frame, Diverter Valve, Hydraulically operated front hood, Hydraulic lines with 3/4" quick disconnects, case drain line, and 14-pin electrical harness, mounting brackets and hardware. REQUIRES: XE or XHP hydraulics 40-41 GPM (150-155 LPM) AND Pressure 4061 PSI (280 BAR) REQUIRES: Turbo Guard Kit and Debris Kit on machine REQUIRES: Conversion to screw-to-connect quick disconnects for: 299D2 XHP, serial prefix HLM (see M0097141) and 299D3 XE, serial prefix XES/LB3 (see M0110695)</p>		\$42,264 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

MULCHERS - BITE LIMITER

New line of high performance mulchers with bite limiters. The bite limiter minimises stalling of the mulcher and the chisel blade design has been updated to increase life and serviceability. Mulchers are designed for high performance cutting and mulching vegetation, saplings and undergrowth from overgrown agricultural and forested terrain. The hydraulic mulcher reduces saplings, shrubs and trees into mulched material, making it ideal for environmental maintenance, such as brush clearing and creating fire lanes. Other applications include reclaiming untilled land, removing foliage from building construction sites, and shredding pruned material and waste for biomass production.

dealer.cat.com/cda/files/3386820/7/Marketing_Bulletin_Mulchers.pdf

The Turbo Guard Kit and the Debris Kit are required (when available) in applications with the potential for airborne debris. Example airborne debris laden environments are mulching, brushcutting, forestry applications, mowing, certain agricultural applications, paper recycling, etc.. Please refer to the machine price pages "Field Installed Attachments" section for the appropriate part numbers.

Bite Limiter Mulchers Compatibilty for B Series machines and up:

B & B2 & B3				C & C2			D & D2 & D3						
232	226			262	287		246	279	272				
236	252	242	257	246	277	289	226	239	236	257	262	287	297
247	262	268	259	256	279	299	232	249	242	259	277	289	299

The machines must have HF, HF XPS or XHP/XE hydraulics#:

HM315C BL	--	++	--	--	++	++	++	--	--	--	--	++	++	++
-----------	----	----	----	----	----	----	----	----	----	----	----	----	----	----

XHP/XE machines only#:

HM415C BL	--	--	--	--	--	--	--	--	--	--	--	--	--	++
HM418C BL	--	--	--	--	--	--	--	--	--	--	--	--	--	++

- ++ = Compatible with higher productivity
- + = Compatible with lower productivity
- = Not Allowed/Compatible
- # = Using the harness plug the machine is set to the correct flow.
 Not using the harness plug, the machine will be in standard flow.

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

MULCHERS - BITE LIMITER (Cont.)

W	551-4680	<p>MULCHER, HM315C, HF XPS, BL 3,020</p> <p>Mulcher with bite limiter to minimise stalling and to improve the teeth lifetime. Max Cutting depth - diameter: 26mm (1") - 200mm (8") Overall - Drum width: 1882mm (74") - 1582mm (62") , 26 Single bolt retention teeth, Drum speed: 2576-2683 rpm. For hardwood applications. INCLUDES: Dual speed motor, Pressure Gauge, Polychain belt drive, Adjustable push/guard frame, Diverter Valve, Hydraulic lines with 1/2" quick disconnects, case drain line, 14-pin electrical plug to set the machine in High Flow XPS. REQUIRES: High Flow XPS, 120-125 LPM (31-33 gpm) and 280 bar(4061 psi) REQUIRES: 371-3725 Conver. Kit for B/B2/C/C2 Series high flow machines REQUIRES: Turbo Guard Kit and Debris Kit on machine</p>	3,020	\$36,500 NI
W	551-4690	<p>MULCHER, HM415C, XE/XHP, BL 3,020</p> <p>Mulcher with bite limiter to minimise stalling and to improve the teeth lifetime. Max Cutting depth - diameter: 26mm (1") - 200mm (8") Overall - Drum width: 1882mm (74") - 1582mm (62") , 26 Single bolt retention teeth, Drum speed: 2673-2762 rpm. For hardwood applications. INCLUDES: Dual speed motor, Pressure Gauge, Poly chain belt drive, Adjustable push/guard frame, Diverter Valve, Hydraulic lines with 3/4" quick disconnects, case drain line, 14-pin electrical plug to set the machine in Xe or XHP hydraulic setting. REQUIRES: Xe or XHP hydraulics 150-155 LPM (40-41 gpm) and 280 bar (4061 psi). REQUIRES: Turbo Guard Kit and Debris Kit on machine REQUIRES: Conversion to screw-to-connect quick disconnects for: 299D2 XHP, serial prefix HLM (see M0097141) and 299D3 XE, serial prefix XES/LB3 (see M0110695)</p>	3,020	\$39,743 NI
W	551-4700	<p>MULCHER, HM418C, XE/XHP, BL 3,316</p> <p>Mulcher with bite limiter to minimise stalling and to improve the teeth lifetime. Max Cutting depth - diameter: 26mm (1") - 200mm (8") Overall - Drum width: 2122mm (84") -1822mm (74") , 32 Single bolt retention teeth, Drum speed: 2673-2762 rpm. For hardwood applications. INCLUDES: Dual speed motor, Pressure Gauge, Poly chain belt drive, Adjustable push/guard frame, Diverter Valve, Hydraulic lines with 3/4" quick disconnects, case drain line, 14-pin electrical plug to set the machine in Xe or XHP hydraulic setting. REQUIRES: Xe or XHP hydraulics 150-155 LPM (40-41 gpm) and 280 bar (4061 psi). REQUIRES: Turbo Guard Kit and Debris Kit on machine REQUIRES: Conversion to screw-to-connect quick disconnects for: 299D2 XHP, serial prefix HLM (see M0097141) and 299D3 XE, serial prefix XES/LB3 (see M0110695)</p>	3,316	\$42,264 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

MULCHER OPTIONS

W	231-2578	GUARD, MANUAL COUPLER..... 7		\$56 NI
		Required if used in conjunction with machine that has manual coupler. Shields manual levers from debris damage. Two required per machine. Compatible with A/B/C Series machines; not compatible with D-Series		

NOTEF

Optional replacement teeth available through Parts/Antares only:

A series mulchers (double bolt retention)		HM312		HM315
Hardwoods:				
247-5913 Tooth, Carbide		26x		32x
247-5914 Tooth, Carbide Severe Duty		2x		2x
Softwoods:				
308-0221 Tooth, Chisel		28x		34x
308-0222 Insert gr., chisel Replacement for 308-0221				
B series mulchers (single bolt retention)		HM315B		HM415B
382-6262 TOOTH AS., CUTTER		32x		32x
382-6263 TOOTH AS., CUTTER, SEVERE DUTY		2x		2x
C series mulchers		HM112C	HM115C	HM215C
475-2746 Reversible Chisel Tooth		30x	36x	36x
475-2747 Kit, teeth (pack of 10x 475-2746)				
482-1444 Bolt, single retention		30x	36x	36x
For a full set:		HM315C	HM415C	HM418C
475-2810 Standard Carbide tooth		32x	32x	38x
475-2811 Right Side Scraper Carbide		1x	1x	1x
475-2812 Left Side Scraper Carbide		1x	1x	1x
475-2816 Kit-bolt S/N MH500146 and below		34x	34x	38x
487-2141 Kit-bolt S/N MH500147 and up		34x	34x	38x
For a full set (bite limiter):		HM315C-BL	HM415C-BL	HM418C-BL
570-2133 Chisel tooth		24x	24x	30x
475-2811 Right Side Scrapper Carbide		1x	1x	1x
475-2812 Left Side Scrapper Carbide		1x	1x	1x
Optional:				
475-2813 Rock Resistant, additional Carbide surface for use in rocky substrate.				
570-2133 Chisel, Knife tooth requires sharpening every 8-10 hours, please consult OMM for proper practices. REQUIRES: 570-2134 Chisel Adapter (one per tooth, only necessary on first installation of Chisel teeth)				
475-2819 Kit, teeth (Pack of 10x 475-2810 Standard Carbide tooth)				

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

POWER BOX RAKES

216	232	242				262	272			
226	236	246	248	256	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

PR172	C	C	C	C	C	C	C	C	C	C
PR184	C	C	C	C	C	C	C	C	C	C
PR190	C	C	C	C	C	C	C	C	C	C

C = Compatible
 Pre 2015 XHP machines & prefix NLC/SHY check section "CONVERSION KITS"

If no reference numbers appear below there are currently no items available in your region.

W	424-0420	POWER BOX RAKE-HYDRAULIC,PR172	925	\$11,306 NI
		Width overall - working: 2057mm (81") - 1829mm (72") Hydraulic angling +/- 20 degrees over center INCLUDES: Hydraulic lines with 1/2" quick disconnects, mounting bracket, & 14-pin electrical harness REQUIRES: Standard Flow hydraulics, 49-86 l/min (13-23 gpm) at 230 bar (3,340 psi) REQUIRES: Work Tool Harness and 4 button left hand joystick on machine REQUIRES: Conversion harness 377-1579 for B/B2/B3/C/C2 series		
W	277-8210	POWER BOX RAKE-MANUAL, PR172	900	\$10,368 NI
		Width overall - working: 2057mm (81") - 1829mm (72") MANUAL angling: +/- 20 degrees over center REQUIRES: Standard Flow hydraulics, 49-86 l/min (13-23 gpm) at 230 bar (3,340 psi)		
W	424-0421	POWER BOX RAKE-HYDRAULIC,PR184	1,050	\$11,958 NI
		Width overall - working: 2362mm (93") - 2134mm (84") Hydraulic angling +/- 20 degrees over center INCLUDES: Hydraulic lines with 1/2" quick disconnects, mounting bracket, & 14-pin electrical harness REQUIRES: Standard Flow hydraulics, 57-86 l/min (15-23 gpm) at 230 bar (3,340 psi) REQUIRES: Work Tool Harness and 4 button left hand joystick on machine REQUIRES: Conversion harness 377-1579 for B/B2/B3/C/C2 series		
W	277-8215	POWER BOX RAKE-MANUAL, PR184	1,026	\$10,743 NI
		Width overall - working: 2362mm (93") - 2134mm (84") MANUAL angling: +/- 20 degrees over center REQUIRES: Standard Flow hydraulics, 57-86 l/min (15-23 gpm) at 230 bar (3,340 psi)		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-------------------------------	--------------------	-------------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

POWER BOX RAKES (Cont.)

W	424-0422	POWER BOX RAKE-HYDRAULIC,PR190..... 1,320 Width overall - working: 2515mm (99") - 2286mm (90") Hydraulic angling +/- 20 degrees over center INCLUDES: Hydraulic lines with 1/2" quick disconnects, mounting bracket, & 14-pin electrical harness REQUIRES: Standard Flow hydraulics, 57-86 l/min (15-23 gpm) at 230 bar (3,340 psi) REQUIRES: Work Tool Harness and 4 button left hand joystick on machine REQUIRES: Conversion harness 377-1579 for B/B2/B3/C/C2 series	1,320	\$12,889 NI
---	----------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------	--------------------

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

WHEEL SAWS

All wheel saws have radial piston direct drive hydraulic motors for optimal performance and endurance.

NOTE: ALL wheel saws are restricted for sale in the European Union due to local regulations.

APPLIES TO STATED MODELS ONLY (B incl B2&B3 / C incl C2 / D incl D2)
 242B 257B 256C 272D 297C
 246C 257D 259D 277D 277C 287C 299C
 246D 259B 268B 262C 262D 272C 279D 279C 287D 289C 289D 299D

SW345B 3"	C#*	C#*	C#	C#	C#	C	C	C#	C	C	C	C
SW360B 3"						C#	C#*	C#*	C#*	C#*	C#	CR
SW360B 4"				C#	C#*	C	C#*	C#*	C#	C#	C#	CR
SW360B 5"				C#	C#*	C	C#*	C#*	C#	C#	C#	CR
SW360B 6"				C#	C#*	C	C#*	C#*	C#	C#	C#	CR
SW360B 8"				C#	C#*	C	C#*	C#*	C#	C#	C#	CR
SW380B						C#	C#*	C#*	C#*	C#*	C#	CR

SW460B and SW480B for XE/XHP machines ONLY

C = Compatible/ *= lift restricted/ # = Extra counter weight required
 R = For 299D/D2 XHP and 299D3 XE machines avoid exceeding max total rated capacity.

If no reference numbers appear below there are currently no items available in your region.

W	529-5880	WHEEL SAW, SW345, 3"	2,482	\$26,125 NI
		Optimal Flow / Pressure: 33 gpm / 4000 psi (125 l/min / 280 bar)		
		Dimensions (L x W x H): 85" x 73" x 57" (2165 x 1850 x 1455mm)		
		Saw Width x max Dig Depth: 3" x 18" (80mm x 450mm)		
		Bits: 64 x 227-7340 Concrete Conical bits		
		Electro-Hydraulic Side shift, Depth Control		
		Max Pro Pressure Gauge (for identifying optimal performance)		
		INCLUDES: hydraulic lines with quick disconnects, mounting bracket		
		REQUIRES: HF XPS Hydraulics,		
		REQUIRES: Joysticks: Left WT Deluxe and Right Hydraulic Proportional		
		REQUIRES: Control, Work Tool, Electrical		
		REQUIRES: Machine Counterweights		
		REQUIRES: for B/B2/C/B2 with HF(XPS) conversion kit: 371-3725		
		REQUIRES: kit 382-6186 for D series with XHP with prefix NLC/SHY		
		Note: Cannot be used with trench cleaning device		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

WHEEL SAWS (Cont.)

W	529-5867	WHEEL SAW, SW345, 5" 2,240 Optimal Flow / Pressure: 33 gpm / 4000 psi (125 l/min / 280 bar) Dimensions (L x W x H): 85" x 73" x 57" (2165 x 1850 x 1455mm) Saw Width x max Dig Depth: 5" x 18" (130mm x 450mm) Bits: 56 x 227-7340 Concrete Conical bits Electro-Hydraulic Side shift, Depth Control, Trench Cleaning device Max Pro Pressure Gauge (for identifying optimal performance) INCLUDES: hydraulic lines with quick disconnects, mounting bracket REQUIRES: HF XPS Hydraulics, REQUIRES: Joysticks: Left WT Deluxe and Right Hydraulic Proportional REQUIRES: Control, Work Tool, Electrical REQUIRES: Machine Counterweights REQUIRES: for B/B2/C/B2 with HF(XPS) conversion kit: 371-3725 REQUIRES: kit 382-6186 for D series with XHP with prefix NLC/SHY		\$26,444 NI
W	529-5860	WHEEL SAW, SW360, 3" 3,175 Optimal Flow / Pressure: 33 gpm / 4000 psi (125 l/min / 280 bar) Dimensions (L x W x H): 93" x 73" x 70" (2365 x 1850 x 1765mm) Saw Width x Depth: 3" x 24" (80mm x 600mm) Bits: 70 x 227-7340 Concrete Conical bits Electro-Hydraulic Side shift, Depth Control Max Pro Pressure Gauge (for identifying optimal performance) INCLUDES: hydraulic lines with quick disconnects, mounting bracket REQUIRES: HF XPS Hydraulics REQUIRES: Joysticks: Left WT Deluxe and Right Hydraulic Proportional REQUIRES: Control, Work Tool, Electrical pins harness, mounting REQUIRES: Machine Counterweights REQUIRES: for B/B2/C/C2 with HF(XPS) conversion kit: 371-3725 REQUIRES: kit 382-6186 for D series with XHP with prefix NLC/SHY RECOMMENDED: AMICS or advanced display, Heavy Duty tire fitment Note: Cannot be used with trench cleaning device		\$29,597 NI
W	529-5868	WHEEL SAW, SW360, 4" 2,943 Optimal Flow / Pressure: 33 gpm / 4000 psi (125 l/min / 280 bar) Dimensions (L x W x H): 93" x 73" x 70" (2365 x 1850 x 1765mm) Saw Width x Depth: 4" x 24" (100mm x 600mm) Bits: 80 x 227-7340 Concrete Conical bits Electro-Hydraulic Side shift, Depth Control, Trench Cleaning device Max Pro Pressure Gauge (for identifying optimal performance) INCLUDES: hydraulic lines with quick disconnects, mounting bracket REQUIRES: HF XPS Hydraulics REQUIRES: Joysticks: Left WT Deluxe and Right Hydraulic Proportional REQUIRES: Control, Work Tool, Electrical pins harness, mounting REQUIRES: Machine Counterweights REQUIRES: for B/B2/C/C2 with HF(XPS) conversion kit: 371-3725 REQUIRES: kit 382-6186 for D series with XHP with prefix NLC/SHY RECOMMENDED: AMICS or advanced display, Heavy Duty tire fitment		\$29,722 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

WHEEL SAWS (Cont.)

W	440-8260	WHEEL SAW, SW360B, 5" 0 Optimal Flow / Pressure: 33 gpm / 4000 psi (125 l/min / 280 bar) Dimensions (L x W x H): 93" x 73" x 70" (2365 x 1850 x 1765mm) Saw Width x max Dig Depth: 5" x 24" (130mm x 600mm) Bits: 80 x 227-7340 Concrete Conical Electro-Hydraulic Side shift, Depth Control, Trench Cleaner INCLUDES: hydraulic lines with quick disconnects, mounting bracket REQUIRES: HF XPS Hydraulics, REQUIRES: Joysticks: Left WT Deluxe and Right Hydraulic Proportional REQUIRES: Control, Work Tool, Electrical 14-pins REQUIRES: Machine Counterweights REQUIRES: for B/B2/C/C2 with HF(XPS) conversion kit: 371-3725 REQUIRES: kit 382-6186 for D series with XHP with prefix NLC/SHY		\$29,049 NI
W	529-5861	WHEEL SAW, SW360, 6" 2,899 Optimal Flow / Pressure: 33 gpm / 4000 psi (125 l/min / 280 bar) Dimensions (L x W x H): 93" x 73" x 70" (2365 x 1850 x 1765mm) Saw Width x Depth: 6" x 24" (150mm x 600mm) Bits: 96 x 227-7340 Concrete Conical bits Electro-Hydraulic Side shift, Depth Control, Trench Cleaning device Max Pro Pressure Gauge (for identifying optimal performance) INCLUDES: hydraulic lines with quick disconnects, mounting bracket REQUIRES: HF XPS Hydraulics REQUIRES: Joysticks: Left WT Deluxe and Right Hydraulic Proportional REQUIRES: Control, Work Tool, Electrical pins harness, mounting REQUIRES: Machine Counterweights REQUIRES: for B/B2/C/C2 with HF(XPS) conversion kit: 371-3725 REQUIRES: kit 382-6186 for D series with XHP with prefix NLC/SHY		\$30,083 NI
W	529-5862	WHEEL SAW, SW360, 8" 2,921 Optimal Flow / Pressure: 33 gpm / 4000 psi (125 l/min / 280 bar) Dimensions (L x W x H): 93" x 73" x 70" (2365 x 1850 x 1765mm) Saw Width x Depth: 8" x 24" (200mm x 600mm) Bits: 96 x 227-7340 Concrete Conical bits Electro-Hydraulic Side shift, Depth Control, Trench Cleaning device Max Pro Pressure Gauge (for identifying optimal performance) INCLUDES: hydraulic lines with quick disconnects, mounting bracket REQUIRES: HF XPS Hydraulics REQUIRES: Joysticks: Left WT Deluxe and Right Hydraulic Proportional REQUIRES: Control, Work Tool, Electrical pins harness, mounting REQUIRES: Machine Counterweights, Trench clearing device. REQUIRES: for B/B2/C/C2 with HF(XPS) conversion kit: 371-3725 REQUIRES: kit 382-6186 for D series with XHP with prefix NLC/SHY RECOMMENDED: AMICS or advanced display, Heavy Duty tire fitment		\$30,583 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

WHEEL SAWS (Cont.)

W	381-8450	WHEEL SAW, SW380B, 10" 3,142 Optimal Flow / Pressure: 33 gpm / 4000 psi (125 l/min / 280 bar) Dimensions (L x W x H): 98" x 73" x 77" (2490 x 1850 x 1950mm) Saw Width x max Dig Depth: 10" x 31.5" (250mm x 800mm) Bits: 72 x 227-7340 Concrete Conical Electro-Hydraulic Side shift, Depth Control, Trench Cleaner INCLUDES: Hydraulic lines with 1/2" quick disconnect, case drain 14 pins harness, mounting bracket and hardware REQUIRES: HF XPS Hydraulics REQUIRES: Joysticks: Left WT Deluxe and Right Hydraulic Proportional REQUIRES: Control, Work Tool, Electrical REQUIRES: Machine Counterweights REQUIRES: for B/B2/C/B2 with HF(XPS) conversion kit: 371-3725 REQUIRES: kit 382-6186 for D series with XHP with prefix NLC/SHY RECOMMENDED: AMICS or advanced display, Heavy Duty tire fitment NOTE: This wheel saw is made to order and may require extended lead times.		\$40,403 NI
---	----------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	--------------------

WHEEL SAWS - WATER SPRAY KITS

W	591-0708	KIT, WATER SPRAY, SW345/360 10 Water sprinkling kit for dust control/suppression. INCLUDES: 4 sprinkler heads, hoses+ 1 QD for water, mounting hardware REQUIRES: Water Tank, Machine (reference machine attachments section of this price list to order) FOR USE WITH: SW345, SW360		\$514 NI
W	591-0709	KIT, WATER SPRAY, SW380/480 9 Water sprinkling kit for dust control/suppression. INCLUDES: 4 sprinkler heads, hoses+ 1 QD for water, mounting hardware REQUIRES: Water Tank, Machine (reference machine attachments section of this price list to order) FOR USE WITH: SW380, SW480		\$500 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

WHEEL SAWS - B SERIES FOR XE/XHP ONLY

NOTE: ALL wheel saws are restricted for sale in the European Union due to local regulations.

COMPATIBLE FOR STATED MODELS ONLY (D, D2, D3 series only)
 272D/D2 XHP 297D/D2 XHP 299D/D2 XHP
 272D3 XE No XE 299D3 XE

SW460B 3"	C#*	C	CR
SW460B 6"	C#*	C	CR
SW460B 8"	C#*	C	CR
SW480B	C#*	C	CR

C = Compatible/ *= lift restricted/ # = Extra counter weight required
 R = For 299D/D2 XHP and 299D3 XE machines avoid exceeding max total rated capacity.

If no reference numbers appear below there are currently no items available in your region.

W	529-5863	WHEEL SAW, SW460, 3" 3,175	\$29,597 NI
		Optimal Flow / Pressure: 40 gpm / 4000 psi (125 l/min / 280 bar) Dimensions (L x W x H): 93" x 73" x 70" (2365 x 1850 x 1765mm) Saw Width x Depth: 3" x 24" (80mm x 600mm) conversion kit: 371-3725 Bits: 70 x 227-7340 Concrete Conical bits XHP with prefix NLC/SHY Electro-Hydraulic Side shift, Depth Control Max Pro Pressure Gauge (for identifying optimal performance) INCLUDES: hydraulic lines with quick disconnects, mounting bracket REQUIRES: XE or XHP Hydraulics REQUIRES: Joysticks: Left WT Deluxe and Right Hydraulic Proportional REQUIRES: Control, Work Tool, Electrical pins harness, mounting REQUIRES: Machine Counterweights RECOMMENDED: AMICS or advanced display, Heavy Duty tire fitment Note: Cannot be used with trench cleaning device	
W	529-5864	WHEEL SAW, SW460, 6" 2,943	\$30,083 NI
		Optimal Flow / Pressure: 40 gpm / 4000 psi (150 l/min / 280 bar) Dimensions (L x W x H): 93" x 73" x 70" (2365 x 1850 x 1765mm) Saw Width x max Dig Depth: 6" x 24" (160mm x 600mm) Bits: 96 x 227-7340 Concrete Conical bits Electro-Hydraulic Side shift, Depth Control, Trench Cleaning device Max Pro Pressure Gauge (for identifying optimal performance) INCLUDES: Hydraulic lines with 3/4" quick disconnect, case drain 14 pins harness, mounting bracket and hardware REQUIRES: XE or XHP hydraulics. REQUIRES: Joysticks: Left WT Deluxe and Right Hydraulic Proportional REQUIRES: Control, Work Tool, Electrical RECOMMENDED: AMICS or advanced display, Heavy Duty tire fitment	

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

WHEEL SAWS - B SERIES FOR XE/XHP ONLY (Cont.)

W	529-5865	WHEEL SAW, SW460, 8" 3,009 Optimal Flow / Pressure: 40 gpm / 4000 psi (150 l/min / 280 bar) Dimensions (L x W x H): 93" x 73" x 70" (2365 x 1850 x 1765mm) Saw Width x max Dig Depth: 8" x 24" (200mm x 600mm) Bits: 96 x 227-7340 Concrete Conical bits Electro-Hydraulic Side shift, Depth Control, Trench Cleaning device Max Pro Pressure Gauge (for identifying optimal performance) INCLUDES: Hydraulic lines with 3/4" quick disconnect, case drain 14 pins harness, mounting bracket and hardware REQUIRES: XE or XHP hydraulics. REQUIRES: Joysticks: Left WT Deluxe and Right Hydraulic Proportional REQUIRES: Control, Work Tool, Electrical REQUIRES: Machine Counterweights RECOMMENDED: AMICS or advanced display, Heavy Duty tire fitment		\$30,583 NI
W	529-5891	WHEEL SAW, SW480, 10" 3,197 Optimal Flow / Pressure: 40 gpm / 4000 psi (150 l/min / 280 bar) Dimensions (L x W x H): 98" x 73" x 77" (2490 x 1850 x 1950mm) Saw Width x max Dig Depth: 10" x 31.5" (250mm x 800mm) Bits: 72 x 227-7340 Concrete Conical bits Electro-Hydraulic Side shift, Depth Control, Trench Cleaning device Max Pro Pressure Gauge (for identifying optimal performance) INCLUDES: Hydraulic lines with 3/4" quick disconnect, case drain 14 pins harness, mounting bracket and hardware REQUIRES: XE or XHP hydraulics. REQUIRES: Joysticks: Left WT Deluxe and Right Hydraulic Proportional REQUIRES: Control, Work Tool, Electrical RECOMMENDED: AMICS or advanced display, Heavy Duty tire fitment NOTE: This wheel saw is made to order and may require extended lead times		\$41,618 NI

Replacement Conical Drum bits and holders for all Wheel Saws:
 222-7571 All Purpose bit (asphalt & concrete)
 227-7340 Concrete Bit
 375-7681 Heavy Duty Concrete bit
 316-2326 Heavy Duty Asphalt bit
 226-9308 Block Holder for bit
 219-5464 SW45 Wide Deflector RHS and Discharge Blanking Plates Kit
 230-7025 SW60 Discharge Blanking Plates Kit
 104-8591 Punch (Bit Remover)
 8T-4474 Puller (Bit Remover)
 Recommendation: An inventory holding of at least 100 of each tip is advised.

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SHEAR

232	242				262	272			
236	246	248	256	257	267	277	287	297	
239	247	249	256	259	268	279	289	299	

S308	C	C	C	C	C	C	C	C	C
------	---	---	---	---	---	---	---	---	---

C = Compatible

W	583-8100	SHEAR, HYDRAULIC, S308	1,213	\$27,764 NI
		Hydraulic Scrap Shear with 360 degrees left and right rotation. REQUIRES: Standard flow hydraulics, 14 pins WT Harness, 4 button Left Hand Joystick, 171-5558 Bracket and 441-6167 KIT CONTROL REQUIRES: 377-1579 Conversion Kit for A/B/B2/B3/C/C2 Series standard flow machines. No conversion required if used on B3-series high flow or any D-series machines.		
W	171-5558	BRACKET, S308, SSL	280	\$1,806 NI
		FOR USE WITH: 171-5495 SHEAR, S305 and Skid Steer Quick Coupler		
W	441-6167	KIT, CONTROL, S308, SSL	54	\$1,938 NI
		INCLUDES: Hydraulic lines with QDs, hydr. valve for opening/closing an rotation of the S305, 14 pins harness to operate hydr. valve FOR USE WITH: 171-5495 SHEAR, S305 and Skid Steer Quick Coupler		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SILAGE DEFACER

For agricultural applications to shave, cut and prepare silage and hay

216	232	242					262	272		
226	236	246	248	256	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

DFS118	C	C	C	C	C	C	C	C	C	C
DFS121	C	C	C	C	C	C	C	C	C	C
DFS124	C	C	C	C	C	C	C	C	C	C

C = Compatible

W	477-9900	SILAGE DEFACER, DFS118	937	\$7,236 NI
		1841mm (72.5") Working Width		
		Hydraulic Flow range:75-90 l/min (20-23 gpm)		
		Hydraulic pressure range:: 139-230 bar (2,000-3,300 psi)		
		REQUIRES: Standard Flow Hydraulics,		
		INCLUDES: Hydraulic lines with 1/2" quick disconnects		
W	479-8090	SILAGE DEFACER, DFS121	1,052	\$7,583 NI
		2146mm (84.5") Working Width		
		Hydraulic Flow range:75-90 l/min (20-23 gpm)		
		Hydraulic pressure range:: 139-230 bar (2,000-3,300 psi)		
		REQUIRES: Standard Flow Hydraulics,		
		INCLUDES: Hydraulic lines with 1/2" quick disconnects		
W	479-8110	SILAGE DEFACER, DFS124	1,109	\$7,931 NI
		2451mm (96.5") Working Width		
		Hydraulic Flow range:75-90 l/min (20-23 gpm)		
		Hydraulic pressure range:: 139-230 bar (2,000-3,300 psi)		
		REQUIRES: Standard Flow Hydraulics,		
		INCLUDES: Hydraulic lines with 1/2" quick disconnects		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SNOW BLOWERS: NEW DESIGN

New design CAT snowblowers. The impeller (with 4 blades) rotates 90 degrees to the auger rotation (90 deg. turn vs old model). This improves productivity and allows removal from heavy and/or icy snow.
https://www.youtube.com/watch?v=yP_tL7e7oMM

NOTE: ALL snow blowers are restricted for sale in the European Union due to local regulations.

NEW SNOWBLOWER Compatibilty for B Series machines and up:

B & B2 & B3					C & C2			D & D2 & D3							
	232		226		262	287		246	279	272					
	236	252	242	257	246	277	289	226	239	236	257	262	287	297	
	216	247	262	268	259	256	279	299	232	249	242	259	277	289	299

Standard Flow setting only:

SR115	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++
SR118	+-	+-	++	+-	++	++	++	++	++	++	++	++	++	++	++
SR121	--	+-	++	+-	++	++	++	++	++	++	++	++	++	++	++

The machines must have HF, HF XPS or XHP/XE hydraulics#:

SR318	--	--	--	++	++	++	++	++	++	++	++	++	++	++	++
SR321	--	--	--	+-	++	++	++	++	++	++	++	++	++	++	++

++ = compatible with higher productivity

+- = compatible with lower productivity

-- = Not Allowed/Compatible

= The correct flow setting is done by using the harness plug

W	580-0607	SNOW BLOWER, SR115	932	\$9,167 NI
		New 4 blade Impeller design with rotation 90 degr. to auger rotation. Operating/Overall width: 1500mm (60") / 1555mm (61.2") Height incl. chute: 1843mm (72"), Throwing distance 12.2m (40ft) Hydraulics: 76-87 l/min (20-23 G/min) / 200-230bar (2,800-3,300 psi) INCLUDES: hydr. lines& 1/2" quick disconnects, 14 pins electr.harness REQUIRES: Standard Flow hydraulics REQUIRES: Work Tool Harness and 4 button left hand joystick on machine to operate the chute rotation (270 degrees) and chute angle		
W	546-4485	SNOW BLOWER, SR118	952	\$9,306 NI
		New 4 blade Impeller design with rotation 90 degr. to auger rotation. Operating/Overall width: 1800mm (72") / 1880mm (73.4") Height incl. chute: 1843mm (72"), Throwing distance 12.2m (40ft) Hydraulics: 76-87 l/min (20-23 G/min) / 200-230bar (2,800-3,300 psi) INCLUDES: hydr. lines& 1/2" quick disconnects, 14 pins electr.harness REQUIRES: Standard Flow hydraulics REQUIRES: Work Tool Harness and 4 button left hand joystick on machine to operate the chute rotation (270 degrees) and chute angle REQUIRES: 377-1579 Conversion Kit for B/B2/B3/C/C2 Series machines		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SNOW BLOWERS: NEW DESIGN (Cont.)

W	545-8977	SNOW BLOWER, SR121 972 New 4 blade Impeller design with rotation 90 degr. to auger rotation. Operating/Overall width: 2100mm (85") / 2185mm (85.4") Height incl. chute: 1843mm (72"), Throwing distance 12.2m (40ft) Hydraulics: 76-87 l/min (20-23 G/min) / 200-230bar (2,800-3,300 psi) INCLUDES: hydr. lines& 1/2" quick disconnects, 14 pins electr.harness REQUIRES: Standard Flow hydraulics REQUIRES: Work Tool Harness and 4 button left hand joystick on machine to operate the chute rotation (270 degrees) and chute angle REQUIRES: 377-1579 Conversion Kit for B/B2/B3/C/C2 Series machines		\$9,444 NI
W	546-4509	SNOW BLOWER, SR318, HF XPS 995 New 4 blade Impeller design with rotation 90 degr. to auger rotation. Operating/Overall width: 1800mm (72") / 1880mm (73.4") Height incl. chute: 1843mm (72"), Throwing distance 12.2m (40ft) Hydraulics: 120-125 l/min (31-33 G/min) / 200-280bar (2,800-4,100 psi) INCLUDES: hydr. lines& 1/2" quick disconnects, 14 pins electr.harness REQUIRES: High Flow XPS or High Flow hydraulics REQUIRES: Work Tool Harness and 4 button left hand joystick on machine to operate the chute rotation (270 degrees) and chute angle REQUIRES: 377-1579 Conversion Kit for B/B2/B3/C/C2 Series machines		\$10,278 NI
W	546-4504	SNOW BLOWER, SR321, HF XPS 1,015 New 4 blade Impeller design with rotation 90 degr. to auger rotation. Operating/Overall width: 2100mm (85") / 2185mm (85.4") Height incl. chute: 1843mm (72"), Throwing distance 12.2m (40ft) Hydraulics: 120-125 l/min (31-33 G/min) / 200-280bar (2,800-4,100 psi) INCLUDES: hydr. lines& 1/2" quick disconnects, 14 pins electr.harness REQUIRES: High Flow XPS or High Flow hydraulics REQUIRES: Work Tool Harness and 4 button left hand joystick on machine to operate the chute rotation (270 degrees) and chute angle REQUIRES: 377-1579 Conversion Kit for B/B2/B3/C/C2 Series machines		\$10,417 NI
W	546-4522	KIT, SNOW, PERFORMANCE 53 Includes: 2 side cutters, 1 partial impeller/fan cover, 1 chute front plate, 1 chute non metallic liner and fixing materials. FOR USE WITH: ALL above new design snow blowers.		\$382 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SNOW BLOWERS - ORIGINAL DESIGN

NOTE: ALL snow blowers are restricted for sale in the European Union due to local regulations.

	APPLIES TO ALL SERIES								APPLIES TO SPECIFIC SERIES					
	216	226	239	247	252	246	262	277	289	236	242	257	242B3	242D
	216	226	239	247	252	246	262	277	289	236B	242	257	242B3	242D
	232	228	249	267	256	272	287	299		236B2	242B	257B	257B3	259B
										236B3	242B2	257B2	257D	259D
SR117	C	C	C								C	C		
SR118					C	C	C	C	C	C			C	C
SR121				C	C	C	C	C		C			C	C
SR318 XPS		C			C	C	C	C			C	C	C	C
SR321 XPS		C			C	C	C	C			C	C	C	C

C = Compatible

Hydraulic operated direct drive, reversible auger and impeller, and non-binding 180 degree rotating chute and deflector.

NOTE: Guarding the operator against flying objects REQUIRED. If not ordered with machine; Door, Cab, Polycarbonate should be ordered. Please see machine price list for availability.

If no reference numbers appear below there are currently no items available in your region.

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SNOW BUCKETS

For Snow Buckets, see Material Handling Buckets in Bucket section of this price list.

SNOW PLOWS

Availability can be restricted due to snow season.
 Please contact your BCP Work Tools contact.

216	232	242				262	272			
226	236	246	248	252	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

All sizes plows C C C C C C C C C C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	481-3666	SNOW PLOW, 6', SSL	990	\$4,694 NI
		1826mm (72") overall width, Blade height: 31" (800mm) Hydraulic Angling - 30 degrees left or right of center 5 degrees lateral float 1 piece STEEL trip edge with 1 piece BOCE 152mm (6") 4 adjustable springs, 2 heavy duty adjustable skid feet INCLUDES: hydraulic lines with quick disconnects REQUIRES: Standard Flow		
W	481-3667	SNOW PLOW, 7', SSL	1,050	\$4,951 NI
		2134mm (84") overall width, Blade height: 31" (800mm) Hydraulic Angling - 30 degrees left or right of center 5 degrees lateral float 1 piece STEEL trip edge with 1 piece BOCE 152mm (6") 4 adjustable springs, 2 heavy duty adjustable skid feet INCLUDES: hydraulic lines with quick disconnects REQUIRES: Standard Flow		
W	481-3668	SNOW PLOW, 8', SSL	1,105	\$5,208 NI
		2438mm (96") overall width, Blade height: 31" (800mm) Hydraulic Angling - 30 degrees left or right of center 5 degrees lateral float 1 piece STEEL trip edge with 1 piece BOCE 152mm (6") 4 adjustable springs, 2 heavy duty adjustable skid feet INCLUDES: hydraulic lines with quick disconnects REQUIRES: Standard Flow		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SNOW PLOWS (Cont.)

W	481-3669	SNOW PLOW, 9', SSL 1,160 2743mm (108") overall width, Blade height: 31" (800mm) Hydraulic Angling - 30 degrees left or right of center 5 degrees lateral float 1 piece STEEL trip edge with 1 piece BOCE 152mm (6") 4 adjustable springs, 2 heavy duty adjustable skid feet INCLUDES: hydraulic lines with quick disconnects REQUIRES: Standard Flow		\$5,549 NI
W	481-3670	SNOW PLOW, 10', SSL 1,215 3048mm (120") overall width, Blade height: 31" (800mm) Hydraulic Angling - 30 degrees left or right of center 5 degrees lateral float 1 piece STEEL trip edge with a 2 piece BOCE 152mm (6") 4 adjustable springs, 2 heavy duty adjustable skid feet INCLUDES: hydraulic lines with quick disconnects REQUIRES: Standard Flow		\$6,257 NI

SNOW / MULTI V PLOW

A multi functional snow V plow, which can be positioned straight, left or right angled, scooped or V.

	226	232	242	247	252	257	262	277	287	297				
	228	236	239	246	248	249	256	259	268	267	272	279	289	299
1524mm (60")	C	C	C	C	C	C	C	C	C	C	C	C	C	C
2134mm (84")	C	C	C	C	C	C	C	C	C	C	C	C	C	C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	542-7309	SNOW V-PLOW, 5', SSL 641 Hydraulic angling 35 degrees over left hand and right hand side. Straight / Angle width: 1524mm (60") / 1346mm (53") Scoop / V width: 1372 (54") / 1483mm (59"), Blade / Overall height: 737mm (29") / 826mm (33") INCLUDES: 14 pins harness and connecting lines with QDs, 2 steel trip edges with 2 trip springs each, 2 hydraulic cylinders REQUIRES: Standard Flow, Work Tool Harness, Right Hand joystick with thumb roller and Left Hand joystick with 4 buttons.		\$5,833 NI
---	----------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	-------------------

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SNOW / MULTI V PLOW (Cont.)

W	542-7310	SNOW V-PLOW, 7', SSL	941	\$6,667 NI
		Hydraulic angling 35 degrees over left hand and right hand side. Straight / Angle width: 2134mm (84") / 1854mm (73") Scoop / V width: 1847 (73") / 1982mm (78"), Blade / Overall height: 737mm (29") / 826mm (33") INCLUDES: 14 pins harness and connecting lines with QDs, 2 steel trip edges with 2 trip springs each, 2 hydraulic cylinders REQUIRES: Standard Flow, Work Tool Harness, Right Hand joystick with thumb roller and Left Hand joystick with 4 buttons.		

SNOW PUSHES, STRAIGHT

Availability can be restricted due to snow season.
 Please contact your BCP Work Tools contact.

216	232	242				262	272			
226	236	246	248	256	257	267	277	287	297	
228	239	247	249	256	259	268	279	289	299	

All sizes pushes C C C C C C C C C C

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

W	509-3705	SNOW PUSH, 8', RUB.	778	\$2,778 NI
		Incl. 1 piece rubber edge 38mmx152mm (1.5"x 6"), NON trip Width 2.44m (8'), with bolt -on skids on the side Overall Height 897mm (35.3")		
W	479-8115	SNOW PUSH, 8', SSL, RUBBER	1,035	\$3,299 NI
		Width 2.44m (8'), with bolt -on skids on the side 1 piece RUBBER trip edge, height: 119mm (4.7") incl 4 adjustable trip springs, Overall Height 994mm (39")		
W	479-8120	SNOW PUSH, 8', SSL, STEEL	1,080	\$3,549 NI
		Width 2.44m (8'), with bolt -on skids on the side 1 piece STEEL trip edge, height: 119mm (4.7") incl 4 adjustable trip springs, Overall Height 994mm (39")		
W	509-3706	SNOW PUSH, 10', RUB.	866	\$3,299 NI
		Incl. 2 piece rubber edge 38mmx152mm (1.5"x 6"), NON trip Width 3.05m (10'), with bolt-on skids on the side Overall Height 897mm (35.3")		
W	479-8086	SNOW PUSH, 10', SSL, RUBBER	1,150	\$3,889 NI
		Width 3.05m (10'), with bolt-on skids on the side 2 section RUBBER trip edge, height: 119mm (4.7") each with 2 adjustable trip springs, Overall Height 994mm (39")		
W	479-8096	SNOW PUSH, 10', SSL, STEEL	1,200	\$4,222 NI
		Width 3.05m (10'), with bolt-on skids on the side 2 section STEEL trip edge, height: 119mm (4.7") each with 2 adjustable trip springs, Overall Height 994mm (39")		

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SNOW PUSHES, STRAIGHT (Cont.)

W	509-3707	SNOW PUSH, 12', RUB.	952	\$3,813 NI
		Incl. 2 piece rubber edge 38mmx152mm (1.5"x 6"), NON trip Width 3.66m (12'), with bolt-on skids on the side Overall Height 897mm (35.3")		
W	479-8089	SNOW PUSH, 12', SSL, RUBBER	1,345	\$4,625 NI
		Width 3.66m (12'), with bolt-on skids on the side 2 section RUBBER trip edge, height: 119mm (4.7") each with 2 adjustable trip springs, Overall Height 994mm (39")		
W	479-8099	SNOW PUSH, 12', SSL, STEEL	1,400	\$4,889 NI
		Width 3.66m (12'), with bolt-on skids on the side 2 section STEEL trip edge, height: 119mm (4.7") each with 2 adjustable trip springs, Overall Height 994mm (39")		

SNOW STRAIGHT PUSH OPTIONS:

W	481-3675	BACK DRAG, 8', RUBBER	350	\$1,556 NI
W	481-3676	BACK DRAG, 10', RUBBER	425	\$1,854 NI
W	481-3679	BACK DRAG, 12', RUBBER	510	\$2,215 NI
W	481-3680	BACK DRAG, 8', STEEL	390	\$1,611 NI
W	481-3686	BACK DRAG, 10', STEEL	476	\$1,986 NI
W	481-3689	BACK DRAG, 12', STEEL	564	\$2,500 NI

SNOW WINGS

Snow wings with independently controlled wings and angling capability. The snow wings can be configured to suit the needs of any job and continue to adapt to ever changing needs.

SNOW WING Compatibilty for B Series machines and up:

	B & B2 & B3					C & C2			D & D2 & D3							
	232	226				262	287		246	279	272					
	236	252	242	257		246	277	289	226	239	236	257	262	287	297	
	216	247	262	268	259	256	279	299	232	249	242	259	277	289	299	
8'-13'	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++	++
9'-14'	+-	+-	++	+-	++	++	++	++	++	++	++	++	++	++	++	++

++ = Optimal performance

+- = Acceptable performance

<https://www.youtube.com/watch?v=Xx8x0acHeIk&feature=youtu.be>

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

SNOW WINGS (Cont.)

W	572-3142	SNOW WING, 8'-13', SSL 1,750 Hydraulic angling 35 degrees left and right over center snow wing. Overall height: 915mm (36"), 5 degrees lateral float Working width non angled and wings closed: 2445mm (96.3") Overall width non angled closed/open: 2596mm (102.2")/ 4083mm (160.7") Overall width angled closed/open: 2307mm (90.8")/ 3447mm (135.7") INCLUDES: 1 piece steel trip blade incl 2 adjustable trip springs, 2 x hydr. actuator operated 180 degrees rotation end wings incl floating shoes, 14 pins harness and hydr lines incl QDs. REQUIRES: Standard Flow, Optimal required flow 80 l/min (22 US gpm) Work Tool Harness and Deluxe LH Joystick with 4 buttons.	1,750	\$11,944 NI
W	572-3143	SNOW WING, 9'-14', SSL 1,821 Hydraulic angling 35 degrees left and right over center snow wing. Overall height: 915mm (36"), 5 degrees lateral float Working width non angles and wings closed: 2750mm (108.3") Overall width non angled closed/open: 2901mm (114.2")/ 4425mm (174.2") Overall width angled closed/open: 2558mm (100.7")/ 3691mm (145.3") INCLUDES: 1 piece steel trip blade incl 2 adjustable trip springs, 2 x hydr. actuator operated 180 degrees rotation end wings incl floating shoes, 14 pins harness and hydr lines incl QDs. REQUIRES: Standard Flow, Optimal required flow 80 l/min (22 US gpm) Work Tool Harness and Deluxe LH Joystick with 4 buttons.	1,821	\$12,361 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS										Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	--	--	--	--	--	--	--	--	--	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

STUMP GRINDERS

Nomenclature change: SG16 is replacement for SG16B, NO tech. changes
 SG16 stands for standard flow + diameter cutting wheel of approx. 0.6m
 Nomenclature change: SG36 is replacement for SG18B, NO tech. changes
 SG36 stands for high flow + diameter cutting wheel of approx. 0.6m

																287
																289
	226			236			248			257	262			277	297	
	216	242	228	232	239	246	247	268	252	256	259	272	267	279	299	
SG16	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	
SG36 XPS		C	C			C		C		C	C	C		C	C	

C = Compatible

If no reference numbers appear below there are currently no items available in your region.

- W 424-0461 STUMP GRINDER, SG16834 \$8,354 NI**
 SG16 (old SG16B) stands for standard flow +diam.cutting wheel ca. 0.6m
 46" (1175mm) overall width
 18" (457mm) diameter cutting wheel with 32 carbide teeth
 MANUAL adjustable cutting head
 Hydraulic controlled boom swing - 70 degree range of motion
 Electro-hydraulic controlled boom extension 11" (280mm)
 INCLUDES: hydraulic lines with 1/2" quick disconnects, mounting bracket, & 14-pin electrical harness
 REQUIRES: Standard flow hydraulics
 REQUIRES: Left joystick to be WT Deluxe and right joystick to be hydraulic proportional
 REQUIRES: Conversion harness 377-1579 for B/B2/B3/C/C2 series machines
- W 424-0460 STUMP GRINDER, SG36909 \$9,653 NI**
 SG36 (old SG18B) stands for high flow + diam.cutting of wheel ca. 0.6m
 46" (1175mm) overall width
 18" (457mm) diameter cutting wheel with 32 carbide teeth
 Electro-Hydraulic boom swing - 70 degrees range of motion
 Electro-Hydraulic boom extension - 11" (280mm)
 Electro-Hydraulic boom depth - 49 degrees range of motion
 INCLUDES: hydraulic lines with 1/2" quick disconnects, case drain line, 14-pin electrical harness, mounting bracket and hardware
 REQUIRES: High Flow Hydraulics and Control, Work Tool, Electrical.
 REQUIRES: 382-6186 Conversion Kit for D-Series XHPmachines with serial numbers beginning with NLC & SHY
 REQUIRES: 371-3725 Conversion Kit for B/B2/C/C2 Series machines;
 Not required for B3/D Series machines

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS										Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-------------------------------	--	--	--	--	--	--	--	--	--	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

TRENCHERS

Nomenclature change: T109 is replacement for T6B, NO technical changes
 T109 stands for standard flow + trenching depth ca. 0.9m
 Nomenclature change: T112 is replacement for T9B, NO technical changes
 T112 stands for standard flow + trenching depth ca. 1.2m
 Nomenclature change: T315 is replacement for T15B, NO technical change
 T315 stands for high flow + trenching depth ca. 1.5m

																287
																289
	226			236		247	248			257	262			277	297	
	216	242	228	232	239	246	249	268	252	256	259	272	267	279	299	
T109	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	
T112	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	
T315HF/XPS		C	C			C		C		C	C	C		C	C	

Chain selection guide

	Ground conditions / applications				
	Sandy	Loose	Medium	Hard	Rocky
Double Standard	C	C	A	NC	NC
Single Standard	A	C	C	A	NC
50/50 Carbide	NC	A	C	C	A
50/50 Rock-Frost	NC	A	C	C	A
Rock-Frost	NC	NC	A	C	C
Terminator	NC	NC	A	C	C

C= Compatible, A= acceptable performance, NC= Not Compatible
 All trenchers include:
 DIRECT drive unit with one 18" (457mm) spoil auger - right side, hydraulic lines with quick disconnects, mounting bracket and hardware.

If no reference numbers appear below there are currently no items available in your region.

TRENCHERS - T6B

W	261-4806	TRENCHER, T109, MAN. 6" STANDARD 1,012	\$5,417 NI
		T109 (Old T6B) stands for standard flow + trenching depth ca. 0.9m 36" (914mm) Boom, MANUAL side sift, Trench depth: 36" (914mm) with boom angle of 60 degrees Standard chain included, 6" (152mm) cutting width REQUIRES: Standard Flow Hydraulics	

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

TRENCHERS - T6B (Cont.)

W	253-9509	TRENCHER,T109, MANUAL,NO CHAIN 861 T109 (Old T6B) stands for standard flow + trenching depth ca. 0.9m NO CHAIN 36" (914mm) Boom, MANUAL side sift Trench depth: 36" (914mm) with boom angle of 60 degrees REQUIRES: Standard Flow Hydraulics		\$4,514 NI
W	261-8557	TRENCHER,T109, MAN. 8" STD 1,028 T109 (Old T6B) stands for standard flow + trenching depth ca. 0.9m 36" (914mm) Boom, MANUAL side sift, Trench depth: 36" (914mm) with boom angle of 60 degrees Standard chain included, 8" (203mm) cutting width REQUIRES: Standard Flow Hydraulics		\$5,486 NI
W	261-8559	TRENCHER, T109, MAN. 6" COMBO 1,035 T109 (Old T6B) stands for standard flow + trenching depth ca. 0.9m 36" (914mm) Boom, MANUAL side sift, Trench depth: 36" (914mm) with boom angle of 60 degrees Combi chain included, 6" (152mm) cutting width;50/50 Carbide/Cup teeth REQUIRES: Standard Flow Hydraulics		\$5,764 NI
W	261-8561	TRENCHER,T109,MAN 6" ROCKFROST 1,064 T109 (Old T6B) stands for standard flow + trenching depth ca. 0.9m 36" (914mm) Boom, MANUAL side sift, Trench depth: 36" (914mm) with boom angle of 60 degrees Rock/Frost Chain included, 6" (152mm) cutting width REQUIRES: Standard Flow Hydraulics		\$6,528 NI
W	261-8563	TRENCHER,T109,MAN 6" TERMINATOR 1,012 T109 (Old T6B) stands for standard flow + trenching depth ca. 0.9m 36" (914mm) Boom, MANUAL side sift, Trench depth: 36" (914mm) with boom angle of 60 degrees Terminator chain included, 6" (152mm) cutting width REQUIRES: Standard Flow Hydraulics		\$6,667 NI
W	261-4859	TRENCHER,T109,HYD. 6" STANDARD 1,076 T109 (Old T6B) stands for standard flow + trenching depth ca. 0.9m Hydraulic sideshift: 19" (483mm) both left and right over center 36" (914mm) Boom Trench depth: 36" (914mm) with boom angle of 60 degrees Standard chain included, 6" (152mm) cutting width REQUIRES: Standard Flow Hydraulics		\$6,042 NI
W	256-0695	TRENCHER, T109, HYD, NO CHAIN 925 T109 (Old T6B) stands for standard flow + trenching depth ca. 0.9m NO CHAIN Hydraulic sideshift: 19" (483mm) both left and right over center 36" (914mm) Boom Trench depth: 36" (914mm) with boom angle of 60 degrees Standard chain included, 6" (152mm) cutting width REQUIRES: Standard Flow Hydraulics		\$5,139 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

TRENCHERS - T6B (Cont.)

W	261-8558	TRENCHER, T109, HYD. 8" STD 1,092 T109 (Old T6B) stands for standard flow + trenching depth ca. 0.9m Hydraulic sideshift: 19" (483mm) both left and right over center 36" (914mm) Boom Trench depth: 36" (914mm) with boom angle of 60 degrees Standard chain included, 8" (203mm) cutting width REQUIRES: Standard Flow Hydraulics		\$6,139 NI
W	261-8560	TRENCHER, T109, HYD 6" COMBO 1,099 T109 (Old T6B) stands for standard flow + trenching depth ca. 0.9m Hydraulic sideshift: 19" (483mm) both left and right over center 36" (914mm) Boom Trench depth: 36" (914mm) with boom angle of 60 degrees Combi chain included, 6" (152mm) cutting width;50/50 Carbide/Cup teeth REQUIRES: Standard Flow Hydraulics		\$6,389 NI
W	261-8562	TRENCHER, T109, HYD 6" ROCKFROST 1,128 T109 (Old T6B) stands for standard flow + trenching depth ca. 0.9m Hydraulic sideshift: 19" (483mm) both left and right over center 36" (914mm) Boom Trench depth: 36" (914mm) with boom angle of 60 degrees Rock/Frost Chain included, 6" (152mm) cutting width REQUIRES: Standard Flow Hydraulics		\$7,153 NI
W	261-8564	TRENCHER, T109, HYD 6" TERMINATOR 1,076 T109 (Old T6B) stands for standard flow + trenching depth ca. 0.9m Hydraulic sideshift: 19" (483mm) both left and right over center 36" (914mm) Boom Terminator chain included, 6" (152mm) cutting width Rock/Frost Chain included, 6" (152mm) cutting width REQUIRES: Standard Flow Hydraulics		\$7,292 NI

TRENCHERS - T9B

W	233-2346	TRENCHER, T112, MAN. 6" STANDARD 1,076 T112 (Old T9B) stands for standard flow + trenching depth ca. 1.2m 48" (1219mm) Boom, MANUAL side sift, Trench depth: 48" (1219mm) with boom angle of 60 degrees Standard chain included, 6" (152mm) cutting width REQUIRES: Standard Flow Hydraulics		\$5,833 NI
W	208-2700	TRENCHER, T112, MANUAL, NO CHAIN 973 T112 (Old T9B) stands for standard flow + trenching depth ca. 1.2m NO CHAIN 48" (1219mm) Boom, MANUAL side sift, Trench depth: 48" (1219mm) with boom angle of 60 degrees REQUIRES: Standard Flow Hydraulics		\$4,861 NI
W	233-2350	TRENCHER, T112, MAN. 6" COMBO 1,154 T112 (Old T9B) stands for standard flow + trenching depth ca. 1.2m 48" (1219mm) Boom, MANUAL side sift, Trench depth: 48" (1219mm) with boom angle of 60 degrees Combi chain included, 6" (152mm) cutting width;50/50 Carbide/Cup teeth REQUIRES: Standard Flow Hydraulics		\$6,181 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

TRENCHERS - T9B (Cont.)

W	241-4251	TRENCHER, T112, MAN 6" ROCKFROST 1,184 T112 (Old T9B) stands for standard flow + trenching depth ca. 1.2m 48" (1219mm) Boom, MANUAL side sift, Trench depth: 48" (1219mm) with boom angle of 60 degrees Rock/Frost Chain included, 6" (152mm) cutting width REQUIRES: Standard Flow Hydraulics		\$6,944 NI
W	241-4252	TRENCHER, T112, HYD. 6" STANDARD 1,121 T112 (Old T9B) stands for standard flow + trenching depth ca. 1.2m Hydraulic sideshift: 22" (559mm) right of center. 48" (1219mm) Boom, Trench depth: 48" (1219mm) with boom angle of 60 degrees Standard chain included, 6" (152mm) cutting width REQUIRES: Standard Flow Hydraulics		\$6,389 NI
W	208-2708	TRENCHER, T112, HYD, NO CHAIN 987 T112 (Old T9B) stands for standard flow + trenching depth ca. 1.2m NO CHAIN Hydraulic sideshift: 22" (559mm) right of center. 48" (1219mm) Boom, Trench depth: 48" (1219mm) with boom angle of 60 degrees REQUIRES: Standard Flow Hydraulics		\$5,417 NI
W	241-4253	TRENCHER, T112, HYD. 8" STD. 1,186 T112 (Old T9B) stands for standard flow + trenching depth ca. 1.2m Hydraulic sideshift: 22" (559mm) right of center. 48" (1219mm) Boom, Trench depth: 48" (1219mm) with boom angle of 60 degrees Standard chain included, 8" (203mm) cutting width REQUIRES: Standard Flow Hydraulics		\$6,458 NI
W	241-4254	TRENCHER, T112, HYD. 6" COMBO 1,199 T112 (Old T9B) stands for standard flow + trenching depth ca. 1.2m Hydraulic sideshift: 22" (559mm) right of center. 48" (1219mm) Boom, Trench depth: 48" (1219mm) with boom angle of 60 degrees Combi chain included, 6" (152mm) cutting width; 50/50 Carbide/Cup teeth REQUIRES: Standard Flow Hydraulics		\$6,736 NI
W	241-4255	TRENCHER, T112, HYD 6" ROCKFROST 1,229 T112 (Old T9B) stands for standard flow + trenching depth ca. 1.2m Hydraulic sideshift: 22" (559mm) right of center. 48" (1219mm) Boom, Trench depth: 48" (1219mm) with boom angle of 60 degrees Rock/Frost Chain included, 6" (152mm) cutting width REQUIRES: Standard Flow Hydraulics		\$7,500 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

TRENCHERS - T15B HF

W	424-0471	TRENCHER, T315, HF, 6" STD 1,212 T315 (Old T15B) stands for high flow + trenching depth ca. 1.5m 60" (1524mm) Boom, Trench depth: 60" (1520mm) with boom angle of 60 degrees Hydraulic sideshift: 22" (559mm) right of center Standard chain included, 6" (152mm) cutting width INCLUDES: Hydraulic lines with 1/2" quick disconnects, cylinder control valve, & 14-pin electrical harness REQUIRES: High Flow or HF XPS Hydraulics REQUIRES: for B/B2/C/C2 with HF(XPS) conversion kit: 371-3725		\$8,194 NI
W	424-0470	TRENCHER, T315, HF, NO CHAIN 1,055 T315 (Old T15B) stands for high flow + trenching depth ca. 1.5m NO CHAIN 60" (1524mm) Boom, Trench depth: 60" (1520mm) with boom angle of 60 degrees Hydraulic sideshift: 22" (559mm) right of center INCLUDES: Hydraulic lines with 1/2" quick disconnects, cylinder control valve, & 14-pin electrical harness REQUIRES: High Flow or HF XPS Hydraulics REQUIRES: for B/B2/C/C2 with HF(XPS) conversion kit: 371-3725		\$6,944 NI
W	424-0472	TRENCHER, T315, HF, 8" STD 1,287 T315 (Old T15B) stands for high flow + trenching depth ca. 1.5m 60" (1524mm) Boom, Trench depth: 60" (1520mm) with boom angle of 60 degrees Hydraulic sideshift: 22" (559mm) right of center Standard chain included, 8" (203mm) cutting width INCLUDES: Hydraulic lines with 1/2" quick disconnects, cylinder control valve, & 14-pin electrical harness REQUIRES: High Flow or HF XPS Hydraulics REQUIRES: for B/B2/C/C2 with HF(XPS) conversion kit: 371-3725		\$8,333 NI
W	424-0473	TRENCHER, T315, HF, 6" COMBO 1,301 T315 (Old T15B) stands for high flow + trenching depth ca. 1.5m 60" (1524mm) Boom, Trench depth: 60" (1520mm) with boom angle of 60 degrees Hydraulic sideshift: 22" (559mm) right of center Combi chain included, 6" (152mm) cutting width;50/50 Carbide/Cup teeth INCLUDES: Hydraulic lines with 1/2" quick disconnects, cylinder control valve, & 14-pin electrical harness REQUIRES: High Flow or HF XPS Hydraulics REQUIRES: for B/B2/C/C2 with HF(XPS) conversion kit: 371-3725		\$8,750 NI

TRENCHERS - OPTIONS

W	264-5714	CRUMBER ARM, T109 45 REQUIRES: 264-7597 or 264-7598 SHOE, CRUMBER ARM FOR USE WITH: T109 or old A6B		\$347 NI
W	264-7601	CRUMBER ARM, T112 49 REQUIRES: 264-7597 or 264-7598 SHOE, CRUMBER ARM FOR USE WITH: T112 or old A9B		\$382 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

TRENCHERS - OPTIONS (Cont.)

W	264-7602	CRUMBER ARM, T315 54 REQUIRES: 264-7597 or 264-7598 SHOE, CRUMBER ARM FOR USE WITH: T315 or old A15B		\$417 NI
W	264-7597	SHOE, CRUMBER ARM 6" - 8" 9 FOR USE WITH: Chains 6" (152mm) or 8" (202mm) wide		\$83 NI
W	264-7598	SHOE, CRUMBER ARM 10" - 12" 15 FOR USE WITH: Chains 10" (254mm) or 12" (305mm) wide		\$104 NI

TRENCHERS - CHAINS

W	259-0312	CHAIN, T109, 6" STANDARD 131 For T109 (old T6B), trench width 152mm (6"), incl 30 standard teeth		\$903 NI
W	258-8644	CHAIN, T109, 8" STANDARD 167 For T109 (old T6B), trench width 203mm (8"), incl 42 standard teeth		\$972 NI
W	261-4860	CHAIN, T109, 6" COMBO 174 For T109 (old T6B), trench width 152mm (6"), incl 18 standard + 10 carbide teeth		\$1,250 NI
W	261-4805	CHAIN, T109, 6" ROCKFROST 203 For T109 (old T6B), trench width 152mm (6"), incl 36 bits ("picks")		\$2,014 NI
W	243-6349	CHAIN, T109, 6" TERMINATOR 151 For T109 (old T6B), trench width 152mm (6"), incl 30 carbide teeth		\$2,153 NI
W	189-5956	CHAIN, T112, 6" STANDARD 134 For T112 (old T9B), trench width 152mm (6"), incl 18 standard teeth		\$972 NI
W	222-7916	CHAIN, T112, 8" STANDARD 200 For T112 (old T9B), trench width 203mm (8"), incl 50 standard teeth		\$1,042 NI
W	222-7742	CHAIN, T112, 6" COMBO 213 For T112 (old T9B), trench width 152mm (6"), incl 24 standard + 10 carbide teeth		\$1,319 NI
W	222-7743	CHAIN, T112, 6" ROCKFROST 241 For T112 (old T9B), trench width 152mm (6"), incl 42 bits ("picks")		\$2,083 NI
W	189-5957	CHAIN, T315, 6" STANDARD 156 For T315 (old T15B), trench width 152mm (6"), incl 21 standard teeth		\$1,250 NI
W	222-8523	CHAIN, T315, 8" STANDARD 232 For T315 (old T15B), trench width 203mm (8"), incl 58 standard teeth		\$1,389 NI
W	222-7747	CHAIN, T315, 6" COMBO 246 For T315 (old T15B), trench width 152mm (6"), incl 26 standard + 28 carbide teeth		\$1,806 NI

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	------------------------	--------------------	-------------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)***TRENCHERS - CHAINS (Cont.)***

Available through Parts only - NO BRIDGE ORDERS
Replacement Tooth Groups (to be fit on a chain)
Boom size 36" 48" 60"

		914mm	1219mm	1524mm
Chain Without Teeth		263-3419	166-0808	179-6316
152mm (6") Single Standard		263-3420	166-0821	189-0702
203mm (8") Single Standard		263-3421	194-4681	193-5727
254mm (10") Single Standard		263-3426	194-4682	193-5728
305mm (12") Double Standard		263-3427	195-3900	193-5729
152mm (6") 50/50 Carbide		263-3422	208-2781	208-2791
203mm (8") 50/50 Carbide		263-3423	208-2784	208-2794
152mm (6") 50/50 Rock-Frost		263-3424	208-2780	208-2790
203mm (8") 50/50 Rock-Frost			208-2783	208-2793
152mm (6") Rock-Frost			208-2782	208-2792

CATERPILLAR MACHINE PRICE LIST

WT-SSL

USE	REF NO.	CATERPILLAR WORK TOOLS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------------	-----------------	----------------------

216 THRU 299 CTL, MTL, AND SSL LOADERS (CONT.)

DEMO CONTROL KIT

W	296-0582	KIT, DEMO CONTROL HARNESS 2 Enables Caterpillar dealers to quickly and easily demonstrate an electronically controlled work tool on B/B2/B3 SF/C/C2 machines that are not equipped with Control, Work Tool, Electrical.		\$285 NI
W	423-8296	KIT, DEMO CONTROL HARNESS 2 Enables Caterpillar dealers to quickly and easily demonstrate an electronically controlled work tool on B3 HF & D Series machines that are not equipped with Control, Work Tool, Electrical.		\$285 NI

Caterpillar does not warrant, service, or assume responsibility for AEM work tools. All orders, pricing, and other communications must be directed to the manufacturer.

SSL Sectional Snow-Pusher - SSL Interface

All Arctic Sectional Snow-Pusher attachments above are available with following coupler interfaces: Fusion, IT, and SSL
 Contact: Michelle Vaughn
 Email: mvaughn@arcticsnowandice.com
 Web: www.sectionalsnowpusher.com