

CATERPILLAR MACHINE PRICE LIST

**246D**

246D SKID STEER LOADER SANFORD, NC, USA	Ship Weight lbs	LIST PRICE AT DEALER
--------------------------------------------	--------------------	-------------------------

Standard Equipment:

**POWERTRAIN**

- Cat C3.3B diesel engine
- Gross horsepower per SAE J1349  
74.3 hp (55.4 kW) @ 2400 RPM
- EPA tier 4f and EU stage IIIB  
certified with aftertreatment
- Electric fuel priming pump
- Glow plugs starting aid
- Liquid cooled, direct injection
- Air cleaner, dual element, radial seal
- S-O-S sampling valve, hydraulic oil
- Filter, cartridge type, hydraulic
- Filters, cartridge type, fuel  
and water separator
- Radiator / hydraulic oil  
cooler (side-by-side)
- Spring applied, hydraulically released,  
parking brakes
- Hydrostatic transmission
- Four wheel chain drive

**HYDRAULICS**

- Standard flow auxiliary hydraulics with  
continuous flow

**CONTROLS:**

- Electro/hydraulic implement control
- Electro/hydraulic hydrostatic  
transmission control

**ELECTRICAL**

- 12 volt electrical system
- 80 ampere alternator
- Ignition key start/stop/aux switch
- Lights:
  - Gauge backlighting
  - Two rear tail lights
  - Dome light
- Backup alarm
- Electrical outlet, beacon

**OPERATOR ENVIRONMENT**

- Operator warning system indicators:
  - Air filter restriction
  - Alternator Output
  - Armrest raised/operator out of seat
  - Engine coolant temperature
  - Engine oil pressure
  - Glow plug activation
  - Hydraulic filter restriction
  - Hydraulic oil temperature
  - Park brake engages
  - Engine emission system

- Gauges: fuel level and hour meter
- Storage compartment with netting
- Ergonomic contoured armrest
- Adjustable joystick controls
- Control interlock system, when operator  
leaves seat or armrest raised:
  - Hydraulic system disables
  - Hydrostatic transmission disables
  - Parking brake engages
- ROPS cab, open, tilt up
- Anti-theft security system w/6-button  
keypad
- FOPS, Level I
- Top and rear Windows
- Floormat
- Interior rear view mirror
- 12V Electric socket
- Horn
- Hand (dial) throttle, electronic

**FRAMES**

- Lift linkage, radial path
- Chassis, one piece welded
- Machine tie down points (4)
- Belly pan cleanout
- Support, lift arm
- Rear bumper, welded

**OTHER STANDARD EQUIPMENT**

- Engine enclosure - lockable
- Extended life antifreeze (-37C, -34F)
- Coupler, mechanical
- Hydraulic oil level sight gauge
- Radiator coolant level sight gauge
- Radiator expansion bottle
- Cat tough guard hose
- Heavy duty flat faced quick disconnects  
with integrated pressure release
- Split D-ring to route work tool hoses  
along side of left lift arm
- Variable speed hydraulic cooling fan  
Per SAE J818-2007 and EN 474-3:2006 and  
ISO 14397-1:2007
- Rated operating capacity:  
-975 kg (2150 lb)

CATERPILLAR MACHINE PRICE LIST

**246D**

246D SKID STEER LOADER SANFORD, NC, USA	Ship Weight lbs	LIST PRICE AT DEALER
--------------------------------------------	--------------------	-------------------------

**Lane 2 is reserved for the Base Order Management Program  
Please use Lane 2 when placing orders that are part of the Base Order  
Management program**

<b>570-1796</b>	<b>246D SSL DCA1A</b> . . . . . 0	<b>\$48,900</b>
	LANE 1 - AVAILABLE FROM SANFORD PDC	
	LANE 2 - AVAILABLE FROM SANFORD FACTORY USING PRIORITY CODE L2	
	LANE 3 - AVAILABLE FROM SANFORD FACTORY USING PRIORITY CODE L2	

- INCLUDES:
- 345-5246 246D SSL TIER 4 FINAL HRC
  - 421-0340 CONVERSION ARRANGEMENT
  - 563-1163 CERTIFICATION ARR, P65
  - 435-8955 PACKAGE, PERFORMANCE, (H2)
  - 485-0411 CONTROL, ISO, PROP
  - 345-4923 ONE SPEED
  - 345-6157 ROPS, OPEN (C1)
  - 345-6349 SEAT,AIR SUSPENSION,VINYL,HEAT
  - 416-9265 DISPLAY, ADVANCED, LCD, CAMERA
  - 345-4910 QUICK COUPLER, MANUAL
  - 258-4095 SEAT BELT, 2"
  - 486-6957 FAN, COOLING, DEMAND
  - 481-3908 BATTERY, XTRA HVY DUTY, DISC
  - 495-1672 LIGHTS, HALOGEN

NOTE: Please refer to the Lane 1 section to complete your order.

<b>522-7469</b>	<b>246D SSL DCA2</b> . . . . . 0	<b>\$57,910</b>
	LANE 1 - AVAILABLE FROM SANFORD PDC	

- INCLUDES:
- 345-5246 246D SSL TIER 4 FINAL HRC
  - 421-0340 CONVERSION ARRANGEMENT
  - 563-1163 CERTIFICATION ARR, P65
  - 435-8955 PACKAGE, PERFORMANCE, (H2)
  - 485-0412 CONTROL, ISO, PROP, WT
  - 345-4927 TWO SPEED
  - 345-4919 ROPS, ENCLOSED WITH A/C (C3)
  - 345-6359 SEAT,AIR SUSPENSION,CLOTH,HEAT
  - 345-6240 DOOR, CAB, GLASS
  - 465-3706 DISPLAY, ADVANCED, LCD
  - 515-8590 QUICK COUPLER, HYDRAULIC
  - 345-6175 RADIO READY
  - 258-4095 SEAT BELT, 2"
  - 486-6957 FAN, COOLING, DEMAND
  - 481-3908 BATTERY,XTRA HVY DUTY, DISC
  - 345-5148 COUNTERWEIGHT,MACHINE,EXTERNAL
  - 345-3556 HEATER, ENGINE COOLANT, 120V
  - 495-1672 LIGHTS, HALOGEN

NOTE: Please refer to the Lane 1 section to complete your order.

CATERPILLAR MACHINE PRICE LIST

**246D**

246D SKID STEER LOADER SANFORD, NC, USA	Ship Weight lbs	LIST PRICE AT DEALER
--------------------------------------------	--------------------	-------------------------

<b>522-7470</b>	<b>246D SSL DCA3</b> ..... 0	<b>\$62,700</b>
	LANE 1 - AVAILABLE FROM SANFORD PDC	

INCLUDES:

- 345-5246 246D SSL TIER 4 FINAL HRC
- 421-0340 CONVERSION ARRANGEMENT
- 563-1163 CERTIFICATION ARR, P65
- 345-5447 PACKAGE, PERFORMANCE, (H3)
- 485-0415 CONTROL, ISO, PROP, WT
- 345-4929 TWO SPEED WITH RIDE CONTROL
- 345-4919 ROPS, ENCLOSED WITH A/C (C3)
- 345-6359 SEAT,AIR SUSPENSION,CLOTH,HEAT
- 345-6260 DOOR, CAB, POLYCARBONATE
- 465-3706 DISPLAY, ADVANCED, LCD
- 515-8590 QUICK COUPLER, HYDRAULIC
- 345-6175 RADIO READY
- 258-4095 SEAT BELT, 2"
- 486-6957 FAN, COOLING, DEMAND
- 481-3908 BATTERY,XTRA HVY DUTY, DISC
- 345-5148 COUNTERWEIGHT,MACHINE,EXTERNAL
- 345-3556 HEATER, ENGINE COOLANT, 120V
- 495-1672 LIGHTS, HALOGEN

NOTE: Please refer to the Lane 1 section to complete your order.

<b>345-5246</b>	<b>246D SSL TIER 4 FINAL HRC</b> ..... 0	<b>\$45,070</b>
	LANE 2 - AVAILABLE FROM SANFORD FACTORY	
	LANE 3 - AVAILABLE FROM SANFORD FACTORY	
	Available for AM-N, Europe, Turkey, Israel, Puerto Rico & South Korea	

<b>OP-2730</b>	<b>246D MISC MATERIAL SANFORD</b> ..... 0	<b>NC</b>
	ONLY AVAILABLE FROM WACO PARTS SERVICE	
	Use this top level reference number only when ordering KITS in CMOPS to be transferred via the bridge to ANTARES Parts Ordering.	

Work Tools are sourced via Caterpillar Parts Distribution system. Skid Steer Loader and Work Tools order REQUIRE individual CMOPS order entries. Zeebrugge Distribution Center (ZDC) orders do NOT require individual CMOPS order entries and may include both the machine and work tool orders.

Refer to WT\_SSL price list to order Work Tools.

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	--------	-----------------	----------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS**

(MUST CHOOSE ONE FROM EACH CATEGORY)

**LANE SELECTION**

YOU MUST SELECT THIS REFERENCE WHEN ORDERING FROM THE PDC.

OP-9001	LANE 1 ORDER	0	NC
---------	--------------	---	----

**WARNING DECALS**

L	388-8146	INSTRUCTIONS, ANSI, USA . . . . .	0	NC
		This package includes picto decals as required for USA.		
L	388-8040	INSTRUCTIONS, ISO . . . . .	0	NC
		This package includes picto decals as required for all countries except USA.		

**FILM GROUP RIDE CONTROL (FOR USE WITH DCA3 ONLY)**

L	422-3445	FILM, RIDE CONTROL, ANSI . . . . .	0	NC
L	422-3446	FILM, RIDE CONTROL, ISO . . . . .	0	NC

**PRODUCT LINK**

L	441-4818	PRODUCT LINK, CELLULAR PL240 . . . . .	0	NC
		Product Link Basic series PL240 offers expanded coverage including 3G UMTS and HSPA+ as well as 2G GSM and GPRS cellular networks to transmit hour and location informatin for viewing in Product Link's remote monitorin web interface. The data is updated up to 4 times per day while the engine is running. ONLY FOR USE WITH: US Dealers		
L	515-3153	PRODUCT LINK, CELLULAR PL240 . . . . .	0	NC
		Product Link Basic series PL240 uses cellular networks to transmit hour and location information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent data transmission. ONLY FOR USE WITH: Canada		

**TIRES**

P	185-8667	TIRES, 12/16.5 CAT 10PR . . . . .	480	\$408
		Caterpillar Tire - Premium conventional heavy duty tire provides excellent traction in a variety of conditions. Deepest tread available (26/32") (21mm) results in long service life. Extra heavy sidewall construction protects against abrasion, tears and impact damage. Directional chevron tread pattern, bias ply. Includes valve stem protection. 72" (1830mm) width		

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	--------	-----------------	----------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS (CONT.)**

**SERVICE INSTRUCTIONS**

421-8926	<b>SERIALIZED TECHNICAL MEDIA KIT</b> . . . . .	0		<b>NC</b>
	The technical media kit will include the Operations & Maintenance Manual (OMM) and other media specified on the Factory Notification List required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary. Any additional media or translations not included in the kit, should be ordered through publications.cat.com			

**PACKING**

OP-1176	<b>CAROLINA CDC -- AVAILABILITY</b> . . . . .	0		<b>\$1 NET</b>
---------	-----------------------------------------------	---	--	----------------

**PROTECTION**

OP-2266	<b>SHIPPING/STORAGE PROTECTION</b> . . . . .	0		<b>\$203 NET</b>
	Provides protective application of Fluid Film TM for protection while shipping and for extended storage periods. If desired, this product can be power washed with warm soapy water prior to shipment to the customer.			

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**LANE SELECTION**

OP-9002	LANE 2 ORDER . . . . .	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER . . . . .	0	NC

**REGIONAL PACKAGES**

**CONVERSION ARRANGEMENTS**

L	421-0340	CONVERSION ARRANGEMENT . . . . .	0	NC
---	----------	----------------------------------	---	----

**CERTIFICATION ARRANGEMENTS/YEAR OF MANUFACTURE**

L	563-1163	CERTIFICATION ARR, P65 . . . . .	0	NC
		REQUIRED for US		

**WARNING DECALS**

L	388-8146	INSTRUCTIONS, ANSI, USA . . . . .	0	NC
		This package includes picto decals as required for USA.		

**PERFORMANCE PACKAGES**

**HYDRAULIC PERFORMANCE PACKAGES**

L	345-5219	PACKAGE, PERFORMANCE, (H1) . . . . .	0	NC
		All of the following are included in this package: Standard Flow - 23 gpm (87 lpm) Self Level, None Hydraulic Controls - Standard Flow (Must select one below)		
L	435-8955	PACKAGE, PERFORMANCE (H2) . . . . .	0	\$885
		All of the following are included in this package: Standard Flow - 23 gpm (87 lpm) Dual Self Level Hydraulic Controls - Standard Flow (Must select one below)		
L	345-5447	PACKAGE, PERFORMANCE, (H3) . . . . .	0	\$4,435
		All of the following are included in this package: High Flow XPS - 32 gpm (120 lpm) Dual Self Level Hydraulic Controls - High Flow (Must select one below)		

**HYDRAULIC CONTROLS**

**Standard Flow (FOR USE WITH H1 & H2)**

L	485-0410	CONTROL, ISO, ON/OFF . . . . .	0	\$222
		Cannot be used with H3. Provides ISO joystick controls and electronic foot throttle pedal with decel pedal functionality		
L	485-0411	CONTROL, ISO, PROP . . . . .	0	\$426
		Cannot be used with H3. Provides ISO joystick controls (4 button left hand joystick) and electronic foot throttle pedal with decel pedal functionality		

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**PERFORMANCE PACKAGES (CONT.)**

**HYDRAULIC CONTROLS (Cont.)**

L	485-0412	<b>CONTROL, ISO, PROP, WT</b> ..... 0 Cannot be used with H3. Provides ISO joystick controls (4 button left hand joystick) and electronic foot throttle pedal with decel pedal functionality. Also includes 14 pin Work Tool electrical harness.		\$760
L	485-0413	<b>CONTROL, HAND-FOOT, PROP</b> ..... 0 Cannot be used with H3. Provides (single axis) Hand drive joystick controls (4 button left hand joystick) and Foot pedal implement controls		\$840
L	485-0414	<b>CONTROL, HAND-FOOT, PROP, WT</b> ..... 0 Cannot be used with H3. Provides (single axis) Hand drive joystick controls and Foot pedal implement controls (4 button left hand joystick). Also includes 14 pin Work Tool electrical harness.		\$1,165

**High Flow (FOR USE WITH H3 ONLY)**

L	485-0415	<b>CONTROL, ISO, PROP, WT</b> ..... 0 For use with H3 Only. Provides ISO joystick controls (4 button left hand joystick - Thumb roller with 2 button right hand joystick) and 14 pin Work Tool electrical harness. Also includes electronic foot throttle pedal with decel pedal functionality.		\$865
L	485-0416	<b>CONTROL, HAND-FOOT, PROP, WT</b> ..... 0 For use with H3 Only. Provides (single axis) Hand drive joystick controls (4 button left hand joystick-Thumb roller with 2 button right hand joystick) and Foot pedal implement controls. Also includes 14 pin Work Tool electrical harness.		\$1,280

**POWERTRAIN**

L	345-4923	<b>ONE SPEED</b> ..... 0		NC
L	388-7932	<b>ONE SPEED WITH RIDE CONTROL</b> ..... 0		\$1,025
L	345-4927	<b>TWO SPEED</b> ..... 0		\$2,020
L	345-4929	<b>TWO SPEED WITH RIDE CONTROL</b> ..... 0		\$3,045

**FILM GROUP RIDE CONTROL**

L	422-3445	<b>FILM, RIDE CONTROL, ANSI</b> ..... 0 REQUIRED WHEN SELECTING RIDE CONTROL		NC
---	----------	---------------------------------------------------------------------------------	--	----

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**FEATURE PACKAGES**

**COMFORT PACKAGES**

L	345-6155	ROPS, OPEN (C0) . . . . .	0	NC
		All of the following are included in this package: Seat, Static, Vinyl Cab Mounted Controls, Adjustable (hand tool required) Headliner, None		
L	345-6157	ROPS, OPEN (C1) . . . . .	26	\$429
		All of the following are included in this package: Deluxe Headliner & rear post trim covers Cup Holder Seat (Must select one below)		
L	345-4915	ROPS, ENCLOSED WITH HEAT (C2) . . . . .	101	\$2,790
		All of the following are included in this package: Deluxe Headliner & post trim covers Cup Holder Side Windows Heater and Defroster Seat (Must select one below) Door (Must select one below)		
L	345-4919	ROPS, ENCLOSED WITH A/C (C3) . . . . .	210	\$4,800
		All of the following are included in this package: Deluxe Headliner & post trim covers Cup Holder Side Windows Air Conditioner including Heater and Defroster Seat (Must select one below) Door (Must select one below)		

**SEAT**

Must select ONE if a C1, C2 or C3 cab package was selected above.

L	345-6329	SEAT, SUSPENSION, VINYL . . . . .	0	\$352
		Includes: Cab Mounted Controls, Adjustable (hand tool required) For Use With: C1, C2 and C3 Cab Package		
L	345-6349	SEAT,AIR SUSPENSION,VINYL,HEAT . . . . .	0	\$765
		High back heated seat with recline, lumbar support, and Fully Adjustable Seat Mounted Controls. For Use With: C1, C2 and C3 Cab Package		
L	345-6359	SEAT,AIR SUSPENSION,CLOTH,HEAT . . . . .	0	\$790
		High back heated seat with recline, lumbar support, and Fully Adjustable Seat Mounted Controls. For Use With: C2 and C3 Cab Package		

**DOOR**

Must select ONE if an Enclosed ROPS was selected above.

P	345-6240	DOOR, CAB, GLASS . . . . .	0	\$106
P	345-6260	DOOR, CAB, POLYCARBONATE . . . . .	0	\$210



CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**FEATURE PACKAGES (CONT.)**

**RADIO**

Bluetooth radio technology enables the use of a hands free function such as listening to music and making phone calls.

Authorization varies by country, please contact your Cat marketing representative with questions or click on the link below:  
<https://dealer.cat.com/en/products/technology.html>

Selection of ONE required for C2 or C3 Comfort Package

L	345-6175	<b>RADIO READY</b> . . . . . 0 Provides Speakers, Wiring, Radio Box, Antenna & Cable, and hardware required to install a single DIN radio.		\$151
L	345-6180	<b>RADIO, AM/FM, BLUETOOTH</b> . . . . . 0 Provides factory installed radio: Includes Bluetooth interface, microphone, and auxiliary inputs (USB port and aux input jack) to connect external audio devices.		\$499

**MACHINE DISPLAY**

L	416-9265	<b>DISPLAY, ADVANCED, LCD, CAMERA</b> . . . . . 0 Includes: Full color 5 in. LCD screen with digital gauge display. Provides Creep control, Hystat response adjustment, Implement response adjustment, Fuel gauge, Hydraulic temperature gauge, Engine coolant gauge, Tachometer, Language selection and Advanced multi-operator Anti-theft Security System and Monitoring. Also provides USB charging port. Note: Rear camera installed. Anti-theft Security System feature will ship from factory installed but disabled.		\$1,120
---	----------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	---------

**STARTERS, BATTERIES, & ALTERNATORS**

**BATTERIES**

L	492-6088	<b>BATTERY, HEAVY DUTY, 850 CCA</b> . . . . . 0		NC
L	480-3912	<b>BATTERY, HEAVY DUTY, DISC</b> . . . . . 0 850 CCA with Battery Disconnect Switch		\$123
L	361-6372	<b>BATTERY, XTRA HVY DUTY 1000 CCA</b> . . . . . 0 Recommended for cold weather starting.		\$77
L	481-3908	<b>BATTERY, XTRA HVY DUTY, DISC</b> . . . . . 0 1000 CCA with Battery Disconnect Switch Recommended for cold weather starting.		\$201

**OPERATOR ENVIRONMENT**

**LIGHTS**

L	495-1672	<b>LIGHTS, HALOGEN</b> . . . . . 0 Two (2) forward facing adjustable halogen work lights (cab mounted) and two (2) rear facing halogen work lights (frame mounted).		NC
L	495-1671	<b>LIGHTS, LED</b> . . . . . 0 Two (2) forward facing adjustable LED work lights (cab mounted) and two (2) rear facing LED work lights (frame mounted). LED lighting advantages vs halogens: brighter work site illumination, cooler, more resistant to vibration and longer life.		\$274

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**OPERATOR ENVIRONMENT (CONT.)**

**SEAT BELTS**

L	258-4095	SEAT BELT, 2" . . . . .	0	NC
L	258-4096	SEAT BELT, 3" . . . . . Required in California.	0	\$139

**TECHNOLOGY PRODUCTS**

**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	441-4818	PRODUCT LINK, CELLULAR PL240 . . . . . Product Link Basic series PL240 uses cellular networks to transmit hour and location information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent data transmission.	0	NC
L	441-4819	PRODUCT LINK, CELLULAR PL641 . . . . . Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data.	0	\$590 NET

**COOLING**

**COOLING FAN**

L	486-6957	FAN, COOLING, DEMAND . . . . . Provides variable speed hydraulic cooling fan. Sensors monitor machine cooling requirements to modulate the fan speed providing "on demand" cooling.	0	NC
L	435-9224	FAN, COOLING, DEMAND, REVERSING . . . . . Reversing Fan provides automatic and manual purge modes to assist in removing material from the rear door intake screen. Provides both Demand Fan and Reversing Fan functionality.	0	\$825

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**TIRES, RIMS, AND WHEELS**

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice. However, if the tire type cannot be supplied we will contact the dealer to propose alternatives. The dealer needs to choose between an alternative tire or a "rims only" option (where available) within 72 hours. If no response is provided by the deadline, the order will default to the alternative tire and will be changed at that point. As a consequence of a possible tire change, the total machine price will be decreased or increased depending on the price of the new tire.

**1676mm (66") Width**

P	252-0347	<b>TIRES, 12X16.5 CAT 14PR XD</b> . . . . . 597 Caterpillar;XD;Tread Depth=35mm (44/32");1676mm (66") wide Provides very deep tread, ultra heavy sidewalls and extra large rim guards. Ideal for concrete & demolition work, quarries and asphalt recycling. Tread depth is 40% deeper than CAT Premium Conventional Tires. The XD tire features a special tread compound for long wear and durability. Includes valve stem protection.		<b>\$1,200</b>
P	165-4903	<b>TIRES, 12/16.5 GA 10PR</b> . . . . . 515 Galaxy;Bias;"Beefy Baby";1676mm (66") wide Designed with extra side wall strength to protect against punctures and abuse. Extra wide lug bar and deep tread give good traction in soft conditions. Includes valve stem protection.		<b>\$695</b>
P	185-8666	<b>TIRES, 12/16.5 CAT 10PR</b> . . . . . 480 Caterpillar;Bias;Directional chevron tread pattern; Tread Depth=21mm (26/32") 1676mm (66") wide Premium conventional heavy duty tire provides excellent traction in a variety of conditions. Deepest tread available results in long service life. Extra heavy sidewall construction protects against abrasion, tears and impact damage. Includes valve stem protection.		<b>\$408</b>

**1830mm (72") Width**

P	252-0377	<b>TIRES, 33X6X11 CAT FLEX SOLID</b> . . . . . 1,100 Caterpillar Flexport;Extreme Duty;Directional chevron tread pattern; Tread Depth=58mm (75/32");1830mm (72") wide The Flexport design incorporates a series of holes molded through the outer ring of the sidewall. The result is a stable and more cushioned ride while maintaining the benefits of a solid tire. Extra large lugs and deep tread depth mean excellent traction on improved and unimproved surfaces. The rubber tire and steel rim are a one-piece bonded assembly, and replaced as a single unit. No specialized tire service is ever required.		<b>\$2,855</b>
P	252-0346	<b>TIRES, 12X16.5 CAT 14PR XD</b> . . . . . 597 Caterpillar;XD;Tread Depth=35mm (44/32");1830mm (72") wide Provides very deep tread, ultra heavy sidewalls and extra large rim guards. Ideal for concrete & demolition work, quarries and asphalt recycling. Tread depth is 40% deeper than CAT Premium Conventional Tires. The XD tire features a special tread compound for long wear and durability. Includes valve stem protection.		<b>\$1,200</b>

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**TIRES, RIMS, AND WHEELS (CONT.)**

**1830mm (72") Width (Cont.)**

P	165-4898	TIRES, 12/16.5 GA 10PR . . . . .	515	\$695
		Galaxy;Bias;"Beefy Baby";1830mm (72") wide Designed with extra side wall strength to protect against punctures and abuse. Extra wide lug bar and deep tread give good traction in soft conditions. Includes valve stem protection.		
P	185-8667	TIRES, 12/16.5 CAT 10PR . . . . .	480	\$408
		Caterpillar;Bias;Directional chevron tread pattern; Tread Depth=21mm (26/32") 1830mm (72") wide Premium conventional heavy duty tire provides excellent traction in a variety of conditions. Deepest tread available results in long service life. Extra heavy sidewall construction protects against abrasion, tears and impact damage. Includes valve stem protection.		

**QUICK COUPLERS**

L	345-4910	QUICK COUPLER, MANUAL . . . . .	0	NC
L	515-8590	QUICK COUPLER, HYDRAULIC . . . . .	0	\$975

CATERPILLAR MACHINE PRICE LIST

**246D**

---

USE	REF NO.	<b>LANE 2 / 3 MANDATORY</b>	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-----------------------------	--------------------	-------------------------

---

**INSTRUCTIONS**

***SERVICE INSTRUCTIONS***

<b>421-8926</b>	<b>SERIALIZED TECHNICAL MEDIA KIT . . . . . 0</b>	<b>NC</b>
-----------------	---------------------------------------------------	-----------

The technical media kit will include the Operations & Maintenance Manual (OMM) and other media specified on the Factory Notification List required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary.

Any additional media or translations not included in the kit, should be ordered through [publications.cat.com](http://publications.cat.com)

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**SPECIAL ARRANGEMENTS**

C	OP-0528	<b>PAINT, CUSTOM</b> . . . . . 0		<b>\$1,825 NET</b>
---	---------	----------------------------------	--	--------------------

FOR USE IN LANE 3 ONLY  
 Paint specification (RAL #) required. Advise via MSO notes. Custom paint order provides a SINGLE COLOR, non-metallic, high gloss custom finish. Once a custom paint order is placed, it may not be cancelled. Custom paint extends availability from what is published. Contact the factory for current availability information.

Note 1: Florescent colors and matte finishes are not available.  
 Note 2: Some components will NOT receive the custom paint color. The engine and items not externally visible will be painted yellow. CTLs with the optional steel track undercarriage will be provided with a black track. Cylinders, cab, coupler, radiator grill and the MTL undercarriage will be painted black.

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**ELECTRICAL**

L	309-1325	<b>ROTATING BEACON</b> . . . . . 0 Magnetic base, mounted to top of cab. Operates when key switch is in "On" position.		\$212
---	----------	---------------------------------------------------------------------------------------------------------------------------	--	-------

**OTHER ATTACHMENTS**

L	345-5234	<b>RETURN TO DIG/WRKTL POSITIONER</b> . . . . . 0 Return to Dig automatically lowers lift arms and returns work tool to preset angle. Work Tool positioner automatically returns work tool to present angle. Requires H2 or H3 performance package		\$282
L	345-5148	<b>COUNTERWEIGHT, MACHINE, EXTERNAL</b> . . . . . 0 Includes external weights bolted to the frame tower. Suggested for applications where additional rated operating capacity (ROC) is needed. Machine ROC increased by 250 lbs (113 kg).		\$1,010
L	345-3556	<b>HEATER, ENGINE COOLANT, 120V</b> . . . . . 0 120 Volt - For additional cold weather startability.		\$191
L	457-1215	<b>LIFTING EYES, FOUR POINT</b> . . . . . 0 Included in Conversion Arrangements: EU & Rooding CANNOT BE USED WITH: TANK, WATER		\$188
L	563-7518	<b>MOUNTING, FIRE EXTINGUISHER</b> . . . . . 0 Provides in-cab mounting bracket that can accommodate up to a 5 lb. fire extinguisher.		\$196

**WORK TOOLS**

To view and order all available Work Tool Selections refer to WT-SSL or WT-HAMR price lists.  
NOTE: Work Tools, except Hammers, are sourced via Caterpillar parts distribution system.  
CMOPS orders for Skid Steel Loaders and Work Tools MUST be ordered separately.

**FLUIDS**

L	418-9011	<b>OIL, HYDRAULIC, COLD OPERATION</b> . . . . . 0 Recommended for use in hydraulic system where ambient temperatures are below 32 F (0 C).		\$650
---	----------	-----------------------------------------------------------------------------------------------------------------------------------------------	--	-------

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS**

*Available Through Parts Distribution.*

- 345-6070 KIT, FOPS, LEVEL 2**  
Falling Object Protective Structure level 2. Provides additional overhead protection. Recommended for use in demolition applications. Not compatible with the roof mounted Auxiliary Hydraulic Cooler. Meets ISO 3449: 1992  
Note: The part number provided is for reference only. Individual parts must be ordered. Please reference REHS8703 for parts list and installation instructions.
- 474-5632 KIT, SINGLE POINT LIFT**  
Contains parts that attach to cab roof and allow machine to be lifted from a single point. The part number provided is for reference only. Individual parts must be ordered. Please reference REHS9970 for parts list and installation instructions.
- 418-5883 KIT, FOPS LEVEL 2 W/ 4 PT LIFT**  
This kit combines the Falling Object Protective Structure level 2 and 4 point lifting functionality. Recommended for use in applications where additional overhead protection and 4 point lifting are both desired (ex. demolition).  
Note: The part number provided is for reference only. Individual parts must be ordered. Please reference REHS9989 for parts list and installation instructions.
- 466-1959 KIT, CCB HEATER**  
For proper installation, refer to media number REHS6625. Required for operating in temperatures BELOW -18C (-0F). Provides a second heater for the engine closed crankcase breather (CCB) system. Estimated time to install: 1.0 Hr

The RETURN TO DIG/WRKTL POSITIONER feature is available as a Software Enabled Attachment (SEA) and is installed using Electronic Technician and a unique password. Cost to enable the feature via password is approximately \$221 USD Dealer Net (January, 2016). Machine must be equipped with the Electronic Self Level feature, provided in the H2 or H3 performance package to install the SEA.



CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

***Available Through Parts Distribution. (Cont.)***

**DEDICATED ALTERNATE PATTERN (H-pattern):**

As of January 2018, this feature is standard from the factory. There is no cost. Using Electronic Technician the dealer can configure the machine to operate using the alternative "H" control pattern. With this feature there is no method to allow the operator to change the pattern in the cab. Refer to media number REHS8719.

**SELECTABLE PATTERN CONTROL (ISO/H patterns):**

This feature is a Software Enabled Attachment (SEA) and is installed using Electronic Technician and a unique password. The SEA cost to enable the feature via password is approximately \$250 USD Dealer Net (January 2018). Allows an operator to select either standard CAT control pattern or the alternative "H" control pattern with the flip of a switch. Estimated time to install: 30 min. Refer to media number REHS8718 for appropriate parts list.

The components required are available for order from the Parts Department.

***Available Through ANTARES Parts Ordering.***

**NOTE: US & Canada ONLY may place orders in CMOPS to be transferred via the bridge to ANTARES Parts Ordering.  
When ordering via CMOPS include top level reference numbers (OP-2730) and OP number for packing.**

524-0804	KIT, ADVANCED DISPLAY . . . . . 0 For proper installation, refer to media number M0077883. Includes: Full color 5 in. LCD screen with digital gauge display. Provides Creep Control, Hystat response adjustment, Implement response adjustment, Fuel gauge, Hydraulic temperature gauge, Engine coolant gauge, Tachometer, Language selection and Advanced multi-operator Anti-theft Security and Monitoring. Also provides USB charging port. Note: Rear camera ready. Estimated time to install: 1 hour 30 minutes	\$950 NI
388-8284	KIT, CAMERA REAR VIEW . . . . . 0 For proper installation, refer to media number REHS8711. Note: Requires Advanced Display Estimated time to install: 1 hour	\$450 NI
484-0292	KIT, BATTERY DISCONNECT . . . . . 0 For proper installation, refer to media number SESH0524. Provides components needed to install a battery disconnect switch. Estimated time to install: 1 hour 30 minutes	\$124 NI
504-1553	KIT, LICENSE PLATE . . . . . 0  For proper installation, refer to media number M0067678. Estimated time to install: 30 minutes	\$50 NI NET

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering. (Cont.)*

388-8285	KIT, FOOT THROTTLE . . . . .	0		\$324 NI
	For proper installation, refer to media number REHS8712. Estimated time to install: 1 hour 30 minutes			
388-7875	KIT, COUNTERWEIGHT, 100 LB ROC . . . . .	0		\$510 NI
	Kit provides one counterweight per side which increases the Rated Operating Capacity by approximately 100-125 lbs (46 - 57 kg), depending on model. For maximum ROC increase, must order quantity of (2) 388-7875 kits. Includes Mounting hardware for both one counterweight per side configuration and two counterweights per side configuration. Estimated time to install: 30 minutes			
508-1865	KIT, AIR CONDITIONER (HTR/DFR) . . . . .	0		\$2,992 NI
	For proper installation, refer to media number M0070244. Estimated time to install: 8 hours 30 minutes			
388-8266	KIT, AIR CONDITIONER (CONVRN) . . . . .	0		\$1,996 NI
	For proper installation, refer to media number REHS7807. Estimated time to install: 8 hours			
509-5547	KIT, HEATER . . . . .	0		\$1,201 NI
	For proper installation, refer to media number M0070254. Estimated time to install: 6 hours			
388-8275	KIT, WINDOW, SIDES . . . . .	0		\$669 NI
	For proper installation, refer to media number REHS8707. Estimated time to install: 1 hour			
388-8276	KIT, DOOR, CAB, GLASS . . . . .	0		\$983 NI
	For proper installation, refer to media number REHS8708. For use with Serial Number BYF03213 and BELOW. Estimated time to install: 1 hour 30 minutes			
514-9110	KIT, DOOR, CAB, GLASS . . . . .	0		\$983 NI
	For proper installation, refer to media number M0073174. For use with Serial Number BYF03214 and ABOVE. Estimated time to install: 1 hour 30 minutes			
514-9095	KIT, DOOR, CAB, POLYCARBONATE . . . . .	0		\$1,750 NI
	For proper installation, refer to media number M0073172. For use with Serial Number BYF03213 and BELOW. Estimated time to install: 1 hour 30 minutes			
514-9112	KIT, DOOR, CAB, POLYCARBONATE . . . . .	0		\$1,750 NI
	For proper installation, refer to media number M0073176. For use with Serial Number BYF03214 and ABOVE. Estimated time to install: 1 hour 30 minutes			
527-3155	KIT, QUICK COUPLER, HYDRAULIC . . . . .	0		\$1,057 NI
	For proper installation refer to media number M0081347. Estimated time to install: 12 hours			
513-5126	KIT, GUARD, COUPLER . . . . .	0		\$194 NI
	For proper installation, refer to media number M0072576. Provides lower guard that restricts material/debris from entering the underside of the coupler area giving additional safeguarding for electrical components. Estimated time to install: 30 minutes			

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering. (Cont.)*

388-8265	<b>KIT, WT ELECTRICAL CONTROL</b> . . . . . 0			<b>\$189 NI</b>
	For proper installation, refer to media number REHS7806. Includes Work Tool Electrical switch, harness, connector and mounting hardware. Estimated time to install: 2 hours			
388-8273	<b>KIT,WT ELECTRICAL CONTROL, DLX</b> . . . . . 0			<b>\$682 NI</b>
	For proper installation, refer to media number REHS7814. Includes: Work Tool Electrical switch, harness, connector, mounting hardware and 4 button Left Hand Joystick. Estimated time to install: 3 hours			
435-9031	<b>KIT, FAN, DEMAND, REVERSING</b> . . . . . 0			<b>\$1,089 NI</b>
	For proper installation, refer to media number REHS6604. Reversing Fan provides automatic and manual purge modes to assist in removing material from the rear door intake screen. Provides both Demand Fan and Reversing Fan functionality. Estimated time to install: 4 hours			
435-8858	<b>KIT, RIDE CONTROL</b> . . . . . 0			<b>\$1,018 NI</b>
	For proper installation, refer to media number REHS6619. The Ride Control feature allows the lift arms to "float" when the machine travels over rough terrain. The result is a more comfortable ride and better material retention in the bucket or better load retention on pallet forks. For use with Serial Numbers BYF01879 AND BELOW. Estimated time to install: 3 hours			
481-5973	<b>KIT, RIDE CONTROL</b> . . . . . 0			<b>\$1,017 NI</b>
	For proper installation, refer to media number SEHS0161. The Ride Control feature allows the lift arms to "float" when the machine travels over rough terrain. The result is a more comfortable ride and better material retention in the bucket or better load retention on pallet forks. For use with Serial Numbers BYF01880 through BYF02167. Estimated time to install: 3 hours			
490-5119	<b>KIT, RIDE CONTROL</b> . . . . . 0			<b>\$1,017 NI</b>
	For proper installation, refer to media number SEHS0412. The Ride Control feature allows the lift arms to "float" when the machine travels over rough terrain. The result is a more comfortable ride and better material retention in the bucket or better load retention on pallet forks. For use with Serial Numbers BYF02168 AND ABOVE. Estimated time to install: 3 hours			
422-3362	<b>KIT, DUAL SELF LEVEL</b> . . . . . 0			<b>\$735 NI</b>
	For proper installation, refer to media number REHS7811. Estimated time to install: 3 hours 30 minutes Note: Not compatible with H2 or H3 Performance Packages			
388-8283	<b>KIT, RADIO, READY</b> . . . . . 0			<b>\$146 NI</b>
	For proper installation, refer to media number REHS8710. Provides Speakers, Wiring, Radio Box, Antenna & Cable, and hardware required to install a single DIN radio. Estimated time to install: 1 hour			

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering. (Cont.)*

388-8286	<b>KIT, RADIO, AM/FM/BLUETOOTH</b> . . . . . 0			<b>\$560 NI</b>
	For proper installation, refer to media number REHS8705. Includes radio with Bluetooth interface, microphone and auxiliary inputs (USB port and aux input jack) to connect external audio devices. Requires: Radio Ready operator station. Estimated time to install: 45 minutes			
471-7023	<b>KIT, DEBRIS</b> . . . . . 0			<b>\$1,294 NI</b>
	For proper installation, refer to media number SEHS0196. This kit provides additional components for customers in debris intensive applications that restrict debris and other material from entering the engine compartment and the lower machine frame. Provided are various seals and covers that are designed to cover the openings that exist between the frame/body/cab of the machine as well as a fuel strainer and an exhaust stack cover. Also recommended: Turbo Debris Guard Kit Note: If additional component guarding is required, please refer to the Guarding Kit. Estimated time to install: 10 hours			
472-2966	<b>KIT, GUARDING</b> . . . . . 0			<b>\$628 NI</b>
	For proper installation, refer to media number SEHS0199. This kit provides additional guarding for customers in demanding applications where extra safeguarding is required. This kit provides guarding for the front work lights, rear work lights, auxiliary hydraulic connections, work tool electrical harness connection and work tool coupler area. Note: If additional debris guarding is required, please refer to the Debris Kit. Estimated time to install: 1.5 hours			
421-0219	<b>KIT, A/C BREATHER</b> . . . . . 0			<b>\$447 NI</b>
	For proper installation, refer to media number M0068026. This kit provides increased cab air filter life for machines used in dusty or high airborne debris applications. Kit contains duct work and hardware required to relocate the cab fresh air intake to a higher location near the roof of the cab. Estimated time to install: 30 minutes			
415-2795	<b>KIT,ENG AIR INTAKE, PRECLEANER</b> . . . . . 0			<b>\$729 NI</b>
	For proper installation, refer to media number REHS5798. Turbine-type precleaner for the engine air filter. For use in high dust/debris applications. Estimated time to install: 1 hour			
416-5705	<b>KIT, TURBO DEBRIS GUARD</b> . . . . . 0			<b>\$351 NI</b>
	For proper installation, refer to media number REHS7828. This kit contains steel mesh guards that are designed to cover the exhaust manifold and turbocharger to assist in deterring the collection of material on these components. It is recommended that the turbo guard kit be used in conjunction with the debris kit. Estimated time to install: 1 hour 30 minutes			

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering. (Cont.)*

456-5190	<b>KIT, DOOR, HYD FILL CAP</b> . . . . . 0			<b>\$79 NI</b>
	For proper installation, refer to media number REHS9160. Provides lockable cover for hydraulic oil fill. For use with Serial Number BYF02167 and BELOW.			
422-3323	<b>KIT, FRONT ROADING LIGHTS</b> . . . . . 0			<b>\$458 NI</b>
	For proper installation, refer to media number REHS7836. Includes front roading lights and 2 lift arm mounted mirrors. Mandatory for Road Homologation in Italy and Germany. Estimated time to install: 4 hours			
422-3322	<b>KIT, LIGHTS, REAR, ROADING</b> . . . . . 0			<b>\$228 NI</b>
	For proper installation, refer to media number REHS8748. This kit provides Rear Roading light components (rear reflectors, brake lamps, directional indicators/turn signals, hazard lights) in order to meet roading requirements for Italy. Estimated time to install: 1.5 hours			
512-0356	<b>KIT, LIGHTS, REAR, WIDE MOUNT</b> . . . . . 0			<b>\$421 NI</b>
	For proper installation, refer to media number M0071898. This kit provides components that allows the rear lights to be relocated to mounting locations on the sides of the rear frame. Estimated time to install: 30 minutes			
421-0274	<b>KIT, LIFTING EYES, FOUR POINT</b> . . . . . 0			<b>\$225 NI</b>
	For proper installation, refer to media number REHS9993. Estimated time to install: 30 minutes CANNOT BE USED WITH: TANK, WATER			
452-0239	<b>KIT, WINTER, REAR DOOR COVER</b> . . . . . 0			<b>\$250 NI</b>
	Required for operating in temperatures below -32C (-25F). For proper installation refer to media number REHS8737. Provides rear door cover to minimize air flow into the engine compartment. Estimated time to install: 1.0 hour			
422-3241	<b>KIT, PROD LINK, CELLULAR PL641</b> . . . . . 0			<b>\$1,004 NI</b>
	For proper installation, refer to media number REHS9952 Product Link Pro series PL641 uses GSM and CDMA 3G cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data. Estimated time to install: 2.5 hours			
499-2684	<b>KIT, LIGHTS, LED</b> . . . . . 0			<b>\$343 NI</b>
	For proper installation, refer to media number M0066104. Includes two (2) forward facing adjustable work lights (cab mounted) and two (2) rear facing LED work lights (frame mounted). LED lighting advantages vs halogens: brighter work site illumination, cooler, more resistant to vibration and longer life. Estimated time to install: 1 hour			

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering. (Cont.)*

482-5132	<b>KIT, WATER TANK, 42 US GAL, D</b> . . . . . 0			<b>\$1,781 NI</b>
	Mounted to top of cab 42 gallon capacity Includes tank, pump, filter, lines, mounting brackets and quick disconnect For proper installation, refer to media number SEHS0363. Estimated time to install: 9 hours 30 minutes For use with Water Sprinkler Kits for Angle Broom, Pick Up Broom, Utility Broom or Cold Planer			
533-5187	<b>KIT, HAND/FOOT TO ISO (CVRSN)</b> . . . . . 0			<b>\$1,435 NI</b>
	CANNOT BE USED WITH: Four Point Lifting Eyes kit, Single Point Lift kit or Auxiliary Hydraulic Cooler kit For proper installation, refer to media number M0082286. Provides all required components to convert machine control pattern from hand & foot controls to ISO controls. Estimated time to install: 4 hours			
527-2335	<b>KIT, REMOTE GREASE (COUPLER)</b> . . . . . 0			<b>\$218 NI</b>
	For proper installation, refer to media number M0084651. Provides remote location for lubrication of the work tool coupler pins Estimated time to install: 3 hours			

**NO RETURNS accepted for kit components not used or for parts removed from machine during kit installation.**

**Shipments will be within 3 - 5 working days of order receipt for delivery by dealer parts stocking truck to dealer stocking facility.**

CATERPILLAR MACHINE PRICE LIST

**246D**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

***ENDORSED FIELD INSTALLED ATTACHMENTS***

Caterpillar does not warrant, service, or assume responsibility for these attachments.

All orders, pricing confirmation, and other communication for these attachments must be directed to the listed manufacturer.

**REMOTETASK TM - REMOTE CONTROL SYSTEM**

Complete system for use with CAT D Series Skid Steer, Multi Terrain, and Compact Track Loaders. Allows the operator to precisely control the machine from outside the cab. Line-of-sight remote control with an approximate range of 1000 feet (300 meters). Dealer installed remote control system includes the Remote Task controller and necessary hardware to convert standard D series SSL, MTL or CTL to remote controlled machine.

NOTE: Certified for use in North America. To verify certification in other regions, please contact BCP Attachments Team.

Email: [bcp\\_work\\_tools@cat.com](mailto:bcp_work_tools@cat.com)

Orders for the remote control system must be placed directly from:

TORC Robotics, Inc.

Tel. +1(800) 530-9285, +1(540) 443-9262

Email: [sales@torcrobotics.com](mailto:sales@torcrobotics.com)

**PACKING**

***DOMESTIC PACKING***

OP-0210	PACK, DOMESTIC TRUCK . . . . .	0	NC
---------	--------------------------------	---	----

***Only to be used when ordering kits via CMOPS.***

OP-2162	PACKING, KIT . . . . .	0	NC
---------	------------------------	---	----

***PROTECTION***

OP-2266	<b>SHIPPING/STORAGE PROTECTION . . . . .</b>	0	<b>\$203 NET</b>
	Provides protective application of Fluid Film TM for protection while shipping and for extended storage periods. If desired, this product can be power washed with warm soapy water prior to shipment to the customer.		

OP-6439	<b>CORROSION INHIBITOR. . . . .</b>	0	<b>\$1,900</b>
	EquipCoat is a flexible protective coating with anti-corrosion additives that encapsulate machine surfaces, including components under the cab and in the engine compartment. Will hold up to washing with non-solvent based cleaners for long-term corrosion resistance. Recommended for machines exposed to corrosive environments(e.g.manure, fertilizer, salt, mining fluids, etc.).		