

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

272D2 SKID STEER LOADER XHP  
SANFORD, NC, USA

Ship Weight  
lbs

LIST PRICE  
AT DEALER

Standard Equipment:

## POWERTRAIN

Cat C3.8 turbo aftercooled diesel engine  
-Gross horsepower per SAE J1349  
110 hp (82 kW) @ 2400 RPM  
-EPA Tier 4 Final and EU Stage IV  
certified with aftertreatment  
-Electric fuel priming pump  
-Air inlet heater starting aid  
-Liquid cooled, direct injection  
Two speed travel with ride control  
Air cleaner, dual element, radial seal  
S-O-S sampling valve, hydraulic oil  
Filter, cartridge type, hydraulic  
Filters, cartridge type, fuel  
and water separator  
Radiator/hydraulic oil  
Cooler (side-by-side)  
Spring applied, hydraulically released,  
parking brakes  
Hydrostatic transmission  
Four wheel chain drive

## HYDRAULICS

HYDRAULICS, XHP  
-High flow: 40 gpm (150 lpm) max  
-High flow pressure: 4061 psi  
28000 kPa max  
-Continuous flow  
-Hydraulics, proportional  
-Worktool harness  
CONTROLS:  
Electro/hydraulic implement control  
Electro/hydraulic hydrostatic  
transmission control

## STARTERS, BATTERIES, & ALTERNATORS

1000 CCA heavy duty battery w/disconnect

## ELECTRICAL

12 volt electrical system  
100 ampere alternator  
Ignition key start / stop / aux switch  
Lights:  
-Gauge backlighting  
-Two rear tail lights  
-Dome light  
Backup alarm  
Electrical outlet, beacon

## OPERATOR ENVIRONMENT

Operator warning system indicators:  
-Air filter restriction  
-Alternator output  
-Armrest raised / operator out of seat  
-Engine coolant temperature

-Engine oil pressure  
-Air inlet heater activation  
-Hydraulic filter restriction  
-Hydraulic oil temperature  
-Park brake engages  
-Engine emission system  
Gauges: DEF level, fuel level,  
hour meter and tachometer  
Storage compartment with netting  
Seat, comfort, air suspension, cloth,  
heat  
-High back heated seat with recline  
-Lumbar support  
-Fully adjustable seat mounted  
controls  
Ergonomic contoured armrest  
Control interlock system, when operator  
leaves seat or armrest raised:  
-Hydraulic system disables  
-Hydrostatic transmission disables  
-Parking brake engages  
ROPS Cab, enclosed (C3), tilt up:  
-Air conditioner incl heater/defroster  
-Side windows  
-Cup holder  
FOPS, Level I  
Top and rear windows  
Deluxe headliner  
Floor mat  
Interior rear view mirror  
12V electric socket  
Horn  
Hand (dial) & foot throttle, electronic  
Dual direction electronic self level -  
(raise and lower)  
Work tool return to dig  
Work tool positioner  
Electronic snubbing (lift)  
Advanced LCD display  
-Full color 5 inch LCD screen  
-Advanced anti-theft security system,  
with 50 user code capability  
-Rear view camera

## FRAMES

Lift linkage, vertical path  
Chassis, one piece welded  
Machine tie down points (4)  
Belly pan cleanout  
Support, lift arm  
Cast rear bumper  
Ventilated rear door with integrated  
sealing

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

---

272D2 SKID STEER LOADER XHP  
SANFORD, NC, USA

Ship Weight  
lbs

LIST PRICE  
AT DEALER

---

## OTHER STANDARD EQUIPMENT

- Engine enclosure - lockable
- Extended life antifreeze (-37C, -34F)
- Coupler, mechanical
- Hydraulic oil level sight gauge
- Radiator coolant level sight gauge
- Radiator expansion bottle
- Cat tough guard hose
- Heavy duty flat faced quick disconnects  
with integrated pressure release
- Split d-ring to route work tool hoses  
along side of left lift arm
- Variable speed hydraulic cooling fan  
Per SAE J818-2007 and EN 474-3:2006 and  
ISO 14397-1:2007
- Rated operating capacity  
At 50% Tipping Load  
- 3650 lb (1656 kg)

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

272D2 SKID STEER LOADER XHP  
 SANFORD, NC, USA

Ship Weight  
 lbs

LIST PRICE  
 AT DEALER

**Lane 2 is reserved for the Base Order Management Program  
 Please use Lane 2 when placing orders that are part of the Base Order  
 Management program**

<b>522-7490</b>	<b>272D2 XHP SSL DCA1</b> . . . . . 0	<b>\$79,840</b>
	LANE 1 - AVAILABLE FROM SANFORD PDC	
	LANE 2 - AVAILABLE FROM SANFORD FACTORY USING PRIORITY CODE L2	
	LANE 3 - AVAILABLE FROM SANFORD FACTORY USING PRIORITY CODE L2	

- INCLUDES:
- 435-8973 272D2 XHP SKID STEER LOADER
  - 421-0340 CONVERSION ARRANGEMENT
  - 563-1163 CERTIFICATION ARR, P65
  - 345-6260 DOOR, CAB, POLYCARBONATE
  - 345-6175 RADIO READY
  - 258-4095 SEAT BELT, 2"
  - 457-3167 FAN, HYDRAULIC, DEMAND
  - 345-3556 HEATER, ENGINE COOLANT, 120V
  - 515-8592 QUICK COUPLER, HYDRAULIC
  - 495-1671 LIGHTS, LED

NOTE: Please refer to the Lane 1 section to complete your order.

<b>435-8973</b>	<b>272D2 XHP SKID STEER LOADER</b> . . . . . 0	<b>\$78,040</b>
	LANE 2 - AVAILABLE FROM SANFORD FACTORY	
	LANE 3 - AVAILABLE FROM SANFORD FACTORY	
	Available for AM-N, Europe, Turkey, Israel, Puerto Rico, South Korea, Australia & New Zealand	

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

272D2 SKID STEER LOADER XHP  
 SANFORD, NC, USA

Ship Weight  
 lbs

LIST PRICE  
 AT DEALER

**0P-3617**

**272D2 XHP MISC MATERIAL** ..... 0

**NC**

ONLY AVAILABLE FROM WACO PARTS SERVICE

Use this top level reference number only when ordering KITS in CMOPS  
 to be transferred via the bridge to ANTARES Parts Ordering.

Work Tools are sourced via Caterpillar Parts Distribution system.  
 Skid Steer Loader and Work Tools order REQUIRE individual CMOPS  
 order entries. Zeebrugge Distribution Center (ZDC) orders do NOT  
 require individual CMOPS order entries and may include both the  
 machine and work tool orders.

Refer to WT\_SSL price list to order Work Tools.

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	--------	-----------------	----------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS**

(MUST CHOOSE ONE FROM EACH CATEGORY)

**LANE SELECTION**

YOU MUST SELECT THIS REFERENCE WHEN ORDERING FROM THE PDC.

OP-9001	LANE 1 ORDER . . . . .	0	NC
---------	------------------------	---	----

**WARNING DECALS**

L	435-8840	INSTRUCTIONS, ANSI, USA . . . . . This package includes picto decals as required for USA.	0	NC
L	435-8844	INSTRUCTIONS, ISO . . . . . This package includes picto decals as required for all countries except USA.	0	NC

**FILM GROUP SELF LEVEL**

L	435-9238	FILM, SELF LEVEL, ANSI . . . . .	0	NC
L	435-9239	FILM, SELF LEVEL, ISO . . . . .	0	NC

**FILM GROUP, RIDE CONTROL**

L	422-3445	FILM, RIDE CONTROL, ANSI . . . . .	0	NC
L	422-3446	FILM, RIDE CONTROL, ISO . . . . .	0	NC

**PRODUCT LINK**

L	441-4818	PRODUCT LINK, CELLULAR PL240 . . . . . Product Link Basic series PL240 offers expanded coverage including 3G UMTS and HSPA+ as well as 2G GSM and GPRS cellular networks to transmit hour and location information for viewing in Product Link's remote monitoring web interface. The data is updated up to 4 times per day while the engine is running. ONLY FOR USE WITH: US Dealers	0	NC
L	515-3153	PRODUCT LINK, CELLULAR PL240 . . . . . Product Link Basic series PL240 uses cellular networks to transmit hour and location information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent data transmission. ONLY FOR USE WITH: Canada	0	NC

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	--------	-----------------	----------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS (CONT.)**

***TIRES***

P	331-2490	TIRES, 14/17.5 CAT 14PR . . . . .	774	\$1,870
		Caterpillar;Bias;Directional chevron tread pattern; Tread Depth=21mm (26/32") 1930mm (76") wide Premium conventional heavy duty tire provides excellent traction in a variety of conditions. Deepest tread available results in long life. Extra heavy sidewall construction protects against abrasion, tears and impact damage. Includes valve stem protection. CANNOT BE USED WITH: Over the Tire Steel Tracks		

***SERVICE INSTRUCTIONS***

	421-8926	SERIALIZED TECHNICAL MEDIA KIT . . . . .	0	NC
		The technical media kit will include the Operations & Maintenance Manual (OMM) and other media specified on the Factory Notification List required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary. Any additional media or translations not included in the kit, should be ordered through publications.cat.com		

***PACKING***

	0P-1176	CAROLINA CDC -- AVAILABILITY . . . . .	0	\$1 NET
--	---------	--	---	---------

***PROTECTION***

	0P-2266	SHIPPING/STORAGE PROTECTION . . . . .	0	\$203 NET
		Provides protective application of Fluid Film TM for protection while shipping and for extended storage periods. If desired, this product can be power washed with warm soapy water prior to shipment to the customer.		

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**LANE SELECTION**

OP-9002	LANE 2 ORDER . . . . .	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
OP-9003	LANE 3 ORDER . . . . .	0	NC

**REGIONAL PACKAGES**

**CONVERSION ARRANGEMENTS**

L	421-0340 CONVERSION ARRANGEMENT . . . . .	0	NC
	FOR USE WITH: ADS-D-N, APD		

**CERTIFICATION ARRANGEMENTS/YEAR OF MANUFACTURE**

L	563-1163 CERTIFICATION ARR, P65 . . . . .	0	NC
	REQUIRED for US		

**WARNING DECALS**

L	435-8840 INSTRUCTIONS, ANSI, USA . . . . .	0	NC
	This package includes picto decals as required for USA.		

**PERFORMANCE PACKAGES**

**FILM GROUP SELF LEVEL**

L	435-9238 FILM, SELF LEVEL, ANSI . . . . .	0	NC
---	---	---	----

**FILM GROUP RIDE CONTROL**

L	422-3445 FILM, RIDE CONTROL, ANSI . . . . .	0	NC
---	---	---	----

**FEATURE PACKAGES**

**DOOR**

P	345-6240 DOOR, CAB, GLASS . . . . .	0	\$106
P	345-6260 DOOR, CAB, POLYCARBONATE . . . . .	0	\$210

**RADIO**

Bluetooth radio technology enables the use of a hands free function such as listening to music and making phone calls. Authorization varies by country, please contact your Cat marketing representative with questions or click on the link below:  
<https://dealer.cat.com/en/products/technology.html>

L	345-6175 RADIO READY . . . . .	0	\$151
	Provides Speakers, Wiring, Radio Box, Antenna & Cable, and hardware required to install a single DIN radio.		

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**FEATURE PACKAGES (CONT.)**

**RADIO (Cont.)**

L	345-6180	<b>RADIO, AM/FM, BLUETOOTH</b> . . . . . 0 Provides factory installed radio: Includes Bluetooth interface, microphone, and auxiliary inputs (USB port and aux input jack) to connect external audio devices.		<b>\$499</b>
---	----------	---	--	--------------

**OPERATOR ENVIRONMENT**

**LIGHTS**

L	495-1671	<b>LIGHTS, LED</b> . . . . . 0 Two (2) forward facing adjustable LED work lights (cab mounted) and two (2) rear facing LED work lights (frame mounted). LED lighting advantages vs halogens: brighter work site illumination, cooler, more resistant to vibration and longer life.		<b>\$274</b>
---	----------	---	--	--------------

**SEAT BELTS**

L	258-4095	<b>SEAT BELT, 2"</b> . . . . . 0		<b>NC</b>
L	258-4096	<b>SEAT BELT, 3"</b> . . . . . 0 Required in California.		<b>\$139</b>

**TECHNOLOGY PRODUCTS**

**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	441-4818	<b>PRODUCT LINK, CELLULAR PL240</b> . . . . . 0 Product Link Basic series PL240 uses cellular networks to transmit hour and location information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent data transmission.		<b>NC</b>
L	441-4819	<b>PRODUCT LINK, CELLULAR PL641</b> . . . . . 0 Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		<b>\$590 NET</b>



CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**COOLING**

**COOLING FAN**

L	457-3167	FAN, COOLING, DEMAND . . . . . 0		NC
		Provides variable speed hydraulic cooling fan. Sensors monitor machine cooling requirements to modulate the fan speed providing "on demand" cooling.		
L	457-2835	FAN, COOLING, DEMAND, REVERSING . . . . . 0		\$825
		Reversing Fan provides automatic and manual purge modes to assist in removing material from the rear door intake screen. Provides both Demand Fan and Reversing Fan functionality.		

**TIRES, RIMS, AND WHEELS**

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice. However, if the tire type cannot be supplied we will contact the dealer to propose alternatives. The dealer needs to choose between an alternative tire or a "rims only" option (where available) within 72 hours. If no response is provided by the deadline, the order will default to the alternative tire and will be changed at that point. As a consequence of a possible tire change, the total machine price will be decreased or increased depending on the price of the new tire.

**1880mm (74") Width**

P	331-2488	TIRES, 14X17.5 CAT 14PR XD . . . . . 694		\$2,400
		Caterpillar XD Tire - 14-ply pneumatic tire with very deep tread, ultra heavy duty sidewalls and extra large rim guards. Ideal for concrete & demolition work, quarries and asphalt recycling. Tread depth 47/32" (37mm) is 43% deeper than Cat Premium Conventional Tires. The XD Tire features a special tread compound for long wear and durability. Bias ply. Includes valve stem protection. 1880mm (74") Width NOTE: Not compatible with Over the Tire Steel Tracks.		

**1930mm (76") Width**

P	331-2490	TIRES, 14/17.5 CAT 14PR . . . . . 774		\$1,870
		Caterpillar Tire - Premium conventional heavy duty tire provides excellent traction in a variety of conditions. Deepest tread available (26/32") (21mm) results in long service life. Extra heavy sidewall construction protects against abrasion, tears and impact damage. Directional chevron tread pattern, bias ply. Includes valve stem protection. 1930mm (76") Width NOTE: Not compatible with Over the Tire Steel Tracks.		

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

---

<b>USE</b>	<b>REF NO.</b>	<b>LANE 2 / 3 MANDATORY</b>	<b>Ship Weight lbs</b>		<b>LIST PRICE AT DEALER</b>
------------	----------------	-----------------------------	----------------------------	--	---------------------------------

---

**QUICK COUPLERS**

L	345-4910	QUICK COUPLER, MANUAL . . . . .	0		NC
L	515-8592	QUICK COUPLER, HYDRAULIC . . . . .	0		\$975

**INSTRUCTIONS**

***SERVICE INSTRUCTIONS***

	421-8926	<b>SERIALIZED TECHNICAL MEDIA KIT . . . . .</b> The technical media kit will include the Operations & Maintenance Manual (OMM) and other media specified on the Factory Notification List required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary. Any additional media or translations not included in the kit, should be ordered through publications.cat.com	0		NC
--	----------	--	---	--	----

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

### SPECIAL ARRANGEMENTS

C	0P-0528	<b>PAINT, CUSTOM</b> . . . . . 0 FOR USE IN LANE 3 ONLY Paint specification (RAL #) required. Advise via MSO notes. Custom paint order provides a SINGLE COLOR, non-metallic, high gloss custom finish. Once a custom paint order is placed, it may not be cancelled. Custom paint extends availability from what is published. Contact the factory for current availability information.  Note 1: Florescent colors and matte finishes are not available. Note 2: Some components will NOT receive the custom paint color. The engine and items not externally visible will be painted yellow. CTLs with the optional steel track undercarriage will be provided with a black track. Cylinders, cab, coupler, radiator grill and the MTL undercarriage will be painted black.		<b>\$1,825 NET</b>
---	---------	---	--	--------------------

### ELECTRICAL

L	309-1325	<b>ROTATING BEACON</b> . . . . . 0 Magnetic base, mounted to top of cab. Operates when key switch is in "On" position.		<b>\$212</b>
---	----------	---	--	--------------

### OTHER ATTACHMENTS

L	345-5148	<b>COUNTERWEIGHT, MACHINE, EXTERNAL</b> . . . . . 0 Includes external weights bolted to the frame tower. Suggested for applications where additional rated operating capacity (ROC) is needed. Machine ROC increased by 250 lbs (113 kg).		<b>\$1,010</b>
L	345-3556	<b>HEATER, ENGINE COOLANT, 120V</b> . . . . . 0 120 Volt - For additional cold weather startability.		<b>\$191</b>
L	457-1215	<b>LIFTING EYES, FOUR POINT</b> . . . . . 0 Included in EU Conversion Arrangement CANNOT BE USED WITH: TANK, WATER		<b>\$188</b>
L	563-7518	<b>MOUNTING, FIRE EXTINGUISHER</b> . . . . . 0 Provides in-cab mounting bracket that can accommodate up to a 5 lb. fire extinguisher.		<b>\$196</b>

### WORK TOOLS

To view and order all available Work Tool Selections refer to WT-SSL or WT-HAMR price lists.  
 NOTE: Work Tools, except Hammers, are sourced via Caterpillar parts distribution system.  
 CMOPS orders for Skid Steer Loaders and Work Tools MUST be ordered separately.

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FLUIDS**

L	418-9011	OIL, HYDRAULIC, COLD OPERATION . . . . . 0 Recommended for use in hydraulic system where ambient temperatures are below 32 F (0 C).		\$650
---	----------	--	--	-------

**FIELD INSTALLED ATTACHMENTS**

*Available Through Parts Distribution.*

- 345-6070 KIT, FOPS, LEVEL 2**  
 Falling Object Protective Structure level 2. Provides additional overhead protection. Recommended for use in demolition applications. Not compatible with the roof mounted Auxiliary Hydraulic Cooler. Meets ISO 3449: 1992  
 Note: The part number provided is for reference only. Individual parts must be ordered. Please reference REHS8703 for parts list and installation instructions.
- 474-5632 KIT, SINGLE POINT LIFT**  
 Contains parts that attach to cab roof and allow machine to be lifted from a single point. The part number provided is for reference only. Individual parts must be ordered. Please reference REHS9970 for parts list and installation instructions.
- 418-5883 KIT, FOPS LEVEL 2 W/ 4 PT LIFT**  
 This kit combines the Falling Object Protective Structure level 2 and 4 point lifting functionality. Recommended for use in applications where additional overhead protection and 4 point lifting are both desired (ex. demolition).  
 Note: The part number provided is for reference only. Individual parts must be ordered. Please reference REHS9989 for parts list and installation instructions.

DEDICATED ALTERNATE PATTERN (H-pattern):  
 As of January 2018, this feature is standard from the factory. There is no cost. Using Electronic Technician the dealer can configure the machine to operate using the alternative "H" control pattern. With this feature there is no method to allow the operator to change the pattern in the cab. Refer to media REHS8719.

SELECTABLE PATTERN CONTROL (ISO/H patterns):  
 This feature is a Software Enabled Attachment (SEA) and is installed using Electronic Technician and a unique password. The SEA cost to enable the feature via password is approximately \$250 USD Dealer Net (January, 2018). Allow an operator to select either standard CAT control pattern or the alternative "H" control pattern with the flip of a switch. Estimated time to install: 30 min. Refer to media number REHS8718 for appropriate parts list.

The components required are available for order from the Parts Department.

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering.*

**NOTE: US & Canada ONLY may place orders in CMOPS to be transferred via the bridge to ANTARES Parts Ordering.  
When ordering via CMOPS include top level reference numbers (OP-2741) and OP number for packing.**

388-8285	<b>KIT, FOOT THROTTLE</b> . . . . . 0	<b>\$324 NI</b>
	For proper installation, refer to media number REHS8712. Estimated time to install: 1 hour 30 minutes	
504-1553	<b>KIT, LICENSE PLATE</b> . . . . . 0	<b>\$50 NI NET</b>
	For proper installation, refer to media number M0067678. Estimated time to install: 30 minutes	
388-7875	<b>KIT, COUNTERWEIGHT, 100 LB ROC</b> . . . . . 0	<b>\$510 NI</b>
	Kit provides one counterweight per side which increases the Rated Operating Capacity by approximately 100-125 lbs (46 - 57 kg), depending on model. For maximum ROC increase, must order quantity of (2) 388-7875 kits. Includes Mounting hardware for both one counterweight per side configuration and two counterweights per side configuration. Estimated time to install: 30 minutes	
388-8275	<b>KIT, WINDOW, SIDES</b> . . . . . 0	<b>\$669 NI</b>
	For proper installation, refer to media number REHS8707. Estimated time to install: 1 hour	
514-9093	<b>KIT, DOOR, CAB, POLYCARBONATE</b> . . . . . 0	<b>\$1,750 NI</b>
	For proper installation, refer to media number M0073170. Estimated time to install: 1.5 hours	
422-3297	<b>KIT, DOOR, CAB, GLASS</b> . . . . . 0	<b>\$983 NI</b>
	For proper installation, refer to media number REHS9992. Estimated time to install: 1.5 hours	
435-9232	<b>KIT, AIR CONDITIONER (CONVRSN)</b> . . . . . 0	<b>\$1,976 NI</b>
	For proper installation, refer to media number REHS9982. Estimated time to install: 7 hours	
435-9231	<b>KIT, HEATER</b> . . . . . 0	<b>\$1,188 NI</b>
	For proper installation, refer to media number REHS9981. Estimated time to install: 7 hours	
388-8265	<b>KIT, WT ELECTRICAL CONTROL</b> . . . . . 0	<b>\$189 NI</b>
	For proper installation, refer to media number REHS7806. Includes Work Tool Electrical switch, harness, connector and mounting hardware. Estimated time to install: 2 hours	
388-8273	<b>KIT, WT ELECTRICAL CONTROL, DLX</b> . . . . . 0	<b>\$682 NI</b>
	For proper installation, refer to media number REHS7814. Includes: Work Tool Electrical switch, harness, connector, mounting hardware and 4 button Left Hand Joystick. Estimated time to install: 3 hours	

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering. (Cont.)*

527-3155	<b>KIT, QUICK COUPLER, HYDRAULIC</b> . . . . . 0	For proper installation refer to media number M0081347. Estimated time to install: 12 hours		<b>\$1,057 NI</b>
513-5126	<b>KIT, GUARD, COUPLER</b> . . . . . 0	For proper installation, refer to media number M0072576. Provides lower guard that restricts material/debris from entering the underside of the coupler area giving additional safeguarding for electrical components. Estimated time to install: 30 minutes		<b>\$194 NI</b>
435-9237	<b>KIT, FAN, DEMAND, REVERSING</b> . . . . . 0	For proper installation, refer to media number REHS6604. Reversing Fan provides automatic and manual purge modes to assist in removing material from the rear door intake screen. Provides both Demand Fan and Reversing Fan functionality. Estimated time to install: 1.5 hours		<b>\$840 NI</b>
388-8283	<b>KIT, RADIO, READY</b> . . . . . 0	For proper installation, refer to media number REHS8710. Provides Speakers, Wiring, Radio Box, Antenna & Cable, and hardware required to install a single DIN radio. Estimated time to install: 1 hour		<b>\$146 NI</b>
388-8286	<b>KIT, RADIO, AM/FM/BLUETOOTH</b> . . . . . 0	For proper installation, refer to media number REHS8705. Includes radio with Bluetooth interface, microphone and auxiliary inputs (USB port and aux input jack) to connect external audio devices. Requires: Radio Ready operator station. Estimated time to install: 45 minutes		<b>\$560 NI</b>
498-6622	<b>KIT, DEBRIS</b> . . . . . 0	For proper installation, refer to media number M0067498. This kit provides additional components for customers in debris intensive applications that restrict debris and other material from entering the engine compartment and the lower machine frame. Provided are various seals and covers that are designed to cover the openings that exist between the frame/body/cab of the machine as well as a fuel strainer and an exhaust stack cover. The Debris Kit is required in applications where airborne debris is present and should be used in conjunction with the Turbo Debris Guard kit. Note: If additional component guarding is required, please refer to the Guarding Kit. Estimated time to install: 10 hours		<b>\$1,838 NI</b>
472-2965	<b>KIT, GUARDING</b> . . . . . 0	For proper installation, refer to media number REHS9959. This kit provides additional guarding for customers in demanding applications where extra safeguarding is required. This kit provides guarding for the front work lights, rear work lights, auxiliary hydraulic connections, work tool electrical harness connection and work tool coupler area. Note: If additional debris guarding is required, please refer to the Debris Kit. Estimated time to install: 1.5 hours		<b>\$628 NI</b>

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering. (Cont.)*

421-0219	<b>KIT, A/C BREATHER</b> . . . . . 0			<b>\$447 NI</b>
	For proper installation, refer to media number M0068026. This kit provides increased cab air filter life for machines used in dusty or high airborne debris applications. Kit contains duct work and hardware required to relocate the cab fresh air intake to a higher location near the roof of the cab. Estimated time to install: 30 minutes			
444-6050	<b>KIT, TURBO DEBRIS GUARD</b> . . . . . 0			<b>\$279 NI</b>
	For proper installation, refer to media number REHS9969. This kit contains steel mesh guards that are designed to cover the exhaust manifold and turbocharger to assist in deterring the collection of material on these components. The Turbo Guard kit is required in applications where airborne debris is present and should be used in conjunction with the Debris Kit. Estimated time to install: 1 hour 30 minutes			
416-5965	<b>KIT,ENG AIR INTAKE, PRECLEANER</b> . . . . . 0			<b>\$457 NI NET</b>
	For proper installation, refer to media number REHS8735. Turbine-type precleaner for the engine air filter. For use in high dust/debris applications. Estimated time to install: 1 hour			
451-8378	<b>KIT, COOLER, AUXILIARY HYDR</b> . . . . . 0			<b>\$2,818 NI</b>
	For proper installation, refer to media number REHS9189. Roof mounted auxiliary hydraulic cooler provides additional hydraulic cooling capacity. For use in heavy duty applications (i.e. mulching, brush cutting, etc.) where the machine is utilized continuously in XHP mode with high demand on the Hystat system at ambient temperatures greater than 38 Celsius (100 Fahrenheit). Not compatible with the FOPS Level 2 guarding. Estimated time to install: 8 hours			
422-3323	<b>KIT, FRONT ROADING LIGHTS</b> . . . . . 0			<b>\$458 NI</b>
	Includes front roading lights and 2 lift arm mounted mirrors. For proper installation, refer to media number REHS7836. Mandatory for Road Homologation in Italy and Germany. Estimated time to install: 4 hours			
422-3322	<b>KIT, LIGHTS, REAR, ROADING</b> . . . . . 0			<b>\$228 NI</b>
	For proper installation, refer to media number REHS8748. This kit provides Rear Roading light components (rear reflectors, brake lamps, directional indicators/turn signals, hazard lights) in order to meet roading requirements for Italy. Estimated time to install: 1.5 hours			
512-0356	<b>KIT, LIGHTS, REAR, WIDE MOUNT</b> . . . . . 0			<b>\$421 NI</b>
	For proper installation, refer to media number M0071898. This kit provides components that allows the rear lights to be relocated to mounting locations on the sides of the rear frame. Estimated time to install: 30 minutes REQUIRED for Italy Roading			

CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering. (Cont.)*

421-0274	<b>KIT, LIFTING EYES, FOUR POINT</b> . . . . . 0			<b>\$225 NI</b>
	For proper installation, refer to media number REHS9993. Estimated time to install: 30 minutes CANNOT BE USED WITH: TANK, WATER			
422-3241	<b>KIT, PROD LINK, CELLULAR PL641</b> . . . . . 0			<b>\$1,004 NI</b>
	For proper installation, refer to media number REHS9952 Product Link Pro series PL641 uses GSM and CDMA 3G cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data. Estimated time to install: 2.5 hours			
482-5132	<b>KIT, WATER TANK, 42 US GAL, D</b> . . . . . 0			<b>\$1,781 NI</b>
	Mounted to top of cab 42 gallon capacity Includes tank, pump, filter, lines, mounting brackets and quick disconnect For proper installation, refer to media number SEHS0363. Estimated time to install: 9 hours 30 minutes For use with Water Sprinkler Kits for Angle Broom, Pick Up Broom, Utility Broom or Cold Planer			
	CANNOT BE USED WITH: Four Point Lifting Eyes kit, Single Point Lift kit or Auxiliary Hydraulic Cooler kit			
527-2335	<b>KIT, REMOTE GREASE (COUPLER)</b> . . . . . 0			<b>\$218 NI</b>
	For proper installation, refer to media number M0084651. Provides remote location for lubrication of the work tool coupler pins Estimated time to install: 3 hours			
541-3141	<b>KIT, WINTER, REAR DOOR COVER</b> . . . . . 0			<b>\$250 NI</b>
	Required for operating in temperatures below -32C (-25F). For proper installation refer to media number REHS8737. Provides rear door cover to minimize air flow into the engine compartment. Estimated time to install: 1.0 hour			

**NO RETURNS accepted for kit components not used or for parts removed from machine during kit installation.**

**Shipments will be within 3 - 5 working days of order receipt for delivery by dealer parts stocking truck to dealer stocking facility.**



CATERPILLAR MACHINE PRICE LIST

# 272D2 XHP

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

***ENDORSED FIELD INSTALLED ATTACHMENTS***

Caterpillar does not warrant, service, or assume responsibility for these attachments.

All orders, pricing confirmation, and other communication for these attachments must be directed to the listed manufacturer.

**REMOTETASK TM - REMOTE CONTROL SYSTEM**

Complete system for use with CAT D Series Skid Steer, Multi Terrain, and Compact Track Loaders. Allows the operator to precisely control the machine from outside the cab. Line-of-sight remote control with an approximate range of 1000 feet (300 meters). Dealer installed remote control system includes the Remote Task controller and necessary hardware to convert standard D series SSL, MTL or CTL to remote controlled machine.

NOTE: Certified for use in North America. To verify certification in other regions, please contact BCP Attachments Team.  
Email: [bcp\\_work\\_tools@cat.com](mailto:bcp_work_tools@cat.com)

Orders for the remote control system must be placed directly from:

TORC Robotics, Inc.  
Tel. +1(800) 530-9285, +1(540) 443-9262  
Email: [sales@torcrobotics.com](mailto:sales@torcrobotics.com)

**PACKING**

***DOMESTIC PACKING***

OP-0210	PACK, DOMESTIC TRUCK . . . . .	0	NC
---------	--------------------------------	---	----

***Only to be used when ordering kits via CMOPS.***

OP-2162	PACKING, KIT . . . . .	0	NC
---------	------------------------	---	----

***PROTECTION***

OP-2266	<b>SHIPPING/STORAGE PROTECTION . . . . .</b>	0	<b>\$203 NET</b>
	Provides protective application of Fluid Film TM for protection while shipping and for extended storage periods. If desired, this product can be power washed with warm soapy water prior to shipment to the customer.		
OP-6439	<b>CORROSION INHIBITOR. . . . .</b>	0	<b>\$1,900</b>
	EquipCoat is a flexible protective coating with anti-corrosion additives that encapsulate machine surfaces, including components under the cab and in the engine compartment. Will hold up to washing with non-solvent based cleaners for long-term corrosion resistance. Recommended for machines exposed to corrosive environments(e.g.manure, fertilizer, salt, mining fluids, etc.).		