

CATERPILLAR MACHINE PRICE LIST

**272D2**

272D2 SKID STEER LOADER  
 SANFORD, NC, USA

Ship Weight  
 lbs

LIST PRICE  
 AT DEALER

Standard Equipment:

**POWERTRAIN**

Cat C3.8 turbo aftercooled diesel engine  
 -Gross horsepower per SAE J1349  
 98 hp (73 kW) @ 2400 RPM  
 -EPA Tier 4 Final and EU Stage IV  
 certified with aftertreatment  
 -Electric fuel priming pump  
 -Air inlet heater starting aid  
 -Liquid cooled, direct injection  
 Air cleaner, dual element, radial seal  
 S-O-S sampling valve, hydraulic oil  
 Filter, cartridge type, hydraulic  
 Filters, cartridge type, fuel  
 and water separator  
 radiator / hydraulic oil  
 cooler (side-by-side)  
 Spring applied, hydraulically released,  
 parking brakes  
 Hydrostatic transmission  
 Four wheel chain drive

**HYDRAULICS**

Standard flow auxiliary hydraulics with  
 continuous flow

**CONTROLS:**

Electro/hydraulic implement control  
 Electro/hydraulic hydrostatic  
 transmission control

**ELECTRICAL**

12 volt electrical system  
 100 ampere alternator  
 Ignition key start / stop / aux switch  
 Lights:  
 -Gauge backlighting  
 -Two rear tail lights  
 -Dome light  
 Backup alarm  
 Electrical outlet, beacon

**OPERATOR ENVIRONMENT**

Operator warning system indicators:  
 -Air filter restriction  
 -Alternator output  
 -Armrest raised / operator out of seat  
 -Engine coolant temperature  
 -Engine oil pressure  
 -Air inlet heater activation  
 -Hydraulic filter restriction  
 -Hydraulic oil temperature  
 -Park brake engages  
 -Engine emission system  
 Gauges: DEF level, fuel level, hour  
 meter and tachometer  
 Storage compartment with netting

Adjustable vinyl seat  
 Ergonomic contoured armrest  
 Adjustable joystick controls  
 Control interlock system, when operator  
 leaves seat or armrest raised :  
 -Hydraulic system disables  
 -Hydrostatic transmission disables  
 -Parking brake engages  
 ROPS Cab, open, tilt up  
 Anti-theft security system with 50 user  
 code capability  
 FOPS, Level I  
 Top and rear windows  
 Floor mat  
 Interior rear view mirror  
 12V electric socket  
 Horn  
 Hand (dial) throttle electronic

**FRAMES**

Lift linkage, vertical path  
 Chassis, one piece welded  
 Machine tie down points (4)  
 Belly pan cleanout  
 Support, lift arm  
 Cast rear bumper  
 Ventilated rear door with integrated  
 sealing

**OTHER STANDARD EQUIPMENT**

Engine enclosure - lockable  
 Extended life antifreeze (-37C, -34F)  
 Coupler, mechanical  
 Hydraulic oil level sight gauge  
 Radiator coolant level sight gauge  
 Radiator expansion bottle  
 Cat tough guard hose  
 Heavy duty flat faced quick disconnects  
 with integrated pressure release  
 Split d-Ring to route work tool hoses  
 along side of left lift arm  
 Variable speed hydraulic cooling fan  
 Per SAE J818-2007 and EN 474-3:2006 and  
 ISO 14397-1:2007  
 Rated operating capacity  
 At 50% Tipping Load  
 - 3400 lb (1542 kg)

CATERPILLAR MACHINE PRICE LIST

**272D2**

272D2 SKID STEER LOADER  
 SANFORD, NC, USA

Ship Weight  
 lbs

LIST PRICE  
 AT DEALER

**Lane 2 is reserved for the Base Order Management Program  
 Please use Lane 2 when placing orders that are part of the Base Order  
 Management program**

**522-7489      272D2 SSL DCA1 . . . . . 0      \$71,770**  
 LANE 1 - AVAILABLE FROM SANFORD PDC  
 LANE 2 - AVAILABLE FROM SANFORD FACTORY USING PRIORITY CODE L2  
 LANE 3 - AVAILABLE FROM SANFORD FACTORY USING PRIORITY CODE L2

- INCLUDES:  
 435-8972 272D2 SKID STEER LOADER  
 421-0340 CONVERSION ARRANGEMENT  
 563-1163 CERTIFICATION ARR, P65  
 435-9050 PACKAGE, PERFORMANCE, (H2)  
 485-0411 CONTROL, ISO, PROP  
 435-8943 TWO SPEED  
 435-9153 ROPS, ENCLOSED WITH A/C (C3)  
 345-6359 SEAT,AIR SUSPENSION,CLOTH,HEAT  
 345-6240 DOOR, CAB, GLASS  
 345-6175 RADIO READY  
 465-3705 DISPLAY, ADVANCED, LCD, CAMERA  
 441-4810 BATTERY, XTRA HVY DUTY, DISC  
 258-4095 SEAT BELT, 2"  
 457-3167 FAN, HYDRAULIC, DEMAND  
 345-3556 HEATER, ENGINE BLOCK, 120V  
 515-8592 QUICK COUPLER, HYDRAULIC  
 495-1672 LIGHTS, HALOGEN

NOTE: Please refer to the Lane 1 section to complete your order.

**435-8972      272D2 SKID STEER LOADER . . . . . 0      \$59,870**  
 LANE 2 - AVAILABLE FROM SANFORD FACTORY  
 LANE 3 - AVAILABLE FROM SANFORD FACTORY  
 Available for AM-N, Europe, Turkey, Israel, Puerto Rico, South Korea,  
 Australia & New Zealand

**0P-3616      272D2 MISC MATERIAL . . . . . 0      NC**  
 ONLY AVAILABLE FROM WACO PARTS SERVICE  
 Use this top level reference number only when ordering KITS in CMOPS  
 to be transferred via the bridge to ANTARES Parts Ordering.

Work Tools are sourced via Caterpillar Parts Distribution system.  
 Skid Steer Loader and Work Tools order REQUIRE individual CMOPS  
 order entries. Zeebrugge Distribution Center (ZDC) orders do NOT  
 require individual CMOPS order entries and may include both the  
 machine and work tool orders.

Refer to WT\_SSL price list to order Work Tools.

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	--------	-----------------	----------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS**

(MUST CHOOSE ONE FROM EACH CATEGORY)

**LANE SELECTION**

YOU MUST SELECT THIS REFERENCE WHEN ORDERING FROM THE PDC.

OP-9001	LANE 1 ORDER . . . . .	0	NC
---------	------------------------	---	----

**WARNING DECALS**

L	435-8840	INSTRUCTIONS, ANSI, USA . . . . .	0	NC
		This package includes picto decals as required for USA.		
L	435-8844	INSTRUCTIONS, ISO . . . . .	0	NC
		This package includes picto decals as required for all countries except USA.		

**FILM GROUP SELF LEVEL**

L	435-9238	FILM, SELF LEVEL, ANSI . . . . .	0	NC
L	435-9239	FILM, SELF LEVEL, ISO . . . . .	0	NC

**PRODUCT LINK**

L	441-4818	PRODUCT LINK, CELLULAR PL240 . . . . .	0	NC
		Product Link Basic series PL240 offers expanded coverage including 3G UMTS and HSPA+ as well as 2G GSM and GPRS cellular networks to transmit hour and location informatin for viewing in Product Link's remote monitorin web interface. The data is updated up to 4 times per day while the engine is running. ONLY FOR USE WITH: US Dealers		
L	515-3153	PRODUCT LINK, CELLULAR PL240 . . . . .	0	NC
		Product Link Basic series PL240 uses cellular networks to transmit hour and location information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent data transmission. ONLY FOR USE WITH: Canada		

**TIRES**

P	345-5498	TIRES, 12/16.5 CAT 10PR . . . . .	0	\$461
		Caterpillar;Bias;Directional chevron tread pattern; Tread Depth=21mm (26/32") 1830mm (72") wide Premium conventional heavy duty tire provides excellent traction in a variety of conditions. Deepest tread available results in long service life. Extra heavy sidewall construction protects against abrasion, tears and impact damage. Includes valve stem protection.		

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	--------	-----------------	----------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS (CONT.)**

**SERVICE INSTRUCTIONS**

421-8926	<b>SERIALIZED TECHNICAL MEDIA KIT</b> . . . . . 0	<b>NC</b>
	The technical media kit will include the Operations & Maintenance Manual (OMM) and other media specified on the Factory Notification List required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary. Any additional media or translations not included in the kit, should be ordered through publications.cat.com	

**PACKING**

OP-1176	<b>CAROLINA CDC -- AVAILABILITY</b> . . . . . 0	<b>\$1 NET</b>
---------	---	----------------

**PROTECTION**

OP-2266	<b>SHIPPING/STORAGE PROTECTION</b> . . . . . 0	<b>\$207 NET</b>
	Provides protective application of Fluid Film TM for protection while shipping and for extended storage periods. If desired, this product can be power washed with warm soapy water prior to shipment to the customer.	

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**LANE SELECTION**

0P-9002	LANE 2 ORDER . . . . .	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		
0P-9003	LANE 3 ORDER . . . . .	0	NC

**REGIONAL PACKAGES**

**CONVERSION ARRANGEMENTS**

L	421-0340	CONVERSION ARRANGEMENT . . . . . FOR USE WITH: ADSD-N, APD	0	NC
---	----------	---	---	----

**CERTIFICATION ARRANGEMENTS/YEAR OF MANUFACTURE**

L	563-1163	CERTIFICATION ARR, P65 . . . . . REQUIRED for US	0	NC
---	----------	---	---	----

**WARNING DECALS**

L	435-8840	INSTRUCTIONS, ANSI, USA . . . . . This package includes picto decals as required for USA.	0	NC
---	----------	--	---	----

**PERFORMANCE PACKAGES**

**HYDRAULIC PERFORMANCE PACKAGES**

L	435-8908	PACKAGE, PERFORMANCE, (H1) . . . . . All of the following are included in this package: Standard Flow - 23 gpm (87 lpm) Self Level, None Hydraulic Controls - Standard Flow (Must select one below)	0	NC
L	435-9050	PACKAGE, PERFORMANCE, (H2) . . . . . All of the following are included in this package: Standard Flow - 23 gpm (87 lpm) Dual Self Level Hydraulic Controls - Standard Flow (Must select one below)	0	\$905
L	435-8909	PACKAGE, PERFORMANCE, (H3) . . . . . All of the following are included in this package: High Flow XPS - 32 gpm (120 lpm) Dual Self Level Hydraulic Controls - High Flow (Must select one below)	0	\$4,525

**FILM GROUP SELF LEVEL**

L	435-9238	FILM, SELF LEVEL, ANSI . . . . . REQUIRED WHEN SELECTING H2 OR H3 PERFORMANCE PACKAGE	0	NC
---	----------	--	---	----

**HYDRAULIC CONTROLS**

**Standard Flow (FOR USE WITH H1 & H2)**

L	485-0410	CONTROL, ISO, ON/OFF . . . . . Cannot be used with H3. Provides ISO joystick controls and electronic foot throttle pedal with decel pedal functionality	0	\$226
---	----------	--	---	-------

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**PERFORMANCE PACKAGES (CONT.)**

**HYDRAULIC CONTROLS (Cont.)**

L	485-0411	<b>CONTROL, ISO, PROP</b> ..... 0 Cannot be used with H3. Provides ISO joystick controls (4 button left hand joystick) and electronic foot throttle pedal with decel pedal functionality		\$435
L	485-0418	<b>CONTROL, ISO, PROP, WT</b> ..... 0 Cannot be used with H3. Provides ISO joystick controls (4 button left hand joystick) and electronic foot throttle pedal with decel pedal functionality. Also includes 14 pin Work Tool electrical harness.		\$775

**High Flow (FOR USE WITH H3 ONLY)**

L	485-0417	<b>CONTROL, ISO, PROP, WT</b> ..... 0 For use with H3 Only. Provides ISO joystick controls (4 button left hand joystick - Thumb roller with 2 button right hand joystick) and 14 pin Work Tool electrical harness. Also includes electronic foot throttle pedal with decel pedal functionality.		\$880
---	----------	--	--	-------

**POWERTRAIN**

L	435-8942	<b>ONE SPEED</b> ..... 0		NC
L	435-8943	<b>TWO SPEED</b> ..... 0		\$2,060
L	435-8944	<b>TWO SPEED WITH RIDE CONTROL</b> ..... 0		\$3,105

**FILM GROUP RIDE CONTROL**

L	422-3445	<b>FILM, RIDE CONTROL, ANSI</b> ..... 0 REQUIRED WHEN SELECTING RIDE CONTROL		NC
---	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**FEATURE PACKAGES**

**COMFORT PACKAGES**

L	435-9150	ROPS, OPEN (C0) . . . . . 0		NC
		All of the following are included in this package: Seat, Static, Vinyl Cab Mounted Controls, Adjustable (hand tool required) Headliner, None		
L	435-9151	ROPS, OPEN (C1) . . . . . 0		\$438
		All of the following are included in this package: Deluxe Headliner & rear post trim covers Cup Holder Seat (Must select one below)		
L	435-9152	ROPS, ENCLOSED WITH HEAT (C2) . . . . . 0		\$2,845
		All of the following are included in this package: Deluxe Headliner & post trim covers Cup Holder Side Windows Heater and Defroster Seat (Must select one below) Door (Must select one below)		
L	435-9153	ROPS, ENCLOSED WITH A/C (C3) . . . . . 0		\$4,895
		All of the following are included in this package: Deluxe Headliner & post trim covers Cup Holder Side Windows Air Conditioner Including Heater/Defroster Seat (Must select one below) Door (Must select one below)		

**SEAT**

Must select ONE if a C1, C2 or C3 cab package was selected above.

L	345-6329	SEAT, SUSPENSION, VINYL . . . . . 0		\$359
		Includes: Cab Mounted Controls, Adjustable (hand tool required) For Use With: C1, C2 and C3 Cab Package		
L	345-6349	SEAT,AIR SUSPENSION,VINYL,HEAT . . . . . 0		\$780
		High back heated seat with recline, lumbar support, and Fully Adjustable Seat Mounted Controls. For Use With: C1, C2 and C3 Cab Package		
L	345-6359	SEAT,AIR SUSPENSION,CLOTH,HEAT . . . . . 0		\$805
		High back heated seat with recline, lumbar support, and Fully Adjustable Seat Mounted Controls. For Use With: C2 and C3 Cab Package		

**DOOR**

Must select ONE if an Enclosed ROPS was selected above.

P	345-6240	DOOR, CAB, GLASS . . . . . 0		\$108
P	345-6260	DOOR, CAB, POLYCARBONATE . . . . . 0		\$214

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**FEATURE PACKAGES (CONT.)**

**RADIO**

Bluetooth radio technology enables the use of a hands free function such as listening to music and making phone calls. Authorization varies by country, please contact your Cat marketing representative with questions or click on the link below: <https://dealer.cat.com/en/products/technology.html>

Selection of ONE required for C2 or C3 Comfort Package

L	345-6175	<b>RADIO READY</b> . . . . . 0 Provides Speakers, Wiring, Radio Box, Antenna & Cable, and hardware required to install a single DIN radio.		<b>\$154</b>
L	345-6180	<b>RADIO, AM/FM, BLUETOOTH</b> . . . . . 0 Provides factory installed radio: Includes Bluetooth interface, microphone, and auxiliary inputs (USB port and aux input jack) to connect external audio devices.		<b>\$510</b>

**ADVANCED MACHINE CONTROL**

L	465-3705	<b>DISPLAY, ADVANCED, LCD, CAMERA</b> . . . . . 0 Includes: Full color 5 in. LCD screen with digital gauge display. Provides Creep control, Hystat response adjustment, Implement response adjustment, DEF gauge, Fuel gauge, Hydraulic temperature gauge, Engine coolant gauge, Tachometer, Language selection and Advanced multi-operator Anti-theft Security System and Monitoring. Also provides USB charging port. Note: Rear camera installed. Anti-Theft Security System feature will ship from factory installed but disabled.		<b>\$1,140</b>
---	----------	--	--	----------------

**STARTERS, BATTERIES, & ALTERNATORS**

**BATTERIES**

L	465-3696	<b>BATTERY, 850 CCA, HEAVY DUTY</b> . . . . . 0 CANNOT BE USED WITH: EU Dealers		<b>NC</b>
L	441-4811	<b>BATTERY, HEAVY DUTY, DISC</b> . . . . . 0 850 CCA with Battery Disconnect Switch		<b>\$125</b>
L	441-4810	<b>BATTERY, XTRA HVY DUTY, DISC</b> . . . . . 0 1000 CCA with Battery Disconnect Switch Recommended for cold weather starting.		<b>\$205</b>

**OPERATOR ENVIRONMENT**

**LIGHTS**

L	495-1672	<b>LIGHTS, HALOGEN</b> . . . . . 0 Two (2) forward facing adjustable halogen work lights (cab mounted) and two (2) rear facing halogen work lights (frame mounted).		<b>NC</b>
L	495-1671	<b>LIGHTS, LED</b> . . . . . 0 Two (2) forward facing adjustable LED work lights (cab mounted) and two (2) rear facing LED work lights (frame mounted). LED lighting advantages vs halogens: brighter work site illumination, cooler, more resistant to vibration and longer life.		<b>\$279</b>



CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**OPERATOR ENVIRONMENT (CONT.)**

**SEAT BELTS**

L	258-4095	SEAT BELT, 2" . . . . .	0	NC
L	258-4096	SEAT BELT, 3" . . . . . Required in California.	0	\$142

**TECHNOLOGY PRODUCTS**

**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	441-4818	PRODUCT LINK, CELLULAR PL240 . . . . . Product Link Basic series PL240 uses cellular networks to transmit hour and location information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent data transmission.	0	NC
L	441-4819	PRODUCT LINK, CELLULAR PL641 . . . . . Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data.	0	\$833

**COOLING**

**COOLING FAN**

L	457-3167	FAN, COOLING, DEMAND . . . . . Provides variable speed hydraulic cooling fan. Sensors monitor machine cooling requirements to modulate the fan speed providing "on demand" cooling.	0	NC
L	457-2835	FAN, COOLING, DEMAND, REVERSING . . . . . Reversing Fan provides automatic and manual purge modes to assist in removing material from the rear door intake screen. Provides both Demand Fan and Reversing Fan functionality.	0	\$840

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**TIRES, RIMS, AND WHEELS**

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice. However, if the tire type cannot be supplied we will contact the dealer to propose alternatives. The dealer needs to choose between an alternative tire or a "rims only" option (where available) within 72 hours. If no response is provided by the deadline, the order will default to the alternative tire and will be changed at that point. As a consequence of a possible tire change, the total machine price will be decreased or increased depending on the price of the new tire.

**1676mm (66") Width**

P	345-5521	<b>TIRES, 12X16.5 CAT 14PR XD</b> . . . . . 0 Caterpillar;XD;Tread Depth=35mm (44/32");1676mm (66") wide Provides very deep tread, ultra heavy sidewalls and extra large rim guards. Ideal for concrete & demolition work, quarries and asphalt recycling. Tread depth is 40% deeper than CAT Premium Conventional Tires. The XD tire features a special tread compound for long wear and durability. Includes valve stem protection.		\$1,280
P	345-5515	<b>TIRES, 12/16.5 GA 10PR</b> . . . . . 0 Galaxy;Bias;"Beefy Baby";1676mm (66") wide Designed with extra side wall strength to protect against punctures and abuse. Extra wide lug bar and deep tread give good traction in soft conditions. Includes valve stem protection.		\$750
P	345-5497	<b>TIRES, 12/16.5 CAT 10PR</b> . . . . . 0 Caterpillar;Bias;Directional chevron tread pattern; Tread Depth=21mm (26/32");1676mm (66") wide Premium conventional heavy duty tire provides excellent traction in a variety of conditions. Deepest tread available results in long service life. Extra heavy sidewall construction protects against abrasion, tears and impact damage. Includes valve stem protection.		\$461

**1830mm (72") Width**

P	345-5525	<b>TIRES, 33X6X11 CAT FLEX SOLID</b> . . . . . 0 Caterpillar Flexport;Extreme Duty;Directional chevron tread pattern; Tread Depth=58mm (75/32");1830mm (72") wide The Flexport design incorporates a series of holes molded through the outer ring of the sidewall. The result is a stable and more cushioned ride while maintaining the benefits of a solid tire. Extra large lugs and deep tread depth mean excellent traction on improved and unimproved surfaces. The rubber tire and steel rim are a one-piece bonded assembly, and replaced as a single unit. No specialized tire service is ever required.		\$3,375
P	345-5522	<b>TIRES, 12X16.5 CAT 14PR XD</b> . . . . . 0 Caterpillar;XD;Tread Depth=35mm (44/32");1830mm (72") wide Provides very deep tread, ultra heavy sidewalls and extra large rim guards. Ideal for concrete & demolition work, quarries and asphalt recycling. Tread depth is 40% deeper than CAT Premium Conventional Tires. The XD tire features a special tread compound for long wear and durability. Includes valve stem protection.		\$1,280

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**TIRES, RIMS, AND WHEELS (CONT.)**

**1830mm (72") Width (Cont.)**

P	345-5514	TIRES, 12/16.5 GA 10PR . . . . . 0 Galaxy;Bias;"Beefy Baby";1830mm (72") wide Designed with extra side wall strength to protect against punctures and abuse. Extra wide lug bar and deep tread give good traction in soft conditions. Includes valve stem protection.		\$750
P	345-5498	TIRES, 12/16.5 CAT 10PR . . . . . 0 Caterpillar;Bias;Directional chevron tread pattern; Tread Depth=21mm (26/32") 1830mm (72") wide Premium conventional heavy duty tire provides excellent traction in a variety of conditions. Deepest tread available results in long service life. Extra heavy sidewall construction protects against abrasion, tears and impact damage. Includes valve stem protection.		\$461

**1880mm (74") Width**

P	331-2488	TIRES, 14X17.5 CAT 14PR XD . . . . . 694 Caterpillar;XD;Tread Depth=37mm (47/32");1880mm (74") wide Provides very deep tread, ultra heavy sidewalls and extra large rim guards. Ideal for concrete & demolition work, quarries and asphalt recycling. Tread depth is 43% deeper than CAT Premium Conventional Tires. The XD tire features a special tread compound for long wear and durability. Includes valve stem protection. CANNOT BE USED WITH: Over the Tire Steel Tracks		\$2,495
---	----------	---	--	---------

**76" (1930mm) Width**

P	331-2490	TIRES, 14/17.5 CAT 14PR . . . . . 774 Caterpillar;Bias;Directional chevron tread pattern; Tread Depth=21mm (26/32") 1930mm (76") wide Premium conventional heavy duty tire provides excellent traction in a variety of conditions. Deepest tread available results in long life. Extra heavy sidewall construction protects against abrasion, tears and impact damage. Includes valve stem protection. CANNOT BE USED WITH: Over the Tire Steel Tracks		\$1,950
---	----------	--	--	---------

**QUICK COUPLERS**

L	345-4910	QUICK COUPLER, MANUAL . . . . . 0		NC
L	515-8592	QUICK COUPLER, HYDRAULIC . . . . . 0		\$995

CATERPILLAR MACHINE PRICE LIST

**272D2**

---

USE	REF NO.	<b>LANE 2 / 3 MANDATORY</b>	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	-----------------------------	--------------------	-------------------------

---

**INSTRUCTIONS**

***SERVICE INSTRUCTIONS***

421-8926	<b>SERIALIZED TECHNICAL MEDIA KIT . . . . . 0</b> The technical media kit will include the Operations & Maintenance Manual (OMM) and other media specified on the Factory Notification List required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary. Any additional media or translations not included in the kit, should be ordered through publications.cat.com	<b>NC</b>
----------	--	-----------

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**SPECIAL ARRANGEMENTS**

C	OP-0528	<b>PAINT, CUSTOM</b> . . . . . 0 FOR USE IN LANE 3 ONLY Paint specification (RAL #) required. Advise via MSO notes. Custom paint order provides a SINGLE COLOR, non-metallic, high gloss custom finish. Once a custom paint order is placed, it may not be cancelled. Custom paint extends availability from what is published. Contact the factory for current availability information.  Note 1: Florescent colors and matte finishes are not available. Note 2: Some components will NOT receive the custom paint color. The engine and items not externally visible will be painted yellow. CTLs with the optional steel track undercarriage will be provided with a black track. Cylinders, cab, coupler, radiator grill and the MTL undercarriage will be painted black.		<b>\$1,860 NET</b>
---	---------	---	--	--------------------

**ELECTRICAL**

L	309-1325	<b>ROTATING BEACON</b> . . . . . 0 Magnetic base, mounted to top of cab. Operates when key switch is in "On" position.		<b>\$216</b>
---	----------	---	--	--------------

**OTHER ATTACHMENTS**

L	345-5234	<b>RETURN TO DIG/WRKTL POSITIONER</b> . . . . . 0 Self Level enabled RTD/WT positioner Return to Dig automatically lowers lift arms and returns work tool to preset angle. Work Tool positioner automatically returns work tool to present angle. Requires H2 or H3 performance package		<b>\$288</b>
L	345-5148	<b>COUNTERWEIGHT, MACHINE, EXTERNAL</b> . . . . . 0 Includes external weights bolted to the frame tower. Suggested for applications where additional rated operating capacity (ROC) is needed. Machine ROC increased by 250 lbs (113 kg).		<b>\$1,030</b>
L	345-3556	<b>HEATER, ENGINE COOLANT, 120V</b> . . . . . 0 120 Volt - For additional cold weather startability.		<b>\$195</b>
L	457-1215	<b>LIFTING EYES, FOUR POINT</b> . . . . . 0 Included in EU Conversion Arrangement CANNOT BE USED WITH: TANK, WATER		<b>\$192</b>
L	563-7518	<b>MOUNTING, FIRE EXTINGUISHER</b> . . . . . 0 Provides in-cab mounting bracket that can accommodate up to a 5 lb. fire extinguisher.		<b>\$200</b>

**WORK TOOLS**

To view and order all available Work Tool Selections refer to WT-SSL or WT-HAMR price lists.  
 NOTE: Work Tools, except Hammers, are sourced via Caterpillar parts distribution system.  
 CMOPS orders for Skid Steer Loaders and Work Tools MUST be ordered separately.

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FLUIDS**

L	418-9011	<b>OIL, HYDRAULIC, COLD OPERATION</b> . . . . . 0 Recommended for use in hydraulic system where ambient temperatures are below 32 F (0 C).		<b>\$665</b>
---	----------	---	--	--------------

**FIELD INSTALLED ATTACHMENTS**

*Available Through Parts Distribution.*

- 345-6070 KIT, FOPS, LEVEL 2**  
 Falling Object Protective Structure level 2. Provides additional overhead protection. Recommended for use in demolition applications. Not compatible with the roof mounted Auxiliary Hydraulic Cooler. Meets ISO 3449: 1992  
 Note: The part number provided is for reference only. Individual parts must be ordered. Please reference REHS8703 for parts list and installation instructions.
- 474-5632 KIT, SINGLE POINT LIFT**  
 Contains parts that attach to cab roof and allow machine to be lifted from a single point. The part number provided is for reference only. Individual parts must be ordered. Please reference REHS9970 for parts list and installation instructions.
- 418-5883 KIT, FOPS LEVEL 2 W/ 4 PT LIFT**  
 This kit combines the Falling Object Protective Structure level 2 and 4 point lifting functionality. Recommended for use in applications where additional overhead protection and 4 point lifting are both desired (ex. demolition).  
 Note: The part number provided is for reference only. Individual parts must be ordered. Please reference REHS9989 for parts list and installation instructions.

The RETURN TO DIG/WRKTL POSITIONER feature is available as a Software Enabled Attachment (SEA) and is installed using Electronic Technician and a unique password. Cost to enable the feature via password is approximately \$221 USD Dealer Net (January, 2016). Machine must be equipped with the Electronic Self Level feature, provided in the H2 or H3 performance package to install the SEA.

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

***Available Through Parts Distribution. (Cont.)***

**DEDICATED ALTERNATE PATTERN (H-pattern):**

As of January 2018, this feature is standard from the factory. There is no cost. Using Electronic Technician the dealer can configure the machine to operate using the alternative "H" control pattern. With this feature there is no method to allow the operator to change the pattern in the cab. Refer to media number REHS8719.

**SELECTABLE PATTERN CONTROL (ISO/H patterns):**

This feature is a Software Enabled Attachment (SEA) and is installed using Electronic Technician and a unique password. The SEA cost to enable the feature via password is approximately \$250 USD Dealer Net (January, 2018). Allows an operator to select either standard CAT control pattern or the alternative "H" control pattern with the flip of a switch. Estimated time to install: 30 min.

Refer to media number REHS8718 for appropriate parts list.

The components required are available for order from the Parts Department.

***Available Through ANTARES Parts Ordering.***

**NOTE: US & Canada ONLY may place orders in CMOPS to be transferred via the bridge to ANTARES Parts Ordering.**

**When ordering via CMOPS include top level reference numbers (OP-2740) and OP number for packing.**

435-9149	KIT, CAMERA REAR VIEW . . . . . 0 For proper installation, refer to media number REHS9988. Note: Requires Advanced Display Estimated time to install: 1 hour 30 minutes	\$457 NI
484-8211	KIT, BATTERY DISCONNECT . . . . . 0 For proper installation, refer to media number SEHS0193. Provides components needed to install a battery disconnect switch. Estimated time to install: 30 minutes	\$125 NI
504-1553	KIT, LICENSE PLATE . . . . . 0  For proper installation, refer to media number M0067678. Estimated time to install: 30 minutes	\$51 NI NET
499-2684	KIT, LIGHTS, LED . . . . . 0 For proper installation, refer to media number M0066104. Includes two (2) forward facing adjustable work lights (cab mounted) and two (2) rear facing LED work lights (frame mounted). LED lighting advantages vs halogens: brighter work site illumination, cooler, more resistant to vibration and longer life. Estimated time to install: 1 hour	\$350 NI
388-8285	KIT, FOOT THROTTLE . . . . . 0 For proper installation, refer to media number REHS8712. Estimated time to install: 1 hour 30 minutes	\$331 NI

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering. (Cont.)*

388-7875	KIT, COUNTERWEIGHT, 100 LB ROC . . . . . 0	\$519 NI
	Kit provides one counterweight per side which increases the Rated Operating Capacity by approximately 100-125 lbs (46 - 57 kg), depending on model. For maximum ROC increase, must order quantity of (2) 388-7875 kits. Includes Mounting hardware for both one counterweight per side configuration and two counterweights per side configuration. Estimated time to install: 30 minutes	
388-8275	KIT, WINDOW, SIDES . . . . . 0	\$683 NI
	For proper installation, refer to media number REHS8707. Estimated time to install: 1 hour	
514-9093	KIT, DOOR, CAB, POLYCARBONATE . . . . . 0	\$1,785 NI
	For proper installation, refer to media number M0073170. Estimated time to install: 1.5 hours	
422-3297	KIT, DOOR, CAB, GLASS . . . . . 0	\$1,003 NI
	For proper installation, refer to media number REHS9992. Estimated time to install: 1.5 hours	
508-1866	KIT, AIR CONDITIONER (HTR/DFR) . . . . . 0	\$3,051 NI
	For proper installation, refer to media number M0070248. Estimated time to install: 8 hours 30 minutes	
435-9232	KIT, AIR CONDITIONER (CONVRN) . . . . . 0	\$2,015 NI
	For proper installation, refer to media number REHS9982. Estimated time to install: 7 hours	
435-9231	KIT, HEATER . . . . . 0	\$1,211 NI
	For proper installation, refer to media number REHS9981. Estimated time to install: 7 hours	
527-3155	KIT, QUICK COUPLER, HYDRAULIC . . . . . 0	\$1,078 NI
	For proper installation refer to media number M0081347. Estimated time to install: 12 hours	
513-5126	KIT, GUARD, COUPLER . . . . . 0	\$199 NI
	For proper installation, refer to media number M0072576. Provides lower guard that restricts material/debris from entering the underside of the coupler area giving additional safeguarding for electrical components. Estimated time to install: 30 minutes	
388-8265	KIT, WT ELECTRICAL CONTROL . . . . . 0	\$193 NI
	For proper installation, refer to media number REHS7806. Includes Work Tool Electrical switch, harness, connector and mounting hardware. Estimated time to install: 2 hours	
388-8273	KIT, WT ELECTRICAL CONTROL, DLX . . . . . 0	\$696 NI
	For proper installation, refer to media number REHS7814. Includes: Work Tool Electrical switch, harness, connector, mounting hardware and 4 button Left Hand Joystick. Estimated time to install: 3 hours	



CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering. (Cont.)*

523-4908	<b>KIT, DUAL SELF LEVEL</b> . . . . . 0			<b>\$750 NI</b>
	For proper installation, refer to media number M0077274. Estimated time to install: 2 hours 45 minutes Note: Not compatible with H2 or H3 Performance Packages.			
481-0031	<b>KIT, RIDE CONTROL</b> . . . . . 0			<b>\$1,038 NI</b>
	For proper installation, refer to media number SEHS0156. Estimated time to install: 3 hours			
435-9237	<b>KIT, FAN, DEMAND, REVERSING</b> . . . . . 0			<b>\$857 NI</b>
	For proper installation, refer to media number REHS6604. Reversing Fan provides automatic and manual purge modes to assist in removing material from the rear door intake screen. Provides both Demand Fan and Reversing Fan functionality. Estimated time to install: 1.5 hours			
388-8283	<b>KIT, RADIO, READY</b> . . . . . 0			<b>\$149 NI</b>
	For proper installation, refer to media number REHS8710. Provides Speakers, Wiring, Radio Box, Antenna & Cable, and hardware required to install a single DIN radio. Estimated time to install: 1 hour			
388-8286	<b>KIT, RADIO, AM/FM/BLUETOOTH</b> . . . . . 0			<b>\$571 NI</b>
	For proper installation, refer to media number REHS8705. Includes radio with Bluetooth interface, microphone and auxiliary inputs (USB port and aux input jack) to connect external audio devices. Requires: Radio Ready operator station. Estimated time to install: 45 minutes			
498-6622	<b>KIT, DEBRIS</b> . . . . . 0			<b>\$1,874 NI</b>
	For proper installation, refer to media number M0067498. This kit provides additional components for customers in debris intensive applications that restrict debris and other material from entering the engine compartment and the lower machine frame. Provided are various seals and covers that are designed to cover the openings that exist between the frame/body/cab of the machine as well as a fuel strainer and an exhaust stack cover. The Debris Kit is required in applications where airborne debris is present and should be used in conjunction with the Turbo Debris Guard kit. Note: If additional component guarding is required, please refer to the Guarding Kit. Estimated time to install: 10 hours			
472-2965	<b>KIT, GUARDING</b> . . . . . 0			<b>\$640 NI</b>
	For proper installation, refer to media number REHS9959. This kit provides additional guarding for customers in demanding applications where extra safeguarding is required. This kit provides guarding for the front work lights, rear work lights, auxiliary hydraulic connections, work tool electrical harness connection and work tool coupler area. Note: If additional debris guarding is required, please refer to the Debris Kit. Estimated time to install: 1.5 hours			

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering. (Cont.)*

421-0219	<b>KIT, A/C BREATHER</b> . . . . . 0			<b>\$456 NI</b>
	For proper installation, refer to media number M0068026. This kit provides increased cab air filter life for machines used in dusty or high airborne debris applications. Kit contains duct work and hardware required to relocate the cab fresh air intake to a higher location near the roof of the cab. Estimated time to install: 30 minutes			
444-6050	<b>KIT, TURBO DEBRIS GUARD</b> . . . . . 0			<b>\$285 NI</b>
	For proper installation, refer to media number REHS9969. This kit contains steel mesh guards that are designed to cover the exhaust manifold and turbocharger to assist in deterring the collection of material on these components. The Turbo Guard kit is required in applications where airborne debris is present and should be used in conjunction with the Debris Kit. Estimated time to install: 1 hour 30 minutes			
416-5965	<b>KIT,ENG AIR INTAKE, PRECLEANER</b> . . . . . 0			<b>\$466 NI NET</b>
	For proper installation, refer to media number REHS8735. Turbine-type precleaner for the engine air filter. For use in high dust/debris applications. Estimated time to install: 1 hour			
422-3323	<b>KIT, FRONT ROADING LIGHTS</b> . . . . . 0			<b>\$468 NI</b>
	Includes front roading lights and 2 lift arm mounted mirrors. For proper installation, refer to media number REHS7836. Mandatory for Road Homologation in Italy and Germany. Estimated time to install: 4 hours			
422-3322	<b>KIT, LIGHTS, REAR, ROADING</b> . . . . . 0			<b>\$232 NI</b>
	For proper installation, refer to media number REHS8748. This kit provides Rear Roading light components (rear reflectors, brake lamps, directional indicators/turn signals, hazard lights) in order to meet roading requirements for Italy. Estimated time to install: 1.5 hours			
512-0356	<b>KIT, LIGHTS, REAR, WIDE MOUNT</b> . . . . . 0			<b>\$429 NI</b>
	For proper installation, refer to media number M0071898. This kit provides components that allows the rear lights to be relocated to mounting locations on the sides of the rear frame. Estimated time to install: 30 minutes REQUIRED for Italy Roading			
421-0274	<b>KIT, LIFTING EYES, FOUR POINT</b> . . . . . 0			<b>\$229 NI</b>
	For proper installation, refer to media number REHS9993. Estimated time to install: 30 minutes CANNOT BE USED WITH: TANK, WATER			
422-3241	<b>KIT, PROD LINK, CELLULAR PL641</b> . . . . . 0			<b>\$1,024 NI</b>
	For proper installation, refer to media number REHS9952 Product Link Pro series PL641 uses GSM and CDMA 3G cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data. Estimated time to install: 2.5 hours			

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

*Available Through ANTARES Parts Ordering. (Cont.)*

482-5132	<b>KIT, WATER TANK, 42 US GAL, D</b> . . . . . 0	<b>\$1,817 NI</b>
	Mounted to top of cab 42 gallon capacity Includes tank, pump, filter, lines, mounting brackets and quick disconnect For proper installation, refer to media number SEHS0363. Estimated time to install: 9 hours 30 minutes For use with Water Sprinkler Kits for Angle Broom, Pick Up Broom, Utility Broom or Cold Planer	
	CANNOT BE USED WITH: Four Point Lifting Eyes kit, Single Point Lift kit or Auxiliary Hydraulic Cooler kit	
527-2335	<b>KIT, REMOTE GREASE (COUPLER)</b> . . . . . 0	<b>\$222 NI</b>
	For proper installation, refer to media number M0084651. Provides remote location for lubrication of the work tool coupler pins Estimated time to install: 3 hours	
541-3141	<b>KIT, WINTER, REAR DOOR COVER</b> . . . . . 0	<b>\$256 NI</b>
	Required for operating in temperatures below -32C (-25F). For proper installation refer to media number REHS8737. Provides rear door cover to minimize air flow into the engine compartment. Estimated time to install: 1.0 hour	

**NO RETURNS accepted for kit components not used or for parts removed from machine during kit installation.**

**Shipments will be within 3 - 5 working days of order receipt for delivery by dealer parts stocking truck to dealer stocking facility.**

CATERPILLAR MACHINE PRICE LIST

**272D2**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

**ENDORSED FIELD INSTALLED ATTACHMENTS**

Caterpillar does not warrant, service, or assume responsibility for these attachments.

All orders, pricing confirmation, and other communication for these attachments must be directed to the listed manufacturer.

**REMOTETASK TM - REMOTE CONTROL SYSTEM**

Complete system for use with CAT D Series Skid Steer, Multi Terrain, and Compact Track Loaders. Allows the operator to precisely control the machine from outside the cab. Line-of-sight remote control with an approximate range of 1000 feet (300 meters). Dealer installed remote control system includes the Remote Task controller and necessary hardware to convert standard D series SSL, MTL or CTL to remote controlled machine.

NOTE: Certified for use in North America. To verify certification in other regions, please contact BCP Attachments Team.  
 Email: bcp\_work\_tools@cat.com

Orders for the remote control system must be placed directly from:

TORC Robotics, Inc.  
 Tel. +1(800) 530-9285, +1(540) 443-9262  
 Email: sales@torcrobotics.com

**PACKING**

**DOMESTIC PACKING**

0P-0210	PACK, DOMESTIC TRUCK . . . . .	0	NC
---------	--------------------------------	---	----

**Only to be used when ordering kits via CMOPS.**

0P-2162	PACKING, KIT . . . . .	0	NC
---------	------------------------	---	----

**PROTECTION**

0P-2266	<b>SHIPPING/STORAGE PROTECTION . . . . .</b>	0	<b>\$207 NET</b>
	Provides protective application of Fluid Film TM for protection while shipping and for extended storage periods. If desired, this product can be power washed with warm soapy water prior to shipment to the customer.		
0P-6439	<b>CORROSION INHIBITOR . . . . .</b>	0	<b>\$1,940</b>
	EquipCoat is a flexible protective coating with anti-corrosion additives that encapsulate machine surfaces, including components under the cab and in the engine compartment. Will hold up to washing with non-solvent based cleaners for long-term corrosion resistance. Recommended for machines exposed to corrosive environments(e.g.manure, fertilizer, salt, mining fluids, etc.).		