

CATERPILLAR MACHINE PRICE LIST

297D2

297D2 MULTI TERRAIN LOADER
 SANFORD, NC, USA

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

Cat C3.8 turbo aftercooled diesel engine
 -Gross horsepower per SAE J1349
 98 hp (73 kW) @ 2400 RPM
 -EPA Tier 4 Final and EU Stage IV
 certified with aftertreatment
 -Electric fuel priming pump
 -Air inlet heater starting aid
 -Liquid cooled, direct injection
 Air cleaner, dual element, radial seal
 S-O-S sampling valve, hydraulic oil
 Filter, cartridge type, hydraulic
 Filters, cartridge type, fuel
 and water separator
 Radiator/hydraulic oil
 Cooler (side-by-side)
 Spring applied, hydraulically released,
 wet multi disc parking brakes
 Hydrostatic transmission

UNDERCARRIAGE

Rubber track 18 in (457 mm)
 Suspension - independent torsion axle
 and oscillating bogie wheels
 Two speed motor

HYDRAULICS

Standard flow auxiliary hydraulics with
 continuous flow
 CONTROLS:
 Electro/hydraulic implement control
 Electro/hydraulic hydrostatic
 transmission control

ELECTRICAL

12 volt electrical system
 100 ampere alternator
 Ignition key start / stop / aux switch
 Lights:
 -Gauge backlighting
 -Two rear tail lights
 -Dome light
 Backup alarm
 Electrical outlet, beacon

OPERATOR ENVIRONMENT

Operator warning system indicators:
 -Air filter restriction
 -Alternator output
 -Armrest raised / operator out of seat
 -Engine coolant temperature
 -Engine oil pressure
 -Air inlet heater activation
 -Hydraulic filter restriction
 -Hydraulic oil temperature

-Park brake engages
 -Engine emission system
 Gauges: DEF level, fuel level,
 hour meter and tachometer
 Storage compartment with netting
 Adjustable vinyl seat
 Ergonomic contoured armrest
 Adjustable joystick controls
 Control interlock system, when operator
 leaves seat or armrest raised :
 -Hydraulic system disables
 -Hydrostatic transmission disables
 -Parking brake engages
 ROPS Cab, open, tilt up
 FOPS, Level I
 Anti-theft security system with 50 user
 code capability
 Top and rear windows
 Floormat
 Interior rear view mirror
 12V electric socket
 Horn
 Hand (dial) & throttle electronic

FRAMES

Lift linkage, vertical path
 Chassis, one piece welded
 Machine tie down points (4)
 Belly pan cleanout
 Support, lift arm
 Cast rear bumper
 Ventilated rear door with integrated
 sealing

OTHER STANDARD EQUIPMENT

Engine enclosure - lockable
 Extended life antifreeze (-37C, -34F)
 Coupler, mechanical
 Hydraulic oil level sight gauge
 Radiator coolant level sight gauge
 Radiator expansion bottle
 Cat tough guard hose
 Heavy duty flat faced quick disconnects
 with integrated pressure release
 Split d-ring to route work tool hoses
 along side of left lift arm
 Variable speed hydraulic cooling fan
 Per SAE J818-2007 and EN 474-3:2006 and
 ISO 14397-1:2007
 Rated Operating Capacity:
 At 50% Tipping Load - 4700 lb (2132 kg)
 At 35% Tipping Load - 3290 lb (1492 kg)

CATERPILLAR MACHINE PRICE LIST

297D2

297D2 MULTI TERRAIN LOADER SANFORD, NC, USA	Ship Weight lbs	LIST PRICE AT DEALER
--	--------------------	-------------------------

**Lane 2 is reserved for the Base Order Management Program
 Please use Lane 2 when placing orders that are part of the Base Order
 Management program.**

**2018 YOY list price reductions will be offset by reductions in
 discounts or merchandising support.**

435-8997	297D2 MULTI TERRAIN LOADER 0 LANE 2 - AVAILABLE FROM SANFORD FACTORY Available for AM-N, Europe, Turkey, Israel, Puerto Rico, Australia & New Zealand	\$95,730
----------	---	-----------------

0P-3618	297D2 MISC MATERIAL 0 ONLY AVAILABLE FROM WACO PARTS SERVICE Use this top level reference number only when ordering KITS in CMOPS to be transferred via the bridge to ANTARES Parts Ordering.	NC
---------	---	-----------

Work Tools are sourced via Caterpillar Parts Distribution system.
 Skid Steer Loader and Work Tools order REQUIRE individual CMOPS
 order entries. Zeebrugge Distribution Center (ZDC) orders do NOT
 require individual CMOPS order entries and may include both the
 machine and work tool orders.

Refer to WT_SSL price list to order Work Tools.

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		

REGIONAL PACKAGES

CONVERSION ARRANGEMENTS

L	421-0340	CONVERSION ARRANGEMENT	0	NC
		FOR USE WITH: ADSD-N, APD		

CERTIFICATION ARRANGEMENTS/YEAR OF MANUFACTURE

L	522-2549	CERTIFICATION ARR, (US/CANADA)	0	NC
		REQUIRED for US and Canada		

WARNING DECALS

L	506-3528	INSTRUCTIONS, ANSI, USA	0	NC
		This package includes picto decals as required for USA.		

PERFORMANCE PACKAGES

HYDRAULIC PERFORMANCE PACKAGES

L	435-8908	PACKAGE, PERFORMANCE, (H1)	0	NC
		All of the following are included in this package: Standard Flow - 23 gpm (87 lpm) Self Level, None Hydraulic Controls - Standard Flow (Must select one below)		
L	435-9050	PACKAGE, PERFORMANCE, (H2)	0	\$905
		All of the following are included in this package: Standard Flow - 23 gpm (87 lpm) Dual Self Level Hydraulic Controls - Standard Flow (Must select one below)		
L	435-8909	PACKAGE, PERFORMANCE, (H3)	0	\$4,525
		All of the following are included in this package: High Flow XPS - 32 gpm (120 lpm) Dual Self Level Hydraulic Controls - High Flow (Must select one below)		

FILM GROUP SELF LEVEL

L	435-9238	FILM, SELF LEVEL, ANSI	0	NC
		REQUIRED WHEN SELECTING H2 OR H3 PERFORMANCE PACKAGE		

HYDRAULIC CONTROLS

Standard Flow (FOR USE WITH H1 & H2)

L	485-0410	CONTROL, ISO, ON/OFF	0	\$226
		Cannot be used with H3. Provides ISO joystick controls and electronic foot throttle pedal with decel pedal functionality		

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

PERFORMANCE PACKAGES (CONT.)

HYDRAULIC CONTROLS (Cont.)

L	485-0411	CONTROL, ISO, PROP 0 Cannot be used with H3. Provides ISO joystick controls (4 button left hand joystick) and electronic foot throttle pedal with decel pedal functionality		\$435
L	485-0418	CONTROL, ISO, PROP, WT 0 Cannot be used with H3. Provides ISO joystick controls (4 button left hand joystick) and electronic foot throttle pedal with decel pedal functionality. Also includes 14 pin Work Tool electrical harness.		\$775

High Flow (FOR USE WITH H3 ONLY)

L	485-0417	CONTROL, ISO, PROP, WT 0 For use with H3 Only. Provides ISO joystick controls (4 button left hand joystick - Thumb roller with 2 button right hand joystick) and 14 pin Work Tool electrical harness. Also includes electronic foot throttle pedal with decel pedal functionality.		\$880
---	----------	--	--	-------

POWERTRAIN

L	435-8895	RIDE CONTROL, NONE 0		NC
L	435-8896	RIDE CONTROL 0		\$1,045

FILM GROUP RIDE CONTROL

L	422-3445	FILM, RIDE CONTROL, ANSI 0 REQUIRED WHEN SELECTING RIDE CONTROL		NC
---	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FEATURE PACKAGES

COMFORT PACKAGES

L	435-9150	ROPS, OPEN (C0) 0		NC
		All of the following are included in this package: Seat, Static, Vinyl Cab Mounted Controls, Adjustable (hand tool required) Headliner, None		
L	435-9151	ROPS, OPEN (C1) 0		\$438
		All of the following are included in this package: Deluxe Headliner & rear post trim covers Cup Holder Seat (Must select one below)		
L	435-9152	ROPS, ENCLOSED WITH HEAT (C2) 0		\$2,845
		All of the following are included in this package: Deluxe Headliner & post trim covers Cup Holder Side Windows Heater and Defroster Seat (Must select one below) Door (Must select one below)		
L	435-9153	ROPS, ENCLOSED WITH A/C (C3) 0		\$4,895
		All of the following are included in this package: Deluxe Headliner & post trim covers Cup Holder Side Windows Air Conditioner Including Heater/Defroster Seat (Must select one below) Door (Must select one below)		

SEAT

Must select ONE if a C1, C2 or C3 cab package was selected above.

L	345-6329	SEAT, SUSPENSION, VINYL 0		\$359
		Includes: Cab Mounted Controls, Adjustable (hand tool required) For Use With: C1, C2 and C3 Cab Package		
L	345-6349	SEAT,AIR SUSPENSION,VINYL,HEAT 0		\$780
		High back heated seat with recline, lumbar support, and Fully Adjustable Seat Mounted Controls. For Use With: C1, C2 and C3 Cab Package		
L	345-6359	SEAT,AIR SUSPENSION,CLOTH,HEAT 0		\$805
		High back heated seat with recline, lumbar support, and Fully Adjustable Seat Mounted Controls. For Use With: C2 and C3 Cab Package		

DOOR

Must select ONE if an Enclosed ROPS was selected above.

P	345-6240	DOOR, CAB, GLASS 0		\$108
P	345-6260	DOOR, CAB, POLYCARBONATE 0		\$214

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FEATURE PACKAGES (CONT.)

RADIO

Selection of ONE required for C2 or C3 Comfort Package

L	345-6175	RADIO READY 0 Provides Speakers, Wiring, Radio Box, Antenna & Cable, and hardware required to install a single DIN radio.		\$154
L	345-6180	RADIO, AM/FM, BLUETOOTH 0 Provides factory installed radio: Includes Bluetooth interface, microphone, and auxiliary inputs (USB port and aux input jack) to connect external audio devices.		\$510

ADVANCED MACHINE CONTROL

L	465-3706	DISPLAY, ADVANCED, LCD 0 Includes: Full color 5 in. LCD screen with digital gauge display. Provides Creep Control, Hystat response adjustment, Implement response adjustment, DEF gauge, Fuel gauge, Hydraulic temperature gauge, Engine coolant gauge, Tachometer, Language selection and Advanced multi-operator Anti-theft Security System and Monitoring. Also provides USB charging port. Note: Rear camera ready. Anti-theft Security System feature will ship from factory installed but disabled.		\$975
L	465-3705	DISPLAY, ADVANCED, LCD, CAMERA 0 Includes: Full color 5 in. LCD screen with digital gauge display. Provides Creep control, Hystat response adjustment, Implement response adjustment, DEF gauge, Fuel gauge, Hydraulic temperature gauge, Engine coolant gauge, Tachometer, Language selection and Advanced multi-operator Anti-theft Security System and Monitoring. Also provides USB charging port. Note: Rear camera installed. Anti-theft Security System feature will ship from factory installed but disabled.		\$1,140

STARTERS, BATTERIES, & ALTERNATORS

BATTERIES

L	465-3696	BATTERY, 850 CCA, HEAVY DUTY 0 CANNOT BE USED WITH: EU Dealers		NC
L	441-4811	BATTERY, HEAVY DUTY, DISC 0 850 CCA with Battery Disconnect Switch		\$125
L	441-4810	BATTERY, XTRA HVY DUTY, DISC 0 1000 CCA with Battery Disconnect Switch Recommended for cold weather starting.		\$205

OPERATOR ENVIRONMENT

LIGHTS

L	495-1672	LIGHTS, HALOGEN 0 Two (2) forward facing adjustable halogen work lights (cab mounted) and two (2) rear facing halogen work lights (frame mounted).		NC
---	----------	--	--	----

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

OPERATOR ENVIRONMENT (CONT.)

LIGHTS (Cont.)

L	495-1671	LIGHTS, LED 0		\$279
		Two (2) forward facing adjustable LED work lights (cab mounted) and two (2) rear facing LED work lights (frame mounted). LED lighting advantages vs halogens: brighter work site illumination, cooler, more resistant to vibration and longer life.		

SEAT BELTS

L	258-4095	SEAT BELT, 2" 0		NC
L	258-4096	SEAT BELT, 3" 0		\$142
		Required in California.		

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation and condition of your equipment. Efficiently and effectively monitor the performance of your assets to help keep your jobs on schedule, maintain equipment condition and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	441-4818	PRODUCT LINK, CELLULAR PL240 0		NC
		Product Link Basic series PL240 uses cellular networks to transmit hour and location information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent data transmission.		
L	441-4819	PRODUCT LINK, CELLULAR PL641 0		\$833
		Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		

COOLING

COOLING FAN

L	457-3167	FAN, COOLING, DEMAND 0		NC
		Provides variable speed hydraulic cooling fan. Sensors monitor machine cooling requirements to modulate the fan speed providing "on demand" cooling.		
L	457-2835	FAN, COOLING, DEMAND, REVERSING 0		\$840
		Reversing Fan provides automatic and manual purge modes to assist in removing material from the rear door intake screen. Provides both Demand Fan and Reversing Fan functionality.		

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------------	--------------------	-------------------------

QUICK COUPLERS

L	345-4910	QUICK COUPLER, MANUAL	0	NC
L	515-8592	QUICK COUPLER, HYDRAULIC	0	\$995

INSTRUCTIONS

SERVICE INSTRUCTIONS

421-8926	SERIALIZED TECHNICAL MEDIA KIT	The technical media kit will include the Operations & Maintenance Manual (OMM) and other media specified on the Factory Notification List required to ship products from the manufacturing facility. Kit may contain multiple Operation & Maintenance Manuals (OMM) based on the final country of destination. Contents will vary. Any additional media or translations not included in the kit, should be ordered through publications.cat.com	0	NC
----------	--	---	---	-----------

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

ELECTRICAL

L	309-1325	ROTATING BEACON 0 Magnetic base, mounted to top of cab. Operates when key switch is in "On" position.		\$216
---	----------	---	--	-------

OTHER ATTACHMENTS

L	345-5234	RETURN TO DIG/WRKTL POSITIONER 0 Self Level enabled RTD/WT positioner Return to Dig automatically lowers lift arms and returns work tool to preset angle. Work Tool positioner automatically returns work tool to present angle. Requires H2 or H3 performance package		\$288
L	345-5148	COUNTERWEIGHT, MACHINE, EXTERNAL 0 Includes external weights bolted to the frame tower. Suggested for applications where additional rated operating capacity (ROC) is needed. Machine ROC increased by 250 lbs (113 kg).		\$1,030
L	345-3556	HEATER, ENGINE COOLANT, 120V 0 120 Volt - For additional cold weather startability.		\$195
L	457-1215	LIFTING EYES, FOUR POINT 0 Included in EU Conversion Arrangement CANNOT BE USED WITH: TANK, WATER		\$192

WORK TOOLS

To view and order all available Work Tool Selections refer to WT-SSL or WT-HAMR price lists.
 NOTE: Work Tools, except Hammers, are sourced via Caterpillar parts distribution system.
 CMOPS orders for Compact Track Loaders and Work Tools MUST be ordered separately.

FLUIDS

L	418-9011	OIL, HYDRAULIC, COLD OPERATION 0 Recommended for use in hydraulic system where ambient temperatures are below 32 F (0 C).		\$665
---	----------	---	--	-------

FIELD INSTALLED ATTACHMENTS

Available Through Parts Distribution.

345-6070	KIT, FOPS, LEVEL 2 Falling Object Protective Structure level 2. Provides additional overhead protection. Recommended for use in demolition applications. Not compatible with the roof mounted Auxiliary Hydraulic Cooler. Meets ISO 3449: 1992 Note: The part number provided is for reference only. Individual parts must be ordered. Please reference REHS8703 for parts list and installation instructions.
----------	--

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FIELD INSTALLED ATTACHMENTS (CONT.)

Available Through Parts Distribution. (Cont.)

- 474-5632 KIT, SINGLE POINT LIFT**
 Contains parts that attach to cab roof and allow machine to be lifted from a single point. The part number provided is for reference only. Individual parts must be ordered. Please reference REHS9970 for parts list and installation instructions.
- 418-5883 KIT, FOPS LEVEL 2 W/ 4 PT LIFT**
 This kit combines the Falling Object Protective Structure level 2 and 4 point lifting functionality. Recommended for use in applications where additional overhead protection and 4 point lifting are both desired (ex. demolition).
 Note: The part number is provided for reference only. Individual parts must be ordered. Please reference REHS9989 for parts list and installation instructions.

The RETURN TO DIG/WRKTL POSITIONER feature is available as a Software Enabled Attachment (SEA) and is installed using Electronic Technician and a unique password. Cost to enable the feature via password is approximately \$221 USD Dealer Net (January, 2016). Machine must be equipped with the Electronic Self Level feature, provided in the H2 or H3 performance package to install the SEA.

DEDICATED ALTERNATE PATTERN (H-pattern):
 As of January 2018, this feature is standard from the factory. There is no cost. Using Electronic Technician the dealer can configure the machine to operate using the alternative "H" control pattern. With this feature there is no method to allow the operator to change the pattern in the cab. Refer to media number REHS8719.

SELECTABLE PATTERN CONTROL (ISO/H patterns):
 This feature is a Software Enabled Attachment (SEA) and is installed using Electronic Technician and a unique password. The SEA cost to enable the feature via password is approximately \$250 USD Dealer Net (January, 2018). Allows an operator to select either standard CAT control pattern or the alternative "H" control pattern with the flip of a switch. Estimated time to install: 30 min.
 Refer to media number REHS8718 for appropriate parts list.

The components required are available for order from the Parts Department.

Available Through ANTARES Parts Ordering.

**NOTE: US & Canada ONLY may place orders in CMOPS to be transferred via the bridge to ANTARES Parts Ordering.
 When ordering via CMOPS include top level reference numbers (OP-2742) and OP number for packing.**

435-9149	KIT, CAMERA REAR VIEW 0 For proper installation, refer to media number REHS9988. Note: Requires Advanced Display Estimated time to install: 1 hour 30 minutes	\$457 NI
-----------------	---	-----------------

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FIELD INSTALLED ATTACHMENTS (CONT.)

Available Through ANTARES Parts Ordering. (Cont.)

484-8211	KIT, BATTERY DISCONNECT	0	\$125 NI
	For proper installation, refer to media number SEHS0193. Provides components needed to install a battery disconnect switch. Estimated time to install: 30 minutes		
504-1553	KIT, LICENSE PLATE	0	\$51 NI NET
	For proper installation, refer to media number M0067678. Estimated time to install: 30 minutes		
499-2684	KIT, LIGHTS, LED	0	\$350 NI
	For proper installation, refer to media number M0066104. Includes two (2) forward facing adjustable work lights (cab mounted) and two (2) rear facing LED work lights (frame mounted). LED lighting advantages vs halogens: brighter work site illumination, cooler, more resistant to vibration and longer life. Estimated time to install: 1 hour		
388-8285	KIT, FOOT THROTTLE	0	\$331 NI
	For proper installation, refer to media number REHS8712. Estimated time to install: 1 hour 30 minutes		
388-7875	KIT, COUNTERWEIGHT, 100 LB ROC	0	\$519 NI
	Kit provides one counterweight per side which increases the Rated Operating Capacity by approximately 100-125 lbs (46 - 57 kg), depending on model. For maximum ROC increase, must order quantity of (2) 388-7875 kits. Includes Mounting hardware for both one counterweight per side configuration and two counterweights per side configuration. Estimated time to install: 30 minutes		
388-8275	KIT, WINDOW, SIDES	0	\$683 NI
	For proper installation, refer to media number REHS8707. Estimated time to install: 1 hour		
514-9093	KIT, DOOR, CAB, POLYCARBONATE	0	\$1,785 NI
	For proper installation, refer to media number M0073170. Estimated time to install: 1.5 hours		
422-3297	KIT, DOOR, CAB, GLASS	0	\$1,003 NI
	For proper installation, refer to media number REHS9992. Estimated time to install: 1.5 hours		
508-1866	KIT, AIR CONDITIONER (HTR/DFR)	0	\$3,051 NI
	For proper installation, refer to media number M0070248. Estimated time to install: 8 hours 30 minutes		
435-9232	KIT, AIR CONDITIONER (CONVRSN)	0	\$2,015 NI
	For proper installation, refer to media number REHS9982. Estimated time to install: 7 hours		
435-9231	KIT, HEATER	0	\$1,211 NI
	For proper installation, refer to media number REHS9981. Estimated time to install: 7 hours		
527-3155	KIT, QUICK COUPLER, HYDRAULIC	0	\$1,078 NI
	For proper installation refer to media number M0081347. Estimated time to install: 12 hours		

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FIELD INSTALLED ATTACHMENTS (CONT.)

Available Through ANTARES Parts Ordering. (Cont.)

513-5126		KIT, GUARD, COUPLER 0 For proper installation, refer to media number M0072576. Provides lower guard that restricts material/debris from entering the underside of the coupler area giving additional safeguarding for electrical components. Estimated time to install: 30 minutes		\$199 NI
388-8265		KIT, WT ELECTRICAL CONTROL 0 For proper installation, refer to media number REHS7806. Includes Work Tool Electrical switch, harness, connector and mounting hardware. Estimated time to install: 2 hours		\$193 NI
388-8273		KIT,WT ELECTRICAL CONTROL, DLX 0 For proper installation, refer to media number REHS7814. Includes: Work Tool Electrical switch, harness, connector, mounting hardware and 4 button Left Hand Joystick. Estimated time to install: 3 hours		\$696 NI
523-4908		KIT, DUAL SELF LEVEL 0 For proper installation, refer to media number M0077274. Estimated time to install: 2 hours 45 minutes Note: Not compatible with H2 or H3 Performance Packages.		\$750 NI
481-0031		KIT, RIDE CONTROL 0 For proper installation, refer to media number SEHS0156. Estimated time to install: 3 hours		\$1,038 NI
435-9237		KIT, FAN, DEMAND, REVERSING 0 For proper installation, refer to media number REHS6604. Reversing Fan provides automatic and manual purge modes to assist in removing material from the rear door intake screen. Provides both Demand Fan and Reversing Fan functionality. Estimated time to install: 1.5 hours		\$857 NI
388-8283		KIT, RADIO, READY 0 For proper installation, refer to media number REHS8710. Provides Speakers, Wiring, Radio Box, Antenna & Cable, and hardware required to install a single DIN radio. Estimated time to install: 1 hour		\$149 NI
388-8286		KIT, RADIO, AM/FM/BLUETOOTH 0 For proper installation, refer to media number REHS8705. Includes radio with Bluetooth interface, microphone and auxiliary inputs (USB port and aux input jack) to connect external audio devices. Requires: Radio Ready operator station. Estimated time to install: 45 minutes		\$571 NI

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FIELD INSTALLED ATTACHMENTS (CONT.)

Available Through ANTARES Parts Ordering. (Cont.)

498-6622	KIT, DEBRIS 0	<p>For proper installation, refer to media number M0067498. This kit provides additional components for customers in debris intensive applications that restrict debris and other material from entering the engine compartment and the lower machine frame. Provided are various seals and covers that are designed to cover the openings that exist between the frame/body/cab of the machine as well as a fuel strainer and an exhaust stack cover. Also recommended: Turbo Debris Guard Kit Note: If additional component guarding is required, please refer to the Guarding Kit. Estimated time to install: 10 hours</p>		\$1,874 NI
472-2965	KIT, GUARDING 0	<p>For proper installation, refer to media number REHS9959. This kit provides additional guarding for customers in demanding applications where extra component safeguarding is required. This kit provides guarding for the front work lights, rear work lights, auxiliary hydraulic connections, work tool electrical harness connection and work tool coupler area. Note: If additional debris guarding is required, please refer to the Debris Kit. Estimated time to install: 1.5 hours</p>		\$640 NI
421-0219	KIT, A/C BREATHER 0	<p>For proper installation, refer to media number M0068026. This kit provides increased cab air filter life for machines used in dusty or high airborne debris applications. Kit contains duct work and hardware required to relocate the cab fresh air intake to a higher location near the roof of the cab. Estimated time to install: 30 minutes</p>		\$456 NI
444-6050	KIT, TURBO DEBRIS GUARD 0	<p>For proper installation, refer to media number REHS9969. This kit contains steel mesh guards that are designed to cover the exhaust manifold and turbocharger to assist in deterring the collection of material on these components. It is recommended that that the turbo guard kit be used in conjunction with the debris kit. Estimated time to install: 1 hour 30 minutes</p>		\$285 NI
416-5965	KIT,ENG AIR INTAKE, PRECLEANER 0	<p>For proper installation, refer to media number REHS8735. Turbine-type precleaner for the engine air filter. For use in high dust/debris applications. Estimated time to install: 1 hour</p>		\$466 NI NET
422-3323	KIT, FRONT ROADING LIGHTS 0	<p>Includes front roading lights and 2 lift arm mounted mirrors. For proper installation, refer to media number REHS7836. Mandatory for Road Homologation in Italy and Germany. Estimated time to install: 4 hours</p>		\$468 NI

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FIELD INSTALLED ATTACHMENTS (CONT.)

Available Through ANTARES Parts Ordering. (Cont.)

422-3322	KIT, LIGHTS, REAR, ROADING 0	For proper installation, refer to media number REHS8748. This kit provides Rear Roading light components (rear reflectors, brake lamps, directional indicators/turn signals, hazard lights) in order to meet roading requirements for Italy. Estimated time to install: 1.5 hours		\$232 NI
512-0356	KIT, LIGHTS, REAR, WIDE MOUNT 0	For proper installation, refer to media number M0071898. This kit provides components that allows the rear lights to be relocated to mounting locations on the sides of the rear frame. Estimated time to install: 30 minutes REQUIRED for Italy Roading		\$429 NI
421-0274	KIT, LIFTING EYES, FOUR POINT 0	For proper installation, refer to media number REHS9993. Estimated time to install: 30 minutes CANNOT BE USED WITH: TANK, WATER		\$229 NI
422-3241	KIT, PROD LINK, CELLULAR PL641 0	For proper installation, refer to media number REHS9952 Product Link Pro series PL641 uses GSM and CDMA 3G cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data. Estimated time to install: 2.5 hours		\$1,024 NI
482-5132	KIT, WATER TANK, 42 US GAL, D 0	Mounted to top of cab 42 gallon capacity Includes tank, pump, filter, lines, mounting brackets and quick disconnect For proper installation, refer to media number SEHS0363. Estimated time to install: 9 hours 30 minutes For use with Water Sprinkler Kits for Angle Broom, Pick Up Broom, Utility Broom or Cold Planer		\$1,817 NI
527-2335	KIT, REMOTE GREASE (COUPLER) 0	CANNOT BE USED WITH: Four Point Lifting Eyes kit, Single Point Lift kit or Auxiliary Hydraulic Cooler kit For proper installation, refer to media number M0084651. Provides remote location for lubrication of the work tool coupler pins Estimated time to install: 3 hours		\$222 NI

NO RETURNS accepted for kit components not used or for parts removed from machine during kit installation.

Shipments will be within 3 - 5 working days of order receipt for delivery by dealer parts stocking truck to dealer stocking facility.

CATERPILLAR MACHINE PRICE LIST

297D2

USE	REF NO.	OPTIONAL ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

FIELD INSTALLED ATTACHMENTS (CONT.)

ENDORSED FIELD INSTALLED ATTACHMENTS

Caterpillar does not warrant, service, or assume responsibility for these attachments.

All orders, pricing confirmation, and other communication for these attachments must be directed to the listed manufacturer.

REMOTETASK TM - REMOTE CONTROL SYSTEM

Complete system for use with CAT D Series Skid Steer, Multi Terrain, and Compact Track Loaders. Allows the operator to precisely control the machine from outside the cab. Line-of-sight remote control with an approximate range of 1000 feet (300 meters). Dealer installed remote control system includes the Remote Task controller and necessary hardware to convert standard D series SSL, MTL or CTL to remote controlled machine.

NOTE: Certified for use in North America. To verify certification in other regions, please contact BCP Attachments Team.
 Email: bcp_work_tools@cat.com

Orders for the remote control system must be placed directly from:

TORC Robotics, Inc.
 Tel. +1(800) 530-9285, +1(540) 443-9262
 Email: sales@torcrobotics.com

PACKING

DOMESTIC PACKING

OP-0210	PACK, DOMESTIC TRUCK	0	NC
---------	--------------------------------	---	----

Only to be used when ordering kits via CMOPS.

OP-2162	PACKING, KIT	0	NC
---------	------------------------	---	----

PROTECTION

OP-2266	SHIPPING/STORAGE PROTECTION	0	\$207 NET
	Provides protective application of Fluid Film TM for protection while shipping and for extended storage periods. If desired, this product can be power washed with warm soapy water prior to shipment to the customer.		