The Educational Services Commission of New Jersey NJ State Approved Co-op #65MCESCCPS

CATERPILLAR MACHINE PRICE LIST

420F2 HRC

LIST PRICE

420F2 BACKHOE LOADER HRC LEICESTER, ENGLAND

Standard Equipment:

BOOMS, STICKS, AND LINKAGES

14'4" Center pivot excavator style backhoe Pilot operated joystick hydraulic controls with pattern changer valve Pilot operated stabilizer controls Boom transport lock Swing transport lock Street pads stabilizer shoes Anti-drift hydraulics (Boom, Stick and E-Stick) Cat Cushion Swing(tm) system Bucket level indicator Lift cylinder brace Return-to-dig (auto bucket positioner) Self-leveling loader with single lever control Transmission neutralizer switch Single Tilt Loader

POWERTRAIN

Cat C4.4, 74.5KW (Net 92HP / 69kW) Direct Injection Turbo Charged Engine, with ACERT technology. US EPA Tier4 Final Emissions Compliant with Selective Catalytic Reduction(SCR) Water separator with service indicator Thermal starting aid system Eco mode A dry-type axial seal air cleaner with integral precleaner, automatic dust ejection system & filter condition indicator Hydraulically boosted multi-plate wet disk brake with dual pedals & interlock Differential lock Drive-line parking brake High Ambient Cooling Package Torque converter Transmission--four speed synchro mesh with power shuttle & neutral safety switch Spin-on fuel, engine oil & transmission oil filters Outboard planetary rear axles **Open Circuit Breather** HYDRAULICS

Load sensing, variable flow system with 43 gpm axial piston pump 6 micron hydraulic filter O-ring face seal hydraulic fittings Caterpillar XT-3 hose Hydraulic oil cooler Pilot control shutoff switch

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY Ship Weight

PPPC, Flow-sharing hydraulic valves Hydraulic suction strainer

ELECTRICAL

12 volt electrical start 150 ampere alternator Horn and Backup Alarm Hazard flashers/turn signals Halogen head lights (4) Halogen rear flood lights (4) Stop and tail lights Audible system fault alarm Key start/stop system 880 CCA maintenance free battery Battery disconnect switch External/internal power receptacles(12v) Diagnostic ports for engine and machine Electronic Control Modules Remote jump start connector

OPERATOR ENVIRONMENT

Lighted gauge group Interior rearview mirror ROPS canopy, Rear Fenders 2-inch retractable seat belt Tilt steering column Steering knob Hand and foot throttle Automatic Engine Speed Control One Touch Low Idle Floor mat and Coat Strap Lockable storage area Air suspension seat

OTHER STANDARD EQUIPMENT

Hydrostatic power steering Standard Storage Box Transport tie-downs Ground line fill fuel tank with 44 gallon capacity Ground line fill diesel exhaust fluid tank with 5 gallon capacity Rubber impact strips on radiator guards Bumper **CD-ROM** Parts Manual Backhoe Safety Manual Operations and Maintenance Manual Lockable hood **Tire Valve Stem Protection** Long Life Coolant -30C (-20F) Padlocks (2 on ST, 3 on IT)

The Educational Services Commission of New Jersey NJ State Approved Co-op #65MCESCCPS

CATERPILLAR MACHINE PRICE LIST

-	420F2 BACKHOE LOADER HRCShip WeightLEICESTER, ENGLANDIbs		LIST PRICE AT DEALER		
Lane 2 is reserved for the Base Order Management Program. Please use Lane 2 when placing orders that are part of the Base Order Management Program.					
558-4671	420F2 BACKHOE LOADER DCA1		\$114,960		
	INCLUDES: 450-8448 420F2 BHL ST, TIER 4, HRC 337-9696 COUNTERWEIGHT, 1015 LBS 450-8757 ENGINE, 74.5KW,C4.4 ACERT, T4F 450-8730 STICK, EXTENDABLE, 14FT 450-8682 CANOPY, BASE 433-4804 SEAT, VINYL 450-8530 HYDRAULICS, MP, 6FCN/8BNK, ST 547-6095 POWERTRAIN, 4WD, POWERSHIFT 457-2797 BATTERY, HEAVY DUTY 447-0049 PRODUCT LINK, CELLULAR, PL641				
558-4672	420F2 BACKHOE LOADER DCA2 LANE 1 - AVAILABLE FROM CLAYTON PRODUCT DISTRIBUTION INCLUDES: 450-8448 420F2 BHL ST, TIER 4, HRC 337-9696 COUNTERWEIGHT, 1015 LBS 450-8757 ENGINE, 74.5KW,C4.4 ACERT, T4F 450-8730 STICK, EXTENDABLE, 14FT 398-2681 RIDE CONTROL 450-8683 CAB, DELUXE 450-8715 AIR CONDITIONER, T4 433-4806 SEAT, DELUXE FABRIC 450-8530 HYDRAULICS, MP, 6FCN/8BNK, ST 547-6095 PT, 4WD, POWERSHIFT 398-2882 COLD WEATHER PACKAGE, 120V HRC 447-0049 PRODUCT LINK, CELLULAR, PL641		\$129,100		
540-0797	420F2 BACKHOE LOADER DCA3 LANE 1 - AVAILABLE FROM CLAYTON PRODUCT DISTRIBUTION INCLUDES: 450-8450 420F2 BHL IT, TIER 4, HRC 337-9696 COUNTERWEIGHT, 1015 LBS 450-8757 ENGINE, 74.5KW,C4.4 ACERT, T4F 450-8730 STICK, EXTENDABLE, 14FT 398-2681 RIDE CONTROL 450-8683 CAB, DELUXE 450-8715 AIR CONDITIONER, T4 395-2942 SEAT, DELUXE FABRIC, HEATED 450-8533 HYDRAULICS, MP, 6FCN/8BNK, IT 450-8616 PT, 4WD, AUTOSHIFT 398-2882 COLD WEATHER PACKAGE, 120V HRC 447-0049 PRODUCT LINK, CELLULAR, PL641I 398-2853 LINES, COMBINED AUX, E-STICK	0 n center	\$143,720		

420F2 BACH LEICESTER,	KHOE LOADER HRC Ship Weight ENGLAND Ibs	LIST PRICE AT DEALER
540-0798	420F2 BACKHOE LOADER DCA4 0 LANE 1 - AVAILABLE FROM CLAYTON PRODUCT DISTRIBUTION CENTER	\$134,980
	INCLUDES: 450-8448 420F2 BHL ST, TIER 4, HRC 450-8683 CAB, DELUXE 433-4806 SEAT, DELUXE FABRIC 450-8715 AIR CONDITIONER 398-2681 RIDE CONTROL 450-8757 ENGINE, 74.5KW, C4.4 ACERT, T4F 450-8730 STICK, EXTENDABLE, 14FT 450-8616 PT, 4WD, AUTOSHIFT 450-8530 HYDRAULICS, MP, 6FCN/8BNK, ST 398-2853 LINES, COMBINED AUX, E-STCK 398-2882 COLD WEATHER PACKAGE, 120V HRC 447-0049 PRODUCT LINK, CELLULAR, PL641 337-9696 COUNTERWEIGHT, 1015 LBS	
450-8448	420F2 BHL ST, TIER 4, HRC 0 LANE 2 - AVAILABLE FROM LEICESTER FACTORY LANE 3 - AVAILABLE FROM LEICESTER FACTORY ONLY FOR USE WITH: AM-N and PUERTO RICO	\$87,880
450-8450	420F2 BHL IT, TIER 4, HRC 0 LANE 2 - AVAILABLE FROM LEICESTER FACTORY LANE 3 - AVAILABLE FROM LEICESTER FACTORY ONLY FOR USE WITH: AM-N and PUERTO RICO	\$95,890
Use the ref kits.	erence below when ordering miscellaneous field installed	
0G-0556	420F2 MISC MTRL, USA & CNDA 0	NC

420F2 HRC

USE	REF NO.	LANE 1 Ship We	ight	LIST PRICE AT DEALER
AN	E 1 AM-NO	RTH MANDATORY ATTACHMENTS		
L	ANE SELEC	TION		
	0P-9001	LANE 1 ORDER Select this option when ordering from the Distribution Center	0	NC
L	IT machines: If a bucket is	CKET Select either 325-5100 or both bucket & cutting edge. No selection should be made from this section. required, select 251-1800 & 9R-5320 from the a to Order' section.		
•	325-5100	BUCKET, LOADER (NONE)	.0	NC
0	337-7436	Ship with no loader bucket. BUCKET-MP, 1.3 YD3, PO, BRKTS 1, 5 1.35 CYD (1.03CUM) SAE capacity Multi Purpose. Drilled to accept bolt-on teeth or cutting edge (not included)	93	\$6,911
>	337-7385	ONLÝ FOR USE WITH: DCA 1 or DCA 2 BUCKET-GP, 1.30 YD3, PO	65	\$3,231
þ	337-7401	ONLY FOR USE WITH:DCA 1 or DCA 2BUCKET-GP, 1.5 YD3, PO1, 01.5 CYD (1.15 CUM) SAE capacity General Purpose. Drilled to accept bolt-on teeth or cutting edge (not included).ONLY FOR USE WITH:DCA 1 or DCA 2	56	\$4,142
C	CUTTING ED Must select if	GES loader bucket required with DCA1 or DCA2.		
•	9R-5321	CUTTING EDGE, TWO PIECE	54	\$331
•	9R-5320	CUTTING EDGE, TWO PIECE, WIDE	54	\$329
7	type cannot b your tire choid Any proposed machine ship	ry-wide tire availability limitations, tire brand and e guaranteed. Every effort will be made to satisfy ce, but we reserve the right to propose alternate tires change will be reviewed with the dealer prior to ment. The machine will ship only with the dealer the proposed alternative tire.		
Þ	533-0488	TIRES, 340 80-18/500 70-24, MX Michelin Power CL (Bias Ply) 12.5/80-18 12PR directional front tir and 500/70-24 20PR (Bias ply) directional rear tires designed to deliver high load capacity. Provides excellent traction and floatation. Wide lugs provide long life and hard surface grip.		\$1,645
V	VORKING LI	IGHTS		
-	491-6734	WORKLIGHTS (8) HALOGEN LAMPS	0	NC
Supers	edes 02JAN2018	3 Subject to change without notice	Ef	fective 02JAN20

Effective 02JAN2019 420F2 HRC-004

USE	REF NO.	LANE 1 Ship	o Weight Ibs	LIST PRICE AT DEALER
	E 1 AM-NO	RTH MANDATORY ATTACHMENTS (CONT.)		
D	ECAL PACK Must select or			
Р	430-9944	INSTRUCTIONS, ANSI	0	NC
•	430-9945	INSTRUCTIONS, ISO INSTRUCTIONS, ISO This package includes picto decals for use outside of USA.	0	NC
-	EAT BELT Select one			
-	206-1747	BELT, SEAT, 2" SUSPENSION CANNOT BE SELECTED BY: dealers from California	0	NC
-	206-1748	SEAT BELT, 3" SUSPENSION	0	\$109
S	TABILIZER Must select or			
5	9R-1085	STABILIZER PADS , STREET Set of two rubber pads which bolt to the standard shoes. For use on prepared surfaces such as asphalt or concrete.	37	NC
)	9R-6007	STABILIZER PADS, FLIP-OVER	85	\$336
	ACKHOE B Must select or	UCKET OR COUPLER ne.		
•	175-7877	BUCKET, HOE, (NONE)	10	NC
•	219-3387	REQUIRED when no backhoe bucket or coupler is installed. BUCKET-HD, 24", 6.2 CFT	. 333	\$1,717
•	254-8941	Includes 5 tooth tips. BUCKET-HC SOIL, 24", 8.5 CFT INCLUDES: 5 angle-down adapters and soil tooth tips.	. 395	\$1,854
•	219-3411	BUCKET-HD, 12", 2.8 CFT	238	\$1,457
•	219-3386	BUCKET-HD, 18", 4.2 CFT Includes 4 tooth tips.	. 284	\$1,508
)	212-8738	BUCKET-DC, 48", 13.0 CFT Ditch cleaning bucket	0	\$2,757
IN	/STRUCTIO Must select	NS AND OPERATION MANUALS		
	421-8926	SERIALIZED TECHNICAL MEDIA KIT	d	NC

420F2 HRC

USE	REF NO.	LANE 1 Ship W	•	LIST PRICE AT DEALER
ANE [·]	1 AM-NO	RTH MANDATORY ATTACHMENTS (CONT.)		
TRA	ANSPORT	PROTECTION		
	461-6839	 SHIPPING/STORAGE PROTECTION Provides protective application of Fluid Film TM for protection while shipping and for extended storage periods. This product will need to be power washed with soapy water prior to shipment to the customer. Currently this is only available to, and required by, machines shipping to USA, Canada & South America. 		\$203 NET
	462-1033	RUST PREVENTATIVE APPLICATOR . Preparation for shipment - Silix applicators required for shipment by sea. Required for all machines for USA, Canada & South America	0	\$108 NE:
	CKING ust select			
	0P-0210	PACK, DOMESTIC TRUCK Required for all machines for USA, Canada & South America	. 0	NC
	0P-3071	 FREIGHT SHIP-TO EXCEEDS RADIUS. A freight surcharge will be applied for the ship-to locations described below. Any applicable surcharge will be billed seperate Contact your trade lane manager for information. Finning: Locations exceeding 500 km radius of Vancouver and E Kramer: Locations exceeding 500 km radius of Regina Toromont: Locations exceeding 500 km radius of Toronto and Wi Hewitt: Locations exceeding 500 km radius of Montreal 	ely. dmonton	NC

Atlantic: Locations exceeding 500 km radius of Halifax and York

NC Machinery: Deliveries to Alaska

Hawthorne: Deliveries to Hawaii

USE	REF NO.	LANE 1	Ship Weight Ibs	LIST PRICE AT DEALER
LAN	E 1 AM-NO	RTH OPTIONAL ATTACHMENTS		
N	lay select a	dditional options (not required).		
Р	211-4292	BEACON, MAGNETIC MOUNT	0	\$231 NI
Р	353-1389	Must be ordered as 'Not-Installed'. GUARD, STABILIZER.	0	\$835
Р	423-7607	Guards to protect Stabilizer cylinder rods from damage. PLATE GROUP - BOOM WEAR	0	\$216
Р	337-6851	Bolt on guard prevents damage to boom. FENDERS, FRONT	0	\$576
L	OADER BUG	CKET FOR IT MACHINES		
Ρ	251-1800	BUCKET-GP, 1.31 YD3, IT	979	\$3,682
Ρ	216-8810	BUCKET-MP, 1.3 YD3, IT 1.25 cu. yd. SAE capacity Multi Purpose IT. Drilled to accept bolt-on teeth or cutting edge (not included).	1,549	\$7,136
Ρ	216-8840	BUCKET-MP, 1.4 YD3, IT 1.35 cu. yd. SAE capacity Multi Purpose IT. Drilled to accept bolt-on teeth or cutting edge, Two piece, Wide	1,612	\$7,632
Ρ	9R-5320	CUTTING EDGE, TWO PIECE, WIDE	154	\$329
Ρ	9R-5321	CUTTING EDGE, TWO PIECE	154 154	\$331 \$331 NI
С	ARRIAGE A	ND FORKS FOR IT MACHINES		
Ρ	6W-8832	CARRIAGE, FORK Standard carriage. Does not include tines.	611	\$2,511
Ρ	195-6935	FORK TINE, 2" X 5" X 48"	216	\$765
Ρ	195-6939	FORK TINE, 2" X 5" X 54" One tine only, specify qty of 2 for pair.	232	\$793
Н	OE COUPLE	ER		
Ρ	444-7500	COUPLER, PG, MAN.D.LOCK, BHL F	192	\$2,090
Ρ	544-1901	to attach one bucket). COUPLER, PIN LOCK, BL F Manual coupler for dedicated Pin Lock backhoe work tools Includes mounting pins and hardware for attaching tools.	S.	\$1,528

USE	REF NO.	LANE 1	Ship Weight Ibs	LIST PRICE AT DEALER
LANE	1 AM-NORTH	OPTIONAL ATTACHMENTS (CONT.)	
Tl		shipped without either bucket or coup nay only be ordered as full, installed pa		

	Thumbs cann selected to co No additional Tine from the the bucket an	not be ordered installed, less the tine. A Tine must be mplete the order. not installed tine allowed When ordering a BHL Thumb & Factory; insure that the correct tine is selected for ad/or bucket/coupler combination. et tine is selected, the bucket and tine may not mate	
Ρ	282-5409	THUMB, HYDRAULIC, NO TINE, BHL 0 Hydraulic Thumb Arrangement without tines REQUIRES: Thumb tine (see below)	\$5,500
Ρ	221-4282	ONLY FOR USE WITH: DCA3 OR DCA4 THUMB, TINE, A 1 0 Buckets with no coupler ONLY FOR USE WITH: 219-3411 BUCKET 12" OR	\$417
Ρ	221-4283	219-3387 BUCKET 24" THUMB, TINE, A 3 Buckets with no coupler FOR USE WITH: 254-8941 BUCKET 24" Buckets with 444-7500 Coupler FOR USE WITH: 219-3411 BUCKET 12" OR 219-3386 BUCKET 18"	\$417
Ρ	281-6708	OR 219-3387 BUCKET 24" THUMB, TINE, A 5 ONLY FOR USE WITH: 444-7500 COUPLER, MANUAL 254-8941 BUCKET 24"	\$417

420F2 HRC

USE		

LANE 2 / 3 MANDATORY Ship Weight Ibs

LIST PRICE AT DEALER

LANE SELECTION

REF

NO.

LANE 2/ LANE 3 FACTORY ARRANGEMENTS

MACHINES ORDERED FROM THIS SECTION WILL BE SOURCED FROM THE FACTORY

0P-9002	LANE 2 ORDER	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program	
0P-9003	LANE 3 ORDER	NC

420F2 HRC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
BOOI	MS, STICK	S, AND LINKAGES		
	ACKHOE S Select one	TICKS		
L	450-8729	STICK, STANDARD, 14FT	0	NC
L	450-8730	STICK, EXTENDABLE, 14FT Provides additional 3'8" (1.13m) of reach	0	\$4,825
POW	ERTRAIN			
P	OWERTRAI	N (Gearbox, Axles, Lines)		
	Two Whee	el Drive		
L	559-2926	POWERTRAIN, 2WD/2WS POWERSHIFT	0	NC
	Four Whee	el Drive		
L	547-6095	POWERTRAIN, 4WD, POWERSHIFT	0	\$9,600
L	450-8616	PT, 4WD, AUTOSHIFT		\$13,330
L	450-8627	PT, 4WD/2WS, AUTOSHIFT, LTC Autoshift with Lockup Torque Converter	0	\$15,800
E/	NGINE (Eng	ine, Cooler, Filters, Lines)		
L	450-8757	ENGINE, 74.5KW,C4.4 ACERT, T4F EPA/ ARB Tier 4 Final Certified engine with aftertreat Net Power @ Rated (2200RPM) SAE J1349 92HP (69k	tment.	\$7,070
HYD	RAULICS			
	DADER & B Select one	ACKHOE HYDRAULICS (inc Valves and Load	er Lines)	
	HYDRAUL	ICS FOR SINGLE TILT MACHINES		
L	450-8525	HYDRAULICS, GP, 5FCN/7BNK, ST ONLY FOR USE WITH: 450-8448 420F2 BHL ST T CANNOT BE USED WITH: E-STICK WHEN AUX LINES	YIER 4 HRC	\$720
L	450-8527	HYDRAULICS, GP, 6FCN/8BNK, ST ONLY FOR USE WITH: 450-8448 420F2 BHL ST T	0	\$1,465
L	450-8528	HYDRAULICS, MP, 5FCN/7BNK, ST ONLY FOR USE WITH: 450-8448 420F2 BHL ST T CANNOT BE USED WITH: E-STICK WHEN AUX LINES	0 YIER 4 HRC	\$1,870
L	450-8530	HYDRAULICS, MP, 6FCN/8BNK, ST ONLY FOR USE WITH: 450-8448 420F2 BHL ST T	0	\$2,615

HYDRAULICS FOR IT (PARALLEL LIFT) MACHINES

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
HYD	RAULICS (CONT.)		
L	OADER & B	ACKHOE HYDRAULICS (inc Valves and Load	er Lines) (Cont.)	
-	450-8531	HYDRAULICS, MP, 5FCN/7BNK, IT ONLY FOR USE WITH: 450-8450 420F2 BHL IT TI CANNOT BE USED WITH: E-STICK WHEN AUX LINES	ER 4 HRC	\$2,030
	450-8533	HYDRAULICS, MP, 6FCN/8BNK, IT	0	\$2,760
LEC	TRICAL			
P	location, opera effectively mor jobs on sched	NK enables the remote transmission of information about the ation, and condition of your equipment. Efficiently and nitoring performance of your assets, it helps keep your ule, maintain equipment condition, and reduce the costs operating your fleet.	2	
	representative HTTPS://DEA	ries by country, please contact your Cat marketing e with questions or click on the link below: ALER.CAT.COM/en/bt/otd/machine-price-list.html ck on the "PRODUCT LINK Hardware Certification" link. ne		
-	447-0048	PRODUCT LINK, SATELLITE PL631E PL631 uses a satellite network to transmit location, u and condition information for viewing in Product Link monitoring web interface. For use in areas with poor	tilization 's remote	\$311 NE
	447-0049	cellular coverage. PRODUCT LINK, CELLULAR, PL6411	transmit ving in Product nology provides	NC
OPEF	RATOR ENV	IRONMENT		
C	AB/ CANOF Select one	γ		
-	450-8682	CANOPY, BASE	0	NC
-	450-8683	CAB , DELUXE . Includes: window defroster, front & rear windshield w system, left & right side doors with locks, coat hook, interior rear view mirror, tilt/tele steering column, flo radio-ready headliner, two internal and two external i sockets, auto-up stabilizers, and system indicators fo filter service and hydraulic temperature warning.	riper/washer or mat, L2v power	\$8,39 0
И	ORKING LI	GHTS		
_	491-6734	WORKLIGHTS (8) HALOGEN LAMPS		NC

420F2 HRC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
OPE	RATOR ENV	(IRONMENT (CONT.)		
V	VORKING LI	GHTS (Cont.)		
L	491-6736	WORKLIGHTS (8) LED LAMPS	0	\$875
S	SEATING Select one			
L	433-4804	SEAT, VINYL	0	NC
L	433-4806	ONLY FOR USE WITH: OPEN CANOPY ONLY SEAT, DELUXE FABRIC		\$925
L	395-2942	SEAT, DELUXE FABRIC, HEATED ONLY FOR USE WITH: DELUXE ENCLOSED CAB	0	\$1,435
S	SEAT BELT Select one			
L	206-1747	BELT, SEAT, 2" SUSPENSION	0	NC
L	206-1748	SEAT BELT, 3" SUSPENSION REQUIRED IN: CALIFORNIA	0	\$109
E	-	NTAL CONTROL ENCLOSED CABS ONLY		
L	450-8714	HEATER, T4		NC
L	450-8715	CANNOT BE USED WITH: MACHINES WHICH HAVE AIR CONDITIONER, T4		\$2,400

TIRES, RIMS, AND WHEELS

TIRES

Select one

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice, but we reserve the right to propose alternate tires Any proposed change will be reviewed with the dealer prior to machine shipment. The machine will ship only with the dealer acceptance of the proposed alternative tire.

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
		ND WHEELS (CONT.) DRIVE TIRES AVAILABLE FROM FIRESTONE	Ŧ	
Ρ	418-7773	 TIRES, 12 16.5/19.5L-24, FS, 2WD Front: Firestone 12 16.5, 10 ply, Duraforce DT NHS Directional tire for heavy 2WD truck loading. Heavy-duty sidewall and large curb rib for more stability and puncture resistance. Rear: Firestone 19.5L-24, 12ply, All Traction Utility Directional tire provides excellent traction and flotatic characteristics. Shock-fortified nylon-cord body resist cuts and punctures. ONLY FOR USE WITH: TWO WHEEL DRIVE POWE 	ility on ts impacts,	\$1,725
TV	NO WHEEL	DRIVE TIRES AVAILABLE FROM GOODYEA	R	
Ρ	379-2160	TIRES, 11L-16/19.5L-24,GY, 2WD Front: Goodyear 11L-16 12 PR F-3 Laborer Non-Directional tire for lighter 2WD truck loading. Excellent handling and mobility with 5-rib design. Resists tearing and cracking with special tread compo Rear: Goodyear 19.5L-24 12 PR R4 IT525 Directional tire with solid performance on rock-hard g Increased wear and performance on hard surfaces. FOR USE WITH: TWO WHEEL DRIVE POWERTRAINS	ound. ground.	\$1,035
FC	OUR WHEEL	DRIVE TIRES AVAILABLE FROM FIRESTON	E	
Ρ	282-3855	TIRES , 12.5 80-18/21L-24 , FS Front: Firestone 12.5/80-18 NHS (12ply) I-3 Super T Directional tire with low profile design that provides e traction and flotation. Tough sidewall for long wear. Rear: Firestone 21L-24 (16ply) R4 ATU (All Traction Directional tire provides excellent traction and flotation characteristics. Shock-fortified nylon-cord body resist cuts and punctures. Adds one inch of rear height with improved rear flotation	Traction Loader. excellent Utility) on ts impacts, tion.	\$2,390
Ρ	380-8961	 ONLY FOR USE WITH: FOUR WHEEL DRIVE POW TIRES, 12.5 80/19.5L-24, FS Front: Firestone 12.5 80-18, 12 ply, I-3 Super Tractice Directional tire with low profile design that provides e traction and flotation. Tough sidewall for long wear. Rear: Firestone 19.5L-24, ATU, 12PLY, 20 PITCH Directional tire provides excellent traction and flotation characteristics. Shock-fortified nylon-cord body resisted cuts and punctures. Designed for superior noise and cancellation. ONLY FOR USE WITH: FOUR WHEEL DRIVE POW 	on excellent on ts impacts, vibration	\$2,010

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
		ND WHEELS (CONT.) . <i>DRIVE TIRES AVAILABLE FROM GOODYEA</i>	\R	
Ρ	379-2161	TIRES , 12.5 80/19.5L-24 , GY Front: Goodyear 12.5 80-1810 PR I-3 Sure Grip Lug Directional tire for good traction and long wear, provi wide, sturdy overlapping lugs. Rear: Goodyear 19.5L-24 12 PR R4 IT525 Directional tire with solid performance on rock-hard Increased wear and performance on hard surfaces.	ded by	\$1,690
F	OUR WHEEL	DRIVE TIRES AVAILABLE FROM MICHELIN	,	
Ρ	320-2384	TIRES, 340 80R18/500 70R24, MX Front: Michelin 340/80R18 XMCL 142A8 Directional tire designed to deliver high load capacity smooth wear and long life with superb grip in all type Rear: Michelin 500/70R24 XMCL 157A8 Directional tire designed for outstanding damage resi extremely long tire life, and high load capacity.of cone ONLY FOR USE WITH: FOUR WHEEL DRIVE POW	r, es of conditions. istance,oth ditions.	\$3,110
FC	OUR WHEEL	DRIVE TIRES FROM MULTIPLE SOURCES		
Ρ	320-2385	 TIRES,340 80R18/500/70-24 MI Front: Michelin 340/80R18. Directional tire designed deliver high load capacity, smooth wear and long life superb grip in all types of conditions. Rear: Michelin 500/70-24 Power CL 164A8 Directional tire provides excellent traction and flotatic characteristics. Shock-fortified nylon-cord body resis cuts and punctures. Combines benefits of radial front with stability of rear ONLY FOR USE WITH: FOUR WHEEL DRIVE POW 	d to with on ts impacts, r bias.	\$2, 4 70
Ρ	533-2163	 TIRES, 340 80R20/480 80R26, MX Michelin 340/80-R20 XMCL radial directional front t 480/80R26 XMCL radial directional rear tires for exc on all types of ground, good wear resistance on hard surfaces. A taller and wider tire combination for sup clearance and floatation. REQUIRES: 311-2230 STEERING STOP 	0 ires and Michelin cellent traction abrasive	\$3,535
Ρ	533-0488	TIRES , 340 80-18/500 70-24 , MX Michelin Power CL (Bias Ply) 12.5/80-18 12PR direct and 500/70-24 20PR (Bias ply) directional rear tires deliver high load capacity. Provides excellent traction and floatation. Wide lugs p	tional front tire designed to	\$1,645
Ρ	533-0479	long life and hard surface grip. TIRES, 340 80R18/500 70R24, MX Michelin 340/80R18 BIBLOAD Radial multi-direction Michelin 500/70R24 BIBLOAD Radial multi-direction more contact on hard surfaces and smoother ride with to wear and tear.	nal front tires and nal rear tires for	\$3,235

420F2 HRC

USE	REF NO.	LANE 2 / 3 MAN	IDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
TIRES	S, RIMS, AI	ND WHEELS (CONT.)			
ST	TEERING ST	TOP			
Ρ	311-2230	STEERING STOP. Front axle steering stop limits the 20- tire arrangements to prevent REQUIRES: 5332163 TIRES, 34	e steering angle on machine interferen	ice.	\$10
отне		IMENTS			
	OUNTERWE Select one	EIGHT			
		g counterweights for IT machines, re ions for the lightest loader attachmer			
]	MINIMUM RE	COMMENDED COUNTERWEIGHT			
420F2 420F2 420F2 420F2 420F2 420F2	2 ST 4WD St 2 ST 2WD St 2 ST 4WD St 2 ST 2WD E- 2 ST 4WD E- 2 ST 4WD E- 2 ST 2WD E-	d Stick GP Bucket d Stick GP Bucket d Stick MP Bucket d Stick MP Bucket Stick GP Bucket Stick GP Bucket Stick MP Bucket	ECOMMENDED WEI0 5301b no cwt no cwt 10151b 10151b 5301b 5301b	ЗНТ	
420F2 420F2 420F2 420F2 420F2 420F2 420F2 420F2 420F2 420F2 420F2 420F2 420F2 420F2 420F2	2 IT 4WD St. 2 IT 2WD St. 2 IT 4WD St. 2 IT 2WD St. 2 IT 4WD St. 2 IT 2WD St. 2 IT 2WD St. 2 IT 4WD St. 2 IT 2WD E- 2 IT 4WD E- 2 IT 2WD E- 3 IT 2WD E	d Stick GP Bucket	no cwt no cwt no cwt no cwt no cwt no cwt no cwt 5301b 5301b no cwt 5301b 5301b 5301b 5301b 5301b 5301b		
Р	337-9693	COUNTERWEIGHT, NONE		0	NC
P	337-9694	COUNTERWEIGHT, 255 LBS		0	\$680
Ρ	337-9695	COUNTERWEIGHT, 530 LBS		0	\$895
Р	337-9696	COUNTERWEIGHT, 1015 LBS		0	\$1,765

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

Effective 02JAN2019 420F2 HRC-015

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
отні	ER ATTACH	IMENTS (CONT.)		
S	t abilizer Pac Select one	Is and Accessories		
Р	9R-1085	STABILIZER PADS, STREET	ioes.	NC
5	9R-6007	For use on prepared surfaces such as asphalt or com STABILIZER PADS , FLIP-OVER Flip-over pads for use on asphalt, concrete or soil.		\$336
BUCI	KETS			
L	OADER BUG	CKETS		
(Must refer	t Select One to the Optio	if ordering a ST machine. For IT Work Tools nal Attachment section).		
Р	325-5100	BUCKET, LOADER (NONE)	0	NC
Ρ	337-7385	BUCKET-GP, 1.30 YD3, PO 1.25 CYD (0.96CUM) SAE capacity General Purpose. accept bolt-on teeth or cutting edge (not included).		\$3,231
Ρ	337-7388	BUCKET-GP, 1.4 YD3, PO		\$3,418
Ρ	337-7401	BUCKET-GP, 1.5 YD3, PO 1.5 CYD (1.15 CUM) SAE capacity General Purpose. accept bolt-on teeth or cutting edge (not included).		\$4,142
P	337-7436	BUCKET-MP, 1.3 YD3, PO, BRKTS		\$6,911
Ρ	337-7442	BUCKET-MP, 1.4 YD3, PO 1.45 CYD (1.1 CUM) SAE capacity Multi Purpose. Dr accept bolt-on teeth or cutting edge (not included). REQUIRES: MP HYDRAULICS		\$7,424
C	UTTING ED			
	(May select wh	hen ordering a bucket)		
Ρ	9R-5320	CUTTING EDGE, TWO PIECE, WIDE Bolt-on reversible cutting edge for the Loader Bucket ONLY FOR USE WITH: 337-7401 BUCKET-GP, 1. 337-7442 BUCKET-MP, 1. 337-7396 BUCKET-GP, 1. 337-7445 BUCKET-MP, 1.	t. 5 CYD or .4 CYD or 3 CYD or	\$329
Ρ	9R-5321	CANNOT BE USED WITH: 9R-5866 TEETH CUTTING EDGE, TWO PIECE Bolt-on reversible cutting edge for the Loader Bucket ONLY FOR USE WITH: 337-7385 BUCKET-GP, 1. 337-7388 BUCKET-GP, 1. 337-7436 BUCKET-MP, 1. 337-7439 BUCKET-MP, 1.	t. 25 CYD or 4 CYD or .3 CYD or	\$331
		CANNOT BE USED WITH: 9R-5866 TEETH		

420F2 HRC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
BUCK	KETS (CON	IT.)		
С	UTTING ED	GE/TEETH (Cont.)		
Ρ	9R-5866	TEETH. Includes eight bolt-on Uniteeth and hardware. ONLY FOR USE WITH: ALL GP & MP LOADER BUC CANNOT BE USED WITH: 9R5320 CUTTING EDGE, T 9R5321 CUTTING EDGE, T	CKETS WO PIECE,WIDE or	\$389
		JCKETS AND COUPLERS		
		s selected hoe bucket should be ordered as installed. elected coupler should be installed and hoe bucket		
	Additional bu	ekets (and bucket pins) may be ordered as not-installed 2/3 Optional section.		
Р	175-7877	BUCKET, HOE, (NONE)		NC
Р	219-3387	BUCKET-HD, 24", 6.2 CFT		\$1,717 \$1,717 N
Р	254-8941	Includes 5 tooth tips. BUCKET-HC SOIL, 24", 8.5 CFT		\$1,854 \$1,854 N
Р	219-3396	Includes 5 angle-down adapters and soil tooth tips. BUCKET-HD ROCK, 24", 7.0 CFT		\$1,892 \$1,892 N
Р	219-3381	Includes 5 tooth tips. BUCKET-SD, 24" 6.2 CFT		\$1,335 \$1,335
Р	247-1950	Includes 5 tooth tips. BUCKET-HD, 24", 7.3 CFT PL	291	\$1,335 N \$1,846
F	247-1330	This Pin Lock bucket includes 5 tooth tips.	370	\$1,846 N
Р	219-3411	ONLY FOR USE WITH: 487-0712 COUPLER, PIN L BUCKET-HD, 12", 2.8 CFT	OCK 238 238	\$1,457 \$1,457 N
Р	219-3386	12- wide, 0.1 CYD (0.078 CUM) capacity Includes 3 tooth tips and Pin set for 12" Buckets. BUCKET-HD, 18", 4.2 CFT	284	\$1,508
F	213-3360	Includes 4 tooth tips.	284	\$1,508 \$1,508 N
Ρ	212-8738	BUCKET-DC, 48", 13.0 CFT	0 453	\$2,757 \$2,757 N
Р	444-7500	Ditch cleaning bucket COUPLER, PG, MAN.D.LOCK, BHL F		\$2,090
P	544-1901	(includes one set of pins and hardware to attach one COUPLER , PIN LOCK , BL F	0 tools.	\$1,528
Ρ	485-5303	Includes mounting pins and hardware for attaching to COUPLER, PG, HYD.D.LOCK,BHL-F	192 uckets.	\$4,083

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

420F2 HRC

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight Ibs	LIST PRICE AT DEALER
INST	RUCTIONS			
	ECAL PACK Select one	(AGES		
Ρ	430-9944	INSTRUCTIONS, ANSI	0	NC
	STRUCTIO Must select	NS AND OPERATION MANUALS		
	421-8926	SERIALIZED TECHNICAL MEDIA KIT	lly required	NC

https://oos.midlandcorp.com/CAT/Default.aspx

420F2 HRC

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER

NOTE

LANE 2 / LANE 3 OPTIONAL SELECTIONS

All items may be ordered as Lane 2 unless specifically designated 'FOR USE IN LANE 3 ONLY'.

HYDRAULICS

RIDE CONTROL

L	398-2681	RIDE CONTROL	\$1,490
	HYDRAULIC	QUICK DISCONNECT	
Ρ	456-3390	COUPLING, QD, THREADED WITH CAPS	\$371 NI
	Thumbs & Tir Thumbs cann selected to con No additional Tine from the the bucket an	ot be shipped without either bucket or coupler. hes may only be ordered as full, installed packages. ot be ordered installed, less the tine. A Tine must be nplete the order. not installed tine allowed When ordering a BHL Thumb & Factory; insure that the correct tine is selected for d/or bucket/coupler combination. t tine is selected, the bucket and tine may not mate	
Ρ	282-5409	THUMB, HYDRAULIC, NO TINE, BHL0 Hydraulic Thumb Arrangement without tines FOR USE WITH: LINES, COMBINED AUX REQUIRES: Thumb tine (see below)	\$5,500
Ρ	221-4282	THUMB, TINE, A 1 0 Buckets with no coupler 0 ONLY FOR USE WITH: 219-3411 BUCKET 12" OR 219-3386 BUCKET 18" 219-3381 BUCKET 24" OR 219-3387 BUCKET 24"	\$417
Ρ	221-4284	THUMB, TINE, A 2	\$417

420F2 HRC

USE	REF NO.	LANE 2 /	3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
HYDF	RAULICS (CONT.)			
T	HUMBS (C	ont.)			
Ρ	221-4283	Bucket with no coupler FOR USE WITH: 254-89 Buckets with: 444-7500 485-5303 CO FOR USE WITH: 219-34	941 BUCKET 24" 9 COUPLER, MANUAL OR 9 DUPLER, HYDR 9 11 BUCKET 12" OR 219-338 9 JCKET 24" OR 219-3387		\$417
Ρ	221-4285	THUMB, TINE, A 4	444-7500 COUPLER, MAI 485-5303 COUPLER, HYI 219-3396 BUCKET 24"	NUAL OR	\$417
Ρ	281-6708	THUMB, TINE, A 5 ONLY FOR USE WITH:		NUAL OR	\$417
BA	аскное н	YDRAULICS			
L	398-2852	LINES, COMBINED AUX, S ONLY FOR USE WITH:	TD STICK 450-8729 STICK, STANDA 5 or 6 FUNCTION HYDRA	ARD, 14FT and	\$3,500
L	398-2853	LINES, COMBINED AUX, E ONLY FOR USE WITH:	-STICK	0 DABLE, 14FT and	\$3,500
ELEC	TRICAL				
М	AGNETIC E	BEACON			
Р	211-4292		JNT	0	\$231 N
Р	433-0154	Must be ordered as 'NO' BEACON, MAGNETIC MOU Must be ordered as 'NO'	JNT, STROBE	0	\$342 N
RA	4 <i>DIO</i>				
Ρ	540-2298	Cat FM Radio with blue	tooth, aux input & micropho H:OPEN CANOPY MACHINE	ne	\$550
RA	ADIO READ	Y CANOPY HEADLIN	ER		
L	398-2875				\$499
FA	ACE FAN				
L	387-6682			0	\$230
L	454-6610	FOR USE WITH: DELUX FAN, STANDARD CAB/ CA FOR USE WITH: CANOF	NOPY	0	\$230

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

Effective 02JAN2019 420F2 HRC-020

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
ELEC	TRICAL (C	ONT.)		
S	ECURITY K	EYPAD		
L	387-6570	SECURITY SYSTEM, KEYPAD	tem to disable switch on until	\$499
Η	EAVY DUT	Y BATTERY		
L	457-2797	BATTERY, HEAVY DUTY INCLUDED IN: COLD WEATHER PACKAGE	0	\$227
С	OLD WEAT	HER PACKAGES		
L	398-2882	COLD WEATHER PACKAGE, 120V HRC Provides additional battery and engine block heater radiator antifreeze (to -55 celsius), mounting for an low temperature diesel fuel (to -30 celsius). The ether bottle is available seperately from Parts D CANNOT BE USED WITH: HEAVY DUTY BATTERY	as well as ether bottle and Distribution	\$78 0
L	396-6505	FUEL, COLD WEATHER Provides low temperature diesel fuel (to -30 celsius) INCLUDED IN: COLD WEATHER PACKAGE	0	\$139 NET
GUA	RDS			
Р	423-7607	PLATE GROUP - BOOM WEAR	0	\$216
Ρ	353-1389	Bolt on guard prevents damage to boom. GUARD, STABILIZER Guards to protect Stabilizer cylinder rods from dam		\$835
отн	ER ATTACH	IMENTS		
F	ENDERS			
Ρ	337-6851	FENDERS, FRONT	0	\$576
S	ERVICE FIL	TER PACK		
Ρ	399-0118	SERVICE FILTER PACK, T4/C4.4	0	\$101 NI NET
		Please order as 'Not-Installed'. This pack includes: Transmission, Engine and Mac filters together with fuel water separator filter. NOTE: Only one pack per machine order.	hine hydraulic	
E	XTERIOR RI	EAR VIEW MIRRORS		
Р	382-2499	MIRRORS, EXTERNAL, BOTH SIDES	0	\$725

CATERPILLAR MACHINE PRICE LIST

CATERPILLAR MACHINE PRICE LIST 420F			2 HRC	
USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
WORI	K TOOLS			
AT	TACHMEN	ITS FOR IT STYLE LOADER ONLY		
•	6W-8832	CARRIAGE, FORK Standard carriage. Does not include tines. ONLY FOR USE WITH: 450-8450 420F2 BHL IT		\$2,511
•	195-6935	FORK TINE, 2" X 5" X 48"		\$765
•	195-6939	One tine only, specify qty of 2 for pair. FORK TINE, 2" X 5" X 54" One tine only, specify qty of 2 for pair.	232	\$793
F	Required if a l	OUICK COUPLER LINES Hydraulic Quick Coupler has been selected. tion on other machines.		
)	450-8577	LINES, HYD COUPLER 14FT STD-STK Provides hydraulic lines, valve and electrical contro REQUIRED BY: HYDRAULIC COUPLER, PG, DUAL STANDARD STICK	oller.	\$2,324
	450-8578	LINES,HYD COUPLER 14FT E-STICK Provides hydraulic lines, valve and electrical contro REQUIRED BY: HYDRAULIC COUPLER, PG, DUAL EXTENDABLE STICK	oller.	\$2,324
BU	ICKET PINS	S		
)	318-9902	PINS, SPARE Includes bucket pins and hardware. FOR USE WITH: 444-7500 COUPLER, PG, MANUA 361-1200 COUPLER, PG, HYD, DU	L, DUAL LOCK	\$175
виск	ETS			
LO	ADER BUG	CKET FOR IT STYLE LOADER		
P	251-1800	BUCKET-GP, 1.31 YD3, IT	d	\$3,682

Р	251-1800	BUCKET-GP, 1.31 YD3, IT	\$3,682
		1.31 cu. yd. SAE capacity General Purpose. Drilled	
		to accept bolt-on teeth or cutting edge, Two piece, Wide	
		(not included).	
		ONLY FOR USE WITH: 450-8450 420F2 BHL IT TIER 4 HRC	
Р	251-1794	BUCKET-GP, 1.5 YD3, IT1, 030	\$4,326
		1.5 cu. yd. SAE capacity General Purpose. Drilled	
		to accept bolt-on teeth or cutting edge, Two piece, Wide	
		(not included).	
		ONLY FOR USE WITH: 450-8450 420F2 BHL IT TIER 4 HRC	
Р	216-8810	BUCKET-MP, 1.3 YD3, IT1, 549	\$7,136 NI
		1.25 cu. yd. SAE capacity Multi Purpose IT. Drilled	. ,
		to accept bolt-on teeth or cutting edge (not included).	
Р	216-8840	BUCKET-MP, 1.4 YD3, IT	\$7,632
		1.35 cu. yd. SAE capacity Multi Purpose IT. Drilled	1.,
		to accept bolt-on teeth or cutting edge, Two piece, Wide	
		(not included).	
		ONLY FOR USE WITH: 450-8450 420F2 BHL IT TIER 4 HRC	

Subject to change without notice Printed in USA U. S. DOLLAR CURRENCY

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
BUCK	ETS (CON	IT.)		
	LOADER E May select on	BUCKET - CUTTING EDGE OR TEETH		
Ρ	9R-5320	CUTTING EDGE, TWO PIECE, WIDE Bolt-on reversible WIDE cutting edge for Loader Bu	ıckets.	\$329
Р	9R-5321	REQUIRES: IT BUCKETS 251-1800, 251-1794 OR CUTTING EDGE, TWO PIECE REQUIRES: IT BUCKET 216-8810		\$331
Ρ	9R-5866	TEETH Includes eight bolt-on Uniteeth and hardware. CANNOT BE USED WITH: 9R5320 CUTTING EDGE		\$389
FLUID	DS			
СС	OLD WEAT	HER FUEL		
L	396-6505	FUEL, COLD WEATHER Provides low temperature diesel fuel (to -30 celsius INCLUDED IN: COLD WEATHER PACKAGE		\$139 NET
FIELD	INSTALLE	ED ATTACHMENTS		
KI	TS			
Kits ca orders MISC orders	an be ordere from the m MTRL refer are transfe	dered with your machine order. ed through CMOPS, but MUST be separate nachine, and MUST include the top level ence number. To ensure the erred through Antares to the Parts Distribution T also select the required Packing reference nur	nber.	
For US	SA and Can	ada, please place your order as follows:		
	556 420F2 m number	MISC MTRL		
the W Rest c	aco or Clay of the world	hipped with your machine, and are not carried in ton Logistics Nodes. may order direct from the plant. order as follows:	1	
Kit ite	m number	MISC MTRL MISCL MTRL		
RI	DE CONTR	OL		
Ρ	387-6451	KIT, RIDE CONTROL (PILOT/ECM) Provides a suspension system by placing an accum lift arm circuit to improve vehicle ride when travelin in roading, load and carry or any other application spillage or operator ride is a concern. Includes ma switch.	nulator in loader ng. For use where bucket	\$1,418 NI

420F2 HRC

CATERPILLAR MACHINE PRICE LIST

REF Ship Weight LIST PRICE LANE 2 / 3 OPTIONAL USE NO. lbs AT DEALER FIELD INSTALLED ATTACHMENTS (CONT.) AUXILIARY, COMBINED FUNCTION HYDRAULIC KITS For use with both one-way flow tools (hammers, compactors) and two-way flow tools (augers, thumbs, side tilt couplers). Units equipped with Standard Sticks require 5 function BH Hydraulics and operate using the right thumb controller. Units equipped with Extendible Sticks require 6 Function BH Hydraulics and operate using the left thumb controller. Mounted near the backhoe valve bank in the chassis, a manual ball valve switches between one-way and two-way flow. Estimated shop time: 8 hours to install kit, plus 8 more hours is needed if adding a valve section to the valve bank (converting 4 to 5 Function, or 5 to 6 Function). Ρ 468-7982 KIT, HYD,COMBINED,14FT STD STK 0 \$3,332 NI Provides diverter valve and hydraulic 3/4" lines routed to midpoint of stick for use with one-way or two-way flow work tools. Includes hydraulic quick disconnect couplings. This kit can be used to build 1 way (hammer) lines. See REHS installation instructions. FOR USE WITH: HYDRAULICS, BH, 5 FUNCTION or HYDRAULICS, BH, 6 FUNCTION and STICK, STANDARD 468-7981 **KIT, HYD, COMBINED, 14FT E-STK**0 \$3,332 NI Ρ Provides diverter valve and hydraulic 3/4" lines routed to midpoint of stick for use with one-way or two-way flow work tools. Includes hydraulic quick disconnect couplings. This kit can be used to build 1 way (hammer) lines. See reference media number REHS installation instructions. FOR USE WITH: E-STICK and HYDRAULICS, BH, 6 FUNCTION **OTHER KITS** 468-7970 Ρ \$1,724 NI **KIT, LINES, HYD CPLR 14FT E-STK**0 Ρ 468-7971 \$1,724 NI 444-7500 D **COUPLER, PG, MAN.D.LOCK, BHL F**192 \$2,090 NI Mechanical quick coupler for backhoe buckets. COUPLER, PG, HYD, DUÂL LOCK 192 Ρ 361-1200 \$4,046 NI Hydraulic quick coupler with dual lock for backhoe buckets. Ρ 387-6458 \$828 NI 455-7380 P \$368 NI

 P
 455-7380
 KIT, LOADER, COUPLING QD
 \$368 NI

 Includes both Male and Female 'Twist to Connect' hydraulic quick disconnect couplings with protective caps.
 \$368 NI

 P
 442-9566
 KIT, HOE, COUPLING Q-DISCON
 \$363 NI

 Includes both Male and Female 'Twist to Connect' hydraulic quick disconnect couplings with protective caps.
 \$363 NI

420F2 HRC

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
FIELD	D INSTALLE	D ATTACHMENTS (CONT.)		
0	THER KITS	(Cont.)		
Ρ	482-1308	KIT, SECURITY KEYPAD Provides a kit to add a keypad unit, self contained i to disable the engine, transmission and other syster on until a valid pass code is entered on the keypad	immobiliser system ms at key switch	\$493 NI
Ρ	387-6472	machine to enable operation. KIT, FENDER, FRONT Provides a kit to add a set of 2 Front Fenders to a m		\$571 NI
		FROM PARTS DISTRIBUTION media number M0078810 installation instructions		
Ρ	511-9785	 KIT, OBJECT HANDLING, BHL-CP Load Control Kit includes the following object hands 512-6861 Load Control Kit (Boom) (1), 512-6863 Load Control Kit (Stick) (2), 512-6862 Load Control Kit (Bucket) (3), 512-5597 Load Control Kit (Stab) (4), 	0 ling kits :	\$3,256 NI
Ρ	512-5597	See reference media number M0078810 installation KIT, LCV, STABILIZER, BHL-CP Load Control Kit will provide a Hose Burst Check Va for the stabs	0	\$546 NI
Ρ	512-6861	See reference media number M0078810 installation KIT, LCV - BOOM, BHL-CP	0	\$733 NI
Ρ	512-6862	See reference media number M0078810 installation KIT, LCV - BUCKET, BHL-CP Load Control Kit will provide a Hose Burst Check Va for the bucket	0 alve (HBCV)	\$1,122 NI
Ρ	512-6863	See reference media number M0078810 installation KIT, LCV - STICK, BHL-CP Load Control Kit will provide a Hose Burst Check V for the stick	alve (HBCV)	\$854 NI
	e see the W1 Distribution	See reference media number M0078810 installation F-BHL price list for other items available from	n instructions	

PACKING

0P-0210	PACK, DOMESTIC TRUCK	NC
461-6839	Required for all machines for USA, Canada & South America SHIPPING/STORAGE PROTECTION	\$203 NET
401-0835	Provides protective film for rust protection while shipping and	\$205 NEI
	for extended storage periods.	
	This product will need to be power washed with soapy water prior	
	to shipment to the customer.	
	REQUIRED BY: AM-N and AM-S DEALERS	

420F2 HRC

\$212 NET

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight Ibs	LIST PRICE AT DEALER
PACKI	NG (CON	IT.)		
	462-1033	RUST PREVENTATIVE APPLICATOR Preparation for shipment - Silix applicators required shipment by sea. Required for all machines for USA, Canada & South	1 for	\$108 NET

	Simplifent by Sea.
	Required for all machines for USA, Canada & South America
0G-3280	PACK, MISCELLANEOUS MATERIAL