



Current Date 16Nov2018

75G EXCAVATOR

ENGINE:

Yanmar 4TNV98C 3.3L - certified with EPA Final Tier 4 emissions
57 SAE Net HP
Direct Injection
Antifreeze Protection to -34 degrees F (-37 degrees C)
Single Dry-Type Air Filter
Electric Fuel Shutoff
Low-Noise Fan with Guard
Full Flow Oil Filter
Heavy-Duty Low Maintenance Batteries
Fuel Filter
Isolation Mounted Radiator/Oil Cooler Trash Screen
50 Amp Alternator - 24 Volt

Automatic Belt Tension Device
Water Separator

HYDRAULICS:

Open Center with Two Variable Displacement Pumps
Hydraulic Shut-Off Lever
Hydraulic Pilot Controls
Axial Piston Swing Motor
Multiple Wet Disk Swing Brake
Boom Reduced-Drift Valves
Mechanical Pattern Changer
Hand Controlled Proportional Auxiliary Hydraulics Plumbed to the End of the Boom

UNDERCARRIAGE:

450 mm (18 In.) Rubber Pad Track Shoes
Front Track Guide
Propel Motor Shield
Planetary Final Drive
Two-Speed Propel

Axial Piston Propel Motor
Back-fill Blade

UPPER STRUCTURE:

Rear-view Mirrors (right, left, and rear)
Toolbox
Vandal Locks for:
Cab Door
Service Doors
Fuel Cap
Hydraulic Reservoir
Toolbox
Work lights:
One Mounted on Frame
One Mounted on Boom
Counterweight 2,877 lbs. (1,305 kg)

FRONT ATTACHMENTS:

WC Thermal Spraying of Bucket Joint
Dirt Seal on all Bucket Pins

One Piece Boom
Less Bucket

OPERATOR'S STATION:

Adjustable Control Positions (Levers to Seat, Seat to Pedals)
Arm Rests
Pilot Control Shut-Off Lever

Short Stroke, Low Effort Pilot Levers
Deluxe Adjustable Cloth Seat with Suspension
Multi-function, Color LCD Monitor System with:
Diagnostic Capability
Systems Monitoring Capability
Multiple Language Capability
Maintenance Tracking
Engine Coolant Temperature Gauge
Engine Coolant Temperature Warning

Fuel Gauge with Low Fuel Indicator
Work Mode Indicator
Auto Idle Indicator
Alternator Charge Indicator

Air Filter Restriction Indicator
Fault Code Alert Indicator
Check Engine Indicator
Wiper Mode Indicator
Work Lights On Indicator
Fuel Rate Display
Clock

Hour Meter
Mode Selection:
One Work Mode
Two Power Modes
Numerous Attachment Modes
Auto-Climate Control/Air Conditioner, Heater with Pressurizer
AM-FM Radio
Machine Information Center (MIC)
Windshield Wiper/Washer with Intermittent Speed
Cell Phone Power Outlet
2 In. Retractable Seat Belt
Tinted Safety Glass
Hot/Cold Box Compartment

Horn
Two Cup Holders
Interior Light
Coat Hook
Floor Mat
Motion Alarm with Cancel Switch
Transparent Tinted Roof
Hatch with Sunshade
Four Fluid-Filled Elastic Mounts
Easy Access Air Conditioning Filter

Indicator with Audible
Alarm
Engine Oil Pressure
Warning Indicator with
Audible Alarm

Required - *You must select one from each category*

▼ BASE MACHINE

F.O.B. US/Canadian Port of Entry except where noted.
See DEALER-INSTALLED ATTACHMENT section for additional source notes.

Description	Code	Price
75G EXCAVATOR	0091FF	\$126,769.00

▼ TRACK SHOES

Description	Code	Price
600 mm (24in.) Track Shoes	3205	\$1,010.00
Triple Semi-Grouser Shoes w/ Blade		
Rubber Crawler Pads	3265	No Added Cost
450 mm (18 In.) Rubber Pads w/ Blade Steel track shoes with vulcanized rubber pads bonded to top of shoes.		
450 mm (18 In.) Continuous Rubber Belt w/ Blade	3275	\$1,010.00
Long lead time required.		

▼ ARM

Description	Code	Price
2.12 M (6 Ft. 11 In.) Arm Assembly with Bucket Cylinder and Linkage	7060	\$6,724.00

Optional - *Select as desired*

▼ ATTACHMENTS FOR FIELD CONVERSION

F.O.B. Dubuque, Iowa for dealer-installed kits, except where noted. Some of the following kits may require additional parts for a complete installation. Prior to ordering, check the installation instructions by going to www.johndeere.com/techinfo and clicking on Library, or by clicking on this Hyperlink ([Installation Bulletin Search](#)), and insert the AT number to retrieve the attachment installation instruction bulletin for additional parts. Exception to above note is FRONTIER Dealer Installed Kits.

All attachments are sold as a quantity of one.

Description	Code	Price
Buckets		
BKH Pin-on Bucket 18 In. (457 mm) Heavy-Duty 5.1 Cu. Ft. (0.14 Cu. M.)	AT437340	\$1,309.00
Must include hydraulic coupler AT442602 if ordered for excavator usage.		
BKH Pin-on Bucket 24 In. (610 mm) Heavy-Duty 8.8 Cu. Ft. (0.25 Cu. M.)	AT437344	\$1,825.00

Must include hydraulic coupler AT442602 if ordered for excavator usage.		
BKH Pin-on Bucket 30 In. (762 mm) Heavy-Duty 10.0 Cu. Ft. (0.28 Cu. M.)	AT437345	\$1,799.00
Must include hydraulic coupler AT442602 if ordered for excavator usage.		
BKH Pin-on Bucket 36 In. (914 mm) Ditching 12.5 Cu. Ft. (0.35 Cu. M.)	AT437616	\$1,536.00
Must include hydraulic coupler AT442602 if ordered for excavator usage. Ditching bucket does not include teeth.		
BKH Pin-on Bucket 36 In. (914 mm) Heavy-Duty; 12.5 Cu. Ft. (0.35 Cu. M.)	AT437346	\$1,792.00
Must include hydraulic coupler AT442602 if ordered for excavator usage.		
<u>Buckets, Ditching</u>		
48 In (1219 mm), 0.64 yd ³ (0.49 M ³) Ditching Bucket	AT339015	\$2,431.00
<u>Buckets, Heavy-Duty</u>		
24 In (610 mm), 0.31 yd ³ (0.24 M ³) Heavy-Duty Bucket	AT395791	\$2,565.00
Includes Five (5) TK-Series Fanggs (TF23D)		
30 In (762 mm), 0.41 yd ³ (0.31 M ³) Heavy-Duty Bucket	AT395792	\$2,709.00
Includes Six (6) TK-Series Fanggs (TF23D)		
36 In (914 mm), 0.51 yd ³ (0.39 M ³) Heavy-Duty Bucket	AT395793	\$2,962.00
Includes Seven (7) TK-Series Fanggs (TF23D)		
<u>Hydraulic Couplers</u>		
Hydraulic Quick Coupler	AT442602	\$7,331.00
For use with John Deere backhoe buckets only. Will not interface with standard excavator buckets. Extra pins required can be ordered through service parts: T185832 T185831		
Thumb Kit, Direct with Coupler	BYT10499	\$5,000.00
Thumb Kit, Direct without Coupler	BYT10498	\$5,000.00
<u>Hydraulics</u>		
Auxiliary Hydraulic Lines Boom to Arm	AT436726	\$1,147.00
Requires AT434128 (ZX 85USB-5)		
Requires AT434127 (ZX 75US-5)		

Requires AT434128 (85G)		
Requires AT434127 (75G)		
Foot Pedal Control Kit for Meterable Two-Way Hydraulics	AT356391	\$1,410.00
Recommended: Hydraulic Filter Restriction Indicator Kit Does not require a solenoid kit.		
Foot Pedal Switch for 1-Way Control of Auxiliary Valve	AT196587	\$515.00
Requires a solenoid kit. Installation instructions T161995. Average installation, 1 hour. For customers who want an auxiliary valve with foot pedal control of attachments that require 1-direction on/off control without metering. Includes foot switch and wiring harness.		
ALSO ORDER: Hydraulic Filter Restriction Indicator Kit Recommended. For a complete system, also order 1-Way or 2-Way Electric Solenoid Valves for Auxiliary Valve and Auxiliary Hydraulic Lines. Average installation, 1 hour. For customers who want an auxiliary valve with foot pedal control of attachments that require 1-direction on/off control without metering. Includes foot switch and wiring harness.		
ALSO ORDER: Hydraulic Filter Restriction Indicator Kit Recommended. For a complete system, also order the 2-Way Electric Solenoid Valves for Auxiliary Valve and Auxiliary Hydraulic Lines.		
Hydraulic Filter Restriction Indicator Kit	AT442872	\$774.00
For iT4 and FT4 only.		
Single Pedal Propel Kit	AT390776	\$2,080.00