

CATERPILLAR MACHINE PRICE LIST

**772G**

772G TRUCK DECATUR, IL, USA	Ship Weight lbs	LIST PRICE AT DEALER
--------------------------------	--------------------	-------------------------

Standard Equipment:

**POWERTRAIN**

- Cat C18 ACERT diesel engine
- Air cleaner with precleaner, two
- Air-to-air aftercooler(ATAAC)
- Electric start
- Engine idle shutdown
- Global off-highway aluminum radiator
- Automatic Retarder Control (ARC)
- Manual retarder (utilizes rear oil cooled, multiple disc brakes)
- Brake release motor, towing
- Dry disc brakes, front
- Front brake disconnect switch, front
- Oil-cooled multiple disc brakes, rear
- Brake wear indicator, rear
- Parking/secondary/service brakes
- Transmission:
  - 7 speed automatic powershift w/ (ECPC) electronic clutch pressure control
  - Advanced productivity electronic control strategy (APECS)
  - Automatic neutral idle
  - Autostall
  - Second gear start

**SUSPENSION SYSTEMS**

- Suspension, front and rear

**ELECTRICAL**

- Alarm backup
- Alternator, 120 amp
- Batteries, maintenance-free, 12V (2), 1400 CCA combined
- Electrical system, 25 amp, 24v to 12v converter
- Backup light, halogen
- Directional signals/hazard warning, front & rear, LED
- Engine compartment light
- Headlights with dimmer
- Operator access courtesy lights
- Lights, side profile
- Lights, stop/tail, LED
- Service center
  - Battery jump start
  - Breakers, electrical
  - Lock out switch
  - Ports, ET and VIMS

**OPERATOR ENVIRONMENT**

- Advisor display
- Air cleaner service indicator
- Fluid level monitoring
- Fuel level monitoring
- Display languages, market based

- Air conditioning/heat
- Automatic temperature control
- Ashtray and cigarette lighter
- Coat hook
- Cup holders (4)
- Diagnostic connection port, 24V
- Entertainment radio ready: 5 amp converter, speakers and wiring harness
- Foot rest
- Brake oil temperature gauge
- Coolant temperature gauge
- Engine overspeed indicator
- Fuel level indicator
- Hour meter
- Speedometer w/odometer
- Tachometer
- Transmission gear indicator
- Hoist lever
- Horn
- Light, courtesy and dome
- Mirrors, heated
- Rollover protection (ROPS) and falling object protection (FOPS)
- Cat COSS 2 deluxe seat
  - full air suspension
  - heated/ventilated
  - retractable 4 point seat belt with shoulder harness
- Seat, training, with lap belt
- Steering wheel, padded/tilt/telescopic
- Storage compartment
- Sun visor
- Throttle lock
- Window, sliding, right side (emergency exit)
- Window, powered, left side windshield wiper intermittent and washer

**TECHNOLOGY PRODUCTS**

- Economy modes, standard and adaptive
- Product link ready
- Payload System (TPMS)
- Vital Info Management System (VIMS)
- Tire monitoring system (TKPH/TMPH)

**GUARDS**

- Driveline
- Engine crankcase
- Fan

**FLUIDS**

- Extended life coolant, -34C (-30F)
- Grouped ground-level filters

CATERPILLAR MACHINE PRICE LIST

**772G**

---

772G TRUCK  
DECATUR, IL, USA

Ship Weight  
lbs

LIST PRICE  
AT DEALER

---

**OTHER STANDARD EQUIPMENT**

- Body down indicator
- Body safety pin (secures body in up position)
- Center mounted rims
- Fuel tank, 530L (140 gallons)
- Ground level battery disconnect
- Ground level engine shutdown
- Ground level grease fittings
- Operation Maintenance Manual (OMM)
- Rims 15 x 33
- Rock ejectors
- Secondary steering, electric
- Tie down eyes
- Tow hooks, front/tow pin, rear
- Vandalism protection locks

CATERPILLAR MACHINE PRICE LIST

**772G**

772G TRUCK DECATUR, IL, USA	Ship Weight lbs	LIST PRICE AT DEALER
--------------------------------	--------------------	-------------------------

<b>549-0689</b>	<b>772G OHT AM-N DCA5A</b> . . . . . 0 LANE 1 - AVAILABLE FROM DECATUR FACTORY	<b>\$795,760</b>
-----------------	---	------------------

Please confirm Lane 1 availability with DSD before placing the order.

INCLUDES:

- 300-0002 772G OFF-HIGHWAY TRUCK
- 444-8416 REGIONAL PKG, NORTH AMERICA
- 444-8424 ADVANCED BRAKING PERFORMANCE
- 541-1712 LIGHTING, HALOGEN
- 444-8441 WEATHER PACKAGE, HEATED MIRRORS
- 444-8435 GREASE FITTINGS, CLSTRD W/FF
- 375-7859 EXHAUST, BODY HEAT
- 444-8430 SUSPENSION, EU
- 341-6731 LANGUAGE, ADVISOR
- 299-7274 FILTER, AIR
- 444-8459 PL, SAT PL321 / TRACTION CTRL
- 549-6787 VISIBILITY, CAMERA

<b>300-0002</b>	<b>772G OFF-HIGHWAY TRUCK</b> . . . . . 74,052 LANE 2 - AVAILABLE FROM DECATUR FACTORY LANE 3 - AVAILABLE FROM DECATUR FACTORY	<b>\$760,710</b>
-----------------	--	------------------

AVAILABLE FOR: AM-NORTH, EU, TURKEY, JAPAN AND SOUTH KOREA

<b>0P-2938</b>	<b>772G MISC MATL DECATUR</b> . . . . . 0 AVAILABLE FROM DECATUR FACTORY	<b>NC</b>
----------------	---	-----------

Only reference numbers that have the text  
 "ALSO AVAILABLE ON A MISCELLANEOUS ORDER" can be used on a misc order.

<b>0P-3760</b>	<b>772 BODY &amp; BODY ATT MISC MTL</b> . . . . . 0 AVAILABLE FROM DECATUR FACTORY	<b>NC</b>
----------------	---	-----------

Use this as the top level reference number when ordering a body or  
 body attachments without ordering a machine.

CATERPILLAR MACHINE PRICE LIST

**772G**

---

USE	REF NO.	Ship Weight lbs	LIST PRICE AT DEALER
-----	------------	--------------------	-------------------------

---

**NOTE**

TPMS REQUIRES: Download cable 305-5528 available from Cat Parts system. VIMS pc annual software subscription available through Cat Literature Distribution System. Caterpillar Dealer annual subscription: form number JERD-2138, Mail Code 969. Customer annual subscription: form number JERD-2175, mail code 47.

CATERPILLAR MACHINE PRICE LIST

**772G**

USE	REF NO.	LANE 1 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS**

**LANE SELECTION**

OP-9001	LANE 1 ORDER	0	NC
---------	--------------	---	----

**TIRES**

L	290-1170	TIRE, 21.00 R33 BS VMTP ** E-4 Bridgestone Radial; Manufacture PN 428818 TKPH=237 (TMPH=162); Max Distance Per Hour=21 km (13 mi) Tread Void Ratio=59%; Tread Depth=61 mm Provides maximum traction on soft ground with a high cut resistant compound.	7,923	\$-10,190
---	----------	--	-------	-----------

**BODY**

L	444-8463	BODY, FLAT FLOOR, STEEL LINER Recommended for hard rock, abrasive materials and applications with higher impact requirements. Good for feeding hoppers and crushers. Exhaust heat ready. All steel wear surfaces are 400 BHN. Includes base floor with additional floor liner of 16mm (.63"); sidewall liner of 8mm (.31"); frontwall liner of 8mm (.31"). Capacity: 31.0 m3 (40.5 yd3) SAE 2:1	24,391	\$64,800
---	----------	---	--------	----------

**WHEEL CHOCKS**

L	365-8571	WHEEL CHOCKS (ANSI) Wheel chocks with ANSI labels	93	\$1,270
---	----------	--	----	---------

**STORAGE PROTECTION**

OP-4616	STORAGE PROTECTION Rust Preventative applied.	0	NC
---------	--	---	----

**PACKING**

OP-0269	DOMESTIC TRUCK The rear dual tires, parts boxes and handrail skid shipped on a separate truck.	0	NC
---------	---	---	----

CATERPILLAR MACHINE PRICE LIST

**772G**

USE	REF NO.	LANE 1 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

**LANE 1 AM-NORTH OPTIONAL ATTACHMENTS**

***TIRE SWAP***

Note: The tires on the Lane 1 machines may vary due to the tire availability from the suppliers. The Lane 1 machines are built with the tire published in the mandatory Lane 1 section in most situations. If different tires are desired, OP-3715 tire swap surcharge needs to be added on the order.

OP-3715	TIRE SWAP SURCHARGE. ....	0	<b>\$2,070 NET</b>
---------	---------------------------	---	--------------------

CATERPILLAR MACHINE PRICE LIST

**772G**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**LANE SELECTION**

	0P-9002	LANE 2 ORDER . . . . .	0	NC
	0P-9003	LANE 3 ORDER . . . . .	0	NC

**REGIONAL PACKAGES**

L	444-8416	REGIONAL PKG, NORTH AMERICA . . . . . Accumulators with ANSI films.	113	NC
---	----------	--	-----	----

**PERFORMANCE PACKAGES**

L	561-8764	STANDARD PERFORMANCE . . . . . Tier 4 Engine without compression brake and extended life brakes.	0	\$4,150
L	444-8424	ADVANCED BRAKING PERFORMANCE . . . . . Tier 4 Engine with compression brake and extended life brakes.	11,718	\$8,030

**FEATURE PACKAGES**

**LIGHTING PACKAGES**

L	541-1712	LIGHTING, HALOGEN . . . . . Contains halogen flood lights.	0	NC
L	541-1713	LIGHTING, HID . . . . . Contains high intensity discharge (HID) high beam flood lights.	0	\$1,260
L	468-8678	LIGHTING, LED . . . . . Contains LED lights. -Front low beam headlights (4 LED/all facing forward) -Front high beam headlights (4 LED/all facing forward) -Rear lights (2 LED/all facing rear) -4 side work lights (4 LED/2 facing side and 2 facing rear tires) -1 engine bay light (1 LED/facing the RH side of engine)	0	\$6,610

**WEATHER PACKAGES**

L	444-8440	WEATHER PACKAGE, BASIC . . . . . For use in ambient temperature above -18C (0F). Contains 2 batteries and standard mirrors.	281	NC
L	444-8441	WEATHER PACKAGE, HEATED MIRRORS . . . . . For use in ambient temperature above -18C (0F). Contains 2 batteries, heated mirrors and ether aid.	283	\$1,160
L	444-8442	WEATHER PACKAGE, PREMIUM . . . . . For use in ambient temperature below -18C (0F). 120 Volt. Contains 2 batteries, fuel heater, fuel line heater, heated mirrors, ether aid, engine block heater and tarp for radiator inlet grill.	369	\$3,325

**SERVICE PACKAGES**

L	309-1646	GREASE FITTINGS, CLUSTERED . . . . . Includes clustered ground level grease fittings.	40	\$7,670
---	----------	--	----	---------

CATERPILLAR MACHINE PRICE LIST

**772G**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**FEATURE PACKAGES (CONT.)**

**SERVICE PACKAGES (Cont.)**

L	444-8435	<b>GREASE FITTINGS, CLSTRD W/FF</b> . . . . . 58 Includes clustered ground level grease fittings and fast fill.		\$9,080
L	361-9374	<b>AUTO LUBE</b> . . . . . 133 Autolube in place of clustered grease fittings.		\$17,830
L	444-8434	<b>AUTO LUBE WITH FAST FILL</b> . . . . . 151 Autolube in place of clustered grease fittings and fast fill.		\$19,110

**POWERTRAIN**

**EXHAUST PACKAGES**

L	375-7860	<b>EXHAUST GP.</b> . . . . . 48 Exhaust has full-time routing of exhaust through muffler which has lower sound levels.		NC
L	375-7859	<b>EXHAUST, BODY HEAT</b> . . . . . 137 Allows both full time body heat or muffler via muffler diverter box. CANNOT BE USED WITH: RUBBER LINER		\$6,280

**SUSPENSION SYSTEMS**

**SUSPENSION SYSTEMS**

L	444-8430	<b>SUSPENSION, EU</b> . . . . . 3,256 Suspension and Cylinders. complies with pressure vessel regulations.		NC
---	----------	---	--	----

**ELECTRICAL**

**ADVISOR LANGUAGE**

L	341-6731	<b>LANGUAGE, ADVISOR</b> . . . . . 0 Languages for Advisor are English/Spanish/French/German/Italian/Portuguese/Dutch/Norwegian/Swedish.		NC
---	----------	---	--	----

**OPERATOR ENVIRONMENT**

**CAB FILTRATION**

L	299-7274	<b>FILTER, AIR</b> . . . . . 18 For use when not ordering the pre cleaner.		NC
L	341-3855	<b>PRECLEANER GP.</b> . . . . . 35 For use in excessively dusty applications.		\$2,465



CATERPILLAR MACHINE PRICE LIST

**772G**

USE	REF NO.	<b>LANE 2 / 3 MANDATORY</b>	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------------	-----------------	----------------------

**TECHNOLOGY PRODUCTS**

**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet.

Authorization varies by country, please contact your Cat marketing representative with questions or click on the link below:  
<HTTPS://DEALER.CAT.COM/en/bt/otd/machine-price-list.html>  
 From there click on the "PRODUCT LINK Hardware Certification" link.

Product Link Pro series PL641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and health information for viewing in Product Link user applications. Cellular technology provides capabilities for frequent transmission and larger volumes of data.

Satellite Product Link uses a satellite network for remote transmission of asset information including location, utilization, and condition. For use in areas with poor or no cellular coverage.

The traction control feature is ideal for customers with everyday changing underfoot conditions such as muddy or soft ground due to water trucks or inclement weather. This feature is beneficial for operator efficiency and safety by allowing the operator to maintain control and higher travel speeds for the truck. Other benefits include lower tire cost by minimizing tire slippage and damage. This traction control electronically monitors and controls rear wheel slippage for greater traction and enhanced truck performance in poor underfoot conditions. If slippage exceeds a set limit based on turning angle and machine speed, the oil cooled disc brakes engage and slow the spinning wheel. Torque is then automatically transferred to the wheel with better traction.

L	509-3018	PL, CELL PL641 . . . . .	0	NC
		Includes Cellular Product Link, PL641 and standard steering control.		
L	509-3019	PL, CELL PL641 / TRACTION CTRL . . . . .	0	\$6,840
		Includes Cellular Product Link, PL641 and Traction Control System.		
L	444-8458	PL, SAT PL321 . . . . .	264	\$311 NET
		Includes Satellite Product Link, PL321 and standard steering control.		
L	444-8459	PL, SAT PL321 / TRACTION CTRL . . . . .	335	\$7,280
		Includes Satellite Product Link, PL321 and Traction Control System.		

CATERPILLAR MACHINE PRICE LIST

**772G**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**TIRES, RIMS, AND WHEELS**

**TIRES**

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice. However, if the tire type cannot be supplied we will contact the dealer to propose alternatives. The dealer needs to choose between an alternative tire or a "rims only" option (where available) within 72 hours. If no response is provided by the deadline, the order will default to the alternative tire and will be changed at that point. As a consequence of a possible tire change, the total machine price will be decreased or increased depending on the price of the new tire.

The information provided can be used to make a tire selection based on the particular conditions at the site. When available, the tire manufacturer should be consulted regarding proper tire selection.

Tread void ratio can be used to evaluate the damage resistance or traction capability of a particular tire. Tires with a numerically low tread void ratio tend to perform better in soft underfoot conditions; tires with a numerically high void ratio tend to perform better in harsh conditions where damage and puncture are a concern.

TKPH (ton kilometer per hour) and distance per hour are measures of the capability of the tire to withstand heat. Tires with a high TKPH or distance per hour ratings will be better suited for long, fast hauls but will be more susceptible to cuts and damage. Tires with a low TKPH or distance per hour rating are better suited for slow speed short hauls and provide improved cut and damage resistance.

Tires will have varying degrees of durability and wear rates.

L	290-1170	TIRE, 21.00 R33 BS VMTP ** E-4 . . . . .	7,923	\$-10,190
		Bridgestone Radial; Manufacture PN 428818 TKPH=237 (TMPH=162); Max Distance Per Hour=21 km (13 mi) Tread Void Ratio=59%; Tread Depth=61 mm Provides maximum traction on soft ground with a high cut resistant compound.		
L	366-7565	TIRE MX 21.00R33 ** E4. . . . .	7,169	\$770
		FOR USE IN LANE 3 ONLY Michelin Radial; Manufacture PN 067981 TKPH=280 (TMPH=191); Max Distance Per Hour=25 km (16 mi) Tread Void Ratio=61%; Tread Depth=71 mm Provides maximum traction on soft ground with a medium cut resistant compound.		
	274-1710	TIRES, ALLOWANCE FOR OMISSION . . . . .	0	\$-45,910
		Less: 1 set of six 21.00R33 (E4)		

CATERPILLAR MACHINE PRICE LIST

**772G**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**BODY**

**BODY PACKAGES**

Caterpillar offers a base body, a base body plus liner, sideboards, and a rubber liner option.

Caterpillar's updated body strategy provides our Customers with a wide range of body applications, with no need for Customer or Dealer modifications upon receipt from the factory. It is Caterpillar's recommendation to always use the Body Selection Guide (AEXC0673) and to know the customer applications prior to ordering any body and placing it into service. If the application is unknown, a single steel liner is recommended. When a body is placed into service, Caterpillar has provided clear and complete inspection guidelines (REHS5062) that should be followed to ensure maximum body life. Caterpillar will not make any recommendations that deviate from these published guidelines. Any deviations from the Body Selection Guide, including liner, are at the Dealer and Customer's discretion and responsibility. You may also contact the Caterpillar Global Construction & Infrastructure (GCI) or Caterpillar Global Mining (CGM) Regional Application Specialist with use of the body system selection guide or for selecting your body.

L	363-1500	<b>BODY, FLAT FLOOR</b> . . . . . 18,051 FOR USE IN LANE 3 ONLY Recommended for low abrasive materials with low impact. Not recommended for hard rock or abrasive applications. Good for feeding hoppers and crushers. All steel wear surfaces are 400 BHN. Exhaust heat ready. Includes one piece floor of 16mm (.63"); sidewall of 14mm (.55"); frontwall of 12mm (.48"). Capacity: 31.3 m3 (41.9 yd3) SAE 2:1	18,051	\$54,440
L	444-8463	<b>BODY, FLAT FLOOR, STEEL LINER</b> . . . . . 24,391 Recommended for hard rock, abrasive materials and applications with higher impact requirements. Good for feeding hoppers and crushers. Exhaust heat ready. All steel wear surfaces are 400 BHN. Includes base floor with additional floor liner of 16mm (.63"); sidewall liner of 8mm (.31"); frontwall liner of 8mm (.31"). Capacity: 31.0 m3 (40.5 yd3) SAE 2:1	24,391	\$64,800
L	444-8464	<b>BODY, FLAT FLOOR, RUBBER LINER</b> . . . . . 26,535 FOR USE IN LANE 3 ONLY Recommended for hard rock and abrasive applications. Highest level of impact and abrasion resistance. Not recommended for cohesive applications. Good for feeding hoppers and crushers. Includes base floor with additional rubber floor liner of 102mm (4"); steel sidewall liner of 8mm(.31") steel; frontwall liner of 8mm(.31") Capacity: 29.7 m3 (38.9 yd3) SAE 2:1 ONLY FOR USE WITH: 375-7860 EXHAUST	26,535	\$67,470
L	363-1550	<b>BODY, QUARRY</b> . . . . . 23,151 Recommended for limestone applications with good fragmentation or overburden applications with good fragmentation. Good for feeding hoppers and crushers. All steel wear surfaces are 400 BHN. Exhaust heat ready. Includes floor of 25mm (1"); sidewall of 14mm (.55"); transition of 16mm (0.64"); frontwall of 16mm (.63"). Does not include liner package. Capacity: 31.1 m3 (40.6 yd3) SAE 2:1	23,151	\$55,920

CATERPILLAR MACHINE PRICE LIST

**772G**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**BODY (CONT.)**

**BODY PACKAGES (Cont.)**

L	363-1510	<b>BODY, DUAL SLOPE</b> . . . . . 17,103 FOR USE IN LANE 3 ONLY Recommended for low abrasive materials with low impact. Not recommended for hard rock or abrasive applications. Good for load centering, stability, material retention on slopes. All steel wear surfaces are 400 BHN. Exhaust heat ready. Includes floor plates of 16mm (0.62"); sidewall plates of 10mm (0.39"); frontwall plates of 12mm (0.48"). Capacity: 31.2 m3 (40.8 yd3) SAE 2:1		<b>\$52,630</b>
L	444-8465	<b>BODY, DUAL SLOPE, STEEL LINER</b> . . . . . 23,908 FOR USE IN LANE 3 ONLY Recommended for hard rock, abrasive materials, and applications with higher impact requirements. Good for load centering, stability, material retention on slopes. All steel wear surfaces are 400BHN. Exhaust heat ready. Includes base floor with additional liner of 16mm (.63") sidewall liner of 8mm (0.31"). Frontwall liner of 8mm (.31"). Capacity: 30.9 m3 (40.4 yd3) SAE 2:1		<b>\$63,030</b>

**PACKING**

**STORAGE PROTECTION**

NOTE: For Chassis orders only, not Body orders.

OP-2671	<b>NO STORAGE PROTECTION</b> . . . . . 0 Please select this if you do not want Rust Preventative applied. ONLY FOR USE WITH: US dealers		<b>NC</b>
NOTE: If No Storage Protection is selected, then corrosion damage will not be covered under standard machine warranty.			
OP-4616	<b>STORAGE PROTECTION</b> . . . . . 0 Please select this if you want Rust Preventative applied.		<b>NC</b>

CATERPILLAR MACHINE PRICE LIST

**772G**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FEATURE PACKAGES**

**VISIBILITY PACKAGE**

L	549-6787	<b>VISIBILITY, CAMERA</b> . . . . . 0 Contains Work Area Vision System (WAVS) with single rearview camera.		\$3,215
L	341-3750	<b>VISIBILITY,CAMERA &amp; EU MIRRORS.</b> . . . . . 26 Contains ISO 5006 mirrors and Work Area Vision System (WAVS) with single rearview camera. The WAVS system with rear vision camera is available to monitor movement behind the truck for improved visibility and enhanced operator efficiency. REQUIRED BY: EU dealers		\$3,845

**TIRES, RIMS, AND WHEELS**

**WHEEL CHOCKS**

L	365-8571	<b>WHEEL CHOCKS (ANSI)</b> . . . . . 93 Wheel chocks with ANSI labels		\$1,270
---	----------	--	--	---------

**BODY**

**BODY ATTACHMENTS**

L	363-1520	<b>SIDEBARDS AS</b> . . . . . 779 Adds 155mm (6in) extension to the body side walls and provides 2.5 m3 (3.4 yd3) of additional volume. ONLY FOR USE WITH: ALL DUAL SLOPE, FLAT FLOOR AND QUARRY BODY AND LINER SYSTEMS		\$3,655
L	363-6370	<b>GUARD, OVERHEAD</b> . . . . . 210 Provides vertical sheet metal around perimeter to limit spillage from canopy.		\$1,295

**FLUIDS**

**ANTIFREEZE**

Standard factory antifreeze protects to -34C (-30F).

0P-2406	<b>ANTIFREEZE, -50C (-58F)</b> . . . . . 0	\$386 NET
0P-2402	<b>COOLANT, -40C (-40F)</b> . . . . . 0	\$199 NET

**FIELD INSTALLED ATTACHMENTS**

For Dealer Installed Options, please refer to Salesgram TEKQ1423 published in September 2017.

CATERPILLAR MACHINE PRICE LIST

**772G**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**PACKING**

MUST SELECT ONE

<b>OP-0269</b>	<b>DOMESTIC TRUCK</b> . . . . .	0	<b>NC</b>
	The rear dual tires, parts boxes and handrail skid shipped on a separate truck.		
<b>OP-0210</b>	<b>PACK, DOMESTIC TRUCK</b> . . . . .	0	<b>NC</b>
	ONLY FOR USE WITH: 0P-2938 772G MISC MATL DECATUR or 0P-3760 772 BODY & BODY ATT MISC MTL		