

CATERPILLAR MACHINE PRICE LIST

**908M**

908M COMPACT WHEEL LOADER  
 LEICESTER, ENGLAND

Ship Weight  
 lbs

LIST PRICE  
 AT DEALER

Standard Equipment:

**POWERTRAIN**

- Emissions Compliance
- Higher Regulated Countries
- Cat 55kw gross, C3.3B, HRC
- For Europe and Canada:
- US EPA Tier 4i or Tier 4f Certified
- EU Stage 3A or 3B Certified
- For United States:
- US EPA Tier 4f Certified
- EU Stage 3B Certified
- Engines are fitted with
- cold start plugs
- electric fuel priming pump
- Air cleaner, two-stage with visual indicator
- Closed Circuit Breather
- Hydraulically driven suction fan
- S-O-S sampling valves (engine oil and hydraulic oil)
- Two speed hydrostatic transmission with inching function, 12 mph-20kph maximum speed
- Frame mounted heavy duty axles with outboard planetary reduction
- Maintenance free,sealed for life, prop shaft and universal joints

**ELECTRICAL**

- 12 volt direct electric starting
- Ignition key start / stop switch
- 80 ampere alternator
- Maintenance free, sealed for life, heavy duty battery
- Battery disconnect switch
- Cab mounted fuse panel
- Service port connector for electronic diagnostics (ET)

**OPERATOR ENVIRONMENT**

- Gauges: -
- Fuel level
- Hydraulic oil temperature
- Engine coolant temperature
- Speedometer
- Operator station on isolation mounts
- Digital service hourmeter
- Operator warning system indicators:
- Master warning
- Parking brake applied
- Hydraulic oil pressure
- Engine oil pressure
- Coolant temperature
- Electrical system
- Hydraulic filter bypass

**OPERATOR ENVIRONMENT (Continued)**

- Multifunction joystick:
- Forward/neutral/reverse
- Gear 1/2 switch, low range
- Continuous flow, auxiliary
- Internal rear view mirror
- Suspension seat, adjustable wrist rest
- Interior/Exterior aux. power sockets
- Suspended brake/accel. pedals
- Cup holder
- Heavy duty easy clean floormat
- Personal storage
- Onboard digital display cluster
- 2 external mirrors - knockback
- Retractable seat belt, 50mm (2 in)

**COOLING**

- Extended life coolant antifreeze
- Protected to -33F (-36C)

**OTHER STANDARD EQUIPMENT**

- Z bar linkage with parallel lift
- 3rd valve aux hydraulics, standard flow
- Engine enclosure - lockable
- Lockable side door compartments
- Hydraulic oil level sight gauge
- Lockable fuel filler cap
- Radiator expansion bottle
- Quick release fuel fltr/water separator
- ECO engine oil drain
- Quick Coupler
- Parking Brake (Secondary Brake)
- Quick disconnect hydraulics, auxiliary
- Recovery hitch & pin
- Front and rear fenders
- Pressure test points
- Machine lifting/tie down points
- Loader end float function
- High intensity rear lights
- Reversing light
- E coat primer
- Self-cancelling direction indicators

CATERPILLAR MACHINE PRICE LIST

**908M**

908M COMPACT WHEEL LOADER LEICESTER, ENGLAND	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

**Lane 2 is reserved for the Base Order Management Program  
 Please use Lane 2 when placing orders that are part of the Base Order  
 Management program.**

<b>550-3585</b>	<b>908M WHEEL LOADER DCA1</b> ..... 0 LANE 1 - AVAILABLE FROM CLAYTON PRODUCT DISTRIBUTION CENTER	<b>\$126,960</b>
-----------------	--	------------------

- INCLUDES:  
 437-9013 908M WHEEL LOADER S3B CERT  
 438-1876 CAB, DELUXE, SINGLE BRAKE  
 539-7204 SEAT, DELUXE  
 236-8015 SEAT BELT, RETRACTABLE 3"  
 308-0189 VALVE, DRAIN, ECO  
 313-1722 LIGHTS, ROADING RH DRIVE DIP  
 377-7559 PRECLEANER  
 423-3083 ALARM, BACK UP  
 433-3258 SECURITY SYSTEM, NONE  
 437-9054 ENGINE, 55KW, C3.3B, T4F, HRC  
 437-9056 SOUND SUPPRESSION, STANDARD  
 437-9070 TRANS 22 MPH DIFF LOCK PILOT  
 437-9092 JOYSTICK, PILOT, TANDEM VALVE  
 437-9132 AIR CONDITIONER, AND HEATER  
 447-0747 FEATURE PACKAGE, LOAD/ROAD  
 447-9417 FAN, COOLING, ON DEMAND  
 448-9539 LIGHTS, CAB, WORKING (FOUR)  
 451-4357 CPLR, VERT, STD FLO, PILOT, SW  
 454-2908 HYDRAULIC OIL, STANDARD  
 454-2910 ANTIFREEZE, -50C (-58F)  
 455-8485 HARNESS, WIRING, WT, VERTICAL  
 508-0797 PRODUCT LINK, CELLULAR, PL240

<b>437-9013</b>	<b>908M WHEEL LOADER S3B CERT</b> ..... 0 LANE 2 - AVAILABLE FROM LEICESTER FACTORY LANE 3 - AVAILABLE FROM LEICESTER FACTORY	<b>\$105,280</b>
-----------------	---	------------------

CATERPILLAR MACHINE PRICE LIST

**908M**

908M COMPACT WHEEL LOADER LEICESTER, ENGLAND	Ship Weight lbs	LIST PRICE AT DEALER
---	--------------------	-------------------------

<b>551-1285</b>	<b>908M CWL AG HANDLER</b> . . . . . 0	<b>\$105,280</b>
	908M Ag Handler: Includes Ag handler branding and limits selections to drive performance and comfort enhancing features, an expectation of the Cat Ag Handler range. LANE 2 - AVAILABLE FROM LEICESTER FACTORY LANE 3 - AVAILABLE FROM LEICESTER FACTORY	

REQUIRES: 437-9070 TRANS 22MPH (35KPH) DIFF LOCK E/H  
 437-9054 ENGINE, 55KW, C3.3B, T4  
 308-0189 VALVE, DRAIN, ECO  
 377-7559 PRECLEANER  
 438-1876 CAB, DELUXE, SINGLE BRAKE  
 539-7204 SEAT, DELUXE  
 437-9132 AIR CONDITIONER AND HEATER  
 447-0747 FEATURE PACKAGE, LOAD/ROAD OR  
 463-8332 FEATURE PACKAGE, LOAD/ROAD, LCV  
 462-2556 TIRES, 400/70 R20, MX, BIBLOAD OR  
 295-4000 TIRES, 400/70,R20, MX, XMCL  
 496-9971 LIGHTS, CAB, WORKING LED  
 260-5501 BEACON, ROTATING  
 423-3083 ALARM, BACK UP  
 455-8485 HARNESS, WIRING, WT, VERTICAL OR  
 455-8486 HARNESS, WIRING, WT, HORIZONTAL  
 541-4413 RADIO, FM BLUETOOTH

<b>0G-0428</b>	<b>908M MISC MTRL LEICESTER</b> . . . . . 0	<b>NC</b>
	Use this top level reference when ordering miscellaneous material without ordering a machine.	

CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 1	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	--------	-----------------	----------------------

**LANE 1 AM-NORTH MANDATORY ATTACHMENTS**

**LANE SELECTION**

0P-9001	LANE 1 ORDER . . . . .	0	NC
	Select this option when ordering from Distribution Center.		

**TIRE SELECTION**

L	295-4000	TIRES, 400/70 R20, MX, XMCL . . . . .	0	\$1,180
		Michelin. Long life traction tire for soft ground conditions Width across tires 79in/1995mm		

**INSTRUCTIONS AND OPERATION MANUALS**

Must select

421-8926	SERIALIZED TECHNICAL MEDIA KIT . . . . .	0	NC
	Kit will include instructions and parts CD in the legally required language, based on the shipping address. Any additional media such as a paper parts manual, not included in the kit, can be ordered through the media website. <a href="https://oos.midlandcorp.com/CAT/Default.aspx">https://oos.midlandcorp.com/CAT/Default.aspx</a>		

**INSTRUCTION DECALS**

L	462-0852	INSTRUCTIONS, ANSI . . . . .	0	NC
		This package includes picto decals as required for the USA. (excl. Canada).		
L	462-0853	INSTRUCTIONS, ISO . . . . .	0	NC
		This package includes picto decals as required for all countries (incl. Canada) excluding the USA.		

**PREP PACK**

519-5210	PREP PACK, EMC . . . . .	0	NC
	Decal to certify the machine meets emc regulations REQUIRED BY: Canadian Dealers		

**PACKING**

0P-0210	PACK, DOMESTIC TRUCK . . . . .	0	NC
	Must select for all DCAs. CANNOT BE USED WITH: EU LAST MILE DEALERS		
0P-4299	PACKING, LAST MILE PROGRAM . . . . .	0	NC
	ONLY FOR USE WITH: EU LAST MILE DEALERS		
0G-3273	RUST PREVENTATIVE APPLICATOR . . . . .	0	\$110 NET
	Preparation for shipment - Silix applicators for shipment by sea		

CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 1 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

**LANE 1 AM-NORTH OPTIONAL ATTACHMENTS**

***BUCKETS***

P	261-1396	BUCKET - LM 2.0 YD3 . . . . .	1,135	\$4,514
		81" (2060mm) wide, incl 1 piece Bolt-on cutting edge		
P	284-9279	BUCKET - GP 1.2 YD3 . . . . .	869	\$3,360
		74" (1880mm) wide With bolt-on cutting edge.		
P	286-0581	BUCKET - GP 1.4 YD3 . . . . .	979	\$3,704
		81" (2060mm) wide With bolt-on cutting edge.		
P	384-1700	BUCKET - GP, 1.0 YD3 . . . . .	0	\$3,190
		74" (1880mm) wide, incl 1 piece Bolt-on cutting edge		

**WORKTOOLS**

SEE WT CWL price list to order Work Tools such as:  
 General Purpose Buckets with various G.E.T.  
 Multi Purpose Buckets with various G.E.T.

Light Material Buckets with bolt on edge  
 Grapple Buckets with bolt on edge  
 Pallet Forks & Carriages  
 Brooms, Angle & Pickup

CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**LANE SELECTION**

OP-9002	LANE 2 ORDER . . . . .	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program		
OP-9003	LANE 3 ORDER . . . . .	0	NC

**REGIONAL PACKAGES**

**ROADING LIGHTS - SELECT ONE FROM:**

313-1722	LIGHTS, ROADING RH DRIVE DIP . . . . .	0	NC
	Roading lights, for driving on right hand side of road.		

**POWERTRAIN**

**ENGINE - Select one**

L	437-9054	ENGINE, 55KW, C3.3B, T4F, HRC . . . . .	0	NC
		US EPA Tier 4f/EU Stage 3B Certified		
		FOR USE WITH 437-9013 908M CWL BASE MACHINE		

**TRANSMISSION - Select one**

Select the correct transmission to allow the required combination of:

Axles (with/without DL)  
 Speed (12mph/20kph or 22mph/35kph)

L	437-9074	TRANS 12 MPH STD E/H . . . . .	0	NC
		Open differentials for E/H joystick		
L	437-9065	TRANS 12 MPH DIFF LOCK E/H . . . . .	0	\$377
		Diff lock for E/H joystick		
L	437-9070	TRANS 22 MPH DIFF LOCK E/H . . . . .	0	\$1,470
		Diff lock for E/H joystick		

**SOUND SUPPRESSION - Select one**

L	437-9056	SOUND SUPPRESSION, STANDARD . . . . .	0	NC
		CANNOT BE USED BY: EU DEALERS		

**DRAIN VALVES - Select one**

L	308-0190	VALVE, DRAIN STD . . . . .	0	NC
		Threaded drain plug fitted in base of hydraulic & fuel tanks.		
L	308-0189	VALVE, DRAIN, ECO . . . . .	0	\$155
		Auto drain plug fitted in base of hydraulic & fuels tanks. Fluid drains when drain tube is screwed into plug.		

**AIR CLEANERS - Select one**

L	273-9577	AIR INTAKE, STANDARD . . . . .	0	NC
		Two-Stage Air Cleaner with in built centrifugal pre-cleaner		
L	377-7559	PRECLEANER . . . . .	0	\$239
		Cyclone precleaner for use in medium to heavy dust environments		

CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**POWERTRAIN (CONT.)**

**COOLING FANS - Select One**

L	447-9417	FAN, COOLING, ON DEMAND . . . . . 0		\$412
		Provides on-demand cooling capability for faster warm-ups, no over cooling, reduced fuel consumption and reduced sound levels. Note: Required when operating in ambient temperatures below -18C (0F)		

**HYDRAULICS**

**WORKTOOL PACKAGES**

Select the required choice of both:

COUPLER: Vertical (previously SSL style) or  
 Horizontal Pin (ISO style) 852mm wide

Horizontal Pin (Atlas style)940mm wide(Not available in all regions)

FLOW: Standard or High Auxiliary Flow

L	451-4357	CPLR, VERT, STD FLOW . . . . . 0		NC
		SSL style coupler Provides a dedicated switch in the cab to operate coupler. 85 ltrs (22 US gallons) per minute		
L	451-4363	CPLR, VERT, HI FLOW . . . . . 0		\$5, 610
		SSL style coupler Provides a dedicated switch in the cab to operate coupler. 130 ltrs (34 US gallons) per minute Includes Worktool Wiring Harness = 14 pin		
L	451-4360	CPLR HPL-ISO,STD FLOW . . . . . 0		\$447
		ISO style coupler Provides a dedicated switch in the cab to operate coupler. 85 ltrs (22 US gallons) per minute		
L	451-4366	CPLR HPL-ISO,HI FLOW . . . . . 0		\$5, 610
		ISO style coupler Provides a dedicated switch in the cab to operate coupler. 130 ltrs (34 US gallons) per minute Includes Worktool Wiring Harness = 8 pin		

**HYDRAULIC HOSE GUARDS**

Select one when ordering a canopy, dependent on whether standard flow or high flow auxiliary hydraulics have been selected

L	455-2291	GUARD, HOSE (VERT/STD CPLR) . . . . . 0		NC
		Hydraulic hose sheaths required with Canopy. REQUIRES: 451-4357 CPLR, VERT, STD FLO,E/H ,SW CANNOT BE USED WITH: Any Cab.		
L	320-8425	GUARD, HOSE . . . . . 0		NC
		Hydraulic hose sheaths required with Canopy. REQUIRES: 451-4363 CPLR, VERT, HI FLO,E/H ,SW CANNOT BE USED WITH: Any Cab		
L	464-2017	GUARD, HOSE (HORIZ/STD CPLR) . . . . . 0		NC
		Hydraulic hose sheaths required with Canopy. REQUIRES: 451-4360 CPLR HORIZ, STD FLO,E/H ,SW CANNOT BE USED WITH: Any Cab		
L	455-2293	GUARD, HOSE (HORIZ/HIFLO CPLR) . . . . . 0		NC
		Hydraulic hose sheaths required with Canopy. REQUIRES: 451-4366 CPLR, HORIZ, HI FLO,E/H ,SW CANNOT BE USED WITH: Any Cab		

CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**ELECTRICAL**

**PRODUCT LINK**

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitoring performance of your assets, it helps keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet

Availability varies by country, please contact your Cat marketing representative with questions or click on the link below:  
[HTTPS://DEALER.CAT.COM/en/bt/otd/machine-price-list.html](https://dealer.cat.com/en/bt/otd/machine-price-list.html)  
 From there click on the "PRODUCT LINK Hardware Certification" link.

L	508-0797	<b>PRODUCT LINK, CELLULAR, PL240</b> . . . . . 0 PL240 uses cellular networks to transmit hours and location for to the Product Link's remote monitoring web interface. It is recommended for customer with smaller fleet because it is low cost subscription, low cost hardware and offer very basic features. It does not support integration with onboard data communication links.		NC
L	509-6603	<b>PRODUCT LINK, CELLULAR, PL641</b> . . . . . 0 PL641 uses GSM and CDMA 3G cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		\$833

**OPERATOR ENVIRONMENT**

**CAB/CANOPY - Select one**

L	438-1874	<b>CAB, STANDARD, SINGLE BRAKE</b> . . . . . 0 ROPS/FOPS certified Fixed steer column, fixed window (left),fixed window (right), heated rear window, coat hook, cabin light, sun visor and lockable storage box.		\$3,540
L	438-1875	<b>CAB, COMFORT, SINGLE BRAKE</b> . . . . . 0 ROPS/FOPS certified Tilt steer column, radio ready, sliding window (left), fixed window (right), heated rear window, coat hook, cabin light, sun visor and lockable storage box.		\$5,280
L	438-1876	<b>CAB, DELUXE, SINGLE BRAKE</b> . . . . . 0 ROPS/FOPS certified Adjustable steering column, sliding window (left), sliding window (right), heated rear window, coat hook, cabin light, sun visor, radio ready kit (wiring,speakers, aerial and grilles) and lockable storage box. REQUIRES: 539-7204 SEAT DELUXE		\$6,000
L	438-1873	<b>CANOPY, STANDARD, TWIN BRAKE</b> . . . . . 0 ROPS/FOPS certified Fixed steer column, coat hook, sun visor CANNOT BE USED BY: EU DEALERS		\$-1,235

**SEATS**

L	539-7203	<b>SEAT, VINYL</b> . . . . . 0 Fully adjustable mechanical suspension with vinyl covered seat upper and mid height backrest. ONLY FOR USE WITH: 438-1873 Canopy		NC
---	----------	---	--	----



CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**OPERATOR ENVIRONMENT (CONT.)**

**SEATS (Cont.)**

L	539-7204	SEAT, DELUXE . . . . . 0		\$775
		Fully adjustable air ride suspension with fabric covered seat upper, mid height backrest, mechanical lumbar support, heated cushions and armrests. REQUIRES: 438-18765 Cab, deluxe - AM-NORTH ONLY FOR USE WITH: 438-1874 Cab, std, 438-1875 Cab, comfort or 438-1876 Cab, deluxe		
L	552-3734	SEAT, DELUXE PLUS . . . . . 0		\$1,060
		Fully adjustable air ride suspension with fabric covered seat upper, mid height backrest, mechanical lumbar support, heated and adjustable comfort cushions, and armrests. REQUIRES: 438-1876 Cab, deluxe - AM-NORTH ONLY FOR USE WITH: 438-1874 Cab std, 438-1875 Cab comfort or 438-1876 Cab, deluxe		

**SEAT BELTS**

L	236-8015	SEAT BELT, RETRACTABLE 3" . . . . . 0		\$244
		High Visibility Orange 76MM (3 inch) wide seat belt. Recommended for customer running extended hours for enhanced comfort. Required in British Columbia, Oregon, California		
L	550-9815	SEAT BELT, RETRACTABLE 2" . . . . . 0		NC
		High Visibility Orange 51MM (2 inch) wide seat belt.		

**ENVIRONMENTAL CONTROL**

Select one with enclosed cab

L	437-9131	HEATER . . . . . 0		NC
L	437-9132	AIR CONDITIONER, AND HEATER . . . . . 0		\$5,510

**JOYSTICK CONTROLS - Select one**

L	437-9092	JOYSTICK,E/H,TANDEM VALVE . . . . . 0		NC
		*Recommended for most North American Dealers*and those who are looking operating specialised rotating work tools in unique applications. Tuned for applications where hydro-mechanical work tool utilisation is high. The valve priority order reflects the following: (1) Work tool Tilt (2) Loader arm lift (3) Auxiliary hydraulics (Typically recommended for snow blower operations)		
L	464-2118	JOYSTICK,E/H, TANDEM, LCV . . . . . 0		NC
		Tandem valve set with additional Load Check Valves. Please note one of the LCV Joystick options is required if a LCV Feature option is to be selected.		

CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**OPERATOR ENVIRONMENT (CONT.)**

**JOYSTICK CONTROLS - Select one (Cont.)**

L	437-9094	JOYSTICK,E/H,PARALLEL VALVE . . . . . 0 *Recommended for most European dealers* and those who are looking for standard loader arm and auxiliary control characteristics for general duties. Hydro-mechanical work tool operation may limit loader lift performance in which case rotating hydro-mechanical work tool operation may need to be interrupted before regular loader operation can take place. (Typically effects snow blower operations)		NC
L	464-2117	JOYSTICK,E/H, PARALLEL, LCV . . . . . 0 Parallel valve set with additional Load Check Valves. Please note one of the LCV Joystick options is required if a LCV Feature option is to be selected.		NC

**MACHINE SECURITY SYSTEM - Select one**

Please note: this is a mandatory selection on machines with an enclosed cab but is NOT available on machines with a canopy.

L	433-3258	SECURITY SYSTEM, NONE . . . . . 0		NC
L	423-6165	SECURITY SYSTEM, MACHINE . . . . . 0 Caterpillar Machine Security System (MSS) to manage access to the machine. Machine is shipped with system inactive. Requires ET to activate		\$1,030

**FEATURE PACKAGES**

Select one

L	449-1896	FEATURE PACKAGE, BASIC . . . . . 0 Basic package does not include new electronically controlled features such as Ride Control, Return To Dig, Electronic Throttle Lock, Rimpull Control, Creeper Control, Implement Modulation control nor Drivetrain Aggressiveness control. FOR USE WITH: 4379092 Joystick, 4379093 Joystick 4379094 Joystick		NC
L	449-1897	FEATURE PACKAGE, BASIC, LCV . . . . . 0 This package includes Load Check Valves in addition to all the features of the 'Basic' feature package. FOR USE WITH: ENCLOSED CABS & 4642117 OR 4642118 Joystick		\$2,325
L	447-0747	FEATURE PACKAGE, LOAD/ROAD . . . . . 0 This package contains all the electronically controlled features such as Ride Control, Return To Dig, Electronic Throttle Lock, Rimpull Control, Creeper Control, Implement Modulation control and Drivetrain Aggressiveness control. FOR USE WITH: 4379092 Joystick, 4379093 Joystick 4379094 Joystick, 4379095 Joystick		\$5,550
L	463-8332	FEATURE PACKAGE, LOAD/ROAD,LCV . . . . . 0 Except for Ride Control, this package includes Load Check Valves in addition to all the features of the 'Road/Load' feature package. FOR USE WITH: ENCLOSED CABS & 4642117 or 4642118 Joystick		\$7,870

CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**TIRES, RIMS, AND WHEELS**

**TIRES**

All tires include one-piece rim (quantity = 4)

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice, but we reserve the right to propose alternate tires. Any proposed change will be reviewed with the dealer prior to machine shipment. The machine will ship only with the dealer acceptance of the proposed alternative tire.

**TIRES AVAILABLE FROM DUNLOP**

L	259-2925	TIRES, 405/70 R20, DL, SPT9 . . . . . 0 Dunlop non-directional tire for mixed on road and off road service. Width across tires 79in/1995mm		\$1,525
---	----------	---	--	---------

**TIRES AVAILABLE FROM MICHELIN**

L	462-2556	TIRES, 400/70 R20, MX, BIBLOAD . . . . . 0 Michelin Bibload Hard Surface. More effective on hard surfaces for agricultural and construction applications. Offers better damage resistance, smooth ride and more traction. Width across tires 1993 mm / 78.5 ins		\$1,970
L	295-4000	TIRES, 400/70 R20, MX, XMCL . . . . . 0 Michelin. Long life traction tire for soft ground conditions Width across tires 79in/1995mm		\$1,180

**TIRES AVAILABLE FROM NOKIAN**

L	457-5850	TIRES, 360/80 R20, NK, TRI 2 . . . . . 0 Nokian.All season tire with excellent grip, high load bearing capacity and superior driving comfort. The unique tread pattern makes this tire the perfect choice for plowing and snow removal applications. Applications both on road and off road. Width across tires 78.6in/1997mm		\$3,950
---	----------	--	--	---------

**FLUIDS**

**HYDRAULIC OIL - Select one**

L	454-2908	HYDRAULIC OIL, STANDARD . . . . . 0		NC
L	304-9376	HYDRAULIC OIL, BIODEGRADABLE . . . . . 0		\$1,350

**ENGINE COOLANT - Select one**

L	454-2909	ANTIFREEZE, -36C (-32F) . . . . . 0		NC
L	454-2910	ANTIFREEZE, -50C (-58F) . . . . . 0 Provides protection to -50C (-58F) with 70% Cat Extended Life Coolant and 30% deionized water. Note: If operating in ambient temperatures below -18C (0F), the demand cooling fan is required.		\$200

CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 2 / 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	----------------------	-----------------	----------------------

**INSTRUCTIONS**

***DECAL PACKAGES***

L	462-0852	INSTRUCTIONS, ANSI . . . . . 0 This package includes picto decals as required for the USA. (excl. Canada).		NC
---	----------	--	--	----

***INSTRUCTIONS AND OPERATION MANUALS***

	421-8926	SERIALIZED TECHNICAL MEDIA KIT . . . . . 0 Kit will include instructions and parts CD in the legally required language, based on the shipping address. Any additional media such as a paper parts manual, not included in the kit, can be ordered through the media website. <a href="https://oos.midlandcorp.com/CAT/Default.aspx">https://oos.midlandcorp.com/CAT/Default.aspx</a>		NC
--	----------	---	--	----

CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**NOTE**

Please note these options may effect whether the machine order is Lane 2 or Lane 3.

**ELECTRICAL**

P	448-9539	<b>LIGHTS, CAB, WORKING HALOGEN</b> . . . . . 0 Four halogen floodlights mounted beneath cab roof, two front, two rear.		\$600
P	496-9971	<b>LIGHTS, CAB, WORKING LED</b> . . . . . 0 Four LED floodlights mounted beneath roof, two front, two rear.		\$820
P	260-5501	<b>BEACON, ROTATING</b> . . . . . 0 Includes the beacon switch & indicator lamp necessary to operate a beacon Must be ordered as 'Not-Installed'.		\$389 NI
P	423-3083	<b>ALARM, BACK UP</b> . . . . . 0 Required for machines sold into North America		\$196
P	455-8485	<b>HARNESS, WIRING, WT, VERTICAL</b> . . . . . 0 Supplies electrical power for valves on selected Work Tools. Included in: Hi Flow Couplers FOR USE WITH: STANDARD FLOW VERTICAL COUPLERS CANNOT BE USED WITH: HORIZONTAL COUPLERS OR VERTICAL HI FLOW COUPLERS		\$327
P	455-8556	<b>HARNESS, WIRING, WT, HORIZONTAL</b> . . . . . 0 Supplies electrical power for valves on selected Work Tools. Included in: Hi Flow Couplers FOR USE WITH: STANDARD FLOW HORIZONTAL COUPLERS CANNOT BE USED WITH: VERTICAL COUPLERS OR HORIZONTAL HI FLOW COUPLERS		\$327
P	345-3556	<b>HEATER, ENGINE COOLANT, 120V</b> . . . . . 0 For additional cold weather startability. Note: If operating in ambient temperatures below -18C (0F), the demand cooling fan is required		\$195

**OPERATOR ENVIRONMENT**

P	279-0643	<b>BLIND, REAR</b> . . . . . 0 CANNOT BE USED ON MACHINES WITH AN OPEN CANOPY		\$305
P	260-5499	<b>RADIO READY, FOR BASE CAB</b> . . . . . 0 Required if Cat Radio to be fitted in 438-1874 Base Cab.		\$322
P	541-4413	<b>RADIO, AM/FM BLUETOOTH</b> . . . . . 0 Cat FM Radio with bluetooth, aux input & microphone. ONLY FOR USE WITH: 438-1875 CAB, COMFORT 438-1876 CAB, DELUXE		\$550

**GUARDS**

**HOSE GUARDS**

P	321-1299	<b>GUARD, HORIZONTAL COUPLER</b> . . . . . 0 Guard designed to protect hoses to the Horizontal Coupler arrangement. For use in arduous conditions. FOR USE WITH: Horizontal Couplers(ISO), 451-4360, 451-4366 (ATLAS) 471-6043		\$66
---	----------	--	--	------

CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**OTHER ATTACHMENTS**

**CUSTOM COLOR**

P	479-0229	CUSTOM COLOR . . . . . 0		\$3,575
		Please contact ORDER ENTRY GROUP before placing CUSTOM COLOR requests. Black components remain black. REQUIRES: 4 digit RAL colour specification ONLY FOR USE WITH: LANE 3		

**WHEEL CHOCK**

P	303-2126	WHEEL CHOCK . . . . . 0		\$129
		CANNOT BE USED WITH: 447-9427 PREP PACK, TUV 20KPH 447-9428 PREP PACK, TUV 35KPH		

**WORK TOOLS**

**FORKS - CLASS 3**

Requires 0G-3149, PACKING, MISCELLANEOUS MATERIAL

Either: refer to Work Tools sections or  
 WT CWL price list to order Work Tools such as:  
 General Purpose Buckets with various G.E.T.  
 Multi Purpose Buckets with various G.E.T.  
 Light Material Buckets with bolt on edge  
 Grapple Buckets with bolt on edge  
 Pallet Forks & Carriages  
 Brooms, Angle & Pickup  
 Skid Steer Loader Worktools

**BUCKETS**

**GENERAL PURPOSE BUCKETS FOR USE WITH VERTICAL PIN COUPLER**

(Previously Skid Steer Coupler)

W	286-0581	BUCKET - GP 1.4 YD3 . . . . . 979		\$3,704
			979	\$3,704 NI
		With bolt-on cutting edge. 2060mm wide		

**FLUIDS**

**COLD WEATHER FUEL**

May select

L	484-5263	FUEL, COLD WEATHER . . . . . 0		\$72
		Provides low temperature diesel fuel (to -30 celsius).		

CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS**

**FIELD INSTALLED ATTACHMENTS**

The following attachments can be ordered from parts distribution. Please contact Part Distribution for current prices.

- P 466-1959 KIT, CCB HEATER**  
 Required for operating in temperatures BELOW -32C (-18F). Provides a second heater for the engine closed crankcase breather (CCB) system. Estimated time to install: 1.0 Hr

**KITS AVAILABLE ONLY FROM SUPERTRAK**

FOB: Punta Gorda, Florida, USA

Order the following kits directly from Supertrak  
 800.446.9858 --- 941.505.7800 --- www.Supertrak.com  
 Supertrak is responsible for the sales, parts, support and warranty.  
 All dealer net prices below are for reference only, and are subject to change by Supertrak.  
 Additional information and pictures are located on DEALER.CAT.COM in the Compact Wheel Loader, 906 - 908 area.

Note: Reference application specific OSHA requirements (e.g. window mesh spacing standards), particularly in forestry applications.

**The following kits are specific to the 906/907/908 machines.**

**CT2026-005 KIT, FRONT WINDOW GUARD. 2650 USD NET**  
 Bolt-on kit provides upper and lower front window protection along with upper cab light guarding. 3" (75mm) mesh opening with 1/4" (6mm) wire diameter can be customized to meet the application requirements. Upper window guard opens with overcenter latches for easy window cleaning.  
 Estimated installation time: 3 hrs.

**CT2026-008 KIT, REAR WINDOW GUARD. 3769 USD NET**  
 Guards provide protection for rear lights, rear window, and rear side corner windows. 3" (75mm) mesh opening with 1/4" (6mm) wire diameter can be customized to meet the application requirements. Side and corner guards open with latches for easy cleaning. Rear center portion is fixed, yet cleaning clearance is provided. Some light welding is required.  
 Estimated installation time: 5 hrs.

**CT2026-003 KIT, LOWER WINDOW DEBRIS GUARD. 679 USD NET**  
 Steel shields protect the lower front windows in mulching applications. Visibility is not obscured, as each shield is viewed within the front tire profile. Some light welding is required.  
 Estimated installation time: 2hrs.

CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

***KITS AVAILABLE ONLY FROM SUPERTRAK (Cont.)***

CT2026-009 KIT, CAB DOOR SCREENS. 1652 USD NET  
 Guards protect the door glass from top to bottom on both sides.  
 The guards are hinged for cleaning with bolts for fasteners.  
 3" (75mm) mesh opening with 1/4" (6mm) wire diameter can be customized  
 customized to meet the application requirements. Some light  
 welding required.  
 Estimated installation time: 2.5hrs.

CT2007-032 KIT, BRAKE DEBRIS GUARD. 435 USD NET (906/907)  
 Prevents debris intrusion between the front axle and main frame,  
 protecting the brake assembly. Some light welding is required.  
 Estimated installation time: 2hrs.

CT2026-001 KIT, BRAKE LINE GUARDS. 654 USD NET  
 Bolt-on design shields the outboard brake lines on the front axle.  
 Estimated installation time: 0.5hrs

CT2026-002 KIT, TOWER HOSE GUARD. 632 USD NET  
 Left and Right guards protect lift cylinder hoses in main frame.  
 Compatible with or without front fenders. Bolt-on design attaches  
 to existing mounting pattern for front fenders.  
 Estimated installation time: 0.5hrs.

CT2026-006 KIT, RH BELLY GUARD. 549 USD NET  
 Two piece guard protects the hydraulic system components and  
 hoses. Some light welding is required.  
 Estimated installation time: 3hrs.

CT2026-007 KIT, LAMP COVER GUARD. 486 USD NET  
 Bolt-on lamp guards are reversible from side to side and allow  
 some lamp positioning adjustment. Mesh design incorporates  
 1" (25mm) squares.  
 Estimated installation time: 0.5hrs.

MT1228-006 KIT, FUEL FILLER, METAL. 787 USD NET  
 Bolt-on metal design provides a robust, damage resistant fuel  
 neck. Unit has a strainer and an integral lip to reduce fuel  
 tank contamination. Includes locking fuel cap with a non-standard,  
 unique key.  
 Estimated installation time: 0.5hrs.



CATERPILLAR MACHINE PRICE LIST

**908M**

USE	REF NO.	LANE 2 / 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	---------------------	-----------------	----------------------

**FIELD INSTALLED ATTACHMENTS (CONT.)**

***KITS AVAILABLE ONLY FROM SUPERTRAK (Cont.)***

CT2026-004 KIT, REAR HALF FENDER UNDER CAB DEBRIS KIT. 897 USD NET (906/907)  
 Bolt-on steel fenders include integral seals which also prevent debris intrusion underneath operator station.  
 Estimated installation time: 2hrs.

CT2007-043 (906/907) KIT, REAR HOOD GUARD. 2,299 USD NET  
 Swing out gate protects engine enclosure from blunt impacts while reversing. Kit mounts to the rear counterweight.  
 Estimated installation time: 3 hrs.

CT2007-044 (906/907) KIT, TAIL LIGHT GUARD. 404 USD NET  
 Steel plate guards prevent damage from blunt impacts while reversing. Guards mount to the rear counterweight.  
 Estimated installation time: 1 hr.

CT2007-046 KIT, DRIVESHAFT GUARD. 3,056 USD NET  
 Guard prevents twine and baling wire from getting wound around the driveshaft and also prevents blunt impact damage. Protection is maintained with steering and oscillation of the chassis.  
 Estimated installation time: 2.5 hrs.

**PACKING**

***SHIPPING***

0G-3273	RUST PREVENTATIVE APPLICATOR. . . . . 0 Preparation for shipment - Silix applicators for shipment by sea. Required by: German Dealers CANNOT BE USED WITH: EU LAST MILE DEALERS	\$110 NET
0G-3150	PACK, ROLL ON/ROLL OFF BY SEA . . . . . 0 CANNOT BE USED WITH: EU LAST MILE DEALERS	\$223 NET
0G-3149	PACK, MISCELLANEOUS MATERIAL . . . . . 0 Required by 'not-installed' worktools and buckets.	NC