

CATERPILLAR MACHINE PRICE LIST

950GC

950GC WHEEL LOADER QINGZHOU, CHINA	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------------	--------------------	-------------------------

Standard Equipment:

POWERTRAIN

Engine Cat C7.1 and ATAAC
 Torque converter
 Transmission, automatic, power shift (4F/3R), kick-down function, overspeed protection
 Brakes, full hydraulic enclosed wet-disc
 EIMS (Engine Idle Management System)
 Fan, radiator, electronically controlled, hydraulically driven, temperature sensing, on demand
 Filter, fuel primary-water separator/ secondary
 Radiator, unit core (9.5 fpi) with ATAAC
 Starting aid, glow plugs
 Switch, transmission neutralizer lockout

HYDRAULICS

Load sensing implement system pilot operated
 Dedicated load sensing steering pump
 Dedicated brake and fan gear pump

ELECTRICAL

Alarm, back-up/main disconnect switch
 Alternator (145-amp, brush type)
 Batteries (2), maintenance free
 Ignition key; start/stop switch
 Lighting system, halogen (6 total)
 -Four (4) halogen work lights
 -Two (2) halogen road lights
 Starting and charging system (24-volt)
 Starter, electric (heavy duty)

OPERATOR ENVIRONMENT

Air conditioning (HVAC) with 10 vents and filter unit located outside of cab
 Bucket/work tool function lockout
 Cab, pressurized and sound suppressed
 Hydroformed (ROPS/FOPS) structure
 12V power port (10A)
 Coat hook
 Pilot hydraulic controls, lift and tilt function
 Computerized monitoring system
 Gauges:
 -Engine coolant temperatures/fluid level
 -Hydraulic/transmission oil temperature
 -Tachometer
 Digital indicators
 -Gear indicator
 -Speedometer
 -Service meter units
 -Fault codes
 Warning indicators:

-Air inlet heater
 -Electrical malfunction
 -Engine inlet manifold temperature
 -Engine oil pressure, fuel level
 -Fuel pressure high/low
 -Hydraulic oil level, parking brake
 -Primary steering oil pressure
 -Service brake oil pressure
 -Action light, engine malfunction
 -Transmission filter bypass
 Heater and defroster
 Horn
 Cup holders and personal tray on right console
 Storage tray behind seat
 Mirrors, rearview external
 Seat, Cat Comfort (cloth) suspension
 Seat belt
 Steering column, adjustable angle
 Wipers/washers (front and rear)
 Window, sliding (left and right side)

TIRES, RIMS, AND WHEELS

A tire must be selected from the mandatory attachments section
 Tire availability might vary by region
 Base machine price includes an allowance for base radial tires.

FLUIDS

Premixed 50% concentration of extended life coolant with freeze protection to -34C (-29F)

OTHER STANDARD EQUIPMENT

Lift and bucket return-to-dig kick outs (Electro-Magnetic), mechanical adjustment
 Couplings, Caterpillar O-ring face seal
 Doors, service access (locking)
 Front fender, steel
 Grill, airborne debris
 Hitch, drawbar with pin
 Hood, non-metallic on steel structure, wing doors
 Hoses, Caterpillar XT
 Counterweight
 Linkage, Z-Bar, fabricated crosstube/ tilt lever
 SOS oil sampling valves
 Sight gages :
 -Engine coolant, hydraulic oil
 -Transmission oil level
 Diagnostic pressure taps
 -Transmission speed clutches

CATERPILLAR MACHINE PRICE LIST

950GC950GC WHEEL LOADER
QINGZHOU, CHINAShip Weight
lbsLIST PRICE
AT DEALER**OTHER STANDARD EQUIPMENT (CONT.)**

- Transmission forward and reverse clutches
- Steering pump load and discharge pressure
- Skate system accumulator pressure
- Front and rear brake pressure
- Product Link Ready

CATERPILLAR MACHINE PRICE LIST

950GC

950GC WHEEL LOADER QINGZHOU, CHINA	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------------	--------------------	-------------------------

**Lane 2 is reserved for the Base Order Management program.
Please use Lane 2 when placing orders that are part of the Base Order Management program.**

468-0900 950GC WHEEL LOADER HRC 0 \$258,980

LANE 2 - AVAILABLE FROM SELECT EPC LOCATIONS FOR AM-N
 LANE 2 - AVAILABLE FROM ZEEBRUGGE EPC FOR EU
 LANE 3 - AVAILABLE FROM SELECT EPC LOCATIONS FOR AM-N
 LANE 3 - AVAILABLE FROM ZEEBRUGGE EPC FOR EU

INCLUDES:

- Engine, Cat C7.1 w/ US EPA Tier 4 Final /EU Stage IV rating.
- Cat Clean Emissions Module (CEM) with Diesel Particulate Filter (DPF) remote Diesel Exhaust Fluid (DEF) tank & pump
DEF Gauges available in Computerized monitoring system.
- EIS Automatic Engine Idle Shutdown
- Rearview Camera
- Entertainment Radio Ready

CATERPILLAR MACHINE PRICE LIST

950GC

950GC WHEEL LOADER QINGZHOU, CHINA	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------------	--------------------	-------------------------

550-7693	950 GC WHEEL LOADER AM-N DCA1 0 LANE 1 - AVAILABLE FROM SAVANNAH DISTRIBUTION CENTER	\$261,430
-----------------	--	------------------

- INCLUDES:
- 468-0900 950GC WHEEL LOADER HRC
 - 1S-9937 AIR INLET STANDARD, RAIN CAP
 - 361-1437 OMISSION, WORKTOOL
 - 387-5940 LINKAGE, STANDARD, 3V/QC
 - 390-6000 STEERING SYSTEM, STANDARD
 - 391-5315 SEAT BELT, 3", AUTO-ANTI-CINCH
 - 392-3809 TOOL BOX
 - 392-8373 WORKING LIGHTS, HALOGEN, AUX
 - 415-4247 ROADING LIGHTS STANDARD
 - 452-7014 FAN, STANDARD
 - 468-0812 AXLES, OPEN/OPEN
 - 468-0816 QUICK COUPLER CONTROL
 - 468-0904 REGIONAL PKG, USA
 - 468-0909 PKG, COLD WEATHER (AM-N)
 - 468-1560 BATTERIES, STANDARD HRC
 - 469-3112 LUBRICATION MANUAL
 - 469-3139 COUNTERWEIGHT, 3016LBS
 - 474-6205 PRODUCT LINK, CELLULAR PL641
 - 474-6209 CONVERTER (24V TO 12V/15A)
 - 474-6212 RADIO, AM/FM
 - 489-0438 SUSPENSION SEAT, AIR
 - 489-2727 WARNING BEACON, LED
 - 494-8875 TIRES, 23.5R25 MAX MS302 ** L3
 - 499-3122 AIR CONDITIONING, MANUAL C
 - 521-7456 HYDRAULICS, 2V, W/RIDE CTRL ANSI
 - 521-9762 SINGLE AXIS LEVERS W/FNR, 2V C

Supersedes 02JAN2018

Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice

Printed in USA
U. S. DOLLAR CURRENCY

Effective 02JAN2019

950GC-004

CATERPILLAR MACHINE PRICE LIST

950GC

950GC WHEEL LOADER QINGZHOU, CHINA	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------------	--------------------	-------------------------

550-7694 950 GC WHEEL LOADER AM-N DCA2 0 LANE 1 - AVAILABLE FROM SAVANNAH DISTRIBUTION CENTER	0	\$268,040
---	---	------------------

- INCLUDES:
- 468-0900 950GC WHEEL LOADER HRC
 - 1S-9937 AIR INLET STANDARD, RAIN CAP
 - 361-1437 OMISSION, WORKTOOL
 - 387-5940 LINKAGE, STANDARD, 3V/QC
 - 390-6000 STEERING SYSTEM, STANDARD
 - 391-5315 SEAT BELT, 3", AUTO-ANTI-CINCH
 - 392-3809 TOOL BOX
 - 392-8373 WORKING LIGHTS, HALOGEN, AUX
 - 415-4247 ROADING LIGHTS STANDARD
 - 452-7014 FAN, STANDARD
 - 468-0814 AXLES, LSD/OPEN
 - 468-0816 QUICK COUPLER CONTROL
 - 468-0904 REGIONAL PKG, USA
 - 468-0909 PKG, COLD WEATHER (AM-N)
 - 468-1560 BATTERIES, STANDARD HRC
 - 469-3112 LUBRICATION MANUAL
 - 469-3139 COUNTERWEIGHT, 3016LBS
 - 474-6205 PRODUCT LINK, CELLULAR PL641
 - 474-6209 CONVERTER (24V TO 12V/15A)
 - 474-6212 RADIO, AM/FM
 - 489-0438 SUSPENSION SEAT, AIR
 - 489-2727 WARNING BEACON, LED
 - 494-8875 TIRES, 23.5R25 MAX MS302 ** L3
 - 499-3122 AIR CONDITIONING, MANUAL C
 - 521-7458 HYDRAULICS,3V,W/RIDE CTRL ANSI
 - 521-9764 SINGLE AXIS LEVERS W/FNR, 3V C

CATERPILLAR MACHINE PRICE LIST

950GC

950GC WHEEL LOADER QINGZHOU, CHINA	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------------	--------------------	-------------------------

568-9987	950 GC WHEEL LOADER AM-N DCA3 0 LANE 1 - AVAILABLE FROM SAVANNAH DISTRIBUTION CENTER	\$270,260
-----------------	--	------------------

- INCLUDES:
 468-0900 950GC WHEEL LOADER HRC
 1S-9937 AIR INLET STANDARD, RAIN CAP
 361-1437 OMISSION, WORKTOOL
 387-5940 LINKAGE, STANDARD, 3V/QC
 390-6000 STEERING SYSTEM, STANDARD
 391-5315 SEAT BELT, 3", AUTO-ANTI-CINCH
 392-3809 TOOL BOX
 392-8373 WORKING LIGHTS, HALOGEN, AUX
 415-4247 ROADING LIGHTS STANDARD
 452-7014 FAN, STANDARD
 468-0813 AXLES, LSD/LSD
 468-0816 QUICK COUPLER CONTROL
 468-0904 REGIONAL PKG, USA
 468-0909 PKG, COLD WEATHER (AM-N)
 468-1560 BATTERIES, STANDARD HRC
 469-3112 LUBRICATION MANUAL
 469-3139 COUNTERWEIGHT, 3016LBS
 474-6205 PRODUCT LINK, CELLULAR PL641
 474-6209 CONVERTER (24V TO 12V/15A)
 474-6212 RADIO, AM/FM
 489-0438 SUSPENSION SEAT, AIR
 489-2727 WARNING BEACON, LED
 499-3122 AIR CONDITIONING, MANUAL C
 521-7458 HYDRAULICS,3V,W/RIDE CTRL ANSI
 521-9764 SINGLE AXIS LEVERS W/FNR, 3V C
 565-4738 TIRE, 23.5R25 MAX MS202**L2

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	MANDATORY ATTACHMENTS	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------------	-----------------	----------------------

LANE 1 AM-NORTH MANDATORY ATTACHMENTS

LANE SELECTION

0P-9001	LANE 1 ORDER	0	NC
	Select this option when ordering from the PDC		

PACKING

0P-4834	ROLL ON-ROLL OFF	0	\$84 NET
	Machine is in mobile condition and all attachments are installed unless specified.		

5P-2506	SERIALIZED TECHNICAL MEDIA KIT	0	NC
	Kit will include instructions and parts CD or parts book in the legally required language, based on shipping address. Any additional media such as a paper parts manual, not included in the kit, can be ordered through the media website.		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 2 AM-NORTH MANDATORY ATTACHMENTS

LANE SELECTION

OP-9002	LANE 2 ORDER	0	NC
	Only for dealers enrolled in the Base Orders Management (BOM) program.		

REGIONAL PACKAGES

L	468-0904	REGIONAL PKG, USA	0	NC
		INCLUDES: -Brake pedal, standard -ANSI decals -Ambient temperature capability up to 47C (117F) AVAILABLE FOR: US		
L	523-8766	REGIONAL PKG, CANADA	0	NC
		INCLUDES: -Brake pedal, standard -ISO decals -Ambient temperature capability up to 47C (117F) AVAILABLE FOR: CANADA		

FEATURE PACKAGES

L	468-0906	PKG, COOLING STANDARD	0	NC
L	468-0909	PKG, COLD WEATHER (AM-N)	0	\$1,010
		INCLUDES : -Ether starting aid -Jacket water heater 120V -Bypass Valve		

BOOMS, STICKS, AND LINKAGES

LINKAGE ARRANGEMENTS

L	387-5780	LINKAGE, STANDARD	0	NC
L	387-5940	LINKAGE, STANDARD, 3V/QC	0	\$515
		Linkage with hardward installed for the installation of Quick Coupler lines and/or third function front lines.		
		NOTE: Does not include Quick Coupler lines/hydraulics or Third Function lines/hydraulics.		
L	546-5020	LINKAGE, STANDARD, AL/3V/QC	0	\$720
		Linkage for the installation of Caterpillar Autolube system, 3V and/or QC.		

NOTE: Does not include Autolube system/lines, Quick Coupler lines/hydraulics or Third Function lines/hydraulics

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 2 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

BOOMS, STICKS, AND LINKAGES (Cont.)

COUNTERWEIGHT

L	469-3139	COUNTERWEIGHT, 3016LBS	0	NC
		Includes DEF tank box.		

POWERTRAIN

AXLE PACKAGES

Axle packages include a combination of traction aids (open front and rear differentials or limited slip front and/or rear differentials).

NOTE:

LSD - Limited Slip Differentials

Limited slip differentials should only be ordered if application and ground condition require them.

Limited slip differentials will increase fuel consumption and tire wear/dragging if used on firm ground.

Limited slip differentials will decrease machine maneuverability on good ground conditions.

L	468-0812	AXLES, OPEN/OPEN	0	NC
		INCLUDES: -Open front differential -Open rear differential Recommended for mainly firm/dry ground condition like yard application, truck loading and Load-and-Carry with good ground condition. Lowest fuel consumption.		
L	468-0813	AXLES, LSD/LSD	0	\$4,235
		INCLUDES: -Limited slip front differential -Limited slip rear differential Recommended for very adverse wet and loose ground condition and applications like snow removal and dozing (overburden removal). Will reduce operator comfort and increase fuel consumption.		
L	468-0814	AXLES, LSD/OPEN	0	\$2,010
		INCLUDES: -Limited slip front differential -Open rear differential Recommended for wet/loose ground condition like Load-and-Carry in wet conditions, uphill with empty bucket and stockpiling in material. Will reduce operator comfort and increase fuel consumption.		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 2 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

POWERTRAIN (Cont.)

AIR INLETS, ENGINE

L	1S-9937	AIR INLET STANDARD, RAIN CAP 0		NC
		Engine air inlet to be used in moderate dust and airborne debris environments.		
L	130-3280	PRECLEANER 0		\$725
		Turbine engine air inlet precleaner, to be used in high dust and airborne debris environments.		

HYDRAULICS

Must select either 2V or 3V Hydraulic arrangement. Selection will limit optional attachments compatible to your machine order.

NOTE: Ride control provides the operator with a smoother ride over rough terrain, enabling a more comfortable ride at higher speeds. The benefit is reduced cycle times, higher productivity and better fuel efficiency while performing Load-and-Carry applications. The system works by using an accumulator to dampen the linkage motion, acting as a shock absorber.

L	390-5913	HYDRAULICS, 2V, W/O RIDE CTRL 0		NC
		INCLUDES: -2 valve hydraulic system for implement lift and tilt -No ride control		
L	521-7456	HYDRAULICS, 2V, W/RIDE CTRL ANSI 0		\$3,405
		INCLUDES: -2 valve hydraulic system for implement lift and tilt -Ride control		
		ONLY FOR USE WITH: 468-0904 REGIONAL PKG, USA		
L	521-7457	HYDRAULICS, 2V, W/RIDE CTRL ISO 0		\$3,405
		INCLUDES: -2 valve hydraulic system for implement lift and tilt -Ride control		
		ONLY FOR USE WITH: 523-8766 REGIONAL PKG, CANADA		
L	397-9895	HYDRAULICS, 3V, W/O RIDE CTRL 0		\$4,225
		INCLUDES: -3 valve hydraulic system -No ride control		
		ONLY FOR USE WITH: 387-5940 LINKAGE, STANDARD, 3V/QC		
L	521-7458	HYDRAULICS, 3V, W/RIDE CTRL ANSI 0		\$7,620
		INCLUDES: -3 valve hydraulic system -Ride control		
		ONLY FOR USE WITH: 387-5940 LINKAGE, STANDARD, 3V/QC And 468-0904 REGIONAL PKG, USA		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 2 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

HYDRAULICS (Cont.)

L	521-7459	HYDRAULICS,3V,W/RIDE CTRL ISO 0		\$7,620
		INCLUDES: -3 valve hydraulic system -Ride control ONLY FOR USE WITH: 387-5940 LINKAGE, STANDARD, 3V/GC and 523-8766 REGIONAL PKG, CANADA		

STARTERS, BATTERIES, & ALTERNATORS

L	468-1560	BATTERIES, STANDARD HRC 0		NC
		Box holding two 12V, 1400CCA, 200Ah maintenance free Cat Batteries. Unaided starting capability down to -18C (0F).		

ELECTRICAL

LIGHTS ROADING

L	415-4247	ROADING LIGHTS STANDARD 0		NC
		Provides high beam/low beam lamps, front and rear turn signals, side marker lights, and reflective side markers for roading applications.		

LIGHTS WORKING

L	415-4215	WORKING LIGHTS, HALOGEN 0		NC
		4 halogen working lights, cab mounted (2 facing forward/2 facing rearward)		
L	392-8373	WORKING LIGHTS, HALOGEN, AUX 0		\$104
		4 halogen working lights, cab mounted (2 facing forward/2 facing rearward) 4 open connectors to connect optional light packages (2 front/2 rear)		

OPERATOR ENVIRONMENT

IMPLEMENT CONTROLS

L	521-9762	SINGLE AXIS LEVERS W/FNR, 2V C 0		NC
		Implement lift and tilt controls with two single axis levers, pilot controlled. ONLY FOR USE WITH: HYDRAULICS, 2V, W/O RIDE CTRL or W/ RIDE CTRL		
L	521-9763	JOYSTICK W/FNR, 2V C 0		NC
		Implement lift and tilt controls with one joystick, pilot controlled. Integrates a horn button and FNR switch. ONLY FOR USE WITH: HYDRAULICS, 2V, W/O RIDE CTRL or W/ RIDE CTRL		
L	521-9764	SINGLE AXIS LEVERS W/FNR, 3V C 0		\$515
		Implement lift, tilt and third function controls with three single axis levers, pilot controlled. ONLY FOR USE WITH: HYDRAULICS, 3V, W/O RIDE CTRL or W/ RIDE CTRL		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 2 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

OPERATOR ENVIRONMENT (Cont.)

L	521-9765	JOYSTICK W/FNR & ONE SAL, 3V C 0		\$515
		Implement lift and tilt controls with one joystick, third function with one single axis lever on the right hand side, all pilot controlled. ONLY FOR USE WITH: HYDRAULICS, 3V, W/O RIDE CTRL or W/ RIDE CTRL		

OPERATOR SEAT

L	489-0437	SUSPENSION SEAT, MECHANICAL 0		NC
		Seat with spring-mechanical suspension, height adjustable, fore-aft, armrest, back and head rest adjustments. Fabric cushions.		
L	489-0438	SUSPENSION SEAT, AIR 0		\$515
		Seat with air suspension, height adjustable, fore-aft, armrest, back and head rest adjustments. Fabric cushions.		

SEAT BELTS

L	391-5315	SEAT BELT, 3", AUTO-ANTI-CINCH 0		NC
		Auto tightening and anti-cinch 75 mm (3 inch) wide seat belt. It can provide max 5 cm(2 inch) free space to let operator reach.		

AIR CONDITIONING

L	499-3122	AIR CONDITIONING, MANUAL C 0		NC
---	----------	---	--	-----------

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Cat marketing representative with questions.

L	474-6205	PRODUCT LINK, CELLULAR PL641 0		NC
		Product Link Pro series PL641 uses GSM and CDMA 3G cellular networks to transmit location, utilization and condition information for viewing in Product Link-s remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 2 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

TECHNOLOGY PRODUCTS (Cont.)

L	474-6206	PRODUCT LINK, SATELLITE PL631 0 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. For use in areas with poor or no cellular coverage.		NC
---	----------	---	--	-----------

SAFETY AND SECURITY

STEERING

L	390-6000	STEERING SYSTEM, STANDARD 0 Standard steering wheel (HMU).		NC
L	390-5985	STEERING SYSTEM, SECONDARY 0 Standard steering wheel (HMU) with electric secondary steering pump. Includes test switch and warning indicator in cab.		\$2,975

COOLING

FAN HYDRAULIC - COOLER

L	452-7014	FAN, STANDARD 0		NC
L	489-7752	FAN, REVERSING , ISO 0 Provides reversing function to the standard hydraulically driven demand fan. This provides the ability to reverse the airflow direction to remove debris from the radiator and engine enclosures while the machine is still operating. Includes automatic and manual controls for airflow reversal. Recommended for applications with a high content of airborne debris. ONLY FOR USE WITH: 523-8766 REGIONAL PKG, CANADA AVAILABLE FOR: CANADA		\$715
L	489-7753	FAN, REVERSING , ANSI 0 Provides reversing function to the standard hydraulically driven demand fan. This provides the ability to reverse the airflow direction to remove debris from the radiator and engine enclosures while the machine is still operating. Includes automatic and manual controls for airflow reversal. Recommended for applications with a high content of airborne debris. ONLY FOR USE WITH: 468-0904 REGIONAL PKG, USA AVAILABLE FOR: US		\$715

TIRES, RIMS, AND WHEELS

Includes rims, and come in a set of 4.

TIRES AVAILABLE FROM MAXAM

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 2 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

TIRES, RIMS, AND WHEELS (Cont.)

L	494-8875	TIRES, 23.5R25 MAX MS302 ** L3 0 Maxam Radial, MS302, tubeless. Self-cleaning tread design provides excellent traction and floatation.		\$-2,665
---	----------	---	--	----------

TIRES AVAILABLE FROM BRIDGESTONE

L	494-8872	TIRES, 23.5R25 BS VUT * L2 0 Bridgestone radial, tubeless, Non-directional pattern VUT features superior traction and excellent self-cleaning, lighter weight provides superior maneuverability.		\$1,330
L	494-8871	TIRES, 23.5R25 BS VJT * L3 0 Bridgestone radial, tubeless, the V-STEEL J-TRACTION features advanced non-directional tread pattern, low-vibration characteristics enhance riding comfort and extra-tough for more lasting reliability.		\$4,920

OTHER ATTACHMENTS

TOOL BOX

L	392-3725	NO TOOLBOX 0		NC
L	392-3809	TOOL BOX 0 Provides a lockable toolbox located under the battery box on the left hand side of the machine.		\$307

GREASING ARRANGEMENTS

L	469-3112	LUBRICATION MANUAL 0 Requires manual greasing of pin joints according to maintenance schedule. Several fittings remote located for better access.		NC
L	555-5581	AUTOLUBE 0 Provides Caterpillar Autolube system. Greases pin joints requiring daily lubrication: linkage pins joints including bucket pins, articulation hitch, steering cylinders and rear axle trunnions. ONLY FOR USE WITH: 546-5020 LINKAGE, STD LIFT, AL/3V/QC		\$5,710

QUICK COUPLERS

CIRCUIT ACTUATION QC - NO COUPLER

P	471-0569	NO QUICK COUPLER READY 0		NC
---	----------	------------------------------------	--	----

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 2 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

QUICK COUPLERS (Cont.)

P	468-0816	QUICK COUPLER CONTROL. 0		\$3,030
		Includes all hydraulic lines, vertical wedge activation switch and dual level kick-out sensors (Bucket and Fork) with selection switch in the cab.		

WORK TOOLS

NOTE: AVAILABILITY FOR BUCKETS

NOTE: "GET" is NOT automatically included on bucket orders. GET must be entered on the order with your bucket selection, unless text for bucket states otherwise. Please make the "GET" selection from "GET" listed immediately following the bucket listing.

NOTE: Recommend use of bolt-on adapter option, adapter and segment option, or bolt-on cutting edge option for General Purpose Buckets and Material Handling Buckets.

NOTE: Material density will determine the appropriate capacity bucket. Refer to the Specalog. Exceeding maximum payload may cause loader instability.

GC-TYPE GENERAL PURPOSE BUCKETS

P	448-5092	BUCKET-GP GC, 114" 4.00YD3 3,071		\$11,011
		PERFORMANCE SERIES BUCKET 950 GC dedicated bucket CAPACITIES: Rated: 2.9 M3 (3.75 YD3) bare or without bolt-on edges or segments Rated: 3.1 M3 (4.00 YD3) with bolt-on edges or adapters/teeth&segments 110%: 3.4 M3 (4.50 YD3) with bolt-on edges or adapters/teeth&segments Max recommended material density : 1720KG/M3 (2900lbs/YD3)		
P	461-6531	BUCKET-GP GC, 114" 4.25YD3 3,161		\$11,403
		PERFORMANCE SERIES BUCKET 950 GC dedicated bucket CAPACITIES: Rated: 3.1 M3 (4.00 YD3) bare or without bolt-on edges or segments Rated: 3.3 M3 (4.25 YD3) with bolt-on edges or adapters/teeth&segments 110%: 3.6 M3 (4.75 YD3) with bolt-on edges or adapters/teeth&segments Max recommended material density : 1600KG/M3 (2700lbs/YD3)		

MATERIAL HANDLING BUCKETS

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 2 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

WORK TOOLS (Cont.)

P	419-1626	BKTA GC, 120" 5.75YD3 PO 4,559 PERFORMANCE SERIES BUCKET For Coal; Light Material Handling Includes GET: bolt-on cutting edge (BOCE) Rated: 4.4 M3 (5.75 YD3) with bolt-on cutting edge 110%: 4.8 M3 (6.25 YD3) with bolt-on edges or adapters/teeth&segments Max recommended material density : 1120KG/M3 (1890lbs/YD3)		\$20,172
---	----------	---	--	----------

FUSION QUICK COUPLER

P	310-9391	QUICK COUPLER, FUSION 1,090 REQUIRES: 468-0816 QUICK COUPLER CONTROL		\$6,579
---	----------	--	--	---------

BUCKETS FOR FUSION QUICK COUPLER

P	382-9834	BKT GP ST 114" 4.0 YD3 FUS 3,302 PERFORMANCE SERIES BUCKET CAPACITIES: Rated: 2.9 M3 (3.75 YD3) bare or without bolt-on edges or segments Rated: 3.1 M3 (4.00 YD3) with bolt-on edges or adapters/teeth&segments 110%: 3.4 M3 (4.50 YD3) with bolt-on edges or adapters/teeth&segments Max recommended material density : 1600KG/M3 (2700lbs/YD3) ONLY FOR USE WITH: 310-9391 QUICK COUPLER, FUSION		\$12,953
---	----------	---	--	----------

CUTTING EDGE

P	139-9229	CUTTING EDGE, BOLT-ON 600 30mm thick (1 required)		\$1,635
---	----------	---	--	---------

GET

P	257-1766	ADAPTERS, TIP, BOLT-ON, K080 298 Set of 8 bolt-on adapters, includes corner adapters and hardware. (1 required) REQUIRES: K080 tips		\$2,286
P	229-6969	TIP, GENERAL DUTY 26 Set of 1 tip and retainer (8 tips per bucket required) ONLY FOR USE WITH: 257-1766 ADAPTERS, TIP, BOLT-ON, K080		\$68
P	229-6964	TIP, EXTRA DUTY 29 set of 1 tip and retainer (8 tips per bucket required) ONLY FOR USE WITH: 257-1766 ADAPTERS, TIP, BOLT-ON, K080		\$74
P	139-9279	SEGMENTS, BOLT ON 351 Set of 7 segments, 30mm Thick (1 required) ONLY FOR USE WITH: ADAPTERS, TIP, BOLT-ON & TIPS		\$1,881

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE 2 AM-NORTH MANDATORY ATTACHMENTS (CONT.)

INSTRUCTIONS

OPERATION AND MAINTENANCE MANUAL

5P-2506	SERIALIZED TECHNICAL MEDIA KIT 0 Kit will include instructions and parts CD or parts book in the legally required language, based on shipping address. Any additional media such as a paper parts manual, not included in the kit, can be ordered through the media website. https://oos.midlandcorp.com/CAT/Default.aspx	NC
---------	--	-----------

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

LANE 2 AM-NORTH OPTIONAL ATTACHMENTS

ELECTRICAL

LIGHTS WORKING - OPTIONAL

P	415-4203	LIGHTS, WORKING, EXTRA HALOGEN 0 4 extra working lights, cab mounted, halogen (2 facing forward and 2 facing rear) ONLY FOR USE WITH: 392-8373 WORKING LIGHTS, HALOGEN, AUX		\$765
P	501-2465	LIGHTS, WORKING EXTRA, LED 0 4 extra working lights, cab mounted LED, (2 facing forward HI LED and 2 facing rear led) ONLY FOR USE WITH: 392-8373 WORKING LIGHTS, HALOGEN, AUX		\$1,175

BEACON

P	489-2727	WARNING BEACON, LED 0 Provides a rotating warning beacon, flip down.		\$392
---	----------	--	--	-------

OPERATOR ENVIRONMENT

SUN VISOR

P	391-5330	SUN VISOR, REAR 0 Rear window pull down sun visor similar to the sun visor on front windshield.		\$104
---	----------	---	--	-------

RADIO

P	474-6212	RADIO, AM/FM 0		\$240
---	----------	-----------------------------	--	-------

CONVERTER-POWER

P	474-6209	CONVERTER (24V TO 12V/15A) 0 Provides a 24V to 12V converter (15A). No extra mounting provisions included, can be used to power a CB Radio.		\$925
---	----------	---	--	-------

TECHNOLOGY PRODUCTS

SPEED LIMITER

P	525-0144	SPEED LIMITER (20 KPH) 0 Controls the engine rpm to keep the ground speed at 20km/hour max.		\$575
---	----------	---	--	-------

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 2 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

LANE 2 AM-NORTH OPTIONAL ATTACHMENTS (CONT.)

GUARDS

FENDERS

P	415-7735	FENDER, EXTENSIONS, STEEL 0 Short rear fender extensions covering top of wheel. Attached to the swing up service door.		\$297
P	432-7325	FENDER, ROADING, NON-METALLIC 0 Roading fenders arrangement includes fender extensions on front fenders and full wrap non-metallic fenders for rear wheels. Rear fenders are attached to the swing up service door.		\$880

FLUIDS

ANTIFREEZE

NOTE: Standard machine includes antifreeze protection to -34C (-29F).
 Different lubricants are also required for extreme temperatures.
 Please reference operation and maintenance manual.

OP-2407	ANTIFREEZE, -50C (-58F) 0 Extended life coolant		\$251 NET
---------	--	--	-----------

PACKING

PACKING FOR MACHINE (Must Select One)

OP-4834	ROLL ON-ROLL OFF 0 Machine is in mobile condition and all attachments are installed unless specified.		\$84 NET
---------	--	--	----------

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-------------------------	-----------------	----------------------

LANE SELECTION

LANE SELECTION

0P-9003	LANE 3 ORDER	0	NC
---------	------------------------	---	----

Supersedes 02JAN2018

Caterpillar: Confidential Green
US-A-19-01 A

Subject to change without notice

Printed in USA
U. S. DOLLAR CURRENCY

Effective 02JAN2019

950GC-020

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

REGIONAL PACKAGES

To configure a machine, you must select a Regional Package that applies to your region.

L	468-0904	REGIONAL PKG, USA	0	NC
		INCLUDES: -Brake pedal, standard -ANSI decals -Ambient temperature capability up to 47C (117F)		

FEATURE PACKAGES

L	468-0906	PKG, COOLING STANDARD	0	NC
L	468-0909	PKG, COLD WEATHER (AM-N)	0	\$1,010
		INCLUDES : -Ether starting aid -Jacket water heater 120V -Bypass Valve		

BOOMS, STICKS, AND LINKAGES

LINKAGE ARRANGEMENTS

L	387-5780	LINKAGE, STANDARD	0	NC
L	387-5940	LINKAGE, STANDARD, 3V/QC	0	\$515
		Linkage with hardward installed for the installation of Quick Coupler lines and/or third function front lines.		

NOTE: Does not include Quick Coupler lines/hydraulics or Third Function lines/hydraulics.

L	546-5020	LINKAGE, STANDARD, AL/3V/QC	0	\$720
		Linkage for the installation of Caterpillar Autolube system, 3V and/or QC.		

NOTE: Does not include Autolube system/lines, Quick Coupler lines/hydraulics or Third Function lines/hydraulics.

COUNTERWEIGHT

L	469-3139	COUNTERWEIGHT, 3016LBS	0	NC
		Includes DEF tank box.		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

POWERTRAIN

Axle packages include a combination of traction aids (open front and rear differentials or limited slip front and/or rear differentials).

NOTE: LSD - Limited Slip Differentials

Limited slip differentials should only be ordered if application and ground condition require them.
 Limited slip differentials will increase fuel consumption and tire wear/dragging if used on firm ground.
 Limited slip differentials will decrease machine maneuverability on good ground conditions.

L	468-0812	AXLES, OPEN/OPEN 0 INCLUDES: -Open front differential -Open rear differential Recommended for mainly firm/dry ground condition like yard application, truck loading and Load-and-Carry with good ground condition. Lowest fuel consumption.		NC
L	468-0813	AXLES, LSD/LSD 0 INCLUDES: -Limited slip front differential -Limited slip rear differential Recommended for very adverse wet and loose ground condition and applications like snow removal and dozing (overburden removal). Will reduce operator comfort and increase fuel consumption.		\$4,235
L	468-0814	AXLES, LSD/OPEN 0 INCLUDES: -Limited slip front differential -Open rear differential Recommended for wet/loose ground condition like Load-and-Carry in wet conditions, uphill with empty bucket and stockpiling in material. Will reduce operator comfort and increase fuel consumption.		\$2,010

AIR INLETS, ENGINE

L	1S-9937	AIR INLET STANDARD, RAIN CAP 0 Engine air inlet to be used in moderate dust and airborne debris environments.		NC
L	130-3280	PRECLEANER. 0 Turbine engine air inlet precleaner, to be used in high dust and airborne debris environments.		\$725

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

HYDRAULICS

Must select either 2V or 3V Hydraulic arrangement. Selection will limit optional attachments compatible to your machine order.

NOTE: Ride control provides the operator with a smoother ride over rough terrain, enabling a more comfortable ride at higher speeds. The benefit is reduced cycle times, higher productivity and better fuel efficiency while performing Load-and-Carry applications. The system works by using an accumulator to dampen the linkage motion, acting as a shock absorber.

L	390-5913	HYDRAULICS, 2V, W/O RIDE CTRL	0	NC
		INCLUDES: -2 valve hydraulic system for implement lift and tilt -No ride control		
L	521-7456	HYDRAULICS,2V,W/RIDE CTRL ANSI	0	\$3,405
		INCLUDES: -2 valve hydraulic system for implement lift and tilt -Ride control		
		ONLY FOR USE WITH: 468-0904 REGIONAL PKG, USA		
L	397-9895	HYDRAULICS, 3V, W/O RIDE CTRL	0	\$4,225
		INCLUDES: -3 valve hydraulic system -No ride control		
		ONLY FOR USE WITH: 387-5940 LINKAGE, STANDARD, 3V/QC		
L	521-7458	HYDRAULICS,3V,W/RIDE CTRL ANSI	0	\$7,620
		INCLUDES: -3 valve hydraulic system -Ride control		
		ONLY FOR USE WITH: 387-5940 LINKAGE, STANDARD, 3V/QC And 468-0904 REGIONAL PKG, USA		

STARTERS, BATTERIES, & ALTERNATORS

L	468-1560	BATTERIES, STANDARD HRC	0	NC
		Box holding two 12V, 1400CCA, 200Ah maintenance free Cat Batteries. Unaided starting capability down to -18C (0F).		

ELECTRICAL

LIGHTS ROADING

L	415-4247	ROADING LIGHTS STANDARD	0	NC
		Provides high beam/low beam lamps, front and rear turn signals, side marker lights, and reflective side markers for roading applications.		

LIGHTS WORKING

L	415-4215	WORKING LIGHTS, HALOGEN	0	NC
		4 halogen working lights, cab mounted (2 facing forward/2 facing rearward)		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

ELECTRICAL (CONT.)

LIGHTS WORKING (Cont.)

L	392-8373	WORKING LIGHTS, HALOGEN, AUX 0 4 halogen working lights, cab mounted (2 facing forward/2 facing rearward) 4 open connectors to connect optional light packages (2 front/2 rear)		\$104
---	----------	--	--	--------------

OPERATOR ENVIRONMENT

IMPLEMENT CONTROLS

L	521-9762	SINGLE AXIS LEVERS W/FNR, 2V C 0 Implement lift and tilt controls with two single axis levers, pilot controlled. ONLY FOR USE WITH: HYDRAULICS, 2V, W/O RIDE CTRL or W/ RIDE CTRL		NC
L	521-9763	JOYSTICK W/FNR, 2V C 0 Implement lift and tilt controls with one joystick, pilot controlled. Integrates a horn button and FNR switch. ONLY FOR USE WITH: HYDRAULICS, 2V, W/O RIDE CTRL or W/ RIDE CTRL		NC
L	521-9764	SINGLE AXIS LEVERS W/FNR, 3V C 0 Implement lift, tilt and third function controls with three single axis levers, pilot controlled. ONLY FOR USE WITH: HYDRAULICS, 3V, W/O RIDE CTRL or W/ RIDE CTRL		\$515
L	521-9765	JOYSTICK W/FNR & ONE SAL, 3V C 0 Implement lift and tilt controls with one joystick, third function with one single axis lever on the right hand side, all pilot controlled. ONLY FOR USE WITH: HYDRAULICS, 3V, W/O RIDE CTRL or W/ RIDE CTRL		\$515

OPERATOR SEAT

L	489-0437	SUSPENSION SEAT, MECHANICAL 0 Seat with spring-mechanical suspension, height adjustable, fore-aft, armrest, back and head rest adjustments. Fabric cushions.		NC
L	489-0438	SUSPENSION SEAT, AIR 0 Seat with air suspension, height adjustable, fore-aft, armrest, back and head rest adjustments. Fabric cushions.		\$515

SEAT BELTS

L	391-5315	SEAT BELT, 3", AUTO-ANTI-CINCH 0 Auto tightening and anti-cinch 75 mm (3 inch) wide seat belt. It can provide max 5 cm(2 inch) free space to let operator reach.		NC
---	----------	---	--	-----------

AIR CONDITIONING

L	499-3122	AIR CONDITIONING, MANUAL C 0		NC
---	----------	---	--	-----------

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet. Availability varies by country - please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Cat marketing representative with questions.

L	474-6205	PRODUCT LINK, CELLULAR PL641 0 Product Link Pro series PL641 uses GSM and CDMA 3G cellular networks to transmit location, utilization and condition information for viewing in Product Link-s remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		NC
L	474-6206	PRODUCT LINK, SATELLITE PL631 0 Product Link Pro series PL631 uses a satellite network to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. For use in areas with poor or no cellular coverage.		NC

SAFETY AND SECURITY

STEERING

L	390-6000	STEERING SYSTEM, STANDARD 0 Standard steering wheel (HMU).		NC
L	390-5985	STEERING SYSTEM, SECONDARY 0 Standard steering wheel (HMU) with electric secondary steering pump. Includes test switch and warning indicator in cab.		\$2, 975

COOLING

FAN HYDRAULIC - COOLER

L	452-7014	FAN, STANDARD 0		NC
L	489-7753	FAN, REVERSING , ANSI 0 Provides reversing function to the standard hydraulically driven demand fan. This provides the ability to reverse the airflow direction to remove debris from the radiator and engine enclosures while the machine is still operating. Includes automatic and manual controls for airflow reversal. Recommended for applications with a high content of airborne debris. ONLY FOR USE WITH: 468-0904 REGIONAL PKG, USA		\$715

TIRES, RIMS, AND WHEELS

Includes rims, and come in a set of 4.

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS (CONT.)

TIRES AVAILABLE FROM MAXAM

L	494-8875	TIRES, 23.5R25 MAX MS302 ** L3 0 Maxam Radial, MS302, tubeless. Self-cleaning tread design provides excellent traction and floatation.		\$-2,665
---	----------	---	--	----------

TIRES AVAILABLE FROM BRIDGESTONE

L	494-8872	TIRES, 23.5R25 BS VUT * L2 0 Bridgestone radial, tubeless, Non-directional pattern VUT features superior traction and excellent self-cleaning, lighter weight provides superior maneuverability.		\$1,330
L	494-8871	TIRES, 23.5R25 BS VJT * L3 0 Bridgestone radial, tubeless, the V-STEEL J-TRACTION features advanced non-directional tread pattern, low-vibration characteristics enhance riding comfort and extra-tough for more lasting reliability.		\$4,920

OTHER ATTACHMENTS

TOOL BOX

L	392-3725	NO TOOLBOX 0		NC
L	392-3809	TOOL BOX 0 Provides a lockable toolbox located under the battery box on the left hand side of the machine.		\$307

GREASING ARRANGEMENTS

L	469-3112	LUBRICATION MANUAL 0 Requires manual greasing of pin joints according to maintenance schedule. Several fittings remote located for better access.		NC
L	555-5581	AUTOLUBE 0 Provides Caterpillar Autolube system. Greases pin joints requiring daily lubrication: linkage pins joints including bucket pins, articulation hitch, steering cylinders and rear axle trunnions. ONLY FOR USE WITH: 546-5020 LINKAGE, STD LIFT, AL/3V/QC		\$5,710

QUICK COUPLERS

CIRCUIT ACTUATION QC - NO COUPLER

P	471-0569	NO QUICK COUPLER READY 0		NC
P	468-0816	QUICK COUPLER CONTROL 0 Includes all hydraulic lines, vertical wedge activation switch and dual level kick-out sensors (Bucket and Fork) with selection switch in the cab.		\$3,030

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

WORK TOOLS

AVAILABILITY FOR BUCKETS

NOTE: "GET" is NOT automatically included on bucket orders.
 GET must be entered on the order with your bucket selection, unless text for bucket states otherwise.
 Please make the "GET" selection from "GET" listed immediately following the bucket listing.

NOTE: Recommend use of bolt-on adapter option, adapter and segment option, or bolt-on cutting edge option for General Purpose Buckets and Material Handling Buckets.

NOTE: Material density will determine the appropriate capacity bucket. Refer to the Specalog. Exceeding maximum payload may cause loader instability.

GC-TYPE GENERAL PURPOSE BUCKETS

P	448-5092	BUCKET-GP GC, 114" 4.00YD3	3,071	\$11,011
		PERFORMANCE SERIES BUCKET 950 GC dedicated bucket CAPACITIES: Rated: 2.9 M3 (3.75 YD3) bare or without bolt-on edges or segments Rated: 3.1 M3 (4.00 YD3) with bolt-on edges or adapters/teeth&segments 110%: 3.4 M3 (4.50 YD3) with bolt-on edges or adapters/teeth&segments Max recommended material density : 1720KG/M3 (2900lbs/YD3)		
P	461-6531	BUCKET-GP GC, 114" 4.25YD3	3,161	\$11,403
		PERFORMANCE SERIES BUCKET 950 GC dedicated bucket CAPACITIES: Rated: 3.1 M3 (4.00 YD3) bare or without bolt-on edges or segments Rated: 3.3 M3 (4.25 YD3) with bolt-on edges or adapters/teeth&segments 110%: 3.6 M3 (4.75 YD3) with bolt-on edges or adapters/teeth&segments Max recommended material density : 1600KG/M3 (2700lbs/YD3)		

MATERIAL HANDLING BUCKETS

P	419-1626	BKTA GC, 120" 5.75YD3 PO	4,559	\$20,172
		PERFORMANCE SERIES BUCKET For Coal; Light Material Handling Includes GET: bolt-on cutting edge (BOCE) Rated: 4.4 M3 (5.75 YD3) with bolt-on cutting edge 110%: 4.8 M3 (6.25 YD3) with bolt-on edges or adapters/teeth&segments Max recommended material density : 1120KG/M3 (1890lbs/YD3)		

FUSION QUICK COUPLER

P	310-9391	QUICK COUPLER, FUSION	1,090	\$6,579
		REQUIRES: 468-0816 QUICK COUPLER CONTROL		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 3 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

WORK TOOLS (CONT.)

BUCKETS FOR FUSION QUICK COUPLER

P	382-9834	BKT GP ST 114" 4.0 YD3 FUS	3,302	\$12,953
		PERFORMANCE SERIES BUCKET		
		CAPACITIES:		
		Rated: 2.9 M3 (3.75 YD3) bare or without bolt-on edges or segments		
		Rated: 3.1 M3 (4.00 YD3) with bolt-on edges or adapters/teeth&segments		
		110%: 3.4 M3 (4.50 YD3) with bolt-on edges or adapters/teeth&segments		
		Max recommended material density : 1600KG/M3 (2700lbs/YD3)		
		ONLY FOR USE WITH: 310-9391 QUICK COUPLER, FUSION		

CUTTING EDGE

P	139-9229	CUTTING EDGE, BOLT-ON	600	\$1,635
		30mm thick (1 required)		

GET

P	257-1766	ADAPTERS, TIP, BOLT-ON, K080	298	\$2,286
		Set of 8 bolt-on adapters, includes corner adapters and hardware.		
		(1 required)		
		REQUIRES: K080 tips		
P	229-6969	TIP, GENERAL DUTY	26	\$68
		Set of 1 tip and retainer (8 tips per bucket required)		
		ONLY FOR USE WITH: 257-1766 ADAPTERS, TIP, BOLT-ON, K080		
		485-7017 BKT-MH GC, 2997MM 3.10M3 (118" 4.00YD3) FM		
P	229-6964	TIP, EXTRA DUTY	29	\$74
		set of 1 tip and retainer (8 tips per bucket required)		
		ONLY FOR USE WITH: 485-7017 BKT-MH GC, 2997MM 3.10M3 (118" 4.00YD3) FM		
P	139-9279	SEGMENTS, BOLT ON	351	\$1,881
		Set of 7 segments, 30mm Thick (1 required)		
		ONLY FOR USE WITH: ADAPTERS, TIP, BOLT-ON & TIPS		

INSTRUCTIONS

OPERATION AND MAINTENANCE MANUAL

5P-2506	SERIALIZED TECHNICAL MEDIA KIT	0	NC
	Kit will include instructions and parts CD or parts book in the		
	legally required language, based on shipping address.		
	Any additional media such as a paper parts manual, not included		
	in the kit, can be ordered through the media website.		
	https://oos.midlandcorp.com/CAT/Default.aspx		

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

ELECTRICAL

LIGHTS WORKING

P	415-4203	LIGHTS, WORKING, EXTRA HALOGEN 0 4 extra working lights, cab mounted, halogen (2 facing forward and 2 facing rear) ONLY FOR USE WITH: 392-8373 WORKING LIGHTS, HALOGEN, AUX		\$765
P	501-2465	LIGHTS, WORKING EXTRA, LED 0 4 extra working lights, cab mounted LED, (2 facing forward HI LED and 2 facing rear led) ONLY FOR USE WITH: 392-8373 WORKING LIGHTS, HALOGEN, AUX		\$1,175

BEACON

P	489-2727	WARNING BEACON, LED 0 Provides a rotating warning beacon, flip down.		\$392
---	----------	--	--	-------

OPERATOR ENVIRONMENT

SUN VISOR

P	391-5330	SUN VISOR, REAR 0 Rear window pull down sun visor similar to the sun visor on front windshield.		\$104
---	----------	---	--	-------

RADIO

P	474-6212	RADIO, AM/FM 0		\$240
---	----------	---------------------------------	--	-------

CONVERTER-POWER

P	474-6209	CONVERTER (24V TO 12V/15A) 0 Provides a 24V to 12V converter (15A). No extra mounting provisions included, can be used to power a CB Radio.		\$925
---	----------	---	--	-------

TECHNOLOGY PRODUCTS

SPEED LIMITER

P	525-0144	SPEED LIMITER (20 KPH) 0 Controls the engine rpm to keep the ground speed at 20km/hour max.		\$575
---	----------	---	--	-------

GUARDS

FENDERS

P	415-7735	FENDER, EXTENSIONS, STEEL 0 Short rear fender extensions covering top of wheel. Attached to the swing up service door.		\$297
P	432-7325	FENDER, ROADING, NON-METALLIC 0 Roading fenders arrangement includes fender extensions on front fenders and full wrap non-metallic fenders for rear wheels. Rear fenders are attached to the swing up service door.		\$880

CATERPILLAR MACHINE PRICE LIST

950GC

USE	REF NO.	LANE 3 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

FLUIDS

ANTIFREEZE

NOTE: Standard machine includes antifreeze protection to -34C (-29F).
 Different lubricants are also required for extreme temperatures.
 Please reference operation and maintenance manual.

0P-2407	ANTIFREEZE, -50C (-58F)	0		\$251 NET
	Extended life coolant			

PACKING

PACKING FOR MACHINE

0P-4834	ROLL ON-ROLL OFF	0		\$84 NET
	Machine is in mobile condition and all attachments are installed unless specified.			