

CATERPILLAR MACHINE PRICE LIST

986K

986K WHEEL LOADER
 DECATUR, IL, USA

Ship Weight
 lbs

LIST PRICE
 AT DEALER

Standard Equipment:

POWERTRAIN

Brakes, oil-cooled, multi-disc, service/secondary
 Case drain screens
 Crankcase guard
 Electro hydraulic parking brake
 Engine, C15 ACERT MEUI diesel, turbocharged/aftercooled
 Ground level engine shutoff
 Manual switch and automatic fuel priming
 Turbine precleaner, engine air intake
 Starting aid, ether, automatic
 Torque converter, neutralizer
 Transmission, planetary powershift, 4F/4R electronic control

Couplings, Cat O-ring face seals
 Doors, service access (locking)
 Ecology drains for engine, radiator, hydraulic tank
 Fuel tank, 535 L (141 gal)
 Hitch, drawbar with pin
 Hoses, Cat XT(TM)
 Hydraulic, steering and brake filtration/screening system
 Hydraulically driven demand fan
 Oil sampling valves
 Rear access to cab and service platform
 Steering, load sensing
 Vandalism protection caplocks

ELECTRICAL

Alarm, back-up
 Alternator, 145-amp
 Batteries, dry
 Converter, 10/15-amp, 24V to 12V
 Lights (work, access & service platform, directional)
 Starting and charging system, 24V
 Starter emergency start receptacle

OPERATOR ENVIRONMENT

Air conditioner
 Cab, sound suppressed and pressurized, integrated rollover protective structure (ROPS/FOPS), radio ready for entertainment includes antenna, speakers and converter (12-volt 5-amp), and power port
 Controls, lift and tilt function
 Heater, defroster
 Horn, electric
 Instrumentation, gauges:
 -Coolant temperature
 -Fuel level
 -Hydraulic oil temperature
 -Powertrain oil temperature
 Light, dome (cab)
 Lunchbox and beverage holders
 Mirrors, rearview (externally mounted)
 Seat, Cat Comfort (cloth), air suspension, six-way adjustable
 Seat belt, 2-point, 76mm (3"), minder
 STIC control system
 Transmission gear indicator
 Wet-arm wipers/washers (front and rear), intermittent wipers (front and rear)

OTHER STANDARD EQUIPMENT

Automatic bucket lift kickout/positioner

CATERPILLAR MACHINE PRICE LIST

986K

986K WHEEL LOADER DECATUR, IL, USA	Ship Weight lbs	LIST PRICE AT DEALER
---------------------------------------	--------------------	-------------------------

438-4200 986K WHEEL LOADER 0 LANE 2 - AVAILABLE FROM DECATUR FACTORY LANE 3 - AVAILABLE FROM DECATUR FACTORY	0	\$787,130
--	---	-----------

AVAILABLE FOR: AM-N, EU, ISRAEL, JAPAN, & SOUTH KOREA

0P-4275 986K MISCELLANEOUS MATERIAL 0 AVAILABLE FROM DECATUR FACTORY	0	NC
---	---	-----------

Only reference numbers under the Factory Sourced Kits section can be used on a MISC order.

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

LANE SELECTION

	OP-9002	LANE 2 ORDER	0	NC
	OP-9003	LANE 3 ORDER	0	NC

REGIONAL PACKAGES

L	484-0020	REGIONAL PACKAGE, STANDARD AVAILABLE FOR: ALL REGIONS EXCEPT EU	0	NC
L	484-0015	REGIONAL PACKAGE, EU AVAILABLE FOR: ALL REGIONS EXCEPT CANADA	0	NC

BOOMS, STICKS, AND LINKAGES

LIFT ARRANGEMENTS

L	563-4458	LIFT, STANDARD (2V) Provides standard lift with 2-valve function. Recommended for use with Load and Carry applications.	0	NC
L	563-4459	LIFT, STANDARD (3V) FOR USE WITH LANE 3 ONLY Provides standard lift with 3-valve function. Recommended for use with Load and Carry applications.	0	\$7,850
L	563-4460	LIFT, HIGH (2V) Provides high lift with 2-valve function. Recommended for any application where maximum dump clearance is desired.	0	\$6,920
L	563-4461	LIFT, HIGH (3V) FOR USE WITH LANE 3 ONLY Provides high lift with 3-valve function. Recommended for any application where maximum dump clearance is desired.	0	\$14,790
L	536-7957	LIFT, BLOCK HANDLER (2V) FOR USE WITH LANE 3 ONLY Specialized machine for block handling applications. Includes larger lift and tilt cylinders, extra counterweight, lift arm, and links. Other attachments that can complement this offering ride control and axle oil cooler. REQUIRES: 483-9860 LUBRICATION or 483-9875 AUTOLUBE 488-7750 COUNTERWEIGHT, BLOCK HANDLER 488-4620 or 488-4640 ENGINE, BRAKE 489-0183 FUEL TANK, BLOCK HANDLER 42PR or ** Tires with HLA Rims	0	\$6,110
L	536-7958	LIFT, BLOCK HANDLER (3V) FOR USE WITH LANE 3 ONLY Specialized machine for block handling applications. Includes larger lift and tilt cylinders, extra counterweight, lift arm, and links. Other attachments that can complement this offering ride control and axle oil cooler. REQUIRES: 483-9860 LUBRICATION or 483-9875 AUTOLUBE 488-7750 COUNTERWEIGHT, BLOCK HANDLER 488-4620 or 488-4640 ENGINE, BRAKE 489-0183 FUEL TANK, BLOCK HANDLER 42PR or ** Tires with HLA Rims	0	\$10,570

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

BOOMS, STICKS, AND LINKAGES (CONT.)

LUBRICATION ARRANGEMENTS

L	483-9850	LUBRICATION, MANUAL, STD LIFT 0		NC
		ONLY FOR USE WITH: 488-4650 or 488-4660 LIFT, STANDARD		
L	483-9855	LUBRICATION, MANUAL, HIGH LIFT 0		NC
		ONLY FOR USE WITH: 488-4670 or 488-4680 LIFT, HIGH		
L	483-9860	LUBRICATION, MANUAL (BH) 0		NC
		FOR USE WITH LANE 3 ONLY		
		ONLY FOR USE WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		
L	483-9865	AUTOLUBE, STD LIFT 0		\$13,890
		ONLY FOR USE WITH: 488-4650 or 488-4660 LIFT, STANDARD		
L	483-9870	AUTOLUBE, HIGH LIFT 0		\$13,890
		ONLY FOR USE WITH: 488-4670 or 488-4680 LIFT, HIGH		
L	483-9875	AUTOLUBE (BH) 0		\$13,890
		FOR USE WITH LANE 3 ONLY		
		ONLY FOR USE WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		

COUNTERWEIGHTS

L	488-7730	COUNTERWEIGHT, STD LIFT 0		NC
		ONLY FOR USE WITH: 488-4650 or 488-4660 LIFT, STANDARD		
L	488-7760	COUNTERWEIGHT, AGGREGATE 0		\$11,970
		Provides additional counterweight for the Aggregate Handler, which allows customers to maximize machine payload in re-handling applications. Reference salesgram TEK@1233-01.		
		REQUIRES: GENERAL PURPOSE or COAL BUCKET		
		ONLY FOR USE WITH: 488-4650 or 488-4660 LIFT, STANDARD		
L	488-7740	COUNTERWEIGHT, HIGH LIFT 0		NC
		ONLY FOR USE WITH: 488-4670 or 488-4680 LIFT, HIGH		
L	488-7750	COUNTERWEIGHT, BLOCK HANDLER 0		\$31,190
		FOR USE WITH LANE 3 ONLY		
		ONLY FOR USE WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		

POWERTRAIN

ENGINE ARRANGEMENTS

L	488-4610	ENGINE, STANDARD 0		NC
		US EPA T4F/EU Stage V Technology		
		ONLY FOR USE WITH: 438-4200 986K WHEEL LOADER		
		CANNOT BE USED WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		
L	488-4620	ENGINE, BRAKE 0		\$2,745
		US EPA T4F/EU Stage V Technology		
		Provides engine braking for steep grades or speed reduction.		
		ONLY FOR USE WITH: 438-4200 986K WHEEL LOADER		

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

SUSPENSION SYSTEMS

RIDE CONTROL

The ride control option provides a suspension system by placing one accumulator in the lift circuit. Manual off and automatic mode selection. In auto mode the suspension system engages when reaching preset value. It reduces bounce caused by bucket-induced loads when traveling loaded or unloaded. For use in high speed roading, load and carry, and any other application in which load retention, bucket spillage, or operator ride may be a problem. This option is ideal for government bid specifications.

L	483-9840	NO RIDE CONTROL	0	NC
L	496-5275	RIDE CONTROL Axle oil cooler is recommended with ride control attachment and any high braking applications. AVAILABLE FOR: ALL REGIONS EXCEPT EU	0	\$8,690
L	496-5270	RIDE CONTROL (EU) Axle oil cooler is recommended with ride control attachment and any high braking applications. AVAILABLE FOR: ALL REGIONS EXCEPT CANADA	0	\$8,690

LINE GROUPS

STEERING

L	483-9750	STEERING, STANDARD	0	NC
L	483-9755	STEERING, SECONDARY Provides a ground speed driven supplemental steering pump. REQUIRED BY: EU	0	\$7,360

STARTERS, BATTERIES, & ALTERNATORS

STARTING ARRANGEMENTS

L	488-4010	STARTING, STANDARD Provides standard fuel lines.	0	NC
L	488-4020	STARTING, COLD Provides heated fuel lines and 2 additional batteries. REQUIRES: 491-5355 GUARD, BOTTOM	0	\$1,730

ELECTRICAL

LIGHTS

L	434-5124	LIGHTS, HALOGEN	0	NC
L	434-5122	LIGHTS, LED	0	\$1,700

Supersedes 02JAN2018
 Caterpillar: Confidential Green
 US-A-19-01 A

Subject to change without notice
 Printed in USA
 U. S. DOLLAR CURRENCY

Effective 02JAN2019
 986K-005

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

OPERATOR ENVIRONMENT

CAB PACKAGES

NOTE: 2-point seat belts are standard. 4-point seat belts are available through parts distribution if needed.

L	558-2533	CAB, BASIC PLUS 0		\$3,380
		INCLUDES:		
		-Seat, heated & ventilated		
		-Cab door, sliding window (LH)		
		-Cab precleaner, non-powered		
		-CB radio, ready		

INTEGRATED OBJECT DETECTION SYSTEM

L	488-7602	CAMERA, REAR VISION 0		NC
		Provides an object detection system (camera only) to enhance operator awareness of surroundings. This system uses visual information only in order to provide the operator with additional information about the work area to the rear of the wheel loader.		
		REQUIRES: 495-4471 DISPLAY, PRIMARY		
L	488-7601	DETECTION, OBJECT (RADAR) 0		\$2,800
		Provides an object detection system (camera & radar) to enhance operator awareness of surroundings. This system uses visual and radar information in order to provide the operator with additional information about the work area to the rear of the wheel loader. For a list of countries that RF radar is approved for use in, visit https://dealer.cat.com/detect		
		REQUIRES: 495-4471 DISPLAY, PRIMARY		

DISPLAY

L	495-4471	DISPLAY, PRIMARY 0		NC
		REQUIRES: 492-2211 or 490-2480 CPM PAYLOAD WEIGHING		

TECHNOLOGY PRODUCTS

PRODUCT LINK

Product Link enables the remote transmission of information about the location, operation, and condition of your equipment. Efficiently and effectively monitor performance of your assets to help keep your jobs on schedule, maintain equipment condition, and reduce the costs of owning and operating your fleet.

Authorization varies by country, please reference <https://Dealer.cat.com/PL/Certification> for certified countries. Please contact your Caterpillar marketing representative with questions.

L	490-6103	PRODUCT LINK, CELLULAR PLE641 0		NC
		Product Link Elite series PLE641 offers expanded coverage including 3G UMTS and CDMA2000 as well as 2G GSM and CDMA cellular networks to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. Cellular technology provides capabilities for frequent transmission and larger volumes of data.		

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

PRODUCT LINK (Cont.)

L	490-6105	PRODUCT LINK, SATELLITE PLE631 0 Product Link Elite series PLE631 uses a satellite network to transmit location, utilization and condition information for viewing in Product Link's remote monitoring web interface. For use in areas with poor or no cellular coverage.		\$432
---	----------	--	--	-------

FUEL SYSTEMS

FUEL TANK

L	489-0198	FUEL TANK, NON-FAST FILL 0 CANNOT BE USED WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		NC
L	489-0181	FUEL TANK, FAST FILL 0 CANNOT BE USED WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		\$1,680
L	489-0183	FUEL TANK, BLOCK HANDLER 0 ONLY FOR USE WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		NC

COOLING

L	483-9920	COOLING, NON-AOC 0		NC
L	483-9925	COOLING, AOC 0 Axle oil cooler attachment is recommended with ride control for long downhill grades or any high braking applications. REQUIRES: 491-5355 GUARD, BOTTOM		\$9,740

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS

Due to industry-wide tire availability limitations, tire brand and type cannot be guaranteed. Every effort will be made to satisfy your tire choice. However, if the tire type cannot be supplied we will contact the dealer to propose alternatives. The dealer needs to choose between an alternative tire or a "rims only" option (where available) within 72 hours. If no response is provided by the deadline, the order will default to the alternative tire and will be changed at that point. As a consequence of a possible tire change, the total machine price will be decreased or increased depending on the price of the new tire.

NOTE: All tires are tubeless, include heavy duty rims and come in a set of 4.

NOTE: 42PR tires may be used to improve lateral stability. Recommended for use with uneven floors and/or high truck loading heights with dense materials.

NOTE: Tires with HLA rims have tires mounted on rims for Heavy Load Applications. These are required for machines in block handler applications and any other application where higher loads may be encountered.

NOTE: Block Handler orders require 42PR or ** tires with HLA rims.

TIRES AVAILABLE FROM BRIDGESTONE

P	491-7383	TIRES, 35/65-33 BS DL 42PR L5 0 Bridgestone Bias; Tread Depth=97mm (122/32"); Rim=28"x33" Suitable for severe rock environments where maximum damage protection is needed. CANNOT BE USED WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		\$8,180
P	452-4111	TIRES, 35/65-33 BS 42PR L5 HLA 6,210 Same tire as above, but with Heavy Load Application rims. HLA rims are required for block handler applications and any other application where higher loads may be encountered.		\$13,980
P	528-6454	TIRES, 35/65R33 BS VSNT ** L4 0 Bridgestone Radial; Tread Depth=62.5mm (79/32"); Rim=28"x33" Provides damage resistance, mobility, and traction in moderate rock environments. CANNOT BE USED WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		\$-1,240
P	493-6840	TIRES, 35/65R33 BS ** L4 HLA 0 Same tire as above, but with Heavy Load Application rims. HLA rims are required for block handler applications and any other application where higher loads may be encountered.		\$4,560
P	491-7382	TIRES, 35/65R33 BS VSDL ** L5 0 Bridgestone Radial; Tread Depth=95mm (120/32"); Rim=28"x33" Suitable for severe rock environments where maximum damage protection is needed. CANNOT BE USED WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		\$13,320

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

TIRES, RIMS, AND WHEELS (CONT.)

TIRES AVAILABLE FROM BRIDGESTONE (Cont.)

P	452-4118	TIRES, 35/65R33 BS ** L5 HLA 1,610 Bridgestone Radial VSDL IDU with Heavy Load Application rims. HLA rims are required for block handler applications and any other application where higher loads may be encountered.		\$25,240
---	----------	--	--	----------

TIRES AVAILABLE FROM MICHELIN

P	499-3063	TIRES, 35/65R33 MX ** L5 0 Michelin Radial XMINED2; Tread Depth=97mm (122/32"); Rim=28"x33" Directional tire suitable for severe rock environments where maximum damage protection is needed. CANNOT BE USED WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		\$32,380
P	499-3064	TIRES, 35/65R33 MX *** L4 0 Michelin Radial XTXL; Tread Depth=60mm (76/32"); Rim=28"x33" Directional tire that provides damage resistance, mobility, and traction in moderate rock environments. CANNOT BE USED WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		\$10,080

TIRES, ALLOWANCE FOR OMISSION

P	490-7502	RIMS ONLY, TIRES OMITTED 0 CANNOT BE USED WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		\$-38,340
P	442-6345	RIMS ONLY (HLA), TIRES OMITTED -9,152 Provides Heavy Load Application rims. HLA rims are required for machines in block handler applications and any other application where higher loads may be encountered.		\$-32,540

OTHER ATTACHMENTS

FENDERS

L	527-6980	FENDERS, STANDARD 0 Provides standard front fenders.		NC
L	527-6990	FENDERS, ROADING 0 Provides full coverage front and rear fenders.		\$1,860
L	527-7000	FENDERS, ROADING (STEEL) 0 Provides full coverage steel front and rear fenders.		\$3,055

ACCESS ARRANGEMENTS

L	490-0620	STAIRWAYS W/TOE KICKS, LH & RH 0 ONLY FOR USE WITH: 438-4200 986K WHEEL LOADER		NC
---	----------	---	--	----

SOUND SUPPRESSION

L	488-5520	NO SOUND SUPPRESSION 0 Operator sound pressure level: 72 dB(A) per ISO 6396 Machine sound power level: 112 dB(A) per ISO 6395 ONLY FOR USE WITH: 438-4200 986K WHEEL LOADER		NC
---	----------	--	--	----

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 MANDATORY	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	------------------	-----------------	----------------------

OTHER ATTACHMENTS (CONT.)

SOUND SUPPRESSION (Cont.)

L	488-5510	SOUND SUPPRESSION 0		\$4,250
		Operator sound pressure level: 72 dB(A) per ISO 6396		
		Machine sound power level: 110 dB(A) per ISO 6395		
		REQUIRES: 499-1976 GUARD, TRANSMISSION		
		491-5355 GUARD, BOTTOM		
		ONLY FOR USE WITH: 438-4200 986K WHEEL LOADER		
		REQUIRED BY: EU & SOUTH KOREA		

FLUIDS

HYDRAULIC OIL

L	530-3056	HYDRAULIC OIL, STANDARD 0		NC
L	530-3057	HYDRAULIC OIL, ARCTIC 0		\$4,367
		Installs 0W-20 CAT TDTO Cold Weather Oil in place of standard		
		10W HYDO-10 hydraulic oil. For use in cold climates for ambient		
		temperature down to -40C (-40F).		

INSTRUCTIONS

ROPS/FOPS FILMS

L	540-6894	FILMS, ROPS/FOPS 0		NC
		Provides ROPS/FOPS films required for countries outside of China.		

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

STARTERS, BATTERIES, & ALTERNATORS

STARTING AIDS

MAY SELECT ONE ONLY

L	295-1039	HEATER, ENGINE COOLANT 120V 3 Engine coolant heater for 120 volt external power source.		\$256
---	----------	--	--	-------

ELECTRICAL

L	490-6091	LIGHT, WARNING BEACON 0		\$520
---	----------	-----------------------------------	--	-------

OPERATOR ENVIRONMENT

L	495-4472	DISPLAY, SECONDARY 0 REQUIRED BY: UK		\$2,395
---	----------	---	--	---------

L	143-3604	MIRRORS, HANDRAIL MOUNTED 26 Provides rear view outboard handrail mounted mirrors. REQUIRED BY: 521-6265 WHEEL CHOCKS		\$595
---	----------	---	--	-------

RADIOS

MAY SELECT ONE ONLY

L	486-8075	RADIO, AM/FM 0		\$282
---	----------	--------------------------	--	-------

L	486-8073	RADIO, AM/FM/CD/BT/SAT 0 BlueTooth radio technology enables the use of a hands free function such as listening to music and making phone calls. Authorization varies by country, please contact your Cat marketing representative with questions or click on the link below: https://dealer.cat.com/en/products/technology.html Requires service contract with satellite radio provider.		\$780
---	----------	---	--	-------

TECHNOLOGY PRODUCTS

SOFTWARE ENABLED ATTACHMENTS (SEA) INSTRUCTIONS

Technology apps are activated by Software Enabled Attachments (SEA). SEAs are available factory installed or can be purchased for dealer installation.

Refer to Information Release Memo (IRM) EES03 -01 (media number PELJ0138) in the Caterpillar Media Information Center for further explanation of SEAs. Select the Product Support tab and search for number PELJ0138. Refer to REHS1238 & REHS8401 for how to obtain a Factory Level Password. Contact FPS: Internet with Corporate Web Security (CWS) ([https:// fps.cat.com/](https://fps.cat.com/)).

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

TECHNOLOGY PRODUCTS (CONT.)

CAT PRODUCTION MEASUREMENT (CPM) PAYLOAD WEIGHING SYSTEM

CPM includes an integrated onboard payload weighing scale with material management, cycle count & time recording and wireless production detail reporting capability.

- Payload & cycle totals are sent wirelessly to VisionLink. (Cat Essentials subscription required.)
- Detailed payload reports and KPI metrics can be visualized on-line and downloaded for further analysis, with a subscription to Cat Advanced Productivity. (First 6 months included with purchase of CPM; subscription fee applies thereafter. Requires PLE641 cellular Product Link.)

Refer to <https://dealer.cat.com> for complete technical specifications; operation, sales, marketing and technical support publications.

NOTES:

- 1) Demo and permanent software are available from the factory.
- 2) For field installation, permanent software can be purchased through the Caterpillar Feature Protection System and enabled by a dealer technician with Cat ET and an SEA password. SEA p/n 433-2014. Consult ANTARES parts distribution system for latest SEA price.
- 3) Both demo and permanent software require calibration prior to customer use.

CALIBRATION INSTRUCTIONS

This app requires calibration and set-up by either the dealer or customer. Refer to the Systems Operation Test & Adjust manual UENR7119 for system calibration, material and truck ID lists set-up and operation instructions.

L	492-2211	CPM PAYLOAD WEIGHING READY 0 Includes demo software for CPM, dealer enabled for up to 250 hours. To activate demo software, it must be enabled by a dealer technician with Cat ET. No password is required. For permanent software activation in the field, purchase of software is required. See note 2 above for details. ONLY FOR USE WITH: 495-4471 DISPLAY, PRIMARY REQUIRED BY: 495-4471 DISPLAY, PRIMARY		NC
L	490-2480	CPM PAYLOAD WEIGHING 0 Includes permanent software for CPM. Software is factory enabled, but the system must be calibrated prior to customer use. See note above for calibration instructions. ONLY FOR USE WITH: 495-4471 DISPLAY, PRIMARY REQUIRED BY: 495-4471 DISPLAY, PRIMARY		\$5,380
L	495-3127	PRINTER, PAYLOAD 0 ONLY FOR USE WITH: 492-2211 CPM PAYLOAD WEIGHING READY or 490-2480 CPM PAYLOAD WEIGHING		\$2,135

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

COOLING

L	527-7343	COOLING, HIGH AMBIENT 0 Provides increased air flow through software. Recommended for ambient temperatures up to 50C (122F).		NC
---	----------	---	--	-----------

TIRES, RIMS, AND WHEELS

L	542-6577	MONITORING, TIRE PRESSURE 0 Provides four sensors that mount to the valve stem of each tire along with a receiver module that monitors both pressure and temperature in each tire. Tire pressure and temperature information is shared with the operator via the info display. Warnings are provided through Unified Fleet if pressure is outside of a configurable target range. The system is not recommended for use on tires with liquid additives or sealants.		\$3,000
---	----------	---	--	----------------

GUARDS

L	499-1976	GUARD, TRANSMISSION 0 REQUIRED BY: 488-5510 SOUND SUPPRESSION 488-5530 SOUND SUPPRESSION		\$2,625
L	491-5355	GUARD, BOTTOM 0 REQUIRED BY: 488-5510 SOUND SUPPRESSION 488-5530 SOUND SUPPRESSION 483-9925 COOLING, AOC 488-4020 STARTING, COLD		\$740

OTHER ATTACHMENTS

L	490-2495	OIL CHANGE SYSTEM, HIGH SPEED 0 Provides remote port and components for high speed oil change.		\$510
L	521-6265	WHEEL CHOCKS 0 Includes wheel chocks and an integrated storage system. REQUIRES: 143-3604 MIRRORS, HANDRAIL MOUNTED CANNOT BE USED WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		\$1,505

QUICK COUPLERS

L	418-0100	QUICK COUPLER, BLOCK HANDLING 2,760 ONLY FOR USE WITH: 536-7957 or 536-7958 LIFT, BLOCK HANDLER		\$26,042
---	----------	---	--	-----------------

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

WORK TOOLS

BLOCK HANDLING FORKS

L	453-9880	FORK, BLOCK HANDLING (QC)	5,796	\$38,321 NI
		69" (1745mm) non-swinging tines Maximum width over tines: 55" (1400mm) TINE WIDTH: 11.8" (300mm) TINE THICKNESS: 5.7" (145mm) ONLY FOR USE WITH: 418-0100 QUICK COUPLER, BLOCK HANDLING		

BUCKETS

For questions on buckets intended for Machine Orders please contact your Marketing Subsidiary Machine Coordinator.

Loose buckets should be ordered on a MISC Order through Caterpillar Work Tools - Wamego using source code OP-0672. For availability of loose buckets please email worktools@cat.com.

If you are going to order a loose bucket from CWTS and a machine from Aurora and if you need them shipped at the same time then you need to cross-reference the MSO's with each other.

"GET" is NOT automatically included on bucket orders. "GET" must be entered on the order with your bucket selection, unless text for bucket states otherwise. Please make the "GET" selection from the "GET" listed immediately following the bucket listing. Rock bucket selections list "GET" for spade or straight edge.

Material density will determine the appropriate capacity bucket. Refer to the Specalog. Exceeding maximum payload may cause loader instability.

All listed Maximum Recommended Material Densities are based on the maximum gross weight that the 988K is rated for minus the weight of the bucket and all required G.E.T. at 100% fill factor.

GENERAL PURPOSE BUCKETS

P	512-1180	BUCKET-GP, 146" 8.00YD3	8,177 8,177	\$40,506 \$40,506 NI
		PERFORMANCE SERIES BUCKET Maximum Recommended Material Density: 1632 kg/m3 (2750 lb/yd3) STRAIGHT EDGE 5.9M3(7.7YD3) w/bolt-on adapters, K110, 3820mm (150") wide 6.1M3(8.0YD3) w/bolt-on adapters & segments, K110, 3820mm (150") wide 6.1M3(8.0YD3) w/bolt-on cutting edge system, 3735mm (147") wide		

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

BUCKETS (CONT.)

GENERAL PURPOSE BUCKETS (Cont.)

P	513-7400	BUCKET-GP, 145" 9.00YD3	8,666 8,666	\$40,506 \$40,506 NI
		PERFORMANCE SERIES BUCKET Maximum Recommended Material Density: 1451 kg/m3 (2444 lb/yd3) STRAIGHT EDGE 6.7M3(8.7YD3) w/bolt-on adapters, K110, 3820mm (150") wide 6.9M3(9.0YD3) w/bolt-on adapters & segments, K110, 3820mm (150") wide 6.9M3(9.0YD3) w/bolt-on cutting edge system, 3735mm (147") wide		
P	513-7420	BUCKET-GP, 145" 10.00YD3	9,057 9,057	\$42,669 \$42,669 NI
		PERFORMANCE SERIES BUCKET Maximum Recommended Material Density: 1306 kg/m3 (2200 lb/yd3) STRAIGHT EDGE 7.4M3(9.7YD3) w/bolt-on adapters, K110, 3820mm (150") wide 7.6M3(10.0YD3) w/bolt-on adapters & segments, K110, 3820mm (150") wide 7.6M3(10.0YD3) w/bolt-on cutting edge system, 3735mm (147") wide		

AGGREGATE GENERAL PURPOSE BUCKET

P	477-1900	BUCKET-GP, 145" 11.0 YD3	9,590 9,590	\$45,086 \$45,086 NI
		Maximum Recommended Material Density: 1580 kg/m3 (2670 lb/yd3) STRAIGHT EDGE 8.2M3(10.7YD3) w/bolt-on adapters, K110, 3820mm (150") wide 8.4M3(11.0YD3) w/bolt-on adapters & segments, K110, 3820mm (150") wide 8.4M3(11.0YD3) w/bolt-on cutting edge system, 3735mm (147") wide ONLY FOR USE WITH: 488-7760 COUNTERWEIGHT, AGGREGATE		

GET (K110) for GENERAL PURPOSE BUCKETS

P	104-4369	CUTTING EDGE, BOLT-ON	956	\$2,513
		35mm thick w/ 40mm end bits		
P	174-7950	GUARD, CORNER	304	\$1,057
		ONLY FOR USE WITH: 104-4369 CUTTING EDGE, BOLT-ON		
P	232-0167	ADAPTERS, BOLT ON, SET OF 8	555	\$3,968
		45mm thick ONLY FOR USE WITH: K110 tips		
P	183-5321	SEGMENTS, BOLT-ON, SET OF 7	648	\$1,792
		45mm thick. Use with STRAIGHT Buckets. ONLY FOR USE WITH: K110 Adapters and tips		
P	309-1127	TIP, GENERAL DUTY	26	\$129
		Recommended for general application in moderate impact and abrasive conditions. Good penetration, (2) self-sharpening cavities. ONLY FOR USE WITH: K110 Adapters		
P	309-1122	TIP, EXTRA DUTY	36	\$163
		Recommended for general applications requiring more wear material in moderate-to-high impact conditions. Good wear material, good penetration. ONLY FOR USE WITH: K110 Adapters		

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

BUCKETS (CONT.)

ROCK PERFORMANCE SERIES BUCKETS

Rock Buckets are designed for bank or face loading and bucket base edges are drilled to accept bolt-on segments unless indicated in bucket description. Sidebars are drilled to accept two sets of sidebar protectors unless otherwise indicated. Additional wear protection is available as an option.

P	527-4050	BKT RSP 150" 7.00YD3 PO	8,393 8,393	\$46,783 \$46,783 NI
		PERFORMANCE SERIES BUCKET Maximum Recommended Material Density: 1865 kg/m3 (3143 lb/yd3) SPADE EDGE INCLUDES: (8) weld-on Advansys 110 double strap adapters REQUIRES: (8) Advansys 110 tips and (1) segment group		
P	527-4060	BKT RSP 150" 7.50YD3 PO	8,666 8,666	\$48,124 \$48,124 NI
		PERFORMANCE SERIES BUCKET Maximum Recommended Material Density: 1741 kg/m3 (2933 lb/yd3) SPADE EDGE INCLUDES: (8) weld-on Advansys 110 double strap adapters REQUIRES: (8) Advansys 110 tips and (1) segment group		
P	525-6140	BKT RSP 150" 8.00YD3 PO	8,845 8,845	\$49,838 \$49,838 NI
		PERFORMANCE SERIES BUCKET Maximum Recommended Material Density: 1632 kg/m3 (2750 lb/yd3) SPADE EDGE INCLUDES: (8) weld-on Advansys 110 double strap adapters REQUIRES: (8) Advansys 110 tips and (1) segment group		
P	476-2127	BUCKET-ROCK, 150" 7.00YD3	9,692 9,692	\$53,115 \$53,115 NI
		SPADE EDGE Will accept 2 sets of sidebar protectors. INCLUDES: (8) weld-on K110 double strap adapters REQUIRES: (8) K110 tips and (1) segment group ONLY FOR USE WITH: 418-0100 QUICK COUPLER, BLOCK HANDLING		

GET (Advansys 110 / K110) for ROCK BUCKETS
 (includes mounting hardware)

P	109-9051	SEGMENT, BOLT-ON, SET OF 7	807	\$2,232
		40mm thick. Use with SPADE buckets.		
P	124-6346	SEGMENTS, H.A., BOLT-ON, SET OF 7	805	\$2,679
		45mm thick, Half Arrow. Use with SPADE buckets.		
P	505-4014	TIP, GENERAL DUTY	31	\$156
		Recommended for general application in moderate impact and abrasive conditions. Good penetration, (2) self-sharpening cavities. ONLY FOR USE WITH: Advansys 110 adapters		
P	505-4012	TIP, HEAVY DUTY ADVANSYS	39	\$190
		Recommended for general applications requiring more wear material in moderate-to-high impact conditions. Good wear material, good penetration. ONLY FOR USE WITH: Advansys 110 adapters		

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

BUCKETS (CONT.)

GET (Advansys 110 / K110) for ROCK BUCKETS (Cont.)

P	505-4010	TIP, HEAVY PENETRATION 47 Recommended for high abrasive and impact conditions, especially shot rock. Excellent penetration and wear material. ONLY FOR USE WITH: Advansys 110 adapters		\$250
P	505-4011	TIP, HEAVY ABRASION 51 Recommended for high abrasive, moderate impact, easier-to-penetrate materials. Excellent wear material, less penetration. ONLY FOR USE WITH: Advansys 110 adapters		\$263
P	505-4013	TIP, HEAVY DUTY LONG LIFE (ARM 40 Recommended for general applications requiring more wear material in low-to-moderate impact conditions. Good wear material, extended wear l Good penetration. ONLY FOR USE WITH: Advansys 110 adapters		\$344
P	309-1123	TIP, PENETRATION 23 Recommended for harder-to-penetrate, moderate impact, low-to-moderate abrasive materials. Very good penetration less wear material. ONLY FOR USE WITH: K110 adapters		\$128
P	208-8827	PLATE GP-WEAR 232 Bolt-on bottom, rear base edge wear plates 35mm thick wear plate		\$593
P	356-6437	PROTECTORS, SIDEBAR, SET OF 2 106 Set of two, one for RH and one for LH side of the bucket.		\$1,118
P	494-8224	PROTECTORS, SIDEBAR, SET OF 4 212 Set of four, two for RH and two for LH side of the bucket.		\$2,265

HEAVY DUTY ROCK PERFORMANCE SERIES BUCKETS

The Heavy Rock Bucket is designed for bank or face loading and include all the features of the Rock Bucket with upsized Advansys 130 Double Strap Adapters, three-piece shell liner package, inner and outer side wear plates, bolt-on rear base edge wear protection, bottom outer ski plates bolt-on Half Arrow Segments, wings (rock deflectors) and two sets of Sidebar Protectors.

P	527-4070	BKT RSP HD 158" 7.00YD3 PO 11,307 PERFORMANCE SERIES BUCKET Maximum Recommended Material Density: 1865 kg/m3 (3143 lb/yd3) SPADE EDGE INCLUDES: (8) weld-on Advansys 130 double strap adapters, (6) 20-series MAWPs for bottom, rear wear protection REQUIRES: (8) Advansys 130 tips	11,307 11,307	\$63,150 \$63,150 NI
---	----------	---	------------------	---------------------------------------

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

BUCKETS (CONT.)

EXTREME DUTY ROCK BUCKET

The Extreme Duty Rock Bucket is designed for bank or face loading granite or similar materials and include all of the features of the Heavy Duty Rock Bucket. In addition, the bucket features thicker sideplates, high impact rock guard design, wings (rock deflectors) with wear protection, BEEPS (Base Edge End Protection) and two sets of upsized Sidebar Protectors.

P	527-4080	BKT RSP HD 163" 6.50YD3 PO	12,377 12,377	\$66,282 \$66,282 NI
		Maximum Recommended Material Density: 1540 kg/m3 (2600 lb/yd3) SPADE EDGE INCLUDES: (8) weld-on Advansys 130 double strap adapters, (6) 20-series MAWPs for bottom, rear wear protection REQUIRES: (8) Advansys 130 tips		

GET (Advansys 130) for HEAVY DUTY and EXTREME DUTY BUCKETS

P	381-4095	TIP, HEAVY PENETRATION	65	\$350
		Recommended for high abrasive and impact conditions, especially shot rock. Excellent penetration and wear material. ONLY FOR USE WITH: Advansys 130 adapters		
P	381-4096	TIP, HEAVY ABRASION	68	\$379
		Recommended for high abrasive, moderate impact, easier-to-penetrate materials. Excellent wear material, less penetration. ONLY FOR USE WITH: Advansys 130 adapters		

COAL PERFORMANCE SERIES BUCKET

P	513-7450	BUCKET-COAL, 145" 13.50YD3	11,464 11,464	\$44,286 \$44,286 NI
		PERFORMANCE SERIES BUCKET Maximum Recommended Material Density: 967 kg/m3 (1630 lb/yd3) STRAIGHT EDGE INCLUDES: BOLT-ON CUTTING EDGE (BOCE)		

SERRATED EDGE PERFORMANCE SERIES BUCKET

P	519-1465	BUCKET-ROCK, 150" 8.00YD3	9,389 9,389	\$48,840 \$48,840 NI
		PERFORMANCE SERIES BUCKET Maximum Recommended Material Density: 1632 kg/m3 (2750 lb/yd3) SERRATED V-SPADE EDGE		

FLUIDS

ANTIFREEZE

Standard machine includes antifreeze protection to -34C (-29F). Different lubricants are also required for extreme temperatures. Please refer to operation and maintenance manual.

P	0P-2411	COOLANT, -50C (-58F)	0	\$520 NET
---	---------	----------------------	---	-----------

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

FACTORY SOURCED KITS

RETRO-FIT KITS for CURRENT 986K

If ordering on a MISC MSO, you need to use OP-4275 for TOP LEVEL and OP-0812 for PACKING.

Kits must be ordered as NOT-INSTALLED.

No returns on Kit components or for parts removed.

C	458-3103	KIT, CAB PRECLEANER (POWERED) 0 986K Ser# SWH00001 & up 986K Ser# NL800001 & up Provides all parts for field installation of powered cab precleaner.		\$7,120 NI
C	560-2917	KIT, TIRE PRESSURE MONITORING 0 986K Ser# MH800001 & up, SWH00001 & up, NL800001 & up Provides four sensors that mount to the valve stem of each tire along with a receiver module that monitors both pressure and temperature in each tire. Tire pressure and temperature information is shared with the operator via the primary display. Warnings are provided through Unified Fleet if pressure is outside of a configurable target range. Software license for Cat Tire Pressure Monitoring (TPM) will be a separate charge. Requires SEA for permanent activation.		\$3,400 NI
C	563-3195	KIT, WHEEL CHOCKS 0 986K Ser# MH800001 & up, SWH00001 & up, NL800001 & up Provides all parts for field installation of wheel chocks and an integrated storage system.		\$1,330 NI

INSTRUCTIONS

FILMS

P	504-1365	FILM, AM-NORTH 0 REQUIRED BY: AM-NORTH		NC
P	500-8750	FILMS, ANSI 0 REQUIRED BY: AM-NORTH EXCEPT QUEBEC (N050)		NC

PACKING

MUST SELECT ONE

	OP-0294	PACK, DOMESTIC TRUCK 0 Complete machine loaded on truck. CANNOT BE USED WITH: TIRE OMISSION		NC
	OP-0201	DOMESTIC TRUCK, TIRE REMOVAL 0 Removes tires/rims. CANNOT BE USED WITH: TIRE OMISSION		\$610 NET
	OP-2829	PACK, DOMESTIC TRUCK 0 Complete machine loaded on truck. ONLY FOR USE WITH: TIRE OMISSION		\$262 NET
	OP-0812	PACK, MISC SHIPMENTS 0 Use this as the packing reference number on a MISC MSO.		NC

CATERPILLAR MACHINE PRICE LIST

986K

USE	REF NO.	LANE 2 OPTIONAL	Ship Weight lbs	LIST PRICE AT DEALER
-----	---------	-----------------	-----------------	----------------------

PACKING (CONT.)

COVER GROUP

L	531-3147	COVER GROUP..... 0		NC
Required when ordering dual stairs without fast fuel. CANNOT BE USED WITH: 489-0181 FUEL TANK, FAST FILL REQUIRED BY: 490-0620 or 551-4400 STAIRWAYS W/TOE KICKS, LH & RH				

TRANSPORT GROUP

P	530-2863	TRANSPORT, BUCKET (NI) / OMIT 0		NC
Required when ordering a Not Installed (NI) Bucket on your machine order or when omitting a Bucket from your machine order.				